



***Test Report No. 8812328348***

**Applicant: Wavion Ltd.**

**Equipment Under Test:**

***2.4 GHz Band Outdoor WiFi  
(802.11b/g) Wireless Base Station***

**Model: WBS-2400**

**FCC ID: UGM-WBS2400-1**

***From The Standards Institution  
Of Israel  
Industry Division  
Electronics & Telematics Laboratory  
EMC Section***



***Certificate No. 1487-01***



Test Report No.: 8812328348

Page 1 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

<b>Applicant:</b>	Wavion Ltd.
<b>Address:</b>	6 Ha'yetsira Street, Yoqne'am-Ilit, 20692, Israel
<b>Sample for test selected by:</b>	The customer
<b>The date of test:</b>	April 2008

**Description of Equipment**

<b>Under Test (EUT):</b>	2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station
<b>Model:</b>	WBS-2400
<b>Manufactured by:</b>	Wavion Ltd.

**Reference Documents:**

- ❖ **CFR 47 FCC:** Rules and Regulations; Part 15. "Radio frequency devices"; Subpart C: "Intentional radiators" (2006).
- ❖ **Test Results:** The EUT was found meeting with the relevant requirements of CFR 47 FCC Part 15 Sections: 15.205, 15.207, 15.209, 15.247.

This Test Report contains 105 Pages and may be used only in full.	This Test Report applies only to the specimen tested and may not be applied to other specimens of the same product.
--	--



Test Report No.: 8812328348

Page 2 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
Model: WBS-2400 FCC ID: UGM-WBS2400-1

## Table of Contents

<b>1. Applicant information</b>	<b>3</b>
<b>2. Test performance</b>	<b>3</b>
<b>3. Scope</b>	<b>4</b>
<b>4. EUT (equipment under test) description.</b>	<b>4</b>
4.1. <i>General Description</i>	4
4.2. <i>EUT's sub-assemblies list.</i>	5
4.3. <i>EUT ports and lines.</i>	5
4.4. <i>Potential emission source:</i>	5
4.5. <i>EUT technical characteristic</i>	6
<b>5. Test configuration:</b>	<b>7</b>
5.1. <i>Environmental evaluation and exposure limit according to FCC CFR 47 part 1, §1.1307, §1.1310</i>	9
<b>6. Test specification, Methods and Procedures</b>	<b>10</b>
<b>7. Measurements, examinations and derived results</b>	<b>10</b>
7.1. <i>Location of the Test Site:</i>	10
7.2. <i>Normal test condition:</i>	10
7.3. <i>Conducted emission test (per Section 15.207):</i>	11
7.4. <i>Radiated emission test, general requirements (per section 15.209):</i>	13
7.5. <i>Conducted spurious emission</i>	15
7.6. <i>Radiated emission test on Radio Unit – spurious (per Section 15.209):</i>	48
7.7. <i>Radiated emission test on Radio Unit - restricted bands (per Section 15.205):</i>	50
7.8. <i>Minimum bandwidth</i>	56
7.9. <i>Maximum peak output power</i>	66
7.10. <i>Peak power spectral density of digital modulated systems according to § 15.247(d)</i>	77
<b>8. Appendix 1: Test equipment used</b>	<b>98</b>
<b>9. Appendix 2 Antenna Factor and Cable Loss</b>	<b>99</b>
<b>10. Appendix 3: Test configuration illustration</b>	<b>103</b>



Test Report No.: 8812328348

Page 3 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

## 1. Applicant information

Company: Wavion Ltd.

Address : 6 Ha'yetsira Street

City: Yoqne'am-Ilit

Country : Israel

## 2. Test performance

Location: SII EMC Section  
Wavion Ltd.

Purpose of test: Apparatus compliance verification in according with CFR 47 FCC Requirement  
Test specification: CFR 47 FCC Part 15 Sections: 15.205, 15.207, 15.209, 15.247

Test	FCC Part 15	Test result
Radiated emissions in restricted bands	Sec.15.205	Complies
Radiated Emission on Radio Unit: spurious	Sec.15.209	Complies
Conducted emission	Sec.15.207	Complies
Radiated emission – general requirements	Sec.15.209	Complies
Minimum bandwidth	Sec. 15.247 (a) (2)	Complies
Maximum peak output power	Sec.15.247 (b)	Complies
Peak power spectral density	Sec.15.247 (d)	Complies
Conducted spurious emissions	Sec.15.247 (c)	Complies

Electronics &  
Telematics Laboratory  
30 April 2008

Approved by: Eng. Yuri Rozenberg  
Position: Head of EMC Branch

Tested by: Albert Herzenshtein  
Position: Test Engineer

Test Report No.: 8812328348

Page 4 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

### 3. Scope

This test report contains results measured on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station (FCC ID: UGM-WBS2400-1) according to the relevant requirements of CFR 47 FCC Part 15 Subpart C.

### 4. EUT (equipment under test) description.

#### 4.1. General Description

The WBS-2400 is a new category of Wi-Fi Wireless Base Station designed from the ground up for metro-Wi-Fi deployments. It is based on six antennas and radios and custom-built ASICs, utilizes Wavion's powerful multi-antenna signal processing technologies, and provides significant performance gains to off-the-shelf 802.11 standards-based Wi-Fi clients.

The WBS-2400 Wi-Fi Wireless Base Station uses six omni-directional antennas and beam-forming technology in order to provide significant performance gains to off-the-shelf 802.11 standards-based Wi-Fi clients.

The EUT's block diagram is shown in Figure 1.




Figure 1. EUT's block diagram



Test Report No.: 8812328348

Page 5 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

#### 4.2. EUT's sub-assemblies list.

The EUT ports and lines are detailed in Table 1.

No.	Description	P/N; Model	Manufacturer
1	Digital Board	PC00018	Wavion
2	RF Board	PC00041	Wavion
3	RF Board	PC00040	Wavion
4	Interface card	PC00023	Wavion
5	AC/DC PS	LS75-48	Nemic Lambda
6	DC/DC PS	PKB4711PINB	Ericsson
7	AC Connector	50909	Remke
8	Antenna	MT-341017/N/A	MTI
9	Power Unit	PC00019	Wavion
10	RF filter	DFCH52G43HFHAA-TM1	Murata
11	RF filter	SRP2437K8N50SB	Bitel
12	RF filter	6BCR4B-2437/C67-L	Comnav
13	RF filter	SKY33100	Skyworks

Table 1. Sub-assemblies list

#### 4.3. EUT ports and lines.

The EUT ports and lines are detailed in Table 2.

Port Type	Port Description	Connected from / to	Connector type	Qty.	Cable Type	Cable Length
AC Power	AC inlet	Wall outlet/Power TAP-inlet	Standard	1	Unshielded	6m
Data	Data/PoE	PD-Client	RJ-45 shielded	4	CAT-5e	Up to 100m

Table 2. The EUT ports and lines

#### 4.4. Potential emission source:

The potential emission sources are detailed in Table 3.

Frequency	Location	Remarks
40 MHz	On board	Crystal Oscillator with PLL

Table 3. Potential emission sources



Test Report No.: 8812328348

Page 6 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
Model: WBS-2400 FCC ID: UGM-WBS2400-1

#### 4.5. EUT technical characteristic

Type of equipment									
Stand-alone (Equipment with or without its own control provisions)									
Intended use	Condition of use								
Fixed	Always at a distance more than 2 m from all people								
Assigned frequency range	2400MHz to 2483.5MHz								
Operating frequency range	2412MHz to 2462MHz (WLAN channels 1 to 11)								
RF channel spacing	5MHz								
Maximum rated output power	At transmitter 50 Ω RF output connector								
	19dBm@2412MHz								
	19dBm@2437MHz								
	19dBm@2462MHz								
Is transmitter output power variable?	Yes								
	minimum RF power								
	4dBm								
	maximum RF power								
	19dBm								
Antenna connection									
unique coupling	V (N-Type)								
standard connector	integral								
	V								
	with temporary RF connector								
	without temporary RF connector								
External antenna/s technical characteristics									
Type	Manufacturer	Model number	Gain						
Omni-directional	MTI	MT-341017/N/A	7.4dBi						
Transmitter 99% power bandwidth		12000kHz to 16000kHz							
Transmitter aggregate data rate/s (min-maximum)		1Mbps to 54Mbps							
Type of modulation		OFDM, DSSS, CCK							
Type of multiplexing		CSMA/CA							
Modulating test signal (baseband)		Random data							
Maximum transmitter duty cycle in normal use		90.%	Tx ON time	...X....msec	Period	...X....msec			
Transmitter duty cycle supplied for test		100%	Tx ON time	...X....msec	Period	...X....msec			
Transmitter power source									
V	DC	Nominal rated voltage	PoE 55VDC						
V	AC mains	Nominal rated voltage	90-240VAC	Frequency: 50/60Hz					
Spread spectrum technique used		Frequency hopping (FHSS)							
		Digital transmission system (DTS)							
		Hybrid							
Spread spectrum parameters for transmitters tested per FCC 15.247 only									
DSSS	chip sequence length		11bits						
	spectrum width		12MHz						



Test Report No.: 8812328348

Page 7 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

## 5. Test configuration:

The WBS-2400 unit has 4 possible RF board configurations. The difference between all the RF board configurations is the manufacturer of the transmit filter. Below is a list of all the supported filter manufacturers:

RF board PCB number PC00040: 1) Murata; 2) Bitel; 3) Comnav

RF board PCB number PC00041: 4) Skyworks

All of the above filters have the same operating frequency range. Also, the only difference between PCB number PC00040 and PCB number PC00041 is the footprint of the transmit filter.

The transmission power of each RF board is calibrated during the production process to a predetermined level, which is independent of the transmit filter manufacturer.

To withstand in every configuration and to use filters and boards in any complicating for the

WBS-2400 device has been performed the following:

1. Conducted Test: the conducted test (Minimum bandwidth; Peak power spectral density and Conducted spurious emissions) was performed with all possible configurations of Murata, Skyworks, Bitel and Comnav.
2. Find the worst case sample, where it is most critical at band edge.
3. Radiated (on the band edge) and repeat Conducted Tests of worst case sample.

In order to find the "worst case" sample, which can represent all kinds of RF filters, each filter was pre-tested as described above. After all radio conducted tests the Skyworks models were chosen as the "worst case", all final measurements were performed with 6 Skyworks filters.

For Radiated emission measurements per sec. 15.209 requirements the EUT was configured for tests as shown in Figure 2.

For transmitter measurements per sec. 15.247 requirements the EUT was configured for tests as shown in Figure 3.

For Radiated emission measurements per sec. 15.205 requirements the Radio unit was tested with antennas, detailed in Table 4.

Mnuf.	Freq. Range GHz	Gain dBi	Model	Type
MTI	2.4-2.4835	7.4	MT-341017/N/A	Omni-directional-

Table 4. Details of antenna used in WBS-2400.

Test Report No.: 8812328348



Page 8 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

RF output terminated by 50Ω

**Figure 2. Radiated emission test setup****Figure 3. Transmitter measurements test setup**



Test Report No.: 8812328348

Page 9 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

### 5.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, §1.1307, §1.1310

Limit for power density for general population/uncontrolled exposure is 1 mW/cm<sup>2</sup>.

The power density P (mW/cm<sup>2</sup>) = Pt /4π r<sup>2</sup>.

Where:

Pt - The transmitted power (EIRP) (mW)

Pt- the transmitted power which is equal to the output power 19 dBm plus maximum antenna gain – 7.4 dBi

r - The distance from the unit (cm)

The 1(mW/cm<sup>2</sup>) limit can be calculated from the above based on the following data:

The maximum EIRP for each transmit output = 26.4 dBm = 436.5mW

r =  $\sqrt{436.5/4\pi}$  = 5.9 cm

For aggregate Pt- the transmitted power which is equal to the output power 26.9 dBm plus maximum directional antenna gain – 15.2 dBi

The maximum aggregate EIRP = 42.1 dBm = 16218 mW:

r =  $\sqrt{16218/4\pi}$  = 35.9 cm

The allowed distance “r”, where RF exposure limits may not be exceeded, is 35.9 cm from the unit antenna main lobe.

The EUT with the attached antenna are mounted only outside the building on the high level pole or wall, which are above general public, see the manufacturer instructions for installation provided in attached documentation.



Test Report No.: 8812328348

Page 10 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

## 6. Test specification, Methods and Procedures

### Test Specification:

- ❖ CFR 47 FCC: Rules and Regulations; Part 15. "Radio frequency devices"; Subpart C: "Intentional radiators" (2006).

### Methods and Procedures:

- ❖ ANSI C63/4/2003: "American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz".

## 7. Measurements, examinations and derived results

### 7.1. Location of the Test Site:

The tests were conducted in the EMC laboratory of the Standards Institution of Israel in Tel-Aviv, in Wavion's laboratory and at open test site located at Kibbutz Native Halamed Hai in Emek HaEla, Israel.

### 7.2. Normal test condition:

Temperature: 22 °C

Humidity: 50 %



Test Report No.: 8812328348

Page 11 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

### 7.3. Conducted emission test (per Section 15.207):

#### 7.3.1. Requirements:

The EUTs conducted emission within the band 150 kHz to 30 MHz shall not exceed value required in section 15.207 (a).

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

\*Decreases with the logarithm of the frequency.

#### 7.3.2. Test procedure:

Each EUT was placed on a non-metallic table in a shielded chamber at a height of 80 cm from the floor and 40 cm from the nearest wall.

The EUT was operated to transmitting through the customer software.

First, initial scans were performed in normal (transmitting) mode of operation for carrier (channel) frequency at low, middle and the high of the 2.412 - 2.462 GHz frequency range under 4 data transfer bit rates. The worst results from all measurements (2412MHz frequency, 6Mbps bit rate) are presented at the plots 1 and 2.

Test equipment (EMI receiver) setup was as follow:

##### Initial scan:

Detector type Peak  
Mode Max hold  
Bandwidth 9 kHz  
Step size Continuous sweep  
Sweep time >100 msec

##### Measurements

Detector type Quasi-peak, Avg (CISPR)  
Bandwidth 9 kHz  
Measurement time 200 seconds/MHz  
Observation >15 seconds

### 7.3.3.

#### 7.3.4. Test results:

The test results were found complies with relevant standard requirements.

Test results are shown in Plots #1, 2.


Test Report No.: 8812328348

Page 12 of 105 Pages


Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1



**Plot # 1. Conducted emissions measurement result on 120 VAC power. Line- phase.**



**Plot # 2. Conducted emissions measurement result on 120 VAC power. Line- neutral.**



Test Report No.: 8812328348

Page 13 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

#### 7.4. Radiated emission test, general requirements (per section 15.209):

##### 7.4.1. Requirements:

The EUT's radiated emission shall not exceed value required in section 15.209.

##### 7.4.2. Test description:

The measurements were performed at the Open Area Test Site.

The test configuration is shown in Fig.2.

The EUT was arranged on a non-metallic table 0.8 m placed on the turn-table.

The measurements were performed at a 10 m measurement distance.

The Biconilog 30 MHz-2 GHz antenna was used.

The frequency range was investigated from 30 MHz to 2 GHz.

The measurements were performed at each frequency at which the signal was 20 dB below the limit or less.

The level were maximized by initially rotating turntable through 360°, varying the antenna height between 1 m and 4 m, rerouting EUT cables and changing antenna polarization from vertical to horizontal. The measuring equipment settings were:

##### Initial scan:

Detector type	Peak
Mode	Max hold
Bandwidth	120 kHz
Step size	Continuous sweep
Sweep time	>1 seconds/MHz

##### Measurements:

Detector type	Quasi-peak (CISPR 16)
Bandwidth	120 kHz
Measurement time	20 seconds/MHz
Observation	>15 seconds

##### 7.4.3. Radiated emission test results:

The test results were found complies with relevant standard requirements.

Test results are presented in Table 5.



Test Report No.: 8812328348

Page 14 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

**Table 5. Radiated emission test results**  
**FCC Part 15 section 15.209**

Frequency (MHz)	Turn-table Angle (°)	Antenna Polariz.	Antenna Height (m)	Emission Level Note 1 (dB $\mu$ V/m)	Limit @ 3 m (dB $\mu$ V/m)	Margin Note 2 (dB)	Results
113	354	V	115	36.3	43.5	7.2	Complies
80	355	H	400	39.0	40	1.0	Complies
73.1	321	V	146	38.1	40	1.9	Complies
152.9	227	V	120	36.8	43.5	6.7	Complies
186.9	171	V	386	35.6	43.5	7.9	Complies
200	26	V	289	34.1	43.5	9.4	Complies
240	18	V	321	37.1	46	8.9	Complies
300	15	V	236	38.9	46	7.1	Complies
320	34	H	151	40.9	46	5.1	Complies
400	104	H	385	36.4	46	9.6	Complies

Note 1: Emission level = E Reading (dB $\mu$ V) + Cable loss (dB) + Antenna Factor (dB/m) + 10 dB

Where 10 dB is an extrapolation to 3m distance factor.

For Cable Loss and Antenna Factor refer to Appendix 2.

Note 2: Margin (dB) = Limit (dB $\mu$ V/m) – Emission level (dB $\mu$ V/m)



Test Report No.: 8812328348

Page 15 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

## 7.5. Conducted spurious emission

### 7.5.1. Requirements:

Clause 15.247(c). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### 7.5.2. Pre-test scanning:

In order to find the “worst case” sample, which can represent all kinds of RF filters, each filter was pre-tested. The following filters were pre-tested: Murata, Comnav, Bitel, Skyworks. After all conducted spurious emissions tests the Skyworks models were chosen as the “worst case”, all final measurements were performed with 6 Skyworks filters (see 7.5.4).

### 7.5.3. Test Procedure:

The transmitter output is connected to a spectrum analyzer.

The RBW is set to 100 kHz.

The VBW is set to 300 kHz.

The spectrum from 30MHz to 26GHz is investigated with the transmitter set to the low, middle and high frequencies.



### 7.5.4. Test Results:





The WBS-2400 configurations for preliminary tests were as following: 2 RF filters Skyworks (outputs 1 & 2), 1 RF filter Comnav (output 3), 2 RF filter Bitel (outputs 4 & 5), 1 RF filter Murata (output 6).

The plots of conducted spurious emissions pre-scan for each RF filters (outputs 1-6 accordantly) are presented on the plots # 3-62. The most differences in spurious emissions were found. Following pre-scan tests results the “worst case” from the point of view of spurious emissions is Skyworks filter.

Test Report No.: 8812328348

Page 16 of 105 Pages

 Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
 Model: WBS-2400 FCC ID: UGM-WBS2400-1


**Test Report No.: 8812328348**
**Page 17 of 105 Pages**
**Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station**
**Model: WBS-2400**
**FCC ID: UGM-WBS2400-1**

**Plot # 7.**
**Output 3. Low frequency bandedge.  
802.11b mode.**
**Plot # 8.**
**Output 3. Low frequency spurious.  
802.11b mode.**
**Plot # 9.**
**Output 4. Low frequency bandedge.  
802.11b mode.**
**Plot # 10.**
**Output 4. Low frequency spurious.  
802.11b mode.**



Test Report No.: 8812328348





Page 18 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400


FCC ID: UGM-WBS2400-1




**Test Report No.: 8812328348**
**Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station**
**Model: WBS-2400**
**Page 19 of 105 Pages**
**FCC ID: UGM-WBS2400-1**


Test Report No.: 8812328348

Page 20 of 105 Pages





Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
Model: WBS-2400 FCC ID: UGM-WBS2400-1





Plot # 19.





**Output 5. Middle frequency spurious.**  
802.11b mode.

Plot # 20.

**Output 6. Middle frequency spurious.**  
802.11b mode.



**Test Report No.: 8812328348**
**Page 21 of 105 Pages**
**Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station**  
**Model: WBS-2400**  
**FCC ID: UGM-WBS2400-1**

**Plot # 21.**
**Output 1. High frequency bandedge.  
802.11b mode.**
**Plot # 22.**
**Output 1. High frequency spurious.  
802.11b mode.**

**Plot # 23.**
**Output 2. High frequency bandedge.  
802.11b mode.**
**Plot # 24.**
**Output 2. High frequency spurious.  
802.11b mode.**

**Test Report No.: 8812328348**
**Page 22 of 105 Pages**
**Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station**  
**Model: WBS-2400** **FCC ID: UGM-WBS2400-1**

**Plot # 25.**
**Output 3. High frequency bandedge.**  
**802.11b mode.**
**Plot # 26.**
**Output 3. High frequency spurious.**  
**802.11b mode.**

**Plot # 27.**
**Output 4. High frequency bandedge.**  
**802.11b mode.**
**Plot # 28.**
**Output 4. High frequency spurious.**  
**802.11b mode.**



**Test Report No.: 8812328348**
**Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station**
**Model: WBS-2400**
**Page 23 of 105 Pages**
**FCC ID: UGM-WBS2400-1**

**Plot # 29.**
**Output 5. High frequency bandedge.  
802.11b mode.**

**Plot # 30.**
**Output 5. High frequency spurious.  
802.11b mode.**

**Plot # 31.**
**Output 6. High frequency bandedge.  
802.11b mode.**

**Plot # 32.**
**Output 6. High frequency spurious.  
802.11b mode.**

Test Report No.: 8812328348

Page 24 of 105 Pages

 Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
 Model: WBS-2400 FCC ID: UGM-WBS2400-1


Plot # 33.

 Output 1. Low frequency bandedge.  
 802.11g mode.


Plot # 35.



 Output 2. Low frequency bandedge.  
 802.11g mode.

Plot # 34.

 Output 1. Low frequency spurious.  
 802.11g mode.

Test Report No.: 8812328348



Page 25 of 105 Pages

 Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
 Model: WBS-2400 FCC ID: UGM-WBS2400-1


Plot # 37.

 Output 3. Low frequency bandedge.  
 802.11g mode.

Plot # 38.

 Output 3. Low frequency spurious.  
 802.11g mode.


Plot # 39.



 Output 4. Low frequency bandedge.  
 802.11g mode.

Plot # 40.

 Output 4. Low frequency spurious.  
 802.11g mode.

Test Report No.: 8812328348



Page 26 of 105 Pages

 Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
 Model: WBS-2400 FCC ID: UGM-WBS2400-1


Plot # 41.

 Output 5. Low frequency bandedge.  
 802.11g mode.

Plot # 42.

 Output 5. Low frequency spurious.  
 802.11g mode.


Plot # 43.



 Output 6. Low frequency bandedge.  
 802.11g mode.

Plot # 44.


 Output 6. Low frequency spurious.  
 802.11g mode.

Test Report No.: 8812328348


Page 27 of 105 Pages

 Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
 Model: WBS-2400 FCC ID: UGM-WBS2400-1


Plot # 45.

 Output 1. Middle frequency spurious.  
 802.11g mode.


Plot # 47.


 Output 3. Middle frequency spurious.  
 802.11g mode.


Plot # 48.


 Output 4. Middle frequency spurious.  
 802.11g mode.

Test Report No.: 8812328348

Page 28 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
Model: WBS-2400 FCC ID: UGM-WBS2400-1

Plot # 49.


Output 5. Middle frequency spurious.  
802.11g mode.

Plot # 50.


Output 6. Middle frequency spurious.  
802.11g mode.

Test Report No.: 8812328348


Page 29 of 105 Pages

 Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
 Model: WBS-2400 FCC ID: UGM-WBS2400-1



Plot # 51.

 Output 1. High frequency bandedge.  
 802.11g mode.


Plot # 52.

 Output 1. High frequency spurious.  
 802.11g mode.


Plot # 53.



 Output 2. High frequency bandedge.  
 802.11g mode.


Plot # 54.

 Output 2. High frequency spurious.  
 802.11g mode.

Test Report No.: 8812328348



Page 30 of 105 Pages

 Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station  
 Model: WBS-2400 FCC ID: UGM-WBS2400-1


Plot # 55.

 Output 3. High frequency bandedge.  
 802.11g mode.

Plot # 56.



 Output 3. High frequency spurious.  
 802.11g mode.



Plot # 57.

 Output 4. High frequency bandedge.  
 802.11g mode.

Plot # 58.

 Output 4. High frequency spurious.  
 802.11g mode.

**Test Report No.: 8812328348**
**Page 31 of 105 Pages**
**Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station**  
**Model: WBS-2400**  
**FCC ID: UGM-WBS2400-1**

**Plot # 59.**
**Output 5. High frequency bandedge.  
802.11g mode.**

**Plot # 61.**
**Output 6. High frequency bandedge.  
802.11g mode.**

**Plot # 62.**
**Output 6. High frequency spurious.  
802.11g mode.**

Test Report No.: 8812328348

Page 32 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

The final configuration has been built with 6 Skyworks RF filters.

All test results met the requirements.

The tests were performed with the worst case, which is higher power level.


All harmonics/spurs are at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

The results are shown in plots # 63-122.



Plot # 63.

Output 1. Low frequency bandedge.  
802.11b mode.




Plot # 64.

Output 1. Low frequency spurious.  
802.11b mode.



Plot # 65.

Output 2. Low frequency bandedge.  
802.11b mode.



Plot # 66.

Output 2. Low frequency spurious.  
802.11b mode.




Test Report No.: 8812328348

Page 33 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1




Test Report No.: 8812328348

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station


Model: WBS-2400

Page 34 of 105 Pages

FCC ID: UGM-WBS2400-1




**Output 5. Low frequency bandedge.  
802.11b mode.**



**Output 5. Low frequency spurious.  
802.11b mode.**



**Output 6. Low frequency bandedge.  
802.11b mode.**



**Output 6. Low frequency spurious.  
802.11b mode.**





Test Report No.: 8812328348

Page 35 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1



Test Report No.: 8812328348

Page 36 of 105 Pages

Title: Test on 2.4 GHz Band Outdoor WiFi (802.11b/g) Wireless Base Station

Model: WBS-2400

FCC ID: UGM-WBS2400-1

