FCC REPORT (BLE)

Applicant:	National Electronics & Watch Co., Ltd
Address of Applicant:	15/F., Shing Dao Ind. Bldg., 232 Aberdeen Main Road, Aberdeen, HK

Equipment Under Test (EUT)

Product Name:	Smart Gear
Model No.:	M13-963D
FCC ID:	UH5M13-963DBSG
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	10 Jan., 2014
Date of Test:	13 Jan., to 25 Feb., 2014
Date of report issued:	26 Feb., 2014
Test Result:	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	*26 Feb., 2014*	*Original*

Prepared by: Shirley Li ***Date:*** *26 Feb., 2014*

Report Clerk

Reviewed by: Abomb Yang ***Date:*** *26 Feb., 2014*

Project Engineer

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 CLIENT INFORMATION 5
5.2 GENERAL DESCRIPTION OF E.U.T. 5
5.3 TEST ENVIRONMENT AND MODE 7
5.4 DESCRIPTION OF SUPPORT UNITS 7
5.5 LABORATORY FACILITY 7
5.6 LABORATORY LOCATION 7
5.7 TEST INSTRUMENTS LIST 8

6 TEST RESULTS AND MEASUREMENT DATA 9

6.1 ANTENNA REQUIREMENT: 9
6.2 CONDUCTED EMISSION 10
6.3 CONDUCTED OUTPUT POWER 13
6.4 OCCUPY BANDWIDTH 15
6.5 POWER SPECTRAL DENSITY 18
6.6 BAND EDGE 20
6.6.1 Conducted Emission Method 20
6.6.2 Radiated Emission Method 22
6.7 SPURIOUS EMISSION 27
6.7.1 Conducted Emission Method 27
6.7.2 Radiated Emission Method 30

7 TEST SETUP PHOTO 37

8 EUT CONSTRUCTIONAL DETAILS 39

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	National Electronics & Watch Co., Ltd
Address of Applicant:	15/F., Shing Dao Ind. Bldg., 232 Aberdeen Main Road, Aberdeen, HK
Manufacturer:	National Electronics & Watch Co., Ltd
Address of Manufacturer:	15/F., Shing Dao Ind. Bldg., 232 Aberdeen Main Road, Aberdeen, HK
Factory:	EASTERN MOUNT ELECTRONICS & WATCH CO., LTD
Address of Factory:	The second industrial Estate, Hong Hua Shan, Gong Ming Zhen, Baoôan District., Shenzhne, P. R. C

5.2 General Description of E.U.T.

Product Name:	Smart Gear
Model No.:	M13-963D
Operation Frequency:	2402-2480 MHz
Channel numbers:	40
Channel separation:	2 MHz
Modulation technology:	GFSK
Data speed :	1Mbps
Antenna Type:	Internal Antenna
Antenna gain:	0.04 dBi
Power supply:	Rechargeable Li-ion Battery DC3.7V 90mAh

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2442MHz
The Highest channel	2480MHz

5.3 Test environment and mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Operation mode	Keep the EUT in continuous transmitting with modulation
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.	

5.4 Description of Support Units

N/A

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Baoan District, Shenzhen, Guangdong, China
Tel: +86-755-23118282
Fax: +86-755-23116366

5.7 Test Instruments list

Radiated Emission:

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	June 09 2013	June 08 2014
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	May 25 2013	May 24 2014
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	May 25 2013	May 24 2014
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Coaxial Cable	CCIS	N/A	CCIS0016	Apr. 01 2013	Mar. 31 2014
6	Coaxial Cable	CCIS	N/A	CCIS0017	Apr. 01 2013	Mar. 31 2014
7	Coaxial cable	CCIS	N/A	CCIS0018	Apr. 01 2013	Mar. 31 2014
8	Coaxial Cable	CCIS	N/A	CCIS0019	Apr. 01 2013	Mar. 31 2014
9	Coaxial Cable	CCIS	N/A	CCIS0087	Apr. 01 2013	Mar. 31 2014
10	Amplifier(10kHz-1.3GHz)	HP	8447D	CCIS0003	Apr. 01 2013	Mar. 31 2014
11	Amplifier(1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	June 09 2013	June 08 2014
12	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Apr. 01 2013	Mar. 31 2014
13	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2013	Mar. 29 2014
14	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
15	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
16	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP	CCIS0023	May. 25 2013	May. 24 2014
17	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	Apr 01 2013	Mar. 31 2014
18	Loop antenna	Laplace instrument	RF300	EMC0701	Aug. 12 2013	Aug. 11 2014
19	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	May. 25 2013	May. 24 2014
20	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	May. 25 2013	May. 24 2014

Conducted Emission:

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	June 09 2013	June 08 2014
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	May 25 2013	May 24 2014
3	LISN	CHASE	MN2050D	CCIS0074	Apr 01 2013	Mar. 31 2014
4	Coaxial Cable	CCIS	N/A	CCIS0086	Apr. 01 2013	Mar. 31 2014
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

6 Test results and Measurement Data

6.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: *An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.* *15.247(c) (1)(i) requirement:* *(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.*	
E.U.T Antenna:	
The antenna is an internal antenna which cannot replace by end-user, the best case gain of the antenna is 0.04 dBi.	

6.2 Conducted Emission

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.4: 2003
Test Frequency Range:	150 kHz to 30 MHz
Class / Severity:	Class B
Receiver setup:	RBW=9kHz, VBW=30kHz
Limit:	Frequency range (MHz) / Limit (dBuV): Quasi-peak / Average 0.15-0.5: 66 to 56* / 56 to 46* 0.5-5: 56 / 46 5-30: 60 / 50 * Decreases with the logarithm of the frequency.
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.
Test setup:	 *Remark:* *E.U.T: Equipment Under Test* *LISN: Line Impedence Stabilization Network* *Test table height=0.8m*
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Neutral:



Trace: 15

Site : CCIS Conducted test Site
Condition : FCC PART15 B QP LISN NEUTRAL
EUT : Smart Gear
Model : M13-963
Test Mode : BT mode
Power Rating : DC 5V
Environment : Temp: 23 ℃ Huni:56% Atmos:101KPa
Test Engineer: A-bomb
Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.155	40.25	0.25	10.78	51.28	65.74	-14.46	QP
2	0.165	19.99	0.25	10.77	31.01	55.21	-24.20	Average
3	0.180	33.79	0.25	10.77	44.81	64.50	-19.69	QP
4	0.220	14.33	0.25	10.76	25.34	52.83	-27.49	Average
5	0.489	21.07	0.29	10.76	32.12	56.19	-24.07	QP
6	0.489	12.41	0.29	10.76	23.46	46.19	-22.73	Average
7	0.751	8.39	0.19	10.79	19.37	46.00	-26.63	Average
8	1.535	15.14	0.26	10.93	26.33	56.00	-29.67	QP
9	2.608	5.14	0.29	10.93	16.36	46.00	-29.64	Average
10	3.190	16.48	0.29	10.91	27.68	56.00	-28.32	QP
11	13.408	14.34	0.25	10.91	25.50	60.00	-34.50	QP
12	14.213	9.57	0.25	10.91	20.73	50.00	-29.27	Average

Line:



Trace: 17

Site : CCIS Conducted test Site
Condition : FCC PART15 B QP LISN LINE
EUT : Smart Gear
Model : M13-963
Test Mode : BT mode
Power Rating : DC 5V
Environment : Temp: 23 'C Huni:56% Atmos:101KPa
Test Engineer: A-bomb
Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.165	33.73	0.27	10.77	44.77	65.21	-20.44	QP
2	0.170	16.60	0.27	10.77	27.64	54.94	-27.30	Average
3	0.180	33.11	0.28	10.77	44.16	64.50	-20.34	QP
4	0.190	16.44	0.28	10.76	27.48	54.02	-26.54	Average
5	0.471	19.21	0.29	10.75	30.25	56.49	-26.24	QP
6	0.489	12.38	0.29	10.76	23.43	46.19	-22.76	Average
7	0.739	19.27	0.22	10.79	30.28	56.00	-25.72	QP
8	0.751	7.78	0.23	10.79	18.80	46.00	-27.20	Average
9	2.692	4.07	0.27	10.93	15.27	46.00	-30.73	Average
10	3.820	16.78	0.28	10.90	27.96	56.00	-28.04	QP
11	14.213	13.50	0.32	10.91	24.73	60.00	-35.27	QP
12	14.213	9.35	0.32	10.91	20.58	50.00	-29.42	Average

Notes:

1. An initial pre-scan was performed on the live and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss

6.3 Conducted Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.4:2003 and KDB558074
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	Test method refer to KDB558074 v03r01 (DTS Measure Guidance) section 9.2.2.2

Measurement Data

Test CH	Maximum Conducted Output Power (dBm)	Limit(dBm)	Result
Lowest	-1.21	30.00	Pass
Middle	-2.07		
Highest	-3.63		

Test plot as follows:

Test mode:	GFSK



Lowest channel



Middle channel



Highest channel

6.4 Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.4:2003 and KDB558074
Limit:	>500kHz
Test setup:	
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Test CH	6dB Emission Bandwidth (MHz)	Limit(kHz)	Result
Lowest	0.73	>500	Pass
Middle	0.74		
Highest	0.73		

Test CH	99% Occupy Bandwidth (MHz)	Limit(kHz)	Result
Lowest	1.05	N/A	N/A
Middle	1.05		
Highest	1.05		

Test plot as follows:

Test mode:6dB EBW	GFSK



Lowest channel



Middle channel



Highest channel

Test mode:99% OBW	GFSK



Lowest channel



Middle channel



Highest channel

6.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.4:2003 and KDB558074
Limit:	8 dBm
Test setup:	
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Test CH	Power Spectral Density (dBm)	Limit(dBm)	Result
Lowest	-1.94	8.00	Pass
Middle	-2.68		
Highest	-4.08		

Test plots as follow:

Test mode:	



Lowest channel

Middle channel

Highest channel