



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No. :** CQASZ20181100006E-03  
**Applicant:** Shenzhen Shuaixian Electronic Equipment Co., Ltd.  
**Address of Applicant:** NO.10 Lane3, Longxing Rd., Dakang Long Village, Henggang Town, Longgang Dist., Shenzhen, China  
**Manufacturer:** Shenzhen Shuaixian Electronic Equipment Co., Ltd.  
**Address of Manufacturer:** NO.10 Lane3, Longxing Rd., Dakang Long Village, Henggang Town, Longgang Dist., Shenzhen, China  
**Factory:** Shenzhen Shuaixian Electronic Equipment Co., Ltd.  
**Address of Factory:** NO.10 Lane3, Longxing Rd., Dakang Long Village, Henggang Town, Longgang Dist., Shenzhen, China

**Equipment Under Test (EUT):**  
**Product:** Bluetooth wireless headphones  
**All Model No.:** A6, Marathon, SX-910, SX-910A, SX-910H  
**Test Model No.:** A6  
**Brand Name:** SUICEN, LEVIN, Linkwitz  
**FCC ID:** UHBSX-910  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06

**Date of Test:** 2018-11-12 to 2018-11-16  
**Date of Issue:** 2018-11-16  
**Test Result :** **PASS\***

**Tested By:**

(Daisy Qin)

**Reviewed By:**

(Aaron Ma)

**Approved By:**

( Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 1 Version

### Revision History Of Report

| Report No.           | Version | Description    | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20181100006E-03 | Rev.01  | Initial report | 2018-11-16 |

## 2 Contents

|  | Page |
|--|------|
| 1 VERSION .....                              | 2    |
| 2 CONTENTS .....                             | 3    |
| 3 GENERAL INFORMATION .....                  | 4    |
| 3.1 CLIENT INFORMATION.....                  | 4    |
| 3.2 GENERAL DESCRIPTION OF EUT .....         | 4    |
| 3.3 GENERAL DESCRIPTION OF BT .....          | 4    |
| 3.4 GENERAL DESCRIPTION OF BLE.....          | 4    |
| 4 SAR EVALUATION .....                       | 6    |
| 4.1 RF EXPOSURE COMPLIANCE REQUIREMENT ..... | 6    |
| 4.1.1 <i>Standard Requirement</i> .....      | 6    |
| 4.1.2 <i>Limits</i> .....                    | 6    |
| 4.1.3 <i>EUT RF Exposure</i> .....           | 7    |

### 3 General Information

#### 3.1 Client Information

|                          |  |
|--------------------------|--|
| Applicant:               | Shenzhen Shuaixian Electronic Equipment Co., Ltd.  |
| Address of Applicant:    | NO.10 Lane3, Longxing Rd., Dakang Long Village, Henggang Town, Longgang Dist., Shenzhen, China |
| Manufacturer:            | Shenzhen Shuaixian Electronic Equipment Co., Ltd.  |
| Address of Manufacturer: | NO.10 Lane3, Longxing Rd., Dakang Long Village, Henggang Town, Longgang Dist., Shenzhen, China |
| Factory:                 | Shenzhen Shuaixian Electronic Equipment Co., Ltd.  |
| Address of Factory:      | NO.10 Lane3, Longxing Rd., Dakang Long Village, Henggang Town, Longgang Dist., Shenzhen, China |

#### 3.2 General Description of EUT

|                    |  |
|--------------------|--|
| Product Name:      | Bluetooth wireless headphones  |
| All Model No.:     | A6, Marathon, SX-910, SX-910A, SX-910H   |
| Test Model No.:    | A6   |
| Trade Mark:        | SUICEN, LEVIN, Linkwitz  |
| Hardware Version:  | V1.0   |
| Software Version:  | V1.0   |
| Bluetooth Version: | V4.2   |
| Sample Type:       | <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location |
| Power Supply:      | lithium battery:DC3.7V, Charge by DC5.0V   |

#### 3.3 General Description of BT

|                       |   |
|-----------------------|---|
| Operation Frequency:  | 2402MHz~2480MHz                         |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS) |
| Modulation Type:      | GFSK, $\pi/4$ DQPSK, 8DPSK              |
| Number of Channel:    | 79                                      |
| Transfer Rate:        | 1Mbps/2Mbps/3Mbps                       |
| Hopping Channel Type: | Adaptive Frequency Hopping systems      |
| Test Software of EUT: | Blue test 3 (manufacturer declare )     |
| Antenna Type:         | PCB antenna                             |
| Antenna Gain:         | 3.48dBi                                 |

#### 3.4 General Description of BLE

|                       |                                     |
|-----------------------|-------------------------------------|
| Operation Frequency:  | 2402MHz~2480MHz                     |
| Modulation Type:      | GFSK                                |
| Transfer Rate:        | 1Mbps                               |
| Number of Channel:    | 40                                  |
| Test Software of EUT: | Blue test 3 (manufacturer declare ) |
| Antenna Type:         | PCB antenna                         |

---

|               |         |
|---------------|---------|
| Antenna Gain: | 3.48dBi |
|---------------|---------|

Note:

All model: A6, Marathon, SX-910, SX-910A, SX-910H

Only the model A6 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 4.1.3 EUT RF Exposure

#### Measurement Data

| GFSK mode        |                            |                            |                       |       |
|------------------|----------------------------|----------------------------|-----------------------|-------|
| Test channel     | Peak Output Power<br>(dBm) | Tune up tolerance<br>(dBm) | Maximum tune-up Power |       |
|                  |                            |                            | (dBm)                 | (mW)  |
| Lowest(2402MHz)  | 2.500                      | 2.0±1                      | 3.0                   | 1.995 |
| Middle(2441MHz)  | 5.220                      | 4.5±1                      | 5.5                   | 3.548 |
| Highest(2480MHz) | 6.310                      | 5.5±1                      | 6.5                   | 4.467 |
| 8DPSK mode       |                            |                            |                       |       |
| Test channel     | Peak Output Power<br>(dBm) | Tune up tolerance<br>(dBm) | Maximum tune-up Power |       |
|                  |                            |                            | (dBm)                 | (mW)  |
| Lowest(2402MHz)  | 0.310                      | 0±1                        | 1.0                   | 1.259 |
| Middle(2441MHz)  | 4.090                      | 3.5±1                      | 4.5                   | 2.818 |
| Highest(2480MHz) | 5.350                      | 4.5±1                      | 5.5                   | 3.548 |

| Worst case: GFSK  |   |                         |                       |       |                  |                     |
|---|---|-------------------------|-----------------------|-------|------------------|---------------------|
| Channel   | Maximum Peak Conducted Output Power (dBm) | Tune up tolerance (dBm) | Maximum tune-up Power |       | Calculated value | Exclusion threshold |
|   |   |                         | (dBm)                 | (mW)  |                  |                     |
| Lowest (2402MHz)  | 2.500                                     | 2.0±1                   | 3.0                   | 1.995 | 0.62             | 3.0                 |
| Middle (2441MHz)  | 5.220                                     | 4.5±1                   | 5.5                   | 3.548 | 1.11             |                     |
| Highest (2480MHz)                                       | 6.310                                     | 5.5±1                   | 6.5                   | 4.467 | 1.41             |                     |
| Conclusion: the calculated value ≤3.0, SAR is exempted. |   |                         |                       |       |                  |                     |

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20181100006E-01

2) For BLE

Measurement Data

| GFSK mode        |                            |                            |                       |       |
|------------------|----------------------------|----------------------------|-----------------------|-------|
| Test channel     | Peak Output Power<br>(dBm) | Tune up tolerance<br>(dBm) | Maximum tune-up Power |       |
|                  |                            |                            | (dBm)                 | (mW)  |
| Lowest(2402MHz)  | 3.86                       | 3.0±1                      | 4.0                   | 2.512 |
| Middle(2440MHz)  | 5.77                       | 5.0±1                      | 6.0                   | 3.981 |
| Highest(2480MHz) | 6.84                       | 6.0±1                      | 7.0                   | 5.012 |

| Worst case: GFSK  |   |                         |                       |       |                  |                     |
|---|---|-------------------------|-----------------------|-------|------------------|---------------------|
| Channel   | Maximum Peak Conducted Output Power (dBm) | Tune up tolerance (dBm) | Maximum tune-up Power |       | Calculated value | Exclusion threshold |
|   |   |                         | (dBm)                 | (mW)  |                  |                     |
| Lowest (2402MHz)  | 3.86                                      | 3.0±1                   | 4.0                   | 2.512 | 0.78             | 3.0                 |
| Middle (2440MHz)  | 5.77                                      | 5.0±1                   | 6.0                   | 3.981 | 1.24             |                     |
| Highest (2480MHz)                                       | 6.84                                      | 6.0±1                   | 7.0                   | 5.012 | 1.58             |                     |
| Conclusion: the calculated value ≤3.0, SAR is exempted. |   |                         |                       |       |                  |                     |

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20181100006E-02

BDR, EDR and BLE can not simultaneous transmitting at same time.