# Manual

#### INSTALLATION

To install the VRBT300V, attach to the visor of your vehicle using the clip on the rear of the unit.

#### LOW BATTERY WARNING

When the VRBT300V battery is low, the Blue LED will be off, the Red LED will flash, and the speaker will make a BEEP sound.

# POWER ON AND OFF

Press and hold the Multi-Function Button until you hear a short BEEP and HELLO is displayed on the LCD. If the unit connects with a paired device, you will hear a beep in the Bluetooth icon will be displayed on the LCD. When the VRBT300V is in standby mode, press and hold the Multi-Function Button for 3 seconds to turn the unit off. You will hear a long BEEP and both LED lights will turn off.

# PAIRING WITH A BLUETOOTH ENABLED CELL PHONE

- 1. The VRBT300V and the Bluetooth enabled cell phone should be within a distance of 3 feet(1 meter).
- 2. With the VRBT300V OFF ,press and hold the Multi-Function button until you hear 2 beeps. The Red & Blue LEDs will flash indicating the unit is ready to be paired.
- 3. The Bluetooth cell phone will search for nearby Bluetooth devices. The cell phone will display the "VRBT300V" in the list of Bluetooth devices. If you are using a "dongle" type Bluetooth adaptor, follow the manufacturer's instructions for that device.
- 4. Select "VRBT300V" to add this Bluetooth device into the list of paired devices.
- 5. Enter in the PIN Code "0000" and your mobile phone will show that pairing is complete.
- 6. If pairing is successful ,user will hear a long BEEP and the Blue LED will flash about every 3 seconds.

# CANCEL BUTTON

End a call-Press Once
End a call and return to a "CALL ON HOLD" - Press Once
Exit call log book - Press Once

# CALLER ID DISPLAY

The LCD will flash on & off while displaying the phone number of the incoming call. The phone number of the incoming call will be displayed on the LCD.

#### CALL LOG BOOK

Note: The Call Log Book feature DOES NOT access the cell phone's call log book.

- 1. press the 3-way button once to enter the call log menu. The three call log categories are: Missed call->Dialed Calls->Received calls in that order.
- 2. move the 3-way button to the LEFT or RIGHT to navigate the three logs.
- 3. press the 3-way button once to enter each log.
- 4. after you enter a Call Book Log, move the 3-way button to the LEFT or RIGHT to navigate through the phone numbers. press the Multi-Function Button to call the highlighted phone number.
- 5. press the Cancel button to quit the call log Book.

#### CALL LOG DISPLAY

Within the Call log Books, each number is preceded by a single digit number (0-5) and a space to designate the order the calls were received. "0" is the mist recent number; "1" is the next number and so on, up to "5".

#### RECONNECT TO CELL

- 1. if the vrbt300V loses connection by moving out of operating distance of the paired cell phone, reconnect by moving it within the operating area and press the Multi-Function button once to reconnect to the cell phone.
- 2. if the VRBT300v is disconnected because of being powered off, it will connect automatically after powering on again.

# STORAGE CONDITONS

Operating Temperature Range  $0^{\circ}$ C to  $+50^{\circ}$ C( $32^{\circ}$  to  $122^{\circ}$ F) without loss of function.

Storage temperature range: -20°C to +65°C(-4° to 149°F) without any damage. Humidity range: 30%-90% humidity.

# **EARBUD**

Insert the earbud's plug into the headphone jack on the side of the VRBT300V.

Use the earbud for privacy or high ambient noise situations.

Note: Please refer to your cell phone's product user manual for Voiced Dialing, Call & Redial functionality and settings.

FCC NOTE: THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY RADIO OR TV INTERFERENCE CAUSED BY UNAUTHORIZED MODIFICATIONS TO THIS EQUIPMENT. SUCH MODIFICATIONS COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: 1. This device may not cause harmful interference, and 2. This device must accept any interference received, including interference that may cause undesired operation