



SAR Evaluation Report

IN ACCORDANCE WITH THE REQUIREMENTS OF
FCC OET BULLETIN 65 SUPPLEMENT C
IC RSS 102 ISSUE 2 : NOVERMBER 2005

FOR

WLAN PHONE

MODEL: IP3NA-8WV

FCC ID: UI3-8WV
IC: 140L-8WV

REPORT NUMBER: 07J11507-3

ISSUE DATE: FEBUARY 28, 2008

Prepared for

NEC INFRONTIA INC.
6365 NORTH STATE HIGHWAY 161
IRVING, TEXAS 75039-2402, USA

Prepared by

COMPLIANCE CERTIFICATION SERVICES
47173 BENICIA STREET,
FREMONT, CA 94538 USA

NVLAP®

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issued date	Revisions	Revised By
--	2-28-08	Initial issue	Hsin Fu Shih

CERTIFICATE OF COMPLIANCE (SAR EVALUATION)**DATES OF TEST:** February 1, 2008

APPLICANT:	NEC INFRONTIA INC.
ADDRESS:	6365 NORTH STATE HIGHWAY 161 IRVING, TEXAS 75039-2402, USA
FCC ID:	UI3-8WV
MODEL:	IP3NA-8WV
DEVICE CATEGORY:	Portable Device
EXPOSURE CATEGORY:	General Population/Uncontrolled Exposure

WLAN PHONE		
Test Sample is a:	Production unit	
Modulation type:	Direct Sequence Spread Spectrum (DSSS) for 802.11b Orthogonal Frequency Division Multiplexing (OFDM) for 802.11g	
Rule Parts	Frequency Range [MHz]	The Highest SAR Values [1g_mW/g]
FCC 15.247	2412 - 2462	Head Positions: 0.480 Body Positions: 0.080

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in FCC OET 65 Supplement C (Edition 01-01) and RSS 102.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:



Hsin Fu Shih
Engineering Supervisor
Compliance Certification Services

Tested By:



Jonathan King
EMC Engineer
Compliance Certification Services

TABLE OF CONTENTS

1	DEVICE UNDER TEST (DUT) DESCRIPTION	5
2	FACILITIES AND ACCREDITATION	6
3	SYSTEM DESCRIPTION	7
3.1	COMPOSITION OF INGREDIENTS FOR TISSUE SIMULATING LIQUIDS	8
4	TEST POSITIONS FOR DEVICES OPERATING NEXT TO A PERSON'S EAR.....	9
4.1	CHEEK/TOUCH POSITION.....	10
4.2	EAR/TILT POSITION	11
4.3	TEST POSITIONS FOR BODY-WORN AND OTHER SIMILAR CONFIGURATIONS	12
5	SIMULATING LIQUID PARAMETERS CHECK.....	13
5.1	SIMULATING LIQUID PARAMETER CHECK RESULT.....	14
6	SYSTEM PERFORMANCE CHECK.....	16
6.1	SYSTEM PERFORMANCE CHECK RESULTS.....	17
7	SAR MEASURMENT PROCEDURE	18
7.1	DASY4 SAR MEASURMENT PROCEDURE	19
8	PROCEDURE USED TO ESTABLISH TEST SIGNAL	20
9	SAR MEASURMENT RESULTS.....	21
9.1	HEAD POSITIONS - LEFT HAND SIDE (LHS)	21
9.2	HEAD POSITIONS - RIGHT HAND SIDE (RHS)	22
9.3	BODY-WORN POSITION – EUT TESTED WITH 15MM SEPARATION DISTANCE	23
10	MEASURMENT UNCERTAINTY	24
10.1	MEASURMENT UNCERTAINTY FOR 300 MHZ – 3000 MHZ	24
11	EQUIPMENT LIST AND CALIBRATION.....	25
12	PHOTOS	26
13	ATTACHMENTS.....	28

1 DEVICE UNDER TEST (DUT) DESCRIPTION

WLAN PHONE		
Normal operation:	Head and body worn positions	
Accessories:	<u>Headset:</u> Manufacturer: Hosiden Corporation Part Number: TYX3588-010197	
Duty cycle:	802.11b mode:	89%
	802.11g mode:	58%
Antenna(s)	Main Antenna: Sub Antenna:	Manufacturer: Sansei Electric Co., Ltd. Part Number: IP3NA-8WV MAIN ANTENNA Manufacturer: NEC Infrontia Corp. Part Number: NOT APPLICABLE
Note: Only the Main Antenna was used for the SAR testing.		
Battery:	Manufacturer: Part Number:	NEC Tokin Corp. WLPS3(E)BATT. PACK-A

2 FACILITIES AND ACCREDITATION


The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, CA 94538 USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."



CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

3 SYSTEM DESCRIPTION



The DASY4 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY4 software.
- Remote controls with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validate the proper functioning of the system.

3.1 COMPOSITION OF INGREDIENTS FOR TISSUE SIMULATING LIQUIDS

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

Salt: 99+% Pure Sodium Chloride

Sugar: 98+% Pure Sucrose

Water: De-ionized, 16 MΩ+ resistivity

HEC: Hydroxyethyl Cellulose


DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1, 3, 3-tetramethylbutyl)phenyl]ether

4 TEST POSITIONS FOR DEVICES OPERATING NEXT TO A PERSON'S EAR

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper 1/4 of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point". The "test device reference point" should be located at the same level as the center of the earpiece region. The "vertical centerline" should bisect the front surface of the handset at its top and bottom edges. A "ear reference point" is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the "phantom reference plane" defined by the three lines joining the center of each "ear reference point" (left and right) and the tip of the mouth.

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the "N-F" line defined along the base of the ear spacer that contains the "ear reference point". For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The "test device reference point" is aligned to the "ear reference point" on the head phantom and the "vertical centerline" is aligned to the "phantom reference plane". This is called the "initial ear position". While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:



4.1 CHEEK/TOUCH POSITION


The device is brought toward the mouth of the head phantom by pivoting against the "ear reference point" or along the "N-F" line for the SCC-34/SC-2 head phantom.

This test position is established:

- i. When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.
- ii. (or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

Cheek / Touch Position




4.2 EAR/TILT POSITION

With the handset aligned in the "Cheek/Touch Position":

- i. If the earpiece of the handset is not in full contact with the phantom's ear spacer (in the "Cheek/Touch position") and the peak SAR location for the "Cheek/Touch" position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the "initial ear position" by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.
- ii. (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both "ear reference points" (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the "test device reference point" until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15° . After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both "ear reference points" until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the "Cheek/Touch" and "Ear/Tilt" positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tilt/Ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.




4.3 TEST POSITIONS FOR BODY-WORN AND OTHER SIMILAR CONFIGURATIONS

Without the belt-clips or holsters

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.

5 SIMULATING LIQUID PARAMETERS CHECK

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The relative permittivity and conductivity of the tissue material should be within $\pm 5\%$ of the values given in the table below.



Reference Values of Tissue Dielectric Parameters for Head and Body Phantom (for 150 – 3000 MHz and 5800 MHz)

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE Standard 1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE Standard 1528.

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)

5.1 SIMULATING LIQUID PARAMETER CHECK RESULT

Simulating Liquid Dielectric Parameter Check Result @ Head 2450 MHz

Room Ambient Temperature = 23°C; Relative humidity = 45% Measured by: Jonathan King

Simulating Liquid			Parameters		Measured	Target	Deviation (%)	Limit (%)
f (MHz)	Temp. (°C)	Depth (cm)	e'	Relative Permittivity (ϵ_r):	38.1918	39.2	-2.57	± 5
2450	22	15	e''	Conductivity (σ):	13.6528	1.80	3.38	± 5

Liquid Check

Ambient temperature: 23 deg. C; Liquid temperature: 22 deg. C

February 01, 2008 09:47 AM

Frequency	e'	e''
2400000000.	38.3732	13.4758
2405000000.	38.3439	13.5067
2410000000.	38.3201	13.5167
2415000000.	38.3012	13.5392
2420000000.	38.2914	13.5490
2425000000.	38.2728	13.5714
2430000000.	38.2504	13.5888
2435000000.	38.2454	13.6002
2440000000.	38.2300	13.6120
2445000000.	38.2160	13.6254
2450000000.	38.1918	13.6528
2455000000.	38.1624	13.6569
2460000000.	38.1454	13.6758
2465000000.	38.1205	13.6848
2470000000.	38.0958	13.6937
2475000000.	38.0604	13.6896
2480000000.	38.0500	13.7087
2485000000.	38.0349	13.7153
2490000000.	38.0241	13.7267
2495000000.	38.0040	13.7760
2500000000.	37.9797	13.7905

The conductivity (σ) can be given as:

$$\sigma = \omega \epsilon_0 e'' = 2 \pi f \epsilon_0 e''$$

where $f = \text{target } f * 10^6$

$$\epsilon_0 = 8.854 * 10^{-12}$$

Simulating Liquid Dielectric Parameter Check Result @ Muscle 2450 MHz

Room Ambient Temperature = 23°C; Relative humidity = 45% Measured by: Jonathan King

Simulating Liquid			Parameters		Measured	Target	Deviation (%)	Limit (%)
f (MHz)	Temp. (°C)	Depth (cm)	e'	Relative Permittivity (ϵ_r):	51.2854	52.7	-2.68	± 5
2450	22	15	e''	Conductivity (σ):	14.2909	1.94780	1.95	-0.11
								± 5

Liquid Check

Ambient temperature: 23 deg. C; Liquid temperature: 22 deg. C

February 01, 2008 09:56 AM

Frequency	e'	e''
2400000000.	51.4353	14.0563
2405000000.	51.4254	14.0879
2410000000.	51.3881	14.1238
2415000000.	51.3751	14.1521
2420000000.	51.3625	14.1654
2425000000.	51.3507	14.2000
2430000000.	51.3459	14.2040
2435000000.	51.3358	14.2183
2440000000.	51.3226	14.2329
2445000000.	51.3025	14.2564
2450000000.	51.2854	14.2909
2455000000.	51.2476	14.2850
2460000000.	51.2289	14.2997
2465000000.	51.1923	14.3001
2470000000.	51.1632	14.3061
2475000000.	51.1509	14.3134
2480000000.	51.1357	14.3358
2485000000.	51.1291	14.3471
2490000000.	51.1080	14.3847
2495000000.	51.1077	14.4295
2500000000.	51.0691	14.4936

The conductivity (σ) can be given as:

$$\sigma = \omega \epsilon_0 \epsilon'' = 2 \pi f \epsilon_0 \epsilon''$$

where $f = \text{target } f * 10^6$

$$\epsilon_0 = 8.854 * 10^{-12}$$

6 SYSTEM PERFORMANCE CHECK

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications of $\pm 10\%$.

System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the SAM twin phantom filled with Head simulating liquid of the following parameters.
- The DASY4 system with an Isotropic E-Field Probe EX3DV3-SN: 3554 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 5 x 5 x 7 fine cube was chosen for cube integration($dx=dy=7.5\text{mm}$; $dz=5\text{mm}$).
For 5 GHz band - Special 8x8x8 fine cube was chosen for cube integration($dx=dy=4.3\text{mm}$; $dz=3\text{mm}$)
- Distance between probe sensors and phantom surface was set to 4 mm.
For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.0mm
- The dipole input power (forward power) was $250\text{ mW} \pm 3\%$.
- The results are normalized to 1 W input power.

IEEE Standard 1528-2003 Recommended Reference Value.

Frequency (MHz)	Distance (mm)	1g SAR [W/kg]	10g SAR [W/kg]
300	15	3.0	2.0
450	15	4.9	3.3
835	15	9.5	6.2
900	15	10.8	6.9
1450	10	29.0	16.0
1800	10	38.1	19.8
1900	10	39.7	20.5
2000	10	41.1	21.1
2450	10	52.4	24.0
3000	10	63.8	25.7

Note: All SAR values normalized to 1 W forward power.

6.1 SYSTEM PERFORMANCE CHECK RESULTS**System Validation Dipole: D2450V2 SN: 706**

Date: February 1, 2008

Ambient Temperature = 23°C; Relative humidity = 45%

Measured by: Jonathan King

Head Simulating Liquid			SAR (mW/g)		Normalized to 1 W	Target	Deviation (%)	Limit (%)
f (MHz)	Temp. (°C)	Depth (cm)	1g	13.90	55.6	52.4	6.11	± 10
2450	22	15	1g	13.90	55.6	52.4	6.11	± 10
			10g	6.18	24.72	24.0	3.00	± 10

7 SAR MEASURMENT PROCEDURE

A summary of the procedure follows:

- a) A measurement of the SAR value at a fixed location is used as a reference value for assessing the power drop of the EUT. The SAR at this point is measured at the start of the test, and then again at the end of the test.
- b) The SAR distribution at the exposed flat section of the flat phantom is measured at a distance of 4 mm from the inner surface of the shell. The area covers the entire dimension of the EUT and the horizontal grid spacing is 15 mm x 15 mm. Based on this data, the area of the maximum absorption is determined by Spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

For 5 GHz band - The SAR distribution at the exposed flat section of the flat phantom is measured at a distance of 2.0 mm from the inner surface of the shell. The area covers the entire dimension of the EUT and the horizontal grid spacing is 10 mm x 10 mm. Based on this data, the area of the maximum absorption is determined by Spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

- c) Around this point, a volume of X=Y= 30 and Z=21 mm is assessed by measuring 5 x 5 x 7 mm points. On the basis of this data set, the spatial peak SAR value is evaluated with the following procedure:

For 5 GHz band - Around this point, a volume of X=Y=24 and Z=20 mm is assessed by measuring 7 x 7 x 9 mm points. On the basis of this data set, the spatial peak SAR value is evaluated with the following procedure:

- (i) The data at the surface are extrapolated, since the centre of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation is based on a least square algorithm. A polynomial of the fourth order is calculated through the points in z-axes. This polynomial is then used to evaluate the points between the surface and the probe tip.
- (ii) The maximum interpolated value is searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g and 10 g) are computed using the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one-dimensional splines with the "Not a knot"- condition (in x, y and z-direction). The volume is integrated with the trapezoidal – algorithm. One thousand points (10 x 10 x 10) are interpolated to calculate the averages.
- (iii) All neighbouring volumes are evaluated until no neighbouring volume with a higher average value is found.
- (iv) The SAR value at the same location as in Step (a) is again measured to evaluate the actual power drift.

7.1 DASY4 SAR MEASURMENT PROCEDURE

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The Minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the Distance of sensor calibration points to probe tip as defined in the probe properties (for example, 1.2 mm for an EX3DV3 probe type).

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4 software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528, EN 50361 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures 5 x 5 x 7 points within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

For 5 GHz band – Same as above except the Zoom Scan measures 7 x 7 x 9 points.

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Step 5: Z-Scan

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation, the extrapolated distance should not be larger than the step size in Z-direction.

8 PROCEDURE USED TO ESTABLISH TEST SIGNAL

The following procedures had been used to prepare the EUT for the SAR test.

The cable assembly insertion loss of 11dB (including 10 dB attenuator and 1dB connectors) was entered as an offset in the power meter to allow for direct reading of power.

802.11b

Channel	Frequency (MHz)	Average Power (dBm)
Low	2412	15.0
Middle	2437	15.1
High	2462	15.0

802.11g

Channel	Frequency (MHz)	Average Power (dBm)
Low	2412	13.5
Middle	2437	13.2
High	2462	13.2

9 SAR MEASURMENT RESULTS


9.1 HEAD POSITIONS - LEFT HAND SIDE (LHS)

					
Touch Position		Tilt (15°) Position			
Test Position	Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated ¹⁾ SAR 1g (mW/g)
802.11b					
Touch	1	2412.0	0.456	0.000	0.456
	6	2437.0	0.467	-0.123	0.480
	11	2462.0	0.413	-0.143	0.427
Tilt (15°)	1	2412.0			
	6	2437.0	0.233	0.000	0.233
	11	2462.0			
802.11g					
Touch	1	2412.0			
	6	2437.0	0.230	-0.055	0.233
	11	2462.0			

Notes:

- 1) The exact method of extrapolation is Measured SAR $\times 10^{(-\text{drift}/10)}$. The SAR reported at the end of the measurement process by the DASY4 system can be scaled up by the Power drift to determine the SAR at the beginning of the measurement process.
- 2) The SAR measured at the middle channel for this configuration is at least 3 dB lower (0.8 mW/g) than SAR limit (1.6 mW/g), thus testing at low & high channel is optional.
- 3) Please see attachments for the detailed measurement data and plots showing the maximum SAR location of the EUT.
- 4) The battery was fully charged in accordance with manufacture's instructions prior to SAR measurements.
- 5) **G mode tilt position was skipped due to significantly lower power and the lower SAR value from the touch position.**



9.2 HEAD POSITIONS - RIGHT HAND SIDE (RHS)

					
Touch Position		Tilt (15°) Position			
Test Position	Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated ¹⁾ SAR 1g (mW/g)
802.11b					
Touch	1 6 11	2412.0 2437.0 2462.0	0.298	0.000	0.298
Tilt (15°)	1 6 11	2412.0 2437.0 2462.0	0.247	-0.150	0.256
802.11g					
Touch	1 6 11	2412.0 2437.0 2462.0	0.156	0.000	0.156

Notes:

- 1) The exact method of extrapolation is Measured SAR $\times 10^{(-\text{drift}/10)}$. The SAR reported at the end of the measurement process by the DASY4 system can be scaled up by the Power drift to determine the SAR at the beginning of the measurement process.
- 2) The SAR measured at the middle channel for this configuration is at least 3 dB lower (0.8 mW/g) than SAR limit (1.6 mW/g), thus testing at low & high channel is optional.
- 3) Please see attachments for the detailed measurement data and plots showing the maximum SAR location of the EUT.
- 4) The battery was fully charged in accordance with manufacturer's instructions prior to SAR measurements.
- 5) G mode tilt position was skipped due to significantly lower output power and the lower SAR value from the touch position.

9.3 BODY-WORN POSITION – EUT TESTED WITH 15MM SEPARATION DISTANCE

					
LCD Facing Up		LCD Facing Down			
Test Position	Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated ¹⁾ SAR 1g (mW/g)
802.11b					
Facing Up	1	2412.0	0.058	0.000	0.058
	6	2437.0			
	11	2462.0			
Facing Down	1	2412.0	0.059	0.000	0.059
	6	2437.0	0.077	-0.031	0.077
	11	2462.0	0.079	-0.008	0.080

Notes:

- 1) The exact method of extrapolation is Measured SAR $\times 10^{(-\text{drift}/10)}$. The SAR reported at the end of the measurement process by the DASY4 system can be scaled up by the Power drift to determine the SAR at the beginning of the measurement process.
- 2) The SAR measured at the middle channel for this configuration is at least 3 dB lower (0.8 mW/g) than SAR limit (1.6 mW/g), thus testing at low & high channel is optional.
- 3) Please see attachments for the detailed measurement data and plots showing the maximum SAR location of the EUT.
- 4) The battery was fully charged in accordance with manufacturer's instructions prior to SAR measurements.
- 5) **G mode positions were skipped due to significantly lower output power and the lower SAR value from the b mode positions.**

10 MEASURMENT UNCERTAINTY

10.1 MEASURMENT UNCERTAINTY FOR 300 MHz – 3000 MHz

Uncertainty component	Tol. (±%)	Probe Dist.	Div.	Ci (1g)	Ci (10g)	Std. Unc.(±%)						
						Ui (1g)	Ui(10g)					
Measurement System												
Probe Calibration	4.80	N	1	1	1	4.80	4.80					
Axial Isotropy	4.70	R	1.732	0.707	0.707	1.92	1.92					
Hemispherical Isotropy	9.60	R	1.732	0.707	0.707	3.92	3.92					
Boundary Effects	1.00	R	1.732	1	1	0.58	0.58					
Linearity	4.70	R	1.732	1	1	2.71	2.71					
System Detection Limits	1.00	R	1.732	1	1	0.58	0.58					
Readout Electronics	1.00	N	1	1	1	1.00	1.00					
Response Time	0.80	R	1.732	1	1	0.46	0.46					
Integration Time	2.60	R	1.732	1	1	1.50	1.50					
RF Ambient Conditions - Noise	1.59	R	1.732	1	1	0.92	0.92					
RF Ambient Conditions - Reflections	0.00	R	1.732	1	1	0.00	0.00					
Probe Positioner Mechanical Tolerance	0.40	R	1.732	1	1	0.23	0.23					
Probe Positioning With Respect to Phantom Shell	2.90	R	1.732	1	1	1.67	1.67					
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	3.90	R	1.732	1	1	2.25	2.25					
Test sample Related												
Test Sample Positioning	1.10	N	1	1	1	1.10	1.10					
Device Holder Uncertainty	3.60	N	1	1	1	3.60	3.60					
Power and SAR Drift Measurement	5.00	R	1.732	1	1	2.89	2.89					
Phantom and Tissue Parameters												
Phantom Uncertainty	4.00	R	1.732	1	1	2.31	2.31					
Liquid Conductivity - Target	5.00	R	1.732	0.64	0.43	1.85	1.24					
Liquid Conductivity - Meas.	8.60	N	1	0.64	0.43	5.50	3.70					
Liquid Permittivity - Target	5.00	R	1.732	0.6	0.49	1.73	1.41					
Liquid Permittivity - Meas.	3.30	N	1	0.6	0.49	1.98	1.62					
Combined Standard Uncertainty	RSS					11.44	10.49					
Expanded Uncertainty (95% Confidence Interval)	K=2					22.87	20.98					
Notes for table												
1. Tol. - tolerance in influence quality												
2. N - Nominal												
3. R - Rectangular												
4. Div. - Divisor used to obtain standard uncertainty												
5. Ci - is the sensitivity coefficient												

11 EQUIPMENT LIST AND CALIBRATION

Name of Equipment	Manufacturer	Type/Model	Serial Number	Cal. Due date		
				MM	DD	Year
Robot - Six Axes	Stäubli	RX90BL	N/A			N/A
Robot Remote Control	Stäubli	CS7MB	3403-91535			N/A
DASY4 Measurement Server	SPEAG	SEUMS001BA	1041			N/A
Probe Alignment Unit	SPEAG	LB (V2)	261			N/A
SAM Phantom (SAM1)	SPEAG	QD000P40CA	1185			N/A
SAM Phantom (SAM2)	SPEAG	QD000P40CA	1050			N/A
Oval Flat Phantom (ELI 4.0)	SPEAG	QD OVA001 B	1003			N/A
Electronic Probe kit	HP	85070C	N/A			N/A
S-Parameter Network Analyzer	Agilent	8753ES-6	US39173569	2	14	2008
E-Field Probe	SPEAG	EX3DV4	3554	4	24	2008
Thermometer	ERTCO	639-1S	1718	8	30	2008
Data Acquisition Electronics	SPEAG	DAE3 V1	500	11	16	2008
System Validation Dipole	SPEAG	D2450V2	706	4	27	2008
Signal Generator	R&S	SMP 04	DE34210	2	16	2009
Power Meter	Giga-tronics	8651A	8651404	4	3	2008
Power Sensor	Giga-tronics	80701A	1834588	4	17	2008
Amplifier	Mini-Circuits	ZHL-42W	D072701-5			N/A
Simulating Liquid	CCS	H2450	N/A			Within 24 hrs of first test
Simulating Liquid	CCS	M2450	N/A			Within 24 hrs of first test

12 PHOTOS

EUT



EUT with Headset Adaptor**Internal Photo**

13 ATTACHMENTS

No.	Contents	No. Of Pages
1	System Performance Check Plots	2
2	SAR Test Plots	14
3	Certificate of E-Field Probe - EX3DV4SN3554	10
4	Certificate of System Validation Dipole - D2450 SN:706	9

END OF REPORT