



FCC CFR47 PART 15 SUBPART C  
INDUSTRY CANADA RSS-210 ISSUE 7  
CERTIFICATION TEST REPORT  
FOR

BLUETOOTH HUB ADAPTER

MODEL NUMBER: LO(BHA)B, LO(BHA)U\*

FCC ID: UI3LOBHA

IC: 140L-LOBHA

REPORT NUMBER : 07J11537-1, REVISION A

ISSUE DATE : JANUARY 23, 2008

*Prepared for*

NEC INFRONTIA, INC.

6365 NORTH STATE HIGHWAY 161

IRVING, TEXAS 75039-2402, USA

*Prepared by*

COMPLIANCE CERTIFICATION SERVICES

47173 BENICIA STREET

FREMONT, CA 94538, U.S.A.

TEL: (510) 771-1000

FAX: (510) 661-0888

\*Details of model(s) and model differences are listed in the body of this report

**NVLAP**<sup>®</sup>

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	1/14/08	Initial Issue	T. Chan
A	01/23/08	Revised IC number	T. Hong

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>5</b>
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>6</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	6
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	6
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>7</b>
5.1. <i>DESCRIPTION OF EUT.....</i>	7
5.2. <i>DESCRIPTION OF MODEL DIFFERENCES.....</i>	7
5.3. <i>MAXIMUM OUTPUT POWER.....</i>	7
5.4. <i>DESCRIPTION OF AVAILABLE ANTENNAS.....</i>	7
5.5. <i>SOFTWARE AND FIRMWARE.....</i>	7
5.6. <i>WORST-CASE CONFIGURATION AND MODE .....</i>	8
5.7. <i>DESCRIPTION OF TEST SETUP.....</i>	9
<b>6. TEST AND MEASUREMENT EQUIPMENT .....</b>	<b>11</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>12</b>
7.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	12
7.1.1. <i>20 dB AND 99% BANDWIDTH.....</i>	12
7.1.2. <i>HOPPING FREQUENCY SEPARATION .....</i>	16
7.1.3. <i>NUMBER OF HOPPING CHANNELS.....</i>	18
7.1.4. <i>AVERAGE TIME OF OCCUPANCY.....</i>	23
7.1.5. <i>OUTPUT POWER .....</i>	30
7.1.6. <i>AVERAGE POWER .....</i>	34
7.1.7. <i>CONDUCTED SPURIOUS EMISSIONS.....</i>	35
<b>8. RADIATED TEST RESULTS .....</b>	<b>44</b>
8.1. <i>LIMITS AND PROCEDURE .....</i>	44
8.2. <i>TRANSMITTER ABOVE 1 GHz .....</i>	45
8.2.1. <i>BASIC DATA RATE GFSK MODULATION.....</i>	45
8.3. <i>RECEIVER ABOVE 1 GHz .....</i>	54
8.4. <i>WORST-CASE BELOW 1 GHz.....</i>	55

---

<b>9. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>59</b>
<b>10. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>63</b>
<b>11. SETUP PHOTOS .....</b>	<b>67</b>

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** NEC INFRONTIA, INC.  
6365 NORTH STATE HIGHWAY 161  
IRVING, TEXAS 75039-2402, USA

**EUT DESCRIPTION:** BLUETOOTH HUB ADAPTER

**MODEL:** LO(BHA)B (tested), LO(BHA)U

**SERIAL NUMBER:** 2483

**DATE TESTED:** JANUARY 11 – 12, 2008

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	No Non-Compliance Noted
RSS-210 Issue 7 Annex 8 and RSS-GEN Issue 2	No Non-Compliance Noted

Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:



---

THU CHAN  
EMC SUPERVISOR  
COMPLIANCE CERTIFICATION SERVICES

Tested By:



---

YOBI ZHOU  
EMC ENGINEER  
COMPLIANCE CERTIFICATION SERVICES

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2003, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 2, and RSS-210 Issue 7.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Power Line Conducted Emission	+/- 2.3 dB
Radiated Emission	+/- 3.4 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is a Bluetooth HUB Adapter.

The radio module is manufactured by JEPICO, model PQUP1013YA.

### 5.2. DESCRIPTION OF MODEL DIFFERENCES

The only difference between LO(BHA)B and LO(BHA)U is the model name. There is no change in radio frequency, RF output power, radio frequency circuitry, Antenna, PCB and functional capabilities.

LO(BHA)B was the model tested.

### 5.3. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	Basic GFSK	12.16	16.44

### 5.4. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an Chip antenna, with a maximum gain of 2.15 dBi.

### 5.5. SOFTWARE AND FIRMWARE

The EUT driver and Utility software installed in the host support equipment during testing was Tera Term Pro, rev. V0.30

## 5.6. WORST-CASE CONFIGURATION AND MODE

EUT has been evaluated at X, and Y-axis. The highest measured output power was at Y-Axis.

## 5.7. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	NEC	VA80J	NA	DoC
AC Adapter	NEC	PA-1600-01	1727642LP	DoC
AC Adapter	NEC	A42406	NG-150642	NA
Jig	NEC	NA	NA	NA


### I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	2	US 115V	Un-shielded	2m	NA
2	DC	2	DC	Un-shielded	2m	Ferrite on EUT's end
3	USB	1	DB9 to USB	Un-shielded	2m	NA
4	Jig	1	10 Pins	Un-shielded	0.1m	NA

### TEST SETUP

The EUT is connected to a laptop and activated through a Jig via a serial to USB cable. The EUT was tested as a standalone unit.

**SETUP DIAGRAM FOR TESTS**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST					
Description	Manufacturer	Model	Asset	Cal Date	Cal Due
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/14/2006	3/18/2008
Antenna, Bilog, 2 GHz	Sunol Sciences	JB1	C01011	10/13/2007	9/2/2008
EMI Receiver, 2.9 GHz	Agilent / HP	8542E	C00957	2/6/2007	6/12/2008
RF Filter Section, 2.9 GHz	Agilent / HP	85420E	C00958	2/6/2007	6/12/2008
Antenna, Horn, 18 GHz	ETS	3117	C01005	4/15/2007	4/15/2008
Preamplifier, 1300 MHz	Agilent / HP	8447D	NA	5/9/2007	5/9/2008
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01063	10/3/2006	9/27/2008
EMI Test Receiver, 30 MHz	R & S	ESHS 20	N02396	1/27/2007	1/27/2008
LISN, 30 MHz	FCC	LISN-50/250-25-2	N02625	9/15/2007	9/15/2008
Peak / Average Power Sensor	Agilent	E9327A	C00964	2/14/2006	127/2008
Peak Power Meter	Agilent / HP	E4416A	C00963	2/14/2006	12/7/2008

## 7. ANTENNA PORT TEST RESULTS

### 7.1. BASIC DATA RATE GFSK MODULATION

#### 7.1.1. 20 dB AND 99% BANDWIDTH

##### LIMIT

None; for reporting purposes only.


##### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to  $\geq 1\%$  of the 20 dB bandwidth. The VBW is set to  $\geq$  RBW. The sweep time is coupled.


##### RESULTS

Channel	Frequency (MHz)	20 dB Bandwidth (kHz)	99% Bandwidth (kHz)
Low	2402	941.892	865.4887
Middle	2441	940.433	863.7827
High	2480	940.721	861.3446

**20 dB AND 99% BANDWIDTH**







### 7.1.2. HOPPING FREQUENCY SEPARATION

#### LIMIT

FCC §15.247 (a) (1)

IC RSS-210 A8.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 100 kHz. The sweep time is coupled.

#### RESULTS

## HOPPING FREQUENCY SEPARATION



### 7.1.3. NUMBER OF HOPPING CHANNELS

#### LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


#### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


#### RESULTS


79 Channels observed.

**NUMBER OF HOPPING CHANNELS**









#### 7.1.4. AVERAGE TIME OF OCCUPANCY

##### LIMIT

FCC §15.247 (a) (1) (iii)

IC RSS-210 A8.1 (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

##### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 31.6 second period (79 channels \* 0.4 s) is equal to  $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{pulse width}$ .


## DH1 RESULTS

Time Of Occupancy = 10 \* 31 pulses \* 0.4233 msec = 131.223 msec

### PULSE WIDTH




**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD**




## DH3 RESULTS

Time Of Occupancy =  $10 * 19$  pulses \* 1.675 msec = 318.25 msec

### PULSE WIDTH




**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD**




## DH5 RESULTS

Time Of Occupancy =  $10 * 12 \text{ pulses} * 2.933 \text{ msec} = 351.96 \text{ msec}$

### PULSE WIDTH



**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD**



### 7.1.5. OUTPUT POWER

#### LIMIT

§15.247 (b) (1)

RSS-210 Issue 7 Clause A8.4

The maximum antenna gain is less than 6 dBi, therefore the limit is 30 dBm.


#### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.


#### RESULTS

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	11.01	30	-18.99
Middle	2441	12.16	30	-17.84
High	2480	10.90	30	-19.10

OUTPUT POWER







### 7.1.6. AVERAGE POWER

#### LIMIT

None; for reporting purposes only.

#### TEST PROCEDURE

The transmitter output is connected to a power meter.

#### RESULTS

The cable assembly insertion loss of 10.8 dB (including 10 dB pad and 0.8 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	9.50
Middle	2441	10.07
High	2480	8.85

### 7.1.7. CONDUCTED SPURIOUS EMISSIONS

#### LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

Limit = -20 dBc

#### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


#### RESULTS


**SPURIOUS EMISSIONS, LOW CHANNEL**







**SPURIOUS EMISSIONS, MID CHANNEL**







**SPURIOUS EMISSIONS, HIGH CHANNEL**





**SPURIOUS BANDEdge EMISSIONS WITH HOPPING ON**





## 8. RADIATED TEST RESULTS

### 8.1. LIMITS AND PROCEDURE

#### LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

#### TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

## 8.2. TRANSMITTER ABOVE 1 GHz


### 8.2.1. BASIC DATA RATE GFSK MODULATION


#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)







**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**







**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**





**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**





## HARMONICS AND SPURIOUS EMISSIONS

High Frequency Measurement Compliance Certification Services, Fremont 5m Chamber															
Company: NEC Engineering Project #: 07U11537 Date: 01.11.2008 Test Engineer: Yobi Zhou Configuration: EUT with Laptop Mode: Tx On															
Test Equipment:															
Horn 1-18GHz		Pre-amplifier 1-26GHz		Pre-amplifier 26-40GHz		Horn > 18GHz		Limit							
T60; S/N: 2238 @3m		T34 HP 8449B						FCC 15.205							
Hi Frequency Cables															
2 foot cable		3 foot cable		12 foot cable		HPF		Reject Filter		<b>Peak Measurements</b> RBW=VBW=1MHz <b>Average Measurements</b> RBW=1MHz ; VBW=10Hz					
Thanh 177079008				C-5m Chamber				R_001							
f GHz	Dist (m)	Read Pl dBuV	Read Avg dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
Low Chan															
4.804	3.0	57.4	49.8	33.7	0.6	-34.8	0.0	0.0	56.8	49.2	74	54	-17.2	-4.8	H
12.010	3.0	42.6	30.8	38.5	0.7	-32.5	0.0	0.0	49.3	37.4	74	54	-24.7	-16.6	H
4.804	3.0	57.8	50.3	33.7	0.6	-34.8	0.0	0.0	57.1	49.7	74	54	-16.9	-4.3	V
12.010	3.0	43.3	31.7	38.5	0.7	-32.5	0.0	0.0	50.0	38.4	74	54	-24.0	-15.6	V
Mid Chan															
4.882	3.0	54.8	47.4	33.7	0.6	-34.8	0.0	0.0	54.2	46.8	74	54	-19.8	-7.2	H
7.323	3.0	55.7	47.6	36.7	0.6	-34.1	0.0	0.0	58.9	50.8	74	54	-15.1	-3.2	H
12.205	3.0	43.5	31.8	29.6	0.7	-32.5	0.0	0.0	41.3	29.6	74	54	-32.7	-24.4	H
4.882	3.0	54.7	47.1	33.7	0.6	-34.8	0.0	0.0	54.1	46.6	74	54	-19.9	-7.4	V
7.323	3.0	53.8	46.0	36.7	0.6	-34.1	0.0	0.0	57.0	49.2	74	54	-17.0	-4.8	V
12.205	3.0	41.4	29.7	29.6	0.7	-32.5	0.0	0.0	39.2	27.5	74	54	-34.8	-26.5	V
High Chan															
4.960	3.0	52.9	45.5	33.8	0.6	-34.8	0.0	0.0	52.5	45.0	74	54	-21.5	-9.0	H
7.440	3.0	54.8	46.8	36.8	0.6	-34.1	0.0	0.0	58.1	50.1	74	54	-15.9	-3.9	H
4.960	3.0	51.3	44.4	33.8	0.6	-34.8	0.0	0.0	50.9	44.0	74	54	-23.1	-10.0	V
7.440	3.0	54.7	46.7	36.8	0.6	-34.1	0.0	0.0	58.0	50.0	74	54	-16.0	-4.0	V
Rev. 4.12.7															
f Measurement Frequency Dist Distance to Antenna Read Analyzer Reading AF Antenna Factor CL Cable Loss				Amp Preamp Gain D Corr Distance Correct to 3 meters Avg Average Field Strength @ 3 m Peak Calculated Peak Field Strength HPF High Pass Filter				Avg Lim Average Field Strength Limit Pk Lim Peak Field Strength Limit Avg Mar Margin vs. Average Limit Pk Mar Margin vs. Peak Limit							

### 8.3. RECEIVER ABOVE 1 GHz

High Frequency Measurement Compliance Certification Services, Fremont 5m Chamber															
Company: NEC Engineering Project #: 07U11537 Date: 01.11.2008 Test Engineer: Yobi Zhou Configuration: EUT with Laptop Mode: Rx (Mid Chan) On															
<u>Test Equipment:</u>															
Horn 1-18GHz			Pre-amplifier 1-26GHz			Pre-amplifier 26-40GHz			Horn > 18GHz			Limit			
T60; S/N: 2238 @3m			T34 HP 8449B									FCC 15.209			
Hi Frequency Cables 2 foot cable      3 foot cable      12 foot cable Thanh 177079008           C-5m Chamber															
HPF      Reject Filter      Peak Measurements RBW=VBW=1MHz      R_001      RBW=1MHz ; VBW=10Hz Average Measurements															
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF	CL	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
Mid Chan															
1.293	3.0	54.9	38.2	27.2	0.3	-37.9	0.0	0.0	44.6	27.8	74	54	-29.4	-26.2	V
1.593	3.0	57.5	37.0	28.0	0.4	-37.4	0.0	0.0	48.5	27.9	74	54	-25.5	-26.1	V
1.890	3.0	52.1	36.1	28.8	0.4	-37.0	0.0	0.0	44.3	28.3	74	54	-29.7	-25.7	V
1.297	3.0	53.0	38.0	27.2	0.3	-37.8	0.0	0.0	42.7	27.7	74	54	-31.3	-26.3	H
1.493	3.0	46.4	33.8	27.7	0.4	-37.6	0.0	0.0	36.9	24.3	74	54	-37.1	-29.7	H
1.893	3.0	47.3	33.9	28.8	0.4	-37.0	0.0	0.0	39.5	26.1	74	54	-34.5	-27.9	H
Rev. 4.12.7															
f      Measurement Frequency Dist      Distance to Antenna Read      Analyzer Reading AF      Antenna Factor CL      Cable Loss					Amp      Preamp Gain D Corr      Distance Correct to 3 meters Avg      Average Field Strength @ 3 m Peak      Calculated Peak Field Strength HPF      High Pass Filter					Avg Lim      Average Field Strength Limit Pk Lim      Peak Field Strength Limit Avg Mar      Margin vs. Average Limit Pk Mar      Margin vs. Peak Limit					

## 8.4. WORST-CASE BELOW 1 GHz


### SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)

#### HORIZONTAL PLOT



Compliance Certification Services  
47173 Benicia Street  
Fremont, CA 94538  
Tel: (510) 771-1000  
Fax: (510) 661-0888

Data#: 4 File#: 07J11537.EMI Date: 01-11-2008 Time: 15:48:34



Trace: 3

Ref Trace:

Condition: FCC CLASS-B HORIZONTAL  
Test Operator: Yobi Zhou  
Project #: 07J11537  
Company : NEC Engineering  
Config : EUT Only  
Mode : Tx Worst Case  
Target : FCC Class B

HORIZONTAL DATA

Page: 1

		Read		Limit	Over	
Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	148.340	43.04	-13.74	29.30	43.50	-14.20 Peak
2	308.390	43.60	-12.04	31.56	46.00	-14.44 Peak
3	344.280	44.72	-11.15	33.57	46.00	-12.43 Peak
4	570.290	44.60	-5.96	38.64	46.00	-7.36 Peak
5	609.090	42.56	-5.21	37.35	46.00	-8.65 Peak
6	647.890	41.01	-4.45	36.56	46.00	-9.44 Peak
7	807.940	34.67	-1.99	32.68	46.00	-13.32 Peak


**SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)**

VERTICAL PLOT



Compliance Certification Services  
47173 Benicia Street  
Fremont, CA 94538  
Tel: (510) 771-1000  
Fax: (510) 661-0888

Data#: 2 File#: 07J11537.EMI Date: 01-11-2008 Time: 15:36:02



Trace: 1

Ref Trace:

Condition: FCC CLASS-B VERTICAL  
Test Operator: Yobi Zhou  
Project #: 07J11537  
Company: NEC Engineering  
Config: EUT Only  
Mode: Tx Worst Case  
Target: FCC Class B

VERTICAL DATA

Page: 1

		Read		Limit	Over	
Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	58.130	51.42	-19.59	31.83	40.00	-8.17 Peak
2	225.940	46.22	-14.98	31.24	46.00	-14.76 Peak
3	487.840	42.61	-7.60	35.01	46.00	-10.99 Peak
4	570.290	41.28	-5.96	35.32	46.00	-10.68 Peak
5	609.090	38.28	-5.21	33.07	46.00	-12.93 Peak
6	647.890	38.59	-4.45	34.14	46.00	-11.86 Peak

## 9. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.


Line conducted data is recorded for both NEUTRAL and HOT lines.

### RESULTS


**6 WORST EMISSIONS**

CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq. (MHz)	Reading			Closs (dB)	Limit QP	EN_B AV	Margin		Remark L1 / L2
	PK (dBuV)	QP (dBuV)	AV (dBuV)				QP (dB)	AV (dB)	
0.20	51.88	--	14.28	0.00	63.69	53.69	-11.81	-39.41	L1
0.36	48.52	--	10.37	0.00	58.66	48.66	-10.14	-38.29	L1
0.48	47.10	--	8.72	0.00	56.41	46.41	-9.31	-37.69	L1
0.20	51.23	--	14.82	0.00	63.53	53.53	-12.30	-38.71	L2
0.30	48.46	--	11.95	0.00	60.19	50.19	-11.73	-38.24	L2
0.41	46.50	--	10.26	0.00	57.73	47.73	-11.23	-37.47	L2
6 Worst Data									

**LINE 1 RESULTS**



## LINE 2 RESULTS



## 10. MAXIMUM PERMISSIBLE EXPOSURE

### FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

### **IC RULES**

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

**Table 5**  
**Exposure Limits for Persons Not Classed As RF and Microwave Exposed Workers (Including the General Public)**

1 Frequency (MHz)	2 Electric Field Strength; rms (V/m)	3 Magnetic Field Strength; rms (A/m)	4 Power Density (W/m <sup>2</sup> )	5 Averaging Time (min)
0.003–1	280	2.19		6
1–10	280/f	2.19/f		6
10–30	28	2.19/f		6
30–300	28	0.073	2*	6
300–1 500	$1.585f^{0.5}$	$0.0042f^{0.5}$	$f/150$	6
1 500–15 000	61.4	0.163	10	6
15 000–150 000	61.4	0.163	10	$616\ 000/f^{1.2}$
150 000–300 000	$0.158f^{0.5}$	$4.21 \times 10^{-4}f^{0.5}$	$6.67 \times 10^{-5}f$	$616\ 000/f^{1.2}$

\* Power density limit is applicable at frequencies greater than 100 MHz.

**Notes:** 1. Frequency,  $f$ , is in MHz.  
2. A power density of 10 W/m<sup>2</sup> is equivalent to 1 mW/cm<sup>2</sup>.  
3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla ( $\mu$ T) or 12.57 milligauss (mG).

## CALCULATIONS

Given

$$E = \sqrt{(30 * P * G) / d}$$

and

$$S = E^2 / 3770$$

where

E = Field Strength in Volts/meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts/square centimeter

Combining equations, rearranging the terms to express the distance as a function of the remaining variables, changing to units of Power to mW and Distance to cm, and substituting the logarithmic form of power and gain yields:

$$d = 0.282 * 10^{((P + G) / 20) / \sqrt{S}}$$

where

d = MPE distance in cm

P = Power in dBm

G = Antenna Gain in dBi

S = Power Density Limit in mW/cm<sup>2</sup>

Rearranging terms to calculate the power density at a specific distance yields

$$S = 0.0795 * 10^{((P + G) / 10) / (d^2)}$$

The power density in units of mW/cm<sup>2</sup> is converted to units of W/m<sup>2</sup> by multiplying by a factor of 10.

**LIMITS**

From FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm<sup>2</sup>


From IC Safety Code 6, Section 2.2 Table 5 Column 4, S = 10 W/m<sup>2</sup>

**RESULTS**

Mode	Band	MPE Distance (cm)	Output Power (dBm)	Antenna Gain (dBi)	FCC Power Density (mW/cm <sup>2</sup> )	IC Power Density (W/m <sup>2</sup> )
Bluetooth	2.4 GHz	20.0	12.16	2.15	0.005	0.05


## 11. SETUP PHOTOS

### ANTENNA PORT CONDUCTED RF MEASUREMENT SETUP




**RADIATED RF MEASUREMENT SETUP FOR DESKTOP & WALL MOUNT CONFIGURATIONS**

X-AXIS FRONT PHOTO




X-AXIS BACK PHOTO



Y-AXIS FRONT PHOTO



Y-AXIS BACK PHOTO



**POWERLINE CONDUCTED EMISSIONS MEASUREMENT SETUP**

LINE CONDUCTED FRONT PHOTO



LINE CONDUCTED BACK PHOTO



**END OF REPORT**