

FCC Part 15.247 Transmitter Certification

Direct Sequence Spread Spectrum Transmitter

Test Report

FCC ID: UID-WRMTM5

FCC Rule Part: 15.247

ACS Report Number: 06-0200-15C

Manufacturer: Sercomm
Applicant: ARRIS International, Inc.

Model: TM552 WRM

RF Exposure Information

General Information:

Manufacturer: SerComm
 Applicant: ARRIS International, Inc.
 ACS Project: 06-0200
 FCC ID: UID-WRMTM5
 Device Category: Mobile
 Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Dipole
 Antenna Gain: 1.8 dBi
 Transmitter Conducted Power: 21.56dBm
 Maximum System EIRP: 23.36dBm
 Operating Configuration: Mobile
 Exposure Conditions: Greater than 20 centimeters

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm²)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)
2462	21.56	1.00	143.22	1.8	1.514	20	0.043

Installation Guidelines

The installation manual contains the following text advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

“RF Exposure (Intentional Radiators Only)

In accordance with FCC requirements of human exposure to radiofrequency fields, the radiating element shall be installed such that a minimum separation distance of 20cm is maintained from the general population.”

Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.