




Test Report No: 23A0721R-RFUSV17S-A

RF EXPOSURE EVALUATION DECLARATION

Product Name	DOCSIS Gateway
Brand Name	ARRIS
Model No.	G20
FCC ID	UIDG20
Applicant's Name / Address	ARRIS 3871 Lakefield Drive Suite 300 SUWANEE Georgia United States 30024
Manufacturer's Name / Address	ARRIS 3871 Lakefield Drive Suite 300 SUWANEE Georgia United States 30024
Test Method Requested, Standard	FCC CFR Title 47 Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.
Verdict Summary	IN COMPLIANCE
Documented By	Hailey Peng. Hailey Peng
Approved By	Rueyyan Lin
Date of Receipt	Oct. 27, 2023
Date of Issue	Dec. 18, 2023
Report Version	V1.0

TEL: +886-3-582-8001 Page Number

1 of 7 FAX: +886-3-582-8958 Issued Date Dec. 18, 2023 Report Version V1.0





INDEX

		page
Compe	etences and Guarantees	3
Genera	al Conditions	3
Revisio	on History	4
1.	General Information	5
1.1.	EUT Description	5
1.2.	Testing Location Information	5
2.	RF Exposure Evaluation	6
2.1.	Test Limit	
2.2.	Test Result of RF Exposure Evaluation	7

2 of 7

V1.0

Dec. 18, 2023



Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General Conditions

- 1. The test results relate only to the samples tested.
- 2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
- 3. This report must not be used to claim product endorsement by TAF or any agency of the government.
- 4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
- Measurement uncertainties evaluated for each testing system and associated connections are given here to
 provide the system information for reference. Compliance determinations do not take into account
 measurement uncertainties for each testing system, but are based on the results of the compliance
 measurement.

TEL: +886-3-582-8001 Page Number : 3 of 7
FAX: +886-3-582-8958 Issued Date : Dec. 18, 2023

Report Version : V1.0



Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	Dec. 18, 2023

TEL: +886-3-582-8001 Page Number : 4 of 7
FAX: +886-3-582-8958 Issued Date : Dec. 18, 2023

Report Version : V1.0



1. General Information

1.1. EUT Description

RF General Information						
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type			
WiFi 2.4 GHz	2400 ~ 2483.5	2412 ~ 2462	802.11b: DSSS 802.11g/n/ac: OFDM 802.11ax: OFDMA			
WiFi 5 GHz	5150 ~ 5250 5250 ~ 5350 5470 ~ 5725 5725 ~ 5850	5180 ~ 5240 5260 ~ 5320 5500 ~ 5720 5745 ~ 5825	802.11a/n/ac: OFDM 802.11ax: OFDMA			

Note: The above EUT information is declared by the manufacturer.

1.2. Testing Location Information

	Testing Location Information					
Tes	Test Laboratory : DEKRA Testing and Certification Co., Ltd.					
	1	ADD: No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.				
	(TAF: 3024)	TEL: +886-3-582-8001				
	2	ADD: No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.				
	(TAF: 3024)	TEL: +886-3-582-8001 FAX: +886-3-582-8958				
	Test site number for address 1 includes HC-SR02. Test site number for address 2 includes HC-CB02, HC-CB03, HC-CB04, HC-SR10 and HC-SR12.					

TEL: +886-3-582-8001 Page Number : 5 of 7
FAX: +886-3-582-8958 Issued Date : Dec. 18, 2023

Report Version : V1.0



2. RF Exposure Evaluation

2.1. Test Limit

(A) Test Limit for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ², H ² or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Test Limit for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ², H ² or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz; *Plane-wave equivalent power density

Power Density (S) is calculated by the following formula:

 $S=(P*G)/4\pi R^2$

where:

S = power density (in appropriate units, e.g. mW/ cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

 $\pi=3.1416$

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

TEL: +886-3-582-8001 Page Number : 6 of 7
FAX: +886-3-582-8958 Issued Date : Dec. 18, 2023
Report Version : V1.0



2.2. **Test Result of RF Exposure Evaluation**

Exposure Environment: General Population / Uncontrolled Exposure

Evaluation Mode	Maximum Conducted Output Power (dBm)	Antenna Gain (dBi)	E.I.R.P (dBm)	Tolerance (dB)	Tune-up E.I.R.P (dBm)	Tune-up E.I.R.P (mW)	Power Density (mW/cm²)	Limit (mW/cm²)
WiFi 2.4 GHz	25.021	2.03	27.051	0.50	27.551	568.984	0.113	1.000
WiFi 5 GHz Band 1	24.757	3.13	27.887	0.50	28.387	689.763	0.137	1.000
WiFi 5 GHz Band 2	23.865	3.13	26.995	0.50	27.495	561.694	0.112	1.000
WiFi 5 GHz Band 3	23.977	3.13	27.107	0.50	27.607	576.368	0.115	1.000
WiFi 5 GHz Band 4	25.195	3.13	28.325	0.50	28.825	762.957	0.152	1.000

Co-location

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WiFi 2.4 GHz + WiFi 5 GHz = 0.113 + 0.152 = 0.265, therefore the maximum calculations of above situations are less than the "1" limit.

Note:

- 1. Distance (cm): 20 for Maximum Permissible Exposure.
- The above EUT information is declared by the manufacturer.
- 3. The results are based on the maximum power.

TEL: +886-3-582-8001 Page Number 7 of 7 FAX: +886-3-582-8958 Issued Date Dec. 18, 2023

Report Version V1.0