



Maximum Permissible Exposure

Equipment : Wireless Cable Modem Gateways
Brand Name : ARRIS
Model No. : SBG6580-2
FCC ID : UIDSBG6580-2
Standard : ANSI/IEEE C95.1
Applicant : **ARRIS GROUP INC**
Manufacturer : 3871 LAKEFIELD DRIVE, SUWANEE, GA 30024,
United States

The product sample received on Dec. 28, 2015 and completely tested on Jan. 12, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI/IEEE C95.1 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Kevin Liang / Assistant Manager





Table of Contents

1	HUMAN EXPOSURE ASSESSMENT	4
1.1	Maximum Permissible Exposure	4

1 Human Exposure Assessment

1.1 Maximum Permissible Exposure

1.1.1 Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30
Note 1: f = frequency in MHz ; *Plane-wave equivalent power density				
Note 2: For the applicable limit, see FCC 1.1310				

1.1.2 MPE Calculation Method

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



1.1.3 Result of Maximum Permissible Exposure (2.4GHz)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm)
2400-2483.5	b	2412-2462	1-11 [11]	1	19.83
2400-2483.5	g	2412-2462	1-11 [11]	2	21.52
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	21.04
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	2	15.45

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Worst Maximum RF Output Power Result							
Exposure Environment		General Population / Uncontrolled Exposure					
Separation Distance (cm)		20					
Condition		RF Output Power (dBm)					
Modulation Mode	N _{TX}	Chain Port 1	Chain Port 2	Sum Chain	DG (dBi)	EIRP Power	PD (S) (mW/cm ²)
g	2	18.49	18.52	21.52	2.41	23.93	0.04917
Maximum Permissible Exposure Limit (mW/cm ²)							1

Note 1: N_{TX} = Number of Transmit Chains



1.1.4 Result of Maximum Permissible Exposure (5.2GHz)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm)
5150-5250	a	5180-5240	36-48 [4]	2	15.71
5150-5250	n (HT20)	5180-5240	36-48 [4]	2	15.59
5150-5250	n (HT40)	5190-5230	38-46 [2]	2	17.70

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Worst Maximum RF Output Power Result							
Exposure Environment		General Population / Uncontrolled Exposure					
Separation Distance (cm)		20					
Condition		RF Output Power (dBm)					
Modulation Mode	N _{TX}	Chain Port 1	Chain Port 2	Sum Chain	DG (dBi)	EIRP Power	PD (S) (mW/cm ²)
n (HT40)	2	14.86	14.50	17.70	1.23	18.93	0.00984
Maximum Permissible Exposure Limit (mW/cm ²)							1

Note 1: N_{TX} = Number of Transmit Chains



1.1.5 Result of Maximum Permissible Exposure (5.8GHz)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm) Co-location
5725-5850	a	5745-5825	149-165 [5]	2	21.32
5725-5850	n (HT20)	5745-5825	149-165 [5]	2	20.79
5725-5850	n (HT40)	5755-5795	151-159 [2]	2	19.91

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Worst Maximum RF Output Power Result							
Exposure Environment		General Population / Uncontrolled Exposure					
Separation Distance (cm)		20					
Condition		RF Output Power (dBm)					
Modulation Mode	N _{TX}	Chain Port 1	Chain Port 2	Sum Chain	DG (dBi)	EIRP Power	PD (S) (mW/cm ²)
a	2	18.28	18.34	21.32	1.23	22.55	0.03578
Maximum Permissible Exposure Limit (mW/cm ²)							1

Note 1: N_{TX} = Number of Transmit Chains