

# RF MEASUREMENT REPORT

---

**FCC ID:** UIDW61  
**Applicant:** ARRIS  
**Product:** Wireless Router  
**Model No.:** W61  
**FCC Classification:** Digital Transmission System (DTS)  
**FCC Rule Part(s):** Part 15 Subpart C (Section 15.247)  
**Result:** Complies  
**Test Date:** 2022-05-02 ~ 2022-06-21

**Reviewed By:**

\_\_\_\_\_  
Vincent Yu

**Approved By:**

\_\_\_\_\_  
Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

### Revision History

Report No.	Version	Description	Issue Date	Note
2205RSU031-U1	Rev. 01	Initial Report	2022-08-03	Valid

## CONTENTS

Description	Page
<b>1. General Information .....</b>	<b>5</b>
1.1. Applicant .....	5
1.2. Manufacturer .....	5
1.3. Testing Facility .....	5
1.4. Product Information.....	6
1.5. Radio Specification .....	6
1.6. Working Frequencies .....	7
1.7. Antenna Details.....	7
<b>2. Test Configuration .....</b>	<b>8</b>
2.1. Test Mode.....	8
2.2. Test System Connection Diagram.....	8
2.3. Test Software .....	8
2.4. Applied Standards.....	8
2.5. Test Environment Condition .....	9
<b>3. Antenna Requirements .....</b>	<b>10</b>
<b>4. Measuring Instrument .....</b>	<b>11</b>
<b>5. Decision Rules and Measurement Uncertainty .....</b>	<b>13</b>
5.1. Decision Rules .....	13
5.2. Measurement Uncertainty .....	13
<b>6. Test Result.....</b>	<b>14</b>
6.1. Summary.....	14
6.2. 6dB Bandwidth Measurement.....	15
6.2.1. Test Limit .....	15
6.2.2. Test Procedure .....	15
6.2.3. Test Setting .....	15
6.2.4. Test Setup .....	15
6.2.5. Test Result .....	15
6.3. Output Power Measurement .....	16
6.3.1. Test Limit .....	16
6.3.2. Test Procedure .....	16
6.3.3. Test Setting .....	16
6.3.4. Test Setup .....	16
6.3.5. Test Result .....	16
6.4. Power Spectral Density Measurement .....	17
6.4.1. Test Limit .....	17

---

6.4.2.	Test Procedure .....	17
6.4.3.	Test Setting .....	17
6.4.4.	Test Setup .....	17
6.4.5.	Test Result .....	18
6.5.	Conducted Band Edge and Out-of-Band Emissions Measurement .....	19
6.5.1.	Test Limit .....	19
6.5.2.	Test Procedure .....	19
6.5.3.	Test Setting .....	19
6.5.4.	Test Setup .....	20
6.5.5.	Test Result .....	20
6.6.	Radiated Spurious Emission Measurement.....	21
6.6.1.	Test Limit .....	21
6.6.2.	Test Procedure .....	21
6.6.3.	Test Setting .....	21
6.6.4.	Test Setup .....	23
6.6.5.	Test Result .....	23
6.7.	Radiated Restricted Band Edge Measurement .....	24
6.7.1.	Test Limit .....	24
6.7.2.	Test Procedure .....	25
6.7.3.	Test Setting .....	25
6.7.4.	Test Setup .....	26
6.7.5.	Test Result .....	26
6.8.	AC Conducted Emissions Measurement .....	27
6.8.1.	Test Limit .....	27
6.8.2.	Test Setup .....	27
6.8.3.	Test Result .....	27
<b>Appendix A - Test Result.....</b>		<b>28</b>
A.1	Duty Cycle Test Result .....	28
A.2	6dB Bandwidth Test Result .....	30
A.3	Output Power Test Result .....	37
A.4	Power Spectral Density Test Result.....	38
A.5	Conducted Band Edge and Out-of-Band Emissions Test Result.....	51
A.6	Radiated Spurious Emission Test Result.....	76
A.7	Radiated Restricted Band Edge Test Result.....	84
A.8	AC Conducted Emissions Test Result .....	156
<b>Appendix B - Test Setup Photograph .....</b>		<b>158</b>
<b>Appendix C - EUT Photograph .....</b>		<b>159</b>

---

**1. General Information**

**1.1. Applicant**

ARRIS  
3871 LAKEFIELD DR, SUWANEE GA 30024, UNITED STATES

**1.2. Manufacturer**

ARRIS  
3871 LAKEFIELD DR, SUWANEE GA 30024, UNITED STATES

**1.3. Testing Facility**

☒	<b>Test Site – MRT Suzhou Laboratory</b>
	<b>Laboratory Location (Suzhou - Wuzhong)</b> D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	<b>Laboratory Location (Suzhou - SIP)</b> 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	<b>Laboratory Accreditations</b>
	A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001 VCCI: <input type="checkbox"/> R-20025 <input type="checkbox"/> G-20034 <input type="checkbox"/> C-20020 <input type="checkbox"/> T-20020 <input type="checkbox"/> R-20141 <input type="checkbox"/> G-20134 <input type="checkbox"/> C-20103 <input type="checkbox"/> T-20104
☒	<b>Test Site – MRT Shenzhen Laboratory</b>
	<b>Laboratory Location (Shenzhen)</b> 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	<b>Laboratory Accreditations</b>
	A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105
☐	<b>Test Site – MRT Taiwan Laboratory</b>
	<b>Laboratory Location (Taiwan)</b> No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	<b>Laboratory Accreditations</b>
	TAF: L3261-190725 FCC: 291082, TW3261 ISED: TW3261

#### 1.4. Product Information

Product Name	Wireless Router
Model No.	W61
EUT Serial No.	23M54B111190103 (Radiated Sample) 23M54B111190084 (Conducted Sample)
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Antenna Information	Refer to Clause 1.7
Power Supply	AC/DC Adapter
Accessory	
Adapter 1#	Model: WA-30P12FU Input:100-120V ~ 50/60Hz 0.9A Max Output: 12V 2.5A
Adapter 2#	Model: F30L10-120250SPAU Input:100-120V ~ 50/60Hz 0.9A Max Output: 12V 2.5A, 30.0W
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

#### 1.5. Radio Specification

Frequency Range	802.11b/g/n-HT20/ax-HE20: 2412 ~ 2462MHz 802.11n-HT40/ax-HE40: 2422 ~ 2452MHz
Channel Number	802.11b/g/n-HT20/ax-HE20: 11 802.11n-HT40/ax-HE40: 7
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM 802.11ax: OFDMA
Data Rate	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 300Mbps 802.11ax: up to 573.5Mbps

Note: For other features of this EUT, test report will be issued separately.

### 1.6. Working Frequencies

802.11b/g/n-HT20/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40/ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

### 1.7. Antenna Details

Antenna Type	Frequency Band	T <sub>x</sub> Paths	N <sub>ss</sub>	Antenna Gain (dBi)				Max. Gain (dBi)	BF DG (dBi)	CDD DG (dBi)	
				Ant 0	Ant 1	Ant 2	Ant 3			Power	PSD
Dipole	2.4GHz	2	1	4.5	4.8	--	--	4.8	7.81	4.8	7.81
	5GHz	2	1	4.9	4.4	--	--	4.9	7.91	4.9	7.91
	6GHz	4	1	5.7	5.2	5.8	5.8	5.8	11.82	5.8	11.82

Remark:

- The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.  
If all antennas have the same gain,  $G_{ANT}$ , Directional gain =  $G_{ANT}$  + Array Gain, where Array Gain is as follows.
  - For power spectral density (PSD) measurements on all devices,  
Array Gain =  $10 \log (N_{ANT} / N_{SS})$  dB;
  - For power measurements on IEEE 802.11 devices,  
Array Gain = 0 dB for  $N_{ANT} \leq 4$ ;
- The EUT also supports beamforming mode, and the beamforming support 802.11n/ac/ax only, not include 802.11a/b/g. BF Directional Gain = Max. Gain +  $10 \log (N_{ANT} / N_{SS})$ .  
For beamforming operation, manufacturer automatically backs power down based on a  $10 \log (N_{ANT})$  factor based on CDD power. Therefore, only the CDD mode was evaluated in this report.


## 2. Test Configuration

### 2.1. Test Mode

Mode 1: Transmit by 802.11b (1Mbps) (CDD Mode)
Mode 2: Transmit by 802.11g (6Mbps) (CDD Mode)
Mode 3: Transmit by 802.11n-HT20 (MCS0) (CDD Mode)
Mode 4: Transmit by 802.11n-HT40 (MCS0) (CDD Mode)
Mode 5: Transmit by 802.11ax-HE20 (MCS0) (CDD Mode)
Mode 6: Transmit by 802.11ax-HE40 (MCS0) (CDD Mode)

### 2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.



Note: Only Adapter #1 was selected for all of RF test.

### 2.3. Test Software

The test utility software used during testing was “Qualcomm Sequence Profiling Resource”, and the version was 5.0-00199. Final power setting please refer to operational description.



## 2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- KDB 662911 D01v02r01
- ANSI C63.10-2013

## 2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

### 3. Antenna Requirements

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

**Conclusion:**

The unit complies with the requirement of §15.203.

#### 4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06292	1 year	2022-10-20	NS-AC1
Anechoic Chamber	BOOMWAVE	NS-AC1	MRTSUE06496	1 year	2022-07-24	NS-AC1
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06572	1 year	2023-04-01	NS-AC1
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06573	1 year	2022-06-29	NS-AC1
				1 year	2023-06-21	
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06574	1 year	2022-07-12	NS-AC1
EMI Test Receiver	R&S	ESR3	MRTSUE06575	1 year	2022-06-27	NS-AC1
				1 year	2023-06-19	
Thermohygrometer	DELI	NO.8813	MRTSUE06588	1 year	2022-06-30	NS-AC1
				1 year	2023-06-21	
Preamplifier	EMCI	EMC184045SE	MRTSUE06641	1 year	2023-01-13	NS-AC1
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2022-06-24	WZ-AC2
				1 year	2023-06-04	
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2022-10-28	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2023-04-21	WZ-AC2
Thermohygrometer	Mingle	ETH529	MRTSUE06170	1 year	2022-12-01	WZ-AC2
Thermohygrometer	testo	Testo 608-H1	MRTSUE11038	1 year	2022-11-11	WZ-AC2
USB Power Sensor	Keysight	U2021XA	MRTSUE06581	1 year	2022-08-15	NS-TR2
Thermohygrometer	DELI	NO.8813	MRTSUE06783	1 year	2023-04-14	NS-TR2
Temperature Chamber	OUKE	OK-TH-100C	MRTSUE06899	1 year	2022-11-01	NS-TR2
Signal Analyzer	Agilent	N9010A	MRTSUE06195	1 year	2023-04-13	NS-AC1/NS-TR2
Signal Analyzer	Keysight	N9020A	MRTSUE10065	1 year	2023-01-11	NS-AC1/NS-TR2
Shielding Room	BOOMWAVE	NS-SR2	MRTSUE06551	5 years	2024-06-03	NS-SR2
EMI Test Receiver	R&S	ESL3	MRTSUE06576	1 year	2022-06-27	NS-SR2
				1 year	2023-06-19	
Two-Line V-Network	R&S	ENV216	MRTSUE06577	1 year	2022-07-04	NS-SR2
				1 year	2023-07-03	
Two-Line V-Network	R&S	ENV216	MRTSUE06578	1 year	2022-07-04	NS-SR2
				1 year	2023-07-03	
Thermohygrometer	DELI	NO.8813	MRTSUE06587	1 year	2022-06-30	NS-SR2
				1 year	2023-06-21	
High Pass Filter	WI	WHKX10-2501-3050 -18000-80SS	MRTSUE06151	1 year	2023-03-09	NS-AC1
Low Pass Filter	MVE	MFL-0000.1000.S2	MRTSUE06516	1 year	2023-03-09	NS-AC1
Notch Filter	XB TECHNOLOGY	XBLBQ-DZA81	MRTSUE06723	1 year	2023-03-09	NS-AC1

Attenuator	MVE	MVE2213	MRTSUE11062	1 year	2022-06-08	NS-TR2
				1 year	2023-06-09	
Attenuator	MVE	MVE2213	MRTSUE11063	1 year	2022-06-08	NS-TR2
				1 year	2023-06-09	
Attenuator	MVE	MVE2213	MRTSUE11064	1 year	2022-06-08	NS-TR2
				1 year	2023-06-09	

Note: The test site with "WZ" code is in the MRT Suzhou laboratory, the test site with "NS" code is in the MRT Shenzhen Laboratory.

Software	Version	Function
EMI V3	V 3.0.0	EMI Test Software
Controller_T-E-TAC-2	1.02	RE Antenna&turtable
Agilent Power Panel	V 3.9	Power

## 5. Decision Rules and Measurement Uncertainty

### 5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

### 5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>AC Conducted Emission Measurement</b>
Measurement Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 9kHz~150kHz: 3.74dB 150kHz~30MHz: 3.44dB
<b>Radiated Disturbance</b>
Measurement Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): Horizontal: 30MHz~300MHz: 5.04dB 300MHz~1GHz: 4.95dB 1GHz~40GHz: 6.40dB Vertical: 30MHz~300MHz: 5.24dB 300MHz~1GHz: 6.03dB 1GHz~40GHz: 6.40dB
<b>Spurious Emissions, Conducted</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.78dB
<b>Output Power</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.13dB
<b>Power Spectrum Density</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.15dB
<b>Occupied Bandwidth</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.28%

## 6. Test Result

### 6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

**Remark:**

- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- For the item of “6dB Bandwidth”, we only evaluated the Ant 1 RF port.
- The EUT supports one configuration only in 802.11ax full RU mode.

## 6.2. 6dB Bandwidth Measurement

### 6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


### 6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

### 6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 6$ . The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3.  $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

### 6.2.4. Test Setup



### 6.2.5. Test Result

Refer to Appendix A.2.

### 6.3. Output Power Measurement

#### 6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 6.3.2. Test Procedure


ANSI C63.10 - 2013 - Section 11.9.2.3.2

#### 6.3.3. Test Setting

##### Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

#### 6.3.4. Test Setup



#### 6.3.5. Test Result

Refer to Appendix A.3.



## 6.4. Power Spectral Density Measurement

### 6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


### 6.4.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.10.5

### 6.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
8. Sweep time = auto couple.
9. Don't use sweep triggering. Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

### 6.4.4. Test Setup



#### **6.4.5. Test Result**

Refer to Appendix A.4.

## **6.5. Conducted Band Edge and Out-of-Band Emissions Measurement**

### **6.5.1. Test Limit**

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

### **6.5.2. Test Procedure**

ANSI C63.10-2013 - Section 11.11

### **6.5.3. Test Setting**

#### **Reference level measurement**


1. Set instrument center frequency to DTS channel center frequency
2. Set the span to  $\geq 1.5$  times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW  $\geq 3 \times$  RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

#### **Emission level measurement**

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

#### 6.5.4. Test Setup

Spectrum Analyzer



DC Block  
&  
Attenuator



#### 6.5.5. Test Result

Refer to Appendix A.5.

## 6.6. Radiated Spurious Emission Measurement

### 6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

### 6.6.3. Test Setting

**Table 1 - RBW as a function of frequency**

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

**Quasi-Peak Measurements below 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

**Peak Measurements above 1GHz**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

**Average Measurements above 1GHz (Method VB)**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle  $\geq 98\%$ , set VBW = 10 Hz.  
If the EUT duty cycle is  $< 98\%$ , set VBW  $\geq 1/T$ . T is the minimum transmission duration.
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Trace was allowed to stabilize

### 6.6.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



### 6.6.5. Test Result

Refer to Appendix A.6.

## 6.7. Radiated Restricted Band Edge Measurement

### 6.7.1. Test Limit

#### For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	--	--	--



All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3 & 6.6 & 11.13

### 6.7.3. Test Setting


#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW  $\geq 1/T$
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

#### 6.7.4. Test Setup



#### 6.7.5. Test Result

Refer to Appendix A.7.

## 6.8. AC Conducted Emissions Measurement


### 6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

### 6.8.2. Test Setup



### 6.8.3. Test Result

Refer to Appendix A.8.

## Appendix A - Test Result


### A.1 Duty Cycle Test Result

Test Site	NS-TR2	Test Engineer	Summer Tang
Test Date	2022-06-07		


Test Mode	Duty Cycle
802.11b	60.28%
802.11g	94.44%
802.11n-HT20	94.39%
802.11n-HT40	94.34%
802.11ax-HE20	93.71%
802.11ax-HE40	94.33%

Duty Cycle (T = Transmission Duration)


802.11b (T = 1.290ms)




802.11g (T = 1.428ms)




802.11n-HT20 (T = 5.432ms)



802.11n-HT40 (T = 5.421ms)






**A.2 6dB Bandwidth Test Result**

Test Site	NS-TR2	Test Engineer	Summer Tang
Test Date	2022-06-07		


Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
11b	1Mbps	01	2412	8.07	≥ 0.5
11b	1Mbps	06	2437	8.08	≥ 0.5
11b	1Mbps	11	2462	8.08	≥ 0.5
11g	6Mbps	01	2412	15.65	≥ 0.5
11g	6Mbps	06	2437	16.27	≥ 0.5
11g	6Mbps	11	2462	15.52	≥ 0.5
11n-HT20	MCS0	01	2412	17.30	≥ 0.5
11n-HT20	MCS0	06	2437	17.07	≥ 0.5
11n-HT20	MCS0	11	2462	17.19	≥ 0.5
11n-HT40	MCS0	03	2422	35.76	≥ 0.5
11n-HT40	MCS0	06	2437	36.26	≥ 0.5
11n-HT40	MCS0	09	2452	36.36	≥ 0.5
11ax-HE20	MCS0	01	2412	18.05	≥ 0.5
11ax-HE20	MCS0	06	2437	18.27	≥ 0.5
11ax-HE20	MCS0	11	2462	18.15	≥ 0.5
11ax-HE20	MCS0	03	2422	37.89	≥ 0.5
11ax-HE20	MCS0	06	2437	37.83	≥ 0.5
11ax-HE20	MCS0	09	2452	37.74	≥ 0.5

802.11b 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)



## 802.11g 6dB Bandwidth


## Channel 01 (2412MHz)



## Channel 06 (2437MHz)




## Channel 11 (2462MHz)





802.11n-HT20 6dB Bandwidth


Channel 01 (2412MHz)




Channel 06 (2437MHz)




Channel 11 (2462MHz)






## 802.11ax-HE20 6dB Bandwidth


## Channel 01 (2412MHz)



## Channel 06 (2437MHz)




## Channel 11 (2462MHz)




802.11ax-HE40 6dB Bandwidth


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



**A.3 Output Power Test Result**

Test Site	NS-TR2	Test Engineer	Summer Tang
Test Date	2022-06-02 ~ 2022-06-09		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)		Total Average Power (dBm)	Limit (dBm)
				Ant 0	Ant 1		
11b	1Mbps	01	2412	22.72	22.81	25.78	≤ 30.00
11b	1Mbps	06	2437	22.53	22.76	25.66	≤ 30.00
11b	1Mbps	11	2462	22.57	22.75	25.67	≤ 30.00
11g	6Mbps	01	2412	22.70	22.85	25.79	≤ 30.00
11g	6Mbps	06	2437	22.74	22.88	25.82	≤ 30.00
11g	6Mbps	11	2462	21.41	21.68	24.56	≤ 30.00
11n-HT20	MCS0	01	2412	21.15	21.51	24.34	≤ 30.00
11n-HT20	MCS0	06	2437	22.39	23.00	25.72	≤ 30.00
11n-HT20	MCS0	11	2462	21.37	21.42	24.41	≤ 30.00
11n-HT40	MCS0	03	2422	18.60	18.96	21.79	≤ 30.00
11n-HT40	MCS0	04	2427	18.22	18.16	21.20	≤ 30.00
11n-HT40	MCS0	05	2432	21.98	21.71	24.86	≤ 30.00
11n-HT40	MCS0	06	2437	21.90	22.03	24.98	≤ 30.00
11n-HT40	MCS0	07	2442	23.01	22.85	25.94	≤ 30.00
11n-HT40	MCS0	08	2447	18.02	17.99	21.02	≤ 30.00
11n-HT40	MCS0	09	2452	18.52	18.90	21.72	≤ 30.00
11ax-HE20	MCS0	01	2412	20.23	20.29	23.27	≤ 30.00
11ax-HE20	MCS0	06	2437	22.40	22.93	25.68	≤ 30.00
11ax-HE20	MCS0	11	2462	20.24	20.27	23.27	≤ 30.00
11ax-HE40	MCS0	03	2422	18.41	18.58	21.51	≤ 30.00
11ax-HE40	MCS0	04	2427	17.77	17.72	20.76	≤ 30.00
11ax-HE40	MCS0	05	2432	21.64	21.51	24.59	≤ 30.00
11ax-HE40	MCS0	06	2437	21.63	21.68	24.67	≤ 30.00
11ax-HE40	MCS0	07	2442	20.70	20.31	23.52	≤ 30.00
11ax-HE40	MCS0	08	2447	17.69	17.65	20.68	≤ 30.00
11ax-HE40	MCS0	09	2452	18.29	18.44	21.38	≤ 30.00

Note: Total Average Power (dBm) =  $10 \cdot \log \{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)}\}$  (dBm).

**A.4 Power Spectral Density Test Result**

Test Site	NS-TR2	Test Engineer	Summer Tang
Test Date	2022-05-02 ~ 2022-06-07		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	AVG PSD (dBm/ 10kHz)		Duty Cycle (%)	Total PSD (dBm/ 10kHz)	Limit (dBm/ 3kHz)
				Ant 0	Ant 1			
11b	1Mbps	01	2412	-3.897	-4.076	60.28	1.223	≤ 6.19
11b	1Mbps	06	2437	-4.406	-4.095	60.28	0.961	≤ 6.19
11b	1Mbps	11	2462	-3.788	-3.597	60.28	1.517	≤ 6.19
11g	6Mbps	01	2412	-6.476	-6.313	94.44	-3.135	≤ 6.19
11g	6Mbps	06	2437	-6.218	-5.741	94.44	-2.714	≤ 6.19
11g	6Mbps	11	2462	-7.319	-7.175	94.44	-3.988	≤ 6.19
11n-HT20	MCS0	01	2412	-8.472	-8.235	94.39	-5.091	≤ 6.19
11n-HT20	MCS0	06	2437	-7.287	-6.682	94.39	-3.713	≤ 6.19
11n-HT20	MCS0	11	2462	-8.397	-7.825	94.39	-4.841	≤ 6.19
11n-HT40	MCS0	03	2422	-13.208	-13.385	94.34	-10.032	≤ 6.19
11n-HT40	MCS0	06	2437	-10.391	-10.458	94.34	-7.161	≤ 6.19
11n-HT40	MCS0	09	2452	-13.679	-13.291	94.34	-10.217	≤ 6.19
11ax-HE20	MCS0	01	2412	-10.797	-10.288	93.71	-7.243	≤ 6.19
11ax-HE20	MCS0	06	2437	-8.143	-8.274	93.71	-4.916	≤ 6.19
11ax-HE20	MCS0	11	2462	-10.704	-10.334	93.71	-7.223	≤ 6.19
11ax-HE40	MCS0	03	2422	-15.180	-14.919	94.33	-11.784	≤ 6.19
11ax-HE40	MCS0	06	2437	-11.847	-11.967	94.33	-8.643	≤ 6.19
11ax-HE40	MCS0	09	2452	-14.743	-14.737	94.33	-11.476	≤ 6.19

Note:

- The EUT duty cycle ≤ 98%, Total PSD =  $10 \cdot \log \{10^{(\text{Ant 0 AVG PSD}/10)} + 10^{(\text{Ant 1 AVG PSD}/10)}\} + 10 \cdot \log (1/\text{Duty Cycle})$ .
- PSD Limit (dBm/3kHz) =  $[8 - (7.81 - 6)]$  (dBm/3kHz) = 6.19 (dBm/3kHz).

802.11b - AVGPSD - Ant 0

Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g - AVGPSD - Ant 0


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)






802.11n-HT20 - AVGPSD - Ant 0


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 - AVGPSD - Ant 0


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)



802.11ax-HE20 - AVGPSD - Ant 0


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11ax-HE40 - AVGPSD - Ant 0


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 9 (2452MHz)



802.11b - AVGPSD - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g - AVGPSD - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT20 - AVGPSD - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 - AVGPSD - Ant 1


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)






802.11ax-HE20 - AVGPSD - Ant 1

Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)

