

## Exposure of humans to RF fields

Transmit Frequency 930.525 MHz

Minimum safe distances have been calculated below.

Power density,  $\text{mW/cm}^2 = E^2/3770$

- Occupational / Controlled Exposure limit will be  $3.10 \text{ mW/cm}^2$   
( $f/300 = 930.5 \text{ MHz}/300$ )

- General Population / Uncontrolled exposure limit will be  $0.62 \text{ mW/cm}^2$   
( $f/1500 = 930.5 \text{ MHz}/1500$ )

The minimum distance from the antenna at which the MPE is met is calculated from the equation relating field strength in V/m, transmit power in watts, transmit antenna gain, transmitter duty cycle and separation distance in metres:

$$E, \text{ V/m} = (\sqrt{30 * P * G}) / d$$

### Controlled

$$E = 3.10 \text{ mW/cm}^2 = E^2/3770$$

$$E = \sqrt{3.1 * 3770}$$

$$E = 108.1 \text{ V/m}$$

### Uncontrolled

$$E = 0.62 \text{ mW/cm}^2 = E^2/3770$$

$$E = \sqrt{0.62 * 3770}$$

$$E = 48.3 \text{ V/m}$$

The rated maximum transmitter power (P) = 5 watts.

Transmitter is operated using an antenna with a gain (G) of up to 28 dBi which equals 631.

The client has declared a duty cycle (DC) of 100% (1)

### Controlled

$$d = \sqrt{30 * P * G * DC} / E$$

$$d = \sqrt{30 * 5 * 631 * 1} / 108.1$$

$$d = 2.85 \text{ metres or } 285 \text{ cm}$$

### Uncontrolled

$$d = \sqrt{30 * 5 * 631 * 1} / 48.3$$

$$d = 6.37 \text{ metres or } 637 \text{ cm}$$

**Result:** Complies if the safe distances defined for each environment are applied.