



Inter**Lab**<sup>®</sup>

FCC Measurement/Technical Report on

KLEER transceiver

NR-207

**Report Reference:** MDE\_MEE\_1213\_FCCa

**Test Laboratory:**

Borsigstr. 11  
Germany  
7Layers AG  
40880 Ratingen



**Note:**

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7 layers AG  
Borsigstrasse 11  
40880 Ratingen, Germany  
Phone: +49 (0) 2102 749 0  
Fax: +49 (0) 2102 749 350  
www.7Layers.com

Aufsichtsratsvorsitzender •  
Chairman of the Supervisory Board:  
Ralf Mertens  
Vorstand • Board:  
Dr. H.-J. Meckelburg

Registergericht • registered in:  
Düsseldorf, HRB 44096  
USt-IdNr • VAT No.:  
DE 203159652  
TAX No. 147/5869/0385



## Table of Contents

<b>0</b>	<b>Summary</b>	<b>3</b>
0.1	Technical Report Summary	3
0.2	Measurement Summary	4
<b>1</b>	<b>Administrative Data</b>	<b>6</b>
1.1	Testing Laboratory	6
1.2	Project Data	6
1.3	Applicant Data	6
1.4	Manufacturer Data	6
<b>2</b>	<b>Test object Data</b>	<b>7</b>
2.1	General EUT Description	7
2.2	EUT Main components	8
2.3	Ancillary Equipment	8
2.4	Auxiliary Equipment	8
2.5	EUT Setups	9
2.6	Operating Modes	9
2.7	Product labelling	9
<b>3</b>	<b>Test Results</b>	<b>10</b>
3.1	Occupied bandwidth	10
3.2	Peak power output	12
3.3	Spurious RF conducted emissions	15
3.4	Spurious radiated emissions	17
3.5	Band edge compliance	22
3.6	Power density	25
<b>4</b>	<b>Test Equipment</b>	<b>27</b>
<b>5</b>	<b>Photo Report</b>	<b>34</b>
<b>6</b>	<b>Setup Drawings</b>	<b>34</b>
<b>7</b>	<b>FCC and IC Correlation of measurement requirements</b>	<b>35</b>
<b>8</b>	<b>Annex measurement plots</b>	<b>36</b>
8.1	Occupied bandwidth	36
8.2	Peak power output	39
8.3	Band edge compliance conducted and Spurious RF conducted emissions	42
8.4	Power density	48



## 0 Summary

### 0.1 Technical Report Summary

#### **Type of Authorization**

Certification for an Intentional Radiator (Digital Device / Spread Spectrum).

#### **Applicable FCC Rules**

Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 2 (10-1-11 Edition) and 15 (10-1-11 Edition). The following subparts are applicable to the results in this test report.

Part 2, Subpart J - Equipment Authorization Procedures, Certification

Part 15, Subpart C – Intentional Radiators

§ 15.201 Equipment authorization requirement

§ 15.207 Conducted limits

§ 15.209 Radiated emission limits; general requirements

§ 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz

#### Note:

The tests were selected and performed with reference to the FCC measurement guide line "Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005"

Instead of applying ANSI C63.4–1992 which is referenced in the FCC Public Note, the newer ANSI C63.4–2009 is applied.

#### **Summary Test Results:**

**The EUT complied with all performed tests as listed in chapter 0.2 Measurement Summary.**



## 0.2 Measurement Summary

<b>FCC Part 15, Subpart C</b>			<b>§ 15.207</b>
Conducted emissions (AC power line)			
The measurement was performed according to ANSI C63.4			2009
<b>OP-Mode</b>	<b>Setup</b>	<b>Port</b>	<b>Final Result</b>
-	-	-	N/A
<b>FCC Part 15, Subpart C</b>			<b>§ 15.247 (a) (1)</b>
Occupied bandwidth			
The measurement was performed according to FCC § 15.31			10-1-11 Edition
<b>OP-Mode</b>	<b>Setup</b>	<b>Port</b>	<b>Final Result</b>
op-mode 1	Setup_02	Int.ant.connector	passed
op-mode 2	Setup_02	Int.ant.connector	passed
op-mode 3	Setup_02	Int.ant.connector	passed
<b>FCC Part 15, Subpart C</b>			<b>§ 15.247 (b) (1)</b>
Peak power output			
The measurement was performed according to FCC § 15.31			10-1-11 Edition
<b>OP-Mode</b>	<b>Setup</b>	<b>Port</b>	<b>Final Result</b>
op-mode 1	Setup_02	Int.ant.connector	passed
op-mode 2	Setup_02	Int.ant.connector	passed
op-mode 3	Setup_02	Int.ant.connector	passed
<b>FCC Part 15, Subpart C</b>			<b>§ 15.247 (d)</b>
Spurious RF conducted emissions			
The measurement was performed according to FCC § 15.31			10-1-11 Edition
<b>OP-Mode</b>	<b>Setup</b>	<b>Port</b>	<b>Final Result</b>
op-mode 1	Setup_02	Int.ant.connector	passed
op-mode 2	Setup_02	Int.ant.connector	passed
op-mode 3	Setup_02	Int.ant.connector	passed
<b>FCC Part 15, Subpart C</b>			<b>§ 15.247 (d), § 15.35 (b), § 15.209</b>
Spurious radiated emissions			
The measurement was performed according to ANSI C63.4			2009
<b>OP-Mode</b>	<b>Setup</b>	<b>Port</b>	<b>Final Result</b>
op-mode 1	Setup_01/02/03	Enclosure	passed
op-mode 2	Setup_01/02/03	Enclosure	passed
op-mode 3	Setup_01/02/03	Enclosure	passed
<b>FCC Part 15, Subpart C</b>			<b>§ 15.247 (d)</b>
Band edge compliance			
The measurement was performed according to FCC § 15.31 / ANSI C63.4			10-1-11 Edition / 2009
<b>OP-Mode</b>	<b>Setup</b>	<b>Port</b>	<b>Final Result</b>
op-mode 1	Setup_02	Int.ant.connector	passed
op-mode 3	Setup_02	Int.ant.connector	passed
op-mode 3	Setup_01	Enclosure	passed



**FCC Part 15, Subpart C**

**§ 15.247 (e)**

Power density

The measurement was performed according to FCC § 15.31

10-1-11 Edition

<b>OP-Mode</b>	<b>Setup</b>	<b>Port</b>	<b>Final Result</b>
op-mode 1	Setup_02	Int.ant.connector	passed
op-mode 2	Setup_02	Int.ant.connector	passed
op-mode 3	Setup_02	Int.ant.connector	passed

N/A not applicable (the EUT is powered by DC)

Responsible for Accreditation Scope: \_\_\_\_\_

Responsible for Test Report: \_\_\_\_\_



## 1 Administrative Data

### 1.1 Testing Laboratory

Company Name: 7Layers AG  
Address: Borsigstr. 11  
40880 Ratingen  
Germany

This facility has been fully described in a report submitted to the FCC and accepted under the registration number 96716 .

The test facility is also accredited by the following accreditation organisation:  
Laboratory accreditation no.: DAkKS D-PL-12140-01-01

Responsible for Accreditation Scope: Dipl.-Ing. Bernhard Retka  
Dipl.-Ing. Robert Machulec  
Dipl.-Ing. Marco Kullik  
Dipl.-Ing. Andreas Petz

Report Template Version: 2012-03-14

### 1.2 Project Data

Responsible for testing and report: Dipl.-Ing. Marco Kullik  
Date of Test(s): 2012-10-15 to 2013-01-07  
Date of Report: 2013-01-09

### 1.3 Applicant Data

Company Name: Mitsubishi Electric Europe B.V.  
Address: Mündelheimer Weg 35  
40472 Düsseldorf  
Germany  
Contact Person: Mr. Rolf Borchert

### 1.4 Manufacturer Data

Company Name: Mitsubishi Electric Corporation  
Address: Sanda Works  
2-3-33, Miwa, Sanda-city  
Hyogo 669-1513  
Japan  
Contact Person:



## 2 Test object Data

### 2.1 General EUT Description

<b>Equipment under Test:</b>	KLEER transceiver
<b>Type Designation:</b>	NR-207
<b>Kind of Device:</b>	Car Multimedia System
<b>(optional)</b>	
<b>Voltage Type:</b>	DC (vehicular)
<b>Voltage Level:</b>	12 V
<b>Tested Modulation Type:</b>	FSK (MSK)

#### General product description:

The KLEER Transceiver is operating in the 2.4 GHz ISM band in the range 2403.0 – 2478.0 MHz and uses the Direct Sequence Spread Spectrum (DSSS) Modulation. The KLEER technology supports 16 channels in the 2.4 GHz ISM band, each spaced by 5 MHz whilst the nominal bandwidth is designed as 3 MHz. The KLEER technology provides Dynamic Frequency Selection.

#### Specific product description for the EUT:

The EUT is a car multimedia system containing besides a KLEER also a Bluetooth transceiver and a GPS receiver.

#### The EUT provides the following ports:

##### Ports

- KLEER antenna connector
- Enclosure
- GPS antenna port
- Bluetooth antenna port
- Cable harness including DC Port
- AM/FM antenna port
- Auxiliary audio port
- Display port
- Night view camera port
- Retrovit NAVI port
- TV tuner port
- RVC/UCI port
- Rear seat entertainment port

The KLEER antenna connector is not accessible for the end user.

**The main components of the EUT are listed and described in Chapter 2.2**



## 2.2 EUT Main components

### Type, S/N, Short Descriptions etc. used in this Test Report

Short Description	Equipment under Test	Type Designation	Serial No.	HW Status	SW Status	Date of Receipt
EUT A (Code: 08780a01)	KLEER transceiver	NR-207	ME7030C22 81040	A21290282 04	A21290158 04	-
Remark: EUT A is equipped with an integral antenna (gain = -4.8 dBi) & antenna connector.						
EUT B (Code: 08780c01)	KLEER transceiver	NR-207	ME7000C22 71008	A21290280 04	A21290156 04	-
Remark: EUT A is equipped with an integral antenna (gain = -4.8 dBi) & antenna connector.						
EUT C (Code: 08780e01)	KLEER transceiver	NR-207	ME7020C07 41011	A21290233 07	A21290182 06	-
Remark: EUT A is equipped with an integral antenna (gain = -4.8 dBi) & antenna connector.						

NOTE: The short description is used to simplify the identification of the EUT in this test report.

## 2.3 Ancillary Equipment

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	HW Status	SW Status	Serial no.	FCC ID
-	-	-	-	-	-	-

## 2.4 Auxiliary Equipment

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Auxiliary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial no.	HW Status	SW Status	FCC ID
AUX1		Display Unit	-	-	-	-
AUX2		Turning knob	-	-	-	-
AUX3		Cable harness	-	-	-	-



## 2.5 EUT Setups

This chapter describes the combination of EUTs and equipment used for testing. The rationale for selecting the EUTs, ancillary and auxiliary equipment and interconnecting cables, is to test a representative configuration meeting the requirements of the referenced standards.

Setup No.	Combination of EUTs	Description and Rationale
Setup_01	EUT A + AUX1 + AUX2 + AUX3	setup for radiated & conducted measurements (AUX1, AUX2 and AUX3 are required to operate the EUT)
Setup_02	EUT B + AUX1 + AUX2 + AUX3	setup for radiated & conducted measurements (AUX1, AUX2 and AUX3 are required to operate the EUT)
Setup_03	EUT C + AUX1 + AUX2 + AUX3	setup for radiated & conducted measurements (AUX1, AUX2 and AUX3 are required to operate the EUT)

## 2.6 Operating Modes

This chapter describes the operating modes of the EUTs used for testing.

Op. Mode	Description of Operating Modes	Remarks
op-mode 1	TX-mode, the EUT transmits on the lowest channel (2403 MHz)	Operation on lowest frequency (channel 0)
op-mode 2	TX-mode, the EUT transmits on the mid channel (2438 MHz)	Operation on mid frequency (channel 7)
op-mode 3	TX-mode, the EUT transmits on the highest channel (2478 MHz)	Operation on highest frequency (channel 15)

### 2.6.1 Special software used for testing

No special software was used for testing.

## 2.7 Product labelling

Please refer to the documentation of the applicant.

### 2.7.1 FCC ID label

FCC ID: UJHNR207UHD  
IC: 662K-NR207

### 2.7.2 Location of the label on the EUT

Please refer to the documentation of the applicant.



## 3 Test Results

### 3.1 Occupied bandwidth

**Standard** FCC Part 15, 10-1-11 Subpart C

**The test was performed according to:** FCC §15.31

#### 3.1.1 Test Description

The Equipment Under Test (EUT) was setup to perform the occupied bandwidth measurements.

The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical.

The results recorded were measured with the modulation which produce the worst-case (widest) occupied bandwidth.

The EUT was connected to spectrum analyzer via a short coax cable with a known loss. Analyzer settings:

- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Span: 30 MHz

#### 3.1.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Used conversion factor: Output power (dBm) = 10 log (Output power (W) / 1mW)

### 3.1.3 Test Protocol

Temperature: 22 °C  
 Air Pressure: 1020 hPa  
 Humidity: 40 %

Op. Mode	Setup	Port
op-mode 1	Setup_01	Int.ant.connector

6 dB bandwidth MHz	Remarks
1.932	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 2	Setup_01	Int.ant.connector

6 dB bandwidth MHz	Remarks
1.812	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 3	Setup_01	Int.ant.connector

6 dB bandwidth MHz	Remarks
1.992	-

### 3.1.4 Test result: Occupied bandwidth

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 2	passed
	op-mode 3	passed



## 3.2 Peak power output

**Standard** FCC Part 15, 10-1-11 Subpart C

**The test was performed according to:** FCC §15.31

### 3.2.1 Test Description

The Equipment Under Test (EUT) was set up to perform the output power measurements. The results recorded were measured with the modulation which produces the worst-case (highest) output power. The reference level of the spectrum analyzer was set higher than the output power of the EUT. The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

### 3.2.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (b) (3)

For systems using digital modulation techniques in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands: 1 watt.

Used conversion factor:  $\text{Limit (dBm)} = 10 \log (\text{Limit (W)}/1\text{mW})$   
==> Maximum Output Power: 30 dBm



### 3.2.3 Test Protocol

Temperature: 22 °C  
Air Pressure: 1020 hPa  
Humidity: 40 %

Op. Mode	Setup	Port
op-mode 1	Setup_01	Int.ant.connector

Output power dBm	Remarks
2.70	The EIRP including antenna gain (-4.8 dBi) is -2.1 dBm. Detector RMS.

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 2	Setup_01	Int.ant.connector

Output power dBm	Remarks
2.0	The EIRP including antenna gain (-4.8 dBi) is -2.8 dBm. Detector RMS.

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 3	Setup_01	Int.ant.connector

Output power dBm	Remarks
1.1	The EIRP including antenna gain (-4.8 dBi) is -3.7 dBm. Detector RMS.

Remark: Please see annex for the measurement plot.



Test result: Peak power output

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 2	passed
	op-mode 3	passed



### 3.3 Spurious RF conducted emissions

**Standard** FCC Part 15, 10-1-11 Subpart C

**The test was performed according to:** FCC §15.31

#### 3.3.1 Test Description

The Equipment Under Test (EUT) was set up to perform the spurious emissions measurements.

The EUT was connected to spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Detector: Peak-Maxhold
- Frequency range: 30 – 25000 MHz
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Sweep Time: 330 s

The reference value for the measurement of the spurious RF conducted emissions is determined during the test “band edge compliance” (cf. chapter 3.5). This value is used to calculate the 20 dBc limit.

#### 3.3.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (c)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### 3.3.3 Test Protocol

Temperature: 23°C  
 Air Pressure: 1020hPa  
 Humidity: 41%

Op. Mode	Setup	Port
op-mode 1	Setup_01	Temp.ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Margin to limit dB
/	/	/	/	/

Remark: No (further) spurious emissions in the range 20 dB below the limit found.  
 Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 2	Setup_01	Temp.ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Margin to limit dB
/	/	/	/	/

Remark: No (further) spurious emissions in the range 20 dB below the limit found.  
 Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 3	Setup_01	Temp.ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Margin to limit dB
/	/	/	/	/

Remark: No (further) spurious emissions in the range 20 dB below the limit found.  
 Please see annex for the measurement plot.

### 3.3.4 Test result: Spurious RF conducted emissions

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 2	passed
	op-mode 3	passed



### 3.4 Spurious radiated emissions

**Standard** FCC Part 15, 10-1-11 Subpart C

**The test was performed according to:** ANSI C63.4–2009

#### 3.4.1 Test Description

The test set-up was made in accordance to the general provisions of ANSI C63.4–2009 in a typical installation configuration. The Equipment Under Test (EUT) was set up on a non-conductive table 1.0 x 2.0 m<sup>2</sup> in the semi-anechoic chamber. The influence of the EUT support table that is used between 30–1000 MHz was evaluated.

The test was performed at the distance of 3 m between the EUT and the receiving antenna. The measurement procedure is implemented into the EMI test software ES-K1 from R&S. The radiated emissions measurements were made in a typical installation configuration. Exploratory tests are performed at 3 orthogonal axes to determine the worst-case orientation of a body-worn or handheld EUT. The final test on all kind of EUTs is performed at 2 axes. A pre-check is also performed while the EUT is powered from both AC and DC (battery) power in order to find the worst-case operating condition.

##### 1. Measurement up to 30 MHz

The test set-up was made in accordance to the general provisions of ANSI C 63.4-2009. The Equipment Under Test (EUT) was set up on a non-conductive table in the anechoic chamber.

The radiated emissions measurements were made in a typical installation configuration. The measurement procedure is implemented into the EMI test software ES-K1 from R&S. The Loop antenna HFH2-Z2 is used.

##### **Step 1:** pre measurement

- Anechoic chamber
- Antenna distance: 10 m
- Detector: Peak-Maxhold
- Frequency range: 0.009 - 0.15 and 0.15 – 30 MHz
- Frequency steps: 0.1 kHz and 5 kHz
- IF-Bandwidth: 0.2 kHz and 10 kHz
- Measuring time / Frequency step: 100 ms

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

##### **Step 2:** final measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is to find the maximum emission level.

- Open area test side
- Antenna distance: according to the Standard
- Detector: Quasi-Peak
- Frequency range: 0.009 – 30 MHz
- Frequency steps: measurement at frequencies detected in step 1
- IF-Bandwidth: 200 Hz - 10 kHz
- Measuring time / Frequency step: 100 ms

## 2. Measurement above 30 MHz and up to 1 GHz

### Step 1: Preliminary scan

Preliminary test to identify the highest amplitudes relative to the limit.

Settings for step 1:

- Antenna distance: 3 m
- Detector: Peak-Maxhold
- Frequency range: 30 – 1000 MHz
- Frequency steps: 60 kHz
- IF-Bandwidth: 120 kHz
- Measuring time / Frequency step: 100  $\mu$ s
- Turntable angle range:  $-180^\circ$  to  $180^\circ$
- Turntable step size:  $90^\circ$
- Height variation range: 1 – 3 m
- Height variation step size: 2 m
- Polarisation: Horizontal + Vertical

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

### Step 2: second measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is, to find out the approximate turntable angle and antenna height for each frequency.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range:  $-180^\circ$  to  $180^\circ$
- Turntable step size:  $45^\circ$
- Height variation range: 1 – 4 m
- Height variation step size: 0.5 m
- Polarisation: horizontal + vertical

After this step the EMI test system has determined the following values for each frequency (of step 1):

- Frequency
- Azimuth value (of turntable)
- Antenna height

The last two values have now the following accuracy:

- Azimuth value (of turntable):  $45^\circ$
- Antenna height: 0.5 m

### Step 3: final measurement

In this step the accuracy of the turntable azimuth and antenna height will be improved.

This is necessary to find out the maximum value of every frequency.

For each frequency, which was determined the turntable azimuth and antenna height will be adjusted. The turntable azimuth will be slowly varied by  $\pm 22.5^\circ$  around this value. During this action the value of emission is continuously measured. The turntable azimuth at the highest emission will be recorded and adjusted. In this position the antenna height is also slowly varied by  $\pm 25$  cm around the antenna height determined. During this action the value of emission is also continuously measured. The antenna height of the highest emission will also be recorded and adjusted.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range:  $-22.5^\circ$  to  $+ 22.5^\circ$  around the determined value
- Height variation range: -0.25m to  $+ 0.25$ m around the determined value

### Step 4: final measurement with QP detector

With the settings determined in step 3, the final measurement will be performed:



EMI receiver settings for step 4:

- Detector: Quasi-Peak(< 1 GHz)
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 1 s

**3. Measurement above 1 GHz**

The following modifications apply to the measurement procedure for the frequency range above 1 GHz:

The Equipment Under Test (EUT) was set up on a non-conductive support at 1.4 m height in the fully-anechoic chamber. The measurement distance was reduced to 1 m. The results were extrapolated by the extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements, inverse linear-distance squared for the power reference level measurements). Due to the fact that in this frequency range a double ridged wave guided horn antenna (up to 18 GHz) and a horn antenna (18–25 GHz) are used, the steps 2-4 are omitted. Step 1 was performed with one height of the receiving antenna only.

EMI receiver settings:

- Detector: Peak, Average
- IF Bandwidth = 1 MHz

After the measurement a plot will be generated which contains a diagram with the results of the preliminary scan and a chart with the frequencies and values of the results of the final measurement.

For the data rate in mode n the test is performed as worst-case-check in order to verify that emissions have a comparable level as found at modes b and g. Typically, the measurement is performed in the frequency range 1 to 8 GHz but it depends on the emissions found during the test for the modes b and g. Please refer to the results for the used frequency range.

**3.4.2 Test Requirements / Limits**

FCC Part 15, Subpart C, §15.247 (d)

... In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limit(dBµV/m @10m)
0.009 – 0.49	2400/F(kHz)	300	Limit (dBµV/m) + 30 dB
0.49 – 1.705	24000/F(kHz)	30	Limit (dBµV/m) + 10 dB
1.705 – 30	30	30	Limit (dBµV/m) + 10 dB

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limit (dBµV/m)
30 – 88	100	3	40.0
88 – 216	150	3	43.5
216 – 960	200	3	46.0
above 960	500	3	54.0

§15.35(b)

..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: Limit (dBµV/m) = 20 log (Limit (µV/m)/1µV/m)

### 3.4.3 Test Protocol

Temperature: 24°C  
 Air Pressure: 1001 hPa  
 Humidity: 36 %

#### 3.4.3.1 Measurement up to 30 MHz

Op. Mode	Setup	Port
op-mode 1	Setup_02	Enclosure

Antenna Position	Frequency MHz	Corrected value dB $\mu$ V/m		Limit dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin to limit dB	Margin to limit dB
		PK	AV	PK	AV	PK	AV
0°	–	–	–	–	–	–	–
90°	–	–	–	–	–	–	–

Remark: No (further) spurious emissions in the range 20 dB below the limit found therefore step 2 was not performed.

#### 3.4.3.2 Measurement above 30 MHz

Op. Mode	Setup	Port
op-mode 1	Setup_01/Setup_03	Enclosure

Polarisation	Frequency MHz	Corrected value dB $\mu$ V/m			Limit dB $\mu$ V/m	Limit dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin to limit dB	Margin to limit dB
		QP	PK	AV	QP	PK	AV	QP/PK	AV
Hor. + Vert.	2873.5	–	52.1	43.4	–	74.0	54.0	21.9	10.6
	4805.0	–	49.2	41.8	–	74.0	54.0	24.8	12.2

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

Op. Mode	Setup	Port
op-mode 2	Setup_01/Setup_03	Enclosure

Polarisation	Frequency MHz	Corrected value dB $\mu$ V/m			Limit dB $\mu$ V/m	Limit dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin to limit dB	Margin to limit dB
		QP	PK	AV	QP	PK	AV	QP/PK	AV
Hor. + Vert.	4877.5	–	45.4	37.2	–	74.0	54.0	28.6	16.8
	7312.5	–	50.3	41.4	–	74.0	54.0	23.7	12.6

Remark: No (further) spurious emissions in the range 20 dB below the limit found.



**Op. Mode**      **Setup**                      **Port**  
 op-mode 3      Setup\_01/Setup\_03      Enclosure

Polarisation	Frequency MHz	Corrected value dBµV/m			Limit dBµV /m	Limit dBµV /m	Limit dBµV /m	Margin to limit dB	Margin to limit dB
		QP	PK	AV	QP	PK	AV	QP/PK	AV
Hor. + Vert.	4955.0	–	51.2	44.0	–	74.0	54.0	22.8	10.0
	7436.0	–	48.5	39.0	–	74.0	54.0	25.5	15.0

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

### 3.4.4 Test result: Spurious radiated emissions

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 2	passed
	op-mode 3	passed



### 3.5 Band edge compliance

**Standard** FCC Part 15, 10-1-11 Subpart C

**The test was performed according to:** ANSI C63.4–2009, FCC §15.31

#### 3.5.1 Test Description

The procedure to show compliance with the band edge requirement is divided into two measurements:

1. Show compliance of the lower and higher band edge by a conducted measurement

For the conducted measurement, the Equipment Under Test (EUT) is placed in a shielded room. The EUT is set to transmit on the lowest channel (2412 MHz). The lower band edge is 2400 MHz and the EUT is set to transmit on the highest channel (2462 MHz). The higher band edge is 2483.5 MHz.

Analyzer settings for conducted measurement:

- Detector: Peak
- RBW / VBW = 100 / 300 kHz

2. Show compliance of the higher band edge falls in to restricted bands by a radiated measurement.

The radiated emissions measurements are performed in a typical installation configuration inside the fully anechoic chamber using a horn antenna at 1 m distance.

EMI receiver settings for radiated measurement:

- Detector: Peak, Average
- IF Bandwidth = 1 MHz

#### 3.5.2 Test Requirements / Limits

FCC Part 15.247 (d)

"In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. ...

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c))."

For the conducted measurement the RF power at the band edge shall be "at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power..."

For the radiated measurement of the higher band edge connected to a restricted band the limit is "specified in Section 15.209(a)".



### 3.5.3 Test Protocol

#### 3.5.3.1 Lower band edge

##### Conducted measurement

Temperature: 22 °C  
Air Pressure: 1020 hPa  
Humidity: 42 %

Op. Mode	Setup	Port
op-mode 1	Setup_01	Int.ant.connector

Frequency MHz	Measured value dBm	Reference value dBm	Limit dBm	Margin to limit dB
2400.00	-30.9	2.5	-17.5	13.4

Remark: Please see annex for the measurement plot.

#### 3.5.3.2 Higher band edge

##### Conducted measurement

Temperature: 22 °C  
Air Pressure: 1020 hPa  
Humidity: 42 %

Op. Mode	Setup	Port
op-mode 3	Setup_01	Int.ant.connector

Frequency MHz	Measured value dBm	Reference value dBm	Limit dBm	Margin to limit dB
2483.50	-45.0	0.4	-19.6	25.4

Remark: Please see annex for the measurement plot.



**Radiated measurement**

Temperature: 24 °C  
 Air Pressure: 1001 hPa  
 Humidity: 36 %

Op. Mode	Setup	Port
op-mode 3	Setup_01	Enclosure

Frequency MHz	Polarisation	Corrected value dBµV/m		Limit dBµV/m		Margin to limit dB	
		PK	AV	PK	AV	PK	AV
2483.50	Hor. + Vert.	60.5	49.4	74.0	54.0	13.6	4.6

Remark: Please see annex for the measurement plot.

**3.5.4 Test result: Band edge compliance**

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 3	passed





### **3.6 Power density**

**Standard** FCC Part 15, 10-1-11 Subpart C

**The test was performed according to:** FCC §15.31

#### **3.6.1 Test Description**

The EUT was connected to spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Detector: Peak-Maxhold
- Resolution Bandwidth (RBW): 3 kHz
- Video Bandwidth (VBW): 30 kHz
- Sweep Time: Coupled

#### **3.6.2 Test Requirements / Limits**

FCC Part 15, Subpart C, §15.247 (e)

For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

...

The same method of determining the conducted output power shall be used to determine the power spectral density.

### 3.6.3 Test Protocol

Temperature: 22 °C  
 Air Pressure: 1020 hPa  
 Humidity: 42 %

Op. Mode	Setup	Port
op-mode 1	Setup_01	Int.ant.connector

Power density dBm/3 kHz	Remarks
-10.17	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 2	Setup_01	Int.ant.connector

Power density dBm/3 kHz	Remarks
-11.38	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 3	Setup_01	Int.ant.connector

Power density dBm/3 kHz	Remarks
-12.71	-

Remark: Please see annex for the measurement plot.

### 3.6.4 Test result: Power density

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 1	passed
	op-mode 2	passed
	op-mode 3	passed

## 4 Test Equipment

The calibration, hardware and software states are shown for the testing period.

### Test Equipment Anechoic Chamber

<b>Lab ID:</b>	<b>Lab 1</b>
<b>Manufacturer:</b>	Frankonia
<b>Description:</b>	Anechoic Chamber for radiated testing
<b>Type:</b>	10.58x6.38x6.00 m <sup>3</sup>

### Single Devices for Anechoic Chamber

Single Device Name	Type	Serial Number	Manufacturer
Air compressor	none	-	Atlas Copco
Anechoic Chamber	10.58 x 6.38 x 6.00 m <sup>3</sup>	none	Frankonia
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	FCC listing 96716 3m Part15/18		2011/01/11   2014/01/10
	IC listing 3699A-1 3m		2011/02/07   2014/02/06
Controller Maturo	MCU	961208	Maturo GmbH
EMC camera	CE-CAM/1	-	CE-SYS
EMC camera Nr.2	CCD-400E	0005033	Mitsubishi
Filter ISDN	B84312-C110-E1		Siemens&Matsushita
Filter Universal 1A	BB4312-C30-H3	-	Siemens&Matsushita

### Test Equipment Auxiliary Equipment for Radiated emissions

<b>Lab ID:</b>	<b>Lab 1</b>
<b>Description:</b>	Equipment for emission measurements
<b>Serial Number:</b>	see single devices

### Single Devices for Auxiliary Equipment for Radiated emissions

Single Device Name	Type	Serial Number	Manufacturer
Antenna mast	AS 620 P	620/37	HD GmbH
Biconical dipole	VUBA 9117	9117-108	Schwarzbeck
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2008/10/27   2013/10/26
	Standard Calibration		2012/01/18   2015/01/17
Broadband Amplifier 18MHz-26GHz	JS4-18002600-32-5P	849785	Miteq
	Path Calibration		2012/05/24   2012/11/23
Broadband Amplifier 1GHz-4GHz	AFS4-01000400-1Q-10P-4	-	Miteq
	Path Calibration		2012/05/24   2012/11/23
Broadband Amplifier 30MHz-18GHz	JS4-00101800-35-5P	896037	Miteq
	Path Calibration		2012/05/24   2012/11/23
Cable "ESI to EMI Antenna"	EcoFlex10	W18.01-2+W38.01-2	Kabel Kusch
	Path Calibration		2012/05/24   2012/11/23
Cable "ESI to Horn Antenna"	UFB311A+UFB293C	W18.02-2+W38.02-2	Rosenberger Micro-Coax
	Path Calibration		2012/05/24   2012/11/23

**Single Devices for Auxiliary Equipment for Radiated emissions (continued)**

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>	
	Path Calibration		2012/05/24	2012/11/23
Double-ridged horn	HF 906	357357/001	Rohde & Schwarz GmbH & Co. KG	
	Standard Calibration		2012/05/18	2015/05/17
Double-ridged horn	HF 906	357357/002	Rohde & Schwarz GmbH & Co. KG	
	Standard Calibration		2012/06/26	2015/06/25
High Pass Filter	4HC1600/12750-1.5-KK Path Calibration	9942011	Trilithic	2012/11/23
High Pass Filter	5HC2700/12750-1.5-KK Path Calibration	9942012	Trilithic	2012/11/23
High Pass Filter	5HC3500/12750-1.2-KK Path Calibration	200035008	Trilithic	2012/11/23
High Pass Filter	WHKX 7.0/18G-8SS Path Calibration	09	Wainwright	2012/11/23
Horn Antenna Schwarzbeck 15-26 GHz BBHA 9170	BBHA 9170			
Log.-per. Antenna	HL 562 Ultralog	830547/003	Rohde & Schwarz GmbH & Co. KG	
Loop Antenna	HFH2-Z2	829324/006	Rohde & Schwarz GmbH & Co. KG	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Standard calibration		2011/10/27	2014/10/26
Pyramidal Horn Antenna 26,5 GHz	3160-09	00083069	EMCO Elektronik GmbH	
Pyramidal Horn Antenna 40 GHz	3160-10	00086675	EMCO Elektronik GmbH	
Tilt device Maturo (Rohacell)	Antrieb TD1.5-10kg	TD1.5- 10kg/024/3790709	Maturo GmbH	



**Test Equipment Auxiliary Test Equipment**

**Lab ID:** Lab 1  
**Manufacturer:** see single devices  
**Description:** Single Devices for various Test Equipment  
**Type:** various  
**Serial Number:** none

**Single Devices for Auxiliary Test Equipment**

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>	
Broadband Power Divider N (Aux)	1506A / 93459	LM390	Weinschel Associates	
Broadband Power Divider SMA	WA1515	A855	Weinschel Associates	
Digital Multimeter 03 (Multimeter)	Fluke 177	86670383	Fluke Europe B.V.	
	<i>Calibration Details</i>		<i>Last Execution</i>	<i>Next Exec.</i>
	Customized calibration		2011/10/19	2013/10/18
Fibre optic link Satellite (Aux)	FO RS232 Link	181-018	Pontis	
Fibre optic link Transceiver (Aux)	FO RS232 Link	182-018	Pontis	
Isolating Transformer	LTS 604	1888	Thalheimer Transformatorenwerke GmbH	
Notch Filter Ultra Stable (Aux)	WRCA800/960-6EEK	24	Wainwright	
Vector Signal Generator	SMIQ 03B	832492/061	Rohde & Schwarz GmbH & Co.KG	



## Test Equipment Digital Signalling Devices

**Lab ID:** Lab 1  
**Description:** Signalling equipment for various wireless technologies.

### Single Devices for Digital Signalling Devices

Single Device Name	Type	Serial Number	Manufacturer
Bluetooth Signalling Unit CBT CBT		100589	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2011/11/24    2014/11/23
CMW500	CMW500	107500	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Initial factory calibration		2012/01/26    2014/01/25
	Firmware: V.2.01.25		2012/07/03    2012/10/29
	3G: KC42x 11.48.02, 12.16.00 LTE: KC501 1.7.0 up to 2.0.0, KC503 1.7.2 up to 2.0.0, KC506 1.9.8 up to 2.0.0, KC507 1.7.0, KC508 1.8.5 up to 2.0.0, KC551 1.4.9 up to 2.0.0, KC553 1.7.0 up to 2.0.0, KC556 2.0.0, KC571 1.8.5 up to 2.0.0, KC572 1.8.5 up to 2.0.0 --- Firmware: V.2.01.25 3G : KC42x 12.23.00 LTE: KC501 1.7.0 up to 2.0.0, KC503 1.7.2 up to 2.0.0, KC506 1.9.8 up to 2.0.0, KC507 1.7.0, KC508 1.8.5 up to 2.0.0, KC551 1.4.9 up to 2.0.0, KC553 1.7.0 up to 2.0.0, KC556 2.0.0, KC571 1.8.5 up to 2.0.0, KC572 1.8.5 up to 2.0.0 --- Firmware: V.3.00.11 LTE: KC501 2.2.0, KC503 2.2.0, KC506 2.2.0, KC508 2.2.0, KC551 2.2.0, KC553 2.2.0, KC556 2.2.0, KC571 2.2.0, KC572 2.2.0 ---		2012/10/29
Universal Radio Communication Tester	CMU 200	102366	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2011/05/26    2013/05/25
	<i>HW/SW Status</i>		<i>Date of Start</i> <i>Date of End</i>
	Hardware: B11, B21V14, B21-2, B41, B52V14, B52-2, B53-2, B56V14, B68 3v04, PCMCIA, U65V04 Software: K21 4v21, K22 4v21, K23 4v21, K24 4v21, K42 4v21, K43 4v21, K53 4v21, K56 4v22, K57 4v22, K58 4v22, K59 4v22, K61 4v22, K62 4v22, K63 4v22, K64 4v22, K65 4v22, K66 4v22, K67 4v22, K68 4v22, K69 4v22 Firmware: µP1 8v50 02.05.06 ---		2007/07/16
Universal Radio Communication Tester	CMU 200	837983/052	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2011/12/07    2014/12/06
	<i>HW/SW Status</i>		<i>Date of Start</i> <i>Date of End</i>



**Single Devices for Digital Signalling Devices (continued)**

Single Device Name	Type	Serial Number	Manufacturer
	HW options: B11, B21V14, B21-2, B41, B52V14, B52-2, B53-2, B54V14, B56V14, B68 3v04, B95, PCMCIA, U65V02 SW options: K21 4v11, K22 4v11, K23 4v11, K24 4v11, K27 4v10, K28 4v10, K42 4v11, K43 4v11, K53 4v10, K65 4v10, K66 4v10, K68 4v10, Firmware: µP1 8v40 01.12.05 ---		2007/01/02
	SW: K62, K69		2008/11/03

**Test Equipment Emission measurement devices**

**Lab ID:** Lab 1  
**Description:** Equipment for emission measurements  
**Serial Number:** see single devices

**Single Devices for Emission measurement devices**

Single Device Name	Type	Serial Number	Manufacturer
Personal Computer	Dell	30304832059	Dell
Power Meter	NRVD	828110/016	Rohde & Schwarz GmbH & Co.KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2012/05/22 2013/05/21
Sensor Head A	NRV-Z1	827753/005	Rohde & Schwarz GmbH & Co.KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2012/05/21 2013/05/20
Signal Generator	SMR 20	846834/008	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	standard calibration		2011/05/12 2014/05/11
Spectrum Analyzer	ESIB 26	830482/004	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2011/12/05 2013/12/04
	<i>HW/SW Status</i>		<i>Date of Start</i> <i>Date of End</i>
	Firmware-Update 4.34.4 from 3.45 during calibration		2009/12/03

**Test Equipment Multimeter 12**

**Lab ID:** Lab 2  
**Description:** Ex-Tech 520  
**Serial Number:** 05157876

**Single Devices for Multimeter 12**

Single Device Name	Type	Serial Number	Manufacturer
Digital Multimeter 12 (Multimeter)	EX520	05157876	Extech Instruments Corp.
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Customized calibration		2011/10/18 2013/10/17



**Test Equipment Shielded Room 07**

**Lab ID:** Lab 2  
*Description:* Shielded Room 4m x 6m

**Test Equipment T/H Logger 04**

**Lab ID:** Lab 2  
*Description:* Luft Opus10  
*Serial Number:* 7481

**Single Devices for T/H Logger 04**

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>
ThermoHygro DataloggerOpus10 THI (8152.00) 04 (Environ)		7481	Lufft Mess- und Regeltechnik GmbH

**Test Equipment Temperature Chamber 01**

**Lab ID:** Lab 2  
*Manufacturer:* see single devices  
*Description:* Temperature Chamber KWP 120/70  
*Type:* Weiss  
*Serial Number:* see single devices

**Single Devices for Temperature Chamber 01**

<i>Single Device Name</i>	<i>Type</i>	<i>Serial Number</i>	<i>Manufacturer</i>	<i>Last Execution</i>	<i>Next Exec.</i>
Temperature Chamber Weiss 01	KWP 120/70	59226012190010	Weiss Umwelttechnik GmbH		
	<i>Calibration Details</i>				
	Customized calibration			2012/03/12	2014/03/11





**Test Equipment WLAN RF Test Solution**

**Lab ID:** Lab 2  
**Manufacturer:** 7 layers AG  
**Description:** Regulatory WLAN RF Tests  
**Type:** WLAN RF  
**Serial Number:** 001


**Single Devices for WLAN RF Test Solution**

Single Device Name	Type	Serial Number	Manufacturer	
Arbitrary Waveform Generator	TGA12101	284482		
Power Meter NRVD	NRVD Standard Calibration	832025/059	2012/07/23	2013/07/22
Power Sensor NRV Z1 A	PROBE Standard Calibration	832279/013	2012/07/23	2013/07/22
Power Supply	NGSM 32/10 <i>Calibration Details</i> Standard Calibration	2725	<i>Last Execution</i> 2011/06/15	<i>Next Exec.</i> 2013/06/14
Rubidium Frequency Normal MFS	Datum MFS Standard Calibration	002	Datum GmbH	2012/08/20 2013/08/19
Signal Analyser FS1Q26	1119.6001.26	832695/007	Rohde & Schwarz GmbH & Co.KG	
Spectrum Analyser	FSU26 Standard calibration <i>HW/SW Status</i>	100136	Rohde & Schwarz GmbH & Co.KG	2012/06/20 2013/06/19
	FSU FW Update to v4.61 SP3, K5 v4.60 and K73 v4.61		2011/12/05	
Spectrum Analyser	FSU3 Standard calibration <i>HW/SW Status</i>	200046	Rohde & Schwarz GmbH & Co.KG	2012/05/15 2013/05/14
	Firmware Version 4.51 SP1 Option FS-K72 4.50 SP1 Option FS-K73 4.50 SP1		2011/12/07	
TOCT Switching Unit	Switching Unit	030106	7 layers, Inc.	
Vector Signal Generator SMIQ03B	SMIQ03B <i>Calibration Details</i> Standard Calibration	832870/017	<i>Last Execution</i> 2010/06/23	<i>Next Exec.</i> 2013/06/20

## 5 Photo Report

Photos are included in an external report.

## 6 Setup Drawings



Remark: Depending on the frequency range suitable antenna types, attenuators or preamplifiers are used.

**Drawing 1:** Setup in the Anechoic chamber:  
Measurements below 1 GHz: Semi-anechoic, conducting ground plane.  
Measurements above 1 GHz: Fully-anechoic, absorbers on all surfaces.



## 7 FCC and IC Correlation of measurement requirements

The following tables show the correlation of measurement requirements for WLAN equipment and Digital Apparatus from FCC and IC standards.

### WLAN equipment

Measurement	FCC reference	IC reference
Conducted emissions on AC mains	§ 15.207	RSS-Gen: 7.2.4
Occupied bandwidth	§ 15.247 (a) (1)	RSS-210: A8.1
Peak power output	§ 15.247 (b) (1)	RSS-210: A8.4
Spurious RF conducted emissions	§ 15.247 (d)	RSS-Gen: 6; RSS-210: A8.5
Spurious radiated emissions	§ 15.247 (d)	RSS-Gen: 6; RSS-210: A8.5
Band edge compliance	§ 15.247 (d)	RSS-210: A8.5
Power density	§ 15.247 (e)	RSS-210: A8.2 (b)
Antenna requirement	§ 15.203 / 15.204	RSS-Gen: 7.1.2

### Digital Apparatus

Measurement	FCC reference	IC reference
Conducted Emissions (AC Power Line)	§ 15.107	ICES-003
Spurious Radiated Emissions	§ 15.109	ICES-003




## 8 Annex measurement plots

### 8.1 Occupied bandwidth

#### Op. Mode

op-mode 1



Title: 6dB Bandwidth


Comment A: CH B: 2403 MHz; 6dB bandwidth (kHz):1932

Date: 7.JAN.2013 13:53:51



**Op. Mode**

op-mode 2




Title: 6dB Bandwidth  
 Comment A: CH M: 2438 MHz; 6dB bandwidth (kHz):1812  
 Date: 7.JAN.2013 10:45:50



**Op. Mode**

op-mode 3




Title: 6dB Bandwidth  
 Comment A: CH T: 2478 MHz; 6dB bandwidth (kHz):1992  
 Date: 7.JAN.2013 11:19:57

## 8.2 Peak power output

### Op. Mode


op-mode 1



Date: 7.JAN.2013 13:25:21

**Op. Mode**

op-mode 2




Date: 7.JAN.2013 13:26:18



**Op. Mode**

op-mode 3



Date: 7.JAN.2013 13:27:10




### 8.3 Band edge compliance conducted and Spurious RF conducted emissions

#### 8.3.1 Band edge compliance conducted

##### Op. Mode

op-mode 1




Title: Band Edge Compliance  
 Comment A: CH B: 2403 MHz  
 Date: 7.JAN.2013 13:57:12



**Op. Mode**

op-mode 3




Title: Band Edge Compliance  
 Comment A: CH T: 2478 MHz  
 Date: 7.JAN.2013 11:37:14



### 8.3.2 Spurious RF conducted emission

#### Op. Mode

op-mode 1




Title: spurious emissions  
 Comment A: CH B: 2403 MHz  
 Date: 7.JAN.2013 14:08:59



### Op. Mode


op-mode 2



Title: spurious emissions  
 Comment A: CH M: 2438 MHz  
 Date: 7.JAN.2013 11:14:44

## Op. Mode

op-mode 3




Title: spurious emissions  
 Comment A: CH T: 2478 MHz  
 Date: 7.JAN.2013 11:52:30

### 8.3.3 Band edge compliance radiated

**Op. Mode**      **higher band edge**

op-mode 3




Radiated measurement (higher band edge)



## 8.4 Power density

### Op. Mode

op-mode 1




Title: Power Density  
Comment A: CH B: 2403 MHz;  
Date: 7.JAN.2013 13:50:12





Op. Mode

op-mode 2




Title: Power Density  
Comment A: CH M: 2438 MHz;  
Date: 7.JAN.2013 11:01:20



Op. Mode

op-mode 3



Title: Power Density  
Comment A: CH T: 2478 MHz;  
Date: 7.JAN.2013 11:35:38