

RF Exposure / MPE Calculation

No. : 10184498H

Applicant : Mitsubishi Electric Corporation Sanda Works
Type of Equipment : Display Audio
Model No. : NR-244UH, NR-245UH
FCC ID : UJHNR244245BTWL

Mitsubishi Electric Corporation Sanda Works declares that Model : NR-244UH, NR-245UH complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "NR-244UH, NR-245UH" as calculated from (B) Limits for General Population / Uncontrolled Exposure of TABLE 1- LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) of §1.1310 Radiofrequency radiation exposure limits.

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 0.31 mW (Maximum average output power)
G = 1.03 Numerical Antenna gain; equal to 0.11 dBi
r = 20.0 cm

For: NR-244UH, NR-245UH

S = 0.00006 mW/cm²

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124