

IQ3 Mini

P2336

IQ3M0B1

Antennas

Version	Date	Changes	Author
1.0	21/02/2023	First edition	M.U.

Table of contents


1	IQ3M0B1	3
	Bluetooth LE Antenna	3
	Wi-Fi Antenna	4
Annex I	5
Annex II	12

1 IQ3M0B1

IQ3 Mini P2336		IQ3M0B1
		BLE (1) + Wi-Fi (2)
Antennas	Number of antennas	2
	Manufacturer	1- N/A 2- N/A
	Model number	1- N/A 2- N/A
	Type	1- Integral, Chip 2- Integral, Chip
	Gain	1- 1.5 dBi 2- 3.0 dBi
	Frequency of Operation	1- 2400 - 2483.5 MHz 2- 2400 - 2483.5 MHz
Channels	Number of channels	1- 40 2- IEEE 802.11b/g/n standard
	Spacing	1- 2 MHz 2- IEEE 802.11b/g/n standard
	Bandwith	1- 2 MHz 2- IEEE 802.11b/g/n standard
Type of Modulation		1- GFSK 2- IEEE 802.11b/g/n standard
Declared Nominal Output Power (Max.)		1- 6 dBm 2- 15 dBm
ITU Emission Designator		1- F1D 2- IEEE 802.11b/g/n standard
Equipment Configuration for frequency Stability: Data Rate		1- 1 Mbit/s 2- IEEE 802.11b/g/n standard
Equipment Configuration for Field Strenght Measurement: Data Rate		1- 1 Mbit/s 2- IEEE 802.11b/g/n standard

Bluetooth LE Antenna


The Bluetooth LE antenna is the 2450AT18D0100 model from Johanson Technology. The antenna is located on the top side of the control circuit, 226571. The following image shows the location of the antenna on the control circuit.



The remaining technical information of the antenna is described in the datasheet attached in Annex I.

Wi-Fi Antenna

The antenna used for Wi-Fi is a built-in antenna integrated in the NINA-W156-03B certified module from u-blox. The module is located on the top of the 226571 circuit. The following image shows the location and dimensions of the module.



The remaining technical information of the antenna is described in the datasheet attached in Annex II.

Annex I

High Frequency Ceramic Solutions

AEC-Q200 Qualification Available

2.45 GHz SMD Antenna, EIA 1206, Detuning resilient, Edge Mount Design **New Global P/N 2450AT18D0100001**
Legacy P/N 2450AT18D0100


Detail Specification: 8/24/2022

Page 1 of 7

Let us help you with the antenna design, optimization, and tuning!

General Specifications	
New Global Part Number	2450AT18D0100001
Frequency (GHz)	2.4 - 2.5
Peak Gain (dBi)	1.5 typ. (XZ-total)
Average Gain (dBi)	-1.0 typ. (XZ-total)
Radiated Efficiency ¹	72%
Return Loss (dB)	10 min.
Impedance (Ω)	50
Input Power (W)	3 max. (CW)
Operating Temperature	-40 to +125°C
Recommended Storage Conditions and Period for unused Product on T&R	+5 to +35°C Humidity 45 - 75% RH 18 months max.
Reel Quantity (pcs./reel)	3,000

<https://www.johansontechnology.com/ask-a-question>



¹Efficiency measured on Johanson's evaluation board PN 2450AT18D0100001CE1

Part Number Explanation (See last page for more info on new and legacy part numbers)			
P/N Suffix	Packing Style	Bulk (loose pcs.)	Suffix = B e.g. 2450AT18D0100001B
		T & R	Suffix = E e.g. 2450AT18D0100001E
		100% Tin	Suffix = None e.g. 2450AT18D0100001(B or S)
	Evaluation Board	2450AT18D0100001CE1	

Mechanical Dimensions		
	In	mm
L	0.126 ± 0.008	3.20 ± 0.2
W	0.063 ± 0.008	1.60 ± 0.2
T	0.047 ± 0.004	1.20 ± 0.1
a	0.012 +0.004 / -0.008	0.30 +0.1 / -0.2
b	0.020 ± 0.008	0.50 ± 0.2

Terminal Configuration		
No.	Function 1	Function 2
1	FEED	GND
2	GND	GND
3	GND	GND
4	GND	FEED

Function 1: Antenna fed from left
 Function 2: Antenna fed from right

Johanson Technology, Inc. reserves the right to make design changes without notice.
 All sales are subject to Johanson Technology, Inc. terms and conditions.





<https://www.johansontechnology.com>
 4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821
 Ver. 4.4 2021 Johanson Technology, Inc. All Rights Reserved

High Frequency Ceramic Solutions

2.45 GHz SMD Antenna, EIA 1206, Detuning resilient, Edge Mount Design **New Global P/N 2450AT18D0100001**
Legacy P/N 2450AT18D0100
 Detail Specification: 8/24/2022 Page 2 of 7

Mounting Considerations 1: Evaluation Board (Standard Layout)



To order a pre-tuned 50Ω EVB with a female SMA connector click here:
<https://www.johansontechnology.com/request-a-sample>
 Reference p/n: 2450AT18D0100001CE1

Johanson Technology, Inc. reserves the right to make design changes without notice.
 All sales are subject to Johanson Technology, Inc. terms and conditions.




<https://www.johansontechnology.com>
 4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821
 Ver. 4.4 2021 Johanson Technology, Inc. All Rights Reserved

High Frequency Ceramic Solutions

2.45 GHz SMD Antenna, EIA 1206, Detuning resilient, Edge Mount Design **New Global P/N 2450AT18D0100001**
 Legacy P/N 2450AT18D0100
 Detail Specification: 8/24/2022 Page 3 of 7

Mounting Considerations 1: Electrical Performance @25°C



Would you like the antenna layout? Have antenna tuning issues?
 Please contact us if you have any questions regarding the implementation of this antenna in your PCB's layout. We'll be happy to guide you to maximize the antenna's performance.
 Contact our applications engineers at:
<https://www.johansontechnology.com/ask-a-question>

Johanson Technology, Inc. reserves the right to make design changes without notice.
 All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821


Ver. 4.4

2021 Johanson Technology, Inc. All Rights Reserved

High Frequency Ceramic Solutions

2.45 GHz SMD Antenna, EIA 1206, Detuning resilient, Edge Mount Design	New Global P/N 2450AT18D0100001 Legacy P/N 2450AT18D0100
Detail Specification: 8/24/2022	Page 4 of 7

Mounting Considerations 1: Typical 2D radiation patterns @ 2.44GHz



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.




<https://www.johansontechnology.com>
 4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821
 Ver. 4.4 2021 Johanson Technology, Inc. All Rights Reserved

High Frequency Ceramic Solutions


2.45 GHz SMD Antenna, EIA 1206, Detuning resilient, Edge Mount Design **New Global P/N 2450AT18D0100001**
 Legacy P/N 2450AT18D0100
 Detail Specification: 8/24/2022 Page 5 of 7

Mounting Considerations 2: Small Clearance or "Thin edge" Applications*

Frequency (GHz)	Peak Gain (dBi)	Average Gain (dBi)	Radiated Efficiency (%)
2.45	0.3 (XZ-plane)	-3.6 (XZ-plane)	66



Mounting Considerations 3: "Thin edge" application on circular PCB



Johanson Technology, Inc. reserves the right to make design changes without notice.
 All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 4.4

2021 Johanson Technology, Inc. All Rights Reserved

High Frequency Ceramic Solutions

2.45 GHz SMD Antenna, EIA 1206, Detuning resilient, Edge Mount Design **New Global P/N 2450AT18D0100001**
 Legacy P/N 2450AT18D0100
 Detail Specification: 8/24/2022 Page 6 of 7

Mounting Considerations 4: Fed from Right Side*

(Feeding the antenna from the right will have no impact on antenna performance)

Solder Resist

Land

Units in mm

*Evaluation board not available

Would you like the layout file of the above? Have antenna tuning issues?
 Please contact us if you have any questions regarding the implementation of this antenna in your PCB's layout. We'll be happy to guide you to maximize the antenna's performance.
 Contact our applications engineers at:
<https://www.johansontechnology.com/ask-a-question>

Johanson Technology, Inc. reserves the right to make design changes without notice.
 All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 4.4

2021 Johanson Technology, Inc. All Rights Reserved

High Frequency Ceramic Solutions

2.45 GHz SMD Antenna, EIA 1206, Detuning resilient, Edge Mount Design
 Detail Specification: 8/24/2022

New Global P/N 2450AT18D0100001
 Legacy P/N 2450AT18D0100

Page 7 of 7

Antenna tuning, optimization, and validation services:

<https://www.johansontechnology.com/ipc-antenna-services>

For more antennas and to download measured S-parameters, go to:

<https://www.johansontechnology.com/antennas>

Soldering Information

<https://www.johansontechnology.com/ipcsoldering-profile>

MSL Info

<https://www.johansontechnology.com/msl-rating>

Packaging Information

<https://www.johansontechnology.com/tape-reel-packaging>

For layout review contact our applications team at:

<https://www.johansontechnology.com/ask-a-question>

RoHS Compliance

<https://www.johansontechnology.com/rohs-compliance>

Recommended Storage Condition and Max Shelf Life

<https://www.johansontechnology.com/recommended-storage-conditions>

Johanson's New Global Part Number Schema

Johanson has instituted a new Global Part Numbering (GPN) system. **Only the part number is changing.** The parts are produced with the exact same materials, manufacturing processes, manufacturing controls, dimensions, physical attributes and testing as the parts supplied with the legacy part numbers.

A database for part number crosses can be accessed at:

<https://www.johansontechnology.com/pn-search>

Johanson Technology, Inc. reserves the right to make design changes without notice.
 All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 4.4

2021 Johanson Technology, Inc. All Rights Reserved