

Test report No:
NIE: 53898RAN.007

Assessment report

FCC 47 CFR Part 2.1091
ISED RSS-102 Issue 5:2015

| | |
|---|--|
| Identification of item tested | Electronic Lock Series including all mechanical variants |
| Trademark | XS4 Original |
| Model and /or type reference | W0S |
| Other identification of the product | FCC ID: UKCW0B IC: 10088A-W0B |
| Features | Not provided data |
| Applicant | SALTO Systems, S.L. Arkotz 9, Polígono Lanbarren 20180, Oiartzun, Gipuzkoa, SPAIN |
| Test method requested, standard | FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) |
| Summary | IN COMPLIANCE |
| Approved by (name / position & signature) | Miguel Lacave Antennas Lab Manager |
| Date of issue | 2018-06-27 |
| Report template No | FAN24_01 |

Index

| | |
|---|----|
| Competences and guarantees | 3 |
| General conditions | 3 |
| Identification of the client..... | 3 |
| General description of the device under evaluation..... | 4 |
| Assessment summary..... | 5 |
| Appendix A: FCC RF Exposure..... | 6 |
| FCC RF Exposure evaluation for mobile devices..... | 7 |
| FCC MPE Evaluation Results..... | 8 |
| Appendix B: ISED RF Exposure..... | 12 |
| ISED RF Exposure evaluation for mobile devices..... | 13 |
| ISED MPE Evaluation Results..... | 14 |

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This assessment report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA and the Accreditation Bodies.

Identification of the client

SALTO Systems, S.L.

Arkotz 9, Polígono Lanbarren

20180, Oiartzun, Gipuzkoa, SPAIN

General description of the device under evaluation

The device under evaluation consists of an electronic lock series, with different model variants, which uses the same main board and can support NFC and Bluetooth Smart technologies. The electronic and batteries will be installed inside the door. During its normal use the separation distance between the antenna and the user will be greater than 20 cm.

| Model | Supported Features | | |
|------------------|--------------------|---------------|----------------------------|
| | NFC ISO 14443-A | NFC ISO 15693 | Bluetooth Smart Direct Key |
| XS4 Original W0S | Yes | Yes | Yes |

Table 1: Supported features

The equipment specifications declared by the manufacturer for each supported feature are:

| Band (MHz) | Technology | Maximum RF output power (dBm) | Maximum antenna gain (dBi) | Maximum radiated power (E.I.R.P.) (dBm) |
|---------------|------------|-------------------------------|----------------------------|---|
| 13.553-13.567 | NFC | 25.0 | N/A | 25.0 |
| 2402.0-2480.0 | Bluetooth | 2.8 | 0.5 | 3.3 |

Table 2: Equipment specifications

Assessment summary

| Radiofrequency radiation exposure limits | | | |
|--|------------|------------|---------------------|
| FCC 47 CFR § 2.1091 & ISED RSS-102 Issue 5 (2015-03) | | | |
| Assessment | Band (MHz) | Technology | VERDICT (Pass/Fail) |
| 1 | 13.5 | NFC | Pass |
| 2 | 2450 | Bluetooth | Pass |

Table 3: Assessment summary

Appendix A: FCC RF Exposure

FCC RF Exposure evaluation for mobile devices

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure | | | | |
| 0.3–3.0 | 614 | 1.63 | * 100 | 6 |
| 3.0–30 | 1842/f | 4.89/f | * 900/f ² | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1,500 | | | f/300 | 6 |
| 1,500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | * 100 | 30 |
| 1.34–30 | 824/f | 2.19/f | * 180/f ² | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1,500 | | | f/1500 | 30 |
| 1,500–100,000 | | | 1.0 | 30 |

f = frequency in MHz * = Plane-wave equivalent power density

FCC MPE Evaluation Results

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction:

$$\text{Power density: } S[mW / cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW / cm^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

R_{\min} = distance to the center of radiation of the antenna

Assessment 1 – NFC – 13.5 MHz Band

| | |
|---|--------|
| Maximum output power (dBm): | 25.0 |
| Maximum antenna Gain (dBi): | N/A |
| Minimum use distance (cm): | 20.0 |
| Worst Case Frequency (MHz): | 13.56 |
| Maximum EIRP (dBm): | 25.0 |
| Maximum EIRP (mW): | 316.23 |
| General population - Power density limit (mW/cm ²): | 0.98 |

Power density at minimum use distance:

| | |
|---|-------|
| Power density (mW/cm ²): | 0.063 |
| General population - Power density limit (mW/cm ²): | 0.98 |
| Verdict for general population: | PASS |

The power density level for this transmission mode is below general population exposure power density limit.

Minimum compliance distance for this technology:

| | |
|--|------|
| Minimum compliance distance for general population (cm): | 5.07 |
| Minimum use distance (cm): | 20.0 |
| Verdict for general population: | PASS |

The minimum use distance is greater than general population exposure minimum compliance distance.

Assessment 2 – Bluetooth Smart Direct Key – 2450 MHz Band

| | |
|---|--------|
| Maximum output power (dBm): | 2.8 |
| Maximum antenna Gain (dBi): | 0.5 |
| Minimum use distance (cm): | 20.0 |
| Worst Case Frequency (MHz): | 2402.0 |
| Maximum EIRP (dBm): | 3.3 |
| Maximum EIRP (mW): | 2.14 |
| General population - Power density limit (mW/cm ²): | 1.0 |

Power density at minimum use distance:

| | |
|---|--------|
| Power density (mW/cm ²): | 0.0004 |
| General population - Power density limit (mW/cm ²): | 1.0 |
| Verdict for general population: | PASS |

The power density level for this transmission mode is below general population exposure power density limit.

Minimum compliance distance for this technology:

| | |
|--|------|
| Minimum compliance distance for general population (cm): | 0.41 |
| Minimum use distance (cm): | 20.0 |
| Verdict for general population: | PASS |

The minimum use distance is greater than general population exposure minimum compliance distance.

Multiple frequencies assessment

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure toward the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less than unity:

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

Where

S_i is the power density of each source;

MPE_i is the power density basic restriction of each source.

This device is able to transmit simultaneously using NFC and Bluetooth Smart. The multiple frequencies calculation will be as follow:

$$\frac{0.063}{0.98} + \frac{0.0004}{1} = 0.064 + 0.0004 = 0.065 < 1 \text{ Limit}$$

Appendix B: ISED RF Exposure

ISED RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph “4. Exposure Limits”, Industry of Canada has adopted the RF field strength limits established in Healths Canada’s RF exposure guideline, Safety code 6:

**Table 4: RF Field Strength Limits for Devices Used by the General Public
 (Uncontrolled Environment)**

| Frequency Range (MHz) | Electric Field (V/m rms) | Magnetic Field (A/m rms) | Power Density (W/m ²) | Reference Period (minutes) |
|---|----------------------------------|---|------------------------------------|---------------------------------|
| 0.003-10 ⁻²¹ | 83 | 90 | - | Instantaneous* |
| 0.1-10 | - | 0.73/ <i>f</i> | - | 6** |
| 1.1-10 | 87/ <i>f</i> ^{0.5} | - | - | 6** |
| 10-20 | 27.46 | 0.0728 | 2 | 6 |
| 20-48 | 58.07/ <i>f</i> ^{0.25} | 0.1540/ <i>f</i> ^{0.25} | 8.944/ <i>f</i> ^{0.5} | 6 |
| 48-300 | 22.06 | 0.05852 | 1,291 | 6 |
| 300-6000 | 3.142 <i>f</i> ^{0.3417} | 0.008335 <i>f</i> ^{0.3417} | 0.02619 <i>f</i> ^{0.6834} | 6 |
| 6000-15000 | 61.4 | 0.163 | 10 | 6 |
| 15000-150000 | 61.4 | 0.163 | 10 | 616000/ <i>f</i> ^{1.2} |
| 150000-300000 | 0.158 <i>f</i> ^{0.5} | 4.21 x 10 ⁻⁴ <i>f</i> ^{0.5} | 6.67 x 10 ⁻⁵ <i>f</i> | 616000/ <i>f</i> ^{1.2} |
| Note: <i>f</i> is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR). | | | | |

ISED MPE Evaluation Results

Each supported transmission technology will be evaluated to determine if it is in compliance with RSS-102 Issue 5, RF Field Strength Limits for devices used by the General Public.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction:

$$\text{Power density: } S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W/m^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

R_{\min} = distance to the center of radiation of the antenna

Assessment 1 – NFC – 13.5 MHz Band

| | |
|---|-------|
| Maximum output power (dBm): | 25.0 |
| Maximum antenna gain (dBi): | N/A |
| Minimum use distance (m): | 0.2 |
| Worst Case Frequency (MHz): | 13.56 |
| Maximum EIRP (dBm): | 25.0 |
| Maximum EIRP (W): | 0.32 |
| General public - Power density limit (W/m ²): | 2.0 |

Power density at minimum use distance:

| | |
|---|------|
| Power density (W/m ²): | 0.63 |
| General public - Power density limit (W/m ²): | 2.0 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public power density limit.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum compliance distance for general public (m): | 0.112 |
| Minimum use distance (m): | 0.2 |
| Verdict for general public: | PASS |

The minimum use distance is greater than general public minimum compliance distance.

Assessment 2 – Bluetooth Smart Direct Key – 2450 MHz Band

| | |
|---|--------|
| Maximum output power (dBm): | 2.8 |
| Maximum antenna gain (dBi): | 0.5 |
| Minimum use distance (m): | 0.2 |
| Worst Case Frequency (MHz): | 2402.0 |
| Maximum EIRP (dBm): | 3.3 |
| Maximum EIRP (W): | 0.0021 |
| General public - Power density limit (W/m ²): | 5.35 |

Power density at minimum use distance:

| | |
|---|-------|
| Power density (W/m ²): | 0.004 |
| General public - Power density limit (W/m ²): | 5.35 |
| Verdict for general public: | PASS |

The power density level for this transmission mode is below general public power density limit.

Minimum compliance distance for this technology:

| | |
|---|-------|
| Minimum compliance distance for general public (m): | 0.006 |
| Minimum use distance (m): | 0.2 |
| Verdict for general public: | PASS |

The minimum use distance is greater than general public minimum compliance distance.

Multiple frequencies assessment

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure toward the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less than unity:

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

Where

S_i is the power density of each source;

MPE_i is the power density basic restriction of each source.

This device is able to transmit simultaneously using NFC and Bluetooth Smart. The multiple frequencies calculation will be as follow:

$$\frac{0.63}{2} + \frac{0.016}{5.35} = 0.315 + 0.001 = 0.316 < 1 \text{ Limit}$$