



Prüfbericht - Nr.: 15023662 001			Seite 1 von 27 Page 1 of 27		
<i>Test Report No.:</i>					
Auftraggeber: <i>Client:</i>		Hearth & Home Technologies Inc. 20802 Kensington Blvd. Lakeville, MN 55044 USA			
Gegenstand der Prüfung: Remote Control for Electric Room Heater <i>Test item:</i>					
Bezeichnung: <i>Identification:</i>		4050-105		Serien-Nr.: <i>Serial No.:</i> N/A	
Wareneingangs-Nr.: <i>Receipt No.:</i>		153079837		Eingangsdatum: 05.06.2007 <i>Date of receipt:</i>	
Prüfart: <i>Testing location:</i>		Refer to section 1.1			
Prüfgrundlage: <i>Test specification:</i>		FCC Part 15, Subpart C			
Prüfergebnis: <i>Test Result:</i>		Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n). <i>The test item passed the test specification(s).</i>			
Prüflaboratorium: <i>Testing Laboratory:</i>		TÜV Rheinland (Shanghai) Co., Ltd.			
geprüft/ tested by:			kontrolliert/ reviewed by:		
10.09.2007	Kong Xiangming/PE		10.09.2007	Lu Xinhua/TC	
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>
Sonstiges/ Other Aspects: FCC ID ULECDT2F					
Abkürzungen: P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet			Abbreviations: P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested		
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>					

Prüfbericht - Nr.: 15023662 001*Test Report No.:***Seite 2 von 27***Page 2 of 27*

TEST SUMMARY

5.1.1 RADIATED EMISSION OF CARRIER FREQUENCY

*Result:**Passed*

5.1.2 SPURIOUS RADIATED EMISSIONS

*Result:**Passed*

5.1.3 BANDWIDTH MEASUREMENT

*Result:**Passed*

Contents

1	TEST SITES	2
1.1	TEST FACILITIES	2
1.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	2
2	GENERAL PRODUCT INFORMATION	2
2.1	PRODUCT FUNCTION AND INTENDED USE	2
2.2	CIRCUIT DESCRIPTION	2
2.3	RATINGS AND SYSTEM DETAILS	2
2.4	INDEPENDENT OPERATION MODES	2
2.5	SUBMITTED DOCUMENTS	2
2.6	RELATED SUBMITTAL(S) GRANTS	2
3	TEST SET-UP AND OPERATION MODES	2
3.1	PRINCIPLE OF CONFIGURATION SELECTION	2
3.2	TEST OPERATION AND TEST SOFTWARE	2
3.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....	2
3.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	2
4	TEST METHODOLOGY	2
4.1	RADIATED EMISSION.....	2
4.2	FIELD STRENGTH CALCULATION.....	2
5	TEST RESULT	2
5.1.1	<i>Radiated Emission of Carrier Frequency</i>	<i>2</i>
5.1.2	<i>Spurious Radiated Emissions.....</i>	<i>2</i>
5.1.3	<i>Bandwidth Measurement.....</i>	<i>2</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	2
7	LIST OF TABLES.....	2
8	LIST OF FIGURES.....	2
9	LIST OF PHOTOGRAPHS	2
10	APPENDIX 1: EXTERNAL PHOTOS	2
11	APPENDIX 2: INTERNAL PHOTOS.....	2
12	APPENDIX 3: FCC LABEL AND LOCATION	2
13	APPENDIX 4: BLOCK DIAGRAM, SCHEMATICS, PCB LAYOUT AND COMPONENT LISTS	2

Prüfbericht - Nr.: 15023662 001

Test Report No.:

Seite 4 von 27

Page 4 of 27

1 Test Sites

1.1 Test Facilities

Laboratory: TÜV Rheinland (Shanghai) Laboratory**Address: Building 2, No. 777 Guangzhong Road West, Shanghai 200072, P.R. China**

The used test equipments below 1GHz are in accordance with CISPR 16-1 series standards for measurement of radio interference.

1.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

No.	Equipment	Model	Serial no.	Cal. due date
1.	Spectrum analyzer	FSP30	100192	10.06.2008
2.	EMI test receiver	ESCI	100280	03.12.2007
3.	Broadband antenna	BTA-H	040005H	20.03.2008
4.	Double ridged broadband horn antenna	BBHA 9120 D	9120D-434	21.06.2008
5.	DC power supplier	0-60V/2A	0502073	08.08.2008
6.	Broadband coaxial preamplifier	BBV 9718	9718-012	12.04.2008

2 General Product Information

2.1 Product Function and Intended Use

The equipment under test (EUT) is a transmitter for the electric room heater operating at 433.920MHz.

The transmitter has two push-to-operate switches that will automatically and immediately deactivate the transmitter when the switch is released, hence transmitter will cease operating within not more than 5 seconds of being released.

FCC ID ULECDT2F

Model	Product description
4050-105	Remote Control For Electric Room Heater

2.2 Circuit Description

One 12V battery is used in this board, special IC SC2262 for remote control is used as main control circuit which was processed with CMOS and is also a remote control coding circuit, whose datum and address are coded into series strand codes. The datum is coded with the high level of SC2262 digit pin controlled by the two trigger switches, and then the codes are sent out through 433.92MHz carrier by high frequency oscillator.

2.3 Ratings and System Details

	Transmitter
Frequency range	: 433.920MHz
Crystal tolerance	: +/-100kHz
Number of channels	: 1
Type of antenna	: Integral antenna
Power supply	: DC 12V
Ports	: None
Protection Class	: III

2.4 Independent Operation Modes

The basic operation modes are:

- Remote Control: It has a push to operate switch and is under manual control at all transmission time. It will cease transmission immediately when the switch is released. The EUT has two control buttons to control the heating function and flame system of the room heater.

For further information refer to User Manual.

Prüfbericht - Nr.: 15023662 001*Test Report No.:***Seite 6 von 27***Page 6 of 27*

2.5 Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork

2.6 Related Submittal(s) Grants

This is a single application for certification of the transmitter.

3 Test Set-up and Operation Modes

3.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible emission level. The test conditions were adapted accordingly in reference to the instructions for use.

3.2 Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

3.3 Special Accessories and Auxiliary Equipment

None.

3.4 Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the Circuit Diagram or the Technical Construction File. No additional measures were employed to achieve compliance.

4 Test Methodology

4.1 Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed on an 80 cm high turntable, and measurement distance is 3 meters. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

4.2 Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the EMI test receiver or spectrum analyzer to the factors associated with antenna correction factor, cable loss and preamplifier.

The equation is expressed as follow:

$$FS = R + AF + CF - PA$$

Where FS = Field strength in dBuV/m at 3 meters.

R = Reading of spectrum analyzer in dBuV.

AF = Antenna factor in dB/m.

CF = Cable attenuation Factor in dB.

PA = Preamplifier factor in dB.

Prüfbericht - Nr.: 15023662 001
Test Report No.:
Seite 9 von 27
Page 9 of 27

5 Test Result

5.1.1 Radiated Emission of Carrier Frequency


Result:	Passed
----------------	---------------

Date of testing : 31.08.2007
 Test specification : FCC Part 15 Section 15.231(b)(1) and (b)(2)
 Test Method : ANSI 63.4-2003
 Measurement location : Semi-anechoic chamber
 Detector function : Quasi-peak
 Measurement BW : 120 kHz
 Supply voltage : DC 12V

Limit Section 15.231(b)


Frequency with in the band (MHz)	Quasi-peak Emission	
	(Microvolt/meter)	(dB μ V/m)
433.920	10996	80.8

The following figures and tables were those measured by an automatic measuring system. In the following figures, “+” means quasi-peak result which was measured in final measurement.

Figure 1: Spectral diagrams and measurement results below 1GHz, Horizontal polarization


Final quasi-peak measurement result:

Frequency (MHz)	Quasi-Peak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Polarization
433.906	66.9	80.8	13.9	H

Figure 2: Spectral diagrams and measurement results below 1GHz, Vertical polarization


Final quasi-peak measurement result:

Frequency (MHz)	Quasi-Peak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Polarization
433.906	65.7	80.8	15.1	V

Prüfbericht - Nr.: 15023662 001
Test Report No.:
Seite 12 von 27
Page 12 of 27
5.1.2 Spurious Radiated Emissions

Result:	Passed
----------------	---------------

Date of testing : 31.08.2007
 Test specification : FCC Part 15 Section 15.231(b)(1) and (b)(3)
 Test method : ANSI 63.4-2003
 Measurement : Semi-anechoic chamber
 location
 Measurement : 3m
 distance
 Detector : Quasi-peak(30-1000MHz)/Peak, Average(1000MHz-4500MHz)
 Measurement BW : 120 kHz(below 1GHz), 1MHz(above 1GHz)
 Supply voltage : DC 12V
 Measuring : 30-4500MHz
 frequency range

Limit Section 15.231(b)

Frequency (MHz)	Field strength (microvolt/meter)	Field strength (dBμV/m)	Measurement distance (meters)
433.920	1099	$20 \cdot \log(1099) = 60.8$	3


Limit Section 15.209

Frequency (MHz)	Field strength (microvolt/meter)	Field strength (dBμV/m)	Measurement distance (meters)
30-88	100	$20 \cdot \log(100) = 40.0$	3
88-216	150	$20 \cdot \log(150) = 43.5$	3
216-960	200	$20 \cdot \log(200) = 46.0$	3
Above 960	500	$20 \cdot \log(500) = 54.0$	3

Note: Higher limits of above two tables apply except for restricted bands.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

The following figures and tables were those measured by an automatic measuring system. In final measurement, quasi-peak value were measured and listed respectively where they had a maximum in previous scanning survey below 1000MHz. And above 1000MHz, average emission measurements are employed. According to section 15.35(b), when average radiated emission measurements are specified, including emission measurement below 1000MHz, there also is limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated.


Figure 3: Spectral diagrams and measurement results above 1GHz, Horizontal polarization

Final measurement result:

Frequency (MHz)	QP/AV result (dBµV/m)	Peak result (dBµV/m)	Limit(QP/AV detector) (dBµV/m)	Limit(Peak detector) (dBµV/m)	Margin(QP/AV detector) (dB)	Margin(Peak detector) (dB)	Polarization
867.750	47.1	N/A	60.8	80.8	13.7	N/A	H
*1301.875	41.8	45.1	54.0	74.0	12.2	28.9	H
1735.000	33.1	37.4	60.8	80.8	27.7	43.4	H

Remarks:

‘*’ indicates the frequency of the emissions falling into the restricted band.

Frequency below 1GHz with quasi-peak detector, refer to figure 1 for detail.

Figure 4: Spectral diagrams and measurement results above 1GHz, Vertical polarization

Final measurement result:

Frequency (MHz)	QP/AV result (dBμV/m)	Peak result (dBμV/m)	Limit(QP/AV detector) (dBμV/m)	Limit(Peak detector) (dBμV/m)	Margin(QP/AV detector) (dB)	Margin(Peak detector) (dB)	Polarization
867.688	42.1	N/A	60.8	80.8	18.7	N/A	V
*1301.875	39.4	41.9	54.0	74.0	14.6	32.1	V
1735.875	31.5	35.7	60.8	80.8	29.3	45.1	V

Remarks:

‘*’ indicates the frequency of the emissions falling into the restricted band.

Frequency below 1GHz with quasi-peak detector, refer to figure 2 for detail.

5.1.3 Bandwidth Measurement

Result:

Passed

Date of testing : 04.09.2007
Test specification : FCC Part 15 section 231(c)
Port of testing : Coupling
Detector function : Peak
Supply voltage : DC 12V


Limit Section 15.231(c)

The bandwidth of the emission shall be no wider than 0.25% if the centre frequency for devices operating above 70MHz and below 900MHz.

The 20dB bandwidth shall be no wider than 0.25% (1.08MHz) of the centre frequency 433.85825MHz.


From the result, it shows that the 20dB points of the lower edge and upper edge are 264 kHz and 228 kHz respectively apart from the centre frequency. Hence it is deemed to fulfill the requirement.

Figure 5: Spectral Diagrams for bandwidth measurement result



6 Photographs of the Test Set-Up


Photograph 1: Set-up for radiated emissions



Prüfbericht - Nr.: 15023662 001
Test Report No.:

Seite 17 von 27
Page 17 of 27

Photograph 2: Set-up for bandwidth measurement



7 List of Tables

Table 1: List of Test and Measurement Equipment	2
---	---

8 List of Figures

Figure 1: Spectral diagrams and measurement results below 1GHz, Horizontal polarization	2
Figure 2: Spectral diagrams and measurement results below 1GHz, Vertical polarization	2
Figure 3: Spectral diagrams and measurement results above 1GHz, Horizontal polarization	2
Figure 4: Spectral diagrams and measurement results above 1GHz, Vertical polarization.....	2
Figure 5: Spectral Diagrams for bandwidth measurement result	2

9 List of Photographs

Photograph 1: Set-up for radiated emissions.....	2
Photograph 2: Set-up for bandwidth measurement	2