



TEST REPORT

Test report no.: 1-0597/20-03-02-B

BNetzA-CAB-02/21-102

Testing laboratory

CTC advanced GmbH

Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
Internet: <http://www.ctcadvanced.com>
e-mail: mail@ctcadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkKS)
The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate starting with the registration number: D-PL-12076-01.

Applicant

ifm electronic gmbh Essen

Friedrichstrasse 1
45128 Essen / GERMANY
Phone: +49 201 2422-0
Contact: Holger Wenzel
e-mail: holger.wenzel@ifm.com
Phone: +49 7542 518-9108

Manufacturer

ifm synton gmbh

Marienfelder Strasse 10
88069 Tettngang / GERMANY

Test standard/s

FCC - Title 47 CFR Part 15 FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

RSS - 247 Issue 2 Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence - Exempt Local Area Network (LE-LAN) Devices

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: **RFID UHF compact unit**
Model name: **DTE904**
FCC ID: **UN6-DTRUHFA01**
IC: **6799A-DTRUHFA01**
Frequency: DTS band 902 MHz to 928 MHz
Technology tested: RFID
Antenna: Integrated antenna
Power supply: 24.0 V DC by external power supply
Temperature range: -20°C to +60°C

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:

Andreas Luckenbill
Head of Department
Radio Communications

Test performed:

Michael Dorongovski
Lab Manager
Radio Communications

1 Table of contents

| | | |
|-------|---|----|
| 1 | Table of contents..... | 2 |
| 2 | General information..... | 3 |
| 2.1 | Notes and disclaimer..... | 3 |
| 2.2 | Application details..... | 3 |
| 2.3 | Test laboratories sub-contracted..... | 3 |
| 3 | Test standard/s, references and accreditations..... | 4 |
| 4 | Reporting statements of conformity – decision rule..... | 5 |
| 5 | Test environment..... | 6 |
| 6 | Test item..... | 6 |
| 6.1 | General description..... | 6 |
| 6.2 | Additional information..... | 6 |
| 7 | Sequence of testing..... | 7 |
| 7.1 | Sequence of testing radiated spurious 9 kHz to 30 MHz..... | 7 |
| 7.2 | Sequence of testing radiated spurious 30 MHz to 1 GHz..... | 8 |
| 7.3 | Sequence of testing radiated spurious 1 GHz to 10 GHz..... | 9 |
| 8 | Description of the test setup..... | 10 |
| 8.1 | Shielded semi anechoic chamber..... | 11 |
| 8.2 | Shielded fully anechoic chamber..... | 13 |
| 8.3 | Conducted measurements system..... | 14 |
| 9 | Measurement uncertainty..... | 15 |
| 10 | Summary of measurement results..... | 16 |
| 10.1 | Additional comments..... | 17 |
| 11 | Measurement results..... | 18 |
| 11.1 | Antenna gain..... | 18 |
| 11.2 | Carrier Frequency Separation..... | 19 |
| 11.3 | Number of Hopping Channels..... | 20 |
| 11.4 | Average Time of Occupancy (dwell time)..... | 21 |
| 11.5 | Spectrum bandwidth of a FHSS system..... | 25 |
| 11.6 | Maximum Output Power..... | 26 |
| 11.7 | Detailed spurious emissions @ the band edge – conducted and radiated..... | 27 |
| 11.8 | Spurious Emissions Conducted..... | 30 |
| 11.9 | Spurious Emissions Radiated < 30 MHz..... | 31 |
| 11.10 | Spurious Emissions Radiated > 30 MHz..... | 34 |
| 12 | Glossary..... | 44 |
| 13 | Document history..... | 45 |
| 14 | Accreditation Certificate – D-PL-12076-01-04..... | 45 |
| 15 | Accreditation Certificate – D-PL-12076-01-05..... | 46 |

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CTC advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTC advanced GmbH.

The testing service provided by CTC advanced GmbH has been rendered under the current "General Terms and Conditions for CTC advanced GmbH".

CTC advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CTC advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CTC advanced GmbH test report include or imply any product or service warranties from CTC advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CTC advanced GmbH.

All rights and remedies regarding vendor's products and services for which CTC advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by CTC advanced GmbH. In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

This test report replaces the test report with the number 1-0597/20-03-02-A and dated 2021-03-17.

2.2 Application details

| | |
|------------------------------------|------------|
| Date of receipt of order: | 2020-07-16 |
| Date of receipt of test item: | 2020-06-02 |
| Start of test: | 2020-06-02 |
| End of test: | 2020-07-20 |
| Person(s) present during the test: | -/- |





2.3 Test laboratories sub-contracted

None

3 Test standard/s, references and accreditations


| Test standard | Date | Description |
|-------------------------------------|---------------|--|
| FCC - Title 47 CFR Part 15 | | FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices |
| RSS - 247 Issue 2 | February 2017 | Digital Transmission Systems (DTs), Frequency Hopping Systems (FHSs) and Licence - Exempt Local Area Network (LE-LAN) Devices |
| RSS - Gen Issue 5 incl. Amendment 1 | March 2019 | Spectrum Management and Telecommunications Radio Standards Specification - General Requirements for Compliance of Radio Apparatus |

| Guidance | Version | Description |
|------------------|---------|--|
| KDB 558074 D01 | v05r02 | GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES |
| ANSI C63.4-2014 | -/- | American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz |
| ANSI C63.10-2013 | -/- | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices |

| Accreditation | Description | |
|------------------|---|---|
| D-PL-12076-01-04 | Telecommunication and EMC Canada https://www.dakks.de/as/ast/d/D-PL-12076-01-04e.pdf |   Deutsche Akkreditierungsstelle D-PL-12076-01-04 |
| D-PL-12076-01-05 | Telecommunication FCC requirements https://www.dakks.de/as/ast/d/D-PL-12076-01-05e.pdf |   Deutsche Akkreditierungsstelle D-PL-12076-01-05 |

4 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3. The measurement uncertainty is mentioned in this test report, see chapter 9, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong."



5 Test environment

| | | | |
|---------------------------|---|-------------------------------------|--|
| Temperature | : | T_{nom} T_{max} T_{min} | +22 °C during room temperature tests No tests under extreme environmental conditions required. No tests under extreme environmental conditions required. |
| Relative humidity content | : | | 55 % |
| Barometric pressure | : | | 1021 hpa |
| Power supply | : | V_{nom} V_{max} V_{min} | 24.0 V DC by external power supply No tests under extreme environmental conditions required. No tests under extreme environmental conditions required. |

6 Test item

6.1 General description

| | | |
|----------------------------|---|---|
| Kind of test item | : | RFID UHF compact unit |
| Model name | : | DTE904 |
| HMN | : | -/- |
| PMN | : | DTE90x (TR10) |
| HVIN | : | DTE904 |
| FVIN | : | -/- |
| S/N serial number | : | Rad. MAC address: 00:02:01:41:60:FF Cond. MAC address: 00:02:01:41:7F:13 |
| Hardware status | : | version 2 |
| Software status | : | E3.3.99 |
| Firmware status | : | -/- |
| Frequency band | : | DTS band 902 MHz to 928 MHz |
| Type of radio transmission | : | FHSS |
| Use of frequency spectrum | : | |
| Type of modulation | : | PR-ASK |
| Number of channels | : | 50 |
| Antenna | : | Integrated antenna |
| Power supply | : | 24.0 V DC by external power supply |
| Temperature range | : | -20°C to +60°C |

6.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup and EUT photos are included in test report: 1-0597/20-03-01_AnnexA
 1-0597/20-03-01_AnnexD

7 Sequence of testing

7.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, it is placed on a table with 0.8 m height.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement*

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the pre-measurement are maximized by the software by rotating the turntable from 0° to 360°.
- Loop antenna is rotated about its vertical axis for maximum response at each azimuth about the EUT. (For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT)
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

*Note: The sequence will be repeated three times with different EUT orientations.

7.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

7.3 Sequence of testing radiated spurious 1 GHz to 10 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).


In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

Agenda: Kind of Calibration

| | | | |
|------|--|-----|--|
| k | calibration / calibrated | EK | limited calibration |
| ne | not required (k, ev, izw, zw not required) | zw | cyclical maintenance (external cyclical maintenance) |
| ev | periodic self verification | izw | internal cyclical maintenance |
| Ve | long-term stability recognized | g | blocked for accredited testing |
| vlk! | Attention: extended calibration interval | | |
| NK! | Attention: not calibrated | *) | next calibration ordered / currently in progress |

8.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 30 MHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform to specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter; EMC32 software version: 10.30.0

$$FS = UR + CL + AF$$

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)

Example calculation:


$$FS [dB\mu V/m] = 12.35 [dB\mu V/m] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB\mu V/m] (35.69 \mu V/m)$$

Equipment table:

| No. | Lab / Item | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|---|------------------|---------------|-----------------|-----------|---------------------|------------------|------------------|
| 1 | A | Switch-Unit | 3488A | HP | 2719A14505 | 300000368 | ev | -/- | -/- |
| 2 | A | Meßkabine 1 | HF-Absorberhalle | MWB AG 300023 | -/- | 300000551 | ne | -/- | -/- |
| 3 | A | Analyzer-Reference-System (Harmonics and Flicker) | ARS 16/1 | SPS | A3509 07/0 0205 | 300003314 | vKI! | 17.01.2020 | 16.01.2022 |
| 4 | A | Antenna Tower | Model 2175 | ETS-Lindgren | 64762 | 300003745 | izw | -/- | -/- |
| 5 | A | Positioning Controller | Model 2090 | ETS-Lindgren | 64672 | 300003746 | izw | -/- | -/- |
| 6 | A | Turntable Interface-Box | Model 105637 | ETS-Lindgren | 44583 | 300003747 | izw | -/- | -/- |

| | | | | | | | | | |
|---|---|--|----------|-------------------------------|------------|-----------|------|------------|------------|
| 7 | A | TRILOG Broadband Test-Antenna 30 MHz - 3 GHz | VULB9163 | Schwarzbeck Mess - Elektronik | 295 | 300003787 | vKI! | 19.02.2019 | 18.02.2021 |
| 8 | A | EMI Test Receiver | ESR3 | Rohde & Schwarz | 102587 | 300005771 | k | 21.05.2019 | 20.11.2020 |
| 9 | A | DC power supply, 60Vdc, 50A, 1200 W | 6032A | HP | 2920A04466 | 300000580 | ne | -/- | -/- |

8.2 Shielded fully anechoic chamber



Measurement distance: tri-log antenna and horn antenna 3 meter; loop antenna 3 meter

FS = UR + CA + AF

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)


Example calculation:

FS [dBµV/m] = 40.0 [dBµV/m] + (-35.8) [dB] + 32.9 [dB/m] = 37.1 [dBµV/m] (71.61 µV/m)

Equipment table:

| No. | Lab / Item | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|--|-------------------------|----------------------|------------|-----------|---------------------|------------------|------------------|
| 1 | B | Active Loop Antenna 9 kHz to 30 MHz | 6502 | EMCO | 2210 | 300001015 | vKI! | 13.06.2019 | 12.06.2021 |
| 2 | A, B | Anechoic chamber | FAC 3/5m | MWB / TDK | 87400/02 | 300000996 | ev | -/- | -/- |
| 3 | A | Double-Ridged Waveguide Horn Antenna 1-18.0GHz | 3115 | EMCO | 9107-3697 | 300001605 | vKI! | 27.02.2019 | 26.02.2021 |
| 4 | A, B | Switch / Control Unit | 3488A | HP | * | 300000199 | ne | -/- | -/- |
| 5 | A, B | EMI Test Receiver 20Hz- 26,5GHz | ESU26 | R&S | 100037 | 300003555 | k | 11.12.2019 | 10.12.2020 |
| 6 | A | Highpass Filter | WHK1.1/15G-10SS | Wainwright | 3 | 300003255 | ev | -/- | -/- |
| 7 | A | Highpass Filter | WHKX7.0/18G-8SS | Wainwright | 19 | 300003790 | ne | -/- | -/- |
| 8 | A | Broadband Amplifier 0.5-18 GHz | CBLU5184540 | CERNEX | 22049 | 300004481 | ev | -/- | -/- |
| 9 | A, B | 4U RF Switch Platform | L4491A | Agilent Technologies | MY50000037 | 300004509 | ne | -/- | -/- |
| 10 | A, B | NEXIO EMV-Software | BAT EMC V3.19.1.9 | EMCO | -/- | 300004682 | ne | -/- | -/- |
| 11 | A, B | PC | ExOne | F+W | -/- | 300004703 | ne | -/- | -/- |
| 12 | A | RF-Amplifier | AMF-6F06001800-30-10P-R | NARDA-MITEQ Inc | 2011572 | 300005241 | ev | -/- | -/- |
| 13 | A, B | DC power supply, 60Vdc, 50A, 1200 W | 6032A | HP | 2818A03450 | 300001040 | vKI! | 12.12.2017 | 11.12.2020 |

8.3 Conducted measurements system



OP = AV + CA
(OP-output power; AV-analyzer value; CA-loss signal path)

Example calculation:

OP [dBm] = 6.0 [dBm] + 11.7 [dB] = 17.7 [dBm] (58.88 mW)

Equipment table:

| No. | Lab / Item | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|------------|---|-----------------|----------------------|---------------|-----------|---------------------|------------------|------------------|
| 1 | A | PC Laboratory 19" | Exone i3 | Fröhlich + Walter | 35230157A0370 | 300004646 | ne | -/- | -/- |
| 2 | A | Spectrum Analyzer | FSV30 | Rohde & Schwarz | 103170 | 300004855 | vKI! | 11.12.2018 | 10.12.2020 |
| 3 | A | USB-GPIB-Interface | 82357B | Agilent Technologies | MY54323070 | 300004852 | ne | -/- | -/- |
| 4 | A | Power Supply DC | HMP2020 | Rohde & Schwarz | 102123 | 300005235 | vKI! | 11.12.2018 | 10.12.2020 |
| 5 | A | Relay Switch Matrix | RSM-1 | CTC advanced GmbH | 0001 | 400001355 | ev | 07.01.2020 | 06.01.2021 |
| 6 | A | Tester Software RadioStar (C.BER2 for BT Conformance) | Version 1.0.0.X | CTC advanced GmbH | 0001 | 400001380 | ne | -/- | -/- |

9 Measurement uncertainty

| Measurement uncertainty | |
|---|--|
| Test case | Uncertainty |
| Antenna gain | ± 3 dB |
| Carrier frequency separation | ± 21.5 kHz |
| Number of hopping channels | -/- |
| Spectrum bandwidth | ± 21.5 kHz absolute; ± 15.0 kHz relative |
| Maximum output power | ± 1 dB |
| Detailed conducted spurious emissions @ the band edge | ± 1 dB |
| Band edge compliance radiated | ± 3 dB |
| Spurious emissions conducted | ± 3 dB |
| Spurious emissions radiated below 30 MHz | ± 3 dB |
| Spurious emissions radiated 30 MHz to 1 GHz | ± 3 dB |
| Spurious emissions radiated 1 GHz to 12.75 GHz | ± 3.7 dB |
| Spurious emissions radiated above 12.75 GHz | ± 4.5 dB |

10 Summary of measurement results

| | |
|-------------------------------------|---|
| <input checked="" type="checkbox"/> | No deviations from the technical specifications were ascertained |
| <input type="checkbox"/> | There were deviations from the technical specifications ascertained |
| <input type="checkbox"/> | This test report is only a partial test report. The content and verdict of the performed test cases are listed below. |

| TC Identifier | Description | Verdict | Date | Remark |
|---------------|-----------------------------------|---------|------------|--------|
| RF-Testing | CFR Part 15 RSS - 247, Issue 2 | Passed | 2021-03-18 | -/- |

| Test specification clause | Test case | Temperature conditions | Power source voltages | Mode | C | NC | NA | NP | Remark |
|---|---|------------------------|-----------------------|--------|-------------------------------------|--------------------------|--------------------------|--------------------------|--------|
| §15.247(b)(4) RSS - 247 / 5.4 (d) | Antenna gain | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(a)(1) RSS - 247 / 5.1 (b) | Carrier frequency separation | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(a)(1) RSS - 247 / 5.1 (d) | Number of hopping channels | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(a)(1) (iii) RSS - 247 / 5.1 (d) | Time of occupancy (dwell time) | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(a)(1) RSS - 247 / 5.1 (a) | Spectrum bandwidth of a FHSS system bandwidth | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(b)(1) RSS - 247 / 5.4 (b) | Maximum output power | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(d) RSS - 247 / 5.5 | Detailed spurious emissions @ the band edge - conducted | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.205 RSS - 247 / 5.5 RSS - Gen | Band edge compliance radiated | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(d) RSS - 247 / 5.5 | Spurious emissions conducted | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.209(a) RSS - Gen | Spurious emissions radiated below 30 MHz | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.247(d) RSS - 247 / 5.5 §15.109 RSS - Gen | Spurious emissions radiated 30 MHz to 1 GHz | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |

| | | | | | | | | | |
|---|---|---------|---------|--------|-------------------------------------|--------------------------|-------------------------------------|--------------------------|-----|
| §15.247(d) RSS - 247 / 5.5 §15.109 RSS - Gen | Spurious emissions radiated above 1 GHz | Nominal | Nominal | PR-ASK | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.107(a) §15.207 | Conducted emissions below 30 MHz (AC conducted) | Nominal | Nominal | -/- | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | -/- |

Note: C = Compliant; NC = Not compliant; NA = Not applicable; NP = Not performed

10.1 Additional comments

Reference documents: 1-0597_20-03-02_log1_conducted.pdf
Bedienung der Applikation zur Steuerung der DTE904.pdf

Special test descriptions: The "config_FCC.xml" file was used for all tests.

Configuration descriptions: All radiated tests were performed without a tag. Additional tests between 1 and 10 GHz were performed with tag in a 20 cm distance to the EUT, as this is defined as the intended use distance of the EUT to a tag by the customer.

Test mode: Special software is used.
EUT is transmitting pseudo random data by itself

11 Measurement results

11.1 Antenna gain

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

| Measurement parameters | |
|-------------------------|--|
| Detector | Peak |
| Sweep time | Auto |
| Resolution bandwidth | 300 kHz |
| Video bandwidth | 1 MHz |
| Span | 500 kHz |
| Trace mode | Max hold |
| External result file | 1-0597_20-03-02_log1_conducted.pdf FCC Part 15.247 Maximum Peak Conducted Output Power ~ Generic 0G9 hopp |
| Test setup | See chapter 8.1 A (radiated) See chapter 8.3 A (conducted) |
| Measurement uncertainty | See chapter 9 |

Limits:

| FCC | IC |
|---|----|
| Antenna gain | |
| <p>The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> | |

Results:

| | Low channel | Middle channel | High channel |
|-----------------------|-------------|----------------|--------------|
| Conducted power [dBm] | 24.0 | 23.6 | 22.7 |
| Radiated power [dBm] | 20.5 | 23.1 | 19.9 |
| Gain [dBi] Calculated | -3.5 | -0.5 | -2.8 |

11.2 Carrier Frequency Separation

| Measurement parameters | |
|-------------------------|-------------------|
| Detector | Peak |
| Sweep time | Auto |
| Resolution bandwidth | 10 kHz |
| Video bandwidth | 30 kHz |
| Span | See plots |
| Trace mode | Max hold |
| Test setup | See chapter 8.3 A |
| Measurement uncertainty | See chapter 9 |


Limits:

| FCC | IC |
|--|----|
| Carrier frequency separation | |
| Minimum 25 kHz or two-thirds of the 20 dB bandwidth of the hopping system whichever is greater. The two-thirds of the 20 dB bandwidth for IC is only valid for the ISM band 2400 – 2483.5 MHz. | |

Result: The channel separation is 500 kHz.

Plot:

Plot 1:



11.3 Number of Hopping Channels

| Measurement parameters | |
|--------------------------|---|
| External result file | 1-0597_20-03-02_log1_conducted.pdf FCC Part 15.247 Number of Hopping channels FHSS ~ Generic 0G9 hopp |
| Used equipment: | See chapter 8.3 A |
| Measurement uncertainty: | See chapter 9 |

Limits:

| FCC | IC |
|--|----|
| Number of hopping channels | |
| At least 25 non overlapping hopping channels. If the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels. | |

Result: 50 channels, see logfile

11.4 Average Time of Occupancy (dwell time)

Measurement:

The measurement is performed in zero span mode to show that none of the 50 used channels is allocated more than 0.4 seconds within a 20 seconds interval (50 channels times 0.4s).

| | |
|--------------------------|-------------------|
| Used equipment: | See chapter 8.3 A |
| Measurement uncertainty: | See chapter 9 |

Limits:


| FCC | IC |
|---|----|
| Average time of occupancy | |
| <p>For frequency hopping systems operating in the 902-928 MHz band: If the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within 10 second period.</p> | |

Result: The time slot length is = 193 ms
 Number of hops / channel @ 20s = 2


→ The average time of occupancy = 386 ms

Plots:


Plot 1: Burst length, lowest channel




Plot 2: Burst length, middle channel




Plot 3: Burst length, highest channel




Plot 4: Number of hops in 20 seconds, lowest channel



Plot 5: Number of hops in 20 seconds, middle channel



Plot 6: Number of hops in 20 seconds, highest channel



11.5 Spectrum bandwidth of a FHSS system

Description:

Measurement of the 20dB bandwidth and 99% bandwidth of the modulated signal.

Measurement:

| Measurement parameters | |
|--------------------------|---|
| External result file | 1-0597_20-03-02_log1_conducted.pdf FCC Part 15.247 Bandwidths ~ Generic 0G9 hopp |
| Used equipment: | See chapter 8.3 A |
| Measurement uncertainty: | See chapter 9 |

Limits:

| FCC | IC |
|--|----|
| Spectrum bandwidth of a FHSS system | |
| The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz. | |

Result:

| Test Conditions | | 20dB BANDWIDTH [kHz] | | |
|-----------------|-----------|----------------------|----------------|--------------|
| | | Low channel | Middle channel | High channel |
| T_{nom} | V_{nom} | 48 | 48 | 52 |

| Test Conditions | | 99% BANDWIDTH [kHz] | | |
|-----------------|-----------|---------------------|----------------|--------------|
| | | Low channel | Middle channel | High channel |
| T_{nom} | V_{nom} | 61 | 61 | 72 |

11.6 Maximum Output Power

Measurement:

| Measurement parameter | |
|--------------------------|--|
| External result file | 1-0597_20-03-02_log1_conducted.pdf FCC Part 15.247 Maximum Peak Conducted Output Power ~ Generic 0G9 hopp |
| Used equipment: | See chapter 8.3 A |
| Measurement uncertainty: | See chapter 9 |

Limits:

| FCC | IC |
|--|----|
| Maximum Output Power Conducted | |
| For frequency hopping systems operating in the 902–928 MHz band: 1 watt (30 dBm) for systems employing at least 50 hopping channels; and, 0.25 watts (24 dBm) for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section. | |

Result:

| Test Conditions | | Maximum Output Power Conducted [dBm] | | |
|-----------------|-----------|--------------------------------------|----------------|--------------|
| | | Low channel | Middle channel | High channel |
| T_{nom} | V_{nom} | 24.0 | 23.6 | 22.7 |

11.7 Detailed spurious emissions @ the band edge – conducted and radiated

Description:

Measurement of the conducted band edge compliance. EUT is measured at the lower and upper band edge in single channel and hopping mode.

| Measurement parameters | |
|-------------------------|--|
| Detector | Peak |
| Sweep time | Auto |
| Resolution bandwidth | 100 kHz |
| Video bandwidth | 300 kHz / 500 kHz |
| Span | Lower Band Edge: 902 MHz Upper Band Edge: 928 MHz |
| Trace mode | Max hold |
| Test setup | See chapter 8.3 A |
| Measurement uncertainty | See chapter 9 |

Limits:


| FCC | IC |
|---|----|
| In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. | |

Results conducted:

| Scenario | Spurious band edge conducted [dB] | |
|-------------------------------|-----------------------------------|-----------------|
| | lowest channel | highest channel |
| Lower band edge – hopping on | > 20 dB | > 20 dB |
| Upper band edge – hopping on | > 20 dB | > 20 dB |
| Lower band edge – hopping off | > 20 dB | > 20 dB |
| Upper band edge – hopping off | > 20 dB | > 20 dB |


Plots:

Plot 1: 20 dB – hopping on



Date: 8 JUL 2020 16:13:03

Plot 2: 20 dB – hopping off



Date: 8 JUL 2020 16:32:19

Results radiated:

No restricted band in the range ± 2 channel bandwidths of the Band-edges of the specified emission band! (608 MHz – 614 MHz and 960 MHz – 1240 MHz).

Section 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|----------------------------|-----------------------|-----------------|------------------|
| 0.090 - 0.110 | 16.42 - 16.423 | 399.9 - 410 | 4.5 - 5.15 |
| ¹ 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614 | 5.35 - 5.46 |
| 2.1735 - 2.1905 | 16.80425 - 16.80475 | 960 - 1240 | 7.25 - 7.75 |
| 4.125 - 4.128 | 25.5 - 25.67 | 1300 - 1427 | 8.025 - 8.5 |
| 4.17725 - 4.17775 | 37.5 - 38.25 | 1435 - 1626.5 | 9.0 - 9.2 |
| 4.20725 - 4.20775 | 73 - 74.6 | 1645.5 - 1646.5 | 9.3 - 9.5 |
| 6.215 - 6.218 | 74.8 - 75.2 | 1660 - 1710 | 10.6 - 12.7 |
| 6.26775 - 6.26825 | 108 - 121.94 | 1718.8 - 1722.2 | 13.25 - 13.4 |
| 6.31175 - 6.31225 | 123 - 138 | 2200 - 2300 | 14.47 - 14.5 |
| 8.291 - 8.294 | 149.9 - 150.05 | 2310 - 2390 | 15.35 - 16.2 |
| 8.362 - 8.366 | 156.52475 - 156.52525 | 2483.5 - 2500 | 17.7 - 21.4 |
| 8.37625 - 8.38675 | 156.7 - 156.9 | 2690 - 2900 | 22.01 - 23.12 |
| 8.41425 - 8.41475 | 162.0125 - 167.17 | 3260 - 3267 | 23.6 - 24.0 |
| 12.29 - 12.293 | 167.72 - 173.2 | 3332 - 3339 | 31.2 - 31.8 |
| 12.51975 - 12.52025 | 240 - 285 | 3345.8 - 3358 | 36.43 - 36.5 |
| 12.57675 - 12.57725 | 322 - 335.4 | 3600 - 4400 | (²) |
| 13.36 - 13.41 | | | |

11.8 Spurious Emissions Conducted

Description:

Measurement of the conducted spurious emissions in transmit mode. The EUT is set to single channel mode. The measurement is repeated for low, mid and high channel.

Measurement:

| Measurement parameter | |
|--------------------------|--|
| External result file | 1-0597_20-03-02_log1_conducted.pdf FCC Part 15.247 TX Spurious Conducted 20 dBc ~ Generic 0G9 hopp |
| Used equipment: | See chapter 8.3 A |
| Measurement uncertainty: | See chapter 9 |

Limits:

| FCC | IC |
|---|----|
| TX spurious emissions conducted | |
| <p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required</p> | |

Result:

| Emission Limitation | | | | | |
|---------------------------------|--|-----------------------------|-----------------------------------|--|---------------------|
| Frequency [MHz] | | Amplitude of emission [dBm] | Limit max. allowed emission power | actual attenuation below frequency of operation [dB] | Results |
| 902.75 | | 22.9 | 30 dBm | | Operating frequency |
| No critical emissions detected. | | | -20 dBc | | |
| 915.25 | | 22.6 | 30 dBm | | Operating frequency |
| No critical emissions detected. | | | -20 dBc | | |
| 927.25 | | 22.4 | 30 dBm | | Operating frequency |
| No critical emissions detected. | | | -20 dBc | | |

11.9 Spurious Emissions Radiated < 30 MHz

Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The EUT is set to single channel mode and the transmit channels are lowest; middle and highest channel. The limits are re-calculated to a measurement distance of 3 m according the ANSI C63.10.

Measurement:

| Measurement parameter | |
|--------------------------|--|
| Detector: | Peak / Quasi Peak |
| Sweep time: | Auto |
| Resolution bandwidth: | F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz |
| Video bandwidth: | F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz |
| Span: | 9 kHz to 30 MHz |
| Trace-Mode: | Max Hold |
| Used equipment: | See chapter 8.2 B |
| Measurement uncertainty: | See chapter 9 |

Limits:


| FCC | | IC | |
|---|-------------------------------|----------------------|--|
| TX spurious emissions radiated < 30 MHz | | | |
| Frequency (MHz) | Field strength (dB μ V/m) | Measurement distance | |
| 0.009 – 0.490 | 2400/F(kHz) | 300 | |
| 0.490 – 1.705 | 24000/F(kHz) | 30 | |
| 1.705 – 30.0 | 30 | 30 | |

Result:


| SPURIOUS EMISSIONS LEVEL [dB μ V/m] | | | | | | | | |
|---|----------|----------------------|-----------------|----------|----------------------|-----------------|----------|----------------------|
| Lowest channel | | | Middle channel | | | Highest channel | | |
| Frequency [MHz] | Detector | Level [dB μ V/m] | Frequency [MHz] | Detector | Level [dB μ V/m] | Frequency [MHz] | Detector | Level [dB μ V/m] |
| All emissions were more than 10 dB below the limit. | | | | | | | | |

Plots:


Plot 1: TX-Mode low channel



Plot 2: TX-Mode mid channel



Plot 3: TX-Mode high channel



11.10 Spurious Emissions Radiated > 30 MHz

11.10.1 Spurious emissions radiated 30 MHz to 1 GHz


| Measurement parameters | |
|-------------------------|-------------------|
| Detector | Peak / Quasi Peak |
| Sweep time | Auto |
| Resolution bandwidth | 3 x VBW |
| Video bandwidth | 120 kHz |
| Span | 30 MHz to 1 GHz |
| Trace mode | Max hold |
| Measured modulation | PR-ASK |
| Test setup | See chapter 8.1 A |
| Measurement uncertainty | See chapter 9 |

Limits:

| FCC | IC | |
|---|-------------------------|----------------------|
| Band-edge Compliance of conducted and radiated emissions | | |
| <p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).</p> | | |
| Frequency (MHz) | Field Strength (dBµV/m) | Measurement distance |
| 30 - 88 | 30.0 | 10 |
| 88 – 216 | 33.5 | 10 |
| 216 – 960 | 36.0 | 10 |
| Above 960 | 54.0 | 3 |

Plots:


Plot 1: 30 MHz – 1 GHz, horizontal & vertical polarization (lowest channel)



Final results:

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|--------------|
| 200.003 | 27.04 | 33.5 | 6.5 | 1000 | 120.0 | 100.0 | V | 315 | 11 |
| 218.216 | 19.51 | 36.0 | 16.5 | 1000 | 120.0 | 136.0 | V | -27 | 12 |
| 227.732 | 20.71 | 36.0 | 15.3 | 1000 | 120.0 | 144.0 | V | 18 | 12 |
| 299.999 | 32.46 | 36.0 | 3.5 | 1000 | 120.0 | 376.0 | H | 135 | 14 |
| 372.320 | 14.71 | 36.0 | 21.3 | 1000 | 120.0 | 380.0 | V | 48 | 16 |
| 866.896 | 35.66 | 36.0 | 0.3 | 1000 | 120.0 | 103.0 | H | 22 | 23 |


Plot 2: 30 MHz – 1 GHz, horizontal & vertical polarization (middle channel)



Final results:

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|--------------|
| 110.519 | 17.31 | 33.5 | 16.2 | 1000 | 120.0 | 140.0 | V | 6 | 12 |
| 200.003 | 29.92 | 33.5 | 3.6 | 1000 | 120.0 | 103.0 | V | 135 | 11 |
| 237.218 | 18.92 | 36.0 | 17.1 | 1000 | 120.0 | 104.0 | V | 10 | 13 |
| 300.009 | 36.24 | 36.0 | -0.2 | 1000 | 120.0 | 100.0 | V | 105 | 14 |
| 399.988 | 26.76 | 36.0 | 9.2 | 1000 | 120.0 | 98.0 | V | 163 | 17 |
| 865.710 | 36.20 | 36.0 | -0.2 | 1000 | 120.0 | 104.0 | H | 32 | 23 |

Plot 3: 30 MHz – 1 GHz, horizontal & vertical polarization (highest channel)



Final results:

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|-----|---------------|--------------|
| 168.655 | 14.92 | 33.5 | 18.6 | 1000 | 120.0 | 194.0 | V | 37 | 10 |
| 199.993 | 30.15 | 33.5 | 3.4 | 1000 | 120.0 | 103.0 | V | 339 | 11 |
| 237.256 | 22.46 | 36.0 | 13.5 | 1000 | 120.0 | 104.0 | V | 207 | 13 |
| 299.993 | 33.92 | 36.0 | 2.1 | 1000 | 120.0 | 103.0 | V | 45 | 14 |
| 319.956 | 15.52 | 36.0 | 20.5 | 1000 | 120.0 | 103.0 | V | 198 | 15 |
| 865.699 | 36.25 | 36.0 | -0.3 | 1000 | 120.0 | 112.0 | H | 29 | 23 |

11.10.2 Spurious emissions radiated above 1 GHz

| Measurement parameters | |
|-------------------------|------------------------------------|
| Detector | Peak / RMS |
| Sweep time | Auto |
| Resolution bandwidth | 1 MHz |
| Video bandwidth | 3 x RBW |
| Span | 1 GHz to 10 GHz |
| Trace mode | Max hold |
| Measured modulation | PR-ASK |
| Test setup | See chapter 8.2 A (1 GHz – 10 GHz) |
| Measurement uncertainty | See chapter 9 |

Limits:

| FCC | | IC | |
|---|-------------------------|----------------------|--|
| TX spurious emissions radiated | | | |
| <p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).</p> | | | |
| §15.209 | | | |
| Frequency (MHz) | Field strength (dBµV/m) | Measurement distance | |
| Above 960 | 54.0 (Average) | 3 | |
| Above 960 | 74.0 (Peak) | 3 | |

Results: Test setup without tag


| TX spurious emissions radiated [dBµV/m] | | | | | | | | |
|---|----------|----------------|------------------------------|----------|----------------|-------------------------------|----------|----------------|
| Lowest channel 902.75 MHz | | | Middle channel 914.75 MHz | | | Highest channel 927.25 MHz | | |
| F [MHz] | Detector | Level [dBµV/m] | F [MHz] | Detector | Level [dBµV/m] | F [MHz] | Detector | Level [dBµV/m] |
| 1100 | Peak | 44.8 | 1100 | Peak | 44.8 | 1100 | Peak | 44.8 |
| | AVG | 41.0 | | AVG | 41.0 | | AVG | 41.0 |
| | Peak | | 2744 | Peak | 44.9 | | Peak | |
| | AVG | | | AVG | 37.3 | | AVG | |
| | Peak | | 4574 | Peak | 47.7 | | Peak | |
| | AVG | | | AVG | 36.3 | | AVG | |

Results: Test setup with tag in a 20 cm distance to the EUT

| TX spurious emissions radiated [dBµV/m] | | | | | | | | |
|---|----------|----------------|------------------------------|----------|----------------|-------------------------------|----------|----------------|
| Lowest channel 902.75 MHz | | | Middle channel 914.75 MHz | | | Highest channel 927.25 MHz | | |
| F [MHz] | Detector | Level [dBµV/m] | F [MHz] | Detector | Level [dBµV/m] | F [MHz] | Detector | Level [dBµV/m] |
| 1100 | Peak | 44.8 | 1100 | Peak | 44.8 | 1100 | Peak | 44.8 |
| | AVG | 41.0 | | AVG | 41.0 | | AVG | 41.0 |
| 2708 | Peak | 50.2 | 2744 | Peak | 50.9 | 2781 | Peak | 51.2 |
| | AVG | 46.8 | | AVG | 47.7 | | AVG | 47.8 |
| 4514 | Peak | 53.9 | 4574 | Peak | 55.5 | 4636 | Peak | 54.6 |
| | AVG | 49.4 | | AVG | 51.8 | | AVG | 50.3 |


Plots: Test setup without tag

Plot 1: 1 GHz – 10 GHz, horizontal & vertical polarization (lowest channel)




NOTE: Blue = peak trace / Green = AVG trace

Plot 2: 1 GHz – 10 GHz, horizontal & vertical polarization (middle channel)



NOTE: Blue = peak trace / Green = AVG trace


Plot 3: 1 GHz – 10 GHz, horizontal & vertical polarization (highest channel)



NOTE: Blue = peak trace / Green = AVG trace


Plots: Test setup with tag in a 20 cm distance to the EUT

Plot 1: 1 GHz – 10 GHz, horizontal & vertical polarisation (lowest channel)




NOTE: Blue = peak trace / Green = AVG trace

Plot 2: 1 GHz – 10 GHz, horizontal & vertical polarisation (middle channel)



NOTE: Blue = peak trace / Green = AVG trace

Plot 3: 1 GHz – 10 GHz, horizontal & vertical polarisation (highest channel)



NOTE: Blue = peak trace / Green = AVG trace

12 Glossary

| | |
|------------------------|--|
| EUT | Equipment under test |
| DUT | Device under test |
| UUT | Unit under test |
| GUE | GNSS User Equipment |
| ETSI | European Telecommunications Standards Institute |
| EN | European Standard |
| FCC | Federal Communications Commission |
| FCC ID | Company Identifier at FCC |
| IC | Industry Canada |
| PMN | Product marketing name |
| HMN | Host marketing name |
| HVIN | Hardware version identification number |
| FVIN | Firmware version identification number |
| EMC | Electromagnetic Compatibility |
| HW | Hardware |
| SW | Software |
| Inv. No. | Inventory number |
| S/N or SN | Serial number |
| C | Compliant |
| NC | Not compliant |
| NA | Not applicable |
| NP | Not performed |
| PP | Positive peak |
| QP | Quasi peak |
| AVG | Average |
| OC | Operating channel |
| OCW | Operating channel bandwidth |
| OBW | Occupied bandwidth |
| OOB | Out of band |
| DFS | Dynamic frequency selection |
| CAC | Channel availability check |
| OP | Occupancy period |
| NOP | Non occupancy period |
| DC | Duty cycle |
| PER | Packet error rate |
| CW | Clean wave |
| MC | Modulated carrier |
| WLAN | Wireless local area network |
| RLAN | Radio local area network |
| DSSS | Dynamic sequence spread spectrum |
| OFDM | Orthogonal frequency division multiplexing |
| FHSS | Frequency hopping spread spectrum |
| GNSS | Global Navigation Satellite System |
| C/N₀ | Carrier to noise-density ratio, expressed in dB-Hz |

13 Document history

| Version | Applied changes | Date of release |
|---------|----------------------------------|-----------------|
| -/- | Initial release | 2020-12-14 |
| A | Model name, PMN and HVIN changed | 2021-03-17 |
| B | HVIN changed | 2021-03-18 |

14 Accreditation Certificate – D-PL-12076-01-04

| first page | last page |
|---|--|
|  <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleG-BV Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition</p> <p>Accreditation </p> <p>The Deutsche Akkreditierungsstelle GmbH attests that the testing laboratory CTC advanced GmbH Untertürkheimer Straße 6-10, 66117 Saarbrücken is competent under the terms of DIN EN ISO/IEC 17025:2018 to carry out tests in the following fields: Telecommunication (TC) and Electromagnetic Compatibility (EMC) for Canadian Standards</p> <p>The accreditation certificate shall only apply in connection with the notice of accreditation of 09.06.2020 with the accreditation number D-PL-12076-01. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 07 pages. Registration number of the certificate: D-PL-12076-01-04</p> <p>Frankfurt am Main, 09.06.2020  by order of: Ing. Ingrid Egner Head of Division</p> <p><small>The certificate together with its annex reflects the status at the time of the date of issue. The current status of the scope of accreditation can be found in the database of accredited bodies of Deutsche Akkreditierungsstelle GmbH. https://www.dakks.de/en/content/accredited-bodies-dakks 100.0000.000000</small></p> | <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Office Berlin Spittelmarkt 10 10117 Berlin</p> <p>Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main</p> <p>Office Braunschweig Bundesallee 100 38116 Braunschweig</p> <p>The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAkKS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf.</p> <p>No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAkKS.</p> <p>The accreditation was granted pursuant to the Act on the Accreditation Body (AkkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products (Official Journal of the European Union L 218 of 9 July 2008, p. 30). DAkKS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations.</p> <p>The up-to-date state of membership can be retrieved from the following websites: EA: www.european-accreditation.org ILAC: www.ilac.org IAF: www.iaf.nu</p> |

Note: The current certificate annex is published on the website (link see below) of the Accreditation Body DAkKS or may be received by CTC advanced GmbH on request

<https://www.dakks.de/as/ast/d/D-PL-12076-01-04e.pdf>

15 Accreditation Certificate – D-PL-12076-01-05

| first page | last page | | | |
|--|---|--|--|--|
|  <p>Deutsche Akkreditierungsstelle GmbH</p> <p>Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleGBV Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition</p> <p>Accreditation </p> <p>The Deutsche Akkreditierungsstelle GmbH attests that the testing laboratory CTC advanced GmbH Untertürkheimer Straße 6-10, 66117 Saarbrücken</p> <p>is competent under the terms of DIN EN ISO/IEC 17025:2018 to carry out tests in the following fields: Telecommunication (FCC Requirements)</p> <p>The accreditation certificate shall only apply in connection with the notice of accreditation of 09.06.2020 with the accreditation number D-PL-12076-01. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 05 pages.</p> <p>Registration number of the certificate: D-PL-12076-01-05</p> <p>Frankfurt am Main, 09.06.2020  by Dipl.-Ing. (FH) Paul Egnier Head of Division</p> <p><small>The certificate together with its annex reflects the status at the time of the date of issue. The current status of the scope of accreditation can be found in the database of accredited bodies of Deutsche Akkreditierungsstelle GmbH. https://www.dakks.de/en/content/accredited-bodies-dakks See notes annex 1.</small></p> | <p>Deutsche Akkreditierungsstelle GmbH</p> <table border="0"> <tr> <td>Office Berlin Spittelmarkt 10 10117 Berlin</td> <td>Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main</td> <td>Office Braunschweig Bundesallee 100 38116 Braunschweig</td> </tr> </table> <p>The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAkKS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf.</p> <p>No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAkKS.</p> <p>The accreditation was granted pursuant to the Act on the Accreditation Body (AAkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products (Official Journal of the European Union L 218 of 9 July 2008, p. 30). DAkKS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations.</p> <p>The up-to-date state of membership can be retrieved from the following websites: EA: www.european-accreditation.org ILAC: www.ilac.org IAF: www.iaf.nu</p> | Office Berlin Spittelmarkt 10 10117 Berlin | Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main | Office Braunschweig Bundesallee 100 38116 Braunschweig |
| Office Berlin Spittelmarkt 10 10117 Berlin | Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main | Office Braunschweig Bundesallee 100 38116 Braunschweig | | |

Note: The current certificate annex is published on the website (link see below) of the Accreditation Body DAkKS or may be received by CTC advanced GmbH on request

<https://www.dakks.de/as/ast/d/D-PL-12076-01-05e.pdf>

END OF TEST REPORT