



FCC PART 15.247  
TEST REPORT

For

**Newer Technology Inc.**

2650 Bridge Lane, Woodstock, IL

**FCC ID: UNH-MXP3802NU2C**

<b>Report Type:</b> Original Report	<b>Product Type:</b> 802.11n/g/b Wireless USB 2.0 Stick Adapter & Extension Cradle
<b>Test Engineer:</b> Allen Qiao	<i>Allen Qiao</i>
<b>Report Number:</b> R1DG120628003-00	
<b>Report Date:</b> 2012-07-09	
<b>Reviewed By:</b> Ivan Cao EMC Engineer	<i>Ivan Cao</i>
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, or any agency of the Federal Government.

\* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

## TABLE OF CONTENTS

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
EQUIPMENT MODIFICATIONS .....	6
SUPPORT EQUIPMENT.....	7
BLOCK DIAGRAM OF TEST SETUP .....	8
<b>SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>FCC §15.247 (i) &amp; §1.1307 (b) (1) &amp; §2.1093- RF EXPOSURE.....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
ANTENNA CONNECTOR CONSTRUCTION .....	11
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>12</b>
APPLICABLE STANDARD .....	12
MEASUREMENT UNCERTAINTY .....	12
EUT SETUP .....	12
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE .....	13
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST RESULTS SUMMARY .....	13
TEST DATA .....	13
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>16</b>
APPLICABLE STANDARD .....	16
MEASUREMENT UNCERTAINTY .....	16
EUT SETUP.....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	17
TEST PROCEDURE .....	17
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	17
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST RESULTS SUMMARY .....	18
TEST DATA .....	18
<b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>	<b>32</b>
APPLICABLE STANDARD .....	32
TEST PROCEDURE .....	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA .....	32
<b>FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER .....</b>	<b>43</b>
APPLICABLE STANDARD .....	43
TEST PROCEDURE .....	43

TEST EQUIPMENT LIST AND DETAILS.....43  
TEST DATA .....43

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....54**

APPLICABLE STANDARD .....54  
TEST PROCEDURE .....54  
TEST EQUIPMENT LIST AND DETAILS.....54  
TEST DATA .....54

**FCC §15.247(e) - POWER SPECTRAL DENSITY .....61**

APPLICABLE STANDARD .....61  
TEST PROCEDURE .....61  
TEST EQUIPMENT LIST AND DETAILS.....61  
TEST DATA .....61

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Newer Technology Inc.*'s product, model number: MXP3802NU2C (*FCC ID: UNH-MXP3802NU2C*) or ("EUT") in this report is a 802.11n/g/b Wireless USB 2.0 Stick Adapter & Extension Cradle, which was measured approximately:6.0 cm (L) x2.1cm (W) x1.0cm (H), rated input voltage: DC 5V from PC, the operating frequency for 802.11b/g/n20 were 2412-2462 MHz and n40 were 2422-2452MHz.

*\* All measurement and test data in this report was gathered from production sample serial number: 120628003 (Assigned by BAACL). The EUT was received on 2012-06-28.*

### Objective

This report is prepared on behalf of *Newer Technology Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

No related submittal(s).

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is  $\pm 0.96$  dB, the uncertainty of any radiation on emissions measurement is  $\pm 4.0$  dB

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b and 802.11g, 802.11n20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

EUT for 802.11b, 802.11g and 802.11 n20 modes were tested with Channel 1, 6 and 11.

For 802.11n40 mode, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	/	/
4	2437	/	/
5	2442	/	/

EUT was tested with Channel 1, 4 and 7.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

### EUT Exercise Software

The test was performed under “QA537x” which was provided by the manufacturer.


### Equipment Modifications

No modification was made to the EUT tested.

**Support Equipment**

Manufacturer	Description	Model	Serial Number
Dell	Laptop	PP11L	N/A

### Block Diagram of Test Setup





**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (i), §1.1307 (b)(1), §2.1093	Maximum Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

---

**FCC §15.247 (i) & §1.1307 (b) (1) & §2.1093- RF EXPOSURE**

---

**Applicable Standard**

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v03r03, no SAR required if power is lower than the flowing threshold:

When routine evaluation is required for SAR and the output power is  $\leq 60/f(\text{GHz})$  mW, the test reduction and test exclusion procedures given herein, or in KDB 616217 or KDB 648474, are applicable.

A device may be used in portable exposure conditions with no restrictions on host platforms when either the source-based time-averaged output power is  $\leq 60/f(\text{GHz})$  mW or all measured 1-g SAR are  $< 0.4$  W/kg. 10 When SAR evaluation is required, the most conservative exposure conditions for all expected operating configurations must be tested.

**Measurement Result**

Conducted output power= 11.74dBm

Antenna gain = 1.0 dBi

SAR exclusion threshold= $60/f=60/2.462=24.37$  mW = 13.87 dBm  $> 11.74$ dBm

**So the SAR evaluation is not necessary.**

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
  - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **Antenna Connector Construction**

The EUT has two printer antenna on the print circuit board, which complied with 15.203, the maximum gain is 1.0dBi, please refer to the internal photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard


FCC§15.207

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Dongguan) is  $\pm 2.4$  dB ( $k=2$ , 95% level of confidence).

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The Laptop was connected to a 120 VAC/60 Hz power source

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<i>Frequency Range</i>	<i>IF B/W</i>
150 kHz – 30 MHz	9 kHz

## Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2011-11-24	2012-11-23
Rohde & Schwarz	L.I.S.N.1	ESH2-Z5	892107/021	2011-11-17	2012-11-16
Com-Power	L.I.S.N.2	LI-200	12005	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**3.59 dB at 0.280 MHz** in the **Neutral** conducted mode

## Test Data


### Environmental Conditions

<b>Temperature:</b>	25 ° C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0 kPa

*The testing was performed by Allen Qiao on 2012-07-07.*


*Test Mode: Transmitting*

120 V, 60 Hz, Line:



Frequency (MHz)	Corrected Result (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/QP/Ave.)
0.285	43.65	0.42	52.14	8.49	Ave.
0.320	42.55	0.42	51.14	8.59	Ave.
0.600	36.97	0.43	46.00	9.03	Ave.
0.320	44.54	0.42	61.14	16.60	QP
0.285	44.34	0.42	62.14	17.80	QP
0.850	27.92	0.44	46.00	18.08	Ave.
0.950	27.49	0.45	46.00	18.51	Ave.
0.600	37.15	0.43	56.00	18.85	QP
1.025	25.89	0.45	46.00	20.11	Ave.
0.950	35.77	0.45	56.00	20.23	QP
1.025	35.34	0.45	56.00	20.66	QP
0.850	34.26	0.44	56.00	21.74	QP

**120V, 60 Hz, Neutral:**



Frequency (MHz)	Corrected Result (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK /QP/Ave.)
0.280	48.70	0.42	52.29	3.59	Ave.
0.565	40.07	0.43	46.00	5.93	Ave.
0.245	45.72	0.42	53.29	7.57	Ave.
0.540	37.71	0.42	46.00	8.29	Ave.
0.845	37.52	0.44	46.00	8.48	Ave.
0.420	36.82	0.42	48.29	11.47	Ave.
0.280	49.47	0.42	62.29	12.82	QP
0.565	41.90	0.43	56.00	14.10	QP
0.420	43.81	0.42	58.29	14.48	QP
0.245	47.23	0.42	63.29	16.06	QP
0.540	39.88	0.42	56.00	16.12	QP
0.845	38.49	0.44	56.00	17.51	QP

## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Dongguan) is 4.0 dB(k=2, 95% level of confidence) .

### EUT Setup

Below 1GHz:



Above 1GHz:





The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

### EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>	<i>Detector</i>
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave.

### Test Procedure

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2011-08-02	2012-08-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-07-05	2012-07-04
Mini-circuits	Amplifier	ZVA-213+	T-E27H	2011-11-24	2012-11-23
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-12-01	2012-11-30
HP	Spectrum Analyzer	8593A	2919A00242	2011-07-09	2012-07-08
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

**9.42 dB at 4874 MHz in the Vertical polarization (802.11b mode)**

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 ° C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0 kPa

*The testing was performed by Allen Qiao on 2012-07-07.*

Mode: Transmitting

1) 30MHz-25GHz

802.11b Mode:

Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/QP/Ave.)	Polar (H/V)	Corrected Factor (dB)	Correction Data (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Comment
Low Channel (2412MHz)								
4824	32.51	Ave.	V	10.79	43.3	54	10.7	Harmonic
4824	30.16	Ave.	H	10.79	40.95	54	13.05	Harmonic
321.2	34.13	QP	H	-4.82	29.31	46	16.69	spurious
321.2	33.68	QP	V	-4.82	28.86	46	17.14	spurious
2378	30.01	Ave.	V	6.83	36.84	54	17.16	spurious
2378	27.24	Ave.	H	6.83	34.07	54	19.93	spurious
4824	40.96	PK	V	10.79	51.75	74	22.25	Harmonic
4824	38.32	PK	H	10.79	49.11	74	24.89	Harmonic
2378	39.36	PK	V	6.95	46.31	74	27.69	spurious
2378	37.29	PK	H	6.95	44.24	74	29.76	spurious
2412	54.76	PK	H	35	89.76	N/A	N/A	Fundamental
2412	49.13	Ave.	H	35	84.13	N/A	N/A	Fundamental
2412	56.24	PK	V	35	91.24	N/A	N/A	Fundamental
2412	51.24	Ave.	V	35	86.24	N/A	N/A	Fundamental
Middle Channel (2437MHz)								
2437	50.03	PK	H	35.2	85.23	N/A	N/A	Fundamental
2437	45.13	Ave.	H	35.2	80.33	N/A	N/A	Fundamental
2437	51.25	PK	V	35.2	86.45	N/A	N/A	Fundamental
2437	46.51	Ave.	V	35.2	81.71	N/A	N/A	Fundamental
4874	33.5	Ave.	V	11.08	44.58	54	9.42	Harmonic
4874	31.82	Ave.	H	11.08	42.9	54	11.1	Harmonic
366.5	33.91	QP	H	-4.41	29.5	46	16.5	spurious
366.5	32.88	QP	V	-4.41	28.47	46	17.53	spurious
4874	42.67	PK	V	11.08	53.75	74	20.25	Harmonic
4874	40.05	PK	H	11.08	51.13	74	22.87	Harmonic
High Channel (2462MHz)								
4924	32.85	Ave.	V	10.98	43.83	54	10.17	Harmonic
4924	30.33	Ave.	H	10.98	41.31	54	12.69	Harmonic
2483.5	30.46	Ave.	V	7.53	37.99	54	16.01	spurious
2483.5	29.03	Ave.	H	7.53	36.56	54	17.44	spurious
402.3	32.06	QP	H	-3.86	28.2	46	17.8	spurious
402.3	31.12	QP	V	-3.86	27.26	46	18.74	spurious
4924	42.97	PK	V	10.98	53.95	74	20.05	Harmonic
4924	40.53	PK	H	10.98	51.51	74	22.49	Harmonic
2483.5	39.24	PK	V	7.53	46.77	74	27.23	spurious
2483.5	37.92	PK	H	7.53	45.45	74	28.55	spurious
2462	48.1	PK	H	35.3	83.4	N/A	N/A	Fundamental
2462	42.05	Ave.	H	35.3	77.35	N/A	N/A	Fundamental
2462	53.43	PK	V	35.3	88.73	N/A	N/A	Fundamental
2462	47.68	Ave.	V	35.3	82.98	N/A	N/A	Fundamental

802.11g Mode:

Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/QP/Ave.)	Polar (H/V)	Corrected Factor (dB)	Correction Data (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Comment
Low Channel (2412MHz)								
4824	32.39	Ave.	V	10.79	43.18	54	10.82	Harmonic
4824	30.43	Ave.	H	10.79	41.22	54	12.78	Harmonic
2386	30.47	Ave.	V	6.83	37.3	54	16.7	spurious
321.2	33.22	QP	H	-4.82	28.4	46	17.6	spurious
321.2	32.63	QP	V	-4.82	27.81	46	18.19	spurious
2386	28.23	Ave.	H	6.83	35.06	54	18.94	spurious
4824	41.88	PK	V	10.79	52.67	74	21.33	Harmonic
4824	39.43	PK	H	10.79	50.22	74	23.78	Harmonic
2378	39.91	PK	V	6.95	46.86	74	27.14	spurious
2378	38.06	PK	H	6.95	45.01	74	28.99	spurious
2412	50.58	PK	H	35	85.58	N/A	N/A	Fundamental
2412	40.95	Ave.	H	35	75.95	N/A	N/A	Fundamental
2412	51.64	PK	V	35	86.64	N/A	N/A	Fundamental
2412	41.88	Ave.	V	35	76.88	N/A	N/A	Fundamental
Middle Channel (2437MHz)								
4874	31.6	Ave.	V	11.08	42.68	54	11.32	Harmonic
4874	29.14	Ave.	H	11.08	40.22	54	13.78	Harmonic
366.5	32.94	QP	H	-4.41	28.53	46	17.47	spurious
366.5	31.83	QP	V	-4.41	27.42	46	18.58	spurious
4874	40.05	PK	V	11.08	51.13	74	22.87	Harmonic
4874	38.94	PK	H	11.08	50.02	74	23.98	Harmonic
2437	47.74	PK	H	35.2	82.94	N/A	N/A	Fundamental
2437	37.39	Ave.	H	35.2	72.59	N/A	N/A	Fundamental
2437	51.49	PK	V	35.2	86.69	N/A	N/A	Fundamental
2437	42.54	Ave.	V	35.2	77.74	N/A	N/A	Fundamental
High Channel (2462MHz)								
4924	32.12	Ave.	V	10.98	43.1	54	10.9	Harmonic
4924	30.07	Ave.	H	10.98	41.05	54	12.95	Harmonic
2483.5	31.28	Ave.	V	7.53	38.81	54	15.19	spurious
402.3	33.68	QP	H	-3.86	29.82	46	16.18	spurious
2483.5	29.16	Ave.	H	7.53	36.69	54	17.31	spurious
402.3	32.03	QP	V	-3.86	28.17	46	17.83	spurious
4924	42.87	PK	V	10.98	53.85	74	20.15	Harmonic
4924	39.33	PK	H	10.98	50.31	74	23.69	Harmonic
2483.5	39.81	PK	V	7.53	47.34	74	26.66	spurious
2483.5	38.29	PK	H	7.53	45.82	74	28.18	spurious
2462	48.64	PK	H	35.3	83.94	N/A	N/A	Fundamental
2462	39.91	Ave.	H	35.3	75.21	N/A	N/A	Fundamental
2462	52.49	PK	V	35.3	87.79	N/A	N/A	Fundamental
2462	42.18	Ave.	V	35.3	77.48	N/A	N/A	Fundamental

802.11n20 Mode:


Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/QP/Ave.)	Polar (H/V)	Corrected Factor (dB)	Correction Data (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Comment
Low Channel (2412MHz)								
2412	48.36	PK	H	35	83.36	N/A	N/A	Fundamental
2412	37.65	Ave.	H	35	72.65	N/A	N/A	Fundamental
2412	49.19	PK	V	35	84.19	N/A	N/A	Fundamental
2412	40.18	Ave.	V	35	75.18	N/A	N/A	Fundamental
4824	33.46	Ave.	V	10.79	44.25	54	9.75	Harmonic
4824	30.83	Ave.	H	10.79	41.62	54	12.38	Harmonic
2386	31.53	Ave.	V	6.83	38.36	54	15.64	spurious
321.2	34.15	QP	H	-4.82	29.33	46	16.67	spurious
321.2	33.36	QP	V	-4.82	28.54	46	17.46	spurious
2386	29.11	Ave.	H	6.83	35.94	54	18.06	spurious
4824	42.66	PK	V	10.79	53.45	74	20.55	Harmonic
4824	39.94	PK	H	10.79	50.73	74	23.27	Harmonic
2378	39.34	PK	V	6.95	46.29	74	27.71	spurious
2378	37.72	PK	H	6.95	44.67	74	29.33	spurious
Middle Channel (2437MHz)								
2437	45.01	PK	H	35.2	80.21	N/A	N/A	Fundamental
2437	35.24	Ave.	H	35.2	70.44	N/A	N/A	Fundamental
2437	46.51	PK	V	35.2	81.71	N/A	N/A	Fundamental
2437	37.45	Ave.	V	35.2	72.65	N/A	N/A	Fundamental
4874	32.95	Ave.	V	11.08	44.03	54	9.97	Harmonic
4874	31.13	Ave.	H	11.08	42.21	54	11.79	Harmonic
366.5	33.86	QP	V	-4.41	29.45	46	16.55	spurious
366.5	32.37	QP	H	-4.41	27.96	46	18.04	spurious
4874	42.19	PK	V	11.08	53.27	74	20.73	Harmonic
4874	40.24	PK	H	11.08	51.32	74	22.68	Harmonic
High Channel (2462MHz)								
2462	46.38	PK	H	35.3	81.68	N/A	N/A	Fundamental
2462	36.39	Ave.	H	35.3	71.69	N/A	N/A	Fundamental
2462	50.56	PK	V	35.3	85.86	N/A	N/A	Fundamental
2462	39.78	Ave.	V	35.3	75.08	N/A	N/A	Fundamental
4924	33.06	Ave.	V	10.98	44.04	54	9.96	Harmonic
4924	31.19	Ave.	H	10.98	42.17	54	11.83	Harmonic
2483.5	31.93	Ave.	V	7.53	39.46	54	14.54	spurious
2483.5	29.25	Ave.	H	7.53	36.78	54	17.22	spurious
402.3	32.17	QP	H	-3.86	28.31	46	17.69	spurious
402.3	31.52	QP	V	-3.86	27.66	46	18.34	spurious
4924	42.36	PK	V	10.98	53.34	74	20.66	Harmonic
4924	40.18	PK	H	10.98	51.16	74	22.84	Harmonic
2483.5	40.18	PK	V	7.53	47.71	74	26.29	spurious
2483.5	38.86	PK	H	7.53	46.39	74	27.61	spurious

802.11n40 Mode:


Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/QP/Ave.)	Polar (H/V)	Corrected Factor (dB)	Correction Data (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Comment
Low Channel (2422MHz)								
2422	43.76	PK	H	35	78.76	N/A	N/A	Fundamental
2422	33.33	Ave.	H	35	68.33	N/A	N/A	Fundamental
2422	49.78	PK	V	35	84.78	N/A	N/A	Fundamental
2422	38.61	Ave.	V	35	73.61	N/A	N/A	Fundamental
4844	32.73	Ave.	V	10.79	43.52	54	10.48	Harmonic
4844	30.19	Ave.	H	10.79	40.98	54	13.02	Harmonic
2386	31.75	Ave.	V	6.83	38.58	54	15.42	spurious
321.2	33.39	QP	V	-4.82	28.57	46	17.43	spurious
2386	29.16	Ave.	H	6.83	35.99	54	18.01	spurious
321.2	32.81	QP	H	-4.82	27.99	46	18.01	spurious
4824	41.82	PK	V	10.79	52.61	74	21.39	Harmonic
4824	39.24	PK	H	10.79	50.03	74	23.97	Harmonic
2378	40.06	PK	V	6.95	47.01	74	26.99	spurious
2378	37.88	PK	H	6.95	44.83	74	29.17	spurious
Middle Channel (2437MHz)								
2437	43.08	PK	H	35.2	78.28	N/A	N/A	Fundamental
2437	33.81	Ave.	H	35.2	69.01	N/A	N/A	Fundamental
2437	49.15	PK	V	35.2	84.35	N/A	N/A	Fundamental
2437	39.58	Ave.	V	35.2	74.78	N/A	N/A	Fundamental
4874	32.96	Ave.	V	11.08	44.04	54	9.96	Harmonic
4874	30.84	Ave.	H	11.08	41.92	54	12.08	Harmonic
366.5	33.14	QP	H	-4.41	28.73	46	17.27	spurious
366.5	32.57	QP	V	-4.41	28.16	46	17.84	spurious
4874	42.26	PK	V	11.08	53.34	74	20.66	Harmonic
4874	39.98	PK	H	11.08	51.06	74	22.94	Harmonic
High Channel (2452MHz)								
2452	45.82	PK	H	35.3	81.12	N/A	N/A	Fundamental
2452	35.88	Ave.	H	35.3	71.18	N/A	N/A	Fundamental
2452	49.4	PK	V	35.3	84.7	N/A	N/A	Fundamental
2452	39.67	Ave.	V	35.3	74.97	N/A	N/A	Fundamental
4904	32.42	Ave.	V	10.98	43.4	54	10.6	Harmonic
4904	30.84	Ave.	H	10.98	41.82	54	12.18	Harmonic
2483.5	32.66	Ave.	V	7.53	40.19	54	13.81	spurious
402.3	33.76	QP	V	-3.86	29.9	46	16.1	spurious
2483.5	30.3	Ave.	H	7.53	37.83	54	16.17	spurious
402.3	32.83	QP	H	-3.86	28.97	46	17.03	spurious
4904	41.36	PK	V	10.98	52.34	74	21.66	Harmonic
4904	39.13	PK	H	10.98	50.11	74	23.89	Harmonic
2483.5	41.73	PK	V	7.53	49.26	74	24.74	spurious
2483.5	39.48	PK	H	7.53	47.01	74	26.99	spurious

Conducted Spurious Emissions at Antenna Port


802.11b Low Channel




802.11b Middle Channel



### 802.11b High Channel




### 802.11g Low Channel







### 802.11g Middle Channel




### 802.11g High Channel




**Chain 0:802.11n20 Low Channel**




**Chain 0:802.11n20 Middle Channel**




**Chain 0:802.11n20 High Channel**




**Chain 1:802.11n20 Low Channel**




**Chain 1:802.11n20 Middle Channel**




**Chain 1:802.11n20 High Channel**




**Chain 0:802.11n40 Low Channel**




**Chain 0:802.11n40 Middle Channel**




### Chain 0:802.11n40 High Channel




### Chain 1:802.11n40 Low Channel



**Chain 1:802.11n40 High Channel**



**Chain 1:802.11n40 High Channel**




## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 ° C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0kPa

*The testing was performed by Allen Qiao on 2012-07-07.*


**Test Result:** Pass.

Please refer to the following tables and plots.




Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (KHz)
Chain 0:802.11b mode			
Low	2412	10.4	>500
Middle	2437	10.4	>500
High	2462	10.4	>500
Chain 0:802.11g mode			
Low	2412	16.48	>500
Middle	2437	16.48	>500
High	2462	16.48	>500
Chain 0:802.11n20 mode			
Low	2412	17.12	>500
Middle	2437	17.12	>500
High	2462	17.12	>500
Chain 1:802.11n20 mode			
Low	2412	17.12	>500
Middle	2437	17.12	>500
High	2462	17.12	>500
Chain 0:802.11n40 mode			
Low	2422	35.52	>500
Middle	2437	35.52	>500
High	2452	35.52	>500
Chain 1:802.11n40 mode			
Low	2422	35.52	>500
Middle	2437	35.52	>500
High	2452	35.52	>500


### 802.11b Low Channel




### 802.11b Middle Channel




### 802.11b High Channel




### 802.11g Low Channel




### 802.11g Middle Channel




### 802.11g High Channel




**Chain 0:802.11n20 Low Channel**




**Chain 0:802.11n20 Middle Channel**




### Chain 0:802.11n20 High Channel




### Chain 1:802.11n20 Low Channel




### Chain 1:802.11n20 Middle Channel




### Chain 1:802.11n20 High Channel



**Chain 0:802.11n40 Low Channel**




**Chain 0:802.11n40 Middle Channel**







### Chain 0:802.11n40 High Channel




### Chain 1:802.11n40 Low Channel



**Chain 1:802.11n40 Middle Channel**



**Chain 1:802.11n40 High Channel**




## FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	100.0 kPa

*The testing was performed by Allen Qiao on 2012-07-07.*

*Test Mode: Transmitting*

Channel	Frequency	Conducted Output Power	Limit	Result
	(MHz)	(dBm)	(dBm)	
802.11b mode				
Low	2412 MHz	11.52	30	PASS
Middle	2437 MHz	11.73	30	PASS
High	2462 MHz	11.70	30	PASS
802.11g mode				
Low	2412 MHz	11.67	30	PASS
Middle	2437 MHz	11.74	30	PASS
High	2462 MHz	11.65	30	PASS
Chain 0:802.11n20 mode				
Low	2412 MHz	8.70	30	PASS
Middle	2437 MHz	8.37	30	PASS
High	2462 MHz	8.54	30	PASS
Chain 1:802.11n20 mode				
Low	2412 MHz	8.64	30	PASS
Middle	2437 MHz	8.65	30	PASS
High	2462 MHz	8.55	30	PASS
Chain 0:802.11n40 mode				
Low	2422 MHz	8.48	30	PASS
Middle	2437 MHz	8.26	30	PASS
High	2452 MHz	8.46	30	PASS
Chain 1:802.11n40 mode				
Low	2422 MHz	8.39	30	PASS
Middle	2437 MHz	8.34	30	PASS
High	2452 MHz	8.39	30	PASS

Total power of 802.11n: Chain 0+ Chain 1


Channel	Frequency (MHz)	Data Rate (Mbps)	Output Power (dBm)	Limit (dBm)	Result
802.11n20 Chain 0+1					
Low	2412	6.5	11.68	30	pass
Middle	2437	6.5	11.52	30	pass
High	2462	6.5	11.56	30	pass
802.11n40 Chain 0+1					
Low	2422	13.5	11.45	30	pass
Middle	2437	13.5	11.31	30	pass
High	2452	13.5	11.44	30	pass

Note: MIMO technology only for 802.11n.


The antenna gain is 1.0 dBi.

Please refer to the following plots


### 802.11b RF Output Power, Low Channel




### 802.11b RF Output Power, Middle Channel




### 802.11b RF Output Power, High Channel




### 802.11g RF Output Power, Low Channel




### 802.11g RF Output Power, Middle Channel




### 802.11g RF Output Power, High Channel



### Chain 0:802.11n20 RF Output Power, Low Channel




### Chain 0:802.11n20 RF Output Power, Middle Channel







### Chain 0:802.11n20 RF Output Power, High Channel




### Chain 1:802.11n20 RF Output Power, Low Channel




### Chain 1:802.11n20 RF Output Power, Middle Channel




### Chain 1:802.11n20 RF Output Power, High Channel




### Chain 0:802.11n40 RF Output Power, Low Channel




### Chain 0:802.11n40 RF Output Power, Middle Channel




### Chain 0:802.11n40 RF Output Power, High Channel




### Chain 1:802.11n40 RF Output Power, Low Channel



### Chain 1:802.11n40 RF Output Power, Middle Channel



### Chain 1:802.11n40 RF Output Power, High Channel



## **FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### **Test Data**

#### **Environmental Conditions**


<b>Temperature:</b>	25 ° C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0 kPa

*The testing was performed by Allen Qiao on 2012-07-07.*

#### **Test Result: Compliance**


Please refer to following plots.

**802.11b: Band Edge, Left Side**




Date: 7.JUL.2012 15:10:59

**802.11b: Band Edge, Right Side**




Date: 7.JUL.2012 15:16:58

**802.11g: Band Edge, Left Side**



Date: 7.JUL.2012 15:25:27


**802.11g: Band Edge, Right Side**



Date: 7.JUL.2012 15:41:43




**Chain 0:802.11n20: Band Edge, Left Side**




Date: 7.JUL.2012 15:49:45

**Chain 0:802.11n20: Band Edge, Right Side**




Date: 7.JUL.2012 15:56:31


**Chain 1:802.11n20: Band Edge, Left Side**




**Chain 1:802.11n20: Band Edge, Right Side**




**Chain 0:802.11n40: Band Edge, Left Side**




**Chain 0:802.11n40: Band Edge, Right Side**



**Chain 1:802.11n40: Band Edge, Left Side**



**Chain 1:802.11n40: Band Edge, Right Side**



## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. According to KDB 558074 D01 DTS Meas Guidance v01, set the RBW = 100 kHz, VBW  $\geq$  300 kHz, set the span to 5-30 % greater than the EBW.
4. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
5. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where  $BWCF = 10\log(3 \text{ kHz}/100 \text{ kHz}) = -15.2 \text{ dB}$ .

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23

\* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	48 %
ATM Pressure:	100.0 kPa

*The testing was performed by Allen Qiao on 2012-07-07 .*

*Test Mode: Transmitting*


**Test Result:** Pass

Channel	Frequency (MHz)	Data Rate (Mbps)	Reading Level (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
Chain 0:802.11b						
Low	2412	1	-3.19	-18.39	8	pass
Middle	2437	1	-3.05	-18.25	8	pass
High	2462	1	-2.83	-18.03	8	pass
Chain 0:802.11g						
Low	2412	6	-10.61	-25.81	8	pass
Middle	2437	6	-10.19	-25.39	8	pass
High	2462	6	-10.46	-25.66	8	pass
Chain 0:802.11n20						
Low	2412	6.5	-13.62	-28.82	8	pass
Middle	2437	6.5	-13.83	-29.03	8	pass
High	2462	6.5	-13.67	-28.87	8	pass
Chain 1:802.11n20						
Low	2412	6.5	-13.49	-28.69	8	pass
Middle	2437	6.5	-13.24	-28.44	8	pass
High	2462	6.5	-13.71	-28.91	8	pass
Chain 0:802.11n40						
Low	2422	13.5	-17.08	-32.28	8	pass
Middle	2437	13.5	-17.01	-32.21	8	pass
High	2452	13.5	-17.04	-32.24	8	pass
Chain 1:802.11n40						
Low	2422	13.5	-17.14	-32.34	8	pass
Middle	2437	13.5	-16.92	-32.12	8	pass
High	2452	13.5	-16.74	-31.94	8	pass


**Note:** the antenna gain is 1.0dBi.

Please refer to the following plots


### Power Spectral Density, 802.11b Low Channel




### Power Spectral Density, 802.11b Middle Channel



### Power Spectral Density, 802.11b High Channel




### Power Spectral Density, 802.11g Low Channel







### Power Spectral Density, 802.11g Middle Channel




### Power Spectral Density, 802.11g High Channel




### Chain 0: Power Spectral Density, 802.11n20 Low Channel




### Chain 0: Power Spectral Density, 802.11n20 Middle Channel




### Chain 0: Power Spectral Density, 802.11n20 High Channel




### Chain 1: Power Spectral Density, 802.11n20 Low Channel




### Chain 1:Power Spectral Density, 802.11n20 Middle Channel




### Chain 1:Power Spectral Density, 802.11n20 High Channel




### Chain 0:Power Spectral Density, 802.11n40 Low Channel




### Chain 0:Power Spectral Density, 802.11n40 Middle Channel




### Chain 0: Power Spectral Density, 802.11n40 High Channel




### Chain 1: Power Spectral Density, 802.11n40 Low Channel



### Chain 1:Power Spectral Density, 802.11n40 Middle Channel



### Chain 1:Power Spectral Density, 802.11n40 High Channel



\*\*\*\*\* END OF REPORT \*\*\*\*\*