



#### FOR CHAIN 1: CH 1





**CH 7** 





## 4.6 BAND EDGES MEASUREMENT

## 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

## 4.6.2 TEST INSTRUMENTS

#### For Single TX:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### For Dual TX:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Spectrum Analyzer	FSP40	100269	Aug. 07, 2007
HORN Antenna	BBHA 9120 D	9120D-563	Jul. 26, 2007
HORN Antenna	BBHA 9170	BBHA9170242	Jan. 16, 2008
RF signal cable	SUCOFLEX 104	218188/218189	Nov. 14, 2007
RF signal cable	8D-FB	Cable-HYCH9-01	Mar. 08, 2007
Software	ADT_Radiated_V7.6	NA	NA
Antenna Tower	2070/2080	512.835.4684	NA
Turn Table	2087-2.03	NA	NA
Antenna Tower &Turn Table Controller EMCO	2090	NA	NA

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.



## 4.6.3 TEST PROCEDURE

## For Single TX:

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 10Hz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW = VBW = 100kHz; Average RBW = 1MHz, VBW = 10Hz) are attached on the following pages.

## For Dual TX:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW = VBW = 100kHz; Average RBW = 1MHz, VBW = 10Hz)

**NOTE:** The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

## 4.6.4 DEVIATION FROM TEST STANDARD

No deviation



## 4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

### 4.6.6 TEST RESULTS

The spectrum plots are attached on the following 24 images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

#### 802.11b DSSS MODULATION:

### NOTE 1:

The band edge emission plot of DSSS technique on the next page shows 49.46dBc between carrier maximum power and local maximum emission in restrict band (2.386080000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 106.15dBuV/m (Peak), so the maximum field strength in restrict band is 106.15 - 49.46 = 56.69dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of DSSS technique on the next page shows 52.05dBc between carrier maximum power and local maximum emission in restrict band (2.386480000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 101.63dBuV/m (Average), so the maximum field strength in restrict band is 101.63 - 52.05 = 49.58dBuV/m which is under 54dBuV/m limit.

### NOTE 2:


The band edge emission plot of DSSS technique on the next second page shows 50.36dBc between carrier maximum power and local maximum emission in restrict band (2.488060000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 106.36dBuV/m (Peak), so the maximum field strength in restrict band is 106.36 – 50.36= 56.00dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on the next third page shows 53.69dBc between carrier maximum power and local maximum emission in restrict band (2.487660000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 102.00dBuV/m (Average), so the maximum field strength in restrict band is 102.00 - 53.69 = 48.31dBuV/m which is under 54dBuV/m limit.
















#### 802.11g OFDM MODULATION:

#### NOTE 1:

The band edge emission plot of OFDM technique on the next page shows 45.10dBc between carrier maximum power and local maximum emission in restrict band (2.389519231GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 109.34dBuV/m (Peak), so the maximum field strength in restrict band is 109.34 - 45.10 = 64.24dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of OFDM technique on the next page shows 48.87dBc between carrier maximum power and local maximum emission in restrict band (2.39000000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 97.56dBuV/m (Average), so the maximum field strength in restrict band is 97.56 – 48.87 = 48.69dBuV/m which is under 54dBuV/m limit.

#### NOTE 2:


The band edge emission plot of OFDM technique on the next second page shows 46.27dBc between carrier maximum power and local maximum emission in restrict band (2.484141026GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 108.65dBuV/m (Peak), so the maximum field strength in restrict band is 108.65 - 46.27 = 62.38dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on the next third page shows 48.70dBc between carrier maximum power and local maximum emission in restrict band (2.483500000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 97.17dBuV/m (Average), so the maximum field strength in restrict band is 97.17 - 48.70 = 48.47dBuV/m which is under 54dBuV/m limit.
















#### DRAFT 802.11n (20MHz) OFDM MODULATION:

#### NOTE 1:

The band edge emission plot of OFDM technique on the next page shows 42.71Bc between carrier maximum power and local maximum emission in restrict band (2.389200000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 111.04dBuV/m (Peak), so the maximum field strength in restrict band is 111.04 - 42.71 = 68.33dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of OFDM technique on the next page shows 49.32dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 101.63dBuV/m (Average), so the maximum field strength in restrict band is 101.63 – 49.32 = 52.31dBuV/m which is under 54dBuV/m limit.

#### NOTE 2:


The band edge emission plot of OFDM technique on the next second page shows 44.34dBc between carrier maximum power and local maximum emission in restrict band (2.483900000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 111.27dBuV/m (Peak), so the maximum field strength in restrict band is 111.27 - 44.34 = 66.93dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on the next third page shows 50.54dBc between carrier maximum power and local maximum emission in restrict band (2.483500000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 101.88dBuV/m (Average), so the maximum field strength in restrict band is 101.88 - 50.54 = 51.34dBuV/m which is under 54dBuV/m limit.
















#### DRAFT 802.11n (40MHz) OFDM MODULATION:

#### NOTE 1:

The band edge emission plot of OFDM technique on the next page shows 38.87dBc between carrier maximum power and local maximum emission in restrict band (2.382400000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 104.50dBuV/m (Peak), so the maximum field strength in restrict band is 104.50 - 38.87 = 65.63dBuV/m which is under 74dBuV/m limit.


The band edge emission plot of OFDM technique on the next page shows 41.76dBc between carrier maximum power and local maximum emission in restrict band (2.39000000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 94.71dBuV/m (Average), so the maximum field strength in restrict band is 94.71 - 41.76 = 52.95dBuV/m which is under 54dBuV/m limit.

#### NOTE 2:


The band edge emission plot of OFDM technique on the next second page shows 40.95dBc between carrier maximum power and local maximum emission in restrict band (2.487100000GHz). The emission of carrier strength list in the test result of channel 7 at the item 4.2.7 is 103.83dBuV/m (Peak), so the maximum field strength in restrict band is 103.83 - 40.95 = 62.88dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on the next third page shows 41.33dBc between carrier maximum power and local maximum emission in restrict band (2.483500000GHz). The emission of carrier strength list in the test result of channel 7 at the item 4.2.7 is 94.30dBuV/m (Average), so the maximum field strength in restrict band is 94.30 - 41.33 = 52.97dBuV/m which is under 54dBuV/m limit.
















## 4.7 ANTENNA REQUIREMENT

## 4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

## 4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Printed Dipole antenna without connector. The maximum Gain of the antenna is 1dBi.



# 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA, CSA
R.O.C.	TAF, BSMI, NCC
Netherlands	Telefication
Singapore	GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

<u>www.adt.com.tw/index.5/phtml</u>. If you have any comments, please feel free to contact us at the following:

## Linko EMC/RF Lab:

Tel: 886-2-26052180 Fax: 886-2-26051924

#### Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343 Fax: 886-3-5935342

# Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232 Fax: 886-3-3185050

Web Site: <u>www.adt.com.tw</u>

The address and road map of all our labs can be found in our web site also.



## 7. APPENDIX-A MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.