

MPE Calculations

Systems operating under the provision of 47 CFR 1.1307(b)(1) shall be operated in a manor that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). The MPE calculation for this exposure is shown below.

Using the Antennas with highest output power:

The peak radiated output power (EIRP) is calculated as follows:

Antenna	Frequency (GHz)	Power input to the antenna (P) (dBm)	Power gain of the antenna (G) (dBi)	EIRP (P+G) (dBm)	EIRP Log ^{-1(dBm/10)} (mW)
giga Ant RUFA 2.4GHz SMD	2.4	18.50	4.40	22.90	194.98

EIRP = P + GWhere

P = Power input to the antenna (mW).

G = Power gain of the antenna (dBi)

The numeric gain (G) of the antenna with a gain specified in dB is determined by:

Antenna	Frequency (GHz)	Antenna Gain (G) (dBi)	Numeric Antenna Gain Log ^{-1(dBm/10)} (dB)
giga Ant RUFA 2.4GHz SMD	2.4	4.40	2.75

 $G = Log^{-1}$ (dB antenna gain/10)

Power density at the specific separation:

				Numeric Power	Maximum Power	Maximum Power
			Power input to	Gain of the	Spectral Density	Spectral Density
		Frequency	the antenna (P)	Antenna (G)	$S=PG/(4R^2\pi)$	Limit
	Antenna	(GHz)	(mW)	(dB)	(<i>mW/cm</i> ²)	(mW/cm^2)
g	iga Ant RUFA 2.4GHz SMD	2.4	70.79	2.75	0.039	1.00

 $S = PG/(4R^2\pi)$

Where

S = Maximum power density (mW/cm²)

P = Power input to the antenna (mW).

G = Numeric power gain of the antenna

R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)

The maximum permissible exposure (MPE) for the general population is 1mW/cm².

The power density at 20cm does not exceed the 1mW/cm² limit. Therefore, the exposure condition is compliant with FCC rules.