

## Compliance with 47 CFR 15.247(i)

*“Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.”*

The EUT is a 2.4GHz transmitter installed in the Rocket Fish M/N RF-WHTIB wireless rear-channel speaker extender. The EUT will only be used with a separation distance of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). The EUT has two antenna ports; both ports use the same antenna model. The max gain of the antenna is +2dBi. The maximum peak conducted output power is 7.9mW.

The maximum peak power is 12.52 mW (EIRP) for FCC ID: UQ5RFWHTIBREC. The transmit frequency is in the 2400-2483.5MHz frequency range. The EUT is not subject to routine environmental evaluation per 47 CFR 2.1091. Per 47 CFR 1.1310, the EUT must meet the General Population/ Uncontrolled exposure limits listed in Table 1.

The MPE estimates are as follows:

Table 1 in 47 CFR 1.1310 defines the maximum permissible exposure (MPE) for the general population as  $(f_{\text{MHz}}/1500) \text{ mW/cm}^2$ . The exposure level at a 20 cm distance from the EUT's transmitting antenna is calculated using the general equation:

$$S = (PG)/4\pi R^2$$

Where: S = power density ( $\text{mW/cm}^2$ )

P = power input to the antenna (mW)

G = numeric power gain relative to an isotropic radiator

R = distance to the center of the radiation of the antenna (20 cm = limit for MPE estimates)

PG = EIRP

Solving for S, the maximum power density 20 cm from the transmitting antenna is summarized in the following table:

### MPE Estimate

#### FCC ID: UQ5RFWHTIBREC

| Antenna Type            | Antenna Manufacturer          | Antenna Part No. | Transmit Frequency (MHz) | Max Peak Conducted Output Power (mW) | Antenna Gain (dBi) | Minimum Antenna Cable Loss (dB) | Power Density @ 20 cm ( $\text{mW/cm}^2$ ) | General Population Exposure Limit from 1.1310 ( $\text{mW/cm}^2$ ) |
|-------------------------|-------------------------------|------------------|--------------------------|--------------------------------------|--------------------|---------------------------------|--|--|
| Multilayer Ceramic Chip | Walsin Technology Corporation | RFANT763511 0A1T | 2400                     | 7.9                                  | 2                  | 0                               | 0.002                                      | 1  |

The power density does not exceed 1.0  $\text{mW/cm}^2$  at 20 cm; therefore, the exposure condition is compliant with FCC rules.

The applicant's radio, FCC ID: UQ5RFWHTIBREC, is compliant with the requirements of 15.247(i).