

RF Exposure / MPE Calculation

No.	14487239H
Customer	Rockwell Automation, Inc.
Description of EUT	UHF RFID Transceiver 58UHF Long US Band
Model Number of EUT	58UHF-TR-200-LR50US
FCC ID	USM-58UHF-LR

Rockwell Automation, Inc. declares that Model: 58UHF-TR-200-LR50US complies with FCC radiation exposure requirement specified in the FCC Rule 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the “58UHF-TR-200-LR50US” as calculated from (B) Limits for General Population / Uncontrolled Exposure of TABLE 1- LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) of §1.1310 Radiofrequency radiation exposure limits.

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 0.6016mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = \frac{P \times G}{4 \times \pi \times r^2}$$

Where

$P =$ 822.24 mW (Maximum average output power)

Time average was used for the above value in consideration of 6-minutes time-averaging

Burst power average was used for the above value in consideration of worst condition.

$G =$ 4.111 Numerical Antenna gain; equal to 6.14 dBi

$r =$ 90 cm (Separation distance)

Power Density Result $S = 0.03321 \text{ mW/cm}^2$