



February 14, 2023

FCC ID: USM-58UHF-SR

To whom it may concern,

We, UL Japan, Inc, hereby declare that UHF RFID Transceiver 58UHF Short US Band, model: 58UHF-TR-100-SR15US (FCC ID: USM-58UHF-SR) of Rockwell Automation, Inc. is exempt from RF exposure SAR evaluation because the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula according to the Code of Federal Regulation title 47 section 1.1307(b)(3)(i)(B). This method is used at separation distances d (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive) for single RF sources. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d / 20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$$

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

When the minimum separation distance is shorter than 0.5 cm, 0.5 cm is applied.

The SAR evaluation exemption threshold is calculated as below.

P_{th} (mW)	1840.08
f (GHz)	0.902
$ERP_{20 \text{ cm}}$ (mW)	1840.08
d (cm)	35.0

Conducted Power	(dBm)	20.67
	(mW)	116.7
Antenna Gain (dBi)		3.62
EIRP (dBm)		24.29
ERP	(dBm)	22.15
	(mW)	164.1

The Maximum time-averaged power or ERP whichever greater is 164.1 mW.

Thank you for your attention to this matter.

Ryota Yamanaka
Engineer