

## Appendix G: General SAR test reduction and exclusion guidance

### KDB 447498 & RSS-102

#### Section 4.3 General SAR test reduction and exclusion guidance

For Standalone SAR exclusion consideration, when the considering SAR exclusion Threshold requirement in KDB 447498 is satisfied standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.

In the frequency range below 100 MHz and test separation distance  $\leq 50$ mm, the SAR Test Exclusion Threshold will be determined as follows

SAR Exclusion Threshold (SARET)

$$\text{SAR Exclusion Threshold} = ([\text{Step 1} + \text{Step 2}] * \text{Step 3a}) * \text{Step 3b}$$

#### Step 1

$$\text{NT} = [(MP/TSD^A) * \sqrt{f_{\text{GHz}}}]$$

NT	=	Numeric Threshold (3.0 for 1-g SAR and 7.5 for 10-g SAR)
MP	=	Max Power of channel (mW) (inc tune up)
TSD <sup>A</sup>	=	Min Test separation Distance or 50mm (whichever is lower) = 50
f <sub>GHz</sub>	=	Transmit frequency (or 100MHz if lower)

We can transpose this formula to allow us to find the maximum power of a channel allowed and compare this to the measured maximum power.

$$\text{MP} = [(NT * TSD^A) / \sqrt{f_{\text{GHz}}}]$$

For Distances Greater than 50 mm Step 2 applies

#### Step 2

$$(TSD^B - 50\text{mm}) * f_{(\text{MHz})}/150$$

Where:

f <sub>MHz</sub> <sup>B</sup>	=	Transmit frequency
TSD <sup>B</sup>	=	Min Test separation Distance (mm) = 50

#### Step 3

3a) The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f_{(\text{MHz})})]$  for *test separation distances* > 50 mm and < 200 mm

3b) The power threshold determined by the equation in steps 1 and 2 for 50 mm and 100 MHz is multiplied by  $1/2$  for *test separation distances*  $\leq 50$  mm

$$\begin{aligned} \text{SARET} &= (\{ [(NT * TSD^A) / \sqrt{f_{\text{GHz}}}] + (TSD^B - 50) * [100/150] \} * (1 + \text{Log} [100 / F_{\text{MHz}}])) * 1/2 \\ \text{SARET} &= (\{ [(3.0 * 50) / \sqrt{0.1}] + (50 - 50) * [100/150] \} * (1 + \text{Log} [100 / F_{\text{MHz}}])) * 1/2 \\ \text{SARET} &= (474 * (1 + \text{Log} [100 / 13.56])) * 1/2 \\ \text{SARET} &= 442.65 \text{ mW} \end{aligned}$$

The calculated output power is 0.00003mW (eirp) is less than the SAR Exclusion Threshold of 468mW, at 5mm test separation distance, for general population and uncontrolled exposure.

Therefore standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.