



Product Features

The ELITE series RX3K advanced access control reader features an integral keypad and is designed for surface mounting to most plain wall finishes, and also fits onto a US, UK or EU electrical backbox.

This powerfully secure and innovative reader has a beautifully clean aesthetic and features an RGB LED that can be applied to many applications, e.g. colour coded access levels, migration status or mood lighting.

The unit is moulded using tough polycarbonate/ABS plastic and includes a shadow line backplate, a subtle design feature that makes the reader appear to float on the wall.

- UK design and manufacture
- High gloss finish in BLACK or WHITE
- Slim profile
- RGB LED
- Fully encapsulated electronics
- Wide range of output formats
- 5 year limited warranty
- Read range up to 10cm (4 inches)

Interfacing

The reader supports a wide variety of output formats allowing it to be used in most access control and related applications, e.g. time and attendance, cashless vending etc.

The combination of an integral speaker, an RGB LED, three control inputs and a variety of LED/buzzer/external control options provide a flexible platform to give the right user interface configuration for your project.

Quality Design

Third Millennium has nearly 20 years of award-winning experience in the design and manufacture of RFID technology and the delivery of world class, state-of-the-art access control projects with our many global partners.



advanced access control reader

Specification

Mechanical

Dimensions: 120mm x 76mm x 21mm (4.2 x 3.0 x 0.8 inches)

Housing: Moulded polycarbonate/ABS

Mounting: Wall surface



Connection (screw terminal)

- | | |
|-----------------|----------------------------------|
| 1 - +Vdc | Supply voltage (+5Vdc to +16Vdc) |
| 2 - DATA1 / CLK | Wiegand or Clock/Data output |
| 3 - DATA0 / DAT | Wiegand or Clock/Data output |
| 4 - GREEN | Green LED control input |
| 5 - RED | Red LED control input |
| 6 - BUZZER | Buzzer control input |
| 7 - TMPR / CP | Tamper or Card Present output |
| 8 - 0V | Supply voltage ground |
| 9 - TTL TX | TTL transmit line |
| 10 - TTL RX | TTL receive line |

Environmental

Operating Temperature: -20°C to +60°C
Humidity: 0 - 100% RHNC
Ingress Protection: IP65

Electrical

Voltage: +5Vdc to +16Vdc
Current: 350mA typical
Data Voltage: Rest >4Vdc / Active <1Vdc
Data Output: Wiegand, Clock & Data, Custom Outputs
Indication: 1 RGB LED + (RGB illuminated keypad)
Sounder: Integral speaker

technologies available with this reader		Standard Part Numbers
Prox Compatible		RX3K00
MIFARE® Classic		RX3K80
Advant / Prime		RX3K60
MIFARE® DESFire® EV1		RX3K90
MIFARE® DESFire® EV1 +		RX3K90 Plus
available in gloss BLACK or WHITE		

MIFARE, MIFARE Classic and MIFARE DESFire EV1 are trademarks of NXP B.V.