

# Test Report of FCC Part 15 C for FCC Certificate

On Behalf of

## ESI Cases and Accessories

**Product description:** Gooseneck FM Transmitter  
**Model No.:** DU7101  
**FCC ID:** UTO-DU7101

**Prepared for:** **ESI Cases and Accessories**  
240 Madison Ave 11 Floor, New York, NY 10016,USA


**Prepared by:** **Bontek Compliance Testing Laboratory Ltd.**  
1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China  
Tel: 86-755-86337020  
Fax: 86-755-86337028


**Report No.:** BCT10IR-1414E  
**Issue Date:** September 13, 2010  
**Test Date:** September 01~13, 2009

**Test by:**

**Reviewed By:**



  
Kendy Wang

  
Tony Wu

**TABLE OF CONTENTS**

**1 - GENERAL INFORMATION ..... 3**  
1.1 Product Description for Equipment Under Test (EUT) ..... 3  
**APPLICANT: ..... 3**  
1.2 Related Submittal(s) / Grant (s) ..... 3  
1.3 Test Methodology ..... 3  
1.4 Test Facility ..... 4  
**2. SYSTEM TEST CONFIGURATION ..... 5**  
2.1 EUT Configuration ..... 5  
2.2 EUT Exercise ..... 5  
2.3 General Test Procedures ..... 5  
2.4 List of Measuring Equipments Used ..... 6  
**3. SUMMARY OF TEST RESULTS ..... 8**  
**4. TEST OF CONDUCTED EMISSION ..... 9**  
4.1 Applicable Standard ..... 9  
4.2 Test Setup Diagram ..... 9  
**5- RADIATED EMISSIONS ..... 10**  
5.1 Limit of Radiated Emissions (FCC 47 CFR 15.209 Class B): ..... 10  
5.2 EUT Setup ..... 10  
5.3 Test Procedure ..... 10  
5.4 Test Result ..... 11  
**6- OCCUPIED BANDWIDTH ..... 19**  
6.1 Requirement of Occupied Bandwidth ..... 19  
6.2 Test Procedure ..... 19  
6.3 Emissions within Band Edges Test Result ..... 19  
**7. ANTENNA REQUIREMENT ..... 23**  
7.1 Standard Applicable ..... 23  
7.2 Antenna Connected Construction ..... 23

# 1 - GENERAL INFORMATION

## 1.1 Product Description for Equipment Under Test (EUT)

Applicant: **ESI Cases and Accessories**  
Address of Applicant: 240 Madison Ave 11 Floor, New York, NY 10016,USA  
Manufacturer: **ESI Cases and Accessories**  
Address of Manufacturer: 240 Madison Ave 11 Floor, New York, NY 10016,USA  
EUT Description: Gooseneck FM Transmitter  
Trade Name: N.A.  
Model No.: DU7101  
Rated Voltage Input:12VDC  
Frequency Range 88~108MHz  
Channel Separation 20kHz  
Product Class: Low Power Communication Device Transmitter  
EUT Cable: Audio input cable, 0.8m long, unshielded

Remark: *\* The test data gathered are from the production sample provided by the manufacturer.*

## 1.2 Related Submittal(s) / Grant (s)

This submittal(s) is a test report based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4 - 2003.

The following Declaration of Conformity report of EUT is prepared in accordance with FCC Rules and Regulations Part 15 Subpart C Section15.239

The objective of the manufacturer is to demonstrate compliance with the described above standards.

## 1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 - 2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. Radiated testing was performed at an antenna to EUT distance 3 meters.

## 1.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### **FCC – Registration No.: 338263**

BONTEK COMPLIANCE TESTING LABORATORY LTD. , EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 338263, March, 2008.

### **IC Registration No.: 7631A**

The 3m alternate test site of BONTEK COMPLIANCE TESTING LABORATORY LTD. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 7631A on August 2009.

### **CNAS - Registration No.: L3923**

BONTEK COMPLIANCE TESTING LABORATORY LTD. to ISO/IEC 17025:25 General Requirements for the Competence of Testing and Calibration Laboratories(CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.The acceptance letter from the CNAS is maintained in our files: Registration:L3923,February,2009.

### **TUV - Registration No.: UA 50145371-0001**

BONTEK COMPLIANCE TESTING LABORATORY LTD. An assessment of the laboratory was conducted according to the"Procedures and Conditions for EMC Test Laboratories"with reference to EN ISO/IEC 17025 by a TUV Rheinland auditor. Audit Report NO. 17010783-001

## **2. SYSTEM TEST CONFIGURATION**

The tests documented in this report were performed in accordance with ANSI C63.4-2003 and FCC CFR 47 Part 15 Subpart C Section 15.239.

### **2.1 EUT Configuration**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### **2.2 EUT Exercise**

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

### **2.3 General Test Procedures**

**Conducted Emissions:** The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 7.1 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak detector mode.

**Radiated Emissions:** The EUT is placed on a turntable, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4-2003.

## 2.4 List of Measuring Equipments Used

Test equipments list of BONTEK COMPLIANCE TESTING LABORATORY LTD.

No.	Equipment	Manufacturer	Model No.	S/N	Calculator date	Calculator due date
1	EMI Test Receiver	R&S	ESCI	100687	2010-4-14	2011-4-13
2	EMI Test Receiver	R&S	ESPI	100097	2010-4-14	2011-4-13
3	Amplifier	HP	8447D	1937A02492	2010-4-14	2011-4-13
4	Single Power Conductor Module	FCC	FCC-LISN-5-50-1-01-CISPR25	07101	2010-4-14	2011-4-13
5	Single Power Conductor Module	FCC	FCC-LISN-5-50-1-01-CISPR25	07102	2010-4-14	2011-4-13
6	Power Clamp	SCHWARZBECK	MDS-21	3812	2010-4-14	2011-4-13
7	Positioning Controller	C&C	CC-C-1F	MF7802113	N/A	N/A
8	Electrostatic Discharge Simulator	TESEQ	NSG437	125	2010-4-14	2011-4-13
9	Fast Transient Burst Generator	SCHAFFNER	MODULA6150	34572	2010-4-14	2011-4-13
10	Fast Transient Noise Simulator	Noiseken	FNS-105AX	31485	2010-4-14	2011-4-13
11	Color TV Pattern Generator	PHILIPS	PM5418	TM209947	N/A	N/A
12	Power Frequency Magnetic Field Generator	EVERFINE	EMS61000-8K	608002	2010-4-14	2011-4-13
13	N/A	N/A	N/A	N/A	N/A	N/A
14	Capacitive Coupling Clamp	TESEQ	CDN8014	25096	2010-4-14	2011-4-13
15	High Field Biconical Antenna	ELECTRO-METRICS	EM-6913	166	2010-4-14	2011-4-13
16	Log Periodic Antenna	ELECTRO-METRICS	EM-6950	811	2010-4-14	2011-4-13
17	Remote Active Vertical Antenna	ELECTRO-METRICS	EM-6892	304	2010-4-14	2011-4-13
18	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	2010-4-14	2011-4-13
19	Horn Antenna	SCHWARZBECK	BBHA9120A	B08000991-0001	2010-4-14	2011-4-13
20	Teo Line Single Phase	SCHWARZBECK	NSLK8128	D-69250	2010-4-14	2011-4-13

	Module					
21	10dB attenuator	SCHWARZBECK	MTAIMP-136	R65.90.0001#06	2010-4-14	2011-4-13
22	Electric bridge	Zentech	100 LCR METER	803024	N/A	N/A
23	RF Current Probe	FCC	F-33-4	80	2010-4-14	2011-4-13
24	SIGNAL GENERATOR	HP	8647A	3349A02296	2010-4-14	2011-4-13
25	MICROWAVE AMPLIFIER	HP	8349B	2627A00994	2010-4-14	2011-4-13
26	Triple-Loop Antenna	EVERFINE	LLA-2	607004	2010-4-14	2011-4-13
27	CDN	FRANKONIA	M2+M3	A3027019	2009-10-20	2011-10-19
28	6dB Attenuator	FRANKONIA	75-A-FFN-06	1001698	2009-10-20	2010-10-19
29	EMV-Mess-Systeme GMBH	FRANKONIA	FLL-75	1020A1109	2009-10-20	2010-10-19
30	EM Injection Clamp	FCC	F-203I-13mm	091536	2009-10-20	2010-10-19
31	9KHz-2.4GHz Signal generator	MARCONI INSTRUMENTS	2024	112260/042	2009-10-20	2010-10-19

### 3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
15.207	Disturbance Voltage at The Mains Terminals	N/A, without AC power supply
15.239	Radiation Emission	Pass
15.239	Occupied Bandwidth	Pass




## 4. TEST OF CONDUCTED EMISSION

### 4.1 Applicable Standard

Section 15.207: For a Low-power Radio-frequency Device is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency Range (MHz)	Limits ( dBuV)	
	Quasi-Peak	Average
0.150~0.500	66~56	56~46
0.500~5.000	56	46
5.000~30.00	60	50

### 4.2 Test Setup Diagram



- Remark: 1. The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC 15.207 limits.
2. The EUT is excluded from investigation of Disturbance Voltage at The Mains Terminals, for it is powered by DC 12V from car bettary. According to the Section 15.207(d), measurement to demonstrate compliance with the limits of Disturbance Voltage at The Mains Terminals are not required to the devices which only employed bettary power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

## 5- RADIATED EMISSIONS

### 5.1 Limit of Radiated Emissions (FCC 47 CFR 15.209 Class B):

Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dB $\mu$ V/m)
30 ~ 88	3	40
88~216	3	43.5
216 ~ 960	3	46
960 ~ 1000	3	54

Note: (1) The tighter limit shall apply at the edge between two frequency bands.

(2) The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

### 5.2 EUT Setup

#### Radiated Measurement Setup




Figure 1 : Frequencies measured below 1 GHz configuration

### 5.3 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

- 1). Configure the EUT according to ANSI C63.4:2003.
- 2). The EUT was placed on the top of the turntable 0.8 meter above ground.
- 3). The receiving antenna was placed 3 meters far away from the turntable.
- 4). The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 5). For Spurious Emissions test, The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization. For each suspected emission, the antenna tower was scanned (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 6). For Field Strength of Fundamental Emissions test, Positioned the loop antenna with its plane vertical at the specified distance of 3 meters between its center and the EUT. The center of the loop antenna is set with 1m above the grounded plane. Then rotated about its vertical axis for finding out the maximum emission level of the EUT.


#### 5.4 Test Result

Temperature ( °C ) : 22~23	EUT: Gooseneck FM Transmitter
Humidity (%RH) : 50~54	M/N: DU7101
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Normal Operating

**Note: The EUT is playing music which ipod input.**

# Harmonics & Spurious Emission (Low Channel: 88.1MHz)


Antenna Polarization: Vertical



## MEASUREMENT RESULT

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
88.100000	45.50	16.4	43.5	-2.0	QP	100.0	0.00	VERTICAL
239.520000	38.30	18.2	46.0	7.7	QP	100.0	0.00	VERTICAL
264.740000	36.60	18.8	46.0	9.4	QP	100.0	0.00	VERTICAL
617.820000	44.20	25.5	46.0	1.8	QP	100.0	0.00	VERTICAL
794.360000	37.20	27.9	46.0	8.8	QP	100.0	0.00	VERTICAL
949.560000	37.00	29.7	46.0	9.0	QP	100.0	0.00	VERTICAL

# Antenna Polarization: Horizontal




## MEASUREMENT RESULT

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
88.100000	48.70	16.4	43.5	-5.2	QP	100.0	0.00	HORIZONTAL
239.520000	41.70	18.2	46.0	4.3	QP	100.0	0.00	HORIZONTAL
264.740000	40.60	18.8	46.0	5.4	QP	100.0	0.00	HORIZONTAL
441.280000	40.50	21.3	46.0	5.5	QP	100.0	0.00	HORIZONTAL
617.820000	39.70	25.5	46.0	6.3	QP	100.0	0.00	HORIZONTAL
794.360000	39.30	27.9	46.0	6.7	QP	100.0	0.00	HORIZONTAL

# Harmonics & Spurious Emission (Middle Channel: 98MHz)


Antenna Polarization: Vertical



## MEASUREMENT RESULT

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
97.900000	46.30	18.2	43.5	-2.8	QP	100.0	0.00	VERTICAL
239.520000	39.80	18.2	46.0	6.2	QP	100.0	0.00	VERTICAL
293.840000	37.50	20.0	46.0	8.5	QP	100.0	0.00	VERTICAL
489.780000	41.80	22.4	46.0	4.2	QP	100.0	0.00	VERTICAL
588.720000	40.20	25.0	46.0	5.8	QP	100.0	0.00	VERTICAL
685.720000	38.60	26.5	46.0	7.4	QP	100.0	0.00	VERTICAL

# Antenna Polarization: Horizontal




## MEASUREMENT RESULT

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
97.900000	52.70	18.2	43.5	-9.2	QP	100.0	0.00	HORIZONTAL
239.520000	41.40	18.2	46.0	4.6	QP	100.0	0.00	HORIZONTAL
293.840000	42.90	20.0	46.0	3.1	QP	300.0	0.00	HORIZONTAL
431.580000	39.50	21.3	46.0	6.5	QP	100.0	0.00	HORIZONTAL
489.780000	40.60	22.4	46.0	5.4	QP	200.0	0.00	HORIZONTAL
687.660000	38.90	26.5	46.0	7.1	QP	100.0	0.00	HORIZONTAL

# Harmonics & Spurious Emission (High Channel: 107.9MHz)

Antenna Polarization: Vertical




## MEASUREMENT RESULT

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
107.900000	40.40	17.8	43.5	3.1	QP	100.0	0.00	VERTICAL
540.220000	42.50	23.8	46.0	3.5	QP	100.0	0.00	VERTICAL
838.980000	36.60	28.5	46.0	9.4	QP	100.0	0.00	VERTICAL
893.300000	36.60	29.2	46.0	9.4	QP	100.0	0.00	VERTICAL
951.500000	37.10	29.7	46.0	8.9	QP	100.0	0.00	VERTICAL
955.380000	36.00	29.7	46.0	10.0	QP	100.0	0.00	VERTICAL



## Antenna Polarization: Horizontal



### MEASUREMENT RESULT

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
107.900000	56.80	17.8	43.5	-13.3	QP	100.0	0.00	HORIZONTAL
119.240000	35.70	16.1	43.5	7.8	QP	300.0	0.00	HORIZONTAL
239.520000	43.20	18.2	46.0	2.8	QP	100.0	0.00	HORIZONTAL
322.940000	43.00	20.4	46.0	3.0	QP	200.0	0.00	HORIZONTAL
431.580000	42.50	21.3	46.0	3.5	QP	100.0	0.00	HORIZONTAL
540.220000	38.80	23.8	46.0	7.2	QP	100.0	0.00	HORIZONTAL

## Fundamental Emission Test Data

### Antenna polarization: Horizontal

Frequency (MHz)	Read Level (dBuV)	Correction Factor (dBuV/m)	FS (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Mode
Low Channel: 88.1MHz						
88.1	37.4	16.4	53.8	68.0	-14.2	PEAK
88.1	13.7	16.4	30.1	48.0	-17.9	AVERAGE
Middle Channel: 98.0MHz						
98.0	29.0	18.2	47.2	68.0	-20.8	PEAK
98.0	11.0	18.2	29.2	48.0	-18.8	AVERAGE
High Channel: 107.9MHz						
107.9	39.3	17.8	57.1	68.0	-10.9	PEAK
107.9	6.3	17.8	24.1	48.0	-23.9	AVERAGE

### Antenna polarization: Vertical

Frequency (MHz)	Read Level (dBuV)	Correction Factor (dBuV/m)	FS (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Mode
Low Channel: 88.1MHz						
88.1	28.3	16.4	44.7	68.0	-23.3	PEAK
88.1	7.9	16.4	24.3	48.0	-23.7	AVERAGE
Middle Channel: 98.0MHz						
98.0	28.1	18.2	46.3	68.0	-21.7	PEAK
98.0	8.5	18.2	26.7	48.0	-21.3	AVERAGE
High Channel: 107.9MHz						
107.9	22.7	17.8	40.5	68.0	-27.5	PEAK
107.9	3.6	17.8	21.4	48.0	-26.6	AVERAGE

## 6- OCCUPIED BANDWIDTH

### 6.1 Requirement of Occupied Bandwidth

Emission from the intentional radiator shall be confined within a band 200kHz wide centered on the operation frequency. The 200kHz band shall lie wholly within the frequency range of 88~108MHz.

### 6.2 Test Procedure


- 1). The EUT was placed on the top of the turntable 0.8 meter above ground.
- 2). The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 3). Power on the EUT and all the supporting units.
- 4). The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 5). For each suspected emission, the antenna tower was scanned (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading of both horizontal and vertical polarization.
- 6). Set EMI test receiver with Max hold. Mark peak, -20dB.

### 6.3 Emissions within Band Edges Test Result


Temperature ( °C ) : 22~23	EUT: Gooseneck FM Transmitter
Humidity (%RH) : 50~54	M/N: DU7101
Barometric Pressure ( mbar ) : 950~1000	Operation Condition: Normal Operating

**Note: The EUT is playing music which ipod input.**


# Low Channel: 88.1MHz



# Middle Channel: 98MHz



# High Channel: 107.9MHz



## **7. ANTENNA REQUIREMENT**

### **7.1 Standard Applicable**

Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **7.2 Antenna Connected Construction**

The antenna connector is designed with permanent attachment and no consideration of replacement.