



TEST REPORT

Report No. : AK044952-001 Date : 2008-12-02

Application No. : LK233380(8)

Client : Janam Technologies LLC
100 Crossways Park West,
Suite 105, Woodbury, NY 11797

Sample Description : One(1) submitted sample(s) stated to be Janam Barcode Scanning Mobile Computer of Model No. XP30W-LP, XP30W-LN, XM60W-LP, XM60W-LN, XM65W-LP and XM65W-LN

Rating : 1 x 3.7 V rechargeable battery
AC 100V ~ 240V to DC 5V adaptor

No. of submitted sample : One (1) piece(s) ***

Date Received : 2008-10-03.

Test Period : 2008-10-29 to 2008-11-15.

Test Requested : FCC Part 15 Class II Permissive Change.

Test Method : 47 CFR Part 15 (10-1-07 Edition)
ANSI C63.4 – 2003


Test Result : See attached sheet(s) from page 2 to 13.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15 Subpart B.

Remarks : All six models are the same in circuitry and components; and therefore model XM60W-LN was chosen to be the representative of the test sample.

The scanner module was changed from a LED module to a LASER module.
The above models are based on the previous original certified models XP30W-1P, XP30W-1N, XM60W-1P, XM60W-1N, XM65W-1P and XM65W-1N.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : 
Mr WONG Lap-Pong, Andrew
Assistant Manager
Electrical Division

FCC ID: UTWM60M65W

Page 1 of 13



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

Table of Contents

1	General Information.....	3
1.1	General Description.....	3
1.2	Location of the test site.....	4
1.3	List of measuring equipment.....	5
1.4	List of supporting equipment.....	6
2	Description of the radiated emission test.....	7
2.1	Test Procedure.....	7
2.2	Test Result.....	7
2.3	Radiated Emission Measurement Data.....	8
2.3	Radiated Emission Measurement Data (Con't).....	9
3	Description of the Line-conducted Test.....	10
3.1	Test Procedure.....	10
3.2	Test Result.....	10
3.3	Graph and Table of Conducted Emission Measurement Data.....	10
4	Photograph.....	11
4.1	Photographs of the Test Setup for Radiated Emission and Conducted Emission.....	11
4.2	Photographs of the External and Internal Configurations of the EUT.....	11
5	Supplementary document.....	12
5.1	Bandwidth.....	12
5.2	Duty cycle.....	12
5.3	Transmission time.....	12
6	Appendices.....	13



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

1 General Information

1.1 General Description

The equipment under test (EUT) is a PDA for Janam barcode scanning mobile computer. The EUT is powered by 1 x 3.7V rechargeable battery. The operation system is WinCE and built-in 34888 KB RAM, Barcode Scanner, Bluetooth and Wi-Fi features. The operation system in between six models as below:

- Model XP30W-1P and XP30W-1N is Palm platform.
- Model XM60W-1P and XM60W-1N is WinCE platform.
- Model XM65W-1P and XM65W-1N is Window Mobile platform.

The brief circuit description is saved with filename: OpDes.pdf



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date
EMI Test Receiver	R&S	ESCI	100152	2009 January 14
EMI Test Receiver	R&S	ESCS30	100001	2008 November 20
Broadband Antenna	Schaffner	CBL6112B	2692	2009 January 21
LISN	R&S	ESH3-Z5	100038	2009 March 01



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

1.4 List of supporting equipment

- Computer:
1. Intel CPU P4 2.8GHz / 512k cache / 533MHz bus
Model: 9426A657
 2. Intel Mother Board
Model: Intel Type: D845EPI/D845GVSR
 3. Seagate Hard-Disk
Model: ST380011A, 80GB
 4. Proview LCD Monitor
Model: 568
 5. Logitech Mouse
Model: M-S34
 6. Hewlett Packard Keyboard
Model: SK-2502C
 7. Hewlett Packard LaserJet 2100TN
Model: C4172A
 8. PenPower Handwriting System
Model: PP403N
 9. RS-232 DB9 Serial Cable with DC Adapter Connector
(Provided by Applicant)



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal to determine which attitude and configuration produce the highest emission during measurement for radiated emission measurement.

2.2 Test Result

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

The emissions from 30MHz to 1000MHz were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next pages.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Mode: PC Connected with Data Transferring and Barcode Scanning

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
332.472	H	19.3	14.7	34.0	46.0	-12.0
465.456	V	22.5	18.6	41.1	46.0	-4.9
531.958	V	18.3	20.2	38.5	46.0	-7.5
565.204	V	17.1	20.2	37.3	46.0	-8.7
581.832	H	21.4	20.2	41.6	46.0	-4.4
598.440	H	23.0	20.2	43.2	46.0	-2.8
615.084	H	20.5	21.6	42.1	46.0	-3.9
631.700	H	21.2	21.6	42.8	46.0	-3.2
671.944	H	20.4	21.6	42.0	46.0	-4.0
767.944	V	13.2	22.1	35.3	46.0	-10.7



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

2.3 Radiated Emission Measurement Data (Con't)

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Mode: Stand Alone with Barcode Scanning

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
144.070	V	20.1	12.6	32.7	43.5	-10.8
166.239	V	19.7	11.0	30.7	43.5	-12.8
332.476	H	18.8	14.7	33.5	46.0	-12.5
498.715	V	14.7	18.6	33.3	46.0	-12.7
531.964	V	20.3	20.2	40.5	46.0	-5.5
565.207	V	16.3	20.2	36.5	46.0	-9.5
581.834	V	18.2	20.2	38.4	46.0	-7.6
671.952	V	19.2	21.6	40.8	46.0	-5.2
714.812	H	13.1	22.1	35.2	46.0	-10.8
767.950	V	14.5	22.1	36.6	46.0	-9.4



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

The PC connected mode and Stand Alone mode were tested. The EUT was tested under a data transferring situation in PC connected mode.

It was found that the EUT met the FCC requirement.

3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filing, the documents are saved with filename TestRpt2.pdf.



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission

For electronic filing, the photos are saved with filename TSup1.jpg to Tsup10.jpg.

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho6.jpg.



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

Not Applicable

5.2 Duty cycle

Not Applicable

5.3 Transmission time

Not Applicable



TEST REPORT

Report No. : AK044952-001

Date : 2008-12-02

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	2	pages
A2.	Photos of the set-up of Conducted Emissions	4	pages
A3.	Photos of External Configurations	1	page
A4.	Photos of Internal Configurations	3	pages
A5.	ID Label/Location	1	page
A6.	Conducted Emission Measurement Data	4	pages
A7.	Block Diagram	1	page
A8.	Schematics Diagram	11	pages
A9.	User Manual	12	pages
A10.	Operation Description	2	pages

***** End of Report *****