



TEST REPORT

Report No. : AJ006714-001 Date : 2007 April 03

Application No. : LG203504(3)

Client : Janam Technologies LLC
40 Goose Hill Road, Cold Spring Harbor,
New York 11724, United States

Sample Description : One(1) submitted sample(s) stated to be Janam XP30N
of Model No. XP30N-1P, XP30N-1N, XM60N-1P and XM60N-1N
Rating : 1 x 3.7 V rechargeable battery
: AC 100V ~ 240V to DC 5V adaptor
No. of submitted sample : Two (2) piece(s) ***

Date Received : 2006 February 26

Test Period : 2006 February 26 – 2007 March 30

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 15.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart C and Subpart B.

Remark : All four models are the same in circuitry and components; and therefore model
XP30N-1P has been chosen to be the representative of the test sample.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____

Danny Chui
Deputy Manager - EL. Division

FCC ID: UTWP30M60N

Page 1 of 15



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

Table of Contents

1	General Information	3
1.1	General Description.....	3
1.2	Location of the test site	4
1.3	List of measuring equipment.....	5
2	Description of the radiated emission test.....	6
2.1	Test Procedure.....	6
2.2	Test Result.....	6
2.3	Radiated Emission Measurement Data.....	7
2.4	Conducted Emission Measurement Data.....	9
3	Description of the Line-conducted Test.....	11
3.1	Test Procedure.....	11
3.2	Test Result.....	11
3.3	Graph and Table of Conducted Emission Measurement Data.....	11
4	Photograph	12
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	12
4.2	Photographs of the External and Internal Configurations of the EUT	12
5	Supplementary document.....	13
5.1	Bandwidth	13
5.2	Duty Cycle.....	13
5.3	Transmission Time.....	13
5.4	Power Spectral Density.....	13
5.5	Average on time.....	14
6	Appendices.....	15



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

1 General Information

1.1 General Description

The equipment under test (EUT) is a PDA for Janam XP30N. The EUT is powered by 1 x 3.7V rechargeable battery. There is built-in 320MB memory, Barcode Scanner and Bluetooth features.

The brief circuit description is saved with filename: OpDes.pdf



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.
EMI Test Receiver	R&S	ESCI	100152
Spectrum Analyzer	R&S	FSP30	100628
Broadband Antenna	Schaffner	CBL6112B	2692
Horn Antenna	EMCO	3116	2616
Horn Antenna	Schwarzbeck	9120D	9120D-531
Pre-Amplifier	Schwarzbeck	9718	9718-119
EMI Test Receiver	R&S	ESCS30	100001
LISN	R&S	ESH3-Z5	100038
LISN	R&S	ESH3-Z5	100010



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

The antenna output terminal was connected to spectrum directly for conducted output power measurement.

2.2 Test Result

All other measurements data were below the limits. Thus, those highest emission data were presented in table 2.3 and 2.4.

Peak Detector data was measured unless otherwise stated.

“#” means emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

2.3 Radiated Emission Measurement Data

Radiated Emission
pursuant to
the requirement of FCC part 15 subpart B

Operation Mode: Barcode Scanning with PC connection

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
44.750	V	15.1	13.0	28.1	40.0	-11.9
398.969	V	17.3	14.9	32.2	46.0	-13.8
465.465	H	19.3	17.9	37.2	46.0	-8.8
664.947	H	19.4	21.2	40.6	46.0	-5.4
664.959	V	17.0	21.2	38.2	46.0	-7.8



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

Radiated Emission
pursuant to
the requirement of FCC part 15 subpart C

Operation Mode: Bluetooth CH00

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (with 35dB Pre-amplify)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
2401.980	V	84.4	0.2	84.6	N/A	N/A
# 4803.940	V	29.8	7.1	36.9	54.0	-17.1

Operation Mode: Bluetooth CH39

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (with 35dB Pre-amplify)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
2440.960	H	83.8	0.2	84.0	N/A	N/A
#4881.940	V	29.1	7.1	36.2	54.0	-17.8
#7322.910	H	17.7	12.1	29.8	54.0	-24.2

Operation Mode: Bluetooth CH78

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (with 35dB Pre-amplify)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
2479.960	H	84.2	0.2	84.4	N/A	N/A
#4959.980	H	30.8	7.1	37.9	54.0	-16.1
#7439.880	H	18.0	12.1	30.1	54.0	-23.9

FCC ID: UTWP30M60N

Page 8 of 15



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

2.4 Conducted Emission Measurement Data

Conducted Emission
pursuant to
the requirement of FCC part 15 subpart C

Operation Mode: Bluetooth CH00

Transmission Power

Frequency (MHz)	Reading (dB μ V)	Reading (μ W)	Limit (W)	Margin (W)
2401.000	97.1	102.936	1.0	-0.999

Spurious Emission

Frequency (MHz)	Measured Field Strength (dB μ V)	Limit (20dB μ V below Carrier)	Margin (dB)
4803.920	36.0	77.1	-41.1
7205.400	44.5	77.1	-32.6
9607.860	28.6	77.1	-48.5



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

Operation Mode: Bluetooth CH39

Transmission Power

Frequency (MHz)	Reading (dB μ V)	Reading (μ W)	Limit (W)	Margin (W)
2440.956	98.4	139.996	1.0	-0.999

Spurious Emission

Frequency (MHz)	Measured Field Strength (dB μ V)	Limit (20dB μ V below Carrier)	Margin (dB)
4881.932	37.8	78.4	-40.6
7322.396	40.3	78.4	-38.1
9763.852	29.8	78.4	-48.6

Operation Mode: Bluetooth CH78

Transmission Power

Frequency (MHz)	Reading (dB μ V)	Reading (μ W)	Limit (W)	Margin (W)
2479.962	100.0	194.674	1.0	-0.999

Spurious Emission

Frequency (MHz)	Measured Field Strength (dB μ V)	Limit (20dB μ V below Carrier)	Margin (dB)
4959.916	34.6	80.0	-45.4
7439.384	36.7	80.0	-43.3



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

The battery charging mode has been tested. The EUT was connected to the adaptor producing the Maximum emission. The measurement data was indicated in Appendix.

It was found that the EUT met the FCC requirement.

3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filing, the documents are saved with filename TestRpt2.pdf.



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to Tsup5.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho4.jpg.



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot saved in TestRpt3.pdf shows the channel spacing has minimum 25KHz.

The plot saved in TestRpt4.pdf shows the frequency hopping channel over 75 hopping frequency.

The plot saved in TestRpt6.pdf shows the band edge is fulfil 15.205 restricted band, and 15.247 (d) requirement.

5.2 Duty Cycle

N/A

5.3 Transmission Time

N/A

5.4 Power Spectral Density

N/A



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

5.5 Average on time

The plot saved in TestRpt5.pdf shows the average on time for frequency hopping channel is with in 0.4 seconds.

The calculation for average on time as below:

Average hopping channel = Transmitted Carrier / Sweep time

Average on time = Packet on time x Average hopping channel

Dwell time = Average on time x number of hopping channel x 0.4

Test result:

Frequency Channel (MHz)	Packet	Dwell Time (Second)	Limit (Second)	Margin
2402	DH1	0.133	0.4	-0.267
2402	DH3	0.265	0.4	-0.135
2402	DH5	0.369	0.4	-0.031
2441	DH1	0.133	0.4	-0.267
2441	DH3	0.265	0.4	-0.135
2441	DH5	0.369	0.4	-0.031
2480	DH1	0.133	0.4	-0.267
2480	DH3	0.265	0.4	-0.135
2480	DH5	0.369	0.4	-0.031



TEST REPORT

Report No. : AJ006714-001

Date : 2007 April 03

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of the set-up of Conducted Emissions	2	pages
A3.	Photos of External Configurations	1	page
A4.	Photos of Internal Configurations	2	pages
A5.	ID Label/Location	1	page
A6.	Channel Spacing	1	page
A7.	Hopping channel	1	page
A8.	Average on time	6	pages
A9.	Restricted band	1	pages
A10.	Block Diagram	1	page
A11.	Conducted Emission Measurement Data	2	pages
A12.	Schematics Diagram	11	pages
A13.	User Manual	12	pages
A14.	Operation Description	2	pages

***** End of Report *****