

Friendcom[®]

GW200

Home LoRaWAN Gateway GW200

Specifications

V0.4



Document information

Info	Content
Keywords	<i>RisingHF, LoRaWAN, IOT, Gateway, specifications</i>
Abstract	This document describes the specifications of the Home GW 200.

1. Preface

This document describes the technical specifications and features of the home gateway GW200.

GW200 is an 8 channels Smart Home Gateway device designed by Friendcom, which is compatible with LoRaWAN protocol and WiFi IEEE 802.11b/g/n. It can also be used as a WiFi router.

2. RHF2S024 LoRaWAN Gateway description

GW200 is an IOT gateway based on LoRaWAN and target to LPWAN network. The GW could support LoRaWAN Class A/C protocol and WiFi IEEE 802.11.b/g/n standard. The 2.4G wireless transmission rate up to 150Mbps. Users could connect the GW to Cloud server via WiFi.

This device integrate an high performance CPU MT7688, one pcs of base-band processor SX1301, that it could support 8 multi-SF channel (SF12 to SF7), 1 single-SF channel and 1 GFSK channel. Output power could achieve to 13dBm max. Sensitivity is as low as -142dBm@300bps. With specified payload length and transmit period, one GW could support 10k nodes.

GW200 is a smart, easy installation and high reliability device. Customers could setup a quick LoRaWAN network for their LPWAN application with GW200.

2.1. Functional Block

GW200 functional block is shown below.




Figure 2-1 GW200 functional block

2.2. Product features and application

Features:

- ✓ LoRaWAN half-duplex operation mode;
- ✓ Include 8 multi-SF LoRa channel, 1 single-SF LoRa channel, and 1 GFSK channel;
- ✓ Output power achieve to 3dBm max, receiver sensitivity as low as -142dBm@300bps;
- ✓ Support LoRaWAN ClassA/C mode;
- ✓ Support 802.11 b/g/n;
- ✓ Support 10base-T and 100base-TX;
- ✓ Support 100m Ethernet cable;

- ✓ Industry 4.0, Industrial monitor
- ✓ Wireless remote control and monitor
- ✓ Smart Home, Smart building, Smart community and Smart city;
- ✓ Wireless alarm and security
- ✓ environment monitor

Application:

- ✓ M2M, IOT and LPWAN
- ✓ Wireless sensor network
- ✓ AMR

2.3. Specifications

Table 2-1 GW200 Specifications

Item Group	Item	Description
System Configuration	Core	MIPS24KEc
	Basic Frequency	580MHZ
	RAM	1G-bit
	Flash	256M-bit
Communication	10M/100Mbps Interface	Access internet via cable
	2.412-2.462G WIFI	Wireless access
	LoRa 915MHz	

Wireless coverage	WIFI	60M(Open Space)
	LoRa	3km(city environment)
Electrical Specification	Power supply input	DC 12V
	Average Power Consumption	<5W
	2.4G WIFI Output Power	11n HT20: 15 ± 2 dBm 11n HT40: 16 ± 2 dBm 11g: 15 ± 2 dBm 11b: 13 ± 2 dBm
	2.4G WIFI Sensitivity	11n HT20 MCS7 150Mbps: -68 dBm@10%PER 11g 54Mbps: -68 dBm@10%PER 11b 11Mbps: -85 dBm@8%PER
	LoRa Output Power	2 ± 1 dBm
	LoRa Sensitivity	-142 dBm@SF12, BW=125kHz
LED	POWER LED	Power access indication
	SYSTEM LED	System status indication
	WIFI LED	WIFI link status indication
	LoRa LED	LoRa link status indication
	USB LED	USB link status indication

	RJ45 LED	RJ45 link status indication
External Interface	RJ45	WAN/LAN Automatic switching between different modes
	USB2.0	Local firmware upgrade and data download
	WIFI antenna	5dBi External antenna
	LoRa antenna	0dBi External antenna
	Power interface	12V/1.5A Power supply input
Dimensions Installation	Dimensions	166*105*28.4mm
	Weight	223.2g
	Installation	On the desktop or Fixed on the wall
Operating Range	Operational temperature range	-20 to +50°C
	Storage temperature range	-40 to +85°C

3. Global electrical specifications and reliability

3.1. Electrical specifications

3.1.1. Power Supply

GW200 is equipped with 12V / 1.5 A 5 energy efficiency power adapter, input voltage range of 100 ~ 240Vac; 50/60Hz, output voltage range 11.4 ~ 12.6 V.

3.1.2. Consumption

Table 3-1 RHF2S024 Total Consumption

Item	Value typ/W
Standby	2.4W
Average	4.1W
MAX	5W

3.1.3. Rf Specifications (LoRaWAN)

Conducted Receiver sensitivity and Transmitter output power would be used to evaluate the performance here.

1) Sensitivity

Test condition: 32byte payload, PER=10%, +25°C.

Table 3-2 Conducted Receiver sensitivity

Part Number	Bandwidth/kHz	Spreading Factor	Sensitivity/dBm
GW200	125	12	-140
		7	-125
	250	12	-136
		7	-122

2) Output power

Test condition: CW signal, +25°C.

Table 3-3 Output power

Part Number	Parameter	Min	Typ	Max	Unit
GW200	Frequency Range (Tx)	902.5		927.5	MHz
	Frequency Range (Rx)	902.5		927.5	MHz
	Max Output power		2		dBm

3.1.4. Antenna performance

The gateway is equipped with an high efficient omnidirectional antenna.

Resistance 50 Ω

VSWR<3.0@470-510MHZ

VSWR<2.0@868-915MHZ

VSWR<1.8@2.4-2.5GHZ

Gain 0dBi@470-510MHZ

0dBi@868-915MHZ

5dBi@2.4-2.5GHZ

Efficiency 470-510MHZ:>35%

868-915MHZ>60%

2.4-2.5GHZ:>60%

3.2. Reliability

Environment test

Table 3-7 Environment test requirement

Item	Test condition	standard	results
Low temperature operation	Temperature: -20°C Operation mode: working with service connected Test duration: 12 h	JESD22-A1 GB/T 2423	Appearance ok; LoRaWAN RF Performance ok; Function ok;
High temperature operation	Temperature: +50°C Operation mode: working with service connected Test duration: 12 h	JESD22-A1 GB/T 2423	Appearance ok; LoRaWAN RF Performance ok; Function ok;
Low temperature Storage	Temperature: -40°C Operation mode: no power, no package Test duration: 24 h	JESD22-A1 GB/T 2423	Appearance ok; LoRaWAN RF Performance ok; Function ok;
High temperature Storage	Temperature: +85°C Operation mode: no power, no package Test duration: 24 h	JESD22-A1 GB/T 2423	Appearance ok; LoRaWAN RF Performance ok; Function ok;

4. Mechanical size and package information

4.1. Mechanical size




Figure 4-1 GW200 Mechanical size

4.2. package information

4.2.1. Package list

Table 4-1 package list

Material	PN	Qty
GW200	GW200-xxx	1
Adapter	12/1.5A	1

4.2.2. Package information



Figure 4-2 GW200 package



Figure 4-3 package inside

4.3. Order information

GW200 include several part number, different part number would be used in different band and area, please contact with sales@risinghf.com for detailed information.

Table 4-2 order information

PN	descriptions
GW200	902.5-927.5MHz

FCC Warning

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the

interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.

Modifications

V0.4 2017-08-25

- + Add Package information

V0.3 2017-08-07

- + Add EU868/IN865/US915/AU915/AS923 Specification parameters and ordering information

- + Update with some error modifications

V0.2 2017-08-04

- + Add Power consumption parameters

V0.1 2017-06-20

- + Create draft.

Please Read Carefully:

Information in this document is provided solely in connection with RisingHF products. RisingHF reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All RisingHF products are sold pursuant to RisingHF's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the RisingHF products and services described herein, and RisingHF assumes no liability whatsoever relating to the choice, selection or use of the RisingHF products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by RisingHF for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN RISINGHF'S TERMS AND CONDITIONS OF SALE RisingHF DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF RisingHF PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

RISINGHF PRODUCTS ARE NOT DESIGNED OR AUTHORIZED FOR USE IN: (A) SAFETY CRITICAL APPLICATIONS SUCH AS LIFE SUPPORTING, ACTIVE IMPLANTED DEVICES OR SYSTEMS WITH PRODUCT FUNCTIONAL SAFETY REQUIREMENTS; (B) AERONAUTIC APPLICATIONS; (C) AUTOMOTIVE APPLICATIONS OR ENVIRONMENTS, AND/OR (D) AEROSPACE APPLICATIONS OR ENVIRONMENTS. WHERE RISINGHF PRODUCTS ARE NOT DESIGNED FOR SUCH USE, THE PURCHASER SHALL USE PRODUCTS AT PURCHASER'S SOLE RISK, EVEN IF RISINGHF HAS BEEN INFORMED IN WRITING OF SUCH USAGE, UNLESS A PRODUCT IS EXPRESSLY DESIGNATED BY RISINGHF AS BEING INTENDED FOR "AUTOMOTIVE, AUTOMOTIVE SAFETY OR MEDICAL" INDUSTRY DOMAINS ACCORDING TO RISINGHF PRODUCT DESIGN SPECIFICATIONS. PRODUCTS FORMALLY ESCC, QML OR JAN QUALIFIED ARE DEEMED SUITABLE FOR USE IN AEROSPACE BY THE CORRESPONDING GOVERNMENTAL AGENCY.

Resale of RisingHF products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by RisingHF for the RisingHF product or service described herein and shall not create or extend in any manner whatsoever, any liability of RisingHF.

RisingHF and the RisingHF logo are trademarks or registered trademarks of RisingHF in various countries.

Information in this document supersedes and replaces all information previously supplied.

The RisingHF logo is a registered trademark of RisingHF. All other names are the property of their respective owners.

© 2015 RISINGHF - All rights reserved

<http://www.risinghf.com>