



NVLAP LAB CODE 200707-0



FCC PART 15.247

MEASUREMENT AND TEST REPORT

For

Xinwei Electronic Co., Ltd., Quanzhou

Wan An Tang Xi Industrial Area. Luo Jiang Quanzhou, Fujian, China

FCC ID: UUPHSE26

This Report Concerns: <input checked="" type="checkbox"/> Original Report		Equipment Type: Bluetooth Headset
Test Engineer:	King Tang 	
Report No.:	RSZ08030403	
Test Date:	2008-04-02 to 2008-04-07	
Report Date:	2008-04-09	
Reviewed By:	EMC Manager: Green Xu 	
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen) This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES	6
EQUIPMENT MODIFICATIONS	6
EXTERNAL I/O CABLE.....	6
CONFIGURATION OF TEST SETUP	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
§15.247 (i) and §2.1093 - RF EXPOSURE.....	9
STANDARD APPLICABLE	9
RESULT:	9
CFR47 §15.203 - ANTENNA REQUIREMENT.....	10
STANDARD APPLICABLE	10
ANTENNA CONNECTOR CONSTRUCTION	10
§15.207 (a) - CONDUCTED EMISSIONS.....	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP.....	11
EMI TEST RECEIVER SETUP.....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST PROCEDURE	12
TEST RESULTS SUMMARY	12
TEST DATA	13
PLOT(S) OF TEST DATA	13
CFR47 §15.205, §15.209, §15.247 - RADIATED EMISSIONS.....	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY	16
EUT SETUP.....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	18
TEST DATA	18
CFR47 §15.247(a) (1)-CHANNEL SEPARATION TEST	22
APPLICABLE STANDARD	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST PROCEDURE	22
TEST DATA	22

CFR47 §15.247(a) (1) – 20dB BANDWIDTH TESTING	27
APPLICABLE STANDARD	27
TEST EQUIPMENT LIST AND DETAILS	27
TEST PROCEDURE	27
TEST DATA	27
CFR47 §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	31
APPLICABLE STANDARD	31
TEST EQUIPMENT LIST AND DETAILS	31
TEST PROCEDURE	31
TEST DATA	31
CFR47 §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	33
APPLICABLE STANDARD	33
TEST EQUIPMENT LIST AND DETAILS	33
TEST PROCEDURE	33
TEST DATA	33
CFR47 §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	37
APPLICABLE STANDARD	37
TEST EQUIPMENT LIST AND DETAILS	37
TEST PROCEDURE	37
TEST DATA	37
CFR47 §15.247(d) - BAND EDGES TESTING	41
APPLICABLE STANDARD	41
TEST EQUIPMENT LIST AND DETAILS	41
TEST PROCEDURE	41
TEST DATA	42

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Xinwei Electronic Co., Ltd., Quanzhou's* product, model number: *E26* or the "EUT" as referred to in this report is a *Bluetooth Headset*, which measures approximately: 14.5 cm L x 10.0 cm W x 5.4 cm H, rated input voltage: DC 5V adapter and DC 3.7 V battery.

Adapter Information:

Model: GFP051T-0510;

Input: AC 100-240V 50/60Hz 0.2A;

Output: DC 5V 1A.

** All measurement and test data in this report was gathered from production sample serial number: 0803006 (Assigned by BACL, Shenzhen). The EUT was received on 2008-03-04.*

Objective

This Type approval report is prepared on behalf of *Xinwei Electronic Co., Ltd., Quanzhou* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 04, 2004. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



NVLAP LAB CODE 200707-0

The current scope of accreditations can be found at
<http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

N/A

Special Accessories

N/A


Equipment Modifications

No modification was made to the unit tested.


External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Detachable USB Cable	1.14	EUT	Adapter

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
CFR47 §15.247 (i), §2.1093	RF Exposure	Compliant
CFR47 §15.203	Antenna Requirement	Compliant
CFR47 §15.207 (a)	Conducted Emissions	Compliant
CFR47 §15.205, §15.209, §15.247(d)	Radiated Emissions	Compliant
CFR47 §15.247 (a)(1)	20 dB Bandwidth	Compliant
CFR47 §15.247(a)(1)	Channel Separation Test	Compliant
CFR47 §15.247(a)(1)(iii)	Time of occupancy (Dwell Time)	Compliant
CFR47 §15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
CFR47 §15.247(b)(1)	Peak Output Power Measurement	Compliant
CFR47 §15.247(d)	Band edges	Compliant

§15.247 (i) and §2.1093 - RF EXPOSURE

Standard Applicable

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

According to FCC Exclusion list, In the following table, fGHz is mid-band frequency in GHz, and d is the distance to a person's body, excluding hands, wrists, feet, and ankles.

Exposure category	<u>low threshold</u>	<u>high threshold</u>
general population	$(60/f_{\text{GHz}})$ mW, $d < 2.5$ cm $(120/f_{\text{GHz}})$ mW, $d \geq 2.5$ cm	$(900/f_{\text{GHz}})$ mW, $d < 20$ cm
occupational	$(375/f_{\text{GHz}})$ mW, $d < 2.5$ cm $(900/f_{\text{GHz}})$ mW, $d \geq 2.5$ cm	$(2250/f_{\text{GHz}})$ mW, $d < 20$ cm

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Result:

This is a portable device and the Max peak output power is $0.4875 \text{ mW} < 24.59 = (60/2.44\text{GHz}) \text{ mW}$

The SAR measurement is exempt.

CFR47 §15.203 - ANTENNA REQUIREMENT

Standard Applicable

According to CFR47 § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a printed antenna on PCB. The maximum gain is 2dBi; please refer to the internal photos.

Result: Compliance.


§15.207 (a) - CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 2.4 dB.

EUT Setup



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<i>Frequency Range</i>	<i>IF B/W</i>
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Com-Power	L.I.S.N.	LI-200	12005	N/A	N/A
Com-Power	L.I.S.N.	LI-200	12208	N/A	N/A
Rohde & Schwarz	EMI Test Receiver	ESCS30	DE25330	2008-03-26	2009-03-26
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2008-03-26	2009-03-26

* Com-Power's LISN were used as the supporting equipment.

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

11.00 dB at 0.3400 MHz in the Hot conductor mode

Test Data**Environmental Conditions**

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by King Tang on 2008-04-07

Test Mode: Charging

Line Conducted Emissions				FCC Part 15.207	
Frequency (MHz)	Amplitude (dBμV)	Detector (QP/AV)	Conductor (Hot/Neutral)	Limit (dBμV)	Margin (dB)
0.3400	48.20	QP	Hot	59.20	11.00
0.3400	45.40	QP	Neutral	59.20	13.80
0.2300	47.50	QP	Hot	62.45	14.95
0.3400	34.20	AV	Neutral	49.20	15.00
0.2100	48.00	QP	Hot	63.21	15.21
0.1700	49.20	QP	Neutral	64.96	15.76
0.2500	46.00	QP	Hot	61.76	15.76
0.2300	46.40	QP	Neutral	62.45	16.05
0.6900	39.30	QP	Neutral	56.00	16.70
0.2700	43.90	QP	Hot	61.12	17.22
0.1700	47.40	QP	Hot	64.96	17.56
0.4300	29.60	AV	Neutral	47.25	17.65
0.1900	45.80	QP	Neutral	64.04	18.24
0.4300	39.00	QP	Neutral	57.25	18.25
0.6900	27.00	AV	Neutral	46.00	19.00
0.3400	29.10	AV	Hot	49.20	20.10
0.2300	30.10	AV	Neutral	52.45	22.35
0.1700	31.60	AV	Neutral	54.96	23.36
0.2700	26.40	AV	Hot	51.12	24.72
0.2500	26.80	AV	Hot	51.76	24.96
0.2100	28.20	AV	Hot	53.21	25.01
0.2300	27.30	AV	Hot	52.45	25.15
0.1900	28.00	AV	Neutral	54.04	26.04
0.1700	25.90	AV	Hot	54.96	29.06


Plot(s) of Test Data

Plot(s) of Test Data is presented hereinafter as reference.

Conduction emission test
FCC Part 15

07. Apr 08 20:43


EUT: BLUETOOTH HEADSET M/N: E26
Manuf: XINWEI
Op Cond: CHARGING
Operator: King
Test Spec: AC 120V/60HZ Hot
Comment: Temp: 25 Humi: 56%



Conduction emission test
FCC Part 15

07. Apr 08 21:01

EUT: BLUETOOTH HEADSET M/N: E26
Manuf: XINWEI
Op Cond: CHARGING
Operator: King
Test Spec: AC 120V/60HZ Neutral
Comment: Temp: 25 Humi: 56%



CFR47 §15.205, §15.209, §15.247 - RADIATED EMISSIONS

Applicable Standard


CFR47 §15.205; §15.209; §15.247 (d).

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB.

EUT Setup



The radiated emission tests were performed in the 3 meters chamber B test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.109, FCC 15.209 and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>
30MHz – 1000 MHz	100 kHz	300 kHz
1000 MHz – 25 GHz	1 MHz	3 MHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2007-11-15	2008-11-15
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2007-10-16	2008-10-16
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2007-08-14	2008-08-14
HP	Amplifier	8449B	3008A00277	2007-09-29	2008-09-29
Sunol Sciences	Horn Antenna	DRH-118	A052604	2007-09-25	2008-09-25
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2007-05-09	2008-05-09

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

For the radiated emissions test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz and peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.109, 15.205, 15.209, and 15.247, with the worst margin reading of:

Transmitting mode (30 - 1000 MHz):

12.3 dB at **235.625025 MHz** in the **Vertical** polarization

Transmitting mode (Above 1 GHz):

5.18 dB at **4804 MHz** in the **Vertical** polarization (**Low Channel**)

4.74 dB at **4882 MHz** in the **Vertical** polarization (**Middle Channel**)

4.07 dB at **4960 MHz** in the **Horizontal** polarization (**High Channel**)

Charging mode:

3.2 dB at **482.369254 MHz** in the **Vertical** polarization


Test Data

Environmental Conditions

Temperature:	20 ° C
Relative Humidity:	50 %
ATM Pressure:	100.8 kPa


The testing was performed by King Tang on 2008-04-03

Test Mode: Transmitting (30 - 1000 MHz)



Frequency (MHz)	Corrected Amp. (dBμV/m)	Antenna Height (cm)	Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dBμV/m)	Margin (dB)
235.625025	33.7	180.0	V	150	-12.0	46.0	12.3
297.120625	31.7	202.0	V	274.0	-9.4	46.0	14.3
46.252950	25.5	320.0	H	81.0	-16.9	40.0	14.5
531.253275	29.4	240.0	H	188.0	-5.6	46.0	16.6
465.348525	29.3	304.0	V	320.0	-6.3	46.0	16.7
31.424425	22.3	120.0	H	120	-6.6	40.0	17.7

Test Mode: Charging (30 - 1000 MHz)



Frequency (MHz)	Corrected Amp. (dBμV/m)	Antenna Height (cm)	Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dBμV/m)	Margin (dB)
482.369254	42.8	242.0	V	160.0	-6.6	46.0	3.2
961.251120	38.8	110.0	H	120.0	2.9	46.0	7.2
151.247014	32.2	150.0	V	39.0	-10.3	40.0	7.8
118.258746	31.3	181.0	H	220.0	-9.2	40.0	8.7
361.258426	33.0	131.0	V	85.0	-7.6	46.0	13.0
30.548210	24.2	320.0	H	130.0	-3.1	40.0	15.8

Test Mode: Transmitting (Above 1GHz)

Freq. (MHz)	Meter Reading (dBuV)	Detector PK/QP/AV	Direction Degree	Antenna			Cable Loss (dB)	Pre- Amp. Gain (dB)	Corr. Amp. (dBuV/m)	FCC Part 15.247/209		
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dBuV/m)	Margin (dB)	Remarks
Frequency in Low Channel												
2402	80.23	PK	0	1.4	H	28.9	3.61	35	77.74	<div></div>	<div></div>	Fund.
2402	75.34	AV	45	1.5	H	28.9	3.61	35	72.85			Fund.
2402	84.21	PK	90	1.4	V	29.1	3.61	35	81.92			Fund.
2402	81.32	AV	360	1.4	V	29.1	3.61	35	79.03			Fund.
4804	42.88	AV	210	1.0	V	34.7	4.64	33.4	48.82	54	5.18	Harmonic
4804	41.23	AV	180	1.0	H	34.6	4.64	33.4	47.07	54	6.93	Harmonic
1688	51.34	AV	310	1.2	V	26.0	2.77	35.0	45.11	54	8.89	Harmonic
1688	45.98	AV	180	1.2	H	26.5	2.77	35.0	40.25	54	13.75	Harmonic
4804	47.21	PK	180	1.2	V	34.7	4.64	33.4	53.15	74	20.85	Harmonic
4804	45.14	PK	200	1.2	H	34.6	4.64	33.4	50.98	74	23.02	Harmonic
1688	53.44	PK	90	1.2	V	26.0	2.77	35.0	47.21	74	26.79	Harmonic
1688	52.37	PK	45	1.2	H	26.5	2.77	35.0	46.64	74	27.36	Harmonic
Frequency in Middle Channel												
2441	81.34	PK	60	1.5	H	29.1	3.61	35	79.05	<div></div>	<div></div>	Fund.
2441	75.63	AV	120	1.3	H	29.1	3.61	35	73.34			Fund.
2441	83.75	PK	257	1.2	V	28.9	3.61	35	81.26			Fund.
2441	81.32	AV	156	1.2	V	28.9	3.61	35	78.83			Fund.
4882	43.42	AV	243	1.4	V	34.6	4.64	33.4	49.26	54	4.74	Harmonic
4882	42.12	AV	95	1.2	H	34.7	4.64	33.4	48.06	54	5.94	Harmonic
1827	53.62	AV	135	1.3	H	26.0	2.77	35.0	47.39	54	6.61	Harmonic
1827	50.38	AV	45	1.1	V	26.5	2.77	35.0	44.65	54	9.35	Harmonic
4882	46.58	PK	180	1.5	V	34.6	4.64	33.4	52.42	74	21.58	Harmonic
4882	45.31	PK	234	1.5	H	34.7	4.64	33.4	51.25	74	22.75	Harmonic
1827	55.12	PK	360	1.4	V	26.5	2.77	35.0	49.39	74	24.61	Harmonic
1827	53.78	PK	157	1.4	H	26.0	2.77	35.0	47.55	74	26.45	Harmonic
Frequency in High Channel												
2480	80.32	PK	90	1.5	H	28.9	3.61	35	77.83	<div></div>	<div></div>	Fund.
2480	77.39	AV	110	1.5	H	28.9	3.61	35	74.90			Fund.
2480	84.01	PK	90	1.4	V	29.1	3.61	35	81.72			Fund.
2480	78.69	AV	360	1.6	V	29.1	3.61	35	76.40			Fund.
4960	44.18	AV	260	1.4	H	34.6	4.55	33.4	49.93	54	4.07	Harmonic
1574	54.76	AV	180	1.5	V	26.0	2.77	35.0	48.53	54	5.47	Spurious
1574	53.22	AV	160	1.2	H	26.5	2.77	35.0	47.49	54	6.51	Spurious
4960	41.49	AV	135	1.2	V	34.7	4.55	33.4	47.34	54	6.66	Harmonic
4960	47.38	PK	0	1.3	V	34.7	4.55	33.4	53.23	74	20.77	Harmonic
4960	45.11	PK	145	1.4	H	34.6	4.55	33.4	50.86	74	23.14	Harmonic
1574	55.88	PK	265	1.3	V	26.0	2.77	35.0	49.65	74	24.35	Spurious
1574	55.27	PK	200	1.5	H	26.5	2.77	35.0	49.54	74	24.46	Spurious

Fund. -- Fundamental

CFR47 §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2007-10-16	2008-10-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 100 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another truce
3. Measure the channel separation.

Limit

FCC Part 15, Subpart C Section 15.247(a)(1). Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB Bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater

Frequency Range (MHz)	Limit (kHz)
902-928	>25kHz or the 20dB bandwidth
2400-2483.5	>25kHz or two-thirds of the 20dB bandwidth
5725-5850	>25kHz or the 20dB bandwidth

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.8 kPa

The testing was performed by King Tang on 2008-04-02.


Test Mode: Transmitting

Channel	Channel Frequency (MHz)	Channel Separation (kHz)	Limit (kHz)	Result
Low Channel	2402	1004	181	Pass
Adjacent Channel	2403			
Mid Channel	2441	1004	181	Pass
Adjacent Channel	2442			
High Channel	2480	1004	181	Pass
Adjacent Channel	2479			

Test Result: Compliance.

Please refer to following plots


Low Channel



CHANNEL SEPRATION L

Date: 2 .APR. 2008 18:12:15


Middle Channel



CHANNEL SEPRATION M

Date: 2 .APR. 2008 18:13:15

High Channel



CHANNEL SEPRATION H

Date: 2.APR.2008 18:15:15

CFR47 §15.247(a) (1) – 20dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2007-10-16	2008-10-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.8 kPa

The testing was performed by King Tang on 2008-04-02.

Test Mode: Transmitting

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)
Low	2402	272
Middle	2441	272
High	2480	272


Test Result: Please refer to following plots

Low Channel

20dB Bandwidth L

Date: 2.APR.2008 18:17:15


Middle Channel



20dB Bandwidth M

Date: 2 .APR. 2008 18:27:15

High Channel



20dB Bandwidth H

Date: 2.APR.2008 18:07:15

CFR47 §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2007-10-16	2008-10-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in transmitting mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.8 kPa

The testing was performed by King Tang on 2008-04-02.


Test Mode: Transmitting

Test Result: Compliance.

Please refer to following plot

Hopping Channel Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
2402-2480	79	>15

Number of Hopping Channels



HOPPING CHANNELS

Date: 2 .APR. 2008 18:22:19

CFR47 §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2007-10-16	2008-10-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.8 kPa

The testing was performed by King Tang on 2008-04-02.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Channel	Pulse width (ms)	Dwell time (s)	Limit (s)	Result
Low	0.52	0.1664	0.4	Pass
Middle	0.52	0.1664	0.4	Pass
High	0.52	0.1664	0.4	Pass


NOTE: Dwell time=Pulse width (ms) × (1600 ÷ 2 ÷ 79) × 31.6 Second

Low Channel

dwell time low

Date: 2.APR.2008 18:18:15


Middle Channel



dwell time middle

Date: 2.APR.2008 18:20:15

High Channel



dwell time high

Date: 2.APR.2008 17:28:35

CFR47 §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2007-10-16	2008-10-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	56 %
ATM Pressure:	100.8kPa


The testing was performed by King Tang on 2008-04-02.

Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


Channel	Channel Frequency (MHz)	Power Output		Limit (w)
		(dBm)	(mw)	
Low	2402	-3.42	0.4549	1
Mid	2441	-3.12	0.4875	1
High	2480	-4.21	0.3793	1

Low Channel

output power low

Date: 2 .APR. 2008 18:40:25


Middle Channel



output power middle

Date: 2 .APR. 2008 18:50:21

High Channel



output power high

Date: 2.APR.2008 18:28:13

CFR47 §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2007-10-16	2008-10-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data**Environmental Conditions**

Temperature:	25°C
Relative Humidity:	56 %
ATM Pressure:	100.8kPa

The testing was performed by King Tang on 2008-04-02.


Test Mode: Transmitting

Frequency (MHz)	Delta Peak to in Band Emission (dBc)	Limit (dBc)
2399.672	56.64	20
2495.968	56.49	20

Test Result: Compliance.

Please refer to following plot.


Band Edge Left Side



OUT OF BAND-LEFT

Date: 2.APR.2008 18:23:35

Band Edge Right Side



OUT OF BAND-RIGHT

Date: 2.APR.2008 18:25:21

***** END OF REPORT *****