

FCC PART 15, SUBPART B and C TEST REPORT

for

VPt Sensor

MODEL: CM-000362

Prepared for

MESA LABS, INC. 12100 WEST 6TH AVENUE LAKEWOOD, COLORADO 80228

Prepared by: Kule Jajimsto

KYLE FUJIMOTO

Approved by: Jomen Rom

JAMES ROSS

COMPATIBLE ELECTRONICS INC. 114 OLINDA DRIVE BREA, CALIFORNIA 92823 (714) 579-0500

DATE: AUGUST 28, 2018

	REPORT	APPENDICES					TOTAL
	BODY	A	B	С	D	E	
PAGES	21	2	2	2	11	49	87

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
SUMMARY OF TEST RESULTS	5
1. PURPOSE	6
2. ADMINISTRATIVE DATA	7
2.1 Location of Testing	7
2.2 Traceability Statement 2.3 Cognizant Personnel	7
2.4 Date Test Sample was Received	7
2.5 Disposition of the Test Sample	7
2.6 Abbreviations and Acronyms	/
3. APPLICABLE DOCUMENTS	8
4. DESCRIPTION OF TEST CONFIGURATION 4.1.1 Cable Construction and Termination	9 10
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	11
5.1 EUT and Accessory List	11
5.2 Emissions Test Equipment	12
6. TEST SITE DESCRIPTION	13
6.1 Test Facility Description 6.2 EUT Mounting, Bonding and Grounding	13
6.3 Measurement Uncertainty	13
7. CHARACTERISTICS OF THE TRANSMITTER	14
7.1 Channel Number and Frequencies	14
7.2 Antenna	14
8. Test Procedures	15
8.1.1 Conducted Emissions Test	15
8.1.2 Radiated Emissions Test	16
8.1.3 RF Emissions Test Results	17
8.2 20 dB Bandwidth 8.3 Paak Output Power	18
8.4 RF Antenna Conducted Test	18
8.5 RF Band Edges	19
8.6 Carrier Frequency Separation	19
8.7 Number of Hopping Frequencies	19
8.9 Fundamental Field Strength (Duty Cycle Calculations)	19
8.10 Variation of the Input Power	20
9. CONCLUSIONS	21

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



APPENDIX	TITLE			
А	Laboratory Accreditations and Recognitions			
В	Modifications to the EUT			
С	Additional Models Covered Under This Report			
D	Diagrams and Charts			
	Test Setup Diagrams			
	Antenna and Effective Gain Factors			
Е	Data Sheets			

LIST OF FIGURES

FIGURE	TITLE
1	Conducted Emissions Test Setup
2	Layout of the Semi-Anechoic Test Chamber

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500



GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the federal government.

Device Tested:	VPt Sensor Model: CM-000362 S/N: 58000012
Product Description:	The EUT a part of a wireless sensor system to monitor the storage of vaccines.
Modifications:	The EUT was not modified in order to meet the specifications.
Customer:	Mesa Labs, Inc. 12100 West 6th Avenue Lakewood, Colorado 80228
Test Dates:	June 1, 6, 8, and 28, 2018; and August 28, 2018

Test Specification covered by accreditation:



Test Specifications:Emissions requirements
CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.207, 15.209, and
15.247Test Procedures:ANSI C63.4: 2013, ANSI C63.10: 2014

Test Deviations: The test procedure was not deviated from during the testing.

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS	
1	Conducted RF Emissions, 150 kHz - 30 MHz	This test was not performed because the EUT is battery powered only.	
2	Radiated RF Emissions, 10 kHz – 9300 MHz	Complies with the Class B limits of CFR Title 47, Part 15, Subpart B; and the limits of CFR Title 47, Part 15 Subpart C, 15.205, 15.209 and 15.247 (d) Highest reading in relation to spec limit: 44.94 dBuV @ 2706.75 MHz (*U = 3.67 dB)	
3	20 dB Bandwidth	Complies with the relevant requirements of CFR Title 47, Part 15, Subpart C, section 15.247 (a)(1)(i)	
4	Peak Power Output	Complies with the relevant requirements of FCC Title 47, Part 15, Subpart C, section 15.247 (b)(2)	
5	RF Band Edges	Complies with the relevant requirements of FCC Title 47, Part 15, Subpart C, section 15.247 (d)	
6	Number of Hopping Frequencies	Complies with the relevant requirements of FCC Title 47, Part 15, Subpart C, section 15.247 (a)(1)(i)	
7	RF Conducted Antenna Test	This test was not preformed because the all emissions were performed via the radiated method described in section 8.1.2 of the test report.	
8	Carrier Frequency Separation	Complies with the relevant requirements of CFR Title 47, Part 15, Subpart C, section 15.247 (a)(1)	
9	Average Time of Occupancy	Complies with the relevant requirements of CFR Title 47, Part 15, Subpart C, section 15.247 (a)(1)(i)	
10	Variation of Input Power	Complies with the relevant requirements of CFR Title 47, Part 15, Subpart A, section 15.31 (e)	

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500



1. PURPOSE

This document is a qualification test report based on the emissions tests performed on the VPt Sensor, Model: CM-000362. The emissions measurements were performed according to the measurement procedure described in ANSI C63.4 and ANSI C63.10. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the **Class B** specification limits defined by CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.207, 15.209, and 15.247.



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The emissions tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Mesa Labs, Inc.

Al Murphy

Director of Engineering – Hardware

Compatible Electronics Inc.

Kyle Fujimoto James Ross Test Engineer Test Engineer

2.4 Date Test Sample was Received

The test sample was received on May 22, 2018.

2.5 Disposition of the Test Sample

The test sample has not been returned to Mesa Labs, Inc. as of the date of this test report.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
LISN	Line Impedance Stabilization Network
N/A	Not Applicable
Tx	Transmit
Rx	Receive

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



The following documents are referenced or used in the preparation of this emissions Test Report.

SPEC	TITLE
FCC Title 47, Part 15 Subpart C	FCC Rules – Radio frequency devices (including digital devices) – Intentional Radiators
FCC Title 47, Part 15 Subpart B	FCC Rules – Radio frequency devices (including digital devices) – Unintentional Radiators
558074 D01 DTS Meas Guidance v04	Guidance for Performing Compliance Measurements on Digital Transmissions Systems (DTS) Operating Under Section 15.247
EN 50147-2: 1997	Anechoic chambers. Alternative test site suitability with respect to site attenuation
ANSI C63.4 2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10 2013	American National Standard for Testing Unlicensed Wireless Devices

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500



4.

The VPt Sensor, Model: CM-000362 (EUT) was connected to a steel thermistor probe and a door switch sensor via its probe and door sensor ports, respectively.

For configurating the EUT for the intentional radiator portion of the test: The EUT was connected to a laptop that had a program that locked one channel at a time so that the low, middle, and high channels could be tested. The EUT was tested in three orthogonal axis. The carrier was modulated in the same way it would be when the EUT was in its normal operating mode.

For configurating the EUT for the unintentional radiator portion of the test: The EUT was connected to a laptop that allowed the EUT to function as normal. The laptop also had a program that locked on channel at a time so that the low, middle, and high channels of the LO of the Rx could be tested.

Note: The laptop was only connected to the EUT to program the correct configuration and then was removed during the testing.

The program is the VPx Configuration Utility software, version 1.1.8.2 BETA. This software is located of the company's servers.

The X-Axis is when the EUT is parallel to the ground reference plane. The Y-Axis is when the EUT is perpendicular to the ground reference plane. The Z-Axis is when the front of the EUT is rotated 90 degrees and perpendicular to the ground reference plane.

The final radiated data for the EUT as well as the conducted data was taken in the modes described above. Please see Appendix E for the data sheets.

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



4.1.1 Cable Construction and Termination

Cable 1

This is a 1.5-meter unshielded cable connecting the steel thermistor probe to the EUT. The cable is hard wired at the steel thermistor probe end and has a 6-pin Hirose connector at the EUT end.

<u>Cable 2</u> This is a 1-meter unshielded cable connecting the door switch sensor to the EUT. The cable is hard wired at the door switch sensor end and has a 3.5mm mono jack connector at the EUT end.



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Page 11 of 21

5.1 EUT and Accessory List

EQUIPMENT	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID
VPt SENSOR	MESA LABS, INC.	CM-000362	58000012	UUYVPX900AP
AC ADAPTER FOR LAPTOP	HEWLETT PACKARD	PPP012D-S	WCNXF0ACX3OCXS	N/A
LAPTOP	HEWLETT PACKARD	PROBOOK 6560B	N/A	N/A
VPx CONFIGURATION UTILITY*	MESA LABS, INC.	VER. 1.1.8.2 BETA	SW-00056	N/A

*This is the software used to program the EUT so that it can transmit in the low, middle, and high channels and also transmit in its normal operation on a continuous basis.

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



5.2 Emissions Test Equipment

EQUIPMENT TYPE	MANU- FACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE		
	RF RADIATED EMISSIONS TEST EQUIPMENT						
TDK TestLab	TDK RF Solutions, Inc.	9.22	700145	N/A	N/A		
EMI Receiver	Rohde & Schwarz	ESIB40	100194	September 26, 2017	1 Year		
System Controller	Sunol Sciences Corporation	SC110V	112213-1	N/A	N/A		
Turntable	Sunol Sciences Corporation	2011VS	N/A	N/A	N/A		
Antenna-Mast	Sunol Sciences Corporation	TWR95-4	112213-3	N/A	N/A		
Loop Antenna	Com-Power	AL-130R	121090	February 9, 2017	2 Year		
CombiLog Antenna	Com-Power	AC-220	61060	July 27, 2017	1 Year		
Horn Antenna	Com-Power	AH-118	071175	February 22, 2018	2 Year		
Preamplifier	Com-Power	PAM-118A	551024	May 10, 2018	1 Year		
Computer	Hewlett Packard	p6716f	MXX1030PX0	N/A	N/A		
LCD Monitor	Hewlett Packard	52031a	3CQ046N3MG	N/A	N/A		

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



6.1 Test Facility Description

Please refer to section 2.1 and 7.1 of this report for emissions test location.

6.2 EUT Mounting, Bonding and Grounding

For frequencies 1 GHz and below: The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane.

For frequencies above 1 GHz: The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 1.5 meters above the ground plane.

The EUT was not grounded.

6.3 Measurement Uncertainty

The uncertainty values are in the table below.

The uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level, using a coverage factor of k=2

MEASUREMENT TYPE	PARTICULAR CONFIGURATION	UNCERTAINTY VALUES
RADIATED EMISSIONS	3-METER CHAMBER, COMBILOG ANTENNA	3.26 (Vertical) 3.19 (Horizontal)
RADIATED EMISSIONS	3-METER CHAMBER, HORN ANTENNA	3.67 dB
AC LINE CONDUCTED EMISSIONS	3-METER CHAMBER, COM-POWER LISN	2.72 dB

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 Channel Number and Frequencies

The FHSS uses at least a minimum of 50 channels minimum using a pseudo random technique. It uses GFSK modulation. The channels are separated by approximately 250 kHz.

The three subbands that the EUT can operate on are: 1. 906.12 MHz to 924.12 MHz, which contains 58 channels 2. 902.62 MHz to 914.87 MHz, which contains 50 channels 3. 914.87 MHz to 927.62 MHz, which contains 50 channels

See Appendix E for the each plot showing the total number of channels in each subband.

7.2 Antenna

The EUT uses an ANT-900-CHP antenna with a gain of 0.5 dBi.

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



8. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

8.1 **RF Emissions**

8.1.1 Conducted Emissions Test

The EMI Receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. A transient limiter was used for the protection of the EMI Receiver input stage, and the offset was adjusted accordingly to read the actual data measured. The LISN output was measured using the EMI Receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI 63:4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The final data was collected under program control by computer software. The final qualification data is located in Appendix E.

The EUT was tested at 120 VAC. The six highest emissions are listed in Table 1.0.

Test Results:

This test was not performed because the EUT operates on battery power only and cannot be connected to the AC public mains.

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



8.1.2 Radiated Emissions Test

The EMI Receiver was used as the measuring meter. Preamplifiers were used to increase the sensitivity of the instrument. The EMI Receiver was initially used with the Analyzer mode feature activated. In this mode, the EMI receiver can then record the actual frequency to be measured. This final reading is then taken accurately in the EMI Receiver mode, which takes into account the cable loss, amplifier gain and antenna factors, so that a true reading is compared to the true limit. The effective measurement bandwidth used for the radiated emissions test was according to the frequency measured.

The frequencies below 1 GHz were quasi-peaked using the quasi-peak detector of the EMI Receiver.

The frequencies above 1 GHz were averaged using a duty cycle correction factor.

The EMI test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI C63.4. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna in order to ensure accurate results.

The EUT was tested at a 3-meter test distance. The six highest emissions are listed in Table 1.0.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER
10 kHz to 150 kHz	200 Hz	Loop Antenna
150 kHz to 30 MHz	9 kHz	Loop Antenna
30 MHz to 1 GHz	120 kHz	CombiLog Antenna
1 GHz to 9.3 GHz	1 MHz	Horn Antenna

Test Results:

The EUT complies with the **Class B** limits of **CFR** Title 47, Part 15, Subpart B; and Subpart C sections 15.205, 15.209, and 15.247 (d) for radiated emissions.

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



8.1.3 RF Emissions Test Results

Table 1.0 RADIATED EMISSION RESULTS VPt Sensor Model: CM-000362

Frequency MHz	EMI Reading (dBuV/m)	Specification Limit (dBuV/m)	Delta (Cor. Reading – Spec. Limit) dB)
4638.10 (Y-Axis) (H)	51.55 (Avg)	53.97	-2.42
4638.10 (X-Axis) (H)	51.02 (Avg)	53.97	-2.95
4638.10 (X-Axis) (V)	49.46 (Avg)	53.97	-4.51
4638.10 (Z-Axis) (H)	45.94 (Avg)	53.97	-8.03
4638.10 (Z-Axis) (V)	45.94 (Avg)	53.97	-8.03
4513.10 (Z-Axis) (H)	45.73 (Avg)	53.97	-8.24

Notes:

- * The complete emissions data is given in Appendix E of this report.
- (V) Vertical
- (H) Horizontal
- (AVG) Average

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



The 20 dB Bandwidth was measured using the EMI Receiver. The resolution bandwidth was $\geq 1 \%$ of the bandwidth and the video bandwidth was $\geq RBW$.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (a)(1)(i). The 20 dB bandwidth is less than the separation between channels. Please see the data sheets located in Appendix E.

8.3 Peak Output Power

The Peak Output Power was measured using radiated emissions method described in section 8.1.2 of this test report except the RBW was set to 8 MHz and the VBW was set to 50 MHz. The peak power was calculated by the following equation:

 $P = [(E*D)^2] / (30 G)$

P = Power in Watts for which you are solving

E = the measured maximum field strength in V/m utilizing the widest available RBW.

G = the numeric gain of the transmitting antenna over an isotropic radiator.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (b)(2). The maximum peak output power is less than 1 Watt. Please see the data sheets located in Appendix E.

8.4 RF Antenna Conducted Test

The RF antenna conducted test was performed using the EMI Receiver. The RF antenna conducted test measured using a direct connection from the RF out on the EUT into the input of the EMI Receiver. The resolution bandwidth was 100 kHz, and the video bandwidth was 300 kHz. The spans were wide enough to include all the harmonics and emissions that were produced by the intentional radiator.

Test Results:

This test was not performed because all of the emissions, including the non-restricted band emissions were done via the radiated method described in section 8.1.2 of this test report.

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



The RF band edges were taken at the edges of the ISM spectrum (902 MHz when the EUT was on the low channel and 928 MHz when the EUT was on the high channel) using the EMI Receiver. The RBW was set to 100 kHz and the VBW was set to 300 kHz. Plots of the fundamental were taken to ensure the amplitude at the band edges were at least 20 dB down from the peak of the fundamental emission. The plots were taken in both frequency hopping mode and single channel mode.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (d). The RF power at the band edges at 902 MHz and 928 MHz meet the requirements of FCC Title 47, Part 15, Subpart C section 15.247 (d). Please see the data sheets located in Appendix E.

8.6 Carrier Frequency Separation

The Channel Hopping Separation Test was measured using the EMI Receiver. The EUT was operating in its normal operating mode. The resolution bandwidth was approximately 30% of the channel spacing, and the video bandwidth \geq RBW. The frequency span was wide enough to include the peaks of two adjacent channels.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (a)(1). The Channel Hopping Separation is greater than the 20 dB bandwidth. Please see the data sheets located in Appendix E.

8.7 Number of Hopping Frequencies

The Number of Hopping Frequencies was measured using the EMI Receiver. The EUT was operating in its normal operating mode. The resolution bandwidth was set to approximately 30% of the channel spacing, and the video bandwidth was \geq RBW. The frequency span was wide enough to include all of the peaks in the frequency band of operation.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (a)(1) and 15.247 (a)(1)(i). Please see the data sheets located in Appendix E.

8.8 Average Time of Occupancy Test

The Average Time of Occupancy Test was measured using the EMI Receiver. The EUT was operating in normal operating mode. The frequency span was taken to 0 Hz to determine the time for each transmission and the number of transmissions over a 20 second period. The RBW was set to be less than the channel spacing. The low hop band table was determined to be the worst case because this mode results in the pulses appearing more frequently.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (a)(1)(i). Please see the data sheets located in Appendix E.

Brea Division	Lake Forest Division	Newbury Park Division
114 Olinda Drive	20621 Pascal Way	1050 Lawrence Drive
Brea, CA 92823	Lake Forest, CA 92630	Newbury Park, CA 91320
(714) 579-0500	(949) 587-0400	(805) 480-4044



8.9 Fundamental Field Strength (Duty Cycle Calculations)

The Peak Transmit Radiated Field Strength was measured at a 3-meter test distance. The EMI Receiver was used to obtain the duty cycle. The data sheets are located in Appendix E.

Where

 $\delta(\mathrm{dB}) = 20\log\left[\sum \left(nt_1 + mt_2 + \dots + \xi t_x\right)/T\right]$

n is the number of pulses of duration t1*m* is the number of pulses of duration t2 ξ is the number of pulses of duration tx*T* is the period of the pulse train or 100 ms if the pulse train length is greater than 100 ms

Duty Cycle Correction Factor = -20.00dB

Pulse = 1 * 8.817635 ms

Total On Time = 8.817635 ms

Duty Cycle Train was longer than 100mS; therefore 100mS span was used.

8.817635 ms / 100 ms = 8.817635 %

 $20 \log (0.08817635) = -21.09 \text{ dB}$ correction factor

Max Duty Cycle Correction Factor = -20.00dB

8.10 Variation of the Input Power

The variation of the input power test was performed using the EMI Receiver. The EUT input power was varied between 85% and 115% of the nominal rated supply voltage. The carrier frequency was monitored for any change in amplitude.

Test Results:

This test was not performed because the EUT operates on battery power only and cannot be connected to the AC public mains.

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



9. CONCLUSIONS

The VPt Sensor, Model: CM-000362, as tested, meets all of the specification limits defined in FCC Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.207, 15.209, and 15.247.



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



APPENDIX A

LABORATORY ACCREDITATIONS AND RECOGNITIONS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



LABORATORY ACCREDITATIONS AND RECOGNITIONS



For US, Canada, Australia/New Zealand, Japan, Taiwan, Korea, and the European Union, Compatible Electronics is currently accredited by NVLAP to ISO/IEC 17025. For the most up-to-date version of our scopes and certificates please visit http://celectronics.com/quality/scope/

Quote from ISO-ILAC-IAF Communiqué on 17025:

"A laboratory's fulfilment of the requirements of ISO/IEC 17025:2005 means the laboratory meets both the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically valid test results and calibrations. The management system requirements in ISO/IEC 17025:2005 (Section 4) are written in language relevant to laboratory operations and meet the principles of ISO 9001:2008 Quality Management Systems — Requirements."



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Page B1

APPENDIX B

MODIFICATIONS TO THE EUT

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC Subpart B and FCC 15.247 specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made to the EUT during the testing.



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



APPENDIX C

ADDITIONAL MODELS COVERED UNDER THIS REPORT

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

VPt Sensor Model: 58000012 S/N: N/A

There are no additional models covered under this report.



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



APPENDIX D

DIAGRAMS AND CHARTS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



FIGURE 1: CONDUCTED EMISSIONS TEST SETUP



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



FIGURE 2: LAYOUT OF THE SEMI-ANECHOIC TEST CHAMBER



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



COM-POWER AL-130R

LOOP ANTENNA

S/N: 121090

CALIBRATION DATE: FEBRUARY 9, 2017

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
0.009	-36.17	15.33
0.01	-35.86	15.64
0.02	-37.30	14.20
0.03	-36.58	14.92
0.04	-36.99	14.51
0.05	-37.66	13.84
0.06	-37.53	13.97
0.07	-37.64	13.86
0.08	-37.52	13.98
0.09	-37.62	13.88
0.1	-37.59	13.91
0.2	-37.79	13.71
0.3	-37.80	13.70
0.4	-37.70	13.80
0.5	-37.79	13.71
0.6	-37.79	13.71
0.7	-37.69	13.81
0.8	-37.49	14.01
0.9	-37.39	14.11
1	-37.39	14.11
2	-37.09	14.41
3	-37.09	14.41
4	-37.19	14.31
5	-36.98	14.52
6	-37.17	14.33
7	-37.05	14.45
8	-36.85	14.65
9	-36.84	14.66
10	-36.75	14.75
15	-37.16	14.34
20	-36.44	15.06
25	-37.88	13.62
30	-39.14	12.36

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



COMBILOG ANTENNA

S/N: 61060

CALIBRATION DATE: JULY 27, 2017

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	23.80	200	14.10
35	24.00	250	15.30
40	24.70	300	17.70
45	22.90	350	17.70
50	22.10	400	19.00
60	17.60	450	21.30
70	12.70	500	21.00
80	11.20	550	22.30
90	13.10	600	23.40
100	14.40	650	22.90
120	15.30	700	24.60
125	15.00	750	24.50
140	12.80	800	25.40
150	16.50	850	26.40
160	12.90	900	27.20
175	14.30	950	27.80
180	14.50	1000	26.80

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



COM POWER AH-118

HORN ANTENNA

S/N: 071175

CALIBRATION DATE: FEBRUARY 22, 2018

FREQUENCY	FACTOR	FREQUENCY	FACTOR
(GHz)	(dB)	(GHz)	(dB)
1.0	23.71	10.0	40.08
1.5	25.46	10.5	40.75
2.0	29.26	11.0	41.78
2.5	27.95	11.5	41.02
3.0	29.03	12.0	40.32
3.5	29.70	12.5	40.96
4.0	30.71	13.0	40.29
4.5	31.62	13.5	39.48
5.0	33.23	14.0	39.89
5.5	35.07	14.5	42.75
6.0	34.43	15.0	40.98
6.5	34.98	15.5	38.54
7.0	36.75	16.0	39.40
7.5	37.10	16.5	39.40
8.0	37.66	17.0	41.74
8.5	39.29	17.5	42.58
9.0	37.75	18.0	44.68
9.5	38.23		

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



COM-POWER PAM-118A

PREAMPLIFIER

S/N: 551024

CALIBRATION DATE: MAY 10, 2018

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	40.99	6.0	39.01
1.1	39.77	6.5	39.00
1.2	39.02	7.0	39.69
1.3	39.44	7.5	38.96
1.4	39.64	8.0	38.57
1.5	40.23	8.5	39.17
1.6	40.17	9.0	38.82
1.7	40.23	9.5	39.30
1.8	39.48	10.0	38.90
1.9	39.85	11.0	38.86
2.0	39.99	12.0	39.87
2.5	40.38	13.0	39.55
3.0	40.64	14.0	38.92
3.5	40.68	15.0	39.33
4.0	40.87	16.0	39.60
4.5	40.04	17.0	40.28
5.0	39.54	18.0	39.58
5.5	39.58		

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400





FRONT VIEW

MESA LABS, INC. VPt SENSOR MODEL: CM-000362 FCC SUBPART B AND C – RADIATED EMISSIONS – BELOW 1 GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400





REAR VIEW

MESA LABS, INC. VPt SENSOR MODEL: CM-000362 FCC SUBPART B AND C – RADIATED EMISSIONS – BELOW 1 GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400




FRONT VIEW

MESA LABS, INC. VPt SENSOR MODEL: CM-000362 FCC SUBPART B AND C – RADIATED EMISSIONS – ABOVE 1 GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400





REAR VIEW

MESA LABS, INC. VPt SENSOR MODEL: CM-000362 FCC SUBPART B AND C – RADIATED EMISSIONS – ABOVE 1 GHz

PHOTOGRAPH SHOWING THE EUT CONFIGURATION FOR MAXIMUM EMISSIONS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



APPENDIX E

DATA SHEETS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Page E2

RADIATED EMISSIONS DATA SHEETS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Low Channel - X-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1805.24	35.54	V	82.60	-47.06	Peak	252.75	101.23	Not in
								Restricted Band
2707.86	37.78	V	73.97	-36.19	Peak	214.00	156.00	
2707.86	35.54	V	53.97	-18.43	Avg	214.00	156.00	
3610.48	38.55	V	73.97	-35.42	Peak	228.25	100.00	
3610.48	36.09	V	53.97	-17.88	Avg	228.25	100.00	
				6.13				
4513.1	43.42	V	73.97	-30.55	Peak	44.00	100.00	
4513.1	37.61	V	53.97	-16.36	Avg	44.00	100.00	
5415.72	45.69	V	73.97	-28.28	Peak	229.25	133.29	
5415.72	41.38	V	53.97	-12.59	Avg	229.25	133.29	
6318.34	45.52	V	73.97	-28.45	Peak	128.50	100.94	Not in
								Restricted Band
7220.96	43.39	V	82.60	-39.21	Peak	259.50	143.14	Not in
								Restricted Band
8123.58								No Emission
8123.58								Detected
9026.2								No Emission
9026.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Low Channel - Y-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1805.24	34.72	V	82.60	-47.88	Peak	241.75	108.76	Not in
								Restricted Band
2707.86	41.89	V	73.97	-32.08	Peak	303.25	171.02	
2707.86	36.64	V	53.97	-17.33	Avg	303.25	171.02	
3610.48	45.78	V	73.97	-28.19	Peak	239.75	154.49	
3610.48	44.10	V	53.97	-9.87	Avg	239.75	154.49	
4513.1	46.84	V	73.97	-27.13	Peak	301.00	147.86	
4513.1	45.00	V	53.97	-8.97	Avg	301.00	147.86	
5415.72	41.75	V	73.97	-32.22	Peak	124.75	135.68	
5415.72	35.22	V	53.97	-18.75	Avg	124.75	135.68	
				3				
6318.34	45.81	V	73.97	-28.16	Peak	165.50	102.61	Not in
								Restricted Band
7220.96	42.99	V	82.60	-39.61	Peak	274.25	125.41	Not in
								Restricted Band
8123.58								No Emission
8123.58								Detected
9026.2								No Emission
9026.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Low Channel - Z-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1805.24	38.83	V	82.60	-43.77	Peak	135.75	228.46	Not in
ļ								Restricted Band
2707.86	40.13	V	73.97	-33.84	Peak	193.00	127.00	
2707.86	38.80	V	53.97	-15.17	Avg	193.00	127.00	
3610.48	36.25	V	73.97	-37.72	Peak	206.75	100.58	
3610.48	32.48	V	53.97	-21.49	Avg	206.75	100.58	
4513.1	43.50	V	73.97	-30.47	Peak	149.25	101.59	
4513.1	41.23	V	53.97	-12.74	Avg	149.25	101.59	
5415.72	43.57	V	73.97	-30.40	Peak	200.00	145.95	
5415.72	41.35	V	53.97	-12.62	Avg	200.00	145.95	
6318.34	45.62	V	73.97	-28.35	Peak	149.75	122.43	Not in
								Restricted Band
7220.96	45.70	V	82.60	-36.90	Peak	162.25	193.95	Not in
								Restricted Band
8123.58								No Emission
8123.58								Detected
9026.2								No Emission
9026.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Low Channel - X-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq	l evel	Pol			Peak /	Table	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1805.24	45.61	Н	82.60	-36.99	Peak	22.00	104.46	Not in
								Restricted Band
2707.86	36.73	Н	73.97	-37.24	Peak	298.00	152.58	
2707.86	34.36	Н	53.97	-19.61	Avg	298.00	152.58	
3610.48	35.39	Н	73.97	-38.58	Peak	280.25	149.05	
3610.48	33.15	Н	53.97	-20.82	Avg	280.25	149.05	
4513.1	46.65	Н	73.97	-27.32	Peak	255.75	188.58	
4513.1	44.60	Н	53.97	-9.37	Avg	255.75	188.58	
5415.72	41.81	Н	73.97	-32.16	Peak	208.00	116.64	
5415.72	36.46	Н	53.97	-17.51	Avg	208.00	116.64	
6318.34	45.26	Н	73.97	-28.71	Peak	133.25	163.26	Not in
								Restricted Band
7220.96	42.69	Н	82.60	-39.91	Peak	225.00	163.32	Not in
								Restricted Band
8123.58								No Emission
8123.58								Detected
9026.2								No Emission
9026.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Low Channel - Y-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1805.24	45.52	Н	82.60	-37.08	Peak	32.25	108.28	Not in
								Restricted Band
2707.86	39.27	Н	73.97	-34.70	Peak	200.00	147.14	
2707.86	37.56	Н	53.97	-16.41	Avg	200.00	147.14	
3610.48	40.68	Н	73.97	-33.29	Peak	76.00	120.34	
3610.48	37.97	Н	53.97	-16.00	Avg	76.00	120.34	
4513.1	46.17	Н	73.97	-27.80	Peak	192.75	115.98	
4513.1	44.39	Н	53.97	-9.58	Avg	192.75	115.98	
5415.72	44.32	Н	73.97	-29.65	Peak	250.25	177.23	
5415.72	40.07	Н	53.97	-13.90	Avg	250.25	177.23	
6318.34	46.32	Н	73.97	-27.65	Peak	234.25	134.25	Not in
								Restricted Band
7220.96	44.68	Н	82.60	-37.92	Peak	166.75	148.82	Not in
								Restricted Band
8123.58								No Emission
8123.58								Detected
9026.2								No Emission
9026.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Low Channel - Z-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.		Pol	1		Peak / QP /	Table Angle	Ant. Height	0
(IVIHZ)	(dBuv/m)	(v/n)		Wargin	Avg	(deg)	(cm)	Comments
1805.24	47.69	Н	82.60	-34.91	Реак	87.00	164.10	Not in
								Restricted Band
0707.00	00.70		70.07	40.07	Deal	0.47.75	400.07	
2707.86	33.70	н	73.97	-40.27	Реак	247.75	138.07	
2707.86	31.16	Н	53.97	-22.81	Avg	247.75	138.07	
0040.40	00.00		70.07	07.04	Deal	004.00	400.04	
3610.48	36.63	Н	73.97	-37.34	Реак	284.00	120.04	
3610.48	32.60	н	53.97	-21.37	Avg	284.00	120.04	
1=10.1	17.00					0.40.00	404 50	
4513.1	47.36	H	73.97	-26.61	Peak	346.00	101.59	
4513.1	45.73	Н	53.97	-8.24	Avg	346.00	101.59	
5415.72	46.76	Н	73.97	-27.21	Peak	342.75	103.44	
5415.72	44.55	Н	53.97	-9.42	Avg	342.75	103.44	
6318.34	46.33	Н	73.97	-27.64	Peak	104.25	170.73	Not in
								Restricted Band
7220.96	43.63	Н	82.60	-38.97	Peak	314.25	137.77	Not in
								Restricted Band
8123.58								No Emission
8123.58								Detected
9026.2								No Emission
9026.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Middle Channel - X-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

					Peak /	Table	Ant.	
Freg. (MHz)	(dBuV/m)	Pol (v/h)	Limit	Margin	QP/ Ava	(dea)	Height (cm)	Comments
1830.24	34.93	V	82.60	-47.67	Peak	313.75	109.53	Not in
				1				Restricted Band
2745.36	37.19	V	73.97	-36.78	Peak	284.00	148.52	
2745.36	31.49	V	53.97	-22.48	Avg	284.00	148.52	
3660.48	37.42	V	73.97	-36.55	Peak	258.25	197.29	
3660.48	32.47	V	53.97	-21.50	Avg	258.25	197.29	
			111					
4575.6	46.08	V	73.97	-27.89	Peak	255.75	163.38	
4575.6	41.30	V	53.97	-12.67	Avg	255.75	163.38	
5490.72	40.97	V	82.60	-41.63	Peak	280.00	114.61	Not in
								Restricted Band
6405.84	46.73	V	82.60	-35.87	Peak	212.50	218.37	Not in
								Restricted Band
7320.96	46.68	V	73.97	-27.29	Peak	199.75	149.11	
7320.96	41.49	V	53.97	-12.48	Avg	199.75	149.11	
8236.08								No Emission
8236.08								Detected
9151.2								No Emission
9151.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Middle Channel - Y-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Frog		Pol			Peak /	Table	Ant.	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1830.24	35.23	V	82.60	-47.37	Peak	153.75	140.04	Not in
								Restricted Band
2745.36	36.36	V	73.97	-37.61	Peak	234.50	158.91	
2745.36	35.75	V	53.97	-18.22	Avg	234.50	158.91	
3660.48	35.15	V	73.97	-38.82	Peak	342.75	112.40	
3660.48	35.14	V	53.97	-18.83	Avg	342.75	112.40	
4575.6	45.23	V	73.97	-28.74	Peak	343.75	100.40	
4575.6	42.24	V	53.97	-11.73	Avg	343.75	100.40	
5490.72	33.88	V	82.60	-48.72	Peak	263.25	127.98	Not in
								Restricted Band
				55				
6405.84	44.13	V	82.60	-38.47	Peak	260.25	144.34	Not in
								Restricted Band
7320.96	45.43	V	73.97	-28.54	Peak	279.00	119.26	
7320.96	43.41	V	53.97	-10.56	Avg	279.00	119.26	
8236.08								No Emission
8236.08								Detected
9151.2								No Emission
9151.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Middle Channel - Z-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.		Pol	Lingit	Manain	Peak / QP /	Table Angle	Ant. Height	Ocumenta
		(v/n)			Avg	(aeg)	(cm)	Comments
1830.24	37.20	V	82.60	-45.34	Реак	197.5	96.82	Not in
								Restricted Band
0745.00	00.70		70.07	40.04	Deal	077.75	400.50	
2745.36	33.76	V	73.97	-40.21	Реак	2/1.75	128.58	
2745.36	31.58	V	53.97	-22.39	Avg	277.75	128.58	
				10.07			040.07	
3660.48	33.70	V	/3.9/	-40.27	Peak	316.25	218.97	
3660.48	30.77	V	53.97	-23.20	Avg	316.25	218.97	
4575.6	45.90	V	73.97	-28.07	Peak	338.50	138.55	
4575.6	43.38	V	53.97	-10.59	Avg	338.50	138.55	
5490.72	32.87	V	82.60	-49.73	Peak	310.75	139.92	Not in
					- Julies	a constant		Restricted Band
6405.84	46.71	V	82.60	-35.89	Peak	334.00	152.34	Not in
								Restricted Band
7320.96	46.43	V	73.97	-27.54	Peak	343.00	192.28	
7320.96	41.66	V	53.97	-12.31	Avg	343.00	192.28	
8236.08								No Emission
8236.08								Detected
9151.2								No Emission
9151.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Middle Channel - X-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq	l evel	Pol			Peak /	Table	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1830.24	40.51	Н	82.60	-42.09	Peak	115.75	157.41	Not in
								Restricted Band
2745.36	33.42	Н	73.97	-40.55	Peak	201.75	162.07	
2745.36	29.77	Н	53.97	-24.20	Avg	201.75	162.07	
3660.48	35.69	Н	73.97	-38.28	Peak	228.00	100.10	
3660.48	29.99	Н	53.97	-23.98	Avg	228.00	100.10	
4575.6	47.45	Н	73.97	-26.52	Peak	61.00	145.77	
4575.6	45.15	Н	53.97	-8.82	Avg	61.00	145.77	
5490.72	40.66	Н	82.60	-41.94	Peak	276.00	203.08	Not in
								Restricted Band
6405.84	47.49	Н	82.60	-35.11	Peak	170.00	207.92	Not in
								Restricted Band
7320.96	44.81	Н	73.97	-29.16	Peak	154.50	210.61	
7320.96	36.05	Н	53.97	-17.92	Avg	154.50	210.61	
8236.08								No Emission
8236.08								Detected
9151.2								No Emission
9151.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Middle Channel - Y-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1830.24	41.99	Н	82.60	-40.61	Peak	152.75	129.83	Not in
								Restricted Band
2745.36	35.42	Н	73.97	-38.55	Peak	101.75	173.53	
2745.36	33.65	Н	53.97	-20.32	Avg	101.75	173.53	
3660.48	34.49	Н	73.97	-39.48	Peak	62.50	202.13	
3660.48	28.14	Н	53.97	-25.83	Avg	62.50	202.13	
4575.6	47.65	Н	73.97	-26.32	Peak	207.25	177.83	
4575.6	44.33	Н	53.97	-9.64	Avg	207.25	177.83	
5490.72	41.46	Н	82.60	-41.14	Peak	144.75	195.80	Not in
								Restricted Band
6405.84	46.48	Н	82.60	-36.12	Peak	229.75	141.95	Not in
								Restricted Band
7320.96	42.48	Н	73.97	-31.49	Peak	123.25	143.80	
7320.96	35.11	Н	53.97	-18.86	Avg	123.25	143.80	
8236.08								No Emission
8236.08								Detected
9151.2								No Emission
9151.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 Middle Channel - Z-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq		Pol			Peak /	Table	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1830.24	42.16	Н	82.60	-40.44	Peak	104.25	168.52	Not in
								Restricted Band
2745.36	37.10	Н	73.97	-36.87	Peak	91.50	177.05	
2745.36	34.11	Н	53.97	-19.86	Avg	91.50	177.05	
3660.48	36.15	Н	73.97	-37.82	Peak	233.25	13419	
3660.48	29.66	Н	53.97	-24.31	Avg	233.25	134.19	
4575.6	47.15	Н	73.97	-26.82	Peak	287.50	104.22	
4575.6	43.25	Н	53.97	-10.72	Avg	287.50	104.22	
5490.72	43.19	Н	82.60	-39.41	Peak	215.50	114.01	Not in
								Restricted Band
				54				
6405.84	47.34	Н	82.60	-35.26	Peak	127.00	137.89	Not in
								Restricted Band
7320.96	43.48	Н	73.97	-30.49	Peak	105.25	172.10	
7320.96	36.13	Н	53.97	-17.84	Avg	105.25	172.10	
8236.08								No Emission
8236.08								Detected
9151.2								No Emission
9151.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 **High Channel - X-Axis Transmit Mode** Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.	Level	Pol	1		Peak / QP /	Table Angle	Ant. Height	0
		(v/n)		wargin	Avg	(aeg)	(cm)	Comments
1855.24	29.58	V	82.60	-53.02	Реак	280.25	222.67	Not in
								Restricted Band
2782.86	38.85	V	73.97	-35.12	Peak	61.25	155.92	
2782.86	36.83	V	53.97	-17.14	Avg	61.25	155.92	
3710.48	38.46	V	73.97	-35.51	Peak	74.50	184.34	
3710.48	34.09	V	53.97	-19.88	Avg	74.50	184.34	
4638.1	50.56	V	73.97	-23.41	Peak	67.50	151.86	
4638.1	49.46	V	53.97	-4.51	Avg	67.50	151.86	
5565.72						a source source		No Emission
5565.72								Detected
								-
6493.34	47.62	V	82.60	-34.98	Peak	33.75	131.92	Not in
								Restricted Band
7420.96								No Emission
7420.96								Detected
8348.58								No Emission
8348.58								Detected
9276.2						1		No Emission
9276.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 **High Channel - Y-Axis Transmit Mode** Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1855.24	30.62	V	82.60	-51.98	Peak	145.75	161.89	Not in
								Restricted Band
2782.86	33.61	V	73.97	-40.36	Peak	232.00	175.80	
2782.86	29.31	V	53.97	-24.66	Avg	232.00	175.80	
3710.48	35.66	V	73.97	-38.31	Peak	19.25	218.25	
3710.48	29.60	V	53.97	-24.37	Avg	19.25	218.25	
4638.1	44.64	V	73.97	-29.33	Peak	183.25	143.92	
4638.1	41.73	V	53.97	-12.24	Avg	183.25	143.92	
5565.72						a source and		No Emission
5565.72								Detected
6493.34	48.19	V	82.60	-34.41	Peak	344.50	103.96	Not in
								Restricted Band
7420.96								No Emission
7420.96								Detected
8348.58								No Emission
8348.58								Detected
9276.2								No Emission
9276.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 High Channel - Z-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
Freq. (MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1855.24	38.36	V	82.60	-44.24	Peak	217.5	108.04	Not in
								Restricted Band
2782.86	34.64	V	73.97	-39.33	Peak	215.75	103.20	
2782.86	31.79	V	53.97	-22.18	Avg	215.75	103.20	
3710.48	34.47	V	73.97	-39.50	Peak	223.50	147.98	
3710.48	25.67	V	53.97	-28.30	Avg	223.50	147.98	
4638.1	48.02	V	73.97	-25.95	Peak	354.00	121.83	
4638.1	45.94	V	53.97	-8.03	Avg	354.00	121.83	
5565.72								No Emission
5565.72				- 14	10000 months			Detected
6493.34	52.78	V	82.60	-29.82	Peak	328.75	196.46	Not in
								Restricted Band
7420.96	45.77	V	73.97	-28.20	Peak	344.75	201.83	
7420.96	39.90	V	53.97	-14.07	Avg	344.75	201.83	
8348.58								No Emission
8348.58								Detected
9276.2								No Emission
9276.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 High Channel - X-Axis Transmit Mode Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
Freq. (MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1855.24	33.54	Н	82.60	-49.06	Peak	170.75	106.73	Not in
								Restricted Band
2782.86	38.07	Н	73.97	-35.90	Peak	254.75	122.19	
2782.86	35.49	Н	53.97	-18.48	Avg	254.75	122.19	
3710.48	39.80	Н	73.97	-34.17	Peak	201.00	187.92	
3710.48	36.45	Н	53.97	-17.52	Avg	201.00	187.92	
4638.1	52.15	Н	73.97	-21.82	Peak	26.50	164.94	
4638.1	51.02	Н	53.97	-2.95	Avg	26.50	164.94	
5565.72								No Emission
5565.72				- 144	Marine Sector			Detected
6493.34	54.88	Н	82.60	-27.72	Peak	351.25	100.64	Not in
								Restricted Band
7420.96	43.53	Н	73.97	-30.44	Peak	63.50	101.17	
7420.96	35.15	Н	53.97	-18.82	Avg	63.50	101.17	
8348.58								No Emission
8348.58								Detected
9276.2								No Emission
9276.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 **High Channel - Y-Axis Transmit Mode** Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Frea.	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1855.24	35.29	Н	82.60	-47.31	Peak	190.75	208.52	Not in
								Restricted Band
2782.86	41.32	Н	73.97	-32.65	Peak	211.00	142.97	
2782.86	35.44	Н	53.97	-18.53	Avg	211.00	142.97	
3710.48	40.46	Н	73.97	-33.51	Peak	202.75	179.98	
3710.48	36.21	Н	53.97	-17.76	Avg	202.75	179.98	
4638.1	53.15	Н	73.97	-20.82	Peak	192.25	180.10	
4638.1	51.55	Н	53.97	-2.42	Avg	192.25	180.10	
5565.72					· / / ·	. Internet		No Emission
5565.72								Detected
6493.34	55.11	Н	82.60	-27.49	Peak	196.75	217.41	Not in
								Restricted Band
7420.96	43.69	Н	73.97	-30.28	Peak	169.00	204.82	
7420.96	34.59	Н	53.97	-19.38	Avg	169.00	204.82	
8348.58								No Emission
8348.58								Detected
9276.2								No Emission
9276.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Mesa Labs, Inc. VPt Sensor Model: CM-000362 **High Channel - Z-Axis Transmit Mode** Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Freq.	Level	Pol			Peak / QP /	Table Angle	Ant. Height	
(MHz)	(dBuV/m)	(v/h)	Limit	Margin	Avg	(deg)	(cm)	Comments
1855.24	36.42	Н	82.60	-46.18	Peak	296.25	144.88	Not in
								Restricted Band
2782.86	37.43	Н	73.97	-36.54	Peak	300.50	140.40	
2782.86	31.79	Н	53.97	-22.18	Avg	300.50	140.40	
3710.48	38.10	Н	73.97	-35.87	Peak	286.75	198.97	
3710.48	30.90	Н	53.97	-23.07	Avg	286.75	198.97	
4638.1	48.02	Н	73.97	-25.95	Peak	210.00	195.64	
4638.1	45.94	Н	53.97	-8.03	Avg	210.00	195.64	
5565.72						a contra contra		No Emission
5565.72								Detected
6493.34	48.86	Н	82.60	-33.74	Peak	210.00	200.00	Not in
								Restricted Band
7420.96	45.77	Н	73.97	-28.20	Peak	215.00	225.00	
7420.96	39.90	Н	53.97	-14.07	Avg	215.00	225.00	
8348.58								No Emission
8348.58								Detected
9276.2								No Emission
9276.2								Detected

Note: The channel that had the maximum amplitude for the fundamental was used to establish the reference level.

The reading with the worst case amplitude is Horizontal X-Axis - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



FCC 15.247 and FCC Class B Mesa Labs, Inc. VPt Sensor

Model: CM-000362

Date: 06/04/2018 Lab: D Tested By: Kyle Fujimoto

Non Harmonic Emissions from the Tx - 10 kHz to 30 MHz and 1 GHz to 9.3 GHz Digital Portion from the EUT - 10 kHz to 30 MHz and 1 GHz to 9.3 GHz

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
								No Emissions Detected
								from the Non Harmonic Emissions
								from the Tx
								10 kHz to 30 MHz
								No Emissions Detected
								from the Non Harmonic Emissions
								from the Tx
								1 GHz to 9.3 GHz
					1		in and	No Emissions Detected
								from the Digital Portion
								of the EUT
								10 kHz to 30 MHz
								No Emissions Detected
								from the Digital Portion
								of the EUT
								1 GHz to 9.3 GHz
								Tested in both Horizontal and
								Vertical Polarizations

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



FCC Class B and RSS-GEN Mesa Labs, Inc. VPt Sensor

Model: CM-000362

Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Receiver Portion - 10 kHz to 30 MHz and 1 GHz to 9.3 GHz

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
								No Emissions Detected
								in Receiver Mode
								10 kHz to 30 MHz
								No Emissions Detected
								in Receiver Mode
								1 GHz to 9.3 GHz
							1964 - A. A.	
								Tested in both Horizontal and
								Vertical Polarizations

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Page E23

Title: Pre-Scan - FCC Class B File: Rohde & Schwarz - Pre-Scan TRANSMITTER FCC Class B - 30 MHz to 1000 MHz.set Operator: Johnny EUT Type: VPI Sensor EUT Condition: The EUT is continuously transmitting Company: Mesa Labs, Inc Model: CM-000362 S/N: 58000012 Note: Testing X axis (worst case) - The emission in the 902-928 MHz band is subject to the limits of FCC 15.247 instead because it is the Intentional radiator.

6/8/2018 12:52:48 PM Sequence: Preliminary Scan



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Title: Radiated Final - FCC Class B File: Rohde & Schwarz - Final Scan TRANSMITTER FCC Class B - 30 MHz to 1000 MHz.set Operator: Johnny EUT Type: VPt Sensor EUT Condition: The EUT is continuously transmitting Company: Mesa Labs, Inc Model: CM-000362 S/N: 58000012 Note: Testing X axis (worst case)

(PEAK) EMI Freq Pol Transducer (QP) EMI (PEAK) Margin (QP) Margin Limit Cable Ttbl Agl Twr Ht (MHz) (deg) 24.75 (dBµV/m) (dBµV/m) (dB) (dB) (dBµV/m) (dB) (dB) (cm) 31.50 27.07 -12.93 н 21.85 -18.15 40.00 23.86 0.82 258.55 38.70 28.06 22.86 -11.94 -17.14 40.00 24.55 112.25 144.16 0.89 н 112.60 144.70 Н 33.54 31.64 -9.96 -17.86 -11.86 -20.56 43.50 14.99 1.15 144.00 123.50 258.67 127.56 25.64 н 22.94 43.50 14.66 1.28 160.70 н 32.76 28.70 -10.74 -14.80 43.50 12.99 1.30 244.50 193.05 29.17 25.17 176.90 н 33.21 -10.29 -14.33 43 50 14.38 1.32 311.00 160.64 193.10 н 29.41 -14.09 -18.33 43.50 14.24 1.45 269.25 111.26 217.30 н 37.05 32.51 -8.95 -13.49 46.00 14.54 1.57 117.75 110.97

FCC Class B



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400

Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044

6/8/2018 1:26:12 PM Sequence: Final Measurements



Title: Pre-Scan - FCC Class B File: Rohde & Schwarz - Pre-Scan RECEIVER - FCC Class B - 30 MHz to 1000 MHz.set Operator: Johnny EUT Type: VPt Sensor EUT Condition: The EUT is continuously receiving Company: Mesa Labs, Inc Model: CM-000362 S/Nt: S8000012 Note: Testing X axis (worse case) 6/8/2018 2:06:06 PM Sequence: Preliminary Scan



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Title: Radiated Final - FCC Class B File: Rohde & Schwarz - Final Scan RECEIVER FCC Class B - 30 MHz to 1000 MHz.set Operator: Johnny Le EUT Type: VPt Sensor EUT Condition: The EUT is continuously Receiving Company: Mesa Labs, Inc Model: CM-000362 S/N: 58000012

Freq	Pol	(PEAK) EMI	(QP) EMI	(PEAK) Margin	(QP) Margin	Limit	Transducer	Cable	Ttbl Agl	Twr Ht
(MHz)		(d BµV/m)	(dBµV/m)	(dB)	(d B)	(dBµV/m)	(dB)	(dB)	(deg)	(cm)
36.30	н	27.33	22.32	-12.67	-17.68	40.00	24.16	0.86	163.50	340.58
39.10	н	27.58	22.84	-12.42	-17.16	40.00	24.59	0.89	47.50	324.58
40.40	н	27.41	22.81	-12.59	-17.19	40.00	24.56	0.90	126.00	357.47
112.80	н	33.19	28.99	-10.31	-14.51	43.50	14.99	1.15	148.75	242.43
161.30	н	28.40	22.67	-15.10	-20.83	43.50	13.02	1.30	90.50	193.05
177.20	н	33.51	24.44	-9.99	-19.06	43.50	14.38	1.32	67.25	193.23
213.00	н	33.03	30.58	-10.47	-12.92	43.50	14.44	1.55	81.25	111.32
214.20	н	33.03	30.60	-10.47	-12.90	43.50	14.47	1.56	91.25	127.68
216.00	н	32.41	29.84	-11.09	-13.66	43.50	14.51	1.56	84.25	127.62

FCC Class B



Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044 Page E26

6/8/2018 2:30:41 PM Sequence: Final Measurements



Page E27

BAND EDGES DATA SHEETS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Marker 2 [T2] RBW 100 kHz RF Att 20 dB Ref Lvl 66.01 dB¥V VBW 300 kHz 112 db**y**v 902.0000000 MHz SWT 5 ms db⊾v Unit 112 dBJ 902.0000000 MHz ▽ -102 dBN. 100 902 2525<mark>050 MH</mark>z TRG 90 -D1 82.01 dbyv IN1 80 **2VIEW 2MA** 70 WU. white abrel mit Mur mh 1. March Win pure hmy wh mahmala Р0 60 TDS 50 40 30 20 F1 12 Start 890 MHz 1.5 MHz/ Stop 905 MHz Date: 6.JUN.2018 16:47:11

Band Edge - Low Channel - Fixed Frequency Mode

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044



Marker 2 [T2] 100 kHz RF Att 20 dB RBW Ref Lvl 66.30 dBVV 300 kHz VBW 102 db**y**v 928.0000000 MHz SWT 5 ms Unit dB⊿V 102 dBN 928.0000000 MHz ∇ dB_J 90 7.66533066 MHz TRG 80 D1 72.98 dbuv IN1 70 M. M.M achener Ull rid Mah 2МА 60 Р0 50 TDS 40 30 20 10 F1 2 Start 920 MHz 1.5 MHz/ Stop 935 MHz 6.JUN.2018 Date: 16:52:36

Band Edge - High Channel - Fixed Frequency Mode

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044





Band Edge - Low Channel - Frequency Hopping Mode

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044



Page E31



Band Edge - High Channel - Frequency Hopping Mode

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



Page E32

-20 DB BANDWIDTH DATA SHEETS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400





-20 dB Bandwidth - Low Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400

Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044





-20 dB Bandwidth - Middle Channel

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400

Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044


-20 dB Bandwidth - High Channel

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400

Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044



Page E36

PEAK POWER OUTPUT DATA SHEETS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



FCC 15.247

Mesa Labs, Inc. VPt Sensor Model: CM-000362 Date: 06/01/2018 Lab: D Tested By: Kyle Fujimoto

Setting = VPx Coniguration Utility - Ver 1.1.8.2 Beta - SW-00056 Peak Output Power

Frea.	Level		Antenna Gain	Numeric	Power Output	Power Output	Power Output	
(MHz)	(dBuV/m)	Level (V/m)	(dBi)	Gain	(Watts)	(mW)	(dBm)	Comments
902.62	97.87	0.078252821	0.5	1.122018	0.00163727	1.63727	2.14	Vert. X-Axis
915.12	96.63	0.067842212	0.5	1.122018	0.00123061	1.23061	0.90	Vert. X-Axis
927.62	91.45	0.037368013	0.5	1.122018	0.00037335	0.37335	-4.28	Vert. X-Axis
902.62	99.76	0.097274722	0.5	1.122018	0.00253000	2.53000	4.03	Vert. Y-Axis
915.12	97.34	0.07362071	0.5	1.122018	0.00144918	1.44918	1.61	Vert. Y-Axis
927.62	92.05	0.040040547	0.5	1.122018	0.00042867	0.42867	-3.68	Vert. Y-Axis
902.62	99.90	0.098855309	0.5	1.122018	0.00261289	2.61289	4.17	Vert. Z-Axis
915.12	100.70	0.108392691	0.5	1.122018	0.00314139	3.14139	4.97	Vert. Z-Axis
927.62	94.46	0.052844525	0.5	1.122018	0.00074666	0.74666	-1.27	Vert. Z-Axis
					and the second			
902.62	102.60	0.134896288	0.5	1.122018	0.00486543	4.86543	6.87	Horiz. X-Axis
915.12	98.13	0.08063062	0.5	1.122018	0.00173829	1.73829	2.40	Horiz. X-Axis
927.62	95.93	0.062589286	0.5	1.122018	0.00104742	1.04742	0.20	Horiz. X-Axis
902.62	99.09	0.090053376	0.5	1.122018	0.00216831	2.16831	3.36	Horiz. Y-Axis
915.12	98.13	0.08063062	0.5	1.122018	0.00173829	1.73829	2.40	Horiz. Y-Axis
927.62	95.22	0.057676646	0.5	1.122018	0.00088945	0.88945	-0.51	Horiz. Y-Axis
902.62	96.51	0.066911382	0.5	1.122018	0.00119707	1.19707	0.78	Horiz. Z-Axis
915.12	97.42	0.074301914	0.5	1.122018	0.00147612	1.47612	1.69	Horiz. Z-Axis
927.62	93.41	0.046827395	0.5	1.122018	0.00058630	0.58630	-2.32	Horiz. Z-Axis

The Power in Watts is obtained by the following Formula Below:

P=[(E*D)^2]/(30*G)

P = Power in Watts

E = The Measured Maximum Field Strength in V/m

G = The Numeric Gain of the Transmitting Antenna over an Isotropic Radiator

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



CHANNEL FREQUENCY SEPARATION DATA SHEET

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400



10 dB Delta 1 [T2] RBW 100 kHz RF Att Ref Lvl 0.01 dB VBW 300 kHz 87 db**y**v 249.97995992 kHz SWT 5 ms Unit db⊿v 87 **V**₁ 74 55 dB 80 **1** 9.97995 70 3 db**y**v--D1 63 60 IN1 **2MA** 50 40 TDS 30 20 10 0 -10 -13 Start 902.14 MHz 126 kHz/ Stop 903.4 MHz 1.JUN.2018 10:32:04 Date:

Channel Frequency Separation

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044



NUMBER OF FREQUENCIES

DATA SHEET

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400





Number of Channels is 58 – 906.12 MHz to 924.12 MHz Band

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044





Number of Channels is 50 – 902.62 MHz to 914.87 MHz Band

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044





Number of Channels is 50 – 914.87 MHz to 927.62 MHz Band

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044



Page E44

TIME OF OCCUPANCY

DATA SHEETS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400





Time of One Pulse – 8.817635 ms Note: Worst Case Mode of low band hop table used, which results in the pulses appearing more frequently.

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044





One Pulse Per 20 Seconds Total Time = 8.817635 ms per 20 seconds Limit = 400 ms per 20 seconds Note: Worst Case Mode of low band hop table used, which results in the pulses appearing more frequently.

> Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044



DUTY CYCLE

DATA SHEETS

Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500 Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400





Time of One Pulse – 8.817635 ms Note: Worst Case Mode of low band hop table used, which results in the pulses appearing more frequently.

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044



Marker 1 [T2] RBW 50 kHz RF Att 10 dB Ref Lvl 30.63 dBVV VBW 200 kHz 87 db**y**v 4.709419 s SWT 10 s Unit db⊿v 87 А 80 70 60 I2D **2MA** 50 40 ~ MALLMMA **ا**ر 30 20 10 0 -10 -13 Center 902.62 MHz 1 s/ 28.JUN.2018 15:59:44 Date:

One pulse per 100 ms worst case Total duty cycle = 8.817635 ms / 100 ms = 8.817635%Note: Worst Case Mode of low band hop table used, which results in the pulses appearing more frequently.

> Brea Division 114 Olinda Drive Brea, CA 92823 (714) 579-0500

Lake Forest Division 20621 Pascal Way Lake Forest, CA 92630 (949) 587-0400 Newbury Park Division 1050 Lawrence Drive Newbury Park, CA 91320 (805) 480-4044