

FCC COMPLIANCE REPORT

Equipment Under Test (EUT) :

Name : TPMS
Model No. : TP2-PC1-RX
FCC ID : UVNTP2-PC1-RX

Standards : FCC Part 15, Subpart B, Class B
ANSI C63.4:2003
CISPR22:2006
CISPR16-2:2005

Date of Receipt : 15 May 2008

Date of Test : 16 May 2008

Date of Issue : 19 May 2008

Test Result :	PASS
---------------	------

In the configuration tested, the EUT complied with the standards specified above.

Remarks :

This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report shall not be reproduced except in full, without the written approval of the laboratory. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Fant

Forest Lee
EMC Technical Manager
SGS Testing Korea Co., Ltd.

Contents

1. General Information	3
1.1 Applicant & Manufacturer Information	3
1.2 General Description of EUT	3
1.3 Details of EUT	3
1.4 Description of Support Units	3
1.5 Cable List	3
1.6 System Configuration	4
1.7 Test Set-Up Configuration	4
1.8 Measurement Procedure	4
1.9 Standards Applicable for Testing	5
1.10 Summary of Results	5
2. Radio Disturbance	6
2.1 Test Results	6
2.2 Frequency Range	6
2.3 Limits Of Conducted And Radiated Emission	6
2.4 Test of Conducted Emission	7
2.4.1 Test Equipments	7
2.4.2 Test Site	7
2.4.3 Operating Environment	7
2.4.4 Measurement Data	7
2.5 Test of Radiated Emission	8
2.5.1 Test Instruments	8
2.5.2 Test Site	8
2.5.3 Operating Environment	8
2.5.4 Measurement Data	8
3. Photographs of Test	9
4. Photographs of Product	10

1. General Information

1.1 Applicant & Manufacturer Information

Applicant : SEETRON. Inc.

Address of Applicant : 201-403, BUCHEON Techno-Park, 192, Yakdae-Dong, Wonmi-Gu, Bucheon-City, 420-733, Korea

Manufacturer : SEETRON. Inc.

1.2 General Description of EUT

Product Name : TPMS

Model No. : TP2-PC1-RX

Serial No. : None

FCC ID : UVNTP2-PC1-RX

1.3 Details of EUT

Tested Power Supply : DC 12 V

Description of Operating : Operate it continually.

1.4 Description of Support Units

Product	Model No.	Serial No.	Manufacturer
Car Battery	GHV-140	N/A	Global Battery Co., Ltd.


1.5 Cable List

Start		END		Cable Spec	
Name	I/O Port	Name	I/O Port	Length	Shield
EUT	DC IN	Cigar Jack or Car Battery	DC OUT	1.9	Unshielded
Cigar Jack	DC IN DC OUT	Car Battery EUT	DC OUT DC IN	1.4 1.9	Unshielded Unshielded
Car Battery	DC OUT	Cigar Jack	DC IN	1.4	Unshielded

1.6 System Configuration

Description	Model	Serial No.	Manufacturer
Display Board	HACO_RX	N/A	SEETRON
Cigar Jack	N/A	N/A	N/A

1.7 Test Set-Up Configuration



1.8 Measurement Procedure

Conducted Emission Testing was performed according ANSI C63.4:2003 in a shielded room with peripherals placed on a table, 0.8m high over a metal floor. It was located more than required distance away from the shielded room wall. Radiated Emission Testing was performed according to ANSI C63.4:2003 at the open field test site. The EUT was placed in a 0.8m high table along with the peripherals. The turn table was separated from the antenna distance 3 meters. Cables were placed in a position to produce maximum emissions as determined by experimentation, and operation mode was selected for maximum. The frequencies and amplitudes of maximum emission were measured at varying azimuths, antenna heights and antenna polarities. Reported are maximized emission levels.

1.9 Standards Applicable for Testing

Table of tests to be carried out under FCC Part 15, Subpart B, CLASS B

Test Standards	Status
FCC Part 15, Subpart B, Class B	Applicable
Deviation from Standard	No Deviation

1.10 Summary of Results

The data collected shows that Model **TP2-PC1-RX** complies with of the FCC Part 15, Subpart B Rules.

The emission level is very lower than the limit by over 20 dB.

Radio Disturbance

2.1 Test Results

	Results
Conducted Emission	N/A
Radiated Emission	PASS

Note : This is power supplied from Car Battery, so, the conducted emission is not performed.

2.2 Frequency Range

Conducted Emission : 150 kHz - 30 MHz

Radiated Emission : 30 MHz - 960 MHz and above 960 MHz

2.3 Limits Of Conducted And Radiated Emission

2.3.1 Limit Of Conducted Emission Of FCC Part 15.107

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi - peak	Average	Quasi - peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

Note : (1) The lower limit shall apply at the transition frequencies.

(2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

(3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected there to, shall not exceed the level of field strengths specified above.

2.3.2 Limit Of Radiated Emission Of FCC Part 15.109

FREQUENCY (MHz)	Class A (at 10m)*	Class B (at 3m)*
	uV/m(dBuV/m)	uV/m(dBuV/m)
30 - 88	90(39)	100(40)
88 - 216	150(43.5)	150(43.5)
216 - 960	210(46.5)	200(46)
Above 960	300(49.0)	500(54)

Note : (1) *Detector Function : Quasi-Peak

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

2.4 Test of Conducted Emission

2.4.1 Test Equipments

Equipment	Model No.	Manufacturer	Date of Calibration
Test Receiver	ESHS 10	Rohde & Schwarz	Sep. 2007
Two-Line V-Network	NNB 41	SCHAFFNER	Sep. 2007
Two-Line V-Network	ENV216	Rohde & Schwarz	Jan. 2008
Shield Room	-	Seoyoung EMC	-

2.4.2 Test Site

Name and address : SGS Testing Korea Co., Ltd.
18-34, Sanbon-dong, Gunpo, Gyeonggi-do, Korea. 435-041

2.4.3 Operating Environment

Temperature : °C Humidity : % RH

Atmospheric Pressure : kPa

2.4.4 Measurement Data

Measurement Bandwidth : 9kHz

Date of Test :

John Oh / Test Engineer

2.5 Test of Radiated Emission

2.5.1 Test Instruments

Description	Model	Manufacturer	Date of Calibration
Amplifier	8447F	H/P	Sep. 2007
Test Receiver	ESVS10	Rohde & Schwarz	Apr. 2008
Bi-Log Antenna	HL562	Rohde & Schwarz	Oct. 2007
Spectrum Analyzer	8593E	HP	Sep. 2007

2.5.2 Test Site

Name and address : SGS Testing Korea Co., Ltd.
18-34, Sanbon-dong, Gunpo, Gyeonggi-do, Korea, 435-041

2.5.3 Operating Environment

Temperature : 24.8 °C Humidity : 32.0 % RH
Atmospheric Pressure : 101.0 kPa

2.5.4 Measurement Data

Measurement Bandwidth : 120 kHz

Date of Test : 16 May 2008

FREQ. (MHz)	LEVEL (dB μ V)	POL (H/V)	*AF (dB)	**CL (dB)	F/S (dB μ V/m)	LIMIT (dB μ V/m)	***MARGIN (dB)
The emission level is very lower than limit by over 20 dB.							

* AF = Antenna Factor. ** CL = Cable Loss


*** Margin=Each Frequency Limit Level(dBuV) + AF - (CL)



John Oh / Test Engineer

3. Photographs of Test

- Front View of Radiated Emission (EUT)



- Front View of Radiated Emission (Cigar Jack)

