

1.1. Test Result of RF Exposure Evaluation

- . Product: HT1100 Handy Terminal
- . Test Item: RF Exposure Evaluation Data
- . Test site: OATSI-SD
- . Test Mode: Normal Operation

1.1.1. Antenna Gain

The maximum Gain is 5.5 dBi.

1.1.2. EUT Operation condition

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

1.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Modulation Standard: IEEE 802.11b

Test Date: April. 04, 2007 Temperature: 23 Humidity: 68%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	17.04	0.036
06	2437	17.02	0.036
11	2462	17.41	0.039

Modulation Standard: IEEE 802.11g

Test Date: April. 04, 2007 Temperature: 23 Humidity: 68%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	15.74	0.026
06	2437	15.88	0.027
11	2462	15.85	0.027

The MPE is calculated as $0.026 \text{ mW / cm}^2 < \text{limit } 1 \text{ mW / cm}^2$. So, RF exposure limit warning or SAR test are not required.

For 2412-2462 MHz, the EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.