

FCC PART 15 SUBPART C TEST REPORT

for

3.7' Rugged PDA

Model No.: P37B

FCC ID: UVZP37B

of

Applicant: ACA Digital Corporation

**Address: 17F, NO. 866-7 Zhongzheng Rd., Zhonghe City,
Taipei county, 235 TAIWAN, R.O.C.**

Tested and Prepared

by


Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1

A2LA Accredited No.: 2732.01

Report No.: W6M20812-9482-C-1



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B

TABLE OF CONTENTS

1	General Information	2
1.1	Notes	2
1.2	Testing laboratory	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	Details of approval holder	3
1.4	Application details	4
1.5	General information of Test item	4
1.6	Test standards	5
2	Technical test	6
2.1	Summary of test results	6
2.2	Test environment	6
2.3	Test Equipment List	7
2.4	General Test Procedure	9
3	Test results (enclosure)	11
3.1	Peak Output Power (transmitter)	12
3.2	Equivalent isotropic radiated power	14
3.3	RF Exposure Compliance Requirements	14
3.4	Transmitter Radiated Emissions in restricted Bands	15
3.5	Spurious emissions (tx)	16
3.6	Carrier Frequency Separation	24
3.7	Number of Hopping Frequencies	25
3.7.1	Pseudorandom Frequency Hopping Sequence	25
3.7.2	Coordination of hopping sequences to other transmitters	25
3.7.3	System Receiver Hopping Capability	25
3.8	Time of Occupancy (Dwell Time)	26
3.9	20dB Bandwidth	28
3.9.1	System Receiver Input Bandwidth	28
3.10	Minimum 6 dB Bandwidth	29
3.11	Band-edge Compliance of RF Emissions	30
3.12	Peak Power Spectral Density	32
3.13	Radiated Emissions from Digital Part	33
3.14	Power Line Conducted Emission	34
Appendix		36



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.


The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services (Taiwan) Co., Ltd.

Tester:

February 10, 2009

Kevin Wang



Date


WTS-Lab. Name

Signature

Technical responsibility for area of testing:

February 10, 2009


Chang Tse-Ming



Date

WTS-Lab. Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company

Worldwide Testing Services (Taiwan) Co., Ltd.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1

1.3 Details of approval holder

Name:

ACA Digital Corporation

Street:

17F, NO. 866-7 Zhongzheng Rd.,

City:

Zhonghe City Taipei county, 235

Country:


Taiwan R.O.C.

Telephone:

+886-2-8228-1121

Fax:

+886-2-2228-9448



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

1.4 Application details

Date of receipt of test item: December 8, 2008
Date of test: from December 9, 2008 to February 6, 2009

1.5 General information of Test item

Type of test item: 3.7' Rugged PDA
Model number: P37B
Multi-listing model number: A37B
Brand name: ACA-Digital
Photos: see Annex

Technical data

Frequency band for WLAN: 2.412 – 2.462 GHz

Frequency (ch Low): 2.412 GHz

Frequency (ch Middle): 2.437 GHz

Frequency (ch High): 2.462 GHz

Frequency band for Bluetooth: 2.402 – 2.480 GHz

Frequency (ch Low): 2.402 GHz

Frequency (ch Middle): 2.441 GHz

Frequency (ch High): 2.480 GHz

Number of Channels: WLAN: 11 channels
Bluetooth: 79 channels

Power supply: Adaptor (I/P: AC 100-240 V / 50-60 Hz / 1.5 A, O/P: 11.0-13.5 Vdc / 3.82-3.11 A)
Battery (7.4V, 1900 mAh, rechargeable Li-ion)

Operation modes: duplex


Modulation Type: WLAN: DSSS / OFDM
Bluetooth: GFSK 、 π / 4DQPSK 、 8DPSK

Antenna Type: 1/2 λ dipole antenna

Antenna gain: 2 dBi

Emission designator: 11b: DSSS: 15M2G1D
11g: OFDM: 16M4W7D
Bluetooth (Normal mode): 962KF7D
Bluetooth (EDR mode): 1M29F1D

Additional information: There are four testing modes in the test report.
Mode A: IEEE 802.11b
Mode B: IEEE 802.11g
Mode C: Bluetooth (Normal mode)
Mode D: Bluetooth (EDR mode)



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Host device: none

Classification:

Fixed Device	<input type="checkbox"/>
Mobile Device (Human Body distance > 20cm)	<input type="checkbox"/>
Portable Device (Human Body distance < 20cm)	<input checked="" type="checkbox"/>
Modular Radio Device	<input type="checkbox"/>

Transmitter

Unom

Mode A (DSSS)

Power (ch 1 or Low): Conducted: 15.80 dBm
Power (ch 6 or Middle): Conducted: 14.40 dBm
Power (ch 11 or High): Conducted: 14.24 dBm

Mode B (OFDM)

Power (ch 1 or Low): Conducted: 17.29 dBm
Power (ch 6 or Middle): Conducted: 16.02 dBm
Power (ch 11 or High): Conducted: 16.56 dBm

Mode C Normal Mode

Power (ch 0 or ch Low): Conducted: -2.04 dBm
Power (ch 39 or ch Middle): Conducted: -2.95 dBm
Power (ch 78 or ch High): Conducted: -2.91 dBm

Mode D EDR Mode


Power (ch 0 or ch Low): Conducted: -0.38 dBm
Power (ch 39 or ch Middle): Conducted: -0.93 dBm
Power (ch 78 or ch High): Conducted: -0.44 dBm

Manufacturer: (if applicable)

Name: ACA Digital Corporation
Street: 17F, NO. 866-7 Zhongzheng Rd.,
City: Zhonghe City Taipei county, 235
Country: Taiwan R.O.C.

1.6 Test standards

Technical standard : FCC RULES PART 15 SUBPART C § 15.247 (2008-07)



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 3 were ascertained in the course of the tests performed.

2.2 Test environment

Temperature: 23 °C

Relative humidity content: 20 ... 75 %


Air pressure: 86 ... 103 kPa

Details of power supply
Adaptor (I/P: AC 100-240 V / 50-60 Hz / 1.5 A,
O/P: 11.0-13.5 Vdc / 3.82-3.11 A)
Battery (7.4V, 1900 mAh, rechargeable Li-ion)

Extreme conditions parameters: test voltage : -- extreme
min : -- V
max : -- V

Measurement Uncertainty:

Measurement item	Uncertainty
Peak Output Power	0.51 dB
Spurious Emissions radiated – Transmitter operating	1.67 dB
Carrier Frequency Separation	2060.94 Hz
Time of Occupancy (Dwell Time)	0.04 ms
20 dB Bandwidth	14.243 kHz
Minimum 6 dB Bandwidth	0.04 ms
Band-edge Compliance of RF Emission	1.52 dBc
Peak Power Spectral Density	0.746 dB
Power Line Conducted Emission	1.77 dB




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2008/9/18	2009/9/17
ETSTW-CE 002	PREREULATOR MODE DC POWER SUPPLY	None	None	None	Function Test	
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V- NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2008/9/15	2009/9/14
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	2008/9/15	2009/9/14
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2008/5/10	2009/5/09
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	Schwarzbeck	2008/9/18	2009/9/17
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2008/7/25	2009/7/24
ETSTW-CE 015	CISPR 22 TWO BALANCED TELECOM PAIRS IMPEDANCE STABILIZATION NETWORK	FCC-TLISN-T8-02	20307	FCC	2008/9/22	2009/9/21
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2008/9/24	2009/9/23
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	2007/10/12	2009/10/11
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2008/10/8	2009/10/7
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2008/9/22	2009/9/21
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2008/9/18	2009/9/17
ETSTW-RE 011	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070165	MOTECH	Function Test	
ETSTW-RE 017	Log-Periodic Antenna	HL025	352886/001	R&S	2008/5/5	2009/5/4
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2008/10/27	2009/10/26
ETSTW-RE 020	MICROWAVE HORN ANTENNA	AT4002A	306915	AR	Function Test	
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	2008/8/27	2009/8/26
ETSTW-RE 028	Log-Periodic DipoleArray Antenna	3148	34429	EMCO	2008/4/23	2009/4/22
ETSTW-RE 029	Biconical Antenna	3109	33524	EMCO	2008/4/23	2009/4/22
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	EMCO	2008/3/26	2009/3/25
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	2008/9/1	2009/8/31
ETSTW-RE 033	WaveRunner 6000A Serise Oscilloscope	WAVERUNNER 6100A	LCRY0604P14508	LeCroy	2008/6/27	2009/6/26
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	2008/9/1	2009/8/31
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2009/1/8	2011/1/7
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2008/5/2	2009/5/1
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2008/5/22	2009/5/21
ETSTW-RE 047	ESA-E SERIES SPECTRUM ANALYZER	E4445A	MY46181369	Agilent	2008/6/26	2009/6/25




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	2008/9/1	2009/8/31
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2007/5/2	2009/5/1
ETSTW-RE 055	SPECTRUM ANALYZER	FSU-26	200074	R&S	2008/7/1	2009/6/30
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	2008/9/1	2009/8/31
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2008/10/28	2009/10/27
ETSTW-RE 105	Match Pad	MDCS1500	None	WOKEN	2008/10/9	2009/10/8
ETSTW-RE 106	Match Pad	MDCS1510	None	WOKEN	2008/10/9	2009/10/8
ETSTW-RE 107	LUMPED ELEMENT POWER DIVIDER	PL2-10	146	MCLI	2008/11/24	2009/11/23
ETSTW-GSM 02	Universal Radio Communication Tester	CMU 200	109439	R&S	2008/9/23	2009/9/22
ETSTW-GSM 23	Power Divider	4901.19.A	None	SUHNER	2008/9/22	2009/9/21



Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient. temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m


The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2003 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by Worldwide Testing Services (Taiwan) Co., Ltd. at the registered open field test site located No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.). The Registration Number: **930600**.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Equivalent radiated Power	15.247(b)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions radiated – Transmitter operating	15.247(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions conducted – Transmitter operating	15.247	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Carrier Frequency Separation	15.247(a) (1)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Number of Hopping Frequencies	15.247(a) (1)(i)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Time of Occupancy (Dwell Time)	15.247(a) (1)(i)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
20 dB Bandwidth	15.247(a) (1)(i)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Minimum 6 dB Bandwidth	15.247(a)(2)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Band-edge Compliance of RF Emission	15.247(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Peak Power Spectral Density	15.247(d)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission from Digital Part	15.109	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Power Line Conducted Emission	15.207(a)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

The follows is intended to leave blank.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Mode A:

Test conditions	Conducted Power		
	Channel Low	Channel Middle	Channel High
	[dBm]	[dBm]	[dBm]
T _{nom} = 23°C V _{nom} = 120 V	15.80	14.40	14.24

Mode B:

Test conditions	Conducted Power		
	Channel Low	Channel Middle	Channel High
	[dBm]	[dBm]	[dBm]
T _{nom} = 23°C V _{nom} = 120 V	17.29	16.02	16.56

Mode C:

Test conditions	Conducted Power		
	Channel Low	Channel Middle	Channel High
	[dBm]	[dBm]	[dBm]
T _{nom} = 23°C V _{nom} = 120 V	-2.04	-2.95	-2.91

Mode D:

Test conditions	Conducted Power		
	Channel Low	Channel Middle	Channel High
	[dBm]	[dBm]	[dBm]
T _{nom} = 23°C V _{nom} = 120 V	-0.38	-0.93	-0.44



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B

Test conditions	Radiated Power		
	Channel Low [dBm]	Channel Middle [dBm]	Channel High [dBm]
T _{nom} = -- °C V _{nom} = -- V	--	--	--

Test conditions T _{nom} = -- °C, V _{nom} = -- V Frequency[MHz]	Signal Field strength TX highest power mode dB μ V/m
--	--
Measurement uncertainty	< 3 dB

Maximum Peak Output Power


Limits:

Frequency MHz	Number of hopping channels			
	≥ 75	≥ 50	49 ≥ 25	74 ≥ 15
902-928		30 dBm	24 dBm	
2400-2483.5 MHz	30 dBm	-		21 dbm
5725-5850 MHz	30 dBm	-		

In case of employing transmitter antennas having antenna gain >dB_i and using fixed point-to point operation consider §15.247 (b)(4).

Test equipment used: ETSTW-RE 055, ETSTW-RE 064

Explanation: See attached diagrams in appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain

$$\begin{aligned} \text{EIRP} &= 17.29 \text{ dBm} + 2 \text{ dBi} \\ &= 19.29 \text{ dBm} \end{aligned}$$

Limit: EIRP = +36 dBm for Antenna gain <6dBi

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 017 ETSTW-RE 021
ETSTW-RE 028 ETSTW-RE 030 ETSTW-RE 043 ETSTW-RE 044

3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{P G}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance


D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	53.58	Peak value
D	dB		
AG	dBi	2	
G		1.6	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.0171	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1,0



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.4 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26500 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency \leq 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency >1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency >1 GHz , RBW:1 MHz , VBW: 10 Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of Digit Transmission Systems:


"If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation."

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time}/ 100\text{ms})$

Note: No duty cycle correction was added to the reading of this EUT.

Explanation: See attached diagrams in Appendix.



Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.5 Spurious emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Marker-Delta-Method" or the „Duty-Cycle Correction Factor“.

Summary table with radiated data of the test plots

Model: P37B	Date: 2009/1/9-2/2							
Mode: 802.11b TX CH1	Temperature: 26 °C							
Polarization: Horizontal	Humidity: 50 %							
Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
368.738	12.02	peak	16.94	28.96	74.00	-45.04	140	150

Frequency (MHz)	Reading (dBuV) Peak Ave.	Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave.	Limit @3m (dBuV/m) Peak Ave.	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)			
4824.000	39.45	---	-1.30	38.15	---	74.00	54.00	-35.85	270	150
7236.000	40.71	---	1.86	42.57	---	74.00	54.00	-31.43	30	150
9648.000	20.42	---	25.06	39.48	---	74.00	54.00	-34.52	240	150
12060.000	19.96	---	29.44	43.40	---	74.00	54.00	-30.60	150	150
14472.000	21.75	---	31.65	41.40	---	74.00	54.00	-32.60	180	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	15.06	peak	16.74	31.80	74.00	-42.20	110	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4824.000	40.13	---	-1.30	38.83	---	74.00	54.00	-35.17	220	150
7236.000	40.72	---	1.86	42.58	---	74.00	54.00	-31.42	180	150
9648.000	19.49	---	25.06	38.55	---	74.00	54.00	-35.45	210	150
12060.000	21.78	---	29.44	45.22	---	74.00	54.00	-28.78	250	150
14472.000	21.92	---	31.65	41.57	---	74.00	54.00	-32.43	120	150

Mode: 802.11b TX CH6 Temperature: 26 °C Engineer: Kevin
Polarization: Horizontal Humidity: 50 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	15.52	peak	17.10	32.62	74.00	-41.38	220	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4874.000	39.24	---	-1.30	37.94	---	74.00	54.00	-36.06	170	150
7331.000	41.22	---	1.86	43.08	---	74.00	54.00	-30.92	160	150
9748.000	20.77	---	24.94	39.71	---	74.00	54.00	-34.29	180	150
12185.000	20.10	---	29.74	43.84	---	74.00	54.00	-30.16	170	150
14622.000	20.37	---	32.14	40.51	---	74.00	54.00	-33.49	210	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	20.33	peak	16.74	37.07	74.00	-36.93	200	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
2437.000	40.86	---	-5.10	35.76	---	74.00	54.00	-38.24	170	150
4874.000	39.17	---	-1.30	37.87	---	74.00	54.00	-36.13	180	150
7331.000	40.78	---	1.86	42.64	---	74.00	54.00	-31.36	120	150
9748.000	19.65	---	24.94	38.59	---	74.00	54.00	-35.41	210	150
12185.000	20.49	---	29.74	44.23	---	74.00	54.00	-29.77	280	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Mode: 802.11b TX CH11 Temperature: 26 °C Engineer: Kevin
Polarization: Horizontal Humidity: 50 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	16.08	peak	17.10	33.18	74.00	-40.82	220	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4924.000	39.40	---	-1.20	38.20	---	74.00	54.00	-35.80	120	150
7386.000	42.07	---	1.97	44.04	---	74.00	54.00	-29.96	110	150
9848.000	21.40	---	25.49	40.89	---	74.00	54.00	-33.11	200	150
12310.000	20.60	---	30.04	44.64	---	74.00	54.00	-29.36	80	150
14772.000	20.60	---	32.56	41.16	---	74.00	54.00	-32.84	100	150


Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Corr.	Peak	Ave.			
361.723	20.46	peak		16.74	37.20	74.00	-36.80	170	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4924.000	39.43	---	-1.20	38.23	---	74.00	54.00	-35.77	210	150
7386.000	42.34	---	1.97	44.31	---	74.00	54.00	-29.69	130	150
9848.000	20.16	---	25.49	39.65	---	74.00	54.00	-34.35	120	150
12310.000	20.22	---	30.04	44.26	---	74.00	54.00	-29.74	100	150
14772.000	21.67	---	32.56	42.23	---	74.00	54.00	-31.77	210	150

Mode: 802.11gTX CH1 Temperature: 26 °C Engineer: Kevin
Polarization: Horizontal Humidity: 50 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	17.74	peak	17.10	34.84	74.00	-39.16	140	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Frequency (MHz)	Reading (dBuV) Peak Ave.	Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave.	Limit @3m (dBuV/m) Peak Ave.	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)			
4824.000	39.79	---	-1.30	38.49	---	74.00	54.00	-35.51	240	150
7236.000	40.38	---	1.86	42.24	---	74.00	54.00	-31.76	310	150
9648.000	20.00	---	25.06	39.06	---	74.00	54.00	-34.94	280	150
12060.000	21.64	---	29.44	45.08	---	74.00	54.00	-28.92	350	150
14472.000	21.62	---	31.65	41.27	---	74.00	54.00	-32.73	340	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	22.26	peak	16.74	39.00	74.00	-35.00	110	150

Frequency (MHz)	Reading (dBuV) Peak Ave.	Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave.	Limit @3m (dBuV/m) Peak Ave.	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)			
4824.000	39.72	---	-1.30	38.42	---	74.00	54.00	-35.58	210	150
7236.000	40.56	---	1.86	42.42	---	74.00	54.00	-31.58	170	150
9648.000	19.57	---	25.06	38.63	---	74.00	54.00	-35.37	210	150
12060.000	20.63	---	29.44	44.07	---	74.00	54.00	-29.93	130	150
14472.000	21.05	---	31.65	40.70	---	74.00	54.00	-33.30	100	150

Mode: 802.11g TX CH6

Temperature: 26

Engineer: Kevin

Polarization: Horizontal

Humidity: 50


%

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	19.06	peak	17.10	36.16	74.00	-37.84	210	150

Frequency (MHz)	Reading (dBuV) Peak Ave.	Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave.	Limit @3m (dBuV/m) Peak Ave.	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)			
4874.000	39.54	---	-1.30	38.24	---	74.00	54.00	-35.76	210	150
7331.000	41.52	---	1.86	43.38	---	74.00	54.00	-30.62	250	150
9748.000	20.15	---	24.94	39.09	---	74.00	54.00	-34.91	20	150
12185.000	19.80	---	29.74	43.54	---	74.00	54.00	-30.46	360	150
14622.000	20.61	---	32.14	40.75	---	74.00	54.00	-33.25	210	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	23.03	peak	16.74	39.77	74.00	-34.23	340	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4874.000	39.81	---	-1.30	38.51	---	74.00	54.00	-35.49	280	150
7331.000	41.84	---	1.86	43.70	---	74.00	54.00	-30.30	350	150
9748.000	20.95	---	24.94	39.89	---	74.00	54.00	-34.11	350	150
12185.000	21.77	---	29.74	45.51	---	74.00	54.00	-28.49	320	150
14622.000	20.69	---	32.14	40.83	---	74.00	54.00	-33.17	210	150

Mode: 802.11g TX CH11

Temperature: 26 °C

Engineer: Kevin

Polarization: Horizontal

Humidity: 50 %


Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	19.58	peak	17.10	36.68	74.00	-37.32	250	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4924.000	39.57	---	-1.20	38.37	---	74.00	54.00	-35.63	210	150
7386.000	41.91	---	1.97	43.88	---	74.00	54.00	-30.12	220	150
9848.000	19.80	---	25.49	39.29	---	74.00	54.00	-34.71	210	150
12310.000	21.61	---	30.04	45.65	---	74.00	54.00	-28.35	350	150
14772.000	21.84	---	32.56	42.40	---	74.00	54.00	-31.60	210	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	22.30	peak	16.74	39.04	74.00	-34.96	220	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4924.000	39.17	---	-1.20	37.97	---	74.00	54.00	-36.03	310	150
7386.000	41.52	---	1.97	43.49	---	74.00	54.00	-30.51	40	150
9848.000	20.13	---	25.49	39.62	---	74.00	54.00	-34.38	220	150
12310.000	21.15	---	30.04	45.19	---	74.00	54.00	-28.81	350	150
14772.000	21.43	---	32.56	41.99	---	74.00	54.00	-32.01	120	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Mode: Bluetooth TX CH0 Temperature: 26 °C Engineer: Kevin
Polarization: Horizontal Humidity: 50 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
152.826	26.26	peak	15.41	41.67	74.00	-32.33	210	150
415.030	25.87	peak	18.10	43.97	74.00	-30.03	140	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4801.603	54.48	47.96	-1.30	53.18	46.66	74.00	54.00	-7.34	210	150
7206.000	42.17	---	1.89	44.06	---	74.00	54.00	-29.94	250	150
9608.000	20.34	---	25.34	39.68	---	74.00	54.00	-34.32	210	150
12010.000	19.73	---	29.32	43.05	---	74.00	54.00	-30.95	250	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
212.345	28.72	peak	12.38	41.10	74.00	-32.90	210	150
624.048	22.68	peak	22.29	44.97	74.00	-29.03	155	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4803.985	55.01	41.77	-1.30	53.71	40.47	74.00	54.00	-13.53	210	150
7206.000	42.03	---	1.89	43.92	---	74.00	54.00	-30.08	220	150
9608.000	20.91	---	25.34	40.25	---	74.00	54.00	-33.75	170	150
12010.000	21.39	---	29.32	44.71	---	74.00	54.00	-29.29	160	150

Mode: Bluetooth TX CH39 Temperature: 26 °C Engineer: Kevin
Polarization: Horizontal Humidity: 50 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
153.908	25.03	peak	15.42	40.45	74.00	-33.55	210	150
415.030	25.84	peak	18.10	43.94	74.00	-30.06	170	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4881.764	54.00	---	-1.30	52.70	---	74.00	54.00	-21.30	280	150
7323.000	41.15	---	1.85	43.00	---	74.00	54.00	-31.00	260	150
9764.000	20.14	---	25.02	39.16	---	74.00	54.00	-34.84	210	150
12205.000	19.48	---	29.79	43.27	---	74.00	54.00	-30.73	250	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
211.263	29.02	peak	12.36	41.38	74.00	-32.62	210	150
624.048	21.80	peak	22.29	44.09	74.00	-29.91	210	150

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak Ave.	Corr.	Peak Ave.	Peak Ave.			
4881.764	56.86	42.03	-1.30	55.56	40.73	74.00	54.00
7323.000	41.25	---	1.85	43.10	---	74.00	54.00
9764.000	19.91	---	25.02	38.93	---	74.00	54.00
12205.000	19.92	---	29.79	43.71	---	74.00	54.00

Mode: Bluetooth TX CH78
Temperature: 26 °C
Polarization: Horizontal
Humidity: 50 %
Engineer: Kevin


Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
153.908	25.76	peak	15.42	41.18	74.00	-32.82	200	150
415.030	25.19	peak	18.10	43.29	74.00	-30.71	320	150

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak Ave.	Corr.	Peak Ave.	Peak Ave.			
4961.924	57.25	42.83	-1.05	56.20	41.78	74.00	54.00
7440.000	42.43	---	1.80	44.23	---	74.00	54.00
9920.000	19.58	---	26.04	39.62	---	74.00	54.00
12400.000	19.91	---	30.26	44.17	---	74.00	54.00

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
213.968	28.23	peak	12.41	40.64	74.00	-33.36	230	150
624.048	21.48	peak	22.29	43.77	74.00	-30.23	280	150

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak Ave.	Corr.	Peak Ave.	Peak Ave.			
4953.908	56.51	42.52	-1.08	55.43	41.44	74.00	54.00
7440.000	42.55	---	1.80	44.35	---	74.00	54.00
9920.000	20.27	---	26.04	40.31	---	74.00	54.00
12400.000	20.69	---	30.26	44.95	---	74.00	54.00



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B


Note

1. Correction Factor = Antenna factor + Cable loss - Preamplifier
2. The formula of measured value as: Test Result = Reading + Correction Factor
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. See the attached diagram as appendix.

All other not noted test plots do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 017, ETSTW-RE 018,
ETSTW-RE 021, ETSTW-RE 028, ETSTW-RE 029, ETSTW-RE 030,
ETSTW-RE 042, ETSTW-RE 043, ETSTW-RE 064



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.6 Carrier Frequency Separation

Carrier Frequency Separation was measured with modulation (declared by manufacturer).

According to FCC rules part 15 subpart C §15.247 frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater.

Mode C and Mode D:

Test conditions	Channel Separation	
	Channel 0	Channel 0+1
T _{nom} = 23°C V _{nom} = 120 V		1000 kHz

Test conditions	Channel Separation	
	Channel 39	Channel 39+1
T _{nom} = 23°C V _{nom} = 120 V		1006.410256 kHz

Test conditions	Channel Separation	
	Channel 78	Channel 78+1
T _{nom} = 23°C V _{nom} = 120 V		1000 kHz

Limits:

Frequency Range MHz	Limits	
	20 dB bandwidth < 25 kHz	20 dB bandwidth > 25 kHz
902-928	25 kHz	20 dB bandwidth
2400-2483.5	25 kHz	20 dB bandwidth
5725-5850.0	25 kHz	20 dB bandwidth

Test equipment used: ETSTW-RE 055, ETSTW-RE 064

Explanation: This test is not applicable for Mode A and Mode B because these two modes are not FHSS modulation. See attached diagrams in appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.7 Number of Hopping Frequencies

According to FCC rules part 15 subpart C §15.247 frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies. Frequency hopping systems in 5725-5850 MHz bands shall use least 75 hopping frequencies.

For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies; if the 20dB bandwidth of the hopping channel 250 kHz or greater, the system shall use at least 25 hopping frequencies.

Mode C and Mode D:

Test conditions	Operating Mode	Number of Channels
$T_{nom}= 23^{\circ}C$	$V_{nom}= 120 V$	normal transmitting

Limits:

Frequency Range MHz	Limit	
	20dB Bandwidth	Number of Channels
902-928 MHz	Bandwidth < 250 kHz	≥ 50
	Bandwidth ≥ 250 kHz	≥ 25
2400-2483.5	not defined	15
5725-5850.0 MHz	1 MHz	75

Test equipment used: ETSTW-RE 055, ETSTW-RE 064

Explanation: This test is not applicable for Mode A and Mode B because these two modes are not FHSS modulation. See attached diagrams in appendix.

3.7.1 Pseudorandom Frequency Hopping Sequence

The generation of the hopping sequence is determined by the Bluetooth cord specification and complies with the FCC requirements.

3.7.2 Coordination of hopping sequences to other transmitters

According to the Bluetooth core specification V1.1 such a coordination is not possible. During scatternet function only one of the two hopping sequences will be used at a definite moment.

3.7.3 System Receiver Hopping Capability

According to the Bluetooth core specification. The system receivers shift frequencies in synchronization with the transmitted signals.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.8 Time of Occupancy (Dwell Time)

Frequency hopping systems operating in the 5725-5850 MHz band shall use an average time of occupancy on any frequency not greater than 0.4 seconds within a 30 second period.

In 2400-2483,5 MHz band the average time of occupancy on any channel shall not be greater than 0,4 seconds multiplied by the number of hopping channels employed.


For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the average time of occupancy on any frequency shall not greater than 0.4 seconds within a 20 second period; if the 20dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

Mode C and Mode D:

Test conditions	Operating mode	Measurement period	Time of Occupancy
$T_{\text{nom}} = 23^{\circ}\text{C}$ $V_{\text{nom}} = 120 \text{ V}$ Channel 0	normal transmitting-DH 1	31.6 s	147.52 ms
	normal transmitting-DH 3	31.6 s	275.84 ms
	normal transmitting-DH 5	31.6 s	321.53 ms

Test conditions	Operating mode	Measurement period	Time of Occupancy
$T_{\text{nom}} = 23^{\circ}\text{C}$ $V_{\text{nom}} = 120 \text{ V}$ Channel 39	normal transmitting-DH 1	31.6 s	147.52 ms
	normal transmitting-DH 3	31.6 s	274.88 ms
	normal transmitting-DH 5	31.6 s	327.14 ms

Test conditions	Operating mode	Measurement period	Time of Occupancy
$T_{\text{nom}} = 23^{\circ}\text{C}$ $V_{\text{nom}} = 120 \text{ V}$ Channel 78	normal transmitting-DH 1	31.6 s	127.04 ms
	normal transmitting-DH 3	31.6 s	274.88 ms
	normal transmitting-DH 5	31.6 s	327.14 ms



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B

Limits and measurement periods:

Frequency MHz	Number of channels	Measurement Period	Limit
902 – 928	≥ 50	20 s	0,4 s
	$49 \geq 25$	10 s	0,4 s
2400 – 2483,5	≥ 15	0,4 s * number of used channels	0,4 s
5725- 5850	≥ 75	30 s	0,4s

Test equipment used: ETSTW-RE 055, ETSTW-RE 064

Explanation: This test is not applicable for Mode A and Mode B because these two modes are not FHSS modulation. See attached diagrams in appendix, which show the On-time and the number of counted events during the measurement period



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.9 20dB Bandwidth

Frequency hopping systems operating in the 5725-5850 MHz bands shall use a maximum 20dB bandwidth of 1 MHz.

The 20dB bandwidth is measured on the lowest, middle and highest hopping channel.

For frequency hopping systems operating in the 902-928 MHz band the maximum 20dB bandwidth of the hopping channel is 500 kHz.

Mode C:

Test conditions	20 dB Bandwidth		
	Channel Low	Channel Middle	Channel High
T _{nom} = 23°C V _{nom} = 120 V	961.538461538 kHz	961.538461538 kHz	955.128205128 kHz

Mode D:

Test conditions	20 dB Bandwidth		
	Channel Low	Channel Middle	Channel High
T _{nom} = 23°C V _{nom} = 120 V	1.294871795 MHz	1.282051282 MHz	1.282051282 MHz

Limits:


Frequency Range / MHz	Limit
902-928	≤ 500 kHz
2400-2483.5	not defined
5725-5850	≤ 1 MHz

Test equipment used: ETSTW-RE 055 ETSTW-RE 064

Explanation: This test is not applicable for Mode A and Mode B because these two modes are not FHSS modulation. See attached diagrams in appendix.

3.9.1 System Receiver Input Bandwidth

It is determined in the Bluetooth core specification. The value matches to the bandwidth of transmitter signal.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.10 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission.

The 6 dB bandwidth is the frequency difference between the two markers.

Mode A:

Test conditions		6 dB Bandwidth		
		Channel 1	Channel 6	Channel 11
T _{nom} = 23°C	V _{nom} = 120 V	10.160256410 MHz	10.160256410 MHz	10.192307692 MHz

Mode B:


Test conditions		6 dB Bandwidth		
		Channel 1	Channel 6	Channel 11
T _{nom} = 23°C	V _{nom} = 120 V	16.570512821 MHz	16.570512821 MHz	16.538461538 MHz

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-RE 055

Explanation: This test is not applicable for Mode C and Mode D because these two modes are not DSSS / OFDM modulation. See attached diagrams in appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.11 Band-edge Compliance of RF Emissions

According to FCC rules part 15 subpart C §15.247(c) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

Mode A:

Test conditions		Attenuation at or outside band-edges		
		Lower Band-edge	Upper Band-edge	
T _{nom}	= 23°C	V _{nom} = 120 V	36.05 dB	33.76 dB

Mode B:

Test conditions		Attenuation at or outside band-edges		
		Lower Band-edge	Upper Band-edge	
T _{nom}	= 23°C	V _{nom} = 120 V	31.25 dB	32.70 dB

Mode C:

Test conditions		Attenuation at or outside band-edges		
		Single Frequency		
		Lower Band-edge	Upper Band-edge	
T _{nom}	= 23°C	V _{nom} = 120 V	38.76 dB	42.79 dB

Test conditions		Attenuation at or outside band-edges		
		Hopping Frequency		
		Lower Band-edge	Upper Band-edge	
T _{nom}	= 23°C	V _{nom} = 120 V	39.01 dB	42.79 dB



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B

Mode D:

Test conditions	Attenuation at or outside band-edges	
	Single Frequency	
	Lower Band-edge	Upper Band-edge
T _{nom} = 23°C	V _{nom} = 120 V	36.15 dB
		35.75 dB


Test conditions	Attenuation at or outside band-edges	
	Hopping Frequency	
	Lower Band-edge	Upper Band-edge
T _{nom} = 23°C	V _{nom} = 120 V	36.08 dB
		35.75 dB

Limits:

Frequency Range / MHz	Limit
902 –928	
2400 – 2483.5	- 20 dB
5725 - 5850	

Test equipment used: ETSTW-RE 055

Explanation: See attached diagrams in appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.12 Peak Power Spectral Density

Peak Power Spectral density is measured at low, middle and high channel.

The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.

Mode A:

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel 1 [dBm]	Channel 6 [dBm]	Channel 11 [dBm]
T _{nom} = 23°C	V _{nom} = 120 V	-15.76	-13.10	-18.01

Mode B:


Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel 1 [dBm]	Channel 6 [dBm]	Channel 11 [dBm]
T _{nom} = 23°C	V _{nom} = 120 V	-16.31	-17.91	-18.53

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483,5	8
5725-5850	8

Test equipment used: ETSTW-RE 055

Explanation: This test is not applicable for Mode C and Mode D because these two modes are not DSSS / OFDM modulation. See attached diagrams in appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.13 Radiated Emissions from Digital Part

FCC Rule: 15.109

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 017, ETSTW-RE 028, ETSTW-RE 029, ETSTW-RE 030, ETSTW-RE 042, ETSTW-RE 043, ETSTW-RE 064

Explanation: The test results are listed in the separated test report no. W6M20812-9482-P-15B.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

3.14 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Frequency	Level (dB μ V)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

Model: P37B Date: 2008/12/9
Mode: Temperture: 24 °C Engineer:
Polarization: N Humidity: 50 % Kevin


Frequency (MHz)	Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB)
	QP	Ave.	Corr.	QP	Ave.	QP	Ave.	
0.1655	18.65	16.10	10.15	28.80	26.25	65.18	55.18	-28.93
0.5950	19.23	17.30	10.16	29.39	27.46	56.00	46.00	-18.54
0.8600	18.73	15.96	10.12	28.85	26.08	56.00	46.00	-19.92
2.9150	20.80	14.70	10.06	30.86	24.76	56.00	46.00	-21.24
12.2222	22.20	19.20	10.48	32.68	29.68	60.00	50.00	-20.32
25.9444	23.10	20.90	10.61	33.71	31.51	60.00	50.00	-18.49

Polarization: L1

Frequency (MHz)	Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB)
	QP	Ave.	Corr.	QP	Ave.	QP	Ave.	
0.1547	21.24	19.10	10.18	31.42	29.28	65.74	55.74	-26.46
0.4020	20.10	18.20	10.05	30.15	28.25	57.81	47.81	-19.56
1.8650	18.00	10.60	10.07	28.07	20.67	56.00	46.00	-25.33
3.3300	20.30	11.10	10.09	30.39	21.19	56.00	46.00	-24.81
11.9167	22.20	19.40	10.49	32.69	29.89	60.00	50.00	-20.11
27.9722	22.40	19.40	10.63	33.03	30.03	60.00	50.00	-19.97

Note:

- 1. The formula of measured value as: Test Result = Reading + Correction Factor**
- 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss**
- 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average**
- 4. All not in the table noted test results are more than 20 dB below the relevant limits.**
- 5. See attached diagrams in Appendix.**



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001 ETSTW-CE 003 ETSTW-CE 004 ETSTW-CE 006 ETSTW-RE 064



Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B

Appendix

Measurement diagrams



1. Peak Output Power
2. Spurious Emissions radiated
3. Carrier Frequency Separation
4. Number of Hopping Frequencies
5. Time of Occupancy (Dwell Time)
6. 20dB Bandwidth
7. Minimum 6dB Bandwidth
8. Band-edge Compliance of RF Conducted Emissions
9. Peak Power Spectral Density
10. Power Line Conducted Emission

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Peak Output Power


WLAN Mode (Mode A)



MAX OUTPUT POWER 802.11b CH6


Date: 5.FEB.2009 07:55:13

Registration number: W6M20812-9482-C-1
 FCC ID: UVZP37B




MAX OUTPUT POWER 802.11b CH11
 Date: 5.FEB.2009 07:55:52

WLAN Mode (Mode B)





MAX OUTPUT POWER 802.11g CH1
 Date: 5.FEB.2009 08:01:13



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B





MAX OUTPUT POWER 802.11g CH11

Date: 5.FEB.2009 08:02:34

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Bluetooth Mode (Mode C)




MAX OUTPUT POWER CH39

Date: 10.JAN.2009 13:19:47


Registration number: W6M20812-9482-C-1
 FCC ID: UVZP37B



Registration number: W6M20812-9482-C-1
 FCC ID: UVZP37B



MAX OUTPUT POWER CH39 EDR MODE
 Date: 12.JAN.2009 08:03:31



MAX OUTPUT POWER CH78 EDR MODE
 Date: 12.JAN.2009 08:04:10


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Spurious Emissions radiated

WLAN Mode (Mode A)_ CH 1

Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

WLAN Mode (Mode A)_ CH 6

Antenna Polarization H

82.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B

Antenna Polarization V



Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.



Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

WLAN Mode (Mode A)_ CH 11

Antenna Polarization H


82.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B


Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B


WLAN Mode (Mode B)_ CH 1

Antenna Polarization H

82.0 dBuV/m



82.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Antenna Polarization V







Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B





Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

WLAN Mode (Mode B)_ CH 6

Antenna Polarization H

82.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

WLAN Mode (Mode B)_ CH 11

Antenna Polarization H

82.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B


Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Bluetooth Mode_ CH 0

Antenna Polarization H


82.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B





Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B


Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Bluetooth Mode_ CH 39

Antenna Polarization H


82.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B





Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B


Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B




Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.



Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Bluetooth Mode_ CH 78

Antenna Polarization H

82.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:


1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B





Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:



1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B


Carrier Frequency Separation Bluetooth Mode



FREQUENCY SEPARATION CH0
Date: 10.JAN.2009 15:35:01




FREQUENCY SEPARATION CH39
Date: 10.JAN.2009 15:33:28



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B



FREQUENCY SEPARATION CH78
Date: 10.JAN.2009 15:31:43


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B

Number of Hopping Frequencies Bluetooth Mode



NUMBER OF HOPPING CHO-37
Date: 10.JAN.2009 13:09:17




NUMBER OF HOPPING CH37-78
Date: 10.JAN.2009 13:14:29

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B

Time of Occupancy (Dwell Time) Bluetooth Mode




DELL TIME CH0 DH1(0.461ms * 320events = 147.52ms)

Date: 10.JAN.2009 15:49:20




DELL TIME CH0 DH3(1.724ms * 160events = 275.84ms)

Date: 10.JAN.2009 15:51:52




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B






DELL TIME CH0 DH5(2.923ms * 110events = 321.53ms)
Date: 10.JAN.2009 15:55:22



DELL TIME CH39 DH1(0.461ms * 320events = 147.52ms)
Date: 10.JAN.2009 16:00:32



Registration number: W6M20812-9482-C-1
 FCC ID: UVZP37B






Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1
FCC ID: UVZP37B




DELL TIME CH78 DH5(2.974ms * 110events = 327.14ms)
Date: 10.JAN.2009 16:05:39


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B


20dB Bandwidth Bluetooth Mode



20DB BANDWIDTH CH0
Date: 10.JAN.2009 15:18:20




20DB BANDWIDTH CH39
Date: 10.JAN.2009 15:19:16



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



20DB BANDWIDTH CH78

Date: 10.JAN.2009 15:19:59




20DB BANDWIDTH CH0 EDR MODE

Date: 12.JAN.2009 07:28:57


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



20DB BANDWIDTH CH39 EDR MODE

Date: 12.JAN.2009 07:30:20



20DB BANDWIDTH CH78 EDR MODE


Date: 12.JAN.2009 07:31:17

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B


Minimum 6dB Bandwidth

WLAN Mode



6DB BANDWIDTH 802.11b CH1

Date: 16.JAN.2009 15:16:49




6DB BANDWIDTH 802.11b CH6

Date: 16.JAN.2009 15:20:13


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B




6DB BANDWIDTH 802.11b CH11

Date: 16.JAN.2009 15:22:04



6DB BANDWIDTH 802.11g CH1


Date: 16.JAN.2009 15:29:15



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



6DB BANDWIDTH 802.11g CH6

Date: 16.JAN.2009 15:27:14




6DB BANDWIDTH 802.11g CH11

Date: 16.JAN.2009 15:25:43

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B

Band-edge Compliance of RF Conducted Emissions WLAN Mode



FREQUENCY RANGE 802.11b CH1

Date: 17.JAN.2009 07:27:56




FREQUENCY RANGE 802.11b CH11

Date: 17.JAN.2009 07:32:18


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



FREQUENCY RANGE 802.11g CH1

Date: 17.JAN.2009 07:43:52





FREQUENCY RANGE 802.11g CH11

Date: 17.JAN.2009 07:46:13

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B

Bluetooth Mode



RF Spectrum Analysis (BANDEDGE CH78)


Date: 10.JAN.2009 13:35:18



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



BANDEDGE CHO HOPPING MODE

Date: 10.JAN.2009 13:42:24



BANDEDGE CH78 HOPPING MODE



Date: 10.JAN.2009 13:39:23




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B




BANDEDGE CH78 EDR MODE
Date: 12.JAN.2009 07:41:46



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



BANDEDGE CH0 EDR HOPPING MODE

Date: 12.JAN.2009 07:39:38




BANDEDGE CH78 EDR HOPPING MODE

Date: 12.JAN.2009 07:46:09

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B

Peak Power Spectral Density WLAN Mode




POWER DENSITY 802.11b CH1

Date: 17.JAN.2009 07:54:52



POWER DENSITY 802.11b CH6


Date: 17.JAN.2009 08:01:15



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B




POWER DENSITY 802.11b CH11

Date: 17.JAN.2009 08:10:47



POWER DENSITY 802.11g CH1


Date: 17.JAN.2009 08:39:33



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M20812-9482-C-1

FCC ID: UVZP37B



POWER DENSITY 802.11g CH6

Date: 17.JAN.2009 08:34:23



POWER DENSITY 802.11g CH11


Date: 17.JAN.2009 08:19:35

Registration number: W6M20812-9482-C-1


FCC ID: UVZP37B

Power Line Conducted Emission

LISN N



LISN L1



Up Line: QP Limit Line

Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of AC conducted test data of this test report.