

FCC PART 15 SUBPART C TEST REPORT

for

3.7" Rugged PDA

Model No.: P37B

FCC ID: UVZP37BW

of

Applicant: ACA Digital Corporation

**Address: 17F, NO. 866-7 Zhongzheng Rd., Zhonghe City,
Taipei county, 235 TAIWAN, R.O.C.**

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1

A2LA Accredited No.: 2732.01



Report No.: W6D20909-10102-C-2

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2
FCC ID: UVZP37BW

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	2
1.1	Notes	2
1.2	Testing laboratory	3
1.2.1	<i>Location</i>	3
1.2.2	<i>Details of accreditation status</i>	3
1.3	Details of approval holder	3
1.4	Application details	4
1.5	General information of Test item.....	4
1.6	Test standards	5
2	TECHNICAL TEST	6
2.1	Summary of test results	6
2.2	Test environment	6
2.3	Test Equipment List	7
2.4	General Test Procedure	9
3	TEST RESULTS (ENCLOSURE)	11
3.1	Peak Output Power (transmitter)	12
3.2	Equivalent isotropic radiated power	14
3.3	RF Exposure Compliance Requirements.....	14
3.4	Transmitter Radiated Emissions in restricted Bands	15
3.5	Spurious emissions (tx)	16
3.6	Radiated Emission on the band edge	22
3.7	Minimum 6 dB Bandwidth	23
3.8	Peak Power Spectral Density	24
3.9	Radiated Emissions from Digital Part.....	25
3.10	Power Line Conducted Emission.....	26
Appendix	28



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services (Taiwan) Co., Ltd.

Tester:

October 1, 2009

Kevin Wang

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

October 1, 2009

Chang Tse-Ming

Date

WTS-Lab.

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company

Worldwide Testing Services (Taiwan) Co., Ltd.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1



1.3 Details of approval holder

Name:

ACA Digital Corporation

Street:

17F, NO. 866-7 Zhongzheng Rd.,

City:

Zhonghe City Taipei county, 235

Country:

Taiwan R.O.C.

Telephone:

+886-2-8228-1121

Fax:

+886-2-2228-9448



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

1.4 Application details

Date of receipt of test item: ./.
Date of test: from December 9, 2008 to February 6, 2009

1.5 General information of Test item

Type of test item: 3.7" Rugged PDA
Model number: P37B
Multi-listing model number: ./.
Brand name: ACA-Digital
Photos: see Annex

Technical data

Frequency band for WLAN: 2.412 – 2.462 GHz
Frequency (ch Low): 2.412 GHz
Frequency (ch Middle): 2.437 GHz
Frequency (ch High): 2.462 GHz

Frequency band for Bluetooth: 2.402 – 2.480 GHz
Frequency (ch Low): 2.402 GHz
Frequency (ch Middle): 2.441 GHz
Frequency (ch High): 2.480 GHz

Number of Channels: WLAN: 11 channels
Bluetooth: 79 channels

Power supply: Adaptor (I/P: AC 100-240 V / 50-60 Hz / 1.5 A,
O/P: 11.0-13.5 Vdc / 3.82-3.11 A)
Battery (7.4V, 1900 mAh, rechargeable Li-ion)

Operation modes: duplex

Modulation Type: WLAN: DSSS / OFDM
Bluetooth: GFSK 、 $\pi/4$ DQPSK 、 8DPSK

Antenna Type: 1/2 λ dipole antenna

Antenna gain: 2 dBi

Emission designator: 11b: DSSS: 15M2G1D
11g: OFDM: 16M4W7D
Bluetooth (Normal mode): 962KF7D
Bluetooth (EDR mode): 1M29F1D

Additional information: There are two testing modes in the test report.
Mode A: IEEE 802.11b
Mode B: IEEE 802.11g

For Bluetooth test results, please refer to test report number: W6D20909-10102-C-1.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Host device: none

Classification:

Fixed Device	<input type="checkbox"/>
Mobile Device (Human Body distance > 20cm)	<input type="checkbox"/>
Portable Device (Human Body distance < 20cm)	<input checked="" type="checkbox"/>
Modular Radio Device	<input type="checkbox"/>

Transmitter Unom

Mode A (DSSS)

Power (ch 1 or Low): Conducted: 15.80 dBm

Power (ch 6 or Middle): Conducted: 14.40 dBm

Power (ch 11 or High): Conducted: 14.24 dBm

Mode B (OFDM)

Power (ch 1 or Low): Conducted: 17.29 dBm

Power (ch 6 or Middle): Conducted: 16.02 dBm

Power (ch 11 or High): Conducted: 16.56 dBm

Manufacturer: (if applicable)

Name: ACA Digital Corporation
Street: 17F, NO. 866-7 Zhongzheng Rd.,
City: Zhonghe City Taipei county, 235
Country: Taiwan R.O.C.

1.6 Test standards

Technical standard : FCC RULES PART 15 SUBPART C § 15.247 (2008-07)



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 3 were ascertained in the course of the tests performed.

2.2 Test environment

Temperature: 23 °C

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Details of power supply Adaptor (I/P: AC 100-240 V / 50-60 Hz / 1.5 A, O/P: 11.0-13.5 Vdc / 3.82-3.11 A)
Battery (7.4V, 1900 mAh, rechargeable Li-ion)

Extreme conditions parameters: test voltage : -- extreme
min : -- V
max : -- V

Measurement Uncertainty:

Measurement item	Uncertainty
Peak Output Power	0.51 dB
Spurious Emissions radiated – Transmitter operating	1.67 dB
Minimum 6 dB Bandwidth	14.243 kHz
Band edge	1.52 dBc
Peak Power Spectral Density	0.746 dB
Power Line Conducted Emission	1.77 dB



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2008/9/18	2009/9/17
ETSTW-CE 002	PREREULATOR MODE DC POWER SUPPLY	None	None	None	Function Test	
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V- NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2008/9/15	2009/9/14
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	2008/9/15	2009/9/14
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2008/5/10	2009/5/09
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	Schwarzbeck	2008/9/18	2009/9/17
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2008/7/25	2009/7/24
ETSTW-CE 015	CISPR 22 TWO BALANCED TELECOM PAIRS IMPEDANCE STABILIZATION NETWORK	FCC-TLISN-T8-02	20307	FCC	2008/9/22	2009/9/21
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2008/9/24	2009/9/23
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	2007/10/12	2009/10/11
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2008/10/8	2009/10/7
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2008/9/22	2009/9/21
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2008/9/18	2009/9/17
ETSTW-RE 011	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070165	MOTECH	Function Test	
ETSTW-RE 017	Log-Periodic Antenna	HL025	352886/001	R&S	2008/5/5	2009/5/4
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2008/10/27	2009/10/26
ETSTW-RE 020	MICROWAVE HORN ANTENNA	AT4002A	306915	AR	Function Test	
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	2008/8/27	2009/8/26
ETSTW-RE 028	Log-Periodic DipoleArray Antenna	3148	34429	EMCO	2008/4/23	2009/4/22
ETSTW-RE 029	Biconical Antenna	3109	33524	EMCO	2008/4/23	2009/4/22
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	EMCO	2008/3/26	2009/3/25
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	2008/9/1	2009/8/31
ETSTW-RE 033	WaveRunner 6000A Serise Oscilloscope	WAVERUNNER 6100A	LCRY0604P14508	LeCroy	2008/6/27	2009/6/26
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	2008/9/1	2009/8/31
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2009/1/8	2011/1/7
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2008/5/2	2009/5/1
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2008/5/22	2009/5/21
ETSTW-RE 047	ESA-E SERIES SPECTRUM ANALYZER	E4445A	MY46181369	Agilent	2008/6/26	2009/6/25



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	2008/9/1	2009/8/31
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2007/5/2	2009/5/1
ETSTW-RE 055	SPECTRUM ANALYZER	FSU-26	200074	R&S	2008/7/1	2009/6/30
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	2008/9/1	2009/8/31
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2008/10/28	2009/10/27
ETSTW-RE 105	Match Pad	MDCS1500	None	WOKEN	2008/10/9	2009/10/8
ETSTW-RE 106	Match Pad	MDCS1510	None	WOKEN	2008/10/9	2009/10/8
ETSTW-RE 107	LUMPED ELEMENT POWER DIVIDER	PL2-10	146	MCLI	2008/11/24	2009/11/23
ETSTW-GSM 02	Universal Radio Communication Tester	CMU 200	109439	R&S	2008/9/23	2009/9/22
ETSTW-GSM 23	Power Divider	4901.19.A	None	SUHNER	2008/9/22	2009/9/21



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

$$\begin{array}{ll} \text{Freq (MHz)} & \text{METER READING + ACF + CABLE LOSS (to the receiver)} = \text{FS} \\ 33 & 20 \text{ dB}\mu\text{V} + 10.36 \text{ dB} + 6 \text{ dB} = 36.36 \text{ dB}\mu\text{V/m} @3\text{m} \end{array}$$

The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2003 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by Worldwide Testing Services (Taiwan) Co., Ltd. at the registered open field test site located No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.). The Registration Number: **930600**.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)(3)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Equivalent radiated Power	15.247(b)(3)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions radiated – Transmitter operating	15.247(c): 15.209	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Band Edge Measurement	15.247(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Minimum 6 dB Bandwidth	15.247(a)(2)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Peak Power Spectral Density	15.247(d)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission from Digital Part	15.109	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Power Line Conducted Emission	15.207	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

The follows is intended to leave blank.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Mode A:

Test conditions	Conducted Power		
	Channel Low [dBm]	Channel Middle [dBm]	Channel High [dBm]
T _{nom} = 23°C V _{nom} = 120 V	15.80	14.40	14.24

Mode B:

Test conditions	Conducted Power		
	Channel Low [dBm]	Channel Middle [dBm]	Channel High [dBm]
T _{nom} = 23°C V _{nom} = 120 V	17.29	16.02	16.56

Test conditions	Radiated Power		
	Channel Low [dBm]	Channel Middle [dBm]	Channel High [dBm]
T _{nom} = -- °C V _{nom} = -- V	--	--	--

Test conditions T _{nom} = -- °C, V _{nom} = -- V Frequency[MHz]	Signal Field strength TX highest power mode dB μ V/m
--	--
Measurement uncertainty	< 3 dB



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2
FCC ID: UVZP37BW

Maximum Peak Output Power

Limits:

Frequency MHz	Number of hopping channels			
	≥ 75	≥ 50	$49 \geq 25$	$74 \geq 15$
902-928		30 dBm	24 dBm	
2400-2483.5 MHz	30 dBm	-		21 dbm
5725-5850 MHz	30 dBm	-		

In case of employing transmitter antennas having antenna gain $> \text{dBi}$ and using fixed point-to point operation consider §15.247 (b)(4).

Test equipment used: ETSTW-RE 055, ETSTW-RE 064

Explanation: See attached diagrams in appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain

EIRP = 17.29 dBm + 2 dBi

= 19.29 dBm

Limit: EIRP = +36 dBm for Antenna gain <6dBi

Test equipment used: ETSTW-RE 003 ETSTW-RE 004 ETSTW-RE 017 ETSTW-RE 021
ETSTW-RE 028 ETSTW-RE 030 ETSTW-RE 043 ETSTW-RE 044

3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{P G}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	53.58	Peak value
D	dB		
AG	dBi	2	
G		1.6	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.0171	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1,0



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3.4 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26500 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency \leq 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency >1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency >1 GHz , RBW:1 MHz , VBW: 10 Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of Digit Transmission Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time} / 100\text{ms})$

Note: No duty cycle correction was added to the reading of this EUT.

Explanation: See attached diagrams in Appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3.5 Spurious emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Marker-Delta-Method" or the „Duty-Cycle Correction Factor“.

Summary table with radiated data of the test plots

Model: P37B	Date: 2009/1/9-2/2	
Mode: 802.11b TX CH1	Temperature: 26 °C	
Polarization: Horizontal	Humidity: 50 %	

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
368.738	12.02	peak	16.94	28.96	74.00	-45.04	140	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4824.000	39.45	---	-1.30	38.15	---	74.00	54.00	-35.85	270	150
7236.000	40.71	---	1.86	42.57	---	74.00	54.00	-31.43	30	150
9648.000	20.42	---	25.06	39.48	---	74.00	54.00	-34.52	240	150
12060.000	19.96	---	29.44	43.40	---	74.00	54.00	-30.60	150	150
14472.000	21.75	---	31.65	41.40	---	74.00	54.00	-32.60	180	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	15.06	peak	16.74	31.80	74.00	-42.20	110	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2
FCC ID: UVZP37BW

Polarization: Vertical

Frequency (MHz)	Reading (dBuV) Peak Ave.		Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave.		Limit @3m (dBuV/m) Peak Ave.		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
4824.000	40.13	---	-1.30	38.83	---	74.00	54.00	-35.17	220	150
7236.000	40.72	---	1.86	42.58	---	74.00	54.00	-31.42	180	150
9648.000	19.49	---	25.06	38.55	---	74.00	54.00	-35.45	210	150
12060.000	21.78	---	29.44	45.22	---	74.00	54.00	-28.78	250	150
14472.000	21.92	---	31.65	41.57	---	74.00	54.00	-32.43	120	150

Mode: 802.11b TX CH6 Temperature: 26 °C Engineer: Kevin
Polarization: Horizontal Humidity: 50 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	15.52	peak	17.10	32.62	74.00	-41.38	220	150

Frequency (MHz)	Reading (dBuV) Peak Ave.		Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave.		Limit @3m (dBuV/m) Peak Ave.		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
4874.000	39.24	---	-1.30	37.94	---	74.00	54.00	-36.06	170	150
7331.000	41.22	---	1.86	43.08	---	74.00	54.00	-30.92	160	150
9748.000	20.77	---	24.94	39.71	---	74.00	54.00	-34.29	180	150
12185.000	20.10	---	29.74	43.84	---	74.00	54.00	-30.16	170	150
14622.000	20.37	---	32.14	40.51	---	74.00	54.00	-33.49	210	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	20.33	peak	16.74	37.07	74.00	-36.93	200	150

Frequency (MHz)	Reading (dBuV) Peak Ave.		Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave.		Limit @3m (dBuV/m) Peak Ave.		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
2437.000	40.86	---	-5.10	35.76	---	74.00	54.00	-38.24	170	150
4874.000	39.17	---	-1.30	37.87	---	74.00	54.00	-36.13	180	150
7331.000	40.78	---	1.86	42.64	---	74.00	54.00	-31.36	120	150
9748.000	19.65	---	24.94	38.59	---	74.00	54.00	-35.41	210	150
12185.000	20.49	---	29.74	44.23	---	74.00	54.00	-29.77	280	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Mode: 802.11b TX CH11 Temperature: 26 °C Engineer: Kevin
Polarization: Horizontal Humidity: 50 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	16.08	peak	17.10	33.18	74.00	-40.82	220	150

Frequency (MHz)	Reading (dBuV) Peak Ave.	Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave.	Limit @3m (dBuV/m) Peak Ave.	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)	
4924.000	39.40	---	-1.20	38.20	74.00	54.00	-35.80	120
7386.000	42.07	---	1.97	44.04	74.00	54.00	-29.96	110
9848.000	21.40	---	25.49	40.89	74.00	54.00	-33.11	200
12310.000	20.60	---	30.04	44.64	74.00	54.00	-29.36	80
14772.000	20.60	---	32.56	41.16	74.00	54.00	-32.84	100

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	20.46	peak	16.74	37.20	74.00	-36.80	170	150

Frequency (MHz)	Reading (dBuV) Peak Ave.	Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave.	Limit @3m (dBuV/m) Peak Ave.	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)	
4924.000	39.43	---	-1.20	38.23	74.00	54.00	-35.77	210
7386.000	42.34	---	1.97	44.31	74.00	54.00	-29.69	130
9848.000	20.16	---	25.49	39.65	74.00	54.00	-34.35	120
12310.000	20.22	---	30.04	44.26	74.00	54.00	-29.74	100
14772.000	21.67	---	32.56	42.23	74.00	54.00	-31.77	210

Mode: 802.11gTX CH1 Temperature: 26 °C Engineer: Kevin
Polarization: Horizontal Humidity: 50 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	17.74	peak	17.10	34.84	74.00	-39.16	140	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4824.000	39.79	---	-1.30	38.49	---	74.00	54.00	-35.51	240	150
7236.000	40.38	---	1.86	42.24	---	74.00	54.00	-31.76	310	150
9648.000	20.00	---	25.06	39.06	---	74.00	54.00	-34.94	280	150
12060.000	21.64	---	29.44	45.08	---	74.00	54.00	-28.92	350	150
14472.000	21.62	---	31.65	41.27	---	74.00	54.00	-32.73	340	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	22.26	peak	16.74	39.00	74.00	-35.00	110	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4824.000	39.72	---	-1.30	38.42	---	74.00	54.00	-35.58	210	150
7236.000	40.56	---	1.86	42.42	---	74.00	54.00	-31.58	170	150
9648.000	19.57	---	25.06	38.63	---	74.00	54.00	-35.37	210	150
12060.000	20.63	---	29.44	44.07	---	74.00	54.00	-29.93	130	150
14472.000	21.05	---	31.65	40.70	---	74.00	54.00	-33.30	100	150

Mode: 802.11g TX CH6

Temperature: 26

°C

Engineer: Kevin

Polarization: Horizontal

Humidity: 50

%

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	19.06	peak	17.10	36.16	74.00	-37.84	210	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4874.000	39.54	---	-1.30	38.24	---	74.00	54.00	-35.76	210	150
7331.000	41.52	---	1.86	43.38	---	74.00	54.00	-30.62	250	150
9748.000	20.15	---	24.94	39.09	---	74.00	54.00	-34.91	20	150
12185.000	19.80	---	29.74	43.54	---	74.00	54.00	-30.46	360	150
14622.000	20.61	---	32.14	40.75	---	74.00	54.00	-33.25	210	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	23.03	peak	16.74	39.77	74.00	-34.23	340	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4874.000	39.81	---	-1.30	38.51	---	74.00	54.00	-35.49	280	150
7331.000	41.84	---	1.86	43.70	---	74.00	54.00	-30.30	350	150
9748.000	20.95	---	24.94	39.89	---	74.00	54.00	-34.11	350	150
12185.000	21.77	---	29.74	45.51	---	74.00	54.00	-28.49	320	150
14622.000	20.69	---	32.14	40.83	---	74.00	54.00	-33.17	210	150

Mode: 802.11g TX CH11

Temperature: 26

°C

Engineer: Kevin

Polarization: Horizontal

Humidity: 50

%

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
374.349	19.58	peak	17.10	36.68	74.00	-37.32	250	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4924.000	39.57	---	-1.20	38.37	---	74.00	54.00	-35.63	210	150
7386.000	41.91	---	1.97	43.88	---	74.00	54.00	-30.12	220	150
9848.000	19.80	---	25.49	39.29	---	74.00	54.00	-34.71	210	150
12310.000	21.61	---	30.04	45.65	---	74.00	54.00	-28.35	350	150
14772.000	21.84	---	32.56	42.40	---	74.00	54.00	-31.60	210	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
361.723	22.30	peak	16.74	39.04	74.00	-34.96	220	150

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.	Corr.	Peak	Ave.	Peak	Ave.			
4924.000	39.17	---	-1.20	37.97	---	74.00	54.00	-36.03	310	150
7386.000	41.52	---	1.97	43.49	---	74.00	54.00	-30.51	40	150
9848.000	20.13	---	25.49	39.62	---	74.00	54.00	-34.38	220	150
12310.000	21.15	---	30.04	45.19	---	74.00	54.00	-28.81	350	150
14772.000	21.43	---	32.56	41.99	---	74.00	54.00	-32.01	120	150

Note

1. Correction Factor = Antenna factor + Cable loss - Preamplifier
2. The formula of measured value as: Test Result = Reading + Correction Factor
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. See the attached diagram as appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2
FCC ID: UVZP37BW

All other not noted test plots do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 017, ETSTW-RE 018,
ETSTW-RE 021, ETSTW-RE 028, ETSTW-RE 029, ETSTW-RE 030,
ETSTW-RE 042, ETSTW-RE 043, ETSTW-RE 064



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3.6 Radiated Emission on the band edge

According to FCC rules part 15 subpart C §15.247(c) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

Mode A:

Test conditions	Attenuation at or outside band-edges	
	Lower Band-edge	Upper Band-edge
T _{nom} = 23°C V _{nom} = 120 V	36.05 dB	33.76 dB

Mode B:

Test conditions	Attenuation at or outside band-edges	
	Lower Band-edge	Upper Band-edge
T _{nom} = 23°C V _{nom} = 120 V	31.25 dB	32.70 dB

Limits:

Frequency Range / MHz	Limit
902 – 928	
2400 – 2483.5	- 20 dB
5725 - 5850	

Test equipment used: ETSTW-RE 055

Explanation: See attached diagrams in appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3.7 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission.

The 6 dB bandwidth is the frequency difference between the two markers.

Mode A:

Test conditions		6 dB Bandwidth			
		Channel 1	Channel 6	Channel 11	
T _{nom}	= 23°C	V _{nom} = 120 V	10.160256410 MHz	10.160256410 MHz	10.192307692 MHz

Mode B:

Test conditions		6 dB Bandwidth			
		Channel 1	Channel 6	Channel 11	
T _{nom}	= 23°C	V _{nom} = 120 V	16.570512821 MHz	16.570512821 MHz	16.538461538 MHz

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-RE 055

Explanation: See attached diagrams in appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3.8 Peak Power Spectral Density

Peak Power Spectral density is measured at low, middle and high channel.

The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.

Mode A:

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel 1 [dBm]	Channel 6 [dBm]	Channel 11 [dBm]
T _{nom} = 23°C	V _{nom} = 120 V	-15.76	-13.10	-18.01

Mode B:

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel 1 [dBm]	Channel 6 [dBm]	Channel 11 [dBm]
T _{nom} = 23°C	V _{nom} = 120 V	-16.31	-17.91	-18.53

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483,5	8
5725-5850	8

Test equipment used: ETSTW-RE 055

Explanation: See attached diagrams in appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3.9 Radiated Emissions from Digital Part

FCC Rule: 15.109

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 017, ETSTW-RE 028, ETSTW-RE 029, ETSTW-RE 030, ETSTW-RE 042, ETSTW-RE 043, ETSTW-RE 064

Explanation: The test results are listed in the separated test report no. W6M20812-9482-P-15B.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

3.10 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Frequency	Level (dB μ V)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

Model:	P37B	Date:	2008/12/9					
Mode:		Temperature:	24	°C				
Polarization:	N	Humidity:	50	%	Engineer: Kevin			
Frequency (MHz)	Reading (dB μ V) QP Ave.	Factor (dB) Corr.	Result (dB μ V) QP Ave.	Limit (dB μ V) QP Ave.	Margin (dB)			
0.1655	18.65	16.10	10.15	28.80	26.25	65.18	55.18	-28.93
0.5950	19.23	17.30	10.16	29.39	27.46	56.00	46.00	-18.54
0.8600	18.73	15.96	10.12	28.85	26.08	56.00	46.00	-19.92
2.9150	20.80	14.70	10.06	30.86	24.76	56.00	46.00	-21.24
12.2222	22.20	19.20	10.48	32.68	29.68	60.00	50.00	-20.32
25.9444	23.10	20.90	10.61	33.71	31.51	60.00	50.00	-18.49

Polarization: L1

Frequency (MHz)	Reading (dB μ V) QP Ave.	Factor (dB) Corr.	Result (dB μ V) QP Ave.	Limit (dB μ V) QP Ave.	Margin (dB)			
0.1547	21.24	19.10	10.18	31.42	29.28	65.74	55.74	-26.46
0.4020	20.10	18.20	10.05	30.15	28.25	57.81	47.81	-19.56
1.8650	18.00	10.60	10.07	28.07	20.67	56.00	46.00	-25.33
3.3300	20.30	11.10	10.09	30.39	21.19	56.00	46.00	-24.81
11.9167	22.20	19.40	10.49	32.69	29.89	60.00	50.00	-20.11
27.9722	22.40	19.40	10.63	33.03	30.03	60.00	50.00	-19.97

Note:

1. The formula of measured value as: Test Result = Reading + Correction Factor
2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. See attached diagrams in Appendix.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2
FCC ID: UVZP37BW

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001 ETSTW-CE 003 ETSTW-CE 004 ETSTW-CE 006 ETSTW-RE 064



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2
FCC ID: UVZP37BW

Appendix

A. Measurement diagrams

1. Peak Output Power
2. Spurious Emissions radiated
3. Minimum 6dB Bandwidth
4. Band Edge
5. Peak Power Spectral Density
6. Power Line Conducted Emission

B. Photos

1. External Photos
2. Internal Photos
3. Set Up Photo of Radiated Emission
4. Set Up Photo of Conducted Emission





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Peak Output Power Mode A




MAX OUTPUT POWER 802.11b CH6
Date: 5.FEB.2009 07:55:13



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW



MAX OUTPUT POWER 802.11b CH11
Date: 5.FEB.2009 07:55:52

Mode B




MAX OUTPUT POWER 802.11g CH1
Date: 5.FEB.2009 08:01:13




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW



MAX OUTPUT POWER 802.11g CH6
Date: 5.FEB.2009 08:01:59



MAX OUTPUT POWER 802.11g CH11
Date: 5.FEB.2009 08:02:34



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Spurious Emissions radiated

Mode A _ CH 1

Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Mode A_CH 6

Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Mode A CH 11

Antenna Polarization H



Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Mode B_CH 1

Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Antenna Polarization V







Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Mode B_CH 6

Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Mode B_CH 11

Antenna Polarization H



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Antenna Polarization V



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

87.0 dBuV/m



Up Line: Peak Limit Line Down Line: Ave Limit Line


Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of radiated test data of this test report.


Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW

Minimum 6dB Bandwidth



6DB BANDWIDTH 802.11b CH1
Date: 16.JAN.2009 15:16:49




6DB BANDWIDTH 802.11b CH6
Date: 16.JAN.2009 15:20:13




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW



6DB BANDWIDTH 802.11b CH11
Date: 16.JAN.2009 15:22:04




6DB BANDWIDTH 802.11g CH1
Date: 16.JAN.2009 15:29:15




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW



6DB BANDWIDTH 802.11g CH6
Date: 16.JAN.2009 15:27:14



6DB BANDWIDTH 802.11g CH11
Date: 16.JAN.2009 15:25:43




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2


FCC ID: UVZP37BW

Band edge



FREQUENCY RANGE 802.11b CH1

Date: 17.JAN.2009 07:27:56



FREQUENCY RANGE 802.11b CH1


Date: 17.JAN.2009 07:32:18




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW



FREQUENCY RANGE 802.11g CH1
Date: 17.JAN.2009 07:43:52



FREQUENCY RANGE 802.11g CH11
Date: 17.JAN.2009 07:46:13




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2


FCC ID: UVZP37BW

Peak Power Spectral Density



POWER DENSITY 802.11b CH1

Date: 17.JAN.2009 07:54:52



POWER DENSITY 802.11b CH6


Date: 17.JAN.2009 08:01:15




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW



POWER DENSITY 802.11b CH11
Date: 17.JAN.2009 08:10:47




POWER DENSITY 802.11g CH1
Date: 17.JAN.2009 08:39:33




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2

FCC ID: UVZP37BW



POWER DENSITY 802.11g CH6
Date: 17.JAN.2009 08:34:23



POWER DENSITY 802.11g CH11
Date: 17.JAN.2009 08:19:35




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6D20909-10102-C-2


FCC ID: UVZP37BW

Power Line Conducted Emission

LISN N



LISN L1



Up Line: QP Limit Line

Down Line: Ave Limit Line

Note:

1. The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
2. The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
3. For corrected test results are listed in the relevant table of AC conducted test data of this test report.