

Blue Bamboo specializes in fast and reliable wireless hardware and data management services that drive mobile workforce productivity without the premium cost.

SIMPLE

With its small design, the H50 is ideal for Mobile workforce environments where portability and ease of use are critical success factors. The H50 also has a large LCD display with screen addressable keys for easy menu driven application and a mag-stripe reader enabling any company to accept loyalty, gift, or stored value cards in the field with optional smart card support.

RELIABLE

Companies today are relying on the mobile workforce to extend services and sales in a more proficient and secure manner. Blue Bamboo's

For more information, please contact +1 888 861 3489 www.bluebamboo.com

premier device features mobile payment transactions which exceed current industry security standards, allowing fast and secure transaction. Created with portability in mind, the H50 is light weight with a sleek ergonomic design suitable for most mobile environments.

AFFORDABLE

An evolving market needs evolving technology, but without the premium cost. Mobile professionals now have an affordable option with the H50. Blue Bamboo's all-in-one handheld wireless unit allows for anytime, anywhere mobile payment transactions giving mobile professionals the ability to increase sales and productivity transactions with a compact and portable device.





H50 Technical Specifications

User interface Integrated PIN pad with DES, 3DES and RSA encryption
128 x 64 pixel backlit LCD display
Buzzer

Buzzer Belt clip

Keypad Numeric, function and screen addressable keys

Printer Embedded thermal printer, up to 12 lines per second

Paper size 58mm/2.3in (width), 40mm/1.6in (paper roll diameter)

Card reader Track 1 and 2 magnetic stripe reader (MSR T 1/2)

IC card reader

Communication ports Serial port

Processor and memory CPU - optimized 32 bit Java bytecode RISC processor

512 KB SRAM 4 MB FLASH

32 KB SRAM (battery backup, key storage)

Software Multi-application GlobalPlatform environment

Certifications EMV level 1

EMV level 2

PCI PED certification FCC, CE, CCC

UL or TUV for power adapter

Battery Rechargeable internal Li-ion battery with external power pack

Up to 200 receipts per single battery charge

Power: 100-240 V, 50/60 Hz

Output: 9VDC 1A

Dimensions (W x D x H) 109 x 192 x 53 mm (4.3 x 7.5 x 2 in)

Weight 424 g / 15 oz / 0,94 lbs

Environment Operating temperature: 0 ~ + 40 °C (+ 32 ~ + 104 °F)

Operating humidity: $20 \sim 85\%$ RH, non-condensing Storage temperature: $-20 \sim +60$ °C ($-4 \sim +140$ °F)

Storage humidity: 10 ~ 90% RH

Optional features 2 SAM'S

33,6k baud modem module

850 / 1800 / 1900 and 900 / 1800 / 1900 GSM / GPRS module

SDK (Software Development Kit)

Track 2 and 3 for the MSR

Serial cable

Rechargeable batteries

Specifications subject to change without notice

For more information, please contact sales@bluebamboo.com

www.bluebamboo.com





