

RF Exposure Evaluation declaration

Product Name : GPRS Module / POS Terminal
Model No. : GPRS Module H50-CM06/POS
Terminal H50-10
FCC ID : UWJH50CM06

Applicant : BLUE BAMBOO (HK) LIMITED
Address : Unit 1001, Lucky Building, No.39 Wellington Street,
Central, Hong Kong

Date of Receipt : 2009/04/20
Issued Date : 2009/05/26
Report No. : 095S008R-HP-US
Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by CNLA, NVLAP, NIST or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.\

1.3. Test Result of RF Exposure Evaluation

Product	:	GPRS Module / POS Terminal
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-4

Antenna Gain:

Antenna Gain: The maximum Gain measured in fully anechoic chamber is -4.5dBi for GSM850 and 1dBi for GSM1900.

Output Power into Antenna & RF Exposure Evaluation Distance:

Channel	Channel Frequency (MHz)	Conducted Peak Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
128	824.20	1940.8859	0.137003
189	836.40	1870.6821	0.132048
251	848.80	1923.0917	0.135747
512	1850.2	972.7472	0.243630
661	1880.0	981.7479	0.245884
810	1909.8	946.2372	0.236990

Note:

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².