

# Emissions Test Report

**EUT Name:** Powerview Gen3 Motor Control Board

**Model No.:** 1012000217

CFR 47 Part 15.247: 2019 and RSS 247: 2017

*Prepared for:*

Hunter Douglas Window Fashions  
One Duette Way  
Broomfield, CO 80020

*Prepared by:*

TUV Rheinland of North America, Inc.  
5015 Brandin Ct.  
Fremont, CA 94538  
Tel: (925) 249-9123  
Fax: (925) 249-9124  
<http://www.tuv.com/>

*Report/Issue Date:* March 19, 2020

*Job #* 234112098

*Report Number:* 32060521.001



# Statement of Compliance

*Manufacturer:* Hunter Douglas Window Fashions  
One Duette Way  
Broomfield, CO 80020  
*Requester / Applicant:* Hunter Douglas Window Fashions  
*Name of Equipment:* Powerview Gen3 Motor Control Board  
*Model No.* 1012000217  
*Type of Equipment:* Intentional Radiator  
*Application of Regulations:* CFR 47 Part 15.247: 2019 and RSS 247: 2017  
*Test Dates:* January 14th, 2020 to January 31st, 2020

*Guidance Documents:*

Emissions: ANSI C63.10-2013, KDB 558074 D01 DTS Measurement Guidance v05r02, KDB 662911 D01 Multiple Transmitter Output v02r01

*Test Methods:*

Emissions: ANSI C63.10-2013, KDB 558074 D01 DTS Measurement Guidance v05r02, KDB 662911 D01 Multiple Transmitter Output v02r01

The electromagnetic compatibility test and documented data described in this report has been performed and recorded by TUV Rheinland, in accordance with the standards and procedures listed herein. As the responsible authorized agent of the EMC laboratory, I hereby declare that the equipment described above has been shown to be compliant with the EMC requirements of the stated regulations and standards based on these results. If any special accessories and/or modifications were required for compliance, they are listed in the Executive Summary of this report.

This report must not be used to claim product endorsement by A2LA or any agency of the U.S. Government. This report shall not be reproduced except in full, without the written authorization of TUV Rheinland of North America.



---

James Borrott

Date March 19, 2020

A2LA Signatory

Date March 19, 2020



**ISED**

**Testing Cert #3331.02**

**US1131**

**2932D**

Table of Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Executive Summary</b>                            | <b>7</b>  |
| 1.1      | Scope   | 7         |
| 1.2      | Purpose   | 7         |
| 1.3      | Summary of Test Results                             | 8         |
| 1.4      | Special Accessories                                 | 8         |
| 1.5      | Equipment Modifications                             | 8         |
| <b>2</b> | <b>Laboratory Information</b>                       | <b>9</b>  |
| 2.1      | Accreditations & Endorsements                       | 9         |
| 2.1.1    | US Federal Communications Commission                | 9         |
| 2.1.2    | NIST / A2LA   | 9         |
| 2.1.3    | ISED  | 9         |
| 2.1.4    | Japan – VCCI  | 9         |
| 2.1.5    | Acceptance by Mutual Recognition Arrangement        | 10        |
| 2.2      | Test Facilities                                     | 10        |
| 2.2.1    | Emission Test Facility                              | 10        |
| 2.3      | Measurement Uncertainty                             | 10        |
| 2.3.1    | Sample Calculation – radiated & conducted emissions | 11        |
| 2.3.2    | Measurement Uncertainty                             | 11        |
| 2.3.3    | Measurement Uncertainty Immunity                    | 12        |
| 2.4      | Calibration Traceability                            | 12        |
| <b>3</b> | <b>Product Information</b>                          | <b>13</b> |
| 3.1      | Product Description                                 | 13        |
| 3.2      | Equipment Configuration                             | 13        |
| 3.3      | Operating Mode                                      | 13        |
| 3.4      | Unique Antenna Connector                            | 14        |
| 3.4.1    | Results   | 14        |
| <b>4</b> | <b>Emissions</b>                                    | <b>15</b> |
| 4.1      | Output Power Requirements                           | 15        |
| 4.1.1    | Test Method   | 15        |
| 4.1.2    | Results   | 16        |
| 4.2      | DTS Bandwidth (6dB) and Occupied Bandwidth          | 18        |
| 4.2.1    | Test Method   | 18        |
| 4.2.2    | Results   | 18        |
| 4.3      | Peak Power Spectral Density                         | 23        |
| 4.3.1    | Test Method   | 23        |
| 4.3.2    | Results   | 24        |
| 4.4      | Out of Band Emissions: Non-Restricted Bands         | 26        |
| 4.4.1    | Test Method   | 26        |
| 4.4.2    | Results   | 27        |

Table of Contents

|            |  |           |
|------------|--|-----------|
| <b>4.5</b> | <b>Out of Band Emissions: Restricted Band Edge</b> | <b>31</b> |
| 4.5.1      | Test Method  | 31        |
| 4.5.2      | Test Results                                       | 32        |
| <b>4.6</b> | <b>Transmitter Spurious Emissions</b>              | <b>34</b> |
| 4.6.1      | Test Methodology                                   | 34        |
| 4.6.2      | Test Setup   | 35        |
| 4.6.3      | Transmitter Spurious Emission Limit                | 36        |
| 4.6.4      | Test Results                                       | 36        |
| <b>4.7</b> | <b>AC Conducted Emissions</b>                      | <b>43</b> |
| 4.7.1      | Test Methodology                                   | 43        |
| 4.7.2      | Test Results                                       | 43        |
| <b>5</b>   | <b>Test Equipment List</b>                         | <b>46</b> |
| <b>5.1</b> | <b>Equipment List</b>                              | <b>46</b> |
| <b>6</b>   | <b>EMC Test Plan</b>                               | <b>47</b> |
| <b>6.1</b> | <b>Introduction</b>                                | <b>47</b> |
| <b>6.2</b> | <b>Customer</b>                                    | <b>47</b> |
| <b>6.3</b> | <b>Equipment Under Test (EUT)</b>                  | <b>47</b> |
| <b>6.4</b> | <b>Product Specifications</b>                      | <b>48</b> |
| <b>6.5</b> | <b>Test Specifications</b>                         | <b>50</b> |

Index of Tables

**Table 1:** Summary of Test Results ..... 8  
**Table 2:** RF Output Power at the Antenna Port – Test Results ..... 16  
**Table 3:** Occupied Bandwidth – Test Results ..... 19  
**Table 4:** Peak Power Spectral Density – Test Results ..... 24  
**Table 5:** Emissions at the Band-Edge – Test Results ..... 27  
**Table 6:** Emissions at the Band-Edge – Test Results ..... 32  
**Table 7:** AC Conducted Emissions – Test Results ..... 43  
**Table 8:** Customer Information ..... 47  
**Table 9:** Technical Contact Information ..... 47  
**Table 10:** EUT Designation ..... 47  
**Table 11:** EUT Specifications ..... 48  
**Table 12:** Antenna Information ..... 49  
**Table 13:** Interface Specifications ..... 49  
**Table 14:** Accessory Equipment ..... 49  
**Table 15:** Ancillary Equipment (used for test purposes only) ..... 49  
**Table 16:** Description of Sample used for Testing ..... 50  
**Table 17:** Description of Test Configuration used for Radiated Measurement. .... 50  
**Table 18:** Test Specifications ..... 50

# 1 Executive Summary

## 1.1 Scope

This report is intended to document the status of conformance with the requirements of the CFR 47 Part 15.247: 2019 and RSS 247: 2017 based on the results of testing performed on January 14th, 2020 to January 31st, 2020 on the 1012000217 manufactured by Hunter Douglas Window Fashions. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

## 1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report. The 2400 MHz to 2483.5 MHz frequency band is covered in this document.

### 1.3 Summary of Test Results

**Table 1:** Summary of Test Results

| Test                                  | Test Method<br>ANSI C 63.10 &<br>C63.4        | Worse Case<br>(Measured)                   | Result          |
|---------------------------------------|---|--|-----------------|
| Maximum Output Power                  | CFR47 15.247 (b),<br>RSS 247 Sect. 5.4 (d)    | 5.75 dBm @ 2453MHz Channel                 | <b>Complied</b> |
| DTS Bandwidth (6dB)                   | CFR47 15.247 (a)(2),<br>RSS 247 Sect. 5.2 (a) | 0.840 MHz @ 2407MHz Channel                | <b>Complied</b> |
| Peak Power Spectral Density           | CFR47 15.247 (e),<br>RSS 247 Sect. 5.2 (b)    | -7.29 dBm @ 2453MHz Channel                | <b>Complied</b> |
| Out of Band Emissions: Non-Restricted | CFR47 15.247 (d),<br>RSS 247 Sect.5.5         | -56.45 dBc @ 24342.96 MHz, Lower Band Edge | <b>Complied</b> |
| Out of Band Emissions: Restricted     | CFR47 15.247 (d),<br>RSS 247 Sect.5.5         | -13.83 dB margin @ 2535.152MHz, Average    | <b>Complied</b> |
| Transmitter Spurious Emissions        | CFR47 15.247 (d),<br>RSS 247 Sect.5.5         | -7.02dB Margin @ 4814.656 MHz, Average     | <b>Complied</b> |
| AC Power Conducted Emission           | CFR47 15.207,<br>RSS-GEN Sect.8.8             | -19.82dB Margin @ 0.36814 MHz, QP          | <b>Complied</b> |

Note 1: This test report covers 2400 MHz to 2483.5 MHz band.

Note 2: Class B limits were applied where applicable.

### 1.4 Special Accessories

No special accessories were necessary in order to achieve compliance.

### 1.5 Equipment Modifications

None



## 2 Laboratory Information

### 2.1 Accreditations & Endorsements

#### 2.1.1 US Federal Communications Commission



TUV Rheinland of North America EMC test facilities located at 1279 Quarry Lane, Ste. A, Pleasanton, CA, 94566, and 5015 Brandin Ct, Fremont, CA 94538, are recognized by the Commission for performing testing services for the general public on a fee basis. These laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (Registration No. US1131). The laboratory Scopes of Accreditation include Title 47 CFR Parts 15, 18 and 90. The accreditations are updated every three years.

#### 2.1.2 NIST / A2LA



TUV Rheinland of North America is accredited by the National Voluntary Laboratory Accreditation Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Guide 17025:2005. The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

#### 2.1.3 ISED

The Pleasanton 5-meter Semi-Anechoic Chamber, has been accepted by ISED to perform testing to 3 and 5 meters based on the test procedures described in ANSI C63.4-2014. The Fremont 10-meter Semi-Anechoic Chamber, has been accepted by ISED to perform testing to 3 and 10 meters based on the test procedures described in ANSI C63.4-2014. Under 2932D

#### 2.1.4 Japan – VCCI



The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) is a group that consists of Information Technology Equipment (ITE) manufacturers and EMC test laboratories. The purpose of the Council is to take voluntary control measures against electromagnetic interference from Information Technology Equipment, and thereby contribute to the development of a socially beneficial and responsible state of affairs in the realm of Information Technology Equipment in Japan. TUV Rheinland of North America EMC test facilities located at 1279 Quarry Lane, Ste. A, Pleasanton, CA, 94566, and 5015 Brandin Ct, Fremont, CA 94538, have been assessed and approved in accordance with the Regulations for Voluntary Control Measures.

VCCI Registration No. for Pleasanton: A-0326

VCCI Registration No. for Fremont: A-0327

### 2.1.5 Acceptance by Mutual Recognition Arrangement



The United States has an established agreement with specific countries under the Asia Pacific Laboratory Accreditation Corporation (APLAC) Mutual Recognition Arrangement. Under this agreement, all TUV Rheinland at 1279 Quarry Ln, Pleasanton, CA 94566 test results and test reports within the scope of the laboratory NIST / A2LA accreditation will be accepted by each member

country.

## 2.2 Test Facilities

Test facilities are located at 5015 Brandin Ct, Fremont, California, 94538, USA and 1279 Quarry Lane, Pleasanton, California 94566, USA (Fremont is the Pleasanton Annex).

### 2.2.1 Emission Test Facility

The Semi-Anechoic Chambers and AC Line Conducted measurement facilities used to collect radiated and conducted emissions data have been constructed in accordance with ANSI C63.7:1992. The Fremont 10 meter semi-anechoic chamber has been measured in accordance with and verified to comply with the theoretical volumetric normalized site attenuation of ANSI C63.4:2014 and SVSWR requirements of CISPR 16-1-4 Consol. Ed. 3.0 (2010-04), at test distances of 3 and 10 meters. This site has been described in reports dated November 1st, 2006, submitted to the FCC, and accepted by letter dated November 28, 2006. The site is listed with the FCC and accredited by A2LA (Testing Certificate #3331.02). The Pleasanton 5 meter semi-anechoic chamber has been verified to comply with the theoretical volumetric normalized site attenuation of ANSI C63.4:2009 and SVSWR requirements of CISPR 16-1-4 Consol. Ed. 3.0 (2010-04) at a test distance of 3 meters. This site has been described in reports dated November 1st, 2006, submitted to the FCC, and accepted by letter dated November 28, 2006. The site is listed with the FCC and accredited by A2LA (Testing Certificate #3331.02).

## 2.3 Measurement Uncertainty

Two types of measurement uncertainty are expressed in this report, per *ISO Guide To The Expression Of Uncertainty In Measurement*, 1<sup>st</sup> Edition, 1995.

*The Combined Standard Uncertainty* is the standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities; it is equal to the positive square root of the sum of the variances or co-variances of these other quantities, weighted according to how the measurement result varies with changes in these quantities. The term *standard uncertainty* is the result of a measurement expressed as a standard deviation.

*The Expanded Uncertainty* defines an interval about the result of a measurement that may be expected to encompass a large fraction of the distribution of values that could reasonably be attributed to the measurement and the fraction may be viewed as the coverage probability or level of confidence of the interval.

### 2.3.1 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{RAW} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where: RAW = Measured level before correction (dBμV)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V/m}}{20}}$$

#### Sample radiated emissions calculation @ 30 MHz

Measurement +Antenna Factor–Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)

$$25 \text{ dBuV/m} + 17.5 \text{ dB} - 20 \text{ dB} + 1.0 \text{ dB} = 23.5 \text{ dBuV/m}$$

### 2.3.2 Measurement Uncertainty

| Per CISPR 16-4-2                               | U <sub>lab</sub> | U <sub>cispr</sub> |
|--|------------------|--------------------|
| <b>Radiated Disturbance @ 10 meters</b>        |                  |                    |
| 30 – 1,000 MHz                                 | 2.25 dB          | 4.51 dB            |
| <b>Radiated Disturbance @ 3 meters</b>         |                  |                    |
| 30 – 1,000 MHz                                 | 2.26 dB          | 4.52 dB            |
| 1 – 6 GHz                                      | 2.12 dB          | 4.25 dB            |
| 6 – 18 GHz                                     | 2.47 dB          | 4.93 dB            |
| <b>Conducted Disturbance @ Mains Terminals</b> |                  |                    |
| 150 kHz – 30 MHz                               | 1.09 dB          | 2.18 dB            |
| <b>Disturbance Power</b>                       |                  |                    |
| 30 MHz – 300 MHz                               | 3.92 dB          | 4.3 dB             |

#### Voltech PM6000A

|  |                          |
|--|--------------------------|
| The estimated combined standard uncertainty for harmonic current and flicker measurements is ± 5.0%. | Per CISPR 16-4-2 Methods |
|--|--------------------------|

### 2.3.3 Measurement Uncertainty Immunity

|   |                   |
|---|-------------------|
| The estimated combined standard uncertainty for ESD immunity measurements is $\pm 8.2\%$ .                | Per IEC 61000-4-2 |
| The estimated combined standard uncertainty for radiated immunity measurements is $\pm 4.10$ dB.          | Per IEC 61000-4-3 |
| The estimated combined standard uncertainty for conducted immunity measurements with CDN is $\pm 3.66$ dB | Per IEC 61000-4-6 |
| The estimated combined standard uncertainty for power frequency magnetic field immunity is $\pm 2.9\%$ .  | Per IEC 61000-4-8 |

#### Thermo KeyTek EMC Pro

|   |
|---|
| The estimated combined standard uncertainty for EFT fast transient immunity measurements is $\pm 2.6\%$ .         |
| The estimated combined standard uncertainty for surge immunity measurements is $\pm 2.6\%$ .                      |
| The estimated combined standard uncertainty for voltage variation and interruption measurements is $\pm 1.74\%$ . |

The expanded uncertainty at a level of 95% confidence is obtained by multiplying the combined standard uncertainty by a coverage factor of 2. Compliance criteria are not based on measurement uncertainty.

### 2.4 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard 17025:2005. Equipment calibration records are kept on file at the test facility.

---

## 3 Product Information

### 3.1 Product Description

The Model 1012000217 is assembled into various motor assemblies and fabricated into Hunter Douglas window coverings that include a fabric member that is rolled around an aluminum tube. User inputs to the system include a push button on the motor module, a TTL level serial port, and 2.4GHz RF signals. The RF protocol used is proprietary to Hunter Douglas and is implemented with Nordic NRF52840 series SoC's (system on chips). At the time of this writing only three primary frequencies are being used in the protocol [2407MHz, 2453MHz, 2471MHz].

The EUT will be in compliance with regulatory standards of regions it will be operating in.

### 3.2 Equipment Configuration

A description of the equipment configuration is given in the Test Plan Section. The EUT was tested as called for in the test standard and was configured and operated in a manner consistent with its intended use. The EUT was connected to rated power and allowed to reach intended operating conditions. The placement of the EUT system components was guided by the test standard and selected to represent typical installation conditions.

In the case of an EUT that can operate in more than one configuration, preliminary testing was performed to determine the configuration that produced maximum radiation.

The final configuration was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

### 3.3 Operating Mode

A description of the operation mode is given in the Test Plan Section. In the case of an EUT that can operate in more than one state, preliminary testing was performed to determine the operating mode that produced maximum radiation.

The final operating mode was selected to produce the worst case radiation for emissions testing.

### **3.4 Unique Antenna Connector**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of CFR47 Parts 15.211, 15.213, 15.217, 15.219, or 15.221.

#### **3.4.1 Results**

The Powerview Gen3 Motor Control Board has 1 dedicated Flex PIFA antenna that has maximum gain of 1.58 dBi. It is attached using a non-standard connector and is not easily accessible to the end user.

## 4 Emissions

Testing was performed in accordance with CFR 47 Part 15.247: 2019 and RSS 247: 2017. These test methods are listed under the laboratory's A2LA Scope of Accreditation. This test measures the levels emanating from the EUT, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices.

### 4.1 Output Power Requirements

*The maximum output power requirement is the maximum equivalent isotropic radiated power delivering at the transmitting antenna under specified conditions of measurements in the presence of modulation.*


*The maximum output power and harmonics shall not exceed CFR47 Part 15.247 (b) and RSS 247 5.4 (d).*

*The maximum transmitted power in the band 2400-2483.5 MHz: 1 W*

#### 4.1.1 Test Method

Method of measurement as stated in ANSI C63.10:2013 Sect. 11.9 was used to measure the channel power output. The worst findings were conducted on 3 channels in each operating range per CFR47 Part 15.247(b) and RSS 247 Sect. 5.4(d); 2400 MHz to 2483.5 MHz. The worst mode results indicated below.

Test Setup:




### 4.1.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s). Worse case data for each mode reported below. Plots of highest power included for low, medium, and high channels.

**Table 2: RF Output Power at the Antenna Port – Test Results**


| Data Rate | Operating Channel (MHz) | Power [dBm] | Limit [dBm] | Margin [dB] |
|-----------|-------------------------|-------------|-------------|-------------|
| 2Mbps     | 2407                    | 5.75        | 30          | -14.25      |
|           | 2453                    | 5.75        | 30          | -14.25      |
|           | 2471                    | 5.63        | 30          | -14.37      |



Date: 14.JAN.2020 08:56:52


**Plot 1. Maximum Conducted Power, 2Mbps 2407MHz**





Date: 14.JAN.2020 08:58:35

**Plot 2. Maximum Conducted Power, 2Mbps 2453MHz**



Date: 14.JAN.2020 09:01:59

**Plot 3. Maximum Conducted Power, 2Mbps 2471MHz**

## 4.2 DTS Bandwidth (6dB) and Occupied Bandwidth

*The occupied bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency.*


*The 99% bandwidth is the bandwidth in which 99% of the transmitted power occupied.*

*The minimum 6 dB bandwidth shall be at least 500 kHz.*

### 4.2.1 Test Method

The conducted method was used to measure the occupied bandwidth according to ANSI C63.10:2013 Section 11.8. The measurement was performed with modulation per CFR47 15.247 (a) (2) and RSS Gen Sect. 6.7. Measurements were performed on the low, middle and high channels of the operating frequency range; 2400 MHz to 2483.5 MHz.

Test Setup:




### 4.2.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).


**Table 3: Occupied Bandwidth – Test Results**

| Bandwidth (MHz)   |             |                     |                           |
|-------------------|-------------|---------------------|---------------------------|
| Data Rate         | Freq. (MHz) | 99% Bandwidth (MHz) | 6dB (DTS) Bandwidth (MHz) |
| 2Mbps             | 2407        | 1.086               | 0.840                     |
|                   | 2453        | 1.884               | 0.8865                    |
|                   | 2471        | 1.8585              | 0.909                     |
| <b>Note:</b> None |             |                     |                           |




Date: 14.JAN.2020 08:10:26

**Plot 4. 2Mbps, 2407MHz, 6dB Bandwidth**




Date: 14.JAN.2020 08:15:42

**Plot 5. 2Mbps, 2453MHz, 6dB Bandwidth**




Date: 14.JAN.2020 08:18:33

**Plot 6. 2Mbps, 2471MHz, 6dB Bandwidth**



Date: 14.JAN.2020 08:55:15

**Plot 7. 2Mbps, 2407MHz, 99% Bandwidth**



Date: 14.JAN.2020 08:50:48

**Plot 8. 2Mbps, 2453MHz, 99% Bandwidth**




### 4.3 Peak Power Spectral Density

According to the CFR47 Part 15.247 (e) and RSS 247 Sect.5.2 (b), the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.1 Test Method

The conducted method was used to measure the channel power output per ANSI C63.10-2013 Section 11.10.2. The measurement was performed with modulation per CFR47 Part 15.247 (e) and RSS 247 Sect.5.2 (b). The worst findings were conducted on 3 channels in each operating frequency range of 2400 MHz to 2483.5 MHz.

Test Setup:




### 4.3.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

**Table 4: Peak Power Spectral Density – Test Results**


| Peak Power Spectral Density |             |                 |             |             |
|-----------------------------|-------------|-----------------|-------------|-------------|
| Data Rate                   | Freq. (MHz) | Total PSD [dBm] | Limit [dBm] | Margin [dB] |
| 2Mbps                       | 2407        | -7.47           | 8           | -15.47      |
|                             | 2453        | -7.29           | 8           | -15.29      |
|                             | 2471        | -8.45           | 8           | -16.45      |
| <b>Note:</b> None           |             |                 |             |             |



Date: 14.JAN.2020 09:12:53


**Plot 10. 2Mbps, 2407MHz PSD**





Date: 14.JAN.2020 09:08:03

**Plot 11. 2 Mbps, 2453MHz PSD**



Date: 14.JAN.2020 09:05:58

**Plot 12. 2Mbps, 2471MHz PSD**


#### 4.4 Out of Band Emissions: Non-Restricted Bands

*Any frequency outside the band of 2400 MHz to 2483.5 MHz, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under the regulation, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. ; CFR 47 Part 15.247(d) and RSS 247 Sect. 5.5.*

##### 4.4.1 Test Method

Conducted measurements per ANSI C63.10-2013 Sections 6.10, 11.11, 14.3.3 were used to measure the undesirable emission requirement in non-restricted bands. The measurement was performed with modulation. The measurement was conducted from 30MHz to 26.5GHz on 3 channels in each mode on the EUT. Reference level was established on the channel with highest measured PSD (2453MHz) as stated in ANSI C63.10-2013 Section 11.11.2. Band edge tests were conducted on the low and high channel of each mode. The worst case measurement of each mode is recorded in this report.

Test Setup:




### 4.4.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).


**Table 5:** Emissions at the Band-Edge – Test Results

| Non-Restricted Frequency Band Edge Emissions |           |                   |                |             |             |            |         |
|--|-----------|-------------------|----------------|-------------|-------------|------------|---------|
| Data Rate                                    | Band Edge | Center Freq (MHz) | Measured (dBm) | Limit (dBm) | Margin (dB) | Freq (MHz) | Results |
| 2Mbps  | Low       | 2407              | -51.78         | -15.33      | -36.45      | 2342.96    | Pass    |
|  | High      | 2471              | -55.07         | -15.78      | -36.7       | 2535.089   | Pass    |
| <b>Note:</b>                                 |           |                   |                |             |             |            |         |




Date: 14.JAN.2020 09:18:13

**Plot 13.** 2Mbps, 2407MHz Lower Band Edge




Date: 14.JAN.2020 09:22:21

**Plot 14. 2Mbps, 2471MHz Upper Band Edge**




Date: 14.JAN.2020 09:25:51

**Plot 15. PSD Reference Measurement, 2Mbps 2453MHz**




Date: 14.JAN.2020 09:38:06

**Plot 16. 2Mbps, 2407MHz 30MHz-26.5GHz Spurious**



Date: 14.JAN.2020 09:32:25

**Plot 17. 2Mbps, 2453MHz 30MHz-26.5GHz Spurious**



Date: 14.JAN.2020 09:46:13

**Plot 18. 2Mbps, 2471MHz 30MHz-26.5GHz Spurious**


## 4.5 Out of Band Emissions: Restricted Band Edge

*Transmitter spurious emissions are emissions outside the frequency range of the equipment when the equipment is in transmitting mode; per requirement of CFR47 15.205, 15.209, 15.247(d), RSS-247 Sect. 5.5, RSS-GEN Sect. 8.9 and 8.10.*

### 4.5.1 Test Method

Radiated measurements per ANSI C63.10-2013 Section 6.10.5 were used to measure the undesirable emission requirement in restricted bands. Peak points were found and RMS Average was taken for each point found. The measurement was performed with modulation. This test was conducted on the upper and lower most channels in each mode on the EUT. The worst case measurement of each channel is recorded in this report. All channels were tested at highest power settings.

### Test Setup




The DUT was stimulated by manufacturer provided test software that is not available to the end user.

#### 4.5.2 Test Results


**Table 6: Emissions at the Band-Edge – Test Results**

| <b>Test Conditions: Radiated Measurement, Normal Temperature and Voltage</b> |                       |                          |                                |                          |                       |               |                |
|--|-----------------------|--------------------------|--------------------------------|--------------------------|-----------------------|---------------|----------------|
| <b>Lower Restricted Band Edge</b>  |                       |                          |                                |                          |                       |               |                |
| <b>Freq. (MHz)</b>   | <b>Mode/Data Rate</b> | <b>Center Freq (MHz)</b> | <b>Detector (Average/Peak)</b> | <b>Measured (dBuV/m)</b> | <b>Limit (dBuV/m)</b> | <b>Margin</b> | <b>Results</b> |
| 2342.867   | 2Mbps                 | 2407                     | Average                        | 39.04                    | 54                    | -14.96        | Pass           |
| 2343.164   | 2Mbps                 | 2407                     | Peak                           | 49.21                    | 74                    | -24.79        | Pass           |
| <b>Upper Restricted Band Edge</b>  |                       |                          |                                |                          |                       |               |                |
| <b>Freq. (MHz)</b>   | <b>Mode</b>           | <b>Center Freq (MHz)</b> | <b>Detector (Average/Peak)</b> | <b>Measured (dBuV/m)</b> | <b>Limit (dBuV/m)</b> | <b>Margin</b> | <b>Results</b> |
| 2535.152   | 2Mbps                 | 2471                     | Average                        | 40.17                    | 54                    | -13.83        | Pass           |
| 2535.210   | 2Mbps                 | 2471                     | Peak                           | 50.84                    | 74                    | -23.16        | Pass           |
| <b>Note:</b>   |                       |                          |                                |                          |                       |               |                |





**Plot 19.** 2Mbps, 2407MHz, Lower Band Edge, Restricted



**Plot 20.** 2Mbps, 2471MHz, Upper Band Edge, Restricted

---

## 4.6 Transmitter Spurious Emissions

*Transmitter spurious emissions are emissions outside the frequency range of the equipment when the equipment is in transmit mode; per requirement of CFR47 15.205, 15.209, 15.247(d), RSS 247 Sect.5.5, RSS-GEN Sect. 8.9 and 8.10.*

### 4.6.1 Test Methodology

#### 4.6.1.1 Preliminary Test

A test program that controls instrumentation and data logging was used to automate the preliminary RF emission test procedure. The frequency range of interest was divided into sub-ranges to yield a frequency resolution of approximately 120 kHz and provide a reading at each frequency for no more than 12° of turntable rotation. For each frequency sub-range the turntable was rotated 360° while peak emission data was recorded and plotted over the frequency range of interest in horizontal and vertical antenna polarization's.

Preliminary emission profile testing was performed inside the anechoic chamber. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm (<1 GHz) and 150cm (>1 GHz) above the floor. The EUT was positioned as shown in the setup photographs. The receiving antenna was placed at a distance of 3m at a fixed height of 1m. Measurement equipment was located outside of the chamber. A video camera was placed inside the chamber to view the EUT.

Pre-scans were performed to determine the worst data rate / chains.

#### 4.6.1.2 Final Test

For each frequency measured, the peak emission was maximized by manipulating the receiving antenna from 1 to 4 meters above the ground plane and placing it at the position that produced the maximum signal strength reading. The turntable was then rotated through 360° while observing the peak signal and placing the EUT at the position that produced maximum radiation. The six highest emissions relative to the limit were measured unless such emissions were more than 20 dB below the limit. If less than six emissions are within 20 dB of the limit, than the noise level of the receiver is measured at frequencies where emissions are expected. Multiples of all oscillator and microprocessor frequencies were also checked.

Final testing was performed on an NSA compliant test site. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm (<1 GHz) and 150cm (>1 GHz) above the ground plane. The placement of EUT and cables were the same as for preliminary testing and is shown in the setup photographs.


#### 4.6.1.3 Deviations

None.


#### 4.6.2 Test Setup

All tests were conducted at full power on low, middle, and high channels. The DUT was stimulated by manufacturer provided test software that is not available to the end user.

##### 30MHz-1GHz



##### 1-26GHz



### 4.6.3 Transmitter Spurious Emission Limit

The spurious emissions of the transmitter shall not exceed the values in CFR47 Part 15.205, 15.209: 2015 and RSS Gen Sect. 8.9 and 8.10: 2014.

| Frequency (MHz)  | Field strength (microvolts/meter) | Measurement distance (meters) |
|------------------|-----------------------------------|-------------------------------|
| 0.009-0.490..... | 2400/F (kHz)                      | 300                           |
| 0.490-1.705..... | 24000/F (kHz)                     | 30                            |
| 1.705-30.0.....  | 30                                | 30                            |
| 30-88.....       | 100 **                            | 3                             |
| 88-216.....      | 150 **                            | 3                             |
| 216-960.....     | 200 **                            | 3                             |
| Above 960.....   | 500                               | 3                             |

### 4.6.4 Test Results


The final measurement data was taken under the worst case operating modes, configurations, and/or cable positions. It also reflects the results including any modifications and/or special accessories listed in Sections 1.4 and test plan.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Worse case configurations/modes shown below, all plots taken using a peak detector in order to identify frequencies of interest. No emissions were observed below 30MHz or above 18GHz.


4.6.4.1 Plots

| Frequency (MHz) | QuasiPeak (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Meas. Time (ms) | Height (cm) | Pol   | Azimuth (deg) |
|-----------------|--------------------|----------------|-------------|-----------------|-------------|-------|---------------|
| 30.966264       | 18.92              | 40.00          | 21.08       | 100.0           | H           | -40.0 | 30.966264     |
| 64.726880       | 11.67              | 40.00          | 28.33       | 100.0           | V           | 10.0  | 64.726880     |
| 118.533800      | 14.74              | 43.52          | 28.78       | 200.0           | V           | 119.0 | 118.533800    |
| 378.761000      | 14.12              | 46.00          | 31.88       | 154.0           | V           | 18.0  | 378.761000    |
| 954.794560      | 26.78              | 46.00          | 19.22       | 101.0           | V           | -14.0 | 954.794560    |




Plot 35. 30MHz-1000MHz, 2Mbps, 2407MHz

| Frequency (MHz) | QuasiPeak (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Meas. Time (ms) | Height (cm) | Pol    | Azimuth (deg) |
|-----------------|--------------------|----------------|-------------|-----------------|-------------|--------|---------------|
| 30.101400       | 19.51              | 40.00          | 20.49       | 128.0           | H           | -118.0 | 30.101400     |
| 62.125000       | 11.40              | 40.00          | 28.60       | 101.0           | V           | -50.0  | 62.125000     |
| 374.575400      | 16.03              | 46.00          | 29.97       | 100.0           | H           | 60.0   | 374.575400    |
| 866.778880      | 24.46              | 46.00          | 21.54       | 128.0           | V           | -74.0  | 866.778880    |
| 954.627840      | 26.76              | 46.00          | 19.24       | 236.0           | V           | -164.0 | 954.627840    |




**Plot 36.** 30MHz-1000MHz, 2Mbps, 2453MHz

| Frequency (MHz) | QuasiPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol        | Azimuth (deg) |
|-----------------|--------------------|----------------|-------------|-----------------|-----------------|-------------|------------|---------------|
| 30.697000       | 19.07              | 40.00          | 20.93       | 288.0           | V               | -175.0      | 30.697000  | 19.07         |
| 119.079760      | 14.74              | 43.52          | 28.78       | 400.0           | V               | -83.0       | 119.079760 | 14.74         |
| 288.551040      | 15.31              | 46.00          | 30.69       | 101.0           | H               | -139.0      | 288.551040 | 15.31         |
| 311.894120      | 17.54              | 46.00          | 28.46       | 101.0           | H               | 129.0       | 311.894120 | 17.54         |
| 660.425840      | 16.79              | 46.00          | 29.21       | 100.0           | V               | -185.0      | 660.425840 | 16.79         |
| 956.831880      | 26.26              | 46.00          | 19.74       | 154.0           | V               | 36.0        | 956.831880 | 26.26         |



**Plot 37.** 30-1000MHz, 2Mbps, 2471MHz


| Frequency (MHz) | MaxPeak (dBµV/m) | Average (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) |
|-----------------|------------------|------------------|----------------|-------------|-----------------|-------------|-----|---------------|
| 1900.463000     | ---              | 20.42            | 54.00          | 33.58       | 1000.000        | 201.0       | V   | 180.0         |
| 1900.463000     | 33.21            | ---              | 74.00          | 40.79       | 1000.000        | 201.0       | V   | 180.0         |
| 4814.656500     | ---              | 46.98            | 54.00          | 7.02        | 1000.000        | 101.0       | H   | 34.0          |
| 4814.656500     | 54.43            | ---              | 74.00          | 19.57       | 1000.000        | 101.0       | H   | 34.0          |
| 7220.102000     | 41.74            | ---              | 74.00          | 32.26       | 1000.000        | 101.0       | H   | 4.0           |
| 7220.102000     | ---              | 29.95            | 54.00          | 24.05       | 1000.000        | 101.0       | H   | 4.0           |
| 9022.287000     | 43.87            | ---              | 74.00          | 30.13       | 1000.000        | 100.0       | H   | 180.0         |
| 9022.287000     | ---              | 30.56            | 54.00          | 23.44       | 1000.000        | 100.0       | H   | 180.0         |
| 12036.416000    | 48.17            | ---              | 74.00          | 25.83       | 1000.000        | 201.0       | V   | -72.0         |
| 12036.416000    | ---              | 35.88            | 54.00          | 18.12       | 1000.000        | 201.0       | V   | -72.0         |
| 17985.342000    | 48.14            | ---              | 74.00          | 25.86       | 1000.000        | 201.0       | V   | 121.0         |
| 17985.342000    | ---              | 34.83            | 54.00          | 19.17       | 1000.000        | 201.0       | V   | 121.0         |



**Plot 38.** 1-18GHz, 2Mbps, 2407MHz




| Frequency (MHz) | MaxPeak (dBµV/m) | Average (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) |
|-----------------|------------------|------------------|----------------|-------------|-----------------|-------------|-----|---------------|
| 1904.470500     | 33.56            | ---              | 74.00          | 40.44       | 1000.000        | 100.0       | V   | -81.0         |
| 1904.470500     | ---              | 20.78            | 54.00          | 33.22       | 1000.000        | 100.0       | V   | -81.0         |
| 2452.708500     | 39.30            | ---              | 74.00          | 34.70       | 1000.000        | 202.0       | V   | 115.0         |
| 2452.708500     | ---              | 33.53            | 54.00          | 20.47       | 1000.000        | 202.0       | V   | 115.0         |
| 4905.304000     | 48.65            | ---              | 74.00          | 25.35       | 1000.000        | 101.0       | H   | 13.0          |
| 4905.304000     | ---              | 39.16            | 54.00          | 14.84       | 1000.000        | 101.0       | H   | 13.0          |
| 8981.227000     | ---              | 30.72            | 54.00          | 23.28       | 1000.000        | 201.0       | H   | 163.0         |
| 8981.227000     | 43.96            | ---              | 74.00          | 30.04       | 1000.000        | 201.0       | H   | 163.0         |
| 12266.691000    | ---              | 38.23            | 54.00          | 15.77       | 1000.000        | 200.0       | V   | 145.0         |
| 12266.691000    | 49.90            | ---              | 74.00          | 24.10       | 1000.000        | 200.0       | V   | 145.0         |
| 17955.244500    | 46.02            | ---              | 74.00          | 27.98       | 1000.000        | 100.0       | V   | 135.0         |
| 17955.244500    | ---              | 33.21            | 54.00          | 20.79       | 1000.000        | 100.0       | V   | 135.0         |



Plot 39. 1-18GHz, 2Mbps, 2453MHz

| Frequency (MHz) | MaxPeak (dBµV/m) | Average (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) |
|-----------------|------------------|------------------|----------------|-------------|-----------------|-------------|-----|---------------|
| 1913.263000     | 34.08            | ---              | 74.00          | 39.92       | 1000.000        | 201.0       | H   | -101.0        |
| 1913.263000     | ---              | 21.02            | 54.00          | 32.98       | 1000.000        | 201.0       | H   | -101.0        |
| 2470.884500     | ---              | 31.28            | 54.00          | 22.72       | 1000.000        | 201.0       | H   | 180.0         |
| 2470.884500     | 36.81            | ---              | 74.00          | 37.19       | 1000.000        | 201.0       | H   | 180.0         |
| 4942.666500     | 44.59            | ---              | 74.00          | 29.41       | 1000.000        | 101.0       | H   | 16.0          |
| 4942.666500     | ---              | 34.92            | 54.00          | 19.08       | 1000.000        | 101.0       | H   | 16.0          |
| 7412.281500     | 43.52            | ---              | 74.00          | 30.48       | 1000.000        | 201.0       | V   | 101.0         |
| 7412.281500     | ---              | 32.04            | 54.00          | 21.96       | 1000.000        | 201.0       | V   | 101.0         |
| 13529.000500    | ---              | 32.91            | 54.00          | 21.09       | 1000.000        | 201.0       | V   | 159.0         |
| 13529.000500    | 45.75            | ---              | 74.00          | 28.25       | 1000.000        | 201.0       | V   | 159.0         |
| 17782.810000    | 47.91            | ---              | 74.00          | 26.09       | 1000.000        | 200.0       | V   | -180.0        |
| 17782.810000    | ---              | 34.88            | 54.00          | 19.12       | 1000.000        | 200.0       | V   | -180.0        |



Plot 40. 1-18GHz, 2Mbps, 2471MHz

## 4.7 AC Conducted Emissions

Testing was performed in accordance with ANSI C63.4: 2014. These test methods are listed under the laboratory's A2LA Scope of Accreditation.

This test measures the levels emanating from the EUT's AC input port, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices.

The AC conducted emissions of equipment under test shall not exceed the values in CFR47 Part 15.207 and RSS-GEN. Sect. 8.8.

### 4.7.1 Test Methodology

A test program that controls instrumentation and data logging was used to automate the AC Power Line Conducted emission test procedure. The frequency range of interest was divided into sub-ranges such as to yield a frequency resolution of 9 kHz. Each phase and neutral of the AC power line were measured with respect to ground. Measurements were performed using a set of 50µH / 50Ω LISNs.

Testing is performed in Lab1. The setup photographs clearly identify which site was used. The vertical ground plane used in the semi-anechoic chamber is a 2m x 2m solid aluminum frame and panel, and it is bonded to the horizontal ground plane.

In the case of tabletop equipment, the EUT is placed on a 1.0m x 1.5m non-conductive table 80cm above the ground plane and 40cm from a vertical ground reference plane. The rear of the EUT was positioned flush with the backside of the table and directly over the LISNs. The power and I/O cables were routed over the edge of the table and bundled approximately 40cm from the ground plane. Support equipment was powered from a separate LISN.

#### 4.7.1.1 Deviations

There were no deviations from this test methodology.

### 4.7.2 Test Results


As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

**Table 7: AC Conducted Emissions – Test Results**

| Test Conditions: Conducted Measurement at Normal Conditions only |                 |                         |
|--|-----------------|-------------------------|
| AC Power: 120 Vac/60 Hz  |                 | Configuration: Tabletop |
| Configuration  | Frequency Range | Test Result             |
| Line 1 (Live)  | 0.15 to 30 MHz  | Pass                    |
| Line 2 (Neutral)   | 0.15 to 30 MHz  | Pass                    |


4.7.2.1 Live Line

| Frequency MHz | Raw dBuV | Cable Loss | Factors dB | Level dBuV | Measurement Type | Line    | Limit dBuV | Margin dB | Pass /Fail |
|---------------|----------|------------|------------|------------|------------------|---------|------------|-----------|------------|
| 0.150272      | 22.08    | 11.18      | 0.09       | 33.35      | Quasi Peak       | Neutral | 65.98      | -32.63    | Pass       |
| 0.150272      | 4.81     | 11.18      | 0.09       | 16.08      | Average          | Neutral | 55.98      | -39.9     | Pass       |
| 0.156337      | 3.33     | 10.84      | 0.08       | 14.25      | Average          | Neutral | 55.66      | -41.41    | Pass       |
| 0.156337      | 21.77    | 10.84      | 0.08       | 32.69      | Quasi Peak       | Neutral | 65.66      | -32.97    | Pass       |
| 0.36814       | 15.22    | 10.1       | 0.04       | 25.36      | Average          | Neutral | 48.54      | -23.18    | Pass       |
| 0.36814       | 28.58    | 10.1       | 0.04       | 38.72      | Quasi Peak       | Neutral | 58.54      | -19.82    | Pass       |
| 3.985008      | 11.04    | 10.21      | 0.03       | 21.28      | Quasi Peak       | Neutral | 56         | -34.72    | Pass       |
| 3.985008      | -2.68    | 10.21      | 0.03       | 7.56       | Average          | Neutral | 46         | -38.44    | Pass       |
| 4.041178      | 2        | 10.21      | 0.03       | 12.24      | Average          | Neutral | 46         | -33.76    | Pass       |
| 4.041178      | 9.96     | 10.21      | 0.03       | 20.2       | Quasi Peak       | Neutral | 56         | -35.8     | Pass       |
| 13.426377     | -0.42    | 10.4       | -0.03      | 9.94       | Average          | Neutral | 50         | -40.06    | Pass       |
| 13.426377     | 10.99    | 10.4       | -0.03      | 21.36      | Quasi Peak       | Neutral | 60         | -38.64    | Pass       |



4.7.2.2 Neutral Line

| Frequency MHz | Raw dBuV | Cable Loss | Factors dB | Level dBuV | Measurement Type | Line    | Limit dBuV | Margin dB | Pass /Fail |
|---------------|----------|------------|------------|------------|------------------|---------|------------|-----------|------------|
| 0.153373      | 22.21    | 11         | 0.09       | 33.3       | Quasi Peak       | Neutral | 65.82      | -32.51    | Pass       |
| 0.153373      | 3.64     | 11         | 0.09       | 14.73      | Average          | Neutral | 55.82      | -41.09    | Pass       |
| 0.208052      | 4.27     | 10.21      | 0.07       | 14.55      | Average          | Neutral | 53.28      | -38.73    | Pass       |
| 0.208052      | 16.52    | 10.21      | 0.07       | 26.8       | Quasi Peak       | Neutral | 63.28      | -36.48    | Pass       |
| 0.216595      | 16.09    | 10.2       | 0.06       | 26.36      | Quasi Peak       | Neutral | 62.95      | -36.59    | Pass       |
| 0.216595      | 4.26     | 10.2       | 0.06       | 14.53      | Average          | Neutral | 52.95      | -38.42    | Pass       |
| 0.37022       | 24.16    | 10.1       | 0.04       | 34.31      | Quasi Peak       | Neutral | 58.5       | -24.19    | Pass       |
| 0.37022       | 11.78    | 10.1       | 0.04       | 21.92      | Average          | Neutral | 48.5       | -26.58    | Pass       |
| 3.853567      | -0.99    | 10.21      | 0.03       | 9.24       | Average          | Neutral | 46         | -36.76    | Pass       |
| 3.853567      | 8.88     | 10.21      | 0.03       | 19.12      | Quasi Peak       | Neutral | 56         | -36.88    | Pass       |
| 13.403309     | 3.72     | 10.4       | -0.03      | 14.08      | Average          | Neutral | 50         | -35.92    | Pass       |
| 13.403309     | 12.64    | 10.4       | -0.03      | 23         | Quasi Peak       | Neutral | 60         | -37       | Pass       |



## 5 Test Equipment List

### 5.1 Equipment List

| Equipment                   | Manufacturer    | Model #                  | Serial/Inst # | Last Cal<br>mm/dd/yyyy | Next Cal<br>mm/dd/yyyy |
|-----------------------------|-----------------|--------------------------|---------------|------------------------|------------------------|
| Spectrum Analyzer           | Rohde & Schwarz | FSU26.5                  | 200050        | 11/20/2019             | 11/20/2020             |
| EMI Receiver                | Rohde & Schwarz | ESW44                    | 101663-dv     | 07/18/2019             | 07/18/2021             |
| L.I.S.N.                    | Com-Power       | LI-215                   | 192000        | 01/16/2019             | 01/16/2021             |
| Transient Limiter           | Com-Power       | LIT-930                  | 531582        | 01/16/2019             | 01/16/2021             |
| Preamplifier, 9 kHz – 1 GHz | Sonoma          | 310N                     | 213221        | 01/16/2019             | 01/16/2021             |
| Bilog Antenna               | Sunol Sciences  | JB3                      | A060502       | 05/27/2018             | 05/27/2020             |
| Amplifier                   | Miteq           | TTA1800-30-HG            | 1842452       | 01/15/2019             | 01/15/2021             |
| Horn Antenna                | Sunol Sciences  | DRH-118                  | A040806       | 03/05/2019             | 03/05/2021             |
| Amplifier                   | HP              | 8449B                    | 3008A01013    | 01/15/2019             | 01/15/2021             |
| Horn Antenna                | EMCO            | RA42-K-F-B-C             | 020131-004    | 03/04/2019             | 03/04/2021             |
| Amplifier                   | Rohde & Schwarz | TS-PR26                  | 3545.7014.03  | 03/04/2019             | 03/04/2021             |
| Amplifier                   | Sonoma          | 310N                     | 185516        | N/A (See Note)         |                        |
| 1.6 GHz Low Pass Filter     | K&L Microwave   | 8L120-X1600-0/09135-0249 | UA691-35      | N/A (See Note)         |                        |
| 2.4GHZ Band Pass Filter     | Microtronics    | BRM50702                 | 009           | N/A (See Note)         |                        |

Note: Equipment is characterized before use.

## 6 EMC Test Plan

### 6.1 Introduction

This section provides a description of the Equipment Under Test (EUT), configurations, operating conditions, and performance acceptance criteria. It is an overview of information provided by the manufacturer so that the test laboratory may perform the requested testing.

### 6.2 Customer

**Table 8:** Customer Information

|                         |                                |
|-------------------------|--------------------------------|
| <b>Company Name</b>     | Hunter Douglas Window Fashions |
| <b>Address</b>          | One Duette Way                 |
| <b>City, State, Zip</b> | Broomfield, CO 80020           |
| <b>Country</b>          | USA                            |

**Table 9:** Technical Contact Information

|               |                                 |
|---------------|---------------------------------|
| <b>Name</b>   | Mike Rockwood                   |
| <b>E-mail</b> | mike.rockwood@hunterdouglas.com |

### 6.3 Equipment Under Test (EUT)

The information provided in the following table should be listed as it should appear in the final report. For those products that have only a model name, list the model number as *non-applicable* and vice-versa.

**Table 10:** EUT Designation

|                     |                                    |
|---------------------|------------------------------------|
| <b>Product Name</b> | Powerview Gen3 Motor Control Board |
| <b>Model Number</b> | 1012000217                         |

## 6.4 Product Specifications

**Table 11:** EUT Specifications

| <b>EUT Specifications</b>   |  |
|---|--|
| Environment   | Indoor/Outdoor   |
| Operating Temperature Range:  | 0-40°C   |
| Multiple Feeds:   | <input type="checkbox"/> Yes and how many<br><input checked="" type="checkbox"/> No  |
| Product Marketing Name (PMN)  | Powerview Gen3 Motor Control Board   |
| Hardware Version Identification Number (HVIN)   | 1012000217 RevB  |
| Firmware Version Identification Number (FVIN)   | --   |
| RF Software Version   | N/A  |
| Operating Modes   | Proprietary Mode, GFSK – 2MB/s   |
| Transmitter Frequency Band  | 2.4 GHz – 2.4835 GHz   |
| Power Setting @ Operating Channel   | See section 4.1.2.   |
| Modulation  | GFSK   |
| TX/RX Chain (s)   | SISO   |
| Type of Equipment   | <input type="checkbox"/> Table Top <input type="checkbox"/> Wall-mount <input type="checkbox"/> Floor standing cabinet<br><input checked="" type="checkbox"/> Other: |
| <b>Note:</b> EUT will be on / transmitted at all times with the highest power levels and antenna gains per channel. |  |



**Table 12: Antenna Information**

| Number    | Antenna Type | Description | Max Gain (dBi) |
|-----------|--------------|-------------|----------------|
| Antenna 0 | Flex PIFA    | GFSK, 2Mb/s | 1.58           |

**Table 13: Interface Specifications**

| Interface Type | Cabled with what type of cable? | Is the cable shielded? | Maximum potential length of the cable?             | Metallic (M), Coax (C), Fiber (F), or Not Applicable? |
|----------------|---------------------------------|------------------------|--|---|
| USB - Serial   | USB                             | No                     | <input checked="" type="checkbox"/> Metric: < 3.0m | N/A   |

**Table 14: Accessory Equipment**

| Equipment          | Manufacturer | Model           | Serial     | Comment           |
|--------------------|--------------|-----------------|------------|-------------------|
| AC/DC Power Supply | Amigo        | ADS0366-W180200 | 2989048000 | Output: 18VDC, 2A |
| <b>Note:</b> None  |              |                 |            |                   |

**Table 15: Ancillary Equipment (used for test purposes only)**

| Equipment            | Manufacturer | Model    | Serial | Used for  |
|----------------------|--------------|----------|--------|---|
| Laptop               | HP           | Pavilion | N/A    | Setup EUT operating channels via Serial connection to EUT                       |
| USB-Serial Interface | N/A          | N/A      | N/A    | Setup EUT operating channels via connection to EUT and USB Connection to Laptop |
| <b>Note:</b> None.   |              |          |        |   |

**Table 16:** Description of Sample used for Testing

| Device     | Serial | RF Connection             | CFR47 Part 15.247   |
|------------|--------|---------------------------|---|
| 1012000217 | N/A    | Integrated Antenna        | Radiated Emissions<br>Conducted Emissions                     |
|            |        | Direct via SMA Connection | Transmit Power, PSD, Occupied Bandwidth, Out of Band Emission |

**Table 17:** Description of Test Configuration used for Radiated Measurement.

| Device   | Antenna   | Mode     | Setup Photo (X-Axis) | Setup Photo (Y-Axis) | Setup Photo (Z-Axis) |
|--|-----------|----------|----------------------|----------------------|----------------------|
| 1012000217   | Flex PIFA | Transmit | EUT Flat             | EUT On Side          | EUT Upright          |
| <b>Note:</b> Worse case during radiated measurements were found when EUT was set on its “X-Axis”. All testing completed from this Axis (See Test setup for Images) |           |          |                      |                      |                      |

## 6.5 Test Specifications

**Table 18:** Test Specifications

| Emissions and Immunity   |             |
|--------------------------|-------------|
| Standard                 | Requirement |
| CFR 47 Part 15.247: 2019 | All         |
| RSS 247 Issue 2, 2017    | All         |

**END OF REPORT**