



RF EXPOSURE REPORT

REPORT NO.: SA970416H07

MODEL NO.: CTR500

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Cradlepoint, Inc

ADDRESS: 1199 Shoreline Lane, Suite 301 Boise, ID 83702

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien,
Taiwan, R.O.C.



RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	6
1500-100,000	1.0	30

F = Frequency in MHz

3. Friis Formula

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, $1 mW/cm^2$. If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,
Page 640, Eq. (11-133).

4. EUT Operating condition

The software provided by client enabled the EUT to transmit and receive data at specific channel frequencies individually.

5. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**



6. Test Results

6.1 Antenna Gain

1. There are two printed antennas provided to this EUT, and the following two dipole antennas are option:

Antenna	Antenna Type	Antenna Connector	Gain (dBi)	Function	Note
Antenna 1	Printed	NA	1	Only RX	Fixed
Antenna 2	Printed	I-PEX	1	TX / RX	
Antenna 3	Dipole	MMCX	2		
Antenna 4	Dipole	MMCX	5		For Option

6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

For Part 802.11b with Dipole antenna

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	53.703	0.034	1.0
6	2437	18.621	0.012	1.0
11	2462	26.915	0.017	1.0

For Part 802.11g with Dipole antenna

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	53.703	0.034	1.0
6	2437	56.234	0.035	1.0
11	2462	60.256	0.038	1.0

For Part 802.11b with Printed antenna

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	53.703	0.013	1.0
6	2437	18.621	0.005	1.0
11	2462	26.915	0.007	1.0

For Part 802.11g with Printed antenna

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	53.703	0.013	1.0
6	2437	56.234	0.014	1.0
11	2462	60.256	0.015	1.0

1x EV-Do :

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1013	824.7	724.436	0.256	0.5498

NOTE: Limit of power density = 824.7 (MHz) / 1500 = 0.5498.

CONCLUSION:

Both of the WLAN and GSM can transmit simultaneously, the formula of calculated the MPE is:

$$CPD_1 / LPD_1 + CPD_2 / LPD_2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is $0.256 / 0.5498 + 0.038 / 1 = 0.50362$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.