

RF Exposure Report

Report No.: SA200121E05A

FCC ID: UXX-S5A103A

Test Model: S5A103A

Series Model: S5A108A

Received Date: Aug. 26, 2020

Test Date: Sep. 26, 2020

Issued Date: Nov. 19, 2020

Applicant: Cradlepoint, Inc.

Address: 1111 West Jefferson Street ,Boise ,Idaho,United States 83702

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	8
Appendix	9

Release Control Record

Issue No.	Description	Date Issued
SA200121E05A	Original release.	Nov. 19, 2020

1 Certificate of Conformity

Product: 5G Adapter
Brand: Cradlepoint, Inc.
Test Model: S5A103A
Series Model: S5A108A
Sample Status: ENGINEERING SAMPLE
Applicant: Cradlepoint, Inc.
Test Date: Sep. 26, 2020
Standards: FCC Part 2 (Section 2.1091)
IEEE C95.3 -2002
References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Nov. 19, 2020
Claire Kuan / Specialist

Approved by :  , **Date:** Nov. 19, 2020
Clark Lin / Technical Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 38 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

For Model: S5A108A					
Antenna No.	Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type	Cable Length
Ant 1	2.47	2.4~2.4835 GHz	Dipole	R-SMA	170mm
	2.18	5.15~5.25 GHz			
	2.47	5.725~5.85 GHz			
Ant 2	2.47	2.4~2.4835 GHz	Dipole	R-SMA	170mm
	2.18	5.15~5.25 GHz			
	2.47	5.725~5.85 GHz			
Ant 3	2.47	2.4~2.4835 GHz	Dipole	R-SMA	170mm
	2.18	5.15~5.25 GHz			
	2.47	5.725~5.85 GHz			
Ant 4	2.47	2.4~2.4835 GHz	Dipole	R-SMA	170mm
	2.18	5.15~5.25 GHz			
	2.47	5.725~5.85 GHz			
LTE Ant 1 (GPS)	2.5	700~960 MHz	Dipole	N-Type	-
	2.2	1428~1600 MHz			
	4.3	1700~2700 MHz			
	4.6	3300~3700 MHz			
	6.1	5150~5925 MHz			
LTE Ant 2	2.5	700~960 MHz			
	2.2	1428~1600 MHz			
	4.3	1700~2700 MHz			
	4.6	3300~3700 MHz			
	6.1	5150~5925 MHz			
LTE Ant 3	2.5	700~960 MHz			
	2.2	1428~1600 MHz			
	4.3	1700~2700 MHz			
	4.6	3300~3700 MHz			
	6.1	5150~5925 MHz			
LTE Ant 4	2.5	700~960 MHz			
	2.2	1428~1600 MHz			
	4.3	1700~2700 MHz			
	4.6	3300~3700 MHz			
	6.1	5150~5925 MHz			

For Model: S5A103A

Antenna No.	Antenna Net Gain (dBi)	Frequency Range	Antenna Type	Connector Type	Cable Length
Ant 1	2.54	2.4~2.4835 GHz	PIFA	i-pex(MHF)	74 mm
	5.16	5.15~5.25 GHz			
	5.65	5.725~5.85 GHz			
Ant 2	2.38	2.4~2.4835 GHz	PIFA	i-pex(MHF)	91 mm
	5.2	5.15~5.25 GHz			
	5.18	5.725~5.85 GHz			
Ant 3	3.59	2.4~2.4835 GHz	PIFA	i-pex(MHF)	197 mm
	5.96	5.15~5.25 GHz			
	5.71	5.725~5.85 GHz			
Ant 4	1.88	2.4~2.4835 GHz	PIFA	i-pex(MHF)	288 mm
	5.09	5.15~5.25 GHz			
	5.75	5.725~5.85 GHz			
LTE Ant 1 (GPS)	1.42	619~960 MHz	Dipole	SMA	-
	0.88	1445~1515 MHz			
	2.69	1710~2700 MHz			
	4.13	3400~3700 MHz			
	4.29	5150~5925 MHz			
LTE Ant 2	1.42	619~960 MHz			
	0.88	1445~1515 MHz			
	2.69	1710~2700 MHz			
	4.13	3400~3700 MHz			
	4.29	5150~5925 MHz			
LTE Ant 3	1.42	619~960 MHz			
	0.88	1445~1515 MHz			
	2.69	1710~2700 MHz			
	4.13	3400~3700 MHz			
	4.29	5150~5925 MHz			
LTE Ant 4	1.42	619~960 MHz			
	0.88	1445~1515 MHz			
	2.69	1710~2700 MHz			
	4.13	3400~3700 MHz			
	4.29	5150~5925 MHz			

Note: Max. gain was selected for the final test, except for the radiated emissions test.

* The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.5 Calculation Result of Maximum Conducted Power

For WLAN:

Operation Mode	Evaluation Frequency (MHz)	Max Power Average (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2412~2462	616.167	8.64	38	0.24827	1
WLAN 5GHz U-NII-1	5180-5240	30.022	11.38	38	0.02273	1
WLAN 5GHz U-NII-3	5745-5825	745.572	11.60	38	0.59390	1

NOTE:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- 2.4GHz: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 8.64\text{dBi}$
- 5GHz_U-NII-1: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.38\text{dBi}$
- 5GHz_U-NII-3: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.60\text{dBi}$

For WWAN < Worst Case > FCC ID: N7NEM91

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
LTE B41-HP	2498.5~2687.5	398.107	4.30	38	0.05905	1

Conclusion:

The formula of calculated the MPE is:

$$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$\text{WLAN 2.4GHz} + \text{WLAN 5GHz} + \text{WWAN} = 0.24827 / 1 + 0.59390 / 1 + 0.05905 / 1 = 0.90122$$

Therefore the maximum calculations of above situations are less than the “1” limit.

Appendix

WWLAN module

MPE Evaluation for FCC ID: N7NEM91 Module

Mode	Equipment Category	Transmitter Range (MHz)		Maximum		Antenna Gain (dBi)	Power Density (mW/cm ²)		Ratio
		Start	Stop	(dBm)	(W)		Vaule	Limit	
UMTS	Band II	1852.4	1907.6	24.5	0.2818	4.3	0.0418	1	0.04180
	Band IV	1712.4	1752.6	24.5	0.2818	4.3	0.0418	1	0.04180
	Band V	826.4	846.6	24.5	0.2818	2.5	0.02762	0.5509	0.05014
LTE	Band 2	1850.7	1909.3	24	0.2512	4.3	0.03726	1	0.03726
	Band 4	1710.7	1754.3	24	0.2512	4.3	0.03726	1	0.03726
	Band 5	824.7	848.3	24	0.2512	2.5	0.02462	0.5498	0.04478
	Band 7	2502.5	2567.5	24	0.2512	4.3	0.03726	1	0.03726
	Band 12	699.7	715.3	24	0.2512	2.5	0.02462	0.4664	0.05279
	Band 13	779.5	784.5	24	0.2512	2.5	0.02462	0.5196	0.04738
	Band 14	790.5	795.5	24	0.2512	2.5	0.02462	0.527	0.04672
	Band 17	706.5	713.5	24	0.2512	2.5	0.02462	0.471	0.05227
	Band 25	1850.7	1914.3	24	0.2512	4.3	0.03726	1	0.03726
	Band 26	824.7	848.3	24	0.2512	2.5	0.02462	0.5498	0.04478
	Band 30	2307.5	2312.5	24	0.2512	4.3	0.03726	1	0.03726
	Band 38	2572.5	2617.5	24.8	0.302	4.3	0.04479	1	0.04479
	Band 41	2498.5	2687.5	24.8	0.302	4.3	0.04479	1	0.04479
	Band 41-HP	2498.5	2687.5	26	0.3981	4.3	0.05905	1	0.05905
	Band 42	3552.5	3597.5	24.8	0.302	4.6	0.048	1	0.04800
	Band 48	3552.5	3697.5	24.8	0.302	4.6	0.048	1	0.04800
Band 66	1710.7	1779.3	24	0.2512	4.3	0.03726	1	0.03726	
Band 71	665.5	695.5	24	0.2512	2.5	0.02462	0.4436	0.05550	
5G NR	nBand 2	1852.4	1907.6	24	0.2512	4.3	0.03726	1	0.03726
	nBand 5	826.5	846.5	24	0.2512	2.5	0.02462	0.551	0.04468
	nBand 41	2506.02	2679.99	24	0.2512	4.3	0.03726	1	0.03726
	nBand 66	1712.5	1777.5	24	0.2512	4.3	0.03726	1	0.03726
	nBand 71	665.5	695.5	24	0.2512	2.5	0.02462	0.4436	0.05550

--- END ---