

FCC SAR TEST REPORT

FCC ID : UZ7-ET85C
Equipment : 2 in 1 Tablet PC with Windows OS
Brand Name : Zebra
Model Name : ET85C
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC 47 CFR Part 2 (2.1093)

The product was received on Sep. 07, 2021 and testing was started from May 25, 2022 and completed on May 25, 2022. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample provide by manufacturer and the test data has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been pass the FCC requirement.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



Sporton International Inc. EMC & Wireless Communications Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan



Table of Contents

1. Statement of Compliance	4
2. Equipment Under Test (EUT) Information	5
2.1 General Information	5
3. Guidance Applied	6
3.1 General LTE SAR Test and Reporting Considerations	7
3.2 General 5G NR SAR Test and Reporting Considerations	10
3.3 Antenna switched capabilities of this device	12
4. Proximity Sensor Triggering Test	13
5. Smart Transmit feature for RF Exposure compliance	22
6. RF Exposure Limits	25
6.1 Uncontrolled Environment	25
6.2 Controlled Environment	25
7. Specific Absorption Rate (SAR)	26
7.1 Introduction	26
7.2 SAR Definition	26
8. System Description and Setup	27
8.1 Test Site Location	27
8.2 E-Field Probe	28
8.3 Data Acquisition Electronics (DAE)	28
8.4 Phantom	29
8.5 Device Holder	30
9. Measurement Procedures	31
9.1 Spatial Peak SAR Evaluation	31
9.2 Power Reference Measurement	32
9.3 Area Scan	32
9.4 Zoom Scan	33
9.5 Volume Scan Procedures	33
9.6 Power Drift Monitoring	33
10. Test Equipment List	34
11. System Verification	35
11.1 Tissue Verification	35
11.2 System Performance Check Results	35
12. RF Exposure Positions	35
12.1 SAR Testing for Tablet	35
13. 5G NR Output Power (Unit: dBm)	36
14. Antenna Location	39
15. SAR Test Results	41
15.1 Body SAR	42
15.2 FR1 n77 Power Class 2 and Power Class 3 Linearity	42
16. Simultaneous Transmission Analysis	43
16.1 5G NR + LTE + WLAN + BT Sim-Tx analysis	43
16.2 Body Exposure Conditions	44
16.3 SPLSR Evaluation and Analysis	46
17. Uncertainty Assessment	52
18. References	52
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA162602-04	01	Initial issue of report	Jun. 14, 2022

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Zebra Technologies Corporation, 2 in 1 Tablet PC with Windows OS, ET85C, are as follows.

Equipment Class	Frequency Band		Highest SAR Summary	Highest Simultaneous Transmission 1g SAR (W/kg)
			Body (Separation 0mm)	
			1g SAR (W/kg)	
Licensed	WCDMA	WCDMA II	0.49	1.58
		WCDMA IV	0.50	
		WCDMA V	1.18	
	LTE	LTE Band 7	0.65	
		LTE Band 12	1.18	
		LTE Band 13	1.19	
		LTE Band 14	1.18	
		LTE Band 2 / 25	0.54	
		LTE Band 5 / 26	1.18	
		LTE Band 30	0.51	
		LTE Band 38 / 41	0.55	
		LTE Band 48	0.61	
		LTE Band 4 / 66	0.49	
		LTE Band 71	1.18	
	FR1	FR1 n5	1.19	
		FR1 n7	0.48	
		FR1 n12	1.20	
		FR1 n2 / n25	0.50	
		FR1 n41	1.01	
		FR1 n66	0.50	
		FR1 n71	1.18	
		FR1 n77	0.47	
DTS	WLAN	2.4GHz WLAN	0.55	1.58
NII		5GHz WLAN	0.69	1.50
DSS	2.4GHz Band	Bluetooth	0.19	1.50
Date of Testing:			2022/5/25	

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: Jason Wang

Report Producer: Carlie Tsai

2. Equipment Under Test (EUT) Information

2.1 General Information

Product Feature & Specification	
Equipment Name	2 in 1 Tablet PC with Windows OS
Brand Name	Zebra
Model Name	ET85C
FCC ID	UZ7-ET85C
Integrated WWAN Module	Brand Name: Quectel Model Name: RM505Q-AE
Integrated WLAN Module	Brand Name: Intel Model Name: AX210NGW
Wireless Technology and Frequency Range	WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 30: 2305 MHz ~ 2315 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 48: 3550 MHz ~ 3700 MHz LTE Band 66: 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz 5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n7 : 2500 MHz ~ 2570 MHz 5G NR n12 : 699 MHz ~ 716 MHz 5G NR n25 : 1850 MHz ~ 1915 MHz 5G NR n41 : 2496 MHz ~ 2690 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz 5G NR n71 : 663 MHz ~ 698 MHz 5G NR n77: 3700 MHz ~ 3980 MHz, 3450MHz ~ 3550MHz WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2 GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3 GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6 GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8 GHz Band: 5725 MHz ~ 5850 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz
Mode	RMC 12.2Kbps HSDPA HSUPA DC-HSDPA LTE: QPSK, 16QAM, 64QAM, 256QAM 5G NR: DFT-s-OFDM/CP-OFDM, Pi/2 BPSK/QPSK/16QAM/64QAM/256QAM WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE NFC: ASK
HW Version	DV
SW Version	Windows 10 Pro
FW Version	TLX09
MFD	2021/Feb.
EUT Stage	Identical Prototype
Remark: 1. Based on original SAR Report to extend 5G FR1 n77 frequency range for part27Q, other transmit band refer to Sporton SAR report no.: FA162602 and the result used perform Sim-Tx analysis. 2. Since this filing just enable n77 frequency range, n77 Plimit was not change, according to Qualcomm Smart Transmit procedure the part2 validation was not necessary, therefore, the part 2 validation refer to original report no.: FA162602	

Accessories Information				
Adaptor with CLA cable	Brand Name	Zebra	Model Number	ADP-45XE B
Battery	Brand Name	ZEBRA	Model Number	BT-000433
Power cord	Brand Name	Zebra	Model Number	450040

Support unit				
CAC Reader	Brand Name	Zebra	Model Number	ZBK-ET8X-SMARTCARD-01
Keyboard	Brand Name	Zebra	Model Number	KBD-ET8X

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards, the below KDB standard may not including in the TAF code without accreditation.

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A Rel.10 LTE SAR Test Guidance v01r02

3.1 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05								
FCC ID	UZ7-ET85C							
Equipment Name	2 in 1 Tablet PC with Windows OS							
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850 MHz ~ 1910 MHz							
	LTE Band 4: 1710 MHz ~ 1755 MHz							
	LTE Band 5: 824 MHz ~ 849 MHz							
	LTE Band 7: 2500 MHz ~ 2570 MHz							
	LTE Band 12: 699 MHz ~ 716 MHz							
	LTE Band 13: 777 MHz ~ 787 MHz							
	LTE Band 14: 788 MHz ~ 798 MHz							
	LTE Band 25: 1850 MHz ~ 1915 MHz							
	LTE Band 26: 814 MHz ~ 849 MHz							
	LTE Band 30: 2305 MHz ~ 2315 MHz							
	LTE Band 38: 2570 MHz ~ 2620 MHz							
	LTE Band 41: 2496 MHz ~ 2690 MHz							
	LTE Band 48: 3550 MHz ~ 3700 MHz							
	LTE Band 66: 1710 MHz ~ 1780 MHz							
LTE Band 71: 663 MHz ~ 698 MHz								
Channel Bandwidth	LTE Band 2:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz							
	LTE Band 4:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz							
	LTE Band 5:1.4MHz, 3MHz, 5MHz, 10MHz							
	LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz							
	LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz							
	LTE Band 13: 5MHz, 10MHz							
	LTE Band 14: 5MHz, 10MHz							
	LTE Band 25:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz							
	LTE Band 26:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz							
	LTE Band 30: 5MHz, 10MHz							
	LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz							
	LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz							
	LTE Band 48: 5MHz, 10MHz, 15MHz, 20MHz							
	LTE Band 66:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz							
LTE Band 71: 5MHz, 10MHz, 15MHz, 20MHz								
uplink modulations used	QPSK / 16QAM / 64QAM / 256QAM							
LTE Voice / Data requirements	Data only							
LTE MPR permanently built-in by design	Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3							
	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)
		1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
	256 QAM	≥ 1						≤ 5
	LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)						
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							
Power reduction applied to satisfy SAR compliance	Yes, Proximity Sensor.							
LTE Carrier Aggregation Combinations	Inter-Band and Intra-Band possible combinations and the detail power measurement please referred to original report, report no.: FA162602.							
LTE Carrier Aggregation Additional Information	This device supports maximum of 3 carriers in the downlink and 2 carriers in the uplink. Additional following LTE Release features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.							

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510				
M	21100	2535	21100	2535	21100	2535	21100	2535				
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560				
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 13												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)		Channel #		Freq.(MHz)	
L	23205		779.5		23230		782					
M	23230		782									
H	23255		784.5									
LTE Band 14												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Channel #		Channel #		Freq.(MHz)		Channel #		Freq.(MHz)	
L	23305		790.5		23330		793					
M	23330		793									
H	23355		795.5									
LTE Band 25												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26047	1850.7	26055	1851.5	26065	1852.5	26090	1855	26115	1857.5	26140	1860
M	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880
H	26683	1914.3	26675	1913.5	26665	1912.5	26640	1910	26615	1907.5	26590	1905

LTE Band 26												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26765	821.5		
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5		
H	27033	848.3	27025	847.5	27015	846.5	26990	844	26965	841.5		
LTE Band 30												
	Bandwidth 5 MHz					Bandwidth 10 MHz						
	Channel #		Freq.(MHz)			Channel #		Freq.(MHz)				
L	27685		2307.5			27710		2310				
M	27710		2310									
H	27735		2312.5									
LTE Band 38												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	37775	2572.5	37800	2575	37825	2577.5	37850	2580				
M	38000	2595	38000	2595	38000	2595	38000	2595				
H	38225	2617.5	38200	2615	38175	2612.5	38150	2610				
LTE Band 41												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	39675	2498.5	39700	2501	39725	2503.5	39750	2506				
L M	40148	2545.8	40160	2547	40173	2548.3	40185	2549.5				
M	40620	2593	40620	2593	40620	2593	40620	2593				
H M	41093	2640.3	41080	2639	41068	2637.8	41055	2636.5				
H	41565	2687.5	41540	2685	41515	2682.5	41490	2680				
LTE Band 48												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	55265	3552.5	55290	3555	55315	3557.5	55340	3560				
L M	55810	3607	55815	3607.5	55820	3608	55830	3609				
M H	56170	3643	56165	3642.5	56160	3642	56150	3641				
H	56715	3697.5	56690	3695	56665	3692.5	56640	3690				
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770
LTE Band 71												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	133147	665.5	133172	668	133197	670.5	133222	673				
M	133297	680.5	133297	680.5	133297	680.5	133297	680.5				
H	133447	695.5	133422	693	133397	690.5	133372	688				



3.2 General 5G NR SAR Test and Reporting Considerations

5G NR Information								
FCC ID	UZ7-ET85C							
Equipment Name	2 in 1 Tablet PC with Windows OS							
Operating Frequency Range of each 5G NR transmission band	5G NR n2: 1850 MHz ~ 1910 MHz 5G NR n5: 824 MHz ~ 849 MHz 5G NR n7: 2500 MHz ~ 2570 MHz 5G NR n12: 699 MHz ~ 716 MHz 5G NR n25: 1850 MHz ~ 1915 MHz 5G NR n41: 2496 MHz ~ 2690 MHz 5G NR n66: 1710 MHz ~ 1780 MHz 5G NR n71: 663 MHz ~ 698 MHz 5G NR n77: 3700 MHz ~ 3980 MHz, 3450MHz ~ 3550MHz							
Channel Bandwidth	5G NR n2: 5MHz, 10MHz, 15MHz, 20MHz 5G NR n5: 5MHz, 10MHz, 15MHz, 20MHz 5G NR n7: 5MHz, 10MHz, 15MHz, 20MHz 5G NR n12: 5MHz, 10MHz, 15MHz 5G NR n25: 5MHz, 10MHz, 15MHz, 20MHz 5G NR n41: 20MHz, 30MHz, 40MHz, 50MHz, 60MHz, 80MHz, 100MHz 5G NR n66: 5MHz, 10MHz, 15MHz, 20MHz 5G NR n71: 5MHz, 10MHz, 15MHz, 20MHz 5G NR n77: 100MHz							
SCS	FDD: SCS15KHz, TDD: SCS30KHz							
uplink modulations used	DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM CP-OFDM QPSK / 16QAM / 64QAM / 256QAM							
A-MPR (Additional MPR) disabled for SAR Testing?	Yes							
LTE Anchor Bands for n2	LTE B5/12/13							
LTE Anchor Bands for n5	LTE B2/30/66							
LTE Anchor Bands for n7	LTE B5/12							
LTE Anchor Bands for n12	LTE B2							
LTE Anchor Bands for n25	LTE B12							
LTE Anchor Bands for n41	LTE B2/25/26/66							
LTE Anchor Bands for n66	LTE B5/12/13/14/71							
LTE Anchor Bands for n71	LTE B2/7/66							
NR Band 2								
	Bandwidth 5MHz		Bandwidth 10MHz		Bandwidth 15MHz		Bandwidth 20MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	370500	1852.5	371000	1855	371500	1857.5	372000	1860
M	376000	1880	376000	1880	376000	1880	376000	1880
H	381500	1907.5	381000	1905	380500	1902.5	380000	1900
NR Band 5								
	Bandwidth 5MHz		Bandwidth 10MHz		Bandwidth 15MHz		Bandwidth 20MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	165300	826.5	165800	829	166300	831.5	166800	834
M	167300	836.5	167300	836.5	167300	836.5	167300	836.5
H	169300	846.5	168800	844	168300	841.5	167800	839
NR Band 7								
	Bandwidth 5MHz		Bandwidth 10MHz		Bandwidth 15MHz		Bandwidth 20MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	500500	2502.5	501000	2505	501500	2507.5	502000	2510
M	507000	2535	507000	2535	507000	2535	507000	2535
H	513500	2567.5	513000	2565	512500	2562.5	512000	2560

NR Band 12															
	Bandwidth 5MHz				Bandwidth 10MHz				Bandwidth 15MHz						
	Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)		Ch. #			Freq. (MHz)			
L	140300		701.5		140800		704		141300			706.5			
M	141500		707.5		141500		707.5		141500			707.5			
H	142700		713.5		142200		711		141700			708.5			
NR Band 25															
	Bandwidth 5MHz				Bandwidth 10MHz				Bandwidth 15MHz				Bandwidth 20MHz		
	Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)
L	370500		1852.5		371000		1855		371500		1857.5		372000		1860
M	376500		1882.5		376500		1882.5		376500		1882.5		376500		1882.5
H	382500		1912.5		382000		1910		381500		1907.5		381000		1905
NR Band 41															
	Bandwidth20MHz			Bandwidth 30MHz		Bandwidth 40MHz		Bandwidth 50MHz		Bandwidth 60MHz		Bandwidth 80MHz		Bandwidth100MHz	
	Ch. #	Freq. (MHz)		Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	501204	2506.02		502200	2511	503202	2516.01	504204	2521.02	505200	2526	507204	2536.02	509202	2546.01
M	518598	2592.99		518598	2592.99	518598	2592.99	518598	2592.99	518598	2592.99	518598	2592.99	518598	2592.99
H	535998	2679.99		534996	2674.98	534000	2670	532998	2664.99	531996	2659.98	529998	2649.99	528000	2640
NR Band 66															
	Bandwidth 5MHz				Bandwidth 10MHz				Bandwidth 15MHz				Bandwidth 20MHz		
	Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)
L	342500		1712.5		343000		1715		343500		1717.5		344000		1720
M	349000		1745		349000		1745		349000		1745		349000		1745
H	355500		1777.5		355000		1775		354500		1772.5		354000		1770
NR Band 71															
	Bandwidth 5MHz				Bandwidth 10MHz				Bandwidth 15MHz				Bandwidth 20MHz		
	Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)
L	133100		665.5		133600		668		13410		670.5		134600		673
M	136100		680.5		136100		680.5		136100		680.5		136100		680.5
H	139100		695.5		138600		693		13810		690.5		137600		688
NR Band 77(3700MHz ~ 3980MHz)															
	Bandwidth100MHz														
	Ch. # Freq. (MHz)														
L	650000								3750						
M	656000								3840						
H	662000								3930						
NR Band 77(3450MHz ~ 3550MHz)															
	Bandwidth100MHz														
	Ch. #								Freq. (MHz)						
L															
M	633332								3499.98						
H															

3.3 Antenna switched capabilities of this device

<Pin Definition of Antenna Interfaces>

Transmit Antenna	Description	Transmit Frequency
MIMO1	5G NR: MHB_TRX & n41 TRX1 ¹⁾ & n77/n78/n79_PRX MIMO; LTE: MHB_TRX & UHB_PRX MIMO ²⁾ WCDMA: MHB_TRX	1400 – 5000 MHz
Main	5G NR: LB_TRX & MHB_DRX MIMO & n41_DRX1 ¹⁾ & n77/n78/n79_DRX MIMO LTE: LB_TRX & MHB_DRX MIMO & UHB_DRX MIMO ²⁾ & LAA PRX WCDMA: LB_TRX	600 – 6000 MHz
Aux	5G NR: LB_DRX & MHB_PRX MIMO & n41 TRX0 ¹⁾ & n77/n78/n79_TRX LTE: LB_DRX & MHB_PRX MIMO & UHB_TRX ²⁾ WCDMA: LB_DRX	600 – 5000 MHz

<Antenna Mapping>

Transmit Antenna	WCDMA	LTE	5G NR Reframed	n41	n77	LB (MHz)	MHB (MHz)	n77 (MHz)
MIMO1	MHB_TRX	MHB_TRX, UHB_PRX ¹ MIMO	MHB_TRX, UHB_PRX ¹ MIMO	TRX1 ²	PRX MIMO	-	1452-2690	3300-4200
Main	LB_TRX	LB_TRX, MHB_DRX MIMO, UHB_PRX ¹ MIMO, LAA PRX	LB_TRX, MHB_DRX MIMO, UHB_DRX ¹ MIMO	DRX1 ²	DRX MIMO	617-960	1452-2690	3300-4200
Aux	LB_DRX	LB_DRX, MHB_PRX MIMO, UHB_TRX ¹	LB_DRX, MHB_PRX MIMO, UHB_TRX ¹	TRX0 ²	TRX	617-960	1452-2690	3300-4200

Remark:

1. UHB frequency range: 3400–3800 MHz
2. NR TRX1 = TX MIMO + PRX MIMO; NR DRX1 = DRX MIMO


4. Proximity Sensor Triggering Test

<Proximity Sensor Triggering Distance (KDB 616217 D04 section 6.2)>:

For the device is fully integrated, touch sensing capacitive sensor. It uses a charge transfer capacitive acquisition method that is capable of near range proximity detection. In this device offers a state of the art capacitive sensing engine with an embedded sampling capacitor and voltage regulator allowing the overall solution cost to be reduced and improving system immunity in noisy environments.

Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed. The details are illustrated as following, and the shortest triggering distances were reported and used for SAR assessment.

In the preliminary triggering distance testing, the tissue-equivalent medium for different frequency bands were used for verification; no other frequency bands tissue-equivalent medium was found to result in shortest triggering distance than that for 1900MHz, and the tissue-equivalent medium for 1900MHz was used for formal proximity sensor triggering testing.




Proximity Sensor Trigger Distance (mm)												
Antenna	Main				MIMO 1				Aux			
Position	Bottom Face		Edge 1		Bottom Face		Edge 1		Bottom Face		Edge 4	
Minimum	Moving toward	Moving away	Moving toward	Moving away	Moving toward	Moving away	Moving toward	Moving away	Moving toward	Moving away	Moving toward	Moving away
	30	36	23	28	38	44	32	33	16	19	25	29

<Proximity Sensor Triggering Coverage (KDB 616217 D04 section 6.3)>:

Since the antenna and sensor are collocated and all of the peak SAR location is overlapping with the sensor pad for this device, therefore, According to KDB 616217 section6.3, these procedures do not apply and are not required for this device. Due to the antenna and sensor are collocated and the peak SAR location is overlapping with the sensor on this device.

<Tablet Tilt angle influences to proximity sensor triggering (KDB 616217 D04 section 6.4)>:

The influence of table tilt angles to proximity sensor triggering was determined by positioning each tablet edge that contains a transmitting antenna, perpendicular to the flat phantom, at above separation distance. Rotating the tablet around the edge next to the phantom in $\leq 10^\circ$ increments until the tablet is $\pm 45^\circ$ from the vertical position at 0° , and the maximum output power remains in the reduced mode.





The Sensor Trigger Distance (mm)						
Position	Edge 1_Main		Edge 1_MIMO 1		Edge 4_Aux	
Minimum	+45	-45	+45	-45	+45	-45
	23	23	32	32	25	25

Proximity sensor power reduction


Exposure Position		Reduce Level (dB)
wireless mode	Antenna	Bottom Face/ Edge 1/ Edge 4 ⁽¹⁾
WCDMA II	MIMO 1	13.10
WCDMA IV	MIMO 1	13.20
WCDMA V	Main	3.40
LTE B2/25	MIMO 1	12.90
LTE B66/4	MIMO 1	13.00
LTE B26/5	Main	3.50
LTE B7	MIMO 1	12.90
LTE B12	Main	2.90
LTE B13	Main	3.60
LTE B14	Main	3.50
LTE B30	MIMO 1	11.70
LTE B41/38(PC3)	MIMO 1	12.30
LTE B41/38(PC2)	MIMO 1	11.90
LTE B48	AUX	7.30
LTE B71	Main	2.20
n5	Main	3.70
n7	MIMO 1	11.30
n12	Main	2.70
n25/n2	MIMO 1	12.90
n41	MIMO 1	8.60
n41 HPUE	MIMO 1	7.60
n41	AUX	11.00
n41 HPUE	AUX	10.00
n66	MIMO 1	12.60
n71	Main	2.50
n77	AUX	9.30
n77 HPUE	AUX	8.30

Remark:


- ⁽¹⁾: Reduced maximum limit applied by activation of proximity sensor.
- Tests were performed in accordance with KDB 616217 D04 section 6.1, 6.2, 6.3, 6.4 and 6.5 and compliant results are shown as below
- For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed:
 - MIMO 1**
 - Bottom Face: [37 mm](#)
 - Edge1: [31 mm](#)
 - Main**
 - Bottom Face: [29 mm](#)
 - Edge1: [22 mm](#)
 - Aux**
 - Bottom Face: [15 mm](#)
 - Edge4: [24 mm](#)


Power Measurement during Sensor Trigger distance testing


**Edge 1 (MIMO1)
(moving toward phantom)**




**Edge 1 (MIMO1)
(moving away phantom)**







Edge 1 (Main)
(moving toward phantom)




Edge 1 (Main)
(moving away phantom)




**Bottom Face (Aux)
(moving toward phantom)**




**Bottom Face (Aux)
(moving away phantom)**



**Edge 4 (Aux)
(moving toward phantom)**



**Edge 4 (Aux)
(moving away phantom)**



5. Smart Transmit feature for RF Exposure compliance

The Smart Transmit algorithm maintains the time-averaged transmit power, in turn, time-averaged RF exposure of SAR_design_target or PD_design_target, below the predefined time-averaged power limit (i.e., input.power.limit for 5G mmW NR), for each characterized technology and band (refer to RF exposure part0 report)

Smart Transmit allows the device to transmit at higher power instantaneously, as high as P_{max}, when needed, but enforces power limiting to maintain time-averaged transmit power to P_{limit}. Below table shows P_{limit} EFS settings and maximum tune up output power P_{max} configured for this EUT for various transmit conditions (Device State Index DSI).

<Terminologies in this report>

P _{limit}	The time-averaged RF power which corresponds to SAR_design_target.
P _{max}	Maximum target power level
SAR_design_target:	The design target for SAR compliance. It should be less than regulatory power density limit to account for all device design related uncertainties.
SAR char	P _{limit} for all the technologies/bands for all applicable DSI

<SAR Characterization>

SAR char must be generated to cover all radio configurations and usage scenarios that the wireless device supports for operating at 6 GHz or below. It will then be used as input for Smart Transmit to control and manage RF exposure for $f < 6$ GHz.

<SAR design target and uncertainty>

The detail SAR design target relate to each exposure conditions pls refer to operation description

Band	Antenna	SAR Design Target 1g SAR (W/kg)	Total Uncertainty (dB)
WCDMA II	MIMO 1	0.40	1
WCDMA IV	MIMO 1	0.40	1
WCDMA V	Main	0.95	1
LTE B2/25	MIMO 1	0.32	2
LTE B66/4	MIMO 1	0.32	2
LTE B26/5	Main	0.757	2
LTE B7	MIMO 1	0.32	2
LTE B12	Main	0.757	2
LTE B13	Main	0.757	2
LTE B14	Main	0.757	2
LTE B30	MIMO 1	0.32	2
LTE B41/38(PC3)	MIMO 1	0.32	2
LTE B41/38(PC2)		0.32	2
LTE B48	AUX	0.32	2
LTE B71	Main	0.757	2
n5	Main	0.757	2
n7	MIMO 1	0.32	2
n12	Main	0.757	2
n25/n2	MIMO 1	0.32	2
n41&n41 HPUE	MIMO 1	0.32	2
n41&n41 HPUE	AUX	0.32	2
n66	MIMO 1	0.32	2
n71	MIMO 1	0.757	2
n77&n77 HPUE	AUX	0.32	2

To account for total uncertainty, SAR_design_target should be determined as:

$$SAR_{design_target} < SAR_{regulatory_limit} \times 10^{\frac{-total\ uncertainty}{10}}$$

<P_{limit} for supported technologies and bands (P_{limit} in EFS file)>

Band	Antenna	Duty cycle	P limit (dBm) time-average power	P Max* (dBm) time-average power
WCDMA II	MIMO 1	100.00%	10.9	24
WCDMA IV	MIMO 1	100.00%	10.8	24
WCDMA V	Main	100.00%	20.6	24
LTE B2/25	MIMO 1	100.00%	10.1	23
LTE B66/4	MIMO 1	100.00%	10	23
LTE B26/5	Main	100.00%	19.5	23
LTE B7	MIMO 1	100.00%	10.1	23
LTE B12	Main	100.00%	20.1	23
LTE B13	Main	100.00%	19.4	23
LTE B14	Main	100.00%	19.5	23
LTE B30	MIMO 1	100.00%	9.3	21
LTE B41/38(PC3)**	MIMO 1	63.30%	8.7	21
LTE B41/38(PC2)**		43.30%	9.5	21.4
LTE B48**	AUX	63.30%	11.7	19
LTE B71	Main	100.00%	20.8	23
n5	Main	100.00%	19.3	23
n7	MIMO 1	100.00%	11.7	23
n12	Main	100.00%	20.3	23
n25/n2	MIMO 1	100.00%	10.1	23
n41	MIMO 1	100.00%	11.4	20
n41 HPUE**	MIMO 1	50.00%	11.4	19
n41	AUX	100.00%	12	23
n41 HPUE**	AUX	50.00%	12	22
n66	MIMO 1	100.00%	10.4	23
n71	MIMO 1	100.00%	20.5	23
n77	AUX	100.00%	13.7	23
n77 HPUE**	AUX	50.00%	13.7	22

*P_{max} is used for RF tune up procedure. The maximum allowed output power is equal to P_{max} + 1dB uncertainty.

**All P_{limit} power levels entered in the Table correspond to average power levels after accounting for duty cycle in the case TDD modulation schemes (for e.g., GSM & LTE TDD & NR TDD).

The max allowed output power is the P_{limit} + 1dB device uncertainty, and if P_{limit} is higher than P_{max}, the device output power will be P_{max} instead.

6. RF Exposure Limits

6.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

7. Specific Absorption Rate (SAR)

7.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

7.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

8. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- The DASY system in SAR Configuration is shown above
- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running windows software and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8.1 Test Site Location

The SAR measurement facilities used to collect data are within both Sporton Lab list below test site location are accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190 and 3786) and the FCC designation No. TW1190 and TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Test Site	EMC & Wireless Communications Laboratory		Wensan Laboratory		
Test Site Location	TW1190 No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan		TW3786 No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan		
Test Site No.	SAR01-HY	SAR03-HY	SAR08-HY	SAR09-HY	SAR15-HY
	SAR04-HY	SAR05-HY	SAR11-HY	SAR12-HY	
	SAR06-HY	SAR10-HY	SAR13-HY	SAR14-HY	

8.2 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

8.3 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

8.4 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

8.5 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

9. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

9.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

10. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	3500MHz System Validation Kit	D3500V2	1014	Jan. 17, 2022	Jan. 16, 2023
SPEAG	Data Acquisition Electronics	DAE4	854	Aug. 19, 2021	Aug. 18, 2022
SPEAG	Dosimetric E-Field Probe	EX3DV4	7590	Mar. 28, 2022	Mar. 27, 2023
Testo	Hygro meter	608-H1	45196600	Oct. 22, 2021	Oct. 21, 2022
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Oct. 24, 2021	Oct. 23, 2022
Keysight	ENA Network Analyzer	E5071C	MY46104758	Sep. 19, 2021	Sep. 18, 2022
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 24, 2021	Sep. 23, 2022
LINE SEIKI	Digital Thermometer	DTM3000-spezial	2942	Oct. 26, 2021	Oct. 25, 2022
Anritsu	Power Meter	ML2495A	1419002	Aug. 18, 2021	Aug. 17, 2022
Anritsu	Power Sensor	MA2411B	1911176	Aug. 18, 2021	Aug. 17, 2022
Anritsu	Power Meter	ML2495A	1804003	Oct. 09, 2021	Oct. 08, 2022
Anritsu	Power Sensor	MA2411B	1726150	Oct. 09, 2021	Oct. 08, 2022
Anritsu	Spectrum Analyzer	N9010A	MY53470118	Jan. 12, 2022	Jan. 11, 2023
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 19, 2021	Aug. 18, 2022
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 12, 2021	Oct. 11, 2022
Mini-Circuits	Power Amplifier	ZVE-8G+	479102029	Sep. 06, 2021	Sep. 05, 2022
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Warison	Directional Coupler	WCOU-10-50S-10	WR889BMC4B1	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. The dipole calibration interval can be extended to 3 years with justification according to KDB 865664 D01. The dipoles are also not physically damaged, or repaired during the interval. The justification data in appendix C can be found which the return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration for each dipole.

13. 5G NR Output Power (Unit: dBm)

General Note:

1. Referencing the procedure in KDB 941225, the test procedures are outlined as below
 - a. For DFT-OFDM output power measurement, full measurement was done for Pi/2 BPSK and QPSK and for the largest supported bandwidth, repeat test for 16QAM/64QAM/256QAM under 1RB 1Offset configuration. For smaller bandwidth, measure conducted power for Pi/2 BPSK and 1RB 1Offset configuration.
 - b. According to the tune-up, CP-OFDM output power is not ½ dB higher than DFT-OFDM mode, and the reported SAR of DFT-OFDM mode reported SAR is ≤ 1.45 W/kg, SAR test and thus conducted power for CP-OFDM mode is not required.
 - c. To start SAR test for the largest channel bandwidth for Pi/2 BPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. Also do SAR test for 50% RB allocation for Pi/2 BPSK SAR testing using 1RB Pi/2 BPSK allocation procedure
 - d. For Pi/2 BPSK with 100% RB allocation, SAR test is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
 - e. For higher modulation QPSK/16QAM/64QAM/256QAM, according to tune-up document the power level is not ½ dB higher than the same configuration in Pi/2 BPSK, also reported SAR for the Pi/2 BPSK configuration is less than 1.45 W/kg, QPSK/16QAM/64QAM/256QAM SAR testing are not required.
 - f. Smaller bandwidth output power for each RB allocation configuration for this device is not ½ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg, smaller bandwidth SAR testing is not required for this device
2. Due to test setup limitations, SAR testing for NR was performed using Factory Test Mode software to establish the connection and perform SAR with 100% transmission. And only for TDD power class2 was performed using Factory Test Mode software to establish the connection and perform SAR with 50% transmission.

<3GPP 38.101 MPR for EN-DC>

Table 6.2.2-1 Maximum power reduction (MPR) for power class 3

Modulation		MPR (dB)		
		Edge RB allocations	Outer RB allocations	Inner RB allocations
DFT-s-OFDM	Pi/2 BPSK	≤ 3.5 ¹	≤ 1.2 ¹	≤ 0.2 ¹
		≤ 0.5 ²	≤ 0.5 ²	0 ²
	QPSK	≤ 1		0
	16 QAM	≤ 2		≤ 1
	64 QAM	≤ 2.5		
CP-OFDM	256 QAM	≤ 4.5		
	QPSK	≤ 3		≤ 1.5
	16 QAM	≤ 3		≤ 2
	64 QAM	≤ 3.5		
	256 QAM	≤ 6.5		

NOTE 1: Applicable for UE operating in TDD mode with Pi/2 BPSK modulation and UE indicates support for UE capability *powerBoosting-pi2BPSK* and if the IE *powerBoostPi2BPSK* is set to 1 and 40 % or less slots in radio frame are used for UL transmission for bands n40, n41, n77, n78 and n79. The reference power of 0 dB MPR is 26 dBm.

NOTE 2: Applicable for UE operating in FDD mode, or in TDD mode in bands other than n40, n41, n77, n78 and n79 with Pi/2 BPSK modulation and if the IE *powerBoostPi2BPSK* is set to 0 and if more than 40 % of slots in radio frame are used for UL transmission for bands n40, n41, n77, n78 and n79.

Table 6.2.2-2 Maximum power reduction (MPR) for power class 2

Modulation		MPR (dB)		
		Edge RB allocations	Outer RB allocations	Inner RB allocations
DFT-s-OFDM	Pi/2 BPSK	≤ 3.5	≤ 0.5	0
	QPSK	≤ 3.5	≤ 1	0
	16 QAM	≤ 3.5	≤ 2	≤ 1
	64 QAM	≤ 3.5	≤ 2.5	
	256 QAM	≤ 4.5		
CP-OFDM	QPSK	≤ 3.5	≤ 3	≤ 1.5
	16 QAM	≤ 3.5	≤ 3	≤ 2
	64 QAM	≤ 3.5		
	256 QAM	≤ 6.5		

Default Power Mode
<n77>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel					633332		
Frequency (MHz)					3499.98		
100	PI/2 BPSK	1	1		24.46		25.0
100	PI/2 BPSK	1	137		24.22		
100	PI/2 BPSK	1	271		24.26		
100	PI/2 BPSK	135	0		24.30		25.0
100	PI/2 BPSK	135	69		24.41		25.0
100	PI/2 BPSK	135	138		24.27		25.0
100	PI/2 BPSK	270	0		24.43		
100	QPSK	1	1		24.28		25.0
100	QPSK	1	137		24.34		
100	QPSK	1	271		24.37		
100	QPSK	135	0		24.24		25.0
100	QPSK	135	69		24.36		
100	QPSK	135	138		24.19		
100	QPSK	270	0		24.42		25.0
100	16QAM	1	1		24.24		25.0
100	64QAM	1	1		24.04		25.0
100	256QAM	1	1		24.27		25.0

<n77 HPUE>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel					633332		
Frequency (MHz)					3499.98		
100	PI/2 BPSK	1	1		26.68		27.0
100	PI/2 BPSK	1	137		26.52		
100	PI/2 BPSK	1	271		26.43		
100	PI/2 BPSK	135	0		25.78		26.5
100	PI/2 BPSK	135	69		26.34		27.0
100	PI/2 BPSK	135	138		25.85		26.5
100	PI/2 BPSK	270	0		26.28		
100	QPSK	1	1		26.68		27.0
100	QPSK	1	137		26.47		
100	QPSK	1	271		26.32		
100	QPSK	135	0		25.77		27.0
100	QPSK	135	69		26.43		
100	QPSK	135	138		25.81		
100	QPSK	270	0		25.75		26.0
100	16QAM	1	1		25.80		26.0
100	64QAM	1	1		24.29		24.5
100	256QAM	1	1		22.30		22.5


Reduced Power Mode
<n77>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel					633332		
Frequency (MHz)					3499.98		
100	PI/2 BPSK	1	1		14.87		15.7
100	PI/2 BPSK	1	137		14.72		
100	PI/2 BPSK	1	271		14.61		
100	PI/2 BPSK	135	0		14.77		15.7
100	PI/2 BPSK	135	69		14.67		15.7
100	PI/2 BPSK	135	138		14.63		15.7
100	PI/2 BPSK	270	0		14.71		
100	QPSK	1	1		14.56		15.7
100	QPSK	1	137		14.70		
100	QPSK	1	271		14.61		
100	QPSK	135	0		14.61		15.7
100	QPSK	135	69		14.68		
100	QPSK	135	138		14.76		
100	QPSK	270	0		14.65		15.7
100	16QAM	1	1		14.52		15.7
100	64QAM	1	1		14.65		15.7
100	256QAM	1	1		14.69		15.7

<n77 HPUE>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel					633332		
Frequency (MHz)					3499.98		
100	PI/2 BPSK	1	1		18.37		18.7
100	PI/2 BPSK	1	137		18.14		
100	PI/2 BPSK	1	271		18.09		
100	PI/2 BPSK	135	0		17.44		18.7
100	PI/2 BPSK	135	69		18.02		18.7
100	PI/2 BPSK	135	138		17.53		18.7
100	PI/2 BPSK	270	0		17.92		
100	QPSK	1	1		18.29		18.7
100	QPSK	1	137		18.09		
100	QPSK	1	271		17.93		
100	QPSK	135	0		17.38		18.7
100	QPSK	135	69		18.13		
100	QPSK	135	138		17.46		
100	QPSK	270	0		17.36		18.7
100	16QAM	1	1		17.41		18.7
100	64QAM	1	1		17.90		18.7
100	256QAM	1	1		17.91		18.7

14. Antenna Location


Edge3
Front View

The separation distance for antenna to edge :

Antenna	To Edge1 (mm)	To Edge2 (mm)	To Edge3 (mm)	To Edge4 (mm)
WWAN Main Antenna	7.9	31.5	203.9	195.5
WWAN Aux Antenna	85.5	287.6	61.5	6.5
WWAN MIMO1 Antenna	7.9	185	203.9	65
WLAN Antenna 1	11.4	248	203.2	30
WLAN/BT Antenna 2	169.1	288.7	32.9	10.3

<SAR test exclusion table>
General Note:

1. The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW"
2. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
3. Per KDB 447498 D01v06, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
4. Per KDB 447498 D01v06, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
5. Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
6. Per KDB 447498 D01v06, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
 - a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · (f(MHz)/150)] mW, at 100 MHz to 1500 MHz
 - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz

<WWAN Aux Antenna>

Exposure Position	Wireless Interface	LTE Band n77
	Calculated Frequency (MHz)	3550
	Maximum power (dBm)	27.0
	Maximum rated power(mW)	501.19
Bottom Face	Separation distance(mm)	5.0
	exclusion threshold	188.9
	Testing required?	Yes
Edge 1	Separation distance(mm)	85.5
	exclusion threshold	435.0
	Testing required?	Yes
Edge 2	Separation distance(mm)	287.6
	exclusion threshold	2456.0
	Testing required?	No
Edge 3	Separation distance(mm)	61.5
	exclusion threshold	195.0
	Testing required?	Yes
Edge 4	Separation distance(mm)	6.6
	exclusion threshold	143.1
	Testing required?	Yes

15. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - c. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The Reported TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. For the exposure positions that proximity sensor power reduction is applied for SAR compliance, additional SAR testing with EUT transmitting full power in sensor trigger distance was performed according to section 4. The test results just verification the sensor trigger distance to meet KDB 616217 requirement, when in normal usage will not operate at trigger distance, therefore, these results were not using performed Sim-Tx analysis.

5G NR Note:

1. Referencing the procedure in KDB 941225, the test procedures are outlined as below:
 - a. To start SAR test for the largest channel bandwidth for PI/2 BPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. Also do SAR test for 50% RB allocation for PI/2 BPSK SAR testing using 1RB PI/2 BPSK allocation procedure
 - b. For PI/2 BPSK with 100% RB allocation, SAR test is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
 - c. For higher modulation QPSK/16QAM/64QAM/256QAM, according to tune-up document the power level is not $\frac{1}{2}$ dB higher than the same configuration in PI/2 BPSK, also reported SAR for the PI/2 BPSK configuration is less than 1.45 W/kg, QPSK/16QAM/64QAM/256QAM SAR testing are not required.
 - d. Smaller bandwidth output power for each RB allocation configuration for this device is not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg, smaller bandwidth SAR testing is not required for this device
 - e. For 5G FR1 n77, the maximum channel bandwidth does not support three non-overlapping channels in the frequency band, the middle channel of the group of overlapping channels were selected for testing.
 - f. Due to test setup limitations, SAR testing for NR was performed using Factory Test Mode software to establish the connection and perform SAR with 100% transmission. And only for TDD power class2 was performed using Factory Test Mode software to establish the connection and perform SAR with 50% transmission



15.1 Body SAR

<5G NR SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	FR1 n77_AUX	100M	BPSK	1	1	Bottom Face	15mm	Aux	OFF	633332	3499.98	Sample 1	24.46	25.00	1.132	-0.15	0.252	0.285
	FR1 n77_AUX	100M	BPSK	135	69	Bottom Face	15mm	Aux	OFF	633332	3499.98	Sample 1	24.41	25.00	1.146	0.08	0.244	0.280
	FR1 n77_AUX	100M	BPSK	1	1	Edge 1	0mm	Aux	OFF	633332	3499.98	Sample 1	24.46	25.00	1.132	0.11	0.016	0.018
	FR1 n77_AUX	100M	BPSK	135	69	Edge 1	0mm	Aux	OFF	633332	3499.98	Sample 1	24.41	25.00	1.146	-0.19	0.013	0.015
	FR1 n77_AUX	100M	BPSK	1	1	Edge 3	0mm	Aux	OFF	633332	3499.98	Sample 1	24.46	25.00	1.132	-0.16	0.105	0.119
	FR1 n77_AUX	100M	BPSK	135	69	Edge 3	0mm	Aux	OFF	633332	3499.98	Sample 1	24.41	25.00	1.146	0.06	0.090	0.103
	FR1 n77_AUX	100M	BPSK	1	1	Edge 4	24mm	Aux	OFF	633332	3499.98	Sample 1	24.46	25.00	1.132	-0.01	0.160	0.181
	FR1 n77_AUX	100M	BPSK	135	69	Edge 4	24mm	Aux	OFF	633332	3499.98	Sample 1	24.41	25.00	1.146	-0.1	0.149	0.171
	FR1 n77_AUX	100M	BPSK	1	1	Bottom Face	0mm	Aux	ON	633332	3499.98	Sample 1	14.87	15.70	1.211	0	0.208	0.252
	FR1 n77_AUX	100M	BPSK	135	69	Bottom Face	0mm	Aux	ON	633332	3499.98	Sample 1	14.77	15.70	1.239	0.01	0.201	0.249
01	FR1 n77_AUX	100M	BPSK	1	1	Edge 4	0mm	Aux	ON	633332	3499.98	Sample 1	14.87	15.70	1.211	-0.01	0.257	0.311
	FR1 n77_AUX	100M	BPSK	135	69	Edge 4	0mm	Aux	ON	633332	3499.98	Sample 1	14.77	15.70	1.239	0.12	0.242	0.300
	FR1 n77_HPUE_AUX	100M	BPSK	1	1	Edge 4	0mm	Aux	ON	633332	3499.98	Sample 1	18.37	18.70	1.079	0.17	0.284	0.306
	FR1 n77_AUX	100M	BPSK	1	1	Edge 4	0mm	Aux	ON	633332	3499.98	Sample 2	14.87	15.70	1.211	0.05	0.243	0.294

15.2 FR1 n77 Power Class 2 and Power Class 3 Linearity

This device support Power Class 2 and Power Class 3 operations for FR1 n77. The highest available duty cycle for Power Class 2 operation is 43.3% using UL-DL configuration 1. Per FCC Guidance based on the device behavior, all SAR tests were performed using Power Class 3. Power Class 2 is tested using the highest SAR test configuration in Power Class 3 for each LTE configuration and exposure condition combination, according to the highest time averaged power for all applicable uplink-downlink configurations in Power Class 2. When the reported SAR vs. output power is linearly scaled with < 10% discrepancy between power classes and all reported SAR are < 1.4 W/kg, Separate SAR testing for Power Class 2 is not required

Use PC3 power level and SAR to estimated PC2 SAR linearly, and check if the deviation from the measured PC2 SAR is <10%

	5G FR1 n77 (Power Class 3)	5G FR1 n77 (Power Class 2)
Maximum Tune up Power (dBm)	15.7	15.7
Reported 1g SAR (W/kg)	0.311	0.216
Duty Cycle	63.30%	43.30%
Frame Averaged (mW)	23.52	16.09
Linearity SAR(W/kg)	0.21	
% deviation from expected linearity		1.53%

16. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body
1.	WWAN + 2.4GHz WLAN Ant 1 + 2.4GHz WLAN Ant 2	Yes
2.	WWAN + 2.4GHz WLAN Ant 1 + Bluetooth Ant 2	Yes
3.	WWAN + 5GHz WLAN Ant 1 + 5GHz WLAN Ant 2 + Bluetooth Ant 2	Yes

General Note:

- In this report is enable n77 Part27Q frequency range, the other band results refer to original report no.: FA162602, and use for Sim-Tx analysis.
- WLAN RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode. Therefore SPLSR calculation was choose worst case with SAR test results of each antenna in SISO mode perform evaluation.
- The Scaled SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation $< 1.6\text{W/kg}$.
 - $\text{SPLSR} = (\text{SAR1} + \text{SAR2})^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6\text{W/kg}$.
 - The SPLSR calculated results please refer to section 16.3.

16.1 5G NR + LTE + WLAN + BT Sim-Tx analysis

In 5G NR + LTE + WLAN + BT simultaneous transmission, 5G NR and LTE transmission are managed and controlled by Qualcomm® Smart Transmit, while the RF exposure from WLAN and BT radios is managed using legacy approach, i.e., through a fixed power back-off if needed.

Since WLAN and BT do not employ time-averaging, 1gSAR and 10gSAR measurement for WLAN and BT need to be conducted at their corresponding rated power following current FCC test procedures to determine reported SAR values.

Smart Transmit current implementation assumes hotspots from 5G NR and LTE are collocated. Therefore, for a total of 100% exposure margin, if LTE uses $x\%$, then the exposure margin left for 5G NR is capped to $(100-x)\%$. Thus, the compliance equation for LTE + 5G NR is

$$x\% * A + (100-x)\% * B \leq 1.0,$$

Where, A is normalized reported time-averaged SAR exposure ratio from LTE, and $A \leq 1.0$; B is normalized reported time-averaged exposure ratio from 5G NR (i.e., PD exposure for 5G FR2 or SAR exposure for 5G FR1), and $B \leq 1.0$.

Let C = normalized reported SAR exposure ratio from WLAN+BT, then for compliance,

$$x\% * A + (100-x)\% * B + C \leq 1.0 \quad (1)$$

$$x\% * A + (100-x)\% * B \leq x\% * \max(A, B) + (100-x)\% * \max(A, B) \leq \max(A, B)$$

$$x\% * A + (100-x)\% * B + C \leq \max(A, B) + C \leq 1.0 \quad (2)$$

if $A + C \leq 1.0$ and $B + C \leq 1.0$ can be proven, then " $x\% * A + (100-x)\% * B + C \leq 1.0$ ". Therefore simultaneous transmission analysis for 5G NR + LTE + WLAN + BT can be performed in two steps

Step 1: Prove total exposure ratio (TER) of LTE + WLAN + BT < 1

Step 2: Prove total exposure ratio (TER) of 5G NR + WLAN + BT < 1



16.2 Body Exposure Conditions

WWAN Band	Exposure Position	1	2	3	4	5	6	1+2+3 Summed 1g SAR (W/kg)	1+2+6 Summed 1g SAR (W/kg)	1+4+5+6 Summed 1g SAR (W/kg)	SPLSR	Case No
		WWAN 1g SAR (W/kg)	2.4GHz WLAN Ant 1 1g SAR (W/kg)	2.4GHz WLAN Ant 2 1g SAR (W/kg)	5GHz WLAN Ant 1 1g SAR (W/kg)	5GHz WLAN Ant 2 1g SAR (W/kg)	Bluetooth Ant 2 1g SAR (W/kg)					
WCDMA II_MIMO1	Bottom Face at 0mm	0.493	0.531	0.552	0.414	0.694	0.194	1.576	1.218	1.795	0.01	Case 1
	Edge 1 at 0mm	0.070	0.147		0.598			0.217	0.217	0.668		
	Edge 4 at 0mm	0.428		0.033		0.384	0.001	0.461	0.429	0.813		
WCDMA IV_MIMO1	Bottom Face at 0mm	0.497	0.531	0.552	0.414	0.694	0.194	1.580	1.222	1.799	0.01	Case 2
	Edge 1 at 0mm	0.064	0.147		0.598			0.211	0.211	0.662		
	Edge 4 at 0mm	0.434		0.033		0.384	0.001	0.467	0.435	0.819		
WCDMA V_MAIN	Bottom Face at 0mm	1.184	0.531	0.552	0.414	0.694	0.194	2.267	1.909	2.486	0.01	Case 3
	Edge 1 at 0mm	0.563	0.147		0.598			0.710	0.710	1.161		
	Edge 2 at 0mm	0.144						0.144	0.144	0.144		
	Edge 3 at 0mm	0.011						0.011	0.011	0.011		
	Edge 4 at 0mm	0.010		0.033		0.384	0.001	0.043	0.011	0.395		
LTE Band 7_MIMO1	Bottom Face at 0mm	0.494	0.531	0.552	0.414	0.694	0.194	1.577	1.219	1.796	0.02	Case 4
	Edge 1 at 0mm	0.439	0.147		0.598			0.586	0.586	1.037		
	Edge 2 at 0mm	0.022						0.022	0.022	0.022		
	Edge 3 at 0mm	0.015						0.015	0.015	0.015		
	Edge 4 at 0mm	0.015		0.033		0.384	0.001	0.048	0.016	0.400		
LTE Band 12_MAIN	Bottom Face at 0mm	1.177	0.531	0.552	0.414	0.694	0.194	2.260	1.902	2.479	0.01	Case 5
	Edge 1 at 0mm	0.603	0.147		0.598			0.750	0.750	1.201		
	Edge 2 at 0mm	0.110						0.110	0.110	0.110		
	Edge 3 at 0mm	0.009						0.009	0.009	0.009		
	Edge 4 at 0mm	0.031		0.033		0.384	0.001	0.064	0.032	0.416		
LTE Band 13_MAIN	Bottom Face at 0mm	1.188	0.531	0.552	0.414	0.694	0.194	2.271	1.913	2.490	0.01	Case 6
	Edge 1 at 0mm	0.756	0.147		0.598			0.903	0.903	1.354		
	Edge 2 at 0mm	0.122						0.122	0.122	0.122		
	Edge 3 at 0mm	0.022						0.022	0.022	0.022		
	Edge 4 at 0mm	0.031		0.033		0.384	0.001	0.064	0.032	0.416		
LTE Band 14_MAIN	Bottom Face at 0mm	1.182	0.531	0.552	0.414	0.694	0.194	2.265	1.907	2.484	0.01	Case 7
	Edge 1 at 0mm	0.833	0.147		0.598			0.980	0.980	1.431		
	Edge 2 at 0mm	0.146						0.146	0.146	0.146		
	Edge 3 at 0mm	0.029						0.029	0.029	0.029		
	Edge 4 at 0mm	0.030		0.033		0.384	0.001	0.063	0.031	0.415		
LTE Band 25_MIMO1	Bottom Face at 0mm	0.497	0.531	0.552	0.414	0.694	0.194	1.580	1.222	1.799	0.01	Case 8
	Edge 1 at 0mm	0.077	0.147		0.598			0.224	0.224	0.675		
	Edge 4 at 0mm	0.538		0.033		0.384	0.001	0.571	0.539	0.923		
LTE Band 26_MAIN	Bottom Face at 0mm	1.176	0.531	0.552	0.414	0.694	0.194	2.259	1.901	2.478	0.01	Case 9
	Edge 1 at 0mm	0.802	0.147		0.598			0.949	0.949	1.400		
	Edge 2 at 0mm	0.195						0.195	0.195	0.195		
	Edge 3 at 0mm	0.017						0.017	0.017	0.017		
	Edge 4 at 0mm	0.015		0.033		0.384	0.001	0.048	0.016	0.400		
LTE Band 30_MIMO1	Bottom Face at 0mm	0.485	0.531	0.552	0.414	0.694	0.194	1.568	1.210	1.787	0.01	Case 10
	Edge 1 at 0mm	0.312	0.147		0.598			0.459	0.459	0.910		
	Edge 4 at 0mm			0.033		0.384	0.001	0.033	0.001	0.385		
LTE Band 41_MIMO1	Bottom Face at 0mm	0.414	0.531	0.552	0.414	0.694	0.194	1.497	1.139	1.716	0.01	Case 11
	Edge 1 at 0mm	0.347	0.147		0.598			0.494	0.494	0.945		
	Edge 2 at 0mm	0.005						0.005	0.005	0.005		
	Edge 3 at 0mm	0.011						0.011	0.011	0.011		
	Edge 4 at 0mm	0.050		0.033		0.384	0.001	0.083	0.051	0.435		
LTE Band 48_AUX	Bottom Face at 0mm	0.489	0.531	0.552	0.414	0.694	0.194	1.572	1.214	1.791	0.02	Case 12
	Edge 1 at 0mm		0.147		0.598			0.147	0.147	0.598		
	Edge 3 at 0mm	0.104						0.104	0.104	0.104		



FCC SAR TEST REPORT


Report No. : FA162602-04

	Edge 4 at 0mm	0.609		0.033		0.384	0.001	0.642	0.610	0.994		
LTE Band 66_MIMO1	Bottom Face at 0mm	0.492	0.531	0.552	0.414	0.694	0.194	1.575	1.217	1.794	0.01	Case 13
	Edge 1 at 0mm	0.065	0.147		0.598			0.212	0.212	0.663		
	Edge 4 at 0mm	0.442		0.033		0.384	0.001	0.475	0.443	0.827		
LTE Band 71_MAIN	Bottom Face at 0mm	1.182	0.531	0.552	0.414	0.694	0.194	2.265	1.907	2.484	0.01	Case 14
	Edge 1 at 0mm	0.579	0.147		0.598			0.726	0.726	1.177		
	Edge 2 at 0mm	0.124						0.124	0.124	0.124		
	Edge 3 at 0mm	0.041						0.041	0.041	0.041		
	Edge 4 at 0mm	0.038		0.033		0.384	0.001	0.071	0.039	0.423		
FR1 n5_MAIN	Bottom Face at 0mm	1.191	0.531	0.552	0.414	0.694	0.194	2.274	1.916	2.493	0.01	Case 15
	Edge 1 at 0mm	0.902	0.147		0.598			1.049	1.049	1.500		
	Edge 2 at 0mm	0.182						0.182	0.182	0.182		
	Edge 3 at 0mm	0.038						0.038	0.038	0.038		
	Edge 4 at 0mm	0.027		0.033		0.384	0.001	0.060	0.028	0.412		
FR1 n7_MIMO1	Bottom Face at 0mm	0.478	0.531	0.552	0.414	0.694	0.194	1.561	1.203	1.780	0.01	Case 16
	Edge 1 at 0mm	0.297	0.147		0.598			0.444	0.444	0.895		
	Edge 2 at 0mm	0.001						0.001	0.001	0.001		
	Edge 3 at 0mm	0.001						0.001	0.001	0.001		
	Edge 4 at 0mm	0.001		0.033		0.384	0.001	0.034	0.002	0.386		
FR1 n12_MAIN	Bottom Face at 0mm	1.196	0.531	0.552	0.414	0.694	0.194	2.279	1.921	2.498	0.01	Case 17
	Edge 1 at 0mm	0.608	0.147		0.598			0.755	0.755	1.206		
	Edge 2 at 0mm	0.137						0.137	0.137	0.137		
	Edge 3 at 0mm	0.015						0.015	0.015	0.015		
	Edge 4 at 0mm	0.037		0.033		0.384	0.001	0.070	0.038	0.422		
FR1 n25_MIMO1	Bottom Face at 0mm	0.500	0.531	0.552	0.414	0.694	0.194	1.583	1.225	1.802	0.01	Case 18
	Edge 1 at 0mm	0.064	0.147		0.598			0.211	0.211	0.662		
	Edge 4 at 0mm	0.440		0.033		0.384	0.001	0.473	0.441	0.825		
FR1 n41_MIMO1	Bottom Face at 0mm	0.496	0.531	0.552	0.414	0.694	0.194	1.579	1.221	1.798	0.02	Case 19
	Edge 1 at 0mm	0.418	0.147		0.598			0.565	0.565	1.016		
	Edge 2 at 0mm	0.014						0.014	0.014	0.014		
	Edge 3 at 0mm	0.016						0.016	0.016	0.016		
	Edge 4 at 0mm	0.012		0.033		0.384	0.001	0.045	0.013	0.397		
FR1 n41_AUX	Bottom Face at 0mm	0.496	0.531	0.552	0.414	0.694	0.194	1.579	1.221	1.798	0.04	Case 20
	Edge 1 at 0mm	0.474	0.147		0.598			0.621	0.621	1.072		
	Edge 2 at 0mm	0.013						0.013	0.013	0.013		
	Edge 3 at 0mm	0.061						0.061	0.061	0.061		
	Edge 4 at 0mm	0.326		0.033		0.384	0.001	0.359	0.327	0.711		
FR1 n66_MIMO1	Bottom Face at 0mm	0.497	0.531	0.552	0.414	0.694	0.194	1.580	1.222	1.799	0.01	Case 21
	Edge 1 at 0mm	0.071	0.147		0.598			0.218	0.218	0.669		
	Edge 4 at 0mm	0.289		0.033		0.384	0.001	0.322	0.290	0.674		
FR1 n71_MAIN	Bottom Face at 0mm	1.180	0.531	0.552	0.414	0.694	0.194	2.263	1.905	2.482	0.01	Case 22
	Edge 1 at 0mm	0.588	0.147		0.598			0.735	0.735	1.186		
	Edge 2 at 0mm	0.103						0.103	0.103	0.103		
	Edge 3 at 0mm	0.013						0.013	0.013	0.013		
	Edge 4 at 0mm	0.040		0.033		0.384	0.001	0.073	0.041	0.425		
FR1 n77_AUX	Bottom Face at 0mm	0.378	0.531	0.552	0.414	0.694	0.194	1.461	1.103	1.680	0.04	Case 23
	Edge 1 at 0mm	0.018	0.147		0.598			0.165	0.165	0.616		
	Edge 3 at 0mm	0.163						0.163	0.163	0.163		
	Edge 4 at 0mm	0.468		0.033		0.384	0.001	0.501	0.469	0.853		

16.3 SPLSR Evaluation and Analysis

General Note:

1. $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary
2. The detail hotspot point for each transmitter in each exposure condition are showing as below figure and the minimum 3D distance for each sum combination is used for SPLSR analysis.



	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 1	WCDMA II_MIMO1	Bottom Face	0.493	0mm	92.42	-57.97	-1.29	60.0	0.91	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	WCDMA II_MIMO1	Bottom Face	0.493	0mm	92.42	-57.97	-1.29	179.3	1.38	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 2	WCDMA IV_MIMO1	Bottom Face	0.497	0mm	90.83	-58.37	-1.2	59.7	0.91	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	WCDMA IV_MIMO1	Bottom Face	0.497	0mm	90.83	-58.37	-1.2	177.7	1.39	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 3	WCDMA V_MAIN	Bottom Face	1.184	0mm	105.54	80.51	-1.24	190.7	1.72	0.01	Not required
	WLAN2.4GHz Ant1		0.531	0mm	92.63	-109.79	-1.97				
	WCDMA V_MAIN	Bottom Face	1.184	0mm	105.54	80.51	-1.24	277.3	1.74	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	WCDMA V_MAIN	Bottom Face	1.184	0mm	105.54	80.51	-1.24	198.4	1.60	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	WCDMA V_MAIN	Bottom Face	1.184	0mm	105.54	80.51	-1.24	281.9	2.07	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	1.08	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	0.73	0.00	Not required
	BT Ant 2		0.194	0mm	-63	-139.6	2.84				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 4	LTE Band 7_MIMO1	Bottom Face	0.494	0mm	95.23	-71.4	-1.58	46.5	0.91	0.02	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 7_MIMO1	Bottom Face	0.494	0mm	95.23	-71.4	-1.58	175.8	1.38	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 5	LTE Band 12_MAIN	Bottom Face	1.177	0mm	101.62	88.35	-1.16	198.3	1.71	0.01	Not required
	WLAN2.4GHz Ant1		0.531	0mm	92.63	-109.79	-1.97				
	LTE Band 12_MAIN	Bottom Face	1.177	0mm	101.62	88.35	-1.16	281.2	1.73	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	LTE Band 12_MAIN	Bottom Face	1.177	0mm	101.62	88.35	-1.16	206.1	1.59	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 12_MAIN	Bottom Face	1.177	0mm	101.62	88.35	-1.16	285.8	2.07	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	1.08	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	0.73	0.00	Not required
	BT Ant 2		0.194	0mm	-63	-139.6	2.84				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				

	Band	Position	SAR (W/kg)	Gap	SAR peak location (cm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
Case 6	LTE Band 13_MAIN	Bottom Face	1.188	0mm	101.51	85.31	-1.2	195.3	1.72	0.01	Not required
	WLAN2.4GHz Ant1		0.531	0mm	92.63	-109.79	-1.97				
	LTE Band 13_MAIN	Bottom Face	1.188	0mm	101.51	85.31	-1.2	278.7	1.74	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	LTE Band 13_MAIN	Bottom Face	1.188	0mm	101.51	85.31	-1.2	203.1	1.60	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 13_MAIN	Bottom Face	1.188	0mm	101.51	85.31	-1.2	283.3	2.08	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	1.08	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	0.73	0.00	Not required
	BT Ant 2		0.194	0mm	-63	-139.6	2.84				
Case 7	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	LTE Band 14_MAIN	Bottom Face	1.182	0mm	101.64	83.62	-1.3	193.6	1.71	0.01	Not required
	WLAN2.4GHz Ant1		0.531	0mm	92.63	-109.79	-1.97				
	LTE Band 14_MAIN	Bottom Face	1.182	0mm	101.64	83.62	-1.3	277.4	1.73	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	LTE Band 14_MAIN	Bottom Face	1.182	0mm	101.64	83.62	-1.3	201.4	1.60	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 14_MAIN	Bottom Face	1.182	0mm	101.64	83.62	-1.3	282.0	2.07	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	1.08	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
Case 8	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	0.73	0.00	Not required
	BT Ant 2		0.194	0mm	-63	-139.6	2.84				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	LTE Band 25_MIMO1	Bottom Face	0.497	0mm	90.93	-56.88	-0.9	61.1	0.91	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 25_MIMO1	Bottom Face	0.497	0mm	90.93	-56.88	-0.9	178.5	1.39	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 9	LTE Band 26_MAIN	Bottom Face	1.176	0mm	99.93	86.91	-1.35	196.8	1.71	0.01	Not required
	WLAN2.4GHz Ant1		0.531	0mm	92.63	-109.79	-1.97				
	LTE Band 26_MAIN	Bottom Face	1.176	0mm	99.93	86.91	-1.35	279.1	1.73	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	LTE Band 26_MAIN	Bottom Face	1.176	0mm	99.93	86.91	-1.35	204.6	1.59	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 26_MAIN	Bottom Face	1.176	0mm	99.93	86.91	-1.35	283.7	2.06	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	1.08	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	0.73	0.00	Not required
	BT Ant 2		0.194	0mm	-63	-139.6	2.84				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				

	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
Case 10	LTE Band 30_MIMO1	Bottom Face	0.485	0mm	104.45	-51.76	-0.69	66.6	0.90	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 30LTE Band 30_MIMO1	Bottom Face	0.485	0mm	104.45	-51.76	-0.69	192.8	1.37	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 11	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 41_MIMO1	Bottom Face	0.414	0mm	93.4	-66.98	-1.65	51.0	0.83	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 41_MIMO1	Bottom Face	0.414	0mm	93.4	-66.98	-1.65	176.0	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 12	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 48_AUX	Bottom Face	0.489	0mm	19.21	-150.81	3.37	83.3	0.90	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 48_AUX	Bottom Face	0.489	0mm	19.21	-150.81	3.37	84.3	1.38	0.02	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 13	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 66_MIMO1	Bottom Face	0.492	0mm	92.43	-56.89	-0.96	61.0	0.91	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 66_MIMO1	Bottom Face	0.492	0mm	92.43	-56.89	-0.96	179.8	1.38	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 14	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (cm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 71_MAIN	Bottom Face	1.182	0mm	104.65	90.92	-0.59	201.1	1.71	0.01	Not required
	WLAN2.4GHz Ant1		0.531	0mm	92.63	-109.79	-1.97				
	LTE Band 71_MAIN	Bottom Face	1.182	0mm	104.65	90.92	-0.59	285.1	1.73	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	LTE Band 71_MAIN	Bottom Face	1.182	0mm	104.65	90.92	-0.59	208.8	1.60	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	LTE Band 71_MAIN	Bottom Face	1.182	0mm	104.65	90.92	-0.59	289.7	2.07	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	1.08	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	0.73	0.00	Not required
	BT Ant 2		0.194	0mm	-63	-139.6	2.84				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				

	Band	Position	SAR (W/kg)	Gap	SAR peak location (cm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
Case 15	FR1 n5_MAIN	Bottom Face	1.191	0mm	107.92	78	-0.7	188.4	1.72	0.01	Not required
	WLAN2.4GHz Ant1		0.531	0mm	92.63	-109.79	-1.97				
	FR1 n5_MAIN	Bottom Face	1.191	0mm	107.92	78	-0.7	276.7	1.74	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	FR1 n5_MAIN	Bottom Face	1.191	0mm	107.92	78	-0.7	196.0	1.61	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	FR1 n5_MAIN	Bottom Face	1.191	0mm	107.92	78	-0.7	281.3	2.08	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	1.08	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	0.73	0.00	Not required
	BT Ant 2		0.194	0mm	-63	-139.6	2.84				
Case 16	FR1 n7_MIMO1	Bottom Face	0.478	0mm	107.05	-53.09	-0.74	65.7	0.89	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	FR1 n7_MIMO1	Bottom Face	0.478	0mm	107.05	-53.09	-0.74	194.5	1.37	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 17	FR1 n12_MAIN	Bottom Face	1.196	0mm	106.06	81.52	-0.74	191.8	1.73	0.01	Not required
	WLAN2.4GHz Ant1		0.531	0mm	92.63	-109.79	-1.97				
	FR1 n12_MAIN	Bottom Face	1.196	0mm	106.06	81.52	-0.74	278.4	1.75	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	FR1 n12_MAIN	Bottom Face	1.196	0mm	106.06	81.52	-0.74	199.5	1.61	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	FR1 n12_MAIN	Bottom Face	1.196	0mm	106.06	81.52	-0.74	283.0	2.08	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	1.08	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	0.73	0.00	Not required
	BT Ant 2		0.194	0mm	-63	-139.6	2.84				
Case 18	FR1 n25_MIMO1	Bottom Face	0.5	0mm	90.1	-56.88	-1.79	61.2	0.91	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	FR1 n25_MIMO1	Bottom Face	0.5	0mm	90.1	-56.88	-1.79	177.8	1.39	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 19	FR1 n41_MIMO1	Bottom Face	0.496	0mm	99.44	-71.35	-1.71	46.8	0.91	0.02	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	FR1 n41_MIMO1	Bottom Face	0.496	0mm	99.44	-71.35	-1.71	179.7	1.38	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				

	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
Case 20	FR1 n41_AUX	Bottom Face	0.496	0mm	-20.78	-147.39	-2.08	120.3	0.91	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	FR1 n41_AUX	Bottom Face	0.496	0mm	-20.78	-147.39	-2.08	44.5	1.38	0.04	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 21	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	FR1 n66	Bottom Face	0.497	0mm	94.06	-58.49	-0.95	59.3	0.91	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	FR1 n66	Bottom Face	0.497	0mm	94.06	-58.49	-0.95	180.5	1.39	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 22	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (cm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	FR1 n71_MAIN	Bottom Face	1.18	0mm	104.42	91.03	-0.78	201.2	1.71	0.01	Not required
	WLAN2.4GHz Ant1		0.531	0mm	92.63	-109.79	-1.97				
	FR1 n71_MAIN	Bottom Face	1.18	0mm	104.42	91.03	-0.78	285.0	1.73	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	FR1 n71_MAIN	Bottom Face	1.18	0mm	104.42	91.03	-0.78	208.9	1.59	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	FR1 n71_MAIN	Bottom Face	1.18	0mm	104.42	91.03	-0.78	289.6	2.07	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	1.08	0.01	Not required
	WLAN2.4GHz Ant2		0.552	0mm	-63	-139.6	2.84				
	WLAN2.4GHz Ant1	Bottom Face	0.531	0mm	92.63	-109.79	-1.97	158.5	0.73	0.00	Not required
	BT Ant 2		0.194	0mm	-63	-139.6	2.84				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
Case 23	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	FR1 n77_AUX	Bottom Face	0.378	0mm	-36	-134	0	132.7	0.79	0.01	Not required
	WLAN5GHz Ant1		0.414	0mm	95.6	-117.6	4.02				
	FR1 n77_AUX	Bottom Face	0.378	0mm	-36	-124	0	35.2	1.27	0.04	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				
	WLAN5GHz Ant1	Bottom Face	0.414	0mm	95.6	-117.6	4.02	162.6	1.30	0.01	Not required
	WLAN5GHz Ant 2 + BT Ant 2		0.888	0mm	-64.8	-144	3.4				

Test Engineer : Jimmy Lu and Dennis Hsieh

17. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [8] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [9] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015
- [10] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015
- [11] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [12] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.