



FCC RADIO TEST REPORT

FCC ID : UZ7EC300K
Equipment : EC30 Enterprise Companion
Brand Name : Zebra
Model Name : EC300K
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC Part 15 Subpart C §15.247

The product was received on Mar. 04, 2019 and testing was started from May 14, 2019 and completed on Jun. 21, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	7
1.4 Testing Location	7
1.5 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	13
2.4 Support Unit used in test configuration and system	15
2.5 EUT Operation Test Setup	15
2.6 Measurement Results Explanation Example.....	15
3 Test Result	16
3.1 6dB and 99% Bandwidth Measurement	16
3.2 Output Power Measurement.....	20
3.3 Power Spectral Density Measurement	23
3.4 Conducted Band Edges and Spurious Emission Measurement	28
3.5 Radiated Band Edges and Spurious Emission Measurement	89
3.6 AC Conducted Emission Measurement.....	94
3.7 Antenna Requirements.....	96
4 List of Measuring Equipment.....	98
5 Uncertainty of Evaluation	100
Appendix A. AC Conducted Emission Test Result	
Appendix B. Radiated Spurious Emission	
Appendix C. Radiated Spurious Emission Plots	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR930401C	01	Initial issue of report	Jun. 26, 2019



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 1.19 dB at 2483.560 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 12.16 dB at 0.335 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Aileen Huang



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	EC30 Enterprise Companion
Brand Name	Zebra
Model Name	EC300K
FCC ID	UZ7EC300K
EUT supports Radios application	WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	EC30 MB EV2 V12
SW Version	Zebra/EC30PR/EC30RT:8.1.0/01-17-19.00-ON-U00-PRD/365:eng/relaese-keys
SW Version for TXBF	Zebra/EC30PR/EC30RT:8.1.0/01-14-06.00-OG-U00-PRD/261:eng/release-keys
FW Version	01-17-19.00-ON-U00-PRD
FW Version for TXBF	01-14-06.00-OG-U00-PRD
MFD	28APR19
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

Specification of Accessories				
AC Adapter - EU	Brand Name	ZEBRA	Part Number	PWR-WUA5V12W0EU
AC Adapter - US	Brand Name	ZEBRA	Part Number	PWR-WUA5V12W0US
TC2X USB-C Cable	Brand Name	ZEBRA	Part Number	CBL-TC2X-USBC01
TC5X USB-C Cable	Brand Name	ZEBRA	Part Number	CBL-TC5X-USBC2A-01
3.5MM headset adapter cable	Brand Name	ZEBRA	Model Name	CBL-TC51-HDST35-01
3.5MM PTT/VOIP headset	Brand Name	ZEBRA	Model Name	HDST-35MM-PTVP-01
3.5MM PTT headset	Brand Name	ZEBRA	Model Name	HDST-35MM-PTT1-01
Body Holster (EC30 Soft Holster)	Brand Name	ZEBRA	Part Number	SG-EC30-HLSTR1-01
Wrist Holster (EC30 Arm Mount (standard strap))	Brand Name	ZEBRA	Part Number	SG-EC30-ARM1-01
Body Holster (EC30 Rigid holster with snap-in design. Rotating Belt Clip with ability to insert in either direction.)	Brand Name	ZEBRA	Part Number	SG-EC30-RHLSTR1-01
Lanyard Adapter with a Vest/Garment clip with coiled tether	Brand Name	ZEBRA	Part Number	SG-EC30-CLIP1-01
Lanyard Adapter (EC30 RETRACTABLE LANYARD WITH MAGNETIC RECOIL, ADJUSTABLE NECK STRAP AND ADAPTER (1 PACK))	Brand Name	ZEBRA	Part Number	SG-EC30-RLYD1-01
Lanyard Adapter (EC30 BASIC LANYARD WITH ADJUSTABLE NECK STRAP AND ADAPTER)	Brand Name	ZEBRA	Part Number	SG-EC30-BLYD1-01
Lanyard Adapter (EC30 RETRACTOR WITH MAGNETIC RECOIL, CARABINER AND ADAPTER)	Brand Name	ZEBRA	Part Number	SG-EC30-RCB1-01



1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Average) Output Power to antenna <CDD Mode>	<p><Ant. 1> 802.11b : 17.80 dBm (0.0603 W) 802.11g : 17.90 dBm (0.0617 W) 802.11n HT20 : 17.70 dBm (0.0589 W) 802.11n HT40 : 17.70 dBm (0.0589 W) 802.11ac VHT20 : 17.80 dBm (0.0603 W) 802.11ac VHT40 : 17.80 dBm (0.0603 W)</p> <p><Ant. 2> 802.11b : 17.80 dBm (0.0603 W) 802.11g : 17.80 dBm (0.0603 W) 802.11n HT20 : 17.70 dBm (0.0589 W) 802.11n HT40 : 17.70 dBm (0.0589 W) 802.11ac VHT20 : 17.80 dBm (0.0603 W) 802.11ac VHT40 : 17.80 dBm (0.0603 W)</p> <p><MIMO Ant. 1 + 2> 802.11b : 21.91 dBm (0.1552 W) 802.11g : 21.86 dBm (0.1535 W) 802.11n HT20 : 21.76 dBm (0.1500 W) 802.11n HT40 : 21.81 dBm (0.1517 W) 802.11ac VHT20 : 21.81 dBm (0.1517 W) 802.11ac VHT40 : 21.86 dBm (0.1535 W)</p>
Maximum (Average) Output Power to antenna <TXBF Mode>	<p><MIMO Ant. 1 + 2> 802.11ac VHT20 : 21.14 dBm (0.1300 W) 802.11ac VHT40 : 21.31 dBm (0.1352 W)</p>
99% Occupied Bandwidth <CDD Mode>	<p><Ant. 1> 802.11b : 12.85MHz 802.11g : 16.90MHz 802.11ac VHT20 : 17.95MHz 802.11ac VHT40 : 36.70MHz</p> <p><Ant. 2> 802.11b : 12.85MHz 802.11g : 16.80MHz 802.11ac VHT20 : 17.95MHz 802.11ac VHT40 : 36.60MHz</p> <p><MIMO Ant. 1> 802.11b : 13.00MHz 802.11g : 16.85MHz 802.11ac VHT20 : 17.95MHz 802.11ac VHT40 : 36.70MHz</p> <p><MIMO Ant. 2> 802.11b : 13.10MHz 802.11g : 16.75MHz 802.11ac VHT20 : 17.90MHz 802.11ac VHT40 : 36.60MHz</p>
99% Occupied Bandwidth <TXBF Mode>	<p><MIMO Ant. 1> 802.11ac VHT20 : : 17.80MHz 802.11ac VHT40 : : 36.60MHz</p> <p><MIMO Ant. 2> 802.11ac VHT20 : : 18.45MHz 802.11ac VHT40 : : 36.60MHz</p>



Standards-related Product Specification			
Antenna Type / Gain	<Ant. 1> PCB Antenna with gain 0.78 dBi <Ant. 2> PCB Antenna with gain 1.93 dBi		
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)		
Antenna Function Description		Ant. 1	Ant. 2
	802.11 b/g/n/ac	V	V
	802.11 b/g/n/ac MIMO	V	V
	802.11 ac TXBF	V	V

Note: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH05-HY	CO05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane for CDD Mode with Ant. 1 and Ant. 2, Z plane for CDD Mode with MIMO Ant. 1+2 and TXBF Mode) were recorded in this report.

- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		



2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Single Mode

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11n HT40 (Covered by VHT40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0

MIMO Mode

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11n HT40 (Covered by VHT40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0

TXBF Mode

Modulation	Data Rate
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (2.4GHz) Link + Bluetooth Link + Scanner Scan Bar Code + Play MP3 + 3.5MM headset adapter cable + 3.5MM PTT/VOIP headset + TC5X USB-C Cable (Charging with AC Adapter)
Remark: For Radiated Test Cases, the tests were performed with 3.5MM PTT headset and TC2X USB-C Cable.	



<CDD Mode>

<Ant. 1>

802.11b RF Avg Output Power (dBm)						
Power vs. Channel			Power vs Data Rate			
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)		
		1M		2M	5.5M	11M
CH 01	2412	17.80	CH 01	17.70	17.70	17.70
CH 06	2437	17.80				
CH 11	2462	17.70				

802.11g RF Avg Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)						
		6M		9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 01	2412	16.90	CH 06	17.80	17.80	17.60	17.60	17.80	17.80	17.80
CH 06	2437	17.90								
CH 11	2462	15.70								

802.11n HT20 RF Avg Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7
CH 01	2412	16.10	CH 06	17.60	17.50	17.50	17.30	17.30	17.30	17.40
CH 06	2437	17.70								
CH 11	2462	15.50								

802.11n HT40 RF Avg Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7
CH 03	2422	14.90	CH 06	17.60	17.60	17.60	17.50	17.50	17.50	17.50
CH 06	2437	17.70								
CH 09	2452	14.70								

802.11ac VHT20 RF Avg Output Power (dBm)											
Power vs. Channel			Power vs Data Rate								
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index							
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8
CH 01	2412	16.20	CH 06	17.70	17.60	17.60	17.40	17.40	17.40	17.50	17.40
CH 06	2437	17.80									
CH 11	2462	15.60									

802.11ac VHT40 RF Avg Output Power (dBm)												
Power vs. Channel			Power vs Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8	MCS 9
CH 03	2422	15.00	CH 06	17.70	17.70	17.70	17.60	17.60	17.60	17.60	17.60	17.60
CH 06	2437	17.80										
CH 09	2452	14.80										



<Ant. 2>

802.11b RF Avg Output Power (dBm)						
Power vs. Channel			Power vs Data Rate			
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)		
		1M		2M	5.5M	11M
CH 01	2412	17.80	CH 01	17.70	17.70	17.70
CH 06	2437	17.70				
CH 11	2462	17.80				

802.11g RF Avg Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)						
		6M		9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 01	2412	16.70	CH 06	17.70	17.70	17.50	17.60	17.70	17.70	17.70
CH 06	2437	17.80								
CH 11	2462	15.80								

802.11n HT20 RF Avg Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7
CH 01	2412	15.90	CH 06	17.60	17.50	17.50	17.30	17.30	17.30	17.30
CH 06	2437	17.70								
CH 11	2462	15.60								

802.11n HT40 RF Avg Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7
CH 03	2422	14.70	CH 06	17.60	17.60	17.60	17.50	17.40	17.50	17.50
CH 06	2437	17.70								
CH 09	2452	14.60								

802.11ac VHT20 RF Avg Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7
CH 01	2412	16.00	CH 06	17.70	17.60	17.60	17.40	17.40	17.40	17.40
CH 06	2437	17.80								
CH 11	2462	15.70								

802.11ac VHT40 RF Avg Output Power (dBm)											
Power vs. Channel			Power vs Data Rate								
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index							
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8
CH 03	2422	14.80	CH 06	17.70	17.70	17.70	17.60	17.50	17.60	17.60	17.60
CH 06	2437	17.80									
CH 09	2452	14.70									



<Ant. 1+2>

802.11b RF Avg Output Power (dBm)						
Power vs. Channel			Power vs Data Rate			
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)		
		1M		2M	5.5M	11M
CH 01	2412	21.91	CH 01	21.76	21.76	21.76
CH 06	2437	21.76				
CH 11	2462	21.81				

802.11g RF Avg Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)						
		6M		9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 01	2412	19.26	CH 06	21.81	21.81	21.61	21.61	21.71	21.81	21.76
CH 06	2437	21.86								
CH 11	2462	18.76								

802.11n HT20 RF Avg Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 01	2412	18.51	CH 06	21.71	21.41	21.41	21.21	21.31	21.36	21.36
CH 06	2437	21.76								
CH 11	2462	18.16								

802.11n HT40 RF Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index						
		MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 03	2422	17.36	CH 06	21.76	21.76	21.76	21.56	21.56	21.56	21.61
CH 06	2437	21.81								
CH 09	2452	17.71								

802.11ac VHT20 RF Avg Output Power (dBm)											
Power vs. Channel			Power vs Data Rate								
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index							
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8
CH 01	2412	18.56	CH 06	21.76	21.51	21.51	21.26	21.36	21.41	21.46	21.41
CH 06	2437	21.81									
CH 11	2462	18.21									

802.11ac VHT40 RF Avg Output Power (dBm)												
Power vs. Channel			Power vs Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8	MCS 9
CH 03	2422	17.41	CH 06	21.81	21.81	21.81	21.61	21.61	21.61	21.66	21.66	21.66
CH 06	2437	21.86										
CH 09	2452	17.76										

<TXBF Mode>


<Ant. 1+2>

802.11ac VHT20 RF Avg Output Power (dBm)												
Power vs. Channel			Power vs Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8	
CH 01	2412	20.94	CH 06	21.08	21.00	20.90	21.09	21.09	21.02	21.09	21.02	
CH 06	2437	21.14										
CH 11	2462	20.16										


802.11ac VHT40 RF Avg Output Power (dBm)												
Power vs. Channel			Power vs Data Rate									
Channel	Frequency (MHz)	MCS Index	Channel	MCS Index								
		MCS 0		MCS 1	MCS 2	MCS 3	MCS 4	MCS 5	MCS 6	MCS 7	MCS 8	MCS 9
CH 03	2422	19.68	CH 06	21.25	21.25	21.19	21.04	21.10	21.17	21.13	21.23	
CH 06	2437	21.31										
CH 09	2452	17.08										

2.3 Connection Diagram of Test System


<AC Conducted Emission Mode>



<WLAN CDD Tx Mode>



<WLAN TXBF Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC1750	MSQ-RTAC66U	N/A	Unshielded, 1.8m
2.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
4.	Barcode	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “Qualcomm Radio Control Toolkit V3.0.303.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

For TXBF mode, the modulation modes and data rates manipulated by the command lines in the engineering program made the EUT link to another EUT by power under the normal operation. The “adb” software tool was used to enable the EUT to transmit signals continuously.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Test Engineer :	Luffy Lin and Richard Qiu	Temperature :	21~25°C
		Relative Humidity :	51~54%

<CDD Mode>

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	12.65	12.80	7.08	7.08	0.50	Pass
11b	1Mbps	1	6	2437	12.80	12.75	7.52	7.04	0.50	Pass
11b	1Mbps	1	11	2462	12.85	12.85	7.54	7.52	0.50	Pass
11g	6Mbps	1	1	2412	16.75	16.80	15.44	15.42	0.50	Pass
11g	6Mbps	1	6	2437	16.80	16.70	15.46	15.78	0.50	Pass
11g	6Mbps	1	11	2462	16.90	16.80	15.68	15.72	0.50	Pass
VHT20	MCS0	1	1	2412	17.85	17.85	15.40	15.32	0.50	Pass
VHT20	MCS0	1	6	2437	17.95	17.90	16.28	15.30	0.50	Pass
VHT20	MCS0	1	11	2462	17.95	17.95	15.96	15.96	0.50	Pass
VHT40	MCS0	1	3	2422	36.40	36.50	35.16	35.12	0.50	Pass
VHT40	MCS0	1	6	2437	36.70	36.60	36.02	35.96	0.50	Pass
VHT40	MCS0	1	9	2452	36.50	36.50	35.15	35.92	0.50	Pass
11b	1Mbps	2	1	2412	12.95	13.00	7.52	8.00	0.50	Pass
11b	1Mbps	2	6	2437	12.95	13.05	7.56	7.56	0.50	Pass
11b	1Mbps	2	11	2462	13.00	13.10	8.00	7.56	0.50	Pass
11g	6Mbps	2	1	2412	16.75	16.70	15.72	15.68	0.50	Pass
11g	6Mbps	2	6	2437	16.85	16.70	15.64	15.40	0.50	Pass
11g	6Mbps	2	11	2462	16.80	16.75	15.68	15.72	0.50	Pass
VHT20	MCS0	2	1	2412	17.95	17.80	16.32	15.08	0.50	Pass
VHT20	MCS0	2	6	2437	17.90	17.85	16.65	15.12	0.50	Pass
VHT20	MCS0	2	11	2462	17.95	17.90	15.70	16.32	0.50	Pass
VHT40	MCS0	2	3	2422	36.40	36.50	35.10	35.16	0.50	Pass
VHT40	MCS0	2	6	2437	36.70	36.50	36.28	35.92	0.50	Pass
VHT40	MCS0	2	9	2452	36.40	36.60	35.08	35.68	0.50	Pass




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<TXBF Modes>

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
VHT20	MCS0	2	1	2412	17.70	18.15	15.12	17.50	0.50	Pass
VHT20	MCS0	2	6	2437	17.75	18.45	15.14	17.56	0.50	Pass
VHT20	MCS0	2	11	2462	17.80	17.90	15.12	17.56	0.50	Pass
VHT40	MCS0	2	3	2422	36.40	36.60	36.88	35.04	0.50	Pass
VHT40	MCS0	2	6	2437	36.60	36.60	35.12	35.92	0.50	Pass
VHT40	MCS0	2	9	2452	36.50	36.50	35.68	36.32	0.50	Pass



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures


<CDD Modes>

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

<TXBF Modes>

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup





3.2.5 Test Result of Average Output Power

Test Engineer :	Luffy Lin and Richard Qiu	Temperature :	21~25°C
		Relative Humidity :	51~54%

<CDD Mode>

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	17.80	17.80		30.00	30.00	0.78	1.93	18.58	19.73	36.00	36.00	Pass
11b	1Mbps	1	6	2437	17.80	17.70		30.00	30.00	0.78	1.93	18.58	19.63	36.00	36.00	Pass
11b	1Mbps	1	11	2462	17.70	17.80		30.00	30.00	0.78	1.93	18.48	19.73	36.00	36.00	Pass
11g	6Mbps	1	1	2412	16.90	16.70		30.00	30.00	0.78	1.93	17.68	18.63	36.00	36.00	Pass
11g	6Mbps	1	6	2437	17.90	17.80		30.00	30.00	0.78	1.93	18.68	19.73	36.00	36.00	Pass
11g	6Mbps	1	11	2462	15.70	15.80		30.00	30.00	0.78	1.93	16.48	17.73	36.00	36.00	Pass
HT20	MCS0	1	1	2412	16.10	15.90		30.00	30.00	0.78	1.93	16.88	17.83	36.00	36.00	Pass
HT20	MCS0	1	6	2437	17.70	17.70		30.00	30.00	0.78	1.93	18.48	19.63	36.00	36.00	Pass
HT20	MCS0	1	11	2462	15.50	15.60		30.00	30.00	0.78	1.93	16.28	17.53	36.00	36.00	Pass
HT40	MCS0	1	3	2422	14.90	14.70		30.00	30.00	0.78	1.93	15.68	16.63	36.00	36.00	Pass
HT40	MCS0	1	6	2437	17.70	17.70		30.00	30.00	0.78	1.93	18.48	19.63	36.00	36.00	Pass
HT40	MCS0	1	9	2452	14.70	14.60		30.00	30.00	0.78	1.93	15.48	16.53	36.00	36.00	Pass
VHT20	MCS0	1	1	2412	16.20	16.00		30.00	30.00	0.78	1.93	16.98	17.93	36.00	36.00	Pass
VHT20	MCS0	1	6	2437	17.80	17.80		30.00	30.00	0.78	1.93	18.58	19.73	36.00	36.00	Pass
VHT20	MCS0	1	11	2462	15.60	15.70		30.00	30.00	0.78	1.93	16.38	17.63	36.00	36.00	Pass
VHT40	MCS0	1	3	2422	15.00	14.80		30.00	30.00	0.78	1.93	15.78	16.73	36.00	36.00	Pass
VHT40	MCS0	1	6	2437	17.80	17.80		30.00	30.00	0.78	1.93	18.58	19.73	36.00	36.00	Pass
VHT40	MCS0	1	9	2452	14.80	14.70		30.00	30.00	0.78	1.93	15.58	16.63	36.00	36.00	Pass
11b	1Mbps	2	1	2412	18.90	18.90	21.91	30.00		1.93		23.84		36.00		Pass
11b	1Mbps	2	6	2437	18.80	18.70	21.76	30.00		1.93		23.69		36.00		Pass
11b	1Mbps	2	11	2462	18.80	18.80	21.81	30.00		1.93		23.74		36.00		Pass
11g	6Mbps	2	1	2412	16.30	16.20	19.26	30.00		1.93		21.19		36.00		Pass
11g	6Mbps	2	6	2437	18.90	18.80	21.86	30.00		1.93		23.79		36.00		Pass
11g	6Mbps	2	11	2462	15.70	15.80	18.76	30.00		1.93		20.69		36.00		Pass
HT20	MCS0	2	1	2412	15.60	15.40	18.51	30.00		1.93		20.44		36.00		Pass
HT20	MCS0	2	6	2437	18.80	18.70	21.76	30.00		1.93		23.69		36.00		Pass
HT20	MCS0	2	11	2462	15.10	15.20	18.16	30.00		1.93		20.09		36.00		Pass
HT40	MCS0	2	3	2422	14.30	14.40	17.36	30.00		1.93		19.29		36.00		Pass
HT40	MCS0	2	6	2437	18.80	18.80	21.81	30.00		1.93		23.74		36.00		Pass
HT40	MCS0	2	9	2452	14.70	14.70	17.71	30.00		1.93		19.64		36.00		Pass
VHT20	MCS0	2	1	2412	15.60	15.50	18.56	30.00		1.93		20.49		36.00		Pass
VHT20	MCS0	2	6	2437	18.90	18.80	21.81	30.00		1.93		23.74		36.00		Pass
VHT20	MCS0	2	11	2462	15.20	15.20	18.21	30.00		1.93		20.14		36.00		Pass
VHT40	MCS0	2	3	2422	14.40	14.40	17.41	30.00		1.93		19.34		36.00		Pass
VHT40	MCS0	2	6	2437	18.80	18.90	21.86	30.00		1.93		23.79		36.00		Pass
VHT40	MCS0	2	9	2452	14.70	14.80	17.76	30.00		1.93		19.69		36.00		Pass



<TXBF Mode>

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
VHT20	MCS0	2	1	2412	17.00	18.70	20.94	30.00		4.38		25.33		36.00	Pass	
VHT20	MCS0	2	6	2437	17.20	19.90	21.14	30.00		4.38		25.53		36.00	Pass	
VHT20	MCS0	2	11	2462	16.10	18.00	20.16	30.00		4.38		24.55		36.00	Pass	
VHT40	MCS0	2	3	2422	16.20	17.10	19.68	30.00		4.38		24.07		36.00	Pass	
VHT40	MCS0	2	6	2437	17.60	19.40	21.31	30.00		4.38		25.69		36.00	Pass	
VHT40	MCS0	2	9	2452	13.60	14.50	17.08	30.00		4.38		21.47		36.00	Pass	

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.


If measurements performed using method (2) plus $10 \log(N)$ exceeds the emission limit, the test should choose method (1) before declaring that the device fails the emission limit.

Method (1): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

Method (2): Measure and add $10 \log(N)$ dB, where N is the number of outputs. (N=2)

3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density


Test Engineer :	Luffy Lin and Richard Qiu	Temperature :	21~25°C
		Relative Humidity :	51~54%

<CDD Modes>

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	-4.82	-4.62	-	0.78	1.93	8.00	8.00	Pass
11b	1Mbps	1	6	2437	-3.40	-4.40	-	0.78	1.93	8.00	8.00	Pass
11b	1Mbps	1	11	2462	-2.76	-4.81	-	0.78	1.93	8.00	8.00	Pass
11g	6Mbps	1	1	2412	-7.93	-8.81	-	0.78	1.93	8.00	8.00	Pass
11g	6Mbps	1	6	2437	-6.51	-7.16	-	0.78	1.93	8.00	8.00	Pass
11g	6Mbps	1	11	2462	-9.04	-8.37	-	0.78	1.93	8.00	8.00	Pass
VHT20	MCS0	1	1	2412	-9.37	-9.41	-	0.78	1.93	8.00	8.00	Pass
VHT20	MCS0	1	6	2437	-7.68	-7.61	-	0.78	1.93	8.00	8.00	Pass
VHT20	MCS0	1	11	2462	-11.02	-9.89	-	0.78	1.93	8.00	8.00	Pass
VHT40	MCS0	1	3	2422	-13.87	-13.32	-	0.78	1.93	8.00	8.00	Pass
VHT40	MCS0	1	6	2437	-11.23	-11.48	-	0.78	1.93	8.00	8.00	Pass
VHT40	MCS0	1	9	2452	-14.16	-14.05	-	0.78	1.93	8.00	8.00	Pass
11b	1Mbps	2	1	2412	-3.66	-2.54	0.47	4.38		8.00		Pass
11b	1Mbps	2	6	2437	-3.77	-3.30	-0.29	4.38		8.00		Pass
11b	1Mbps	2	11	2462	-4.90	-3.70	-0.69	4.38		8.00		Pass
11g	6Mbps	2	1	2412	-9.02	-9.34	-6.01	4.38		8.00		Pass
11g	6Mbps	2	6	2437	-5.81	-5.53	-2.52	4.38		8.00		Pass
11g	6Mbps	2	11	2462	-8.88	-9.10	-5.87	4.38		8.00		Pass
VHT20	MCS0	2	1	2412	-9.68	-9.77	-6.67	4.38		8.00		Pass
VHT20	MCS0	2	6	2437	-7.08	-6.98	-3.97	4.38		8.00		Pass
VHT20	MCS0	2	11	2462	-9.52	-9.77	-6.51	4.38		8.00		Pass
VHT40	MCS0	2	3	2422	-13.82	-13.27	-10.26	4.38		8.00		Pass
VHT40	MCS0	2	6	2437	-9.76	-10.67	-6.75	4.38		8.00		Pass
VHT40	MCS0	2	9	2452	-14.00	-11.52	-8.51	4.38		8.00		Pass




Worst Case Power Density (dBm/3kHz) for MIMO Ant. 1



Date: 29.MAY.2019 09:21:57

Worst Case Power Density (dBm/3kHz) for MIMO Ant. 2





Date: 29.MAY.2019 09:18:13



<TXBF Modes>

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
VHT20	MCS0	2	1	2412	-10.41	-6.84	-3.83	4.38		8.00		Pass
VHT20	MCS0	2	6	2437	-10.06	-4.69	-1.68	4.38		8.00		Pass
VHT20	MCS0	2	11	2462	-9.88	-6.08	-3.07	4.38		8.00		Pass
VHT40	MCS0	2	3	2422	-12.22	-11.50	-8.49	4.38		8.00		Pass
VHT40	MCS0	2	6	2437	-9.54	-7.28	-4.27	4.38		8.00		Pass
VHT40	MCS0	2	9	2452	-13.57	-12.37	-9.36	4.38		8.00		Pass





3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup







3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	Luffy Lin and Richard Qiu	Temperature :	21~25°C
		Relative Humidity :	51~54%

Number of TX = 1, Ant. 1 (Measured)


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 08:07:14

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 08:08:12



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 08:08:27







Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode : 802.11g Test Channel : 01






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 10:20:33

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 10:20:49



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 10:21:03




Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11ac VHT20	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 10:44:13

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 10:44:33



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 10:44:48







Test Mode :	802.11ac VHT20	Test Channel :	11
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	03
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 13:50:35

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 13:50:58



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 13:51:14




Test Mode :	802.11ac VHT40	Test Channel :	09
-------------	----------------	----------------	----





Number of TX = 1, Ant. 2 (Measured)


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 09:06:04

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 09:06:36



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 09:06:53





Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 10:08:44

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 10:09:06



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 10:09:22







Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11ac VHT20	Test Channel :	01
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT20	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 10:56:00

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 10:56:18



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 10:56:35





Test Mode :	802.11ac VHT20	Test Channel :	11
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	03
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 11:57:43

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 11:58:09



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 11:58:24



Test Mode :	802.11ac VHT40	Test Channel :	09
-------------	----------------	----------------	----







<CDD Modes>



Number of TX = 2, Ant. 1 (Measured)

Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----

100kHz PSD reference Level	Channel Plot
-----------------------------------	---------------------




Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
-------------------------------------	-------------------------------------






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 09:25:29

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 09:25:45



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 09:26:00





Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 09:48:19

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 09:48:49





Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 09:49:04







Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11ac VHT20	Test Channel :	01
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT20	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 11:12:23

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 11:12:38





Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 11:12:53





Test Mode :	802.11ac VHT20	Test Channel :	11
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	03
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 11:38:21

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 11:38:43



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 11:38:57




Test Mode :	802.11ac VHT40	Test Channel :	09
-------------	----------------	----------------	----





Number of TX = 2, Ant. 2 (Measured)


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 09:28:49

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 09:29:04



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 09:29:19





Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 09:45:47

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 09:46:12



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 09:46:27







Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11ac VHT20	Test Channel :	01
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT20	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 11:14:48

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 11:15:12





Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 11:15:27





Test Mode : 802.11ac VHT20 Test Channel : 11






Test Mode :	802.11ac VHT40	Test Channel :	03
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 29.MAY.2019 11:34:43

Spurious Emission 30MHz~3GHz



Date: 29.MAY.2019 11:35:08



Spurious Emission 2GHz~25GHz



Date: 29.MAY.2019 11:35:25



Test Mode :	802.11ac VHT40	Test Channel :	09
-------------	----------------	----------------	----







<TXBF Modes>



Number of TX = 2, Ant. 1 (Measured)

Test Mode :	802.11ac VHT20	Test Channel :	01
-------------	----------------	----------------	----

100kHz PSD reference Level	Channel Plot
-----------------------------------	---------------------




Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
-------------------------------------	-------------------------------------






Test Mode :	802.11ac VHT20	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 18.JUN.2019 11:47:49

Spurious Emission 30MHz~3GHz



Date: 18.JUN.2019 11:48:12



Spurious Emission 2GHz~25GHz



Date: 18.JUN.2019 11:48:26





Test Mode :	802.11ac VHT20	Test Channel :	11
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	03
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 14.JUN.2019 14:59:02

Spurious Emission 30MHz~3GHz



Date: 14.JUN.2019 14:59:48



Spurious Emission 2GHz~25GHz



Date: 14.JUN.2019 15:00:04



Test Mode :	802.11ac VHT40	Test Channel :	09
-------------	----------------	----------------	----









Number of TX = 2, Ant. 2 (Measured)

Test Mode :	802.11ac VHT20	Test Channel :	01
-------------	----------------	----------------	----

100kHz PSD reference Level	Channel Plot
-----------------------------------	---------------------




Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
-------------------------------------	-------------------------------------






Test Mode :	802.11ac VHT20	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 18.JUN.2019 11:54:21

Spurious Emission 30MHz~3GHz



Date: 18.JUN.2019 11:54:43



Spurious Emission 2GHz~25GHz



Date: 18.JUN.2019 11:54:58





Test Mode :	802.11ac VHT20	Test Channel :	11
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	03
-------------	----------------	----------------	----






Test Mode :	802.11ac VHT40	Test Channel :	06
-------------	----------------	----------------	----

100kHz PSD reference Level




Date: 14.JUN.2019 15:05:36

Spurious Emission 30MHz~3GHz



Date: 14.JUN.2019 15:06:28



Spurious Emission 2GHz~25GHz



Date: 14.JUN.2019 15:06:42



Test Mode :	802.11ac VHT40	Test Channel :	09
-------------	----------------	----------------	----





3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.




3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW = RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


3.5.4 Test Setup

For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz

<CDD Mode>




<TXBF Modes>




For radiated emissions above 1GHz

<CDD Mode>



<TXBF Modes>





3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 1	Ant. 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4 GHz	0.78	1.93	1.93	4.38	0.00	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$

TXBF modes

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

The EUT supports beamforming for 802.11ac modes.

The directional gain calculation is following F)2)e)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain “DG” is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 1	Ant. 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4 GHz	0.78	1.93	4.38	4.38	0.00	0.00

Power Limit Reduction = DG(Power) – 6dBi, (min = 0)

PSD Limit Reduction = DG(PSD) – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	35419 & 03	30MHz~1GHz	Apr. 30, 2019	May 21, 2019~ Jun. 20, 2019	Apr. 29, 2020	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Dec. 02, 2018	May 21, 2019~ Jun. 20, 2019	Dec. 01, 2019	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY532900 53	20Hz~26.5GHz	Jan. 23, 2019	May 21, 2019~ Jun. 20, 2019	Jan. 22, 2020	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 11, 2019	May 21, 2019~ Jun. 20, 2019	Jan. 10, 2020	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz~18GHz	Apr. 24, 2019	May 21, 2019~ Jun. 20, 2019	Apr. 23, 2020	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	May 20, 2019	May 21, 2019~ Jun. 20, 2019	May 19, 2020	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A023 62	1GHz~26.5GHz	Nov. 02, 2018	May 21, 2019~ Jun. 20, 2019	Nov. 01, 2019	Radiation (03CH07-HY)
Filter	Microwave	H1G013G1	SN477215	1GHz High Pass Filter	Nov. 02, 2018	May 21, 2019~ Jun. 20, 2019	Nov. 01, 2019	Radiation (03CH07-HY)
Filter	Wainwright	WLKS1200-8 SS	SN3	1.2GHz Low Pass Filter	Nov. 02, 2018	May 21, 2019~ Jun. 20, 2019	Nov. 01, 2019	Radiation (03CH07-HY)
Filter	Microwave	H3G018G1	SN477220	3GHz High Pass Filter	Nov. 02, 2018	May 21, 2019~ Jun. 20, 2019	Nov. 01, 2019	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/ 4,MY2865 5/4	9kHz~30MHz	Feb. 26, 2019	May 21, 2019~ Jun. 20, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/ 4,MY2497 1/4,MY156 82/4	30MHz~1GHz	Feb. 26, 2019	May 21, 2019~ Jun. 20, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/ 4,MY2497 1/4,MY156 82/4	1GHz~18GHz	Feb. 26, 2019	May 21, 2019~ Jun. 20, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2858/2	18GHz~40GHz	Feb. 26, 2019	May 21, 2019~ Jun. 20, 2019	Feb. 25, 2020	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	May 21, 2019~ Jun. 20, 2019	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	May 21, 2019~ Jun. 20, 2019	N/A	Radiation (03CH07-HY)
Preamplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	N/A	May 21, 2019~ Jun. 20, 2019	N/A	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 251	18GHz~40GHz	Nov. 20, 2018	May 21, 2019~ Jun. 20, 2019	Nov. 19, 2019	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Apr. 18, 2019	May 21, 2019~ Jun. 20, 2019	Apr. 17, 2020	Radiation (03CH07-HY)
Software	Audix	E3 6.2009-8-24	805040046 56H	N/A	N/A	May 21, 2019~ Jun. 20, 2019	N/A	Radiation (03CH07-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 14, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	May 14, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	May 14, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	May 14, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	May 14, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	May 14, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	May 14, 2019	Dec. 30, 2019	Conduction (CO05-HY)
<CDD Mode>								
Power Sensor	DARE	RPR3006W	13I00030S NO32	9kHz~6GHz	Dec. 03, 2018	May 15, 2019~Jun. 21, 2019	Dec. 02, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	May 15, 2019~Jun. 21, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC120838 2	N/A	Mar. 27, 2019	May 15, 2019~Jun. 21, 2019	Mar. 26, 2020	Conducted (TH05-HY)
<TXBF Mode>								
Power Sensor	DARE	RPR3006W	13I00030S NO32	9kHz~6GHz	Dec. 03, 2018	Jun. 10, 2019~Jun. 20, 2019	Dec. 02, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	Jun. 10, 2019~Jun. 20, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC120838 2	N/A	Mar. 27, 2019	Jun. 10, 2019~Jun. 20, 2019	Mar. 26, 2020	Conducted (TH05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5
---	-----


Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----



Appendix A. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	Temperature :	24~26°C
		Relative Humidity :	52~54%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	36.62	55.88	19.26	L1	OFF	19.5
0.152250	47.86	---	65.88	18.02	L1	OFF	19.5
0.192750	---	34.02	53.92	19.90	L1	OFF	19.5
0.192750	44.64	---	63.92	19.28	L1	OFF	19.5
0.334500	---	37.18	49.34	12.16	L1	OFF	19.5
0.334500	39.48	---	59.34	19.86	L1	OFF	19.5
3.612750	---	25.14	46.00	20.86	L1	OFF	19.7
3.612750	28.04	---	56.00	27.96	L1	OFF	19.7
9.224250	---	25.27	50.00	24.73	L1	OFF	19.9
9.224250	26.64	---	60.00	33.36	L1	OFF	19.9
21.851250	---	25.57	50.00	24.43	L1	OFF	20.3
21.851250	27.21	---	60.00	32.79	L1	OFF	20.3



Test Engineer :	Jimmy Chang	Temperature :	24~26°C
		Relative Humidity :	52~54%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	35.27	55.88	20.61	N	OFF	19.5
0.152250	46.95	---	65.88	18.93	N	OFF	19.5
0.195000	---	34.32	53.82	19.50	N	OFF	19.5
0.195000	44.56	---	63.82	19.26	N	OFF	19.5
0.334500	---	28.78	49.34	20.56	N	OFF	19.5
0.334500	33.63	---	59.34	25.71	N	OFF	19.5
0.829500	---	26.19	46.00	19.81	N	OFF	19.6
0.829500	28.54	---	56.00	27.46	N	OFF	19.6
3.480000	---	24.56	46.00	21.44	N	OFF	19.7
3.480000	26.61	---	56.00	29.39	N	OFF	19.7
16.053000	---	24.70	50.00	25.30	N	OFF	20.2
16.053000	26.23	---	60.00	33.77	N	OFF	20.2



Appendix B. Radiated Spurious Emission

Test Engineer :	Jesse wang, Stan Hsieh and Ken Wu	Temperature :	21~26°C
		Relative Humidity :	52~68%

<CDD Mode>

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11b CH 01 2412MHz		2389.8	54.78	-19.22	74	39.99	32	17.74	34.95	125	185	P	H	
		2389.59	44.19	-9.81	54	29.39	32	17.74	34.94	125	185	A	H	
	*	2412	108.75	-	-	93.89	32.07	17.74	34.95	125	185	P	H	
	*	2412	105.62	-	-	90.76	32.07	17.74	34.95	125	185	A	H	
													H	
														H
			2333.31	54.31	-19.69	74	39.85	31.8	17.59	34.93	348	14	P	V
			2388.96	43.68	-10.32	54	28.88	32	17.74	34.94	348	14	A	V
	*		2412	102.36	-	-	87.5	32.07	17.74	34.95	348	14	P	V
	*		2412	99.24	-	-	84.38	32.07	17.74	34.95	348	14	A	V
														V
														V
802.11b CH 06 2437MHz		2374.82	54.62	-19.38	74	39.96	31.93	17.67	34.94	100	190	P	H	
		2389.94	43.83	-10.17	54	29.04	32	17.74	34.95	100	190	A	H	
	*	2437	108.37	-	-	93.34	32.2	17.79	34.96	100	190	P	H	
	*	2437	105.23	-	-	90.2	32.2	17.79	34.96	100	190	A	H	
			2492.09	54.97	-19.03	74	39.91	32.2	17.84	34.98	100	190	P	H
			2484.74	43.99	-10.01	54	28.92	32.2	17.84	34.97	100	190	A	H
			2376.64	54.66	-19.34	74	40	31.93	17.67	34.94	384	357	P	V
			2387.56	43.73	-10.27	54	28.93	32	17.74	34.94	384	357	A	V
	*		2437	104.58	-	-	89.55	32.2	17.79	34.96	384	357	P	V
	*		2437	101.43	-	-	86.4	32.2	17.79	34.96	384	357	A	V
			2499.23	54.47	-19.53	74	39.41	32.2	17.84	34.98	384	357	P	V
			2494.68	43.84	-10.16	54	28.78	32.2	17.84	34.98	384	357	A	V



802.11b CH 11 2462MHz	*	2462	108.06	-	-	92.99	32.2	17.84	34.97	235	185	P	H
	*	2462	104.91	-	-	89.84	32.2	17.84	34.97	235	185	A	H
		2484.48	54.82	-19.18	74	39.75	32.2	17.84	34.97	235	185	P	H
		2484.72	44.27	-9.73	54	29.2	32.2	17.84	34.97	235	185	A	H
													H
													H
	*	2462	102.07	-	-	87	32.2	17.84	34.97	381	19	P	V
	*	2462	98.96	-	-	83.89	32.2	17.84	34.97	381	19	A	V
		2498.76	54.64	-19.36	74	39.58	32.2	17.84	34.98	381	19	P	V
		2485	43.75	-10.25	54	28.68	32.2	17.84	34.97	381	19	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11b CH 01 2412MHz		4824	44.59	-29.41	74	58.13	34.1	11.39	59.03	100	0	P	H	
													H	
													H	
													H	
			4824	43.08	-30.92	74	56.62	34.1	11.39	59.03	100	0	P	V
														V
														V
802.11b CH 06 2437MHz		4874	43.35	-30.65	74	56.72	34.13	11.42	58.92	100	0	P	H	
		7311	44.39	-29.61	74	53.02	35.7	13.97	58.3	100	0	P	H	
													H	
													H	
			4874	43.79	-30.21	74	57.16	34.13	11.42	58.92	100	0	P	V
			7311	45	-29	74	53.63	35.7	13.97	58.3	100	0	P	V
														V
802.11b CH 11 2462MHz		4924	43.57	-30.43	74	56.76	34.17	11.45	58.81	100	0	P	H	
		7386	45.7	-28.3	74	54.48	35.5	14.07	58.35	100	0	P	H	
													H	
													H	
			4924	44.24	-29.76	74	57.43	34.17	11.45	58.81	100	0	P	V
			7386	45.28	-28.72	74	54.06	35.5	14.07	58.35	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



**2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11g CH 01 2412MHz		2388.225	54.49	-19.51	74	39.69	32	17.74	34.94	128	187	P	H	
		2389.905	45.89	-8.11	54	31.1	32	17.74	34.95	128	187	A	H	
	*	2412	107.52	-	-	92.66	32.07	17.74	34.95	128	187	P	H	
	*	2412	99.8	-	-	84.94	32.07	17.74	34.95	128	187	A	H	
													H	
														H
			2337.3	54.11	-19.89	74	39.65	31.8	17.59	34.93	349	13	P	V
			2388.645	44.58	-9.42	54	29.78	32	17.74	34.94	349	13	A	V
	*		2412	101.37	-	-	86.51	32.07	17.74	34.95	349	13	P	V
	*		2412	93.52	-	-	78.66	32.07	17.74	34.95	349	13	A	V
														V
														V
802.11g CH 06 2437MHz		2365.86	54.59	-19.41	74	39.99	31.87	17.67	34.94	100	190	P	H	
		2389.8	45.05	-8.95	54	30.26	32	17.74	34.95	100	190	A	H	
	*	2437	110.32	-	-	95.29	32.2	17.79	34.96	100	190	P	H	
	*	2437	102.91	-	-	87.88	32.2	17.79	34.96	100	190	A	H	
			2490.34	55.17	-18.83	74	40.1	32.2	17.84	34.97	100	190	P	H
			2483.9	45.24	-8.76	54	30.17	32.2	17.84	34.97	100	190	A	H
			2387.14	54.59	-19.41	74	39.79	32	17.74	34.94	384	357	P	V
			2387.84	44.63	-9.37	54	29.83	32	17.74	34.94	384	357	A	V
	*		2437	106.55	-	-	91.52	32.2	17.79	34.96	384	357	P	V
	*		2437	99.08	-	-	84.05	32.2	17.79	34.96	384	357	A	V
			2493.49	54.18	-19.82	74	39.12	32.2	17.84	34.98	384	357	P	V
			2493.28	44.82	-9.18	54	29.76	32.2	17.84	34.98	384	357	A	V



802.11g CH 11 2462MHz	*	2462	105.93	-	-	90.86	32.2	17.84	34.97	236	185	P	H
	*	2462	98.28	-	-	83.21	32.2	17.84	34.97	236	185	A	H
		2484.28	56.28	-17.72	74	41.21	32.2	17.84	34.97	236	185	P	H
		2483.56	46.51	-7.49	54	31.44	32.2	17.84	34.97	236	185	A	H
													H
													H
	*	2462	98.96	-	-	83.89	32.2	17.84	34.97	382	18	P	V
	*	2462	91.94	-	-	76.87	32.2	17.84	34.97	382	18	A	V
		2483.6	54.76	-19.24	74	39.69	32.2	17.84	34.97	382	18	P	V
		2484.2	44.91	-9.09	54	29.84	32.2	17.84	34.97	382	18	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11g CH 01 2412MHz		4824	43.05	-30.95	74	56.59	34.1	11.39	59.03	100	0	P	H	
													H	
													H	
													H	
			4824	43.3	-30.7	74	56.84	34.1	11.39	59.03	100	0	P	V
														V
														V
802.11g CH 06 2437MHz		4874	42.95	-31.05	74	56.32	34.13	11.42	58.92	100	0	P	H	
		7311	44.01	-29.99	74	52.64	35.7	13.97	58.3	100	0	P	H	
													H	
													H	
			4874	43.36	-30.64	74	56.73	34.13	11.42	58.92	100	0	P	V
			7311	44.95	-29.05	74	53.58	35.7	13.97	58.3	100	0	P	V
														V
802.11g CH 11 2462MHz		4924	43.99	-30.01	74	57.18	34.17	11.45	58.81	100	0	P	H	
		7386	44.15	-29.85	74	52.93	35.5	14.07	58.35	100	0	P	H	
													H	
													H	
			4924	42.8	-31.2	74	55.99	34.17	11.45	58.81	100	0	P	V
			7386	44.55	-29.45	74	53.33	35.5	14.07	58.35	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11n HT20 CH 01 2412MHz		2390	54.21	-19.79	74	39.42	32	17.74	34.95	128	186	P	H	
		2390	45.51	-8.49	54	30.72	32	17.74	34.95	128	186	A	H	
	*	2412	106.78	-	-	91.92	32.07	17.74	34.95	128	186	P	H	
	*	2412	98.95	-	-	84.09	32.07	17.74	34.95	128	186	A	H	
													H	
														H
			2371.32	54.74	-19.26	74	40.08	31.93	17.67	34.94	349	13	P	V
			2389.38	44.53	-9.47	54	29.73	32	17.74	34.94	349	13	A	V
		*	2412	100.19	-	-	85.33	32.07	17.74	34.95	349	13	P	V
		*	2412	92.22	-	-	77.36	32.07	17.74	34.95	349	13	A	V
													V	
													V	
802.11n HT20 CH 06 2437MHz		2386.86	54.35	-19.65	74	39.55	32	17.74	34.94	100	191	P	H	
		2389.8	45.18	-8.82	54	30.39	32	17.74	34.95	100	191	A	H	
		*	2437	110.2	-	-	95.17	32.2	17.79	34.96	100	191	P	H
		*	2437	102.4	-	-	87.37	32.2	17.79	34.96	100	191	A	H
			2488.45	54.79	-19.21	74	39.72	32.2	17.84	34.97	100	191	P	H
			2485.37	45.3	-8.7	54	30.23	32.2	17.84	34.97	100	191	A	H
			2383.36	54.42	-19.58	74	39.69	31.93	17.74	34.94	377	359	P	V
			2371.32	44.56	-9.44	54	29.9	31.93	17.67	34.94	377	359	A	V
		*	2437	106.08	-	-	91.05	32.2	17.79	34.96	377	359	P	V
		*	2437	98.15	-	-	83.12	32.2	17.79	34.96	377	359	A	V
		2488.38	54.54	-19.46	74	39.47	32.2	17.84	34.97	377	359	P	V	
		2485.3	44.92	-9.08	54	29.85	32.2	17.84	34.97	377	359	A	V	



802.11n HT20 CH 11 2462MHz	*	2462	105.93	-	-	90.86	32.2	17.84	34.97	236	188	P	H
	*	2462	97.7	-	-	82.63	32.2	17.84	34.97	236	188	A	H
		2484.92	57.39	-16.61	74	42.32	32.2	17.84	34.97	236	188	P	H
		2483.56	47.71	-6.29	54	32.64	32.2	17.84	34.97	236	188	A	H
													H
													H
	*	2462	99.1	-	-	84.03	32.2	17.84	34.97	382	17	P	V
	*	2462	91.35	-	-	76.28	32.2	17.84	34.97	382	17	A	V
		2499.48	54.54	-19.46	74	39.48	32.2	17.84	34.98	382	17	P	V
		2483.8	44.98	-9.02	54	29.91	32.2	17.84	34.97	382	17	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11n HT20 CH 01 2412MHz		4824	42.71	-31.29	74	56.25	34.1	11.39	59.03	100	0	P	H	
													H	
													H	
													H	
			4824	43.63	-30.37	74	57.17	34.1	11.39	59.03	100	0	P	V
														V
														V
802.11n HT20 CH 06 2437MHz		4874	43.31	-30.69	74	56.68	34.13	11.42	58.92	100	0	P	H	
													H	
			7311	44.97	-29.03	74	53.6	35.7	13.97	58.3	100	0	P	H
														H
			4874	43.07	-30.93	74	56.44	34.13	11.42	58.92	100	0	P	V
			7311	43.91	-30.09	74	52.54	35.7	13.97	58.3	100	0	P	V
														V
802.11n HT20 CH 11 2462MHz		4924	42.92	-31.08	74	56.11	34.17	11.45	58.81	100	0	P	H	
													H	
			7386	45.64	-28.36	74	54.42	35.5	14.07	58.35	100	0	P	H
														H
			4924	43.74	-30.26	74	56.93	34.17	11.45	58.81	100	0	P	V
			7386	44.93	-29.07	74	53.71	35.5	14.07	58.35	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2388.68	56.53	-17.47	74	41.73	32	17.74	34.94	154	188	P	H
		2389.38	48.21	-5.79	54	33.41	32	17.74	34.94	154	188	A	H
	*	2422	103.1	-	-	88.14	32.13	17.79	34.96	154	188	P	H
	*	2422	95.09	-	-	80.13	32.13	17.79	34.96	154	188	A	H
		2492.51	54.55	-19.45	74	39.49	32.2	17.84	34.98	154	188	P	H
		2486.77	45.71	-8.29	54	30.64	32.2	17.84	34.97	154	188	A	H
		2346.54	53.99	-20.01	74	39.47	31.8	17.66	34.94	394	14	P	V
		2386.16	45.31	-8.69	54	30.51	32	17.74	34.94	394	14	A	V
	*	2422	96.86	-	-	81.9	32.13	17.79	34.96	394	14	P	V
	*	2422	89.35	-	-	74.39	32.13	17.79	34.96	394	14	A	V
		2486.28	54.9	-19.1	74	39.83	32.2	17.84	34.97	394	14	P	V
		2499.72	45.45	-8.55	54	30.39	32.2	17.84	34.98	394	14	A	V
802.11n HT40 CH 06 2437MHz		2389.38	54.68	-19.32	74	39.88	32	17.74	34.94	100	190	P	H
		2389.8	47.04	-6.96	54	32.25	32	17.74	34.95	100	190	A	H
	*	2437	106.12	-	-	91.09	32.2	17.79	34.96	100	190	P	H
	*	2437	97.86	-	-	82.83	32.2	17.79	34.96	100	190	A	H
		2483.9	61.72	-12.28	74	46.65	32.2	17.84	34.97	100	190	P	H
		2483.76	51.79	-2.21	54	36.72	32.2	17.84	34.97	100	190	A	H
		2379.02	54.46	-19.54	74	39.8	31.93	17.67	34.94	376	358	P	V
		2389.24	45.39	-8.61	54	30.59	32	17.74	34.94	376	358	A	V
	*	2437	102.32	-	-	87.29	32.2	17.79	34.96	376	358	P	V
	*	2437	93.92	-	-	78.89	32.2	17.79	34.96	376	358	A	V
	2483.9	58.53	-15.47	74	43.46	32.2	17.84	34.97	376	358	P	V	
	2483.55	48.74	-5.26	54	33.67	32.2	17.84	34.97	376	358	A	V	



802.11n HT40 CH 09 2452MHz		2325.4	54.2	-19.8	74	39.74	31.8	17.59	34.93	235	186	P	H
		2371.46	45.23	-8.77	54	30.57	31.93	17.67	34.94	235	186	A	H
	*	2452	103.38	-	-	88.36	32.2	17.79	34.97	235	186	P	H
	*	2452	95.18	-	-	80.16	32.2	17.79	34.97	235	186	A	H
		2484.32	58.11	-15.89	74	43.04	32.2	17.84	34.97	235	186	P	H
		2483.76	50.1	-3.9	54	35.03	32.2	17.84	34.97	235	186	A	H
		2325.82	54.39	-19.61	74	39.93	31.8	17.59	34.93	395	18	P	V
		2381.26	45.33	-8.67	54	30.6	31.93	17.74	34.94	395	18	A	V
	*	2452	97.05	-	-	82.03	32.2	17.79	34.97	395	18	P	V
	*	2452	89.54	-	-	74.52	32.2	17.79	34.97	395	18	A	V
		2485.86	53.91	-20.09	74	38.84	32.2	17.84	34.97	395	18	P	V
		2498.88	45.41	-8.59	54	30.35	32.2	17.84	34.98	395	18	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		4844	42.88	-31.12	74	56.28	34.2	11.39	58.99	100	0	P	H
		7266	44.08	-29.92	74	52.88	35.57	13.91	58.28	100	0	P	H
													H
													H
		4844	42.83	-31.17	74	56.23	34.2	11.39	58.99	100	0	P	V
		7266	43.69	-30.31	74	52.49	35.57	13.91	58.28	100	0	P	V
802.11n HT40 CH 06 2437MHz		4874	42.83	-31.17	74	56.2	34.13	11.42	58.92	100	0	P	H
		7311	44.99	-29.01	74	53.62	35.7	13.97	58.3	100	0	P	H
													H
													H
		4874	43.42	-30.58	74	56.79	34.13	11.42	58.92	100	0	P	V
		7311	45.35	-28.65	74	53.98	35.7	13.97	58.3	100	0	P	V
802.11n HT40 CH 09 2452MHz		4904	43.72	-30.28	74	56.99	34.13	11.45	58.85	100	0	P	H
		7356	43.32	-30.68	74	52.13	35.5	14.02	58.33	100	0	P	H
													H
													H
		4904	42.75	-31.25	74	56.02	34.13	11.45	58.85	100	0	P	V
		7356	43.54	-30.46	74	52.35	35.5	14.02	58.33	100	0	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz
2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
2.4GHz 802.11n HT40 LF		30	23.18	-16.82	40	27.24	24.6	1.32	29.98	-	-	P	H	
		84.27	18.57	-21.43	40	33.09	13.75	1.72	29.99	-	-	P	H	
		134.49	22.23	-21.27	43.5	32.76	17.4	2.01	29.94	-	-	P	H	
		668.2	29.38	-16.62	46	28.49	26.21	4.31	29.63	-	-	P	H	
		862.8	33.5	-12.5	46	28.62	29.01	4.93	29.06	-	-	P	H	
		951	34.28	-11.72	46	27.36	30.39	5.08	28.55	100	0	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
			30	32.33	-7.67	40	36.39	24.6	1.32	29.98	100	0	P	V
			33.78	29.59	-10.41	40	35.68	22.57	1.32	29.98	-	-	P	V
			81.84	27.04	-12.96	40	41.91	13.4	1.72	29.99	-	-	P	V
			666.1	29.04	-16.96	46	28.16	26.2	4.31	29.63	-	-	P	V
			850.9	32.55	-13.45	46	28.1	28.78	4.77	29.1	-	-	P	V
			958.7	34.79	-11.21	46	27.41	30.8	5.08	28.5	-	-	P	V
												V		
												V		
												V		
												V		
												V		
												V		
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11b CH 01 2412MHz		2389.38	56.5	-17.5	74	41.7	32	17.74	34.94	125	240	P	H	
		2390	45.19	-8.81	54	30.4	32	17.74	34.95	125	240	A	H	
	*	2412	109.54	-	-	94.68	32.07	17.74	34.95	125	240	P	H	
	*	2412	106.36	-	-	91.5	32.07	17.74	34.95	125	240	A	H	
													H	
													H	
			2369.22	54.64	-19.36	74	39.98	31.93	17.67	34.94	397	143	P	V
			2390	43.99	-10.01	54	29.2	32	17.74	34.95	397	143	A	V
	*		2412	107.97	-	-	93.11	32.07	17.74	34.95	397	143	P	V
	*		2412	104.65	-	-	89.79	32.07	17.74	34.95	397	143	A	V
													V	
													V	
802.11b CH 06 2437MHz		2384.9	55.21	-18.79	74	40.48	31.93	17.74	34.94	298	266	P	H	
		2389.94	44.61	-9.39	54	29.82	32	17.74	34.95	298	266	A	H	
	*	2437	110.29	-	-	95.26	32.2	17.79	34.96	298	266	P	H	
	*	2437	107.13	-	-	92.1	32.2	17.79	34.96	298	266	A	H	
			2491.67	54.83	-19.17	74	39.76	32.2	17.84	34.97	298	266	P	H
			2487.33	44.44	-9.56	54	29.37	32.2	17.84	34.97	298	266	A	H
			2387.7	55.71	-18.29	74	40.91	32	17.74	34.94	397	154	P	V
			2389.52	44.37	-9.63	54	29.57	32	17.74	34.94	397	154	A	V
	*		2437	108.5	-	-	93.47	32.2	17.79	34.96	397	154	P	V
	*		2437	105.33	-	-	90.3	32.2	17.79	34.96	397	154	A	V
			2498.88	55.06	-18.94	74	40	32.2	17.84	34.98	397	154	P	V
			2494.96	44.41	-9.59	54	29.35	32.2	17.84	34.98	397	154	A	V



802.11b CH 11 2462MHz	*	2462	109.12	-	-	94.05	32.2	17.84	34.97	100	235	P	H
	*	2462	105.82	-	-	90.75	32.2	17.84	34.97	100	235	A	H
		2483.64	54.7	-19.3	74	39.63	32.2	17.84	34.97	100	235	P	H
		2484.48	45.26	-8.74	54	30.19	32.2	17.84	34.97	100	235	A	H
													H
													H
	*	2462	106.54	-	-	91.47	32.2	17.84	34.97	342	152	P	V
	*	2462	103.36	-	-	88.29	32.2	17.84	34.97	342	152	A	V
		2498.52	54.82	-19.18	74	39.76	32.2	17.84	34.98	342	152	P	V
		2485.08	44.19	-9.81	54	29.12	32.2	17.84	34.97	342	152	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	43.56	-30.44	74	57.1	34.1	11.39	59.03	100	0	P	H
													H
													H
													H
		4824	45.02	-28.98	74	58.56	34.1	11.39	59.03	100	0	P	V
													V
													V
802.11b CH 06 2437MHz		4874	47.58	-26.42	74	60.95	34.13	11.42	58.92	100	0	P	H
		7311	44.12	-29.88	74	52.75	35.7	13.97	58.3	100	0	P	H
													H
													H
		4874	43.65	-30.35	74	57.02	34.13	11.42	58.92	100	0	P	V
		7311	44.7	-29.3	74	53.33	35.7	13.97	58.3	100	0	P	V
													V
802.11b CH 11 2462MHz		4824	43.26	-30.74	74	56.8	34.1	11.39	59.03	100	0	P	H
		7386	45.11	-28.89	74	53.89	35.5	14.07	58.35	100	0	P	H
													H
													H
		4924	47.76	-26.24	74	60.95	34.17	11.45	58.81	100	0	P	V
		7386	45.51	-28.49	74	54.29	35.5	14.07	58.35	100	0	P	V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11g CH 01 2412MHz		2390	62.39	-11.61	74	47.6	32	17.74	34.95	124	237	P	H	
		2390	51.01	-2.99	54	36.22	32	17.74	34.95	124	237	A	H	
	*	2412	108.27	-	-	93.41	32.07	17.74	34.95	124	237	P	H	
	*	2412	100.8	-	-	85.94	32.07	17.74	34.95	124	237	A	H	
													H	
														H
			2389.38	55.94	-18.06	74	41.14	32	17.74	34.94	397	144	P	V
			2390	46.88	-7.12	54	32.09	32	17.74	34.95	397	144	A	V
	*		2412	106.37	-	-	91.51	32.07	17.74	34.95	397	144	P	V
	*		2412	98.92	-	-	84.06	32.07	17.74	34.95	397	144	A	V
														V
														V
802.11g CH 06 2437MHz		2387.84	57.28	-16.72	74	42.48	32	17.74	34.94	298	266	P	H	
		2389.52	48.33	-5.67	54	33.53	32	17.74	34.94	298	266	A	H	
	*	2437	111.86	-	-	96.83	32.2	17.79	34.96	298	266	P	H	
	*	2437	104.74	-	-	89.71	32.2	17.79	34.96	298	266	A	H	
			2483.5	56.39	-17.61	74	41.32	32.2	17.84	34.97	298	266	P	H
			2483.69	46.29	-7.71	54	31.22	32.2	17.84	34.97	298	266	A	H
			2341.08	55.11	-18.89	74	40.59	31.8	17.66	34.94	396	154	P	V
			2388.26	45.78	-8.22	54	30.98	32	17.74	34.94	396	154	A	V
	*		2437	110.33	-	-	95.3	32.2	17.79	34.96	396	154	P	V
	*		2437	102.99	-	-	87.96	32.2	17.79	34.96	396	154	A	V
			2486.84	54.65	-19.35	74	39.58	32.2	17.84	34.97	396	154	P	V
			2484.95	45.41	-8.59	54	30.34	32.2	17.84	34.97	396	154	A	V



802.11g CH 11 2462MHz	*	2462	106.7	-	-	91.63	32.2	17.84	34.97	100	237	P	H
	*	2462	98.99	-	-	83.92	32.2	17.84	34.97	100	237	A	H
		2483.52	60.5	-13.5	74	45.43	32.2	17.84	34.97	100	237	P	H
		2483.52	50.85	-3.15	54	35.78	32.2	17.84	34.97	100	237	A	H
													H
													H
	*	2462	103.96	-	-	88.89	32.2	17.84	34.97	346	152	P	V
	*	2462	96.56	-	-	81.49	32.2	17.84	34.97	346	152	A	V
		2483.64	55.01	-18.99	74	39.94	32.2	17.84	34.97	346	152	P	V
		2483.52	45.57	-8.43	54	30.5	32.2	17.84	34.97	346	152	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												