



# FCC RADIO TEST REPORT

**FCC ID** : UZ7EC500K  
**Equipment** : Enterprise Computer  
**Brand Name** : Zebra  
**Model Name** : EC500K  
**Applicant** : Zebra Technologies Corporation  
1 Zebra Plaza, Holtsville, NY 11742  
**Manufacturer** : Zebra Technologies Corporation  
1 Zebra Plaza, Holtsville, NY 11742  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Jul. 09, 2020 and testing was started from Jul. 17, 2020 and completed on Aug. 07, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

*Louis Wu*

Reviewed by: Louis Wu

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1 General Description.....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT .....	6
1.4 Testing Location .....	7
1.5 Applicable Standards.....	7
<b>2 Test Configuration of Equipment Under Test.....</b>	<b>8</b>
2.1 Carrier Frequency Channel .....	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system .....	13
2.5 EUT Operation Test Setup .....	13
2.6 Measurement Results Explanation Example.....	13
<b>3 Test Result.....</b>	<b>14</b>
3.1 Number of Channel Measurement .....	14
3.2 Hopping Channel Separation Measurement .....	16
3.3 Dwell Time Measurement.....	22
3.4 20dB and 99% Bandwidth Measurement .....	24
3.5 Output Power Measurement.....	35
3.6 Conducted Band Edges Measurement.....	37
3.7 Conducted Spurious Emission Measurement .....	44
3.8 Radiated Band Edges and Spurious Emission Measurement .....	54
3.9 AC Conducted Emission Measurement.....	59
3.10 Antenna Requirements.....	61
<b>4 List of Measuring Equipment .....</b>	<b>62</b>
<b>5 Uncertainty of Evaluation.....</b>	<b>64</b>
<b>Appendix A. AC Conducted Emission Test Result</b>	
<b>Appendix B. Radiated Spurious Emission</b>	
<b>Appendix C. Radiated Spurious Emission Plots</b>	
<b>Appendix D. Duty Cycle Plots</b>	
<b>Appendix E. Setup Photographs</b>	



### History of this test report

<b>Report No.</b>	<b>Version</b>	<b>Description</b>	<b>Issued Date</b>
FR070601A	01	Initial issue of report	Sep. 11, 2020



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 7.92 dB at 56.190 MHz
3.9	15.207	AC Conducted Emission	Pass	Under limit 7.79 dB at 0.157 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang**

**Report Producer: Vivian Hsu**



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Enterprise Computer
Brand Name	Zebra
Model Name	EC500K
FCC ID	UZ7EC500K
EUT supports Radios application	NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	EV2
SW Version	Android version 10
FW Version	10-12-29.00-QG-U00-PRD-HEL-04
MFD	17JUN20 13JUN20 20JUN20 15JUN20
EUT Stage	Engineering Sample

Remark: The above EUT's information was declared by manufacturer.

Specification of Accessories				
AC Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V15W0US
USB TYPE-C to TYPE-C cable	Brand Name	Zebra	Part Number	CBL-EC5X-USBC3A-01
Battery 1	Brand Name	Zebra	Part Number	BT-000424-00
Battery 2	Brand Name	Zebra	Part Number	BT-000424-08
Earphone 1	Brand Name	Zebra	Part Number	HDST-35MM-PTVP-01
Earphone 2	Brand Name	Zebra	Part Number	HS2100-OTH
USB TYPE C to 3.5mm audio connector	Brand Name	Symbol	Part Number	ADP-USBC-35MM1-01
3.5mm Jack 43"(1.1m) Standard Cable	Brand Name	Zebra	Part Number	CBL-HS2100-3MS1-01
Trigger Handle	Brand Name	Zebra	Part Number	TRG-EC5X-SNP1-01
Soft Holster	Brand Name	Zebra	Part Number	SG-EC5X-HLSTR1-01
Protective Boot	Brand Name	Zebra	Part Number	SG-EC5X-BOOT1-01



Sample list				
	Sample 1	Sample 2	Sample 3	Sample 4
Operating System	ANDROID	ANDROID	ANDROID	ANDROID
RAM	3GB RAM	4GB	4GB	3GB
FLASH	32GB	64GB	64GB	32GB
Scanner	SE4100	SE4100	SE4100	NO
Front Camera	NO	5MP	5MP	5MP
Rear Camera	13MP	13MP	13MP	13MP
	MICRO SD	MICRO SD	MICRO SD	MICRO SD
	GMS	GMS	GMS	GMS
Back connector	2-PIN	2-PIN	8-PIN	NO I/O CONNECTOR
	ROW - Excludes China	ROW - Excludes China	ROW - Excludes China	ROW - Excludes China

## 1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 3.23 dBm (0.0021 W) Bluetooth EDR (2Mbps) : 2.32 dBm (0.0017 W) Bluetooth EDR (3Mbps) : 2.63 dBm (0.0018 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.845MHz Bluetooth EDR (2Mbps) : 1.161MHz Bluetooth EDR (3Mbps) : 1.143MHz
Antenna Type / Gain	PIFA Antenna with gain 3.1 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

## 1.3 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.4 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH16-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

### 1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-





## 2.2 Test Mode

Channel	Frequency	Bluetooth Average Output Power		
		GFSK / 1Mbps		
		DH1	DH3	DH5
Ch00	2402MHz	1.35 dBm	1.33 dBm	1.29 dBm
Ch39	2441MHz	2.71 dBm	2.48 dBm	2.47 dBm
Ch78	2480MHz	<b>2.98 dBm</b>	2.97 dBm	2.89 dBm

Channel	Frequency	Bluetooth Average Output Power		
		$\pi/4$ -DQPSK / 2Mbps		
		2DH1	2DH3	2DH5
Ch00	2402MHz	-1.86 dBm	-2.04 dBm	-2.12 dBm
Ch39	2441MHz	-0.60 dBm	-0.89 dBm	-0.95 dBm
Ch78	2480MHz	<b>0.07 dBm</b>	-0.35 dBm	-0.43 dBm

Channel	Frequency	Bluetooth Average Output Power		
		8-DPSK / 3Mbps		
		3DH1	3DH3	3DH5
Ch00	2402MHz	-1.75 dBm	-1.97 dBm	-1.94 dBm
Ch39	2441MHz	-0.66 dBm	-0.87 dBm	-0.85 dBm
Ch78	2480MHz	<b>0.03 dBm</b>	-0.35 dBm	-0.69 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		GFSK / 1Mbps		
		DH1	DH3	DH5
Ch00	2402MHz	1.53 dBm	1.52 dBm	1.49 dBm
Ch39	2441MHz	2.87 dBm	2.57 dBm	2.55 dBm
Ch78	2480MHz	<b>3.23 dBm</b>	3.20 dBm	3.18 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		$\pi/4$ -DQPSK / 2Mbps		
		2DH1	2DH3	2DH5
Ch00	2402MHz	0.79 dBm	0.65 dBm	0.70 dBm
Ch39	2441MHz	1.83 dBm	1.81 dBm	1.81 dBm
Ch78	2480MHz	<b>2.32 dBm</b>	2.28 dBm	2.27 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		8-DPSK / 3Mbps		
		3DH1	3DH3	3DH5
Ch00	2402MHz	1.58 dBm	1.00 dBm	1.22 dBm
Ch39	2441MHz	2.33 dBm	2.08 dBm	2.26 dBm
Ch78	2480MHz	<b>2.63 dBm</b>	2.60 dBm	2.61 dBm

**Remark:**The data rate was set in 1Mbps for all the test items due to the highest RF output power.

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.




The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
<b>Conducted Test Cases</b>	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
<b>Radiated Test Cases</b>	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
<b>AC Conducted Emission</b>	Mode 1 : WLAN (2.4GHz) Link + Bluetooth Link + NFC Active + Battery 1 + MPEG4 (Color Bar) + USB Cable (Charging from AC Adapter) for Sample 1		
<b>Remark:</b>			
<ol style="list-style-type: none"> <li>For radiated test cases, the worst mode data rate 1Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.</li> <li>For Radiated Test Cases, the tests were performed with Battery 1, and Sample 1</li> </ol>			

## 2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth Tx Mode>





## 2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	Dell	Latitude 3400	FCC DOC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
4.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
5.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m

## 2.5 EUT Operation Test Setup

The RF test items, utility “QRCT 4” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to contact with base station to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of Number of Hopping Frequency


Test Engineer :	Hank Hsu and Shiming Liu	Temperature :	23.5~24.2°C
		Relative Humidity :	49~55%

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 4.AUG.2020 18:42:24



Date: 4.AUG.2020 18:43:09

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup








3.2.5 Test Result of Hopping Channel Separation

Test Engineer :	Hank Hsu and Shiming Liu	Temperature :	23.5~24.2°C
		Relative Humidity :	49~55%

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	1.003	0.5943	Pass
DH	1Mbps	1	39	2441	1.003	0.5963	Pass
DH	1Mbps	1	78	2480	1.003	0.5982	Pass
2DH	2Mbps	1	0	2402	1.012	0.8104	Pass
2DH	2Mbps	1	39	2441	0.994	0.8104	Pass
2DH	2Mbps	1	78	2480	0.981	0.8365	Pass
3DH	3Mbps	1	0	2402	0.868	0.7959	Pass
3DH	3Mbps	1	39	2441	1.003	0.8046	Pass
3DH	3Mbps	1	78	2480	1.311	0.8133	Pass

<1Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 4.AUG.2020 19:03:16




Channel Separation Plot on Channel 39 - 40



Date: 4.AUG.2020 19:18:03

Channel Separation Plot on Channel 77 - 78




Date: 4.AUG.2020 20:20:17




<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 4.AUG.2020 20:35:17


Channel Separation Plot on Channel 39 - 40



Date: 4.AUG.2020 20:44:43




Channel Separation Plot on Channel 77 - 78



Date: 4.AUG.2020 20:54:20

<3Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 4.AUG.2020 21:27:06




Channel Separation Plot on Channel 39 - 40



Date: 4.AUG.2020 21:33:08

Channel Separation Plot on Channel 77 - 78



Date: 4.AUG.2020 21:40:58

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup






3.3.5 Test Result of Dwell Time

Test Engineer :	Hank Hsu and Shiming Liu	Temperature :	23.5~24.2°C
		Relative Humidity :	49~55%

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec) (MHz)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

Package Transfer Time Plot



Date: 17.JUL.2020 00:51:04

Remark:

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

### 3.4 20dB and 99% Bandwidth Measurement

#### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

#### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
RBW  $\geq$  1-5% of the 99% bandwidth; VBW  $\geq$  3 \* RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
6. Measure and record the results in the test report.

#### 3.4.4 Test Setup








3.4.5 Test Result of 20dB Bandwidth

Test Engineer :	Hank Hsu and Shiming Liu	Temperature :	23.5~24.2°C
		Relative Humidity :	49~55%

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	20db BW (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.892	Pass
DH	1Mbps	1	39	2441	0.894	Pass
DH	1Mbps	1	78	2480	0.897	Pass
2DH	2Mbps	1	0	2402	1.216	Pass
2DH	2Mbps	1	39	2441	1.216	Pass
2DH	2Mbps	1	78	2480	1.255	Pass
3DH	3Mbps	1	0	2402	1.194	Pass
3DH	3Mbps	1	39	2441	1.207	Pass
3DH	3Mbps	1	78	2480	1.220	Pass


<1Mbps>

20 dB Bandwidth Plot on Channel 00






20 dB Bandwidth Plot on Channel 39



Date: 4.AUG.2020 19:24:32

20 dB Bandwidth Plot on Channel 78




Date: 4.AUG.2020 20:23:00




<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 4.AUG.2020 20:38:46


20 dB Bandwidth Plot on Channel 39



Date: 4.AUG.2020 20:46:54




20 dB Bandwidth Plot on Channel 78



Date: 4.AUG.2020 21:10:53

<3Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 4.AUG.2020 21:28:48




20 dB Bandwidth Plot on Channel 39



Date: 4.AUG.2020 21:34:56

20 dB Bandwidth Plot on Channel 78



Date: 4.AUG.2020 21:42:04



3.4.6 Test Result of 99% Occupied Bandwidth

Test Engineer :	Hank Hsu and Shiming Liu	Temperature :	23.5~24.2°C
		Relative Humidity :	49~55%

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	99% Bandwidth (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.839	Pass
DH	1Mbps	1	39	2441	0.845	Pass
DH	1Mbps	1	78	2480	0.845	Pass
2DH	2Mbps	1	0	2402	1.161	Pass
2DH	2Mbps	1	39	2441	1.152	Pass
2DH	2Mbps	1	78	2480	1.161	Pass
3DH	3Mbps	1	0	2402	1.114	Pass
3DH	3Mbps	1	39	2441	1.126	Pass
3DH	3Mbps	1	78	2480	1.143	Pass

<1Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 4.AUG.2020 19:13:36




99% Occupied Bandwidth Plot on Channel 39



Date: 4.AUG.2020 19:50:32

99% Occupied Bandwidth Plot on Channel 78




Date: 4.AUG.2020 20:25:38




<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 4.AUG.2020 20:40:53

99% Occupied Bandwidth Plot on Channel 39




Date: 4.AUG.2020 20:48:00





99% Occupied Bandwidth Plot on Channel 78



Date: 4.AUG.2020 21:12:42

<3Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 4.AUG.2020 21:30:22



99% Occupied Bandwidth Plot on Channel 39



Date: 4.AUG.2020 21:35:58

99% Occupied Bandwidth Plot on Channel 78



Date: 4.AUG.2020 21:43:54

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.5 Output Power Measurement

### 3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:  
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


### 3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup





3.5.5 Test Result of Peak Output Power

Test Engineer :		Hank Hsu and Shiming Liu		Temperature :	23.5~24.2°C
				Relative Humidity :	49~55%

DH	CH.	N <sub>TX</sub>	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	1.53	20.97	Pass
	39	1	2.87	20.97	Pass
	78	1	<b>3.23</b>	20.97	Pass

2DH	CH.	N <sub>TX</sub>	Peak Power (dBm)	Power Limit (dBm)	Test Result
2DH1	0	1	0.79	20.97	Pass
	39	1	1.83	20.97	Pass
	78	1	<b>2.32</b>	20.97	Pass

3DH	CH.	N <sub>TX</sub>	Peak Power (dBm)	Power Limit (dBm)	Test Result
3DH1	0	1	1.58	20.97	Pass
	39	1	2.33	20.97	Pass
	78	1	<b>2.63</b>	20.97	Pass

3.5.6 Test Result of Average Output Power (Reporting Only)

Test Engineer :		Hank Hsu and Shiming Liu		Temperature :	23.5~24.2°C
				Relative Humidity :	49~55%

DH	CH.	N <sub>TX</sub>	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	1.35	5.16
	39	1	2.71	5.16
	78	1	<b>2.98</b>	5.16

2DH	CH.	N <sub>TX</sub>	Average Power (dBm)	Duty Factor (dB)
2DH1	0	1	-1.86	5.16
	39	1	-0.60	5.16
	78	1	<b>0.07</b>	5.16

3DH	CH.	N <sub>TX</sub>	Average Power (dBm)	Duty Factor (dB)
3DH1	0	1	-1.75	5.12
	39	1	-0.66	5.12
	78	1	<b>0.03</b>	5.12

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges

Test Engineer :	Hank Hsu and Shiming Liu	Temperature :	23.5~24.2°C
		Relative Humidity :	49~55%


<1Mbps>

#### Low Band Edge Plot on Channel 00



Date: 4.AUG.2020 19:11:17

#### High Band Edge Plot on Channel 78




Date: 4.AUG.2020 20:24:13




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 4.AUG.2020 20:39:52

High Band Edge Plot on Channel 78




Date: 4.AUG.2020 21:11:46




<3Mbps>

Low Band Edge Plot on Channel 00



Date: 4.AUG.2020 21:29:22

High Band Edge Plot on Channel 78



Date: 4.AUG.2020 21:42:49






### 3.6.6 Test Result of Conducted Hopping Mode Band Edges

Test Engineer :	Hank Hsu and Shiming Liu	Temperature :	23.5~24.2°C
		Relative Humidity :	49~55%


<1Mbps>

#### Hopping Mode Low Band Edge Plot



Date: 4.AUG.2020 18:46:58

#### Hopping Mode High Band Edge Plot




Date: 4.AUG.2020 18:47:47




<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 4.AUG.2020 18:49:34

Hopping Mode High Band Edge Plot




Date: 4.AUG.2020 18:50:54




<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 4.AUG.2020 18:57:32

Hopping Mode High Band Edge Plot



Date: 4.AUG.2020 18:58:02

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.7.4 Test Setup






### 3.7.5 Test Result of Conducted Spurious Emission

Test Engineer :	Hank Hsu and Shiming Liu	Temperature :	23.5~24.2°C
		Relative Humidity :	49~55%


<1Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 4.AUG.2020 19:15:26


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 4.AUG.2020 19:16:08




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 4.AUG.2020 20:18:05


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 4.AUG.2020 20:18:35




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 4.AUG.2020 20:26:19

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 4.AUG.2020 20:26:49




<2Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 4.AUG.2020 20:41:35

CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 4.AUG.2020 20:42:05






CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 4.AUG.2020 20:50:36


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 4.AUG.2020 20:51:05




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 4.AUG.2020 21:13:23

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 4.AUG.2020 21:13:53




<3Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 4.AUG.2020 21:31:06


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 4.AUG.2020 21:31:37




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 4.AUG.2020 21:38:56


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 4.AUG.2020 21:39:27



CSE Plot on Ch 78 between 30MHz ~ 3 GHz



CSE Plot on Ch 78 between 2 GHz ~ 25 GHz





### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

See list of measuring equipment of this test report.


**3.8.3 Test Procedures**

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1 \text{ GHz}$ , RBW=1MHz for  $f > 1\text{GHz}$  ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup

For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz






**For radiated emissions above 1GHz**



**For radiated emissions above 18GHz**





### **3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### **3.8.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix B and C.

### **3.8.7 Duty Cycle**

Please refer to Appendix D.

### **3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix B and C.



### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



AMN = Artificial mains network (LISN)  
AE = Associated equipment  
EUT = Equipment under test  
ISN = Impedance stabilization network

### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Jul. 17, 2020~ Aug. 04, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Meter	Agilent	E4416A	GB412923 44	N/A	Dec. 27, 2019	Jul. 17, 2020~ Aug. 04, 2020	Dec. 26, 2020	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US404415 48	50MHz~18GHz	Dec. 27, 2019	Jul. 17, 2020~ Aug. 04, 2020	Dec. 26, 2020	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 15, 2019	Jul. 17, 2020~ Aug. 04, 2020	Nov. 14, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Dec. 30, 2019	Jul. 17, 2020~ Aug. 04, 2020	Dec. 29, 2020	Conducted (TH05-HY)
BT Base Station	Rohde & Schwarz	CBT	101136	BT 3.0	Oct. 27, 2019	Jul. 17, 2020~ Aug. 04, 2020	Oct. 26, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC130048 4	N/A	Aug. 22, 2019	Jul. 17, 2020~ Aug. 04, 2020	Aug. 21, 2020	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 27, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Jul. 27, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Jul. 27, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Jul. 27, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 27, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Jul. 27, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Jul. 27, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 09, 2020	Jul. 21, 2020~ Aug. 07, 2020	Jan. 08, 2021	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL6111D&0 0802N1D01N- 06	47020&06	30MHz to 1GHz	Oct. 12, 2019	Jul. 21, 2020~ Aug. 07, 2020	Oct. 11, 2020	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-152 2	1G~18GHz	Sep. 19, 2019	Jul. 21, 2020~ Aug. 07, 2020	Sep. 18, 2020	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 980	18GHz~40GHz	Jan. 10, 2020	Jul. 21, 2020~ Aug. 07, 2020	Jan. 09, 2021	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1G	Oct. 01, 2019	Jul. 21, 2020~ Aug. 07, 2020	Sep. 30, 2020	Radiation (03CH16-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 0055006	1GHz~18GHz	May 07, 2020	Jul. 21, 2020~ Aug. 07, 2020	May 06, 2021	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~40GHz	Dec. 13, 2019	Jul. 21, 2020~ Aug. 07, 2020	Dec. 12, 2020	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY532702 64	1GHz~26.5GHz	Dec. 11, 2019	Jul. 21, 2020~ Aug. 07, 2020	Dec.10, 2020	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY572901 11	3Hz~26.5GHz	Dec. 05, 2019	Jul. 21, 2020~ Aug. 07, 2020	Dec. 04, 2020	Radiation (03CH16-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Agilent	E4446A	MY501801 36	3Hz~44GHz	May 04, 2020	Jul. 21, 2020~ Aug. 07, 2020	May 03, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11680/ 4PE	NA	Aug. 30, 2019	Jul. 21, 2020~ Aug. 07, 2020	Aug. 29, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11688/ 4PE	NA	Aug. 30, 2019	Jul. 21, 2020~ Aug. 07, 2020	Aug. 29, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	EC-A5-300 -5757	NA	Aug. 30, 2019	Jul. 21, 2020~ Aug. 07, 2020	Aug. 29, 2020	Radiation (03CH16-HY)
Hygrometer	TECPEL	DTM-303B	TP162965	N/A	Oct. 25, 2019	Jul. 21, 2020~ Aug. 07, 2020	Oct. 24, 2020	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	Jul. 21, 2020~ Aug. 07, 2020	N/A	Radiation (03CH16-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.5
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	6.3
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.7
---	-----






## Appendix A. AC Conducted Emission Test Results

Test Engineer :	Tom Lee	Temperature :	23~25°C
		Relative Humidity :	42~50%

# EUT Information

Report NO : 070601  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	45.08	55.63	10.55	L1	OFF	19.6
0.156750	57.84	---	65.63	7.79	L1	OFF	19.6
0.170250	---	33.17	54.95	21.78	L1	OFF	19.6
0.170250	44.54	---	64.95	20.41	L1	OFF	19.6
0.222630	---	33.79	52.72	18.93	L1	OFF	19.6
0.222630	43.62	---	62.72	19.10	L1	OFF	19.6
0.235500	---	33.70	52.25	18.55	L1	OFF	19.6
0.235500	42.54	---	62.25	19.71	L1	OFF	19.6
0.298500	---	28.79	50.28	21.49	L1	OFF	19.6
0.298500	35.69	---	60.28	24.59	L1	OFF	19.6
0.309750	---	27.15	49.98	22.83	L1	OFF	19.6
0.309750	33.87	---	59.98	26.11	L1	OFF	19.6
0.354750	---	23.61	48.85	25.24	L1	OFF	19.6
0.354750	26.55	---	58.85	32.30	L1	OFF	19.6
1.551750	---	24.82	46.00	21.18	L1	OFF	19.6
1.551750	27.04	---	56.00	28.96	L1	OFF	19.6
9.496500	---	25.67	50.00	24.33	L1	OFF	20.1
9.496500	27.00	---	60.00	33.00	L1	OFF	20.1
13.560000	---	35.08	50.00	14.92	L1	OFF	20.2
13.560000	44.77	---	60.00	15.23	L1	OFF	20.2

# EUT Information

Report NO : 070601  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	41.80	55.88	14.08	N	OFF	19.5
0.152250	53.69	---	65.88	12.19	N	OFF	19.5
0.215250	---	30.40	53.00	22.60	N	OFF	19.5
0.215250	40.09	---	63.00	22.91	N	OFF	19.5
0.242250	---	28.21	52.02	23.81	N	OFF	19.5
0.242250	36.57	---	62.02	25.45	N	OFF	19.5
0.289320	---	26.57	50.54	23.97	N	OFF	19.5
0.289320	33.17	---	60.54	27.37	N	OFF	19.5
0.312990	---	26.68	49.89	23.21	N	OFF	19.5
0.312990	32.71	---	59.89	27.18	N	OFF	19.5
0.564000	---	25.36	46.00	20.64	N	OFF	19.5
0.564000	27.82	---	56.00	28.18	N	OFF	19.5
1.865400	---	24.54	46.00	21.46	N	OFF	19.6
1.865400	26.41	---	56.00	29.59	N	OFF	19.6
6.090000	---	24.88	50.00	25.12	N	OFF	19.7
6.090000	25.76	---	60.00	34.24	N	OFF	19.7
13.562970	---	33.98	50.00	16.02	N	OFF	19.9
13.562970	43.59	---	60.00	16.41	N	OFF	19.9



## Appendix B. Radiated Spurious Emission

Test Engineer :	Jacky Hung, Andy Yang and CR Liao	Temperature :	20~25°C
		Relative Humidity :	50~60%

### 2.4GHz 2400~2483.5MHz

#### BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	Limit	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
					Line	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
BT CH00 2402MHz		2342.235	47.44	-26.56	74	41.28	27.83	8.09	29.76	141	337	P	H	
		2342.235	22.68	-31.32	54	-	-	-	-	-	-	A	H	
	*	2402	105.68	-	-	99.68	27.6	8.19	29.79	141	337	P	H	
	*	2402	80.92	-	-	-	-	-	-	-	-	A	H	
													H	
														H
			2381.715	47.15	-26.85	74	41.1	27.67	8.16	29.78	379	29	P	V
			2381.715	22.39	-31.61	54	-	-	-	-	-	-	A	V
	*		2402	103.62	-	-	97.62	27.6	8.19	29.79	379	29	P	V
	*		2402	78.86	-	-	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		2377.76	46.84	-27.16	74	40.78	27.69	8.15	29.78	102	298	P	H	
		2377.76	22.08	-31.92	54	-	-	-	-	-	-	A	H	
	*	2441	105.15	-	-	99.1	27.6	8.26	29.81	102	298	P	H	
	*	2441	80.39	-	-	-	-	-	-	-	-	A	H	
			2497.27	46.83	-27.17	74	40.8	27.51	8.35	29.83	102	298	P	H
			2497.27	22.07	-31.93	54	-	-	-	-	-	-	A	H
			2324.28	47.01	-26.99	74	40.8	27.9	8.07	29.76	365	32	P	V
			2324.28	22.25	-31.75	54	-	-	-	-	-	-	A	V
	*		2441	102.84	-	-	96.79	27.6	8.26	29.81	365	32	P	V
	*		2441	78.08	-	-	-	-	-	-	-	-	A	V
			2490.13	46.18	-27.82	74	40.16	27.52	8.33	29.83	365	32	P	V
			2490.13	21.42	-32.58	54	-	-	-	-	-	-	A	V



<b>BT CH 78 2480MHz</b>	*	2480	106.64	-	-	100.6	27.54	8.32	29.82	100	301	P	H
	*	2480	81.88	-	-	-	-	-	-	-	-	A	H
		2483.52	55.84	-18.16	74	49.81	27.53	8.32	29.82	100	301	P	H
		2483.52	31.08	-22.92	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	103.66	-	-	97.62	27.54	8.32	29.82	354	28	P	V
	*	2480	78.9	-	-	-	-	-	-	-	-	A	V
		2483.56	52.8	-21.2	74	46.77	27.53	8.32	29.82	354	28	P	V
		2483.56	28.04	-25.96	54	-	-	-	-	-	-	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz  
BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BT CH 00 2402MHz		4804	40.54	-33.46	74	56.11	31.11	12.4	59.08	100	0	P	H	
		4804	15.78	-38.22	54	-	-	-	-	-	-	A	H	
													H	
													H	
			4804	40.07	-33.93	74	55.64	31.11	12.4	59.08	100	0	P	V
			4804	15.31	-38.69	54	-	-	-	-	-	-	A	V
														V
														V
BT CH 39 2441MHz		4882	40.27	-33.73	74	55.85	31.07	12.48	59.13	100	0	P	H	
		4882	15.51	-38.49	54	-	-	-	-	-	-	A	H	
		7323	45.75	-28.25	74	52.13	36.49	15.68	58.55	100	0	P	H	
		7323	20.99	-33.01	54	-	-	-	-	-	-	A	H	
		4882	39.69	-34.31	74	55.27	31.07	12.48	59.13	100	0	P	V	
		4882	14.93	-39.07	54	-	-	-	-	-	-	A	V	
		7323	46.67	-27.33	74	53.05	36.49	15.68	58.55	100	0	P	V	
		7323	21.91	-32.09	54	-	-	-	-	-	-	A	V	
BT CH 78 2480MHz		4960	39.78	-34.22	74	55.14	31.26	12.56	59.18	100	0	P	H	
		4960	15.02	-38.98	54	-	-	-	-	-	-	A	H	
		7440	45.81	-28.19	74	51.83	36.58	15.78	58.38	100	0	P	H	
		7440	21.05	-32.95	54	-	-	-	-	-	-	A	H	
		4960	40.08	-33.92	74	55.44	31.26	12.56	59.18	100	0	P	V	
		4960	15.32	-38.68	54	-	-	-	-	-	-	A	V	
		7440	48.59	-25.41	74	54.61	36.58	15.78	58.38	100	0	P	V	
		7440	23.83	-30.17	54	-	-	-	-	-	-	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Emission above 18GHz

2.4GHz BT (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BT SHF		20366	39.53	-34.47	74	43.52	37.95	11.54	53.58	150	0	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			20184	39.54	-34.46	74	43.84	37.87	11.52	53.69	150	0	P
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz BT LF		146.4	32.83	-10.67	43.5	45.92	17.07	2.12	32.28	100	0	P	H	
		230.79	27.07	-18.93	46	40.4	16.35	2.65	32.33	-	-	P	H	
		385.02	23.29	-22.71	46	30.91	21.24	3.36	32.22	-	-	P	H	
		590.66	27.64	-18.36	46	29.74	25.66	4.18	31.94	-	-	P	H	
		750.71	30.99	-15.01	46	30.45	28.09	4.71	32.26	-	-	P	H	
		885.54	32.06	-13.94	46	29.89	29.04	5.12	31.99	-	-	P	H	
														H
														H
														H
														H
														H
														H
														H
			56.19	32.08	-7.92	40	51.04	12.17	1.28	32.41	100	0	P	V
			149.31	26.64	-16.86	43.5	39.71	17.05	2.16	32.28	-	-	P	V
			353.01	21.44	-24.56	46	30.06	20.47	3.19	32.28	-	-	P	V
			461.65	26.93	-19.07	46	32.03	23.39	3.64	32.13	-	-	P	V
			636.25	28.6	-17.4	46	29.92	26.36	4.32	32	-	-	P	V
			748.77	31.15	-14.85	46	30.61	28.09	4.71	32.26	-	-	P	V
														V
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													





**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
					( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 00		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2402MHz													

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**