



FCC RADIO TEST REPORT

FCC ID : UZ7ET60AW
Equipment : Rugged 2 in 1 Android Tablet
Brand Name : Zebra
Model Name : ET60AW
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC Part 15 Subpart C §15.247

The product was received on Mar. 30, 2023 and testing was performed from Apr. 24, 2023 to Jun. 02, 2023. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	6
1.4 Testing Location	7
1.5 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	13
3 Test Result.....	14
3.1 6dB and 99% Bandwidth Measurement	14
3.2 Output Power Measurement.....	15
3.3 Power Spectral Density Measurement	16
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	18
3.6 AC Conducted Emission Measurement.....	22
3.7 Antenna Requirements.....	24
4 List of Measuring Equipment	25
5 Measurement Uncertainty	26
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR332310B	01	Initial issue of report	Jun. 07, 2023



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	6.89 dB under the limit at 30.000 MHz for Quasi-Peak
3.6	15.207	AC Conducted Emission	Pass	4.49 dB under the limit at 13.560 MHz
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng**Report Producer: Michelle Chen**



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Rugged 2 in 1 Android Tablet
Brand Name	Zebra
Model Name	ET60AW
FCC ID	UZ7ET60AW
Sample 1	Standard sku
Sample 2	FRZ sku
EUT supports Radios application	NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
HW Version	EV2.1
SW Version	A13
FW Version	1.1.2.0.645.4
MFD	27MAR23
EUT Stage	Identical Prototype

Remark: The EUT's information above is declared by manufacturer.

Specification of Accessories				
Adapter	Brand Name	Zebra	Part Number	PWR-BGA15V45W-UC2-WW
Battery 1	Brand Name	Zebra	Part Number	BT-000471-0020
Battery 2	Brand Name	Zebra	Part Number	BT-000471-0820

Supported Unit Used in Test Configuration and System				
USB TYPE C to 3.5mm audio connector	Brand Name	Zebra	Part Number	ADP-USBC-35MM1-01
3.5mm Earphone	Brand Name	Zebra	Part Number	HDST-35MM-PTVP-01
USB TYPE C Earphone	Brand Name	Zebra	Part Number	HPST-USBC-PTT1-01
Headset Jumper	Brand Name	Zebra	Part Number	CBL-TC51-HDST35-01



1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	<Ant. 7> Bluetooth – LE (1Mbps): 4.40 dBm / 0.0028 W Bluetooth – LE (2Mbps): 4.30 dBm / 0.0027 W <Ant. 8> Bluetooth – LE (1Mbps): 3.70 dBm / 0.0023 W Bluetooth – LE (2Mbps): 3.70 dBm / 0.0023 W
99% Occupied Bandwidth	<Ant. 7> 1.017 MHz for 1Mbps 1.994 MHz for 2Mbps <Ant. 8> 1.017 MHz for 1Mbps 1.994 MHz for 2Mbps
Antenna Type / Gain	<Ant. 7> : Monopole Antenna with gain 2.60 dBi <Ant. 8> : Monopole Antenna with gain 2.49 dBi
Type of Modulation	Bluetooth LE: GFSK

Remark: The above EUT's information was declared by manufacturer. Please refer to Disclaimer in report summary.

1.3 Modification of EUT

No modifications made to the EUT during the testing.



1.4 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. CO05-HY (TAF Code: 1190)
Remark	The Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, 03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
20	2442	-	-	



2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

- b. AC power line Conducted Emission was tested under maximum output power.




The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	<Ant. 7>
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
	<Ant. 8>
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps	
Radiated Test Cases	<Ant. 7>
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
	<Ant. 8>
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps


Summary table of Test Cases	
Test Item	Data Rate / Modulation
AC Conducted Emission	Mode 1: Bluetooth Link + WLAN (2.4GHz) Link + NFC On + USB TYPE-A cable (Data Link with USB HD) (Copy data from USB HD to eMMC) + USB TYPE-A with Mouse + Battery 1 + USB TYPE-C (Charging from Adapter) for Sample 1
Remark: 1. For Radiated Test Cases, the tests were performed with Battery 1 and Sample 1. 2. Data Link with USB HD means data application transferred mode between EUT and USB HD. 3. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth – LE Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7-RD0010	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude 3420	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	USB HD	ADATA	HV620S-1T	FCC DoC	Shielded, 1.0m	N/A
5.	Mouse	MSI	S12-0400C40-AA3	FCC DoC	Shielded, 2.0m	N/A
6.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
7.	USB TYPE-C cable	N/A	N/A	N/A	N/A	N/A
8.	USB TYPE-A cable	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT Version 4.0.00206.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGP-M-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.




3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-“.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-“.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Apr. 24, 2023	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 01, 2022	Apr. 24, 2023	Nov. 30, 2023	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 17, 2022	Apr. 24, 2023	Nov. 16, 2023	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 17, 2022	Apr. 24, 2023	Nov. 16, 2023	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Apr. 24, 2023	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Aug. 01, 2022	Apr. 24, 2023	Jul. 31, 2023	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 29, 2022	Apr. 24, 2023	Dec. 28, 2023	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 20, 2022	May 15, 2023~Jun. 02, 2023	Sep. 19, 2023	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-01620	1GHz~18GHz	Aug. 24, 2022	May 15, 2023~Jun. 02, 2023	Aug. 23, 2023	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	1223	18GHz~40GHz	Jul. 05, 2022	May 15, 2023~Jun. 02, 2023	Jul. 04, 2023	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 09, 2022	May 15, 2023~Jun. 02, 2023	Nov. 08, 2023	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-303	1710001800055007	1GHz~18GHz	Jun. 15, 2022	May 15, 2023~Jun. 02, 2023	Jun. 14, 2023	Radiation (03CH11-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	Jun. 28, 2022	May 15, 2023~Jun. 02, 2023	Jun. 27, 2023	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Oct. 07, 2022	May 15, 2023~Jun. 02, 2023	Oct. 06, 2023	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	May 15, 2023~Jun. 02, 2023	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	May 15, 2023~Jun. 02, 2023	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	May 15, 2023~Jun. 02, 2023	N/A	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	May 15, 2023~Jun. 02, 2023	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz~40GHz	Mar. 07, 2023	May 15, 2023~Jun. 02, 2023	Mar. 06, 2024	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	801595/2	30MHz~40GHz	Mar. 07, 2023	May 15, 2023~Jun. 02, 2023	Mar. 06, 2024	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9K~30M	Mar. 07, 2023	May 15, 2023~Jun. 02, 2023	Mar. 06, 2024	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	30M~40G	Mar. 07, 2023	May 15, 2023~Jun. 02, 2023	Mar. 06, 2024	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN11	1.53GHz Low Pass Filter	Sep. 12, 2022	May 15, 2023~Jun. 02, 2023	Sep. 11, 2023	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60SS	SN3	3GHz High Pass Filter	Sep. 12, 2022	May 15, 2023~Jun. 02, 2023	Sep. 11, 2023	Radiation (03CH11-HY)
Hygrometer	TECEPEL	DTM-303B	TP140325	N/A	Nov. 07, 2022	May 15, 2023~Jun. 02, 2023	Nov. 06, 2023	Radiation (03CH11-HY)
Hygrometer	TECEPEL	DTM-303A	TP201996	N/A	Nov. 17, 2022	May 06, 2023~May 31, 2023	Nov. 16, 2023	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054SNO12 (NO:113)	10MHz~6GHz	Dec. 13, 2022	May 06, 2023~May 31, 2023	Dec. 12, 2023	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101905	10Hz - 40GHz(amp)	Aug. 03, 2022	May 06, 2023~May 31, 2023	Aug. 02, 2023	Conducted (TH05-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.40 dB
---	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.80 dB
---	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.30 dB
---	---------

Appendix A. Test Result of Conducted Test Items

<Ant. 7>

Test Engineer:	Sylvia Li	Temperature:	21~25	°C
Test Date:	2023/05/06~2023/05/10	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.017	0.678	0.50	Pass
BLE	1Mbps	1	19	2440	1.017	0.676	0.50	Pass
BLE	1Mbps	1	39	2480	1.017	0.678	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	4.10	30.00	2.60	6.70	36.00	Pass
BLE	1Mbps	1	19	2440	4.40	30.00	2.60	7.00	36.00	Pass
BLE	1Mbps	1	39	2480	2.80	30.00	2.60	5.40	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	3.46	-10.87	2.60	8.00	Pass
BLE	1Mbps	1	19	2440	3.75	-10.56	2.60	8.00	Pass
BLE	1Mbps	1	39	2480	2.21	-12.13	2.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	1.994	1.160	0.50	Pass
BLE	2Mbps	1	19	2440	1.994	1.168	0.50	Pass
BLE	2Mbps	1	39	2480	1.994	1.164	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	4.10	30.00	2.60	6.70	36.00	Pass
BLE	2Mbps	1	19	2440	4.30	30.00	2.60	6.90	36.00	Pass
BLE	2Mbps	1	39	2480	2.80	30.00	2.60	5.40	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	3.53	-13.77	2.60	8.00	Pass
BLE	2Mbps	1	19	2440	3.80	-13.46	2.60	8.00	Pass
BLE	2Mbps	1	39	2480	2.21	-15.05	2.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<Ant. 8>

Test Engineer:	Hank Hsu	Temperature:	21~25	°C
Test Date:	2023/05/06~2023/05/31	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.017	0.676	0.50	Pass
BLE	1Mbps	1	19	2440	1.015	0.674	0.50	Pass
BLE	1Mbps	1	39	2480	1.015	0.676	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	3.60	30.00	2.49	6.09	36.00	Pass
BLE	1Mbps	1	19	2440	3.30	30.00	2.49	5.79	36.00	Pass
BLE	1Mbps	1	39	2480	3.70	30.00	2.49	6.19	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	3.22	-11.11	2.49	8.00	Pass
BLE	1Mbps	1	19	2440	2.73	-11.61	2.49	8.00	Pass
BLE	1Mbps	1	39	2480	3.53	-10.78	2.49	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	1.994	1.164	0.50	Pass
BLE	2Mbps	1	19	2440	1.990	1.160	0.50	Pass
BLE	2Mbps	1	39	2480	1.994	1.160	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	3.50	30.00	2.49	5.99	36.00	Pass
BLE	2Mbps	1	19	2440	3.30	30.00	2.49	5.79	36.00	Pass
BLE	2Mbps	1	39	2480	3.70	30.00	2.49	6.19	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	3.21	-14.10	2.49	8.00	Pass
BLE	2Mbps	1	19	2440	2.73	-14.57	2.49	8.00	Pass
BLE	2Mbps	1	39	2480	3.51	-13.75	2.49	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




<Ant. 7>


6dB Bandwidth

<1Mbps>


6 dB Bandwidth Plot on Channel 00



6 dB Bandwidth Plot on Channel 19




6 dB Bandwidth Plot on Channel 39






<2Mbps>


6 dB Bandwidth Plot on Channel 00



6 dB Bandwidth Plot on Channel 19



6 dB Bandwidth Plot on Channel 39






99% Occupied Bandwidth

<1Mbps>


99% Occupied Bandwidth Plot on Channel 00



Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1	1		2.402022 GHz	0.14 dBm		
T1	1		2.40153646 GHz	-13.91 dBm	Occ Bw	1.016983017 MHz
T2	1		2.40255345 GHz	-14.73 dBm		

Date: 9.MAY.2023 16:22:16


99% Occupied Plot Bandwidth on Channel 19



Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1	1		2.440028 GHz	0.47 dBm		
T1	1		2.43953646 GHz	-13.53 dBm	Occ Bw	1.016983017 MHz
T2	1		2.44055345 GHz	-14.49 dBm		

Date: 9.MAY.2023 16:24:37

99% Occupied Bandwidth Plot on Channel 39



Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1	1		2.480024 GHz	-1.03 dBm		
T1	1		2.47953646 GHz	-15.17 dBm	Occ Bw	1.016983017 MHz
T2	1		2.48055345 GHz	-16.14 dBm		


Date: 9.MAY.2023 16:26:29

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<2Mbps>


99% Occupied Bandwidth Plot on Channel 00



99% Occupied Plot Bandwidth on Channel 19



99% Occupied Bandwidth Plot on Channel 39




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



Power Spectral Density (dBm/3kHz)


<1Mbps>

Power Density (dBm/3kHz) Plot Channel 00




Date: 9.MAY.2023 16:22:45

Power Density (dBm/3kHz) Plot Channel 19



Date: 9.MAY.2023 16:25:01

Power Density (dBm/3kHz) Plot Channel 39




Date: 9.MAY.2023 16:26:56




<2Mbps>


Power Density (dBm/3kHz) Plot Channel 00



Power Density (dBm/3kHz) Plot Channel 19




Power Density (dBm/3kHz) Plot Channel 39






Band Edge and Spurious Emission






<1Mbps> Channel 19

100kHz PSD reference Level Plot




Middle Channel Plot

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<1Mbps> Channel 39

100kHz PSD reference Level Plot




Date: 9.MAY.2023 16:27:14

High Channel Plot




Date: 9.MAY.2023 16:28:24

Spurious Emission 30MHz~1GHz Plot



Date: 9.MAY.2023 16:27:51

Spurious Emission 1GHz~26.5GHz Plot




Date: 9.MAY.2023 16:28:07




<2Mbps> Channel 00

100kHz PSD reference Level Plot




Date: 9.MAY.2023 16:38:43

Low Channel Plot




Date: 9.MAY.2023 16:40:48

Spurious Emission 30MHz~1GHz Plot



Date: 9.MAY.2023 16:39:07

Spurious Emission 1GHz~26.5GHz Plot




Date: 9.MAY.2023 16:39:26




<2Mbps> Channel 19

100kHz PSD reference Level Plot




Middle Channel Plot

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<2Mbps> Channel 39

100kHz PSD reference Level Plot




Date: 9.MAY.2023 16:30:15

High Channel Plot




Date: 9.MAY.2023 16:31:06

Spurious Emission 30MHz~1GHz Plot



Date: 9.MAY.2023 16:30:32

Spurious Emission 1GHz~26.5GHz Plot



Date: 9.MAY.2023 16:30:48




<Ant. 8>


6dB Bandwidth

<1Mbps>


6 dB Bandwidth Plot on Channel 00



6 dB Bandwidth Plot on Channel 19




6 dB Bandwidth Plot on Channel 39






<2Mbps>


6 dB Bandwidth Plot on Channel 00



6 dB Bandwidth Plot on Channel 19



6 dB Bandwidth Plot on Channel 39






99% Occupied Bandwidth


<1Mbps>

99% Occupied Bandwidth Plot on Channel 00




Date: 31.MAY.2023 23:22:52

99% Occupied Plot Bandwidth on Channel 19



Date: 31.MAY.2023 23:26:38

99% Occupied Bandwidth Plot on Channel 39




Date: 31.MAY.2023 23:32:11

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<2Mbps>


99% Occupied Bandwidth Plot on Channel 00



99% Occupied Plot Bandwidth on Channel 19



99% Occupied Bandwidth Plot on Channel 39







Power Spectral Density (dBm/3kHz)

<1Mbps>


Power Density (dBm/3kHz) Plot Channel 00



Power Density (dBm/3kHz) Plot Channel 19




Power Density (dBm/3kHz) Plot Channel 39






<2Mbps>


Power Density (dBm/3kHz) Plot Channel 00



Power Density (dBm/3kHz) Plot Channel 19




Power Density (dBm/3kHz) Plot Channel 39






Band Edge and Spurious Emission






<1Mbps> Channel 19

100kHz PSD reference Level Plot





Middle Channel Plot


Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot











<2Mbps> Channel 19

100kHz PSD reference Level Plot





Middle Channel Plot

Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot








Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	Temperature :	23~26°C
		Relative Humidity :	45~55%

EUT Information

Report NO : 332310
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.159000	---	27.62	55.52	27.90	L1	OFF	19.8
0.159000	49.80	---	65.52	15.72	L1	OFF	19.8
0.165750	---	40.19	55.17	14.98	L1	OFF	19.8
0.165750	56.43	---	65.17	8.74	L1	OFF	19.8
0.174750	---	41.50	54.73	13.23	L1	OFF	19.8
0.174750	55.94	---	64.73	8.79	L1	OFF	19.8
0.181500	---	32.79	54.42	21.63	L1	OFF	19.8
0.181500	53.30	---	64.42	11.12	L1	OFF	19.8
0.249000	---	29.67	51.79	22.12	L1	OFF	19.8
0.249000	45.06	---	61.79	16.73	L1	OFF	19.8
0.262500	---	30.64	51.35	20.71	L1	OFF	19.8
0.262500	44.29	---	61.35	17.06	L1	OFF	19.8
0.336750	---	26.38	49.28	22.90	L1	OFF	19.8
0.336750	37.43	---	59.28	21.85	L1	OFF	19.8
0.804750	---	17.56	46.00	28.44	L1	OFF	19.8
0.804750	30.34	---	56.00	25.66	L1	OFF	19.8
4.029000	---	17.29	46.00	28.71	L1	OFF	19.9
4.029000	23.00	---	56.00	33.00	L1	OFF	19.9
13.560000	---	45.51	50.00	4.49	L1	OFF	20.0
13.560000	54.08	---	60.00	5.92	L1	OFF	20.0
17.868750	---	29.01	50.00	20.99	L1	OFF	20.0

17.868750	34.30	---	60.00	25.70	L1	OFF	20.0
23.498250	---	35.10	50.00	14.90	L1	OFF	20.0
23.498250	41.40	---	60.00	18.60	L1	OFF	20.0

EUT Information

Report NO : 332310
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	31.94	55.40	23.46	N	OFF	19.8
0.161250	53.37	---	65.40	12.03	N	OFF	19.8
0.168000	---	42.65	55.06	12.41	N	OFF	19.8
0.168000	55.86	---	65.06	9.20	N	OFF	19.8
0.179250	---	32.93	54.52	21.59	N	OFF	19.8
0.179250	52.60	---	64.52	11.92	N	OFF	19.8
0.244500	---	25.31	51.94	26.63	N	OFF	19.8
0.244500	44.25	---	61.94	17.69	N	OFF	19.8
0.262500	---	29.07	51.35	22.28	N	OFF	19.8
0.262500	42.98	---	61.35	18.37	N	OFF	19.8
0.341250	---	27.48	49.17	21.69	N	OFF	19.8
0.341250	36.98	---	59.17	22.19	N	OFF	19.8
0.602250	---	22.70	46.00	23.30	N	OFF	19.8
0.602250	30.48	---	56.00	25.52	N	OFF	19.8
3.756750	---	18.24	46.00	27.76	N	OFF	19.9
3.756750	28.36	---	56.00	27.64	N	OFF	19.9
13.560000	---	44.74	50.00	5.26	N	OFF	20.1
13.560000	54.35	---	60.00	5.65	N	OFF	20.1
18.154500	---	29.70	50.00	20.30	N	OFF	20.1
18.154500	35.08	---	60.00	24.92	N	OFF	20.1
23.617500	---	37.03	50.00	12.97	N	OFF	20.2

23.617500	42.68	---	60.00	17.32	N	OFF	20.2
-----------	-------	-----	-------	-------	---	-----	------



Appendix C. Radiated Spurious Emission

Test Engineer :	Yuan Lee and Troye Hsieh	Temperature :	20.1~22.3°C
		Relative Humidity :	54.1~66.9%

<1Mbps>

2.4GHz 2400~2483.5MHz
BLE (Band Edge @ 3m)

BLE ANT	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BLE CH 00 2402MHz		2385.915	53.17	-20.83	74	42.84	27.44	17.09	34.2	182	81	P	H	
		2387.595	43.13	-10.87	54	32.79	27.45	17.09	34.2	182	81	A	H	
	*	2402	107.68	-	-	97.26	27.51	17.11	34.2	182	81	P	H	
	*	2402	107.11	-	-	96.69	27.51	17.11	34.2	182	81	A	H	
													H	
														H
			2350.95	53.06	-20.94	74	42.93	27.3	17.05	34.22	309	49	P	V
			2389.695	43.4	-10.6	54	33.04	27.46	17.1	34.2	309	49	A	V
		*	2402	111.13	-	-	100.71	27.51	17.11	34.2	309	49	P	V
		*	2402	110.62	-	-	100.2	27.51	17.11	34.2	309	49	A	V
														V
														V
BLE CH 19 2440MHz		2323.44	52.76	-21.24	74	42.63	27.35	17.01	34.23	289	67	P	H	
		2388.72	43.25	-10.75	54	32.9	27.45	17.1	34.2	289	67	A	H	
		* 2440	110.17	-	-	99.44	27.74	17.17	34.18	289	67	P	H	
		* 2440	109.63	-	-	98.9	27.74	17.17	34.18	289	67	A	H	
			2490.16	52.93	-21.07	74	41.97	27.88	17.24	34.16	289	67	P	H
			2498.56	43.78	-10.22	54	32.79	27.9	17.25	34.16	289	67	A	H
			2376.08	52.9	-21.1	74	42.63	27.4	17.08	34.21	215	78	P	V
			2388.08	43.11	-10.89	54	32.76	27.45	17.1	34.2	215	78	A	V
		*	2440	112.2	-	-	101.47	27.74	17.17	34.18	215	78	P	V
		*	2440	111.6	-	-	100.87	27.74	17.17	34.18	215	78	A	V
			2499.76	53.53	-20.47	74	42.54	27.9	17.25	34.16	215	78	P	V
			2492.96	43.81	-10.19	54	32.84	27.89	17.24	34.16	215	78	A	V



BLE CH 39 2480MHz	*	2480	110.04	-	-	99.12	27.86	17.23	34.17	176	68	P	H
	*	2480	109.5	-	-	98.58	27.86	17.23	34.17	176	68	A	H
		2483.52	56.15	-17.85	74	45.22	27.87	17.23	34.17	176	68	P	H
		2483.6	44.6	-9.4	54	33.67	27.87	17.23	34.17	176	68	A	H
													H
													H
	*	2480	112.09	-	-	101.17	27.86	17.23	34.17	296	37	P	V
	*	2480	111.65	-	-	100.73	27.86	17.23	34.17	296	37	A	V
		2483.68	56.6	-17.4	74	45.67	27.87	17.23	34.17	296	37	P	V
		2483.52	45.56	-8.44	54	34.63	27.87	17.23	34.17	296	37	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)

BLE ANT	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE ANT 7		4804	40.32	-33.68	74	54.08	32.42	11.76	57.94	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
BLE CH 00 2402MHz		4804	40.95	-33.05	74	54.71	32.42	11.76	57.94	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V



BLE ANT 7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 19 2440MHz		4880	41.52	-32.48	74	54.89	32.76	11.87	58	-	-	P	H
		7320	44.02	-29.98	74	51.48	36.82	14.45	58.73	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			4880	41.45	-32.55	74	54.82	32.76	11.87	58	-	-	P
		7320	45.29	-28.71	74	52.75	36.82	14.45	58.73	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V



BLE ANT 7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BLE CH 39 2480MHz		4960	41.68	-32.32	74	54.69	33.06	11.99	58.06	-	-	P	H	
		7440	42.95	-31.05	74	50.8	36.42	14.44	58.71	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			4960	42.42	-31.58	74	55.43	33.06	11.99	58.06	-	-	P	V
			7440	43.22	-30.78	74	51.07	36.42	14.44	58.71	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.													



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE ANT	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.	
7		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE CH 00 2402MHz		2387.07	52.32	-21.68	74	41.98	27.45	17.09	34.2	213	65	P	H	
		2384.445	43.64	-10.36	54	33.31	27.44	17.09	34.2	213	65	A	H	
	*	2402	109.3	-	-	98.88	27.51	17.11	34.2	213	65	P	H	
	*	2402	107.79	-	-	97.37	27.51	17.11	34.2	213	65	A	H	
													H	
														H
			2364.285	52.66	-21.34	74	42.44	27.36	17.07	34.21	254	66	P	V
			2388.96	43.9	-10.1	54	33.54	27.46	17.1	34.2	254	66	A	V
	*		2402	111.59	-	-	101.17	27.51	17.11	34.2	254	66	P	V
	*		2402	109.92	-	-	99.5	27.51	17.11	34.2	254	66	A	V
														V
														V
BLE CH 19 2440MHz		2321.68	52.39	-21.61	74	42.25	27.36	17.01	34.23	181	69	P	H	
		2386.64	43.8	-10.2	54	33.46	27.45	17.09	34.2	181	69	A	H	
	*	2440	110.66	-	-	99.93	27.74	17.17	34.18	181	69	P	H	
	*	2440	109.17	-	-	98.44	27.74	17.17	34.18	181	69	A	H	
			2492.08	53.14	-20.86	74	42.18	27.88	17.24	34.16	181	69	P	H
			2489.52	44.87	-9.13	54	33.91	27.88	17.24	34.16	181	69	A	H
			2370	52.3	-21.7	74	42.06	27.38	17.07	34.21	215	67	P	V
			2365.04	43.58	-10.42	54	33.36	27.36	17.07	34.21	215	67	A	V
	*		2440	111.99	-	-	101.26	27.74	17.17	34.18	215	67	P	V
	*		2440	110.54	-	-	99.81	27.74	17.17	34.18	215	67	A	V
			2499.76	53.04	-20.96	74	42.05	27.9	17.25	34.16	215	67	P	V
			2496.32	44.39	-9.61	54	33.41	27.89	17.25	34.16	215	67	A	V



BLE CH 39 2480MHz	*	2480	109.85	-	-	98.93	27.86	17.23	34.17	178	75	P	H
	*	2480	108.5	-	-	97.58	27.86	17.23	34.17	178	75	A	H
		2483.52	56.44	-17.56	74	45.51	27.87	17.23	34.17	178	75	P	H
		2483.64	45.91	-8.09	54	34.98	27.87	17.23	34.17	178	75	A	H
													H
													H
	*	2480	111.58	-	-	100.66	27.86	17.23	34.17	290	61	P	V
	*	2480	110.21	-	-	99.29	27.86	17.23	34.17	290	61	A	V
		2483.56	59.03	-14.97	74	48.1	27.87	17.23	34.17	290	61	P	V
		2483.56	46.51	-7.49	54	35.58	27.87	17.23	34.17	290	61	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)

BLE ANT	Note	Frequency (MHz)	Level (dBµV/m)	Margin (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00		4804	41.05	-32.95	74	54.81	32.42	11.76	57.94	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
2402MHz		4804	41.13	-32.87	74	54.89	32.42	11.76	57.94	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V



BLE ANT 7	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 19 2440MHz		4880	43.06	-30.94	74	56.43	32.76	11.87	58	-	-	P	H
		7320	44.22	-29.78	74	51.68	36.82	14.45	58.73	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			4880	41.89	-32.11	74	55.26	32.76	11.87	58	-	-	P
		7320	45.84	-28.16	74	53.3	36.82	14.45	58.73	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V



BLE ANT	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BLE CH 39 2480MHz		4960	41.85	-32.15	74	54.86	33.06	11.99	58.06	-	-	P	H	
		7440	43.12	-30.88	74	50.97	36.42	14.44	58.71	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			4960	42.46	-31.54	74	55.47	33.06	11.99	58.06	-	-	P	V
			7440	42.85	-31.15	74	50.7	36.42	14.44	58.71	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.													



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
ANT					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
7		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
2.4GHz BLE LF		30	33.62	-6.38	40	41.01	23.92	0.84	32.15	-	-	P	H	
		127.74	36.06	-7.44	43.5	48.96	17.44	1.82	32.16	-	-	P	H	
		174.72	27.79	-15.71	43.5	42.76	15.03	2.07	32.07	-	-	P	H	
		559	27.6	-18.4	46	30.12	25.83	3.62	31.97	-	-	P	H	
		776.7	31.77	-14.23	46	31.63	27.73	4.27	31.86	-	-	P	H	
		955.9	33.68	-12.32	46	29.28	30.46	4.68	30.74	-	-	P	H	
														H
														H
														H
														H
														H
														H
			30	33.11	-6.89	40	40.5	23.92	0.84	32.15	100	313	Q	V
			64.56	27.27	-12.73	40	46.69	11.56	1.26	32.24	-	-	P	V
			127.47	33.66	-9.84	43.5	46.55	17.45	1.82	32.16	-	-	P	V
			556.2	27.77	-18.23	46	30.39	25.73	3.61	31.96	-	-	P	V
			756.4	30.53	-15.47	46	30.44	27.71	4.21	31.83	-	-	P	V
			951.7	33.89	-12.11	46	29.74	30.26	4.67	30.78	-	-	P	V
														V
														V
													V	
													V	
													V	
													V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against limit line. The emission position marked as "-" means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only. 													



<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
8		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE CH 00 2402MHz		2389.485	52.54	-21.46	74	42.18	27.46	17.1	34.2	142	181	P	H	
		2383.5	43.07	-10.93	54	32.75	27.43	17.09	34.2	142	181	A	H	
	*	2402	98.47	-	-	88.05	27.51	17.11	34.2	142	181	P	H	
	*	2402	97.82	-	-	87.4	27.51	17.11	34.2	142	181	A	H	
													H	
														H
			2344.965	52.43	-21.57	74	42.3	27.31	17.04	34.22	160	164	P	V
			2386.125	42.96	-11.04	54	32.63	27.44	17.09	34.2	160	164	A	V
	*		2402	96.92	-	-	86.5	27.51	17.11	34.2	160	164	P	V
	*		2402	96.29	-	-	85.87	27.51	17.11	34.2	160	164	A	V
														V
														V
BLE CH 19 2440MHz		2343.92	52.19	-21.81	74	42.06	27.31	17.04	34.22	155	181	P	H	
		2378.96	43.16	-10.84	54	32.87	27.42	17.08	34.21	155	181	A	H	
	*	2440	99.18	-	-	88.45	27.74	17.17	34.18	155	181	P	H	
	*	2440	98.51	-	-	87.78	27.74	17.17	34.18	155	181	A	H	
			2496.32	53.11	-20.89	74	42.13	27.89	17.25	34.16	155	181	P	H
			2485.28	43.64	-10.36	54	32.71	27.87	17.23	34.17	155	181	A	H
			2353.04	53.26	-20.74	74	43.12	27.31	17.05	34.22	154	160	P	V
			2364.24	43.06	-10.94	54	32.84	27.36	17.07	34.21	154	160	A	V
	*		2440	96.93	-	-	86.2	27.74	17.17	34.18	154	160	P	V
	*		2440	96.3	-	-	85.57	27.74	17.17	34.18	154	160	A	V
			2489.36	53.05	-20.95	74	42.09	27.88	17.24	34.16	154	160	P	V
			2498	43.61	-10.39	54	32.62	27.9	17.25	34.16	154	160	A	V



BLE CH 39 2480MHz	*	2480	98.45	-	-	87.53	27.86	17.23	34.17	150	181	P	H
	*	2480	97.81	-	-	86.89	27.86	17.23	34.17	150	181	A	H
		2489.24	53.66	-20.34	74	42.7	27.88	17.24	34.16	150	181	P	H
		2484.96	43.96	-10.04	54	33.03	27.87	17.23	34.17	150	181	A	H
													H
													H
	*	2480	96.47	-	-	85.55	27.86	17.23	34.17	150	144	P	V
	*	2480	95.77	-	-	84.85	27.86	17.23	34.17	150	144	A	V
		2484.76	52.93	-21.07	74	42	27.87	17.23	34.17	150	144	P	V
		2490.8	43.81	-10.19	54	32.85	27.88	17.24	34.16	150	144	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)

BLE Ant. 8	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	41.21	-32.79	74	54.97	32.42	11.76	57.94	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
BLE CH 00 2402MHz		4804	41.71	-32.29	74	55.47	32.42	11.76	57.94	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V



BLE Ant. 8	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BLE CH 19 2440MHz		4880	41.54	-32.46	74	54.91	32.76	11.87	58	-	-	P	H	
		7320	44.54	-29.46	74	52	36.82	14.45	58.73	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			4880	41.72	-32.28	74	55.09	32.76	11.87	58	-	-	P	V
			7320	43.57	-30.43	74	51.03	36.82	14.45	58.73	-	-	P	V
														V
														V
														V
														V
														V
														V
													V	
													V	



BLE Ant. 8	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz		4960	43	-31	74	56.01	33.06	11.99	58.06	-	-	P	H
		7440	43.04	-30.96	74	50.89	36.42	14.44	58.71	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			4960	42.39	-31.61	74	55.4	33.06	11.99	58.06	-	-	P
		7440	42.93	-31.07	74	50.78	36.42	14.44	58.71	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only. 												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE Ant.	Note	Frequency	Level	Margin	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.	
8		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE CH 00 2402MHz		2344.125	52.57	-21.43	74	42.44	27.31	17.04	34.22	171	159	P	H	
		2381.4	43.65	-10.35	54	33.34	27.43	17.09	34.21	171	159	A	H	
	*	2402	98.52	-	-	88.1	27.51	17.11	34.2	171	159	P	H	
	*	2402	97.06	-	-	86.64	27.51	17.11	34.2	171	159	A	H	
													H	
													H	
			2356.515	52.52	-21.48	74	42.34	27.33	17.06	34.21	115	10	P	V
			2385.18	43.77	-10.23	54	33.44	27.44	17.09	34.2	115	10	A	V
	*		2402	97.62	-	-	87.2	27.51	17.11	34.2	115	10	P	V
	*		2402	96.18	-	-	85.76	27.51	17.11	34.2	115	10	A	V
													V	
													V	
BLE CH 19 2440MHz		2341.84	52.58	-21.42	74	42.44	27.32	17.04	34.22	150	179	P	H	
		2323.6	43.62	-10.38	54	33.49	27.35	17.01	34.23	150	179	A	H	
	*	2440	98.58	-	-	87.85	27.74	17.17	34.18	150	179	P	H	
	*	2440	97.14	-	-	86.41	27.74	17.17	34.18	150	179	A	H	
			2491.36	52.72	-21.28	74	41.76	27.88	17.24	34.16	150	179	P	H
			2491.36	44.83	-9.17	54	33.87	27.88	17.24	34.16	150	179	A	H
			2329.52	52.27	-21.73	74	42.13	27.34	17.02	34.22	100	12	P	V
			2368.72	43.64	-10.36	54	33.41	27.37	17.07	34.21	100	12	A	V
	*		2440	96.3	-	-	85.57	27.74	17.17	34.18	100	12	P	V
	*		2440	94.76	-	-	84.03	27.74	17.17	34.18	100	12	A	V
			2491.36	52.4	-21.6	74	41.44	27.88	17.24	34.16	100	12	P	V
			2495.36	44.5	-9.5	54	33.52	27.89	17.25	34.16	100	12	A	V



BLE CH 39 2480MHz	*	2480	98.14	-	-	87.22	27.86	17.23	34.17	150	177	P	H
	*	2480	96.72	-	-	85.8	27.86	17.23	34.17	150	177	A	H
		2485.16	54.08	-19.92	74	43.15	27.87	17.23	34.17	150	177	P	H
		2490.4	44.6	-9.4	54	33.64	27.88	17.24	34.16	150	177	A	H
													H
													H
	*	2480	96.12	-	-	85.2	27.86	17.23	34.17	100	12	P	V
	*	2480	94.69	-	-	83.77	27.86	17.23	34.17	100	12	A	V
		2484.52	53.35	-20.65	74	42.42	27.87	17.23	34.17	100	12	P	V
		2486.4	44.42	-9.58	54	33.48	27.87	17.24	34.17	100	12	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)

BLE Ant. 8	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	41.69	-32.31	74	55.45	32.42	11.76	57.94	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			4804	41.56	-32.44	74	55.32	32.42	11.76	57.94	-	-	P
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V



BLE Ant. 8	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 19 2440MHz		4880	41.74	-32.26	74	55.11	32.76	11.87	58	-	-	P	H
		7320	43.98	-30.02	74	51.44	36.82	14.45	58.73	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			4880	41.9	-32.1	74	55.27	32.76	11.87	58	-	-	P
		7320	45.26	-28.74	74	52.72	36.82	14.45	58.73	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V



BLE Ant. 8	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz		4960	42.42	-31.58	74	55.43	33.06	11.99	58.06	-	-	P	H
		7440	42.45	-31.55	74	50.3	36.42	14.44	58.71	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			4960	42.25	-31.75	74	55.26	33.06	11.99	58.06	-	-	P
		7440	44.55	-29.45	74	52.4	36.42	14.44	58.71	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only. 												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
ANT					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
7		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 00		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2402MHz													

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Margin(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
 - = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 - = 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
 - = 55.45 (dBμV/m)
2. Margin(dB)
 - = Level(dBμV/m) – Limit Line(dBμV/m)
 - = 55.45(dBμV/m) – 74(dBμV/m)
 - = -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
 - = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 - = 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
 - = 43.54 (dBμV/m)
2. Margin(dB)
 - = Level(dBμV/m) – Limit Line(dBμV/m)
 - = 43.54(dBμV/m) – 54(dBμV/m)
 - = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Yuan Lee and Troye Hsieh	Temperature :	20.1~22.3°C
		Relative Humidity :	54.1~66.9%

Note symbol



-L	Low channel location
-R	High channel location







<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
7	Horizontal	Fundamental
Peak	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	 <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
	 <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>	 <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>
Avg.		





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
7	Vertical	Fundamental
Peak	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	 <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg	 <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>	 <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
7	Horizontal	Fundamental
Peak	<p>Date: 2023-05-17</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	<p>Date: 2023-05-17</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg.	<p>Date: 2023-05-17</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>	<p>Date: 2023-05-17</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
7	Horizontal	Fundamental
Peak	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH11-HY Condition : AVG_BE_64 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
7	Vertical	Fundamental
Peak	 <p>Date: 2023-05-17</p> <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	 <p>Date: 2023-05-17</p> <p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg.	 <p>Date: 2023-05-17</p> <p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>	 <p>Date: 2023-05-17</p> <p>Site : 03CH11-HY Condition : AVG_54 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
7	Vertical	Fundamental
Peak	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH11-HY Condition : AVG_BE_64 3m 91200_01620_220824 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
7	Horizontal	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg.	<p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>	<p>Site : 03CH11-HY Condition : AVG_54 3m 91200_01620_220824 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
7	Vertical	Fundamental
Peak	<p>Site : 03CH11-HY Condition : PEAK_BE_74 3m 91200_01620_220824 VERTICAL : RBW:3000.000kHz VBW:3000.000kHz SWT:Auto</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_01620_220824 VERTICAL : RBW:3000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg.	<p>Site : 03CH11-HY Condition : AVG_BE_54 3m 91200_01620_220824 VERTICAL : RBW:3000.000kHz VBW:2.700kHz SWT:Auto</p>	<p>Site : 03CH11-HY Condition : AVG_54 3m 91200_01620_220824 VERTICAL : RBW:3000.000kHz VBW:2.700kHz SWT:Auto</p>



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
7	Horizontal	Vertical
<p>Peak Avg.</p>		



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
7	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH11-HY Condition : :PEAK_74 3m 91200_01620_220824 HORIZONTAL</p>	<p>Site : 03CH11-HY Condition : :PEAK_74 3m 91200_01620_220824 VERTICAL</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
7	Horizontal	Vertical
Peak	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_01620_220824 HORIZONTAL</p>	<p>Site : 03CH11-HY Condition : PEAK_74 3m 91200_01620_220824 VERTICAL</p>