



# FCC RADIO TEST REPORT

**FCC ID** : UZ7MC3300R  
**Equipment** : Mobile Computer  
**Brand Name** : Zebra  
**Model Name** : MC3300R  
**Applicant** : Zebra Technologies Corporation  
1 Zebra Plaza, Holtsville, NY 11742  
**Manufacturer** : Zebra Technologies Corporation  
1 Zebra Plaza, Holtsville, NY 11742  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Jul. 19, 2018 and testing was started from Aug. 03, 2018 and completed on Aug. 31, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description.....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	7
1.3 Modification of EUT .....	7
1.4 Testing Location .....	7
1.5 Applicable Standards.....	8
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>9</b>
2.1 Carrier Frequency Channel .....	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	13
2.4 Support Unit used in test configuration and system .....	14
2.5 EUT Operation Test Setup .....	14
2.6 Measurement Results Explanation Example.....	14
<b>3 Test Result.....</b>	<b>15</b>
3.1 Number of Channel Measurement .....	15
3.2 Hopping Channel Separation Measurement .....	17
3.3 Dwell Time Measurement.....	23
3.4 20dB and 99% Bandwidth Measurement .....	25
3.5 Output Power Measurement.....	36
3.6 Conducted Band Edges Measurement.....	38
3.7 Conducted Spurious Emission Measurement .....	45
3.8 Radiated Band Edges and Spurious Emission Measurement .....	55
3.9 AC Conducted Emission Measurement.....	59
3.10 Antenna Requirements .....	61
<b>4 List of Measuring Equipment .....</b>	<b>62</b>
<b>5 Uncertainty of Evaluation.....</b>	<b>63</b>
<b>Appendix A. AC Conducted Emission Test Result</b>	
<b>Appendix B. Radiated Spurious Emission</b>	
<b>Appendix C. Radiated Spurious Emission Plots</b>	
<b>Appendix D. Duty Cycle Plots</b>	
<b>Appendix E. Setup Photographs</b>	



### History of this test report

Report No.	Version	Description	Issued Date
FR812630-07A	01	Initial issue of report	Sep. 07, 2018



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 3.60 dB at 36.480 MHz
3.9	15.207	AC Conducted Emission	Pass	Under limit 16.40 dB at 0.179 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

**Reviewed by: Wii Chang****Report Producer: Yimin Ho**



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Mobile Computer
<b>Brand Name</b>	Zebra
<b>Model Name</b>	MC3300R
<b>FCC ID</b>	UZ7MC3300R
<b>EUT supports Radios application</b>	UHF RFID WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
<b>HW Version</b>	DV
<b>SW Version</b>	RFID Manager Application Version: 2.0.9.1 RFID Demo. Application Version: 2.2.5.24 Terminal Version: 91-01-49-NN-00-A
<b>FW Version</b>	Module Version: PAAEES00-001-N12 Radio Version: 2.0.29.0 Terminal Version: FUSION_BA_2_10.0.0.019_N
<b>MFD</b>	10JUL18
<b>EUT Stage</b>	Identical Prototype

Remark: The above EUT's information was declared by manufacturer..

Specification of Accessories				
<b>Sentry 2X battery</b>	<b>Brand Name</b>	Zebra	<b>Part Number</b>	BT-000337
<b>MC32 2X battery</b>	<b>Brand Name</b>	Symbol	<b>Part Number</b>	82-000012-02
<b>Adapter</b>	<b>Brand Name</b>	Zebra	<b>Part Number</b>	PWR-WUA5V12W0US
<b>USB cable</b>	<b>Brand Name</b>	Zebra	<b>Part Number</b>	CBL-MC33-USBCHG-01
<b>GUN HOLSTER</b>	<b>Brand Name</b>	Zebra	<b>Part Number</b>	SG-MC3021212-01R



<Sample Information>

	SKU1	SKU2	SKU3
Part Number	MC339R-GE2HA4-US	MC339R-GF2HA4-US	MC333R-GI2HA4-US
RFID Antenna	Long range	Long range	Middle range
Scanner	SE4850	SE4750	SE4750
Keypad	29	29	29
Region	US	US	US

	SKU4	SKU5	SKU6
Part Number	MC339R-GE3HA4US	MC339R-GF3HA4US	MC333R-GI3HA4US
RFID Antenna	Long range	Long range	Middle range
Scanner	SE4850	SE4750	SE4750
Keypad	38	38	38
Region	US	US	US

	SKU7	SKU8	SKU9
Part Number	MC339R-GE4HA4US	MC339R-GF4HA4US	MC333R-GI4HA4US
RFID Antenna	Long range	Long range	Middle range
Scanner	SE4850	SE4750	SE4750
Keypad	47	47	47
Region	US	US	US



## 1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 5.24 dBm (0.0033 W) Bluetooth EDR (2Mbps) : 4.42 dBm (0.0028 W) Bluetooth EDR (3Mbps) : 4.49 dBm (0.0028 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.884MHz Bluetooth EDR (2Mbps) : 1.212MHz Bluetooth EDR (3Mbps) : 1.184MHz
Antenna Type / Gain	Patch Antenna Type with gain 3.39 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

## 1.3 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.4 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	<b>Sporton Site No.</b>	
	03CH11-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.



## **1.5 Applicable Standards**

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.





## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-



## 2.2 Test Mode

Channel	Frequency	Bluetooth Average Output Power		
		GFSK / 1Mbps		
		DH1	DH3	DH5
Ch00	2402MHz	3.76 dBm	3.93 dBm	3.91 dBm
Ch39	2441MHz	<b>4.62 dBm</b>	4.25 dBm	4.01 dBm
Ch78	2480MHz	3.56 dBm	3.48 dBm	3.40 dBm

Channel	Frequency	Bluetooth Average Output Power		
		$\pi/4$ -DQPSK / 2Mbps		
		2DH1	2DH3	2DH5
Ch00	2402MHz	-0.47 dBm	-0.35 dBm	-0.61 dBm
Ch39	2441MHz	<b>1.66 dBm</b>	1.52 dBm	1.25 dBm
Ch78	2480MHz	0.03 dBm	0.27 dBm	0.21 dBm

Channel	Frequency	Bluetooth Average Output Power		
		8-DPSK / 3Mbps		
		3DH1	3DH3	3DH5
Ch00	2402MHz	-0.58 dBm	-0.40 dBm	-0.38 dBm
Ch39	2441MHz	1.52 dBm	<b>1.62 dBm</b>	1.27 dBm
Ch78	2480MHz	0.21 dBm	0.21 dBm	0.26 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		GFSK / 1Mbps		
		DH1	DH3	DH5
Ch00	2402MHz	4.37 dBm	4.28 dBm	4.61 dBm
Ch39	2441MHz	<b>5.24 dBm</b>	4.88 dBm	5.11 dBm
Ch78	2480MHz	4.38 dBm	4.28 dBm	4.22 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		$\pi/4$ -DQPSK / 2Mbps		
		2DH1	2DH3	2DH5
Ch00	2402MHz	2.88 dBm	2.80 dBm	2.30 dBm
Ch39	2441MHz	<b>4.42 dBm</b>	4.37 dBm	3.99 dBm
Ch78	2480MHz	3.46 dBm	3.00 dBm	3.13 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		8-DPSK / 3Mbps		
		3DH1	3DH3	3DH5
Ch00	2402MHz	2.66 dBm	2.57 dBm	2.71 dBm
Ch39	2441MHz	4.42 dBm	<b>4.49 dBm</b>	4.17 dBm
Ch78	2480MHz	3.32 dBm	3.05 dBm	3.19 dBm

**Remark:**The data rate was set in 1Mbps for all the test items due to the highest RF output power.

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.




The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
<b>Conducted Test Cases</b>	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
<b>Radiated Test Cases</b>	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz for SKU 3 Mode 2: CH39_2441 MHz for SKU 3 Mode 3: CH78_2480 MHz for SKU 3 Mode 4: CH78_2480 MHz for SKU 2 Mode 5: CH78_2480 MHz for SKU 1		
<b>AC Conducted Emission</b>	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + 29 Keypad + Scanner + Battery (Sentry 2X) + USB Cable + Adapter (PWR-WUA5V12W0US) for SKU 3		
<b>Remark:</b>			
<ol style="list-style-type: none"> <li>For radiated test cases, the worst mode data rate 1Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.</li> <li>For Radiated Test Cases, the tests were performed with Sentry 2X battery.</li> </ol>			

## 2.3 Connection Diagram of Test System

### <Bluetooth Tx Mode>



### <AC Conducted Emission Mode>





### 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

### 2.5 EUT Operation Test Setup

The RF test items, utility "CMD" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to contact with base station to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

### 2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset}(dB) &= \text{RF cable loss}(dB) + \text{attenuator factor}(dB). \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup







3.1.5 Test Result of Number of Hopping Frequency

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 29.AUG.2018 01:33:07



Date: 29.AUG.2018 01:35:52



## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup






3.2.5 Test Result of Hopping Channel Separation

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	1.002	0.6560	Pass
DH	1Mbps	1	39	2441	1.008	0.6533	Pass
DH	1Mbps	1	78	2480	1.002	0.6480	Pass
2DH	2Mbps	1	0	2402	1.002	0.9000	Pass
2DH	2Mbps	1	39	2441	0.990	0.9000	Pass
2DH	2Mbps	1	78	2480	0.990	0.9000	Pass
3DH	3Mbps	1	0	2402	0.990	0.8680	Pass
3DH	3Mbps	1	39	2441	1.008	0.8720	Pass
3DH	3Mbps	1	78	2480	1.002	0.8720	Pass

<1Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 29.AUG.2018 01:09:52




### Channel Separation Plot on Channel 39 - 40



Date: 29.AUG.2018 01:21:43

### Channel Separation Plot on Channel 77 - 78




Date: 29.AUG.2018 01:23:15




<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 29.AUG.2018 20:20:03


Channel Separation Plot on Channel 39 - 40



Date: 29.AUG.2018 01:53:17




Channel Separation Plot on Channel 77 - 78



Date: 29.AUG.2018 02:07:20

<3Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 29.AUG.2018 02:09:46




### Channel Separation Plot on Channel 39 - 40



Date: 29.AUG.2018 02:25:57

### Channel Separation Plot on Channel 77 - 78



Date: 29.AUG.2018 02:27:03

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup






3.3.5 Test Result of Dwell Time

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec) (MHz)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

Package Transfer Time Plot



Date: 3.AUG.2018 03:08:13

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



### 3.4 20dB and 99% Bandwidth Measurement

#### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
RBW  $\geq$  1-5% of the 99% bandwidth; VBW  $\geq$  3 \* RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
6. Measure and record the results in the test report.

#### 3.4.4 Test Setup






3.4.5 Test Result of 20dB Bandwidth

Mod.	Data Rate	Nrx	CH.	Freq. (MHz)	20db BW (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.984	Pass
DH	1Mbps	1	39	2441	0.980	Pass
DH	1Mbps	1	78	2480	0.972	Pass
2DH	2Mbps	1	0	2402	1.350	Pass
2DH	2Mbps	1	39	2441	1.350	Pass
2DH	2Mbps	1	78	2480	1.350	Pass
3DH	3Mbps	1	0	2402	1.302	Pass
3DH	3Mbps	1	39	2441	1.308	Pass
3DH	3Mbps	1	78	2480	1.308	Pass

<1Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 29.AUG.2018 01:14:51




20 dB Bandwidth Plot on Channel 39



Date: 29.AUG.2018 02:46:56

20 dB Bandwidth Plot on Channel 78




Date: 29.AUG.2018 01:24:23




<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 29.AUG.2018 02:51:22


20 dB Bandwidth Plot on Channel 39



Date: 29.AUG.2018 01:54:33




20 dB Bandwidth Plot on Channel 78



Date: 29.AUG.2018 02:52:34

<3Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 29.AUG.2018 02:55:44




### 20 dB Bandwidth Plot on Channel 39



Date: 29.AUG.2018 02:25:06

### 20 dB Bandwidth Plot on Channel 78



Date: 29.AUG.2018 02:54:18




3.4.6 Test Result of 99% Occupied Bandwidth

Mod.	Data Rate	Nrx	CH.	Freq. (MHz)	99% Bandwidth (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.884	Pass
DH	1Mbps	1	39	2441	0.884	Pass
DH	1Mbps	1	78	2480	0.884	Pass
2DH	2Mbps	1	0	2402	1.208	Pass
2DH	2Mbps	1	39	2441	1.212	Pass
2DH	2Mbps	1	78	2480	1.208	Pass
3DH	3Mbps	1	0	2402	1.184	Pass
3DH	3Mbps	1	39	2441	1.184	Pass
3DH	3Mbps	1	78	2480	1.184	Pass

<1Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 29.AUG.2018 01:15:59




99% Occupied Bandwidth Plot on Channel 39



Date: 29.AUG.2018 01:19:31

99% Occupied Bandwidth Plot on Channel 78




Date: 29.AUG.2018 01:26:03






<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 29.AUG.2018 01:44:59


99% Occupied Bandwidth Plot on Channel 39



Date: 29.AUG.2018 01:55:11




99% Occupied Bandwidth Plot on Channel 78



Date: 29.AUG.2018 02:03:30

<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 29.AUG.2018 02:14:27




99% Occupied Bandwidth Plot on Channel 39



Date: 29.AUG.2018 02:23:25

99% Occupied Bandwidth Plot on Channel 78



Date: 29.AUG.2018 02:30:02

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.5 Output Power Measurement

### 3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:  
(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


### 3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup





3.5.5 Test Result of Peak Output Power

DH	CH.	N <sub>TX</sub>	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	4.37	20.97	Pass
	39	1	5.24	20.97	Pass
	78	1	4.38	20.97	Pass

2DH	CH.	N <sub>TX</sub>	Peak Power (dBm)	Power Limit (dBm)	Test Result
2DH1	0	1	2.88	20.97	Pass
	39	1	4.42	20.97	Pass
	78	1	3.46	20.97	Pass

3DH	CH.	N <sub>TX</sub>	Peak Power (dBm)	Power Limit (dBm)	Test Result
3DH3	0	1	2.57	20.97	Pass
	39	1	4.49	20.97	Pass
	78	1	3.05	20.97	Pass

3.5.6 Test Result of Average Output Power (Reporting Only)

DH	CH.	N <sub>TX</sub>	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	3.76	5.16
	39	1	4.62	5.16
	78	1	3.56	5.16

2DH	CH.	N <sub>TX</sub>	Average Power (dBm)	Duty Factor (dB)
2DH1	0	1	-0.47	5.07
	39	1	1.66	5.07
	78	1	0.03	5.07

3DH	CH.	N <sub>TX</sub>	Average Power (dBm)	Duty Factor (dB)
3DH3	0	1	-0.40	1.85
	39	1	1.62	1.85
	78	1	0.21	1.85

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges


<1Mbps>

#### Low Band Edge Plot on Channel 00



Date: 29.AUG.2018 01:15:22

#### High Band Edge Plot on Channel 78




Date: 29.AUG.2018 01:25:17




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 29.AUG.2018 01:44:14

High Band Edge Plot on Channel 78




Date: 29.AUG.2018 02:03:56






<3Mbps>

Low Band Edge Plot on Channel 00



Date: 29.AUG.2018 02:11:54

High Band Edge Plot on Channel 78




Date: 29.AUG.2018 02:29:02



### 3.6.6 Test Result of Conducted Hopping Mode Band Edges


<1Mbps>

#### Hopping Mode Low Band Edge Plot



Date: 29.AUG.2018 01:32:10

#### Hopping Mode High Band Edge Plot




Date: 29.AUG.2018 01:31:18




<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 29.AUG.2018 01:40:09

Hopping Mode High Band Edge Plot




Date: 29.AUG.2018 01:40:51




<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 29.AUG.2018 03:04:17

Hopping Mode High Band Edge Plot



Date: 29.AUG.2018 03:05:00

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.7.4 Test Setup






### 3.7.5 Test Result of Conducted Spurious Emission


<1Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 29.AUG.2018 01:16:41


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 29.AUG.2018 01:17:11




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 29.AUG.2018 01:18:23


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 29.AUG.2018 01:18:54




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 29.AUG.2018 01:26:54

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 29.AUG.2018 01:27:45






<2Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 29.AUG.2018 01:45:39


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 29.AUG.2018 01:47:20




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 29.AUG.2018 01:55:48


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 29.AUG.2018 01:56:23




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 29.AUG.2018 01:59:57

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 29.AUG.2018 02:02:54




<3Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 29.AUG.2018 02:21:33


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 29.AUG.2018 02:22:03




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 29.AUG.2018 02:19:26


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 29.AUG.2018 02:20:42




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 29.AUG.2018 02:30:43

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 29.AUG.2018 02:31:10



### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

See list of measuring equipment of this test report.



### 3.8.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.




### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### 3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

### 3.8.7 Duty Cycle

Please refer to Appendix D.

### 3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix B and C.



### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	N/A	Dec. 20, 2017	Aug. 03, 2018 ~ Aug. 31, 2018	Dec. 19, 2018	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	50MHz~18GHz	Dec. 20, 2017	Aug. 03, 2018 ~ Aug. 31, 2018	Dec. 19, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2017	Aug. 03, 2018 ~ Aug. 31, 2018	Nov. 20, 2018	Conducted (TH05-HY)
BT Base Station(Measure)	Rohde & Schwarz	CBT	101136	BT 3.0	Sep. 20, 2017	Aug. 03, 2018 ~ Aug. 31, 2018	Sep. 19, 2018	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1300484	N/A	Mar. 01, 2018	Aug. 03, 2018 ~ Aug. 31, 2018	Feb. 28, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 06, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Dec. 08, 2017	Aug. 06, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Aug. 06, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Aug. 06, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Aug. 06, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Aug. 06, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	Aug. 07, 2018 ~ Aug. 27, 2018	Jul. 15, 2019	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Jan. 16, 2018	Aug. 07, 2018 ~ Aug. 27, 2018	Jan. 15, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT-N0602	30MHz~1GHz	Oct. 14, 2017	Aug. 07, 2018 ~ Aug. 27, 2018	Oct. 13, 2018	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 16, 2017	Aug. 07, 2018 ~ Aug. 27, 2018	Oct. 15, 2018	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Aug. 07, 2018 ~ Aug. 27, 2018	Nov. 22, 2018	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Jan. 16, 2018	Aug. 07, 2018 ~ Aug. 27, 2018	Jan. 15, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Oct. 19, 2017	Aug. 07, 2018 ~ Aug. 27, 2018	Oct. 18, 2018	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Aug. 07, 2018 ~ Aug. 27, 2018	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Aug. 07, 2018 ~ Aug. 27, 2018	N/A	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-303K	1710001800054001	1GHz~18GHz	Apr. 16, 2018	Aug. 07, 2018 ~ Aug. 27, 2018	Apr. 15, 2019	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	Aug. 07, 2018 ~ Aug. 27, 2018	Nov. 26, 2018	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Aug. 07, 2018 ~ Aug. 27, 2018	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz-30MHz	Mar. 14, 2018	Aug. 07, 2018 ~ Aug. 27, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 14, 2018	Aug. 07, 2018 ~ Aug. 27, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	30M-18G	Mar. 14, 2018	Aug. 07, 2018 ~ Aug. 27, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 14, 2018	Aug. 07, 2018 ~ Aug. 27, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN11	1G Low Pass	Sep. 18, 2017	Aug. 07, 2018 ~ Aug. 27, 2018	Sep. 17, 2018	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60SS	SN3	2.7G High Pass	Sep. 18, 2017	Aug. 07, 2018 ~ Aug. 27, 2018	Sep. 17, 2018	Radiation (03CH11-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.7
-------------------------------------------------------------------------	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.2
-------------------------------------------------------------------------	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.5
-------------------------------------------------------------------------	-----


### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.2
-------------------------------------------------------------------------	-----



## Appendix A. AC Conducted Emission Test Results

Test Engineer :	Arthur Hsieh	Temperature :	21~25°C
		Relative Humidity :	51~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line




### Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	---	28.79	55.75	26.96	L1	OFF	19.5
0.154500	40.08	---	65.75	25.67	L1	OFF	19.5
0.179250	---	33.11	54.52	21.41	L1	OFF	19.5
0.179250	48.12	---	64.52	16.40	L1	OFF	19.5
0.192750	---	33.93	53.92	19.99	L1	OFF	19.5
0.192750	46.34	---	63.92	17.58	L1	OFF	19.5
0.242250	---	31.33	52.02	20.69	L1	OFF	19.5
0.242250	42.67	---	62.02	19.35	L1	OFF	19.5
0.316500	---	24.79	49.80	25.01	L1	OFF	19.5
0.316500	30.98	---	59.80	28.82	L1	OFF	19.5
0.370500	---	27.17	48.49	21.32	L1	OFF	19.5
0.370500	32.41	---	58.49	26.08	L1	OFF	19.5
3.277500	---	24.67	46.00	21.33	L1	OFF	19.7
3.277500	27.98	---	56.00	28.02	L1	OFF	19.7





Test Engineer :	Arthur Hsieh	Temperature :	21~25°C
		Relative Humidity :	51~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	28.01	55.63	27.62	N	OFF	19.5
0.156750	37.51	---	65.63	28.12	N	OFF	19.5
0.179250	---	30.27	54.52	24.25	N	OFF	19.5
0.179250	45.23	---	64.52	19.29	N	OFF	19.5
0.240000	---	27.83	52.10	24.27	N	OFF	19.5
0.240000	38.91	---	62.10	23.19	N	OFF	19.5
0.303000	---	25.42	50.16	24.74	N	OFF	19.5
0.303000	32.12	---	60.16	28.04	N	OFF	19.5
0.363750	---	25.43	48.64	23.21	N	OFF	19.5
0.363750	30.53	---	58.64	28.11	N	OFF	19.5
0.435750	---	24.83	47.14	22.31	N	OFF	19.5
0.435750	29.68	---	57.14	27.46	N	OFF	19.5
3.448500	---	24.75	46.00	21.25	N	OFF	19.7
3.448500	27.95	---	56.00	28.05	N	OFF	19.7



### Appendix B. Radiated Spurious Emission

Test Engineer :	Hao Hsu, Ken Wu, and Chuan Zhu	Temperature :	21~26°C
		Relative Humidity :	51~56%

<SKU 1>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BT CH 78 2480MHz	*	2480	100.69	-	-	100.53	27.36	6.38	33.58	148	360	P	H	
	*	2480	75.9	-	-	-	-	-	-	-	-	A	H	
		2483.6	43.98	-30.02	74	43.82	27.36	6.38	33.58	148	360	P	H	
		2483.6	19.19	-34.81	54	-	-	-	-	-	-	A	H	
													H	
														H
	*	2480	100.14	-	-	99.98	27.36	6.38	33.58	130	92	P	V	
	*	2480	75.35	-	-	-	-	-	-	-	-	-	A	V
		2486.44	42.68	-31.32	74	42.51	27.36	6.39	33.58	130	92	P	V	
		2486.44	17.89	-36.11	54	-	-	-	-	-	-	A	V	
														V
														V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)	
BT CH 78 2480MHz		4960	40.03	-33.97	74	57.03	31.54	9.97	58.51	100	0	P	H	
		4960	15.24	-38.76	54	-	-	-	-	-	-	A	H	
		7440	42.43	-31.57	74	52.78	36.59	11.72	58.66	100	0	P	H	
		7440	17.64	-36.36	54	-	-	-	-	-	-	A	H	
		4960	39.19	-34.81	74	56.19	31.54	9.97	58.51	100	0	P	V	
		4960	14.4	-39.6	54	-	-	-	-	-	-	-	A	V
		7440	42.84	-31.16	74	53.19	36.59	11.72	58.66	100	0	P	V	
		7440	18.05	-35.95	54	-	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)	
2.4GHz BT LF		68.07	23.86	-16.14	40	43.43	11.88	1.04	32.49	-	-	P	H	
		107.49	29.94	-13.56	43.5	44.48	16.51	1.42	32.47	-	-	P	H	
		155.82	28.67	-14.83	43.5	42.96	16.44	1.7	32.43	-	-	P	H	
		435.8	26.26	-19.74	46	33.14	22.72	2.75	32.35	-	-	P	H	
		660.5	27.22	-18.78	46	30.15	26.23	3.31	32.47	-	-	P	H	
		940.5	34.55	-11.45	46	31.75	30.1	3.99	31.29	100	0	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			36.48	35.25	-4.75	40	46.13	20.79	0.82	32.49	100	0	P	V
			46.74	32.96	-7.04	40	48.71	15.72	1.02	32.49	-	-	P	V
			65.1	30.7	-9.3	40	50.42	11.74	1.03	32.49	-	-	P	V
			514.2	24.33	-21.67	46	30	23.75	2.97	32.39	-	-	P	V
			708.8	28.05	-17.95	46	30.4	26.61	3.48	32.44	-	-	P	V
			937.7	32.54	-13.46	46	29.88	29.98	3.99	31.31	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against limit line.													



<SKU 2>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)	
BT CH 78 2480MHz	*	2480	101.49	-	-	101.33	27.36	6.38	33.58	266	0	P	H	
	*	2480	76.7	-	-	-	-	-	-	-	-	A	H	
		2483.92	45.15	-28.85	74	44.99	27.36	6.38	33.58	266	0	P	H	
		2483.92	20.36	-33.64	54	-	-	-	-	-	-	A	H	
													H	
														H
	*	2480	100.24	-	-	100.08	27.36	6.38	33.58	107	94	P	V	
	*	2480	75.45	-	-	-	-	-	-	-	-	-	A	V
		2484	44.12	-29.88	74	43.96	27.36	6.38	33.58	107	94	P	V	
		2484	19.33	-34.67	54	-	-	-	-	-	-	A	V	
														V
														V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)	
BT CH 78 2480MHz		4960	39.54	-34.46	74	56.54	31.54	9.97	58.51	100	0	P	H	
		4960	14.75	-39.25	54	-	-	-	-	-	-	A	H	
		7440	42.7	-31.3	74	53.05	36.59	11.72	58.66	100	0	P	H	
		7440	17.91	-36.09	54	-	-	-	-	-	-	A	H	
		4960	39.74	-34.26	74	56.74	31.54	9.97	58.51	100	0	P	V	
		4960	14.95	-39.05	54	-	-	-	-	-	-	-	A	V
		7440	42.18	-31.82	74	52.53	36.59	11.72	58.66	100	0	P	V	
		7440	17.39	-36.61	54	-	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
2.4GHz BT LF		108.57	29.04	-14.46	43.5	43.48	16.61	1.42	32.47	-	-	P	H	
		155.55	28.73	-14.77	43.5	42.98	16.48	1.7	32.43	-	-	P	H	
		250.32	21.74	-24.26	46	33.65	18.45	2.02	32.38	-	-	P	H	
		446.3	26.59	-19.41	46	33.3	22.9	2.74	32.35	-	-	P	H	
		699	29.02	-16.98	46	31.61	26.4	3.48	32.47	-	-	P	H	
		944.7	33.28	-12.72	46	30.24	30.3	3.99	31.25	100	0	P	H	
														H
														H
														H
														H
														H
														H
														H
			36.48	35.87	-4.13	40	46.75	20.79	0.82	32.49	100	0	P	V
			45.66	32.89	-7.11	40	48.22	16.14	1.02	32.49	-	-	P	V
			59.97	31.35	-8.65	40	51.3	11.5	1.04	32.49	-	-	P	V
			444.2	24.37	-21.63	46	31.12	22.86	2.74	32.35	-	-	P	V
			725.6	28.43	-17.57	46	30.18	27.11	3.53	32.39	-	-	P	V
			862.1	33.21	-12.79	46	32.2	29.05	3.82	31.86	-	-	P	V
														V
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



<SKU 3>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BT CH00 2402MHz		2322.18	42.32	-31.68	74	42.83	26.95	6.15	33.61	282	360	P	H	
		2322.18	17.53	-36.47	54	-	-	-	-	-	-	A	H	
	*	2402	101.34	-	-	101.44	27.13	6.36	33.59	282	360	P	H	
	*	2402	76.55	-	-	-	-	-	-	-	-	A	H	
													H	
														H
			2350.74	42.59	-31.41	74	42.97	27	6.22	33.6	115	84	P	V
			2350.74	17.8	-36.2	54	-	-	-	-	-	-	A	V
	*		2402	94.99	-	-	95.09	27.13	6.36	33.59	115	84	P	V
	*		2402	70.2	-	-	-	-	-	-	-	-	A	V
														V
														V
BT CH 39 2441MHz		2323.16	42.14	-31.86	74	42.65	26.95	6.15	33.61	313	3	P	H	
		2323.16	17.35	-36.65	54	-	-	-	-	-	-	A	H	
	*	2441	103.01	-	-	102.94	27.27	6.38	33.58	313	3	P	H	
	*	2441	78.22	-	-	-	-	-	-	-	-	A	H	
			2485.51	42.22	-31.78	74	42.05	27.36	6.39	33.58	313	3	P	H
			2485.51	17.43	-36.57	54	-	-	-	-	-	-	A	H
			2383.78	41.61	-32.39	74	41.76	27.09	6.36	33.6	103	94	P	V
			2383.78	16.82	-37.18	54	-	-	-	-	-	-	A	V
	*		2441	97.08	-	-	97.01	27.27	6.38	33.58	103	94	P	V
	*		2441	72.29	-	-	-	-	-	-	-	-	A	V
			2493	42.34	-31.66	74	42.12	27.4	6.39	33.57	103	94	P	V
			2493	17.55	-36.45	54	-	-	-	-	-	-	A	V





<b>BT CH 78 2480MHz</b>	*	2480	103.67	-	-	103.51	27.36	6.38	33.58	265	7	P	H
	*	2480	78.88	-	-	-	-	-	-	-	-	A	H
		2483.56	45.09	-28.91	74	44.93	27.36	6.38	33.58	265	7	P	H
		2483.56	20.3	-33.7	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	96.9	-	-	96.74	27.36	6.38	33.58	100	85	P	V
	*	2480	72.11	-	-	-	-	-	-	-	-	A	V
		2483.72	43.25	-30.75	74	43.09	27.36	6.38	33.58	100	85	P	V
		2483.72	18.46	-35.54	54	-	-	-	-	-	-	A	V
													V
													V
<b>Remark</b>	<ol style="list-style-type: none"> <li>1. No other spurious found.</li> <li>2. All results are PASS against Peak and Average limit line.</li> </ol>												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BT CH 00 2402MHz		4804	38.15	-35.85	74	55.44	31.26	10.03	58.58	100	0	P	H	
		4804	13.36	-40.64	54	-	-	-	-	-	-	A	H	
													H	
													H	
		4804	37.5	-36.5	74	54.79	31.26	10.03	58.58	100	0	P	V	
		4804	12.71	-41.29	54	-	-	-	-	-	-	-	A	V
														V
														V
BT CH 39 2441MHz		4882	38.34	-35.66	74	55.52	31.38	9.99	58.55	100	0	P	H	
		4882	13.55	-40.45	54	-	-	-	-	-	-	A	H	
		7323	41.71	-32.29	74	52.45	36.32	11.75	58.81	100	0	P	H	
		7323	16.92	-37.08	54	-	-	-	-	-	-	A	H	
		4882	38.41	-35.59	74	55.59	31.38	9.99	58.55	100	0	P	V	
		4882	13.62	-40.38	54	-	-	-	-	-	-	A	V	
		7323	40.55	-33.45	74	51.29	36.32	11.75	58.81	100	0	P	V	
		7323	15.76	-38.24	54	-	-	-	-	-	-	A	V	
BT CH 78 2480MHz		4960	38.97	-35.03	74	55.97	31.54	9.97	58.51	100	0	P	H	
		4960	14.18	-39.82	54	-	-	-	-	-	-	A	H	
		7440	41.77	-32.23	74	52.12	36.59	11.72	58.66	100	0	P	H	
		7440	16.98	-37.02	54	-	-	-	-	-	-	A	H	
		4960	39.21	-34.79	74	56.21	31.54	9.97	58.51	100	0	P	V	
		4960	14.42	-39.58	54	-	-	-	-	-	-	A	V	
		7440	42.33	-31.67	74	52.68	36.59	11.72	58.66	100	0	P	V	
		7440	17.54	-36.46	54	-	-	-	-	-	-	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



## Emission below 1GHz

## 2.4GHz BT (LF)

BT	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level (dBµV)	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)	
2.4GHz BT LF		106.41	33.51	-9.99	43.5	48.14	16.42	1.42	32.47	100	0	P	H	
		157.17	29.24	-14.26	43.5	43.57	16.4	1.7	32.43	-	-	P	H	
		263.55	20.36	-25.64	46	31	19.57	2.17	32.38	-	-	P	H	
		441.4	25.36	-20.64	46	32.16	22.81	2.74	32.35	-	-	P	H	
		657	27.76	-18.24	46	30.67	26.25	3.31	32.47	-	-	P	H	
		922.3	33.41	-12.59	46	31.51	29.41	3.95	31.46	-	-	P	H	
														H
														H
														H
														H
														H
														H
			36.48	36.4	-3.6	40	47.28	20.79	0.82	32.49	100	0	P	V
			39.99	36.1	-3.9	40	48.55	19.21	0.83	32.49	-	-	P	V
			63.48	31.18	-8.82	40	50.95	11.69	1.03	32.49	-	-	P	V
			480.6	24.69	-21.31	46	30.78	23.46	2.82	32.37	-	-	P	V
			749.4	29.33	-16.67	46	30.28	27.81	3.57	32.33	-	-	P	V
			902.7	32.89	-13.11	46	31.55	29.02	3.95	31.63	-	-	P	V
														V
														V
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	Limit Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
					( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 00		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2402MHz													

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Hao Hsu, Ken Wu, and Chuan Zhu	Temperature :	21~26°C
		Relative Humidity :	51~56%

Note symbol

-L	Low channel location
-R	High channel location

<SKU 1>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 812630-07</p>	<p>Site : 03CH11-HY            Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 812630-07</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>	<p>Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.		





Emission below 1GHz

2.4GHz BT (LF)



<b>BT</b>	<b>2.4GHz 2400~2483.5MHz</b>	
<b>ANT</b>	<b>BT LF</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>QP / Peak</b>	 <p>Site : 03CH11-HY  Condition : QP 3m BT-LOG 6111D-LF_ETC HORIZONTAL  Detector : Peak  Project : 812630-07</p>	 <p>Site : 03CH11-HY  Condition : QP 3m BT-LOG 6111D-LF_ETC VERTICAL  Detector : Peak  Project : 812630-07</p>



<SKU 2>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 09CH11-HY  Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL  : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto  Detector : Peak  Project : 812630-07</p>	 <p>Site : 09CH11-HY  Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL  : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto  Detector : Peak  Project : 812630-07</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>	<p>Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>



2.4GHz 2400~2483.5MHz



BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.		



Emission below 1GHz

2.4GHz BT (LF)



BT	2.4GHz 2400~2483.5MHz	
ANT	BT LF	
1	Horizontal	Vertical
QP / Peak	 <p>Site : 03CH11-HY  Condition : QP 3m BT-LOG 6111D-LF_ETC HORIZONTAL  Detector : Peak  Project : 812630-07</p>	 <p>Site : 03CH11-HY  Condition : QP 3m BT-LOG 6111D-LF_ETC VERTICAL  Detector : Peak  Project : 812630-07</p>



<SKU 3>

2.4GHz 2400~2483.5MHz




BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH11-4Y  Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL  : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto  Detector : Peak  Project : 812630-07</p>	 <p>Site : 03CH11-4Y  Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL  : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto  Detector : Peak  Project : 812630-07</p>






BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>	<p>Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Fundamental
<p><b>Peak</b></p>	 <p>Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL            Detector : Peak            Project : 812630-07</p>	 <p>Site : 03CH11-HY            Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL            Detector : Peak            Project : 812630-07</p>
<p><b>Peak</b></p>	 <p>Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL            Detector : Peak            Project : 812630-07</p>	<p><b>Left blank</b></p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH11-HY  Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL  : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto  Detector : Peak  Project : 812630-07</p>	 <p>Site : 03CH11-HY  Condition : PEAK_74 3m HORN 91200-HF VERTICAL  : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto  Detector : Peak  Project : 812630-07</p>
Peak	 <p>Site : 03CH11-HY  Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL  : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto  Detector : Peak  Project : 812630-07</p>	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>	<p>Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>	<p>Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 812630-07</p>



2.4GHz 2400~2483.5MHz



BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 812630-07</p>	 <p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 812630-07</p>



<b>BT</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>BT CH39 2441MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH11-11Y Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 812630-07</p>	<p>Site : 03CH11-11Y Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 812630-07</p>





<b>BT</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>BT CH78 2480MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	 <p>Site : 03CH11-11Y Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 812630-07</p>	 <p>Site : 03CH11-11Y Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 812630-07</p>



Emission below 1GHz

2.4GHz BT (LF)


BT	2.4GHz 2400~2483.5MHz	
ANT	BT LF	
1	Horizontal	Vertical
QP / Peak	 <p>Site : 03CH11-HY          Condition : QP 3m BT-LOG 6111D-LF_ETC HORIZONTAL          Detector : Peak          Project : 812630-07</p>	 <p>Site : 03CH11-HY          Condition : QP 3m BT-LOG 6111D-LF_ETC VERTICAL          Detector : Peak          Project : 812630-07</p>




# Appendix D. Duty Cycle Plots

<SKU 1>

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39



**Note:**


1. Worst case Duty cycle = on time/100 milliseconds = 2 \* 2.88 / 100 = 5.76 %
2. Worst case Duty cycle correction factor = 20\*log(Duty cycle) = -24.79 dB
3. DH5 has the highest duty cycle worst case and is reported.






<SKU 2>

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39




Note:

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.




<SKU 3>

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39



Note:

4. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.88 / 100 = 5.76 \%$
5. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
6. DH5 has the highest duty cycle worst case and is reported.



**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.6\text{ms}] = 2$  hops

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$