



# RF EXPOSURE REPORT (FOR RFID)

**REPORT NO.:** SA110311C24A-5 R1

**MODEL NO.:** MC75A6HF

**FCC ID:** UZ7MC75A6HF

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Motorola Solutions Inc.

**ADDRESS:** One Motorola Plaza, Holtsville, NY-11742-1300,  
U.S.A.

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan  
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	NA	Mar. 28, 2011
SA110311C24A-5 R1	Removed radiated power and added conducted power	May 31, 2011



## CERTIFICATION

**PRODUCT:** Mobile Computer  
**MODEL:** MC75A6HF  
**BRAND:** Motorola  
**APPLICANT:** Motorola Solutions Inc.  
**TESTED:** Mar. 16 ~ Mar. 18, 2011  
**TEST SAMPLE:** ENGINEERING SAMPLE  
**STANDARDS:** **FCC Guidelines for Human Exposure**  
**IEEE C95.1**

The above equipment (model: MC75A6HF) have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** :  , **DATE** : May 31, 2011  
Pettie Chen / Specialist

**APPROVED BY** :  , **DATE** : May 31, 2011  
Gary Chang / Assistant Manager



No Evaluation Required if power is below this threshold:

F(MHz)	mW
13.56	4424.779

Maximum measured transmitter power:

Conducted power ( dBm )	Conducted power ( mW )
14.28	26.79

**NOTE:**

Threshold for no SAR evaluation is 4424.779mW  
Transmitter power is 26.79 mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold