




FCC SAR TEST REPORT

FCC ID : UZ7TC26BK
Equipment : Touch computer
Brand Name : Zebra
Model Name : TC26BK
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was received on Mar. 26, 2020 and testing was started from Apr. 21, 2020 and completed on Apr. 25, 2020. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance 4
2. Guidance Applied..... 4
3. Equipment Under Test (EUT) Information 5
3.1 General Information 5
3.2 General LTE SAR Test and Reporting Considerations 7
4. RF Exposure Limits..... 9
4.1 Uncontrolled Environment..... 9
4.2 Controlled Environment..... 9
5. Specific Absorption Rate (SAR).....10
5.1 Introduction10
5.2 SAR Definition.....10
6. System Description and Setup11
6.1 E-Field Probe12
6.2 Data Acquisition Electronics (DAE)12
6.3 Phantom.....13
6.4 Device Holder.....14
7. Measurement Procedures15
7.1 Spatial Peak SAR Evaluation15
7.2 Power Reference Measurement.....16
7.3 Area Scan16
7.4 Zoom Scan.....17
7.5 Volume Scan Procedures.....17
7.6 Power Drift Monitoring.....17
8. Test Equipment List18
9. System Verification19
9.1 Tissue Simulating Liquids.....19
9.2 Tissue Verification20
9.3 System Performance Check Results.....21
10. RF Exposure Positions23
10.1 Ear and handset reference point23
10.2 Definition of the cheek position24
10.3 Definition of the tilt position25
10.4 Body Worn Accessory26
10.5 Product Specific Exposure26
10.6 Wireless Router.....27
11. GSM/UMTS/LTE Output Power (Unit: dBm)28
12. WiFi Output Power (Unit: dBm).....60
13. Bluetooth Exclusions Applied64
14. Antenna Location65
15. SAR Test Results66
15.1 Head SAR68
15.2 Hotspot SAR72
15.3 Body Worn Accessory SAR75
15.4 Product Specific SAR.....78
15.5 Repeated SAR Measurement79
16. Simultaneous Transmission Analysis80
16.1 Head Exposure Conditions81
16.2 Body Exposure Conditions82
16.3 Body-Worn Accessory Exposure Conditions84
16.4 Product Specific Exposure Conditions84
16.5 SPLSR Evaluation and Analysis.....85
17. Uncertainty Assessment88
18. References.....88
Appendix A. Plots of System Performance Check
Appendix B. Plots of High SAR Measurement
Appendix C. DASy Calibration Certificate
Appendix D. Test Setup Photos



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Zebra Technologies Corporation, Touch computer, TC26BK**, are as follows.

Equipment Class	Frequency Band		Highest SAR Summary				Highest Simultaneous Transmission 1g SAR (W/kg)
			Head (Separation 0mm)	Body-worn (Separation 0mm)	Hotspot (Separation 10mm)	Product Specific (Separation 0mm)	
			1g SAR (W/kg)			10g SAR (W/kg)	
Licensed	GSM	GSM850	0.52	0.32	0.45		1.59
		GSM1900	0.80	0.52	1.16		
	WCDMA	WCDMA II	0.82	0.71	0.96		
		WCDMA IV	1.05	0.99	0.98	2.59	
		WCDMA V	0.78	0.42	0.60		
	LTE	LTE Band 2	0.89	0.67	1.10	2.87	
		LTE Band 4	0.90	0.81	0.94	2.25	
		LTE Band 5	0.68	0.41	0.65		
		LTE Band 7	1.28	0.53	0.76		
		LTE Band 38 / 41	1.04	0.35	0.73		
DTS	WLAN	2.4GHz WLAN	1.17	0.30	0.63		1.53
NII		5GHz WLAN	0.85	0.98	1.23	2.03	1.59
Date of Testing:			2020/4/21 ~ 2020/4/25				

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications

Reviewed by: Jason Wang
Report Producer: Daisy Peng

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01
- FCC KDB 941225 D07 UMPC Mini Tablet v01r02



3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	Touch computer
Brand Name	Zebra
Model Name	TC26BK
FCC ID	UZ7TC26BK
Sample1	Single-WAN, WLAN, GMS, SE4710, NFC, 3GB/32GB, Rear camera and Front camera, 2-pin connector
Sample2	Single-WAN, WLAN, GMS, No Scanner, NFC, 3GB/32GB, Rear camera and Front camera, No back connector
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz WLAN 2.4GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8GHz Band: 5725 MHz ~ 5825 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz
Mode	GSM/GPRS/EGPRS/DTM RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA LTE: QPSK, 16QAM, 64QAM WLAN: 802.11a/b/g/n/ac HT20/HT40/VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE NFC:ASK
HW Version	EV1.7
SW Version	Android version 10
OS Version	FUSION_QA_2_1.0.0.008_Q
FW Version	Zebra/TC26PA/TC26:10/03-09-09.00-QN-U00-PRD/Nabe03091333:userdebug/test-keys
MFD	22FEB20
GSM / (E)GPRS Dual Transfer mode	Class A – EUT can support Packet Switched and Circuit Switched Network simultaneously.
EUT Stage	Engineering sample
Remark:	
<ol style="list-style-type: none"> All test items were performed with Sample 1. The device had three batteries. Selected Battery 1 as the main testing and Battery 2~3 will select worst case found in Battery 1 performs. 	



Specification of Accessories				
AC Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V12W0US
AC Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V12W0EU
Battery 1	Brand Name	Zebra	Part Number	BT-000409-00
Battery 2	Brand Name	Zebra	Part Number	BT-000409-50
Battery 3	Brand Name	Zebra	Part Number	BT-000411-08
USB Cable 1 (TypeA plug to TypeC plug)	Brand Name	Zebra	Part Number	CBL-TC5X-USBC2A-01
USB Cable 2 (TypeA plug to TypeC plug)	Brand Name	Zebra	Part Number	CBL-TC2Y-USBC90A-01
Headset 3.5mm type with PTT/micassy	Brand Name	Zebra	Part Number	HDST-35MM-PTVP-01
Adapter Cable PTT headset (3.5mm to 3.5mm)	Brand Name	Zebra	Part Number	CBL-TC51-HDST35-01
Snap on Trigger handle	Brand Name	Zebra	Part Number	TRG-TC2Y-SNP1-01
Belt Holster	Brand Name	Zebra	Part Number	SG-TC2Y-HLSTR1-01
Wearable Arm Mount	Brand Name	Zebra	Part Number	SG-TC2Y-ARMNT-01

Supported Unit Used in Test Configuration and System				
Type C to 3.5mm headset adaptor	Brand Name	Google	Part Number	Pixel-2-2XL



3.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05																																																															
FCC ID	UZ7TC26BK																																																														
Equipment Name	Touch computer																																																														
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz																																																														
Channel Bandwidth	LTE Band 02: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 04: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 05: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 07: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz																																																														
uplink modulations used	QPSK / 16QAM / 64QAM																																																														
LTE Voice / Data requirements	Data only / Voice and Data																																																														
LTE MPR permanently built-in by design	<p>Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3</p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (N_{RB})</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 3</td> </tr> <tr> <td>256 QAM</td> <td colspan="6">≥ 1</td> <td>≤ 5</td> </tr> </tbody> </table>	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)																																																								
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																									
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																								
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																								
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																								
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																								
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																								
256 QAM	≥ 1						≤ 5																																																								
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																														
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																														
Power reduction applied to satisfy SAR compliance	Yes, when operating in hotspot mode that LTE B2 / B4 / B7 power reduction applied to satisfy SAR compliance.																																																														



Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829	20450	829	20450	829
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5
H	20643	848.3	20635	847.5	20625	846.5	20600	844	20600	844	20600	844
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510	20850	2510	20850	2510
M	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560	21350	2560	21350	2560
LTE Band 38												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	37775	2572.5	37800	2575	37825	2577.5	37850	2580	37850	2580	37850	2580
M	38000	2595	38000	2595	38000	2595	38000	2595	38000	2595	38000	2595
H	38225	2617.5	38200	2615	38175	2612.5	38150	2610	38150	2610	38150	2610
LTE Band 41												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	39675	2498.5	39700	2501	39725	2503.5	39750	2506	39750	2506	39750	2506
L	40148	2545.8	40160	2547	40173	2548.3	40185	2549.5	40185	2549.5	40185	2549.5
M	40620	2593	40620	2593	40620	2593	40620	2593	40620	2593	40620	2593
H	41093	2640.3	41080	2639	41068	2637.8	41055	2636.5	41055	2636.5	41055	2636.5
H	41565	2687.5	41540	2685	41515	2682.5	41490	2680	41490	2680	41490	2680



4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.


6.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE


6.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d167	Nov. 25, 2019	Nov. 24, 2020
SPEAG	1750MHz System Validation Kit	D1750V2	1112	Mar. 07, 2019	Mar. 05, 2021
SPEAG	1900MHz System Validation Kit	D1900V2	5d185	Mar. 07, 2019	Mar. 05, 2021
SPEAG	2450MHz System Validation Kit	D2450V2	929	Nov. 21, 2019	Nov. 20, 2020
SPEAG	2600MHz System Validation Kit	D2600V2	1078	Mar. 06, 2019	Mar. 04, 2021
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Sep. 27, 2018	Sep. 25, 2020
SPEAG	Data Acquisition Electronics	DAE4	376	Dec. 06, 2019	Dec. 05, 2020
SPEAG	Data Acquisition Electronics	DAE3	495	May. 21, 2019	May. 20, 2020
SPEAG	Data Acquisition Electronics	DAE4	699	Feb. 26, 2020	Feb. 25, 2021
SPEAG	Data Acquisition Electronics	DAE4	778	May. 21, 2019	May. 20, 2020
SPEAG	Data Acquisition Electronics	DAE4	916	Dec. 17, 2019	Dec. 16, 2020
SPEAG	Dosimetric E-Field Probe	ES3DV3	3169	May. 24, 2019	May. 23, 2020
SPEAG	Dosimetric E-Field Probe	ES3DV3	3184	Sep. 25, 2019	Sep. 24, 2020
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 25, 2019	Sep. 24, 2020
SPEAG	Dosimetric E-Field Probe	EX3DV4	3728	Feb. 04, 2020	Feb. 03, 2021
SPEAG	Dosimetric E-Field Probe	EX3DV4	3925	Sep. 20, 2019	Sep. 19, 2020
RCPTWN	Thermometer	HTC-1	TM685-1	Nov. 12, 2019	Nov. 11, 2020
RCPTWN	Thermometer	HTC-1	TM560-2	Nov. 12, 2019	Nov. 11, 2020
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Oct. 31, 2019	Oct. 30, 2020
Agilent	Wireless Communication Test Set	E5515C	MY50267236	Mar. 18, 2020	Mar. 17, 2021
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Nov. 20, 2019	Nov. 19, 2020
Agilent	ENA Network Analyzer	E5071C	MY46104758	Sep. 06, 2019	Sep. 05, 2020
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 18, 2019	Sep. 17, 2020
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3169	Sep. 10, 2019	Sep. 09, 2020
Anritsu	Power Meter	ML2495A	1036004	Aug. 08, 2019	Aug. 07, 2020
Anritsu	Power Sensor	MA2411B	1027253	Aug. 08, 2019	Aug. 07, 2020
Anritsu	Power Meter	ML2495A	1419002	May. 29, 2019	May. 28, 2020
Anritsu	Power Sensor	MA2411B	1339124	May. 29, 2019	May. 28, 2020
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 27, 2019	Aug. 26, 2020
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 27, 2019	Jun. 26, 2020
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 16, 2019	Oct. 15, 2020
Mini-Circuits	Power Amplifier	ZVE-8G+	6382	Aug. 12, 2019	Aug. 11, 2020
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005-3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole D1750V2, SN: 1112, D1900V2, SN: 5d185, D2600V2, SN: 1078 and D5GHzV2, SN: 1006 can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

9. System Verification

9.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1 Photo of Liquid Height for Head SAR




Fig 10.2 Photo of Liquid Height for Body SAR



9.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ε _r)
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ε _r)	Conductivity Target (σ)	Permittivity Target (ε _r)	Delta (σ) (%)	Delta (ε _r) (%)	Limit (%)	Date
835	22.7	0.930	42.371	0.90	41.50	3.33	2.10	±5	2020/4/22
835	22.5	0.931	42.471	0.90	41.50	3.44	2.34	±5	2020/4/24
1750	22.9	1.360	41.536	1.37	40.10	-0.73	3.58	±5	2020/4/21
1750	22.6	1.407	39.471	1.37	40.10	2.70	-1.57	±5	2020/4/21
1750	22.6	1.397	39.277	1.37	40.10	1.97	-2.05	±5	2020/4/22
1750	22.1	1.394	40.709	1.37	40.10	1.75	1.52	±5	2020/4/23
1900	22.9	1.433	39.411	1.40	40.00	2.36	-1.47	±5	2020/4/21
1900	22.4	1.422	41.123	1.40	40.00	1.57	2.81	±5	2020/4/21
1900	22.6	1.435	39.809	1.40	40.00	2.50	-0.48	±5	2020/4/22
1900	22.1	1.444	39.959	1.40	40.00	3.14	-0.10	±5	2020/4/23
2450	22.5	1.752	38.735	1.80	39.20	-2.67	-1.19	±5	2020/4/25
2600	22.5	1.969	38.529	1.96	39.00	0.46	-1.21	±5	2020/4/21
2600	22.7	1.957	38.474	1.96	39.00	-0.15	-1.35	±5	2020/4/23
2600	22.3	1.994	37.710	1.96	39.00	1.73	-3.31	±5	2020/4/25
5250	22.6	4.700	36.549	4.66	36.00	0.86	1.53	±5	2020/4/25
5600	22.6	4.903	35.363	5.07	35.50	-3.29	-0.39	±5	2020/4/24
5750	22.6	5.063	35.131	5.22	35.90	-3.01	-2.14	±5	2020/4/24



9.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2020/4/22	835	250	D835V2-4d167	ES3DV3 - SN3184	DAE4 Sn916	2.28	9.55	9.12	-4.50
2020/4/24	835	250	D835V2-4d167	ES3DV3 - SN3184	DAE4 Sn916	2.29	9.55	9.16	-4.08
2020/4/21	1750	250	D1750V2-1112	ES3DV3 - SN3169	DAE4 Sn699	9.02	36.70	36.08	-1.69
2020/4/21	1750	250	D1750V2-1112	EX3DV4 - SN3925	DAE4 Sn376	9.56	36.70	38.24	4.20
2020/4/22	1750	250	D1750V2-1112	EX3DV4 - SN3925	DAE4 Sn376	9.50	36.70	38	3.54
2020/4/23	1750	250	D1750V2-1112	EX3DV4 - SN3925	DAE4 Sn376	9.41	36.70	37.64	2.56
2020/4/21	1900	250	D1900V2-5d185	ES3DV3 - SN3169	DAE4 Sn699	9.62	39.40	38.48	-2.34
2020/4/21	1900	250	D1900V2-5d185	EX3DV4 - SN3925	DAE4 Sn376	9.48	39.40	37.92	-3.76
2020/4/22	1900	250	D1900V2-5d185	EX3DV4 - SN3925	DAE4 Sn376	9.57	39.40	38.28	-2.84
2020/4/23	1900	250	D1900V2-5d185	EX3DV4 - SN3925	DAE4 Sn376	10.60	39.40	42.4	7.61
2020/4/25	2450	250	D2450V2-929	ES3DV3 - SN3270	DAE4 Sn778	13.60	53.10	54.4	2.45
2020/4/21	2600	250	D2600V2-1078	ES3DV3 - SN3184	DAE4 Sn916	13.60	57.60	54.4	-5.56
2020/4/23	2600	250	D2600V2-1078	ES3DV3 - SN3184	DAE4 Sn916	13.60	57.60	54.4	-5.56
2020/4/25	2600	250	D2600V2-1078	ES3DV3 - SN3169	DAE4 Sn699	14.40	57.60	57.6	0.00
2020/4/25	5250	100	D5GHzV2-1006-5250	EX3DV4 - SN3728	DAE3 Sn495	7.52	80.70	75.2	-6.82
2020/4/24	5600	100	D5GHzV2-1006-5600	EX3DV4 - SN3728	DAE3 Sn495	8.33	83.30	83.3	0.00
2020/4/24	5750	100	D5GHzV2-1006-5750	EX3DV4 - SN3728	DAE3 Sn495	7.66	80.40	76.6	-4.73

Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2020/4/21	1750	250	D1750V2-1112	ES3DV3 - SN3169	DAE4 Sn699	4.83	19.40	19.32	-0.41
2020/4/21	1750	250	D1750V2-1112	EX3DV4 - SN3925	DAE4 Sn376	4.98	19.40	19.92	2.68
2020/4/22	1750	250	D1750V2-1112	EX3DV4 - SN3925	DAE4 Sn376	4.94	19.40	19.76	1.86
2020/4/23	1750	250	D1750V2-1112	EX3DV4 - SN3925	DAE4 Sn376	5.02	19.40	20.08	3.51
2020/4/21	1900	250	D1900V2-5d185	ES3DV3 - SN3169	DAE4 Sn699	5.06	20.50	20.24	-1.27
2020/4/21	1900	250	D1900V2-5d185	EX3DV4 - SN3925	DAE4 Sn376	4.91	20.50	19.64	-4.20
2020/4/22	1900	250	D1900V2-5d185	EX3DV4 - SN3925	DAE4 Sn376	4.95	20.50	19.8	-3.41
2020/4/23	1900	250	D1900V2-5d185	EX3DV4 - SN3925	DAE4 Sn376	5.42	20.50	21.68	5.76
2020/4/25	5250	100	D5GHzV2-1006-5250	EX3DV4 - SN3728	DAE3 Sn495	2.14	23.20	21.4	-7.76
2020/4/24	5600	100	D5GHzV2-1006-5600	EX3DV4 - SN3728	DAE3 Sn495	2.35	23.80	23.5	-1.26
2020/4/24	5750	100	D5GHzV2-1006-5750	EX3DV4 - SN3728	DAE3 Sn495	2.16	22.90	21.6	-5.68




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

10.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 9.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

10.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

10.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

10.5 Product Specific Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.6 The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.



10.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets (L x W \geq 9 cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.



11. GSM/UMTS/LTE Output Power (Unit: dBm)

<GSM Conducted Power>

General Note:

- For DTM multi-slot class mode, the device was linked with base station simulator (Agilent E5515C) and transmit maximum power on maximum number of TX slots, i.e. one CS timeslot, and additional PS timeslots (1 for DTM class 5 and 9, 2 for DTM class 11) in one TDMA frame.
- Agilent E5515C was used to setup the device operated under DTM mode for power measurement and SAR testing. For conducted power, the power of the burst for voice and the power of the bursts for data was reported separately in the table below, and the frame-average power is derived below to determine SAR testing.

$$DTM \text{ frame average power (dBm)} = 10 * \log [\sum (\text{power of each slot, in mW}) / 8]$$
- Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
- Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode

GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot		33.16	33.26	33.34	34.00	24.16	24.26	24.34	25.00
GPRS 1 Tx slot		33.82	33.99	33.92	34.00	24.82	24.99	24.92	25.00
GPRS 2 Tx slots		30.52	30.81	30.98	31.00	24.52	24.81	24.98	25.00
GPRS 3 Tx slots		28.77	28.53	28.63	29.00	24.51	24.27	24.37	24.74
GPRS 4 Tx slots		27.25	27.71	27.62	28.00	24.25	24.71	24.62	25.00
EDGE 1 Tx slot		27.11	26.77	26.90	28.00	18.11	17.77	17.90	19.00
EDGE 2 Tx slots		24.44	24.11	24.20	25.00	18.44	18.11	18.20	19.00
EDGE 3 Tx slots		22.98	22.60	22.79	23.00	18.72	18.34	18.53	18.74
EDGE 4 Tx slots		21.63	21.22	21.43	22.00	18.63	18.22	18.43	19.00
DTM Multi-slot class 5	GSM 1 Tx slot	30.69	30.85	30.72	31.00	24.66	24.80	24.69	24.98
	GPRS 1 Tx slot	30.67	30.80	30.71	31.00				
DTM Multi-slot class 9	GSM 1 Tx slot	30.50	30.82	31.00	31.00	24.47	24.78	24.96	24.98
	GPRS 1 Tx slot	30.48	30.79	30.97	31.00				
DTM Multi-slot class 11	GSM 1 Tx slot	28.68	29.00	28.93	29.00	24.41	24.74	24.56	24.74
	GPRS 2 Tx slots	28.66	29.00	28.76	29.00				
DTM Multi-slot class 5	GSM 1 Tx slot	30.55	30.84	30.88	31.00	22.45	22.66	22.68	22.94
	EDGE 1 Tx slot	24.35	24.18	24.14	25.00				
DTM Multi-slot class 9	GSM 1 Tx slot	30.53	30.85	30.86	31.00	22.43	22.67	22.67	22.94
	EDGE 1 Tx slot	24.34	24.19	24.16	25.00				
DTM Multi-slot class 11	GSM 1 Tx slot	28.80	28.76	28.72	29.00	21.60	21.49	21.46	21.74
	EDGE 2 Tx slots	22.98	22.74	22.72	23.00				



GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot		31.27	31.29	31.18	31.50	22.27	22.29	22.18	22.50
GPRS 1 Tx slot		31.49	31.43	30.84	31.50	22.49	22.43	21.84	22.50
GPRS 2 Tx slots		27.90	28.50	26.53	28.50	21.90	22.50	20.53	22.50
GPRS 3 Tx slots		26.48	26.46	25.00	26.50	22.22	22.20	20.74	22.24
GPRS 4 Tx slots		25.10	25.09	24.00	25.50	22.10	22.09	21.00	22.50
EDGE 1 Tx slot		27.36	27.22	27.49	27.50	18.36	18.22	18.49	18.50
EDGE 2 Tx slots		22.54	24.27	22.94	24.50	16.54	18.27	16.94	18.50
EDGE 3 Tx slots		20.53	22.06	20.88	22.50	16.27	17.80	16.62	18.24
EDGE 4 Tx slots		19.56	20.41	19.61	21.50	16.56	17.41	16.61	18.50
DTM Multi-slot class 5	GSM 1 Tx slot	27.89	27.19	26.50	28.50	21.84	21.17	20.49	22.48
	GPRS 1 Tx slot	27.84	27.19	26.53	28.50				
DTM Multi-slot class 9	GSM 1 Tx slot	27.90	27.17	26.52	28.50	21.88	21.17	20.50	22.48
	GPRS 1 Tx slot	27.90	27.22	26.53	28.50				
DTM Multi-slot class 11	GSM 1 Tx slot	26.42	25.82	24.94	26.50	22.16	21.52	20.69	22.24
	GPRS 2 Tx slots	26.42	25.76	24.95	26.50				
DTM Multi-slot class 5	GSM 1 Tx slot	27.87	27.23	26.51	28.50	19.96	19.48	19.03	20.92
	EDGE 1 Tx slot	22.54	22.59	22.84	24.50				
DTM Multi-slot class 9	GSM 1 Tx slot	27.83	27.18	26.53	28.50	19.92	19.45	19.07	20.92
	EDGE 1 Tx slot	22.54	22.61	22.93	24.50				
DTM Multi-slot class 11	GSM 1 Tx slot	26.47	25.79	24.94	26.50	19.23	18.82	18.42	20.01
	EDGE 2 Tx slots	20.53	20.62	20.86	22.50				

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15, \beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCl
 - viii. Confirm that E-TFCl is equal to the target E-TFCl of 75 for sub-test 1, and other subtest's E-TFCl
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCl
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Factor to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

Setup Configuration



<WCDMA Conducted Power>

General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is ≤ ¼ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than ¼ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

Default Power Mode

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938	1537	1638	1738	4357	4407	4458			
Frequency (MHz)		1852.4	1880	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6			
3GPP Rel 99	AMR 12.2Kbps	23.95	23.78	23.70	24.00	24.46	24.25	24.38	24.50	25.28	25.27	25.01	25.50
3GPP Rel 99	RMC 12.2Kbps	23.98	23.80	23.71	24.00	24.49	24.30	24.41	24.50	25.30	25.28	25.05	25.50
3GPP Rel 6	HSDPA Subtest-1	22.95	22.81	22.73	23.00	23.50	23.30	23.47	23.50	24.32	24.29	24.08	24.50
3GPP Rel 6	HSDPA Subtest-2	22.99	22.84	22.81	23.00	23.49	23.25	23.49	23.50	24.30	24.14	24.06	24.50
3GPP Rel 6	HSDPA Subtest-3	22.47	22.35	22.30	22.50	22.89	22.77	22.93	23.00	23.98	23.96	23.72	24.00
3GPP Rel 6	HSDPA Subtest-4	22.50	22.33	22.24	22.50	22.95	22.77	22.99	23.00	23.79	23.79	23.59	24.00
3GPP Rel 8	DC-HSDPA Subtest-1	22.93	22.74	22.63	23.00	23.47	23.21	23.44	23.50	24.31	24.24	24.08	24.50
3GPP Rel 8	DC-HSDPA Subtest-2	22.92	22.83	22.74	23.00	23.42	23.16	23.45	23.50	24.23	24.06	23.97	24.50
3GPP Rel 8	DC-HSDPA Subtest-3	22.38	22.25	22.28	22.50	22.87	22.71	22.84	23.00	23.95	23.92	23.64	24.00
3GPP Rel 8	DC-HSDPA Subtest-4	22.46	22.23	22.22	22.50	22.88	22.69	22.91	23.00	23.70	23.73	23.50	24.00
3GPP Rel 6	HSUPA Subtest-1	22.98	22.86	22.79	23.00	23.48	23.28	23.44	23.50	24.48	24.45	24.21	24.50
3GPP Rel 6	HSUPA Subtest-2	21.00	20.84	20.78	21.00	21.46	21.37	21.45	21.50	22.46	22.50	22.15	22.50
3GPP Rel 6	HSUPA Subtest-3	22.00	21.79	21.80	22.00	22.43	22.32	22.46	22.50	23.48	23.46	23.26	23.50
3GPP Rel 6	HSUPA Subtest-4	21.00	20.83	20.78	21.00	21.50	21.29	21.46	21.50	22.48	22.42	22.27	22.50
3GPP Rel 6	HSUPA Subtest-5	23.00	22.90	22.80	23.00	23.48	23.20	23.40	23.50	24.50	24.40	24.20	24.50




Hotspot Power Mode

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513	
Rx Channel		9662	9800	9938		1537	1638	1738	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6	
3GPP Rel 99	AMR 12.2Kbps	23.40	23.26	23.17	23.50	22.98	22.94	22.97	23.00
3GPP Rel 99	RMC 12.2Kbps	23.41	23.27	23.19	23.50	22.99	22.94	22.90	23.00
3GPP Rel 6	HSDPA Subtest-1	22.48	22.29	22.27	22.50	21.99	21.94	21.93	22.00
3GPP Rel 6	HSDPA Subtest-2	21.95	21.86	21.74	22.50	21.56	21.45	21.56	22.00
3GPP Rel 6	HSDPA Subtest-3	21.98	21.87	21.77	22.00	21.43	21.43	21.47	21.50
3GPP Rel 6	HSDPA Subtest-4	21.96	21.83	21.75	22.00	21.41	21.47	21.45	21.50
3GPP Rel 8	DC-HSDPA Subtest-1	22.47	22.25	22.21	22.50	21.97	21.88	21.87	22.00
3GPP Rel 8	DC-HSDPA Subtest-2	21.94	21.79	21.70	22.50	21.55	21.36	21.47	22.00
3GPP Rel 8	DC-HSDPA Subtest-3	21.93	21.84	21.72	22.00	21.41	21.39	21.46	21.50
3GPP Rel 8	DC-HSDPA Subtest-4	21.90	21.77	21.72	22.00	21.34	21.37	21.39	21.50
3GPP Rel 6	HSUPA Subtest-1	22.47	22.28	22.25	22.50	21.99	21.95	21.99	22.00
3GPP Rel 6	HSUPA Subtest-2	20.38	20.31	20.29	20.50	19.94	19.97	19.92	20.00
3GPP Rel 6	HSUPA Subtest-3	21.43	21.29	21.19	21.50	20.97	20.93	20.92	21.00
3GPP Rel 6	HSUPA Subtest-4	20.48	20.27	20.29	20.50	19.98	19.94	20.00	20.00
3GPP Rel 6	HSUPA Subtest-5	22.40	22.30	22.30	22.50	21.91	21.90	21.91	22.00


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4/B5/B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 38 SAR test was covered by Band 41; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM



Default Power Mode

<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	23.87	23.75	23.59	24.5	0
20	QPSK	1	49	23.82	23.70	23.62		
20	QPSK	1	99	23.76	23.66	22.87		
20	QPSK	50	0	22.91	22.77	22.63	23.5	1
20	QPSK	50	24	22.90	22.77	22.77		
20	QPSK	50	50	22.85	22.72	22.72		
20	QPSK	100	0	22.86	22.74	22.61	23.5	1
20	16QAM	1	0	23.13	23.04	22.88		
20	16QAM	1	49	23.13	23.02	22.83		
20	16QAM	1	99	23.04	22.96	22.28	22.5	2
20	16QAM	50	0	22.02	21.89	21.69		
20	16QAM	50	24	22.01	21.92	21.82		
20	16QAM	50	50	21.95	21.87	21.79	22.5	2
20	16QAM	100	0	21.97	21.88	21.67		
20	64QAM	1	0	22.06	22.03	21.82		
20	64QAM	1	49	22.30	22.01	21.85	22.5	2
20	64QAM	1	99	22.10	21.96	21.39		
20	64QAM	50	0	21.01	20.90	20.73		
20	64QAM	50	24	21.01	20.91	20.86	21.5	3
20	64QAM	50	50	20.95	20.87	20.82		
20	64QAM	100	0	20.99	20.90	20.74		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	23.86	23.66	23.53	24.5	0
15	QPSK	1	37	23.74	23.62	23.55		
15	QPSK	1	74	23.73	23.59	22.80		
15	QPSK	36	0	22.90	22.75	22.55	23.5	1
15	QPSK	36	20	22.88	22.68	22.71		
15	QPSK	36	39	22.78	22.65	22.69		
15	QPSK	75	0	22.77	22.69	22.59	23.5	1
15	16QAM	1	0	23.05	23.00	22.86		
15	16QAM	1	37	23.10	22.92	22.77		
15	16QAM	1	74	23.00	22.96	22.25	22.5	2
15	16QAM	36	0	22.02	21.89	21.60		
15	16QAM	36	20	21.91	21.87	21.72		
15	16QAM	36	39	21.93	21.87	21.70	22.5	2
15	16QAM	75	0	21.88	21.78	21.67		
15	64QAM	1	0	22.04	22.02	21.80		
15	64QAM	1	37	22.21	22.01	21.84	22.5	2
15	64QAM	1	74	22.00	21.93	21.33		
15	64QAM	36	0	20.92	20.90	20.63		
15	64QAM	36	20	21.01	20.82	20.83	21.5	3
15	64QAM	36	39	20.89	20.82	20.82		
15	64QAM	75	0	20.93	20.83	20.72		



Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	23.85	23.66	23.58	24.5	0
10	QPSK	1	25	23.75	23.67	23.58		
10	QPSK	1	49	23.71	23.57	22.87		
10	QPSK	25	0	22.87	22.67	22.63	23.5	1
10	QPSK	25	12	22.89	22.77	22.75		
10	QPSK	25	25	22.82	22.62	22.69		
10	QPSK	50	0	22.76	22.68	22.53		
10	16QAM	1	0	23.12	23.00	22.85	23.5	1
10	16QAM	1	25	23.07	22.93	22.80		
10	16QAM	1	49	23.04	22.86	22.28		
10	16QAM	25	0	21.93	21.83	21.69	22.5	2
10	16QAM	25	12	21.94	21.84	21.74		
10	16QAM	25	25	21.86	21.82	21.75		
10	16QAM	50	0	21.91	21.79	21.62		
10	64QAM	1	0	22.00	22.02	21.77	22.5	2
10	64QAM	1	25	22.30	21.97	21.75		
10	64QAM	1	49	22.10	21.94	21.33		
10	64QAM	25	0	20.91	20.86	20.67	21.5	3
10	64QAM	25	12	20.94	20.83	20.80		
10	64QAM	25	25	20.90	20.82	20.73		
10	64QAM	50	0	20.91	20.86	20.68		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	23.83	23.66	23.51	24.5	0
5	QPSK	1	12	23.75	23.60	23.52		
5	QPSK	1	24	23.70	23.66	22.81		
5	QPSK	12	0	22.88	22.77	22.59	23.5	1
5	QPSK	12	7	22.83	22.77	22.76		
5	QPSK	12	13	22.79	22.68	22.66		
5	QPSK	25	0	22.81	22.68	22.55		
5	16QAM	1	0	23.05	22.98	22.84	23.5	1
5	16QAM	1	12	23.07	22.99	22.74		
5	16QAM	1	24	23.01	22.88	22.18		
5	16QAM	12	0	21.92	21.83	21.60	22.5	2
5	16QAM	12	7	21.98	21.88	21.74		
5	16QAM	12	13	21.87	21.82	21.69		
5	16QAM	25	0	21.92	21.87	21.58		
5	64QAM	1	0	21.97	22.01	21.77	22.5	2
5	64QAM	1	12	22.23	21.96	21.80		
5	64QAM	1	24	22.01	21.88	21.33		
5	64QAM	12	0	21.01	20.90	20.64	21.5	3
5	64QAM	12	7	20.99	20.90	20.76		
5	64QAM	12	13	20.95	20.82	20.77		
5	64QAM	25	0	20.90	20.80	20.69		
Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	23.80	23.66	23.57	24.5	0
3	QPSK	1	8	23.74	23.63	23.54		



3	QPSK	1	14	23.72	23.57	22.84		
3	QPSK	8	0	22.87	22.73	22.62	23.5	1
3	QPSK	8	4	22.87	22.72	22.67		
3	QPSK	8	7	22.76	22.62	22.71		
3	QPSK	15	0	22.81	22.70	22.60		
3	16QAM	1	0	23.07	23.03	22.83	23.5	1
3	16QAM	1	8	23.11	22.92	22.79		
3	16QAM	1	14	23.01	22.95	22.23		
3	16QAM	8	0	21.96	21.83	21.69	22.5	2
3	16QAM	8	4	21.93	21.91	21.72		
3	16QAM	8	7	21.93	21.86	21.71		
3	16QAM	15	0	21.95	21.86	21.59		
3	64QAM	1	0	21.98	21.98	21.80	22.5	2
3	64QAM	1	8	22.29	21.93	21.77		
3	64QAM	1	14	22.01	21.86	21.30		
3	64QAM	8	0	21.00	20.89	20.66	21.5	3
3	64QAM	8	4	20.95	20.86	20.77		
3	64QAM	8	7	20.86	20.79	20.79		
3	64QAM	15	0	20.93	20.81	20.70		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	23.81	23.66	23.52	24.5	0
1.4	QPSK	1	3	23.80	23.62	23.55		
1.4	QPSK	1	5	23.68	23.61	22.81		
1.4	QPSK	3	0	22.82	22.75	22.62		
1.4	QPSK	3	1	22.83	22.73	22.67		
1.4	QPSK	3	3	22.76	22.71	22.71		
1.4	QPSK	6	0	22.85	22.64	22.56	23.5	1
1.4	16QAM	1	0	23.03	23.04	22.84	23.5	1
1.4	16QAM	1	3	23.08	22.94	22.81		
1.4	16QAM	1	5	23.04	22.91	22.23		
1.4	16QAM	3	0	21.95	21.82	21.65		
1.4	16QAM	3	1	22.00	21.82	21.82		
1.4	16QAM	3	3	21.89	21.79	21.77		
1.4	16QAM	6	0	21.91	21.81	21.60	22.5	2
1.4	64QAM	1	0	22.03	21.93	21.82	22.5	2
1.4	64QAM	1	3	22.26	21.96	21.83		
1.4	64QAM	1	5	22.06	21.86	21.35		
1.4	64QAM	3	0	21.81	21.93	21.95		
1.4	64QAM	3	1	21.61	21.47	21.46		
1.4	64QAM	3	3	21.48	21.38	21.32		
1.4	64QAM	6	0	20.91	20.87	20.72	21.5	3



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	24.33	24.45	24.29	24.5	0
20	QPSK	1	49	23.94	23.83	23.89		
20	QPSK	1	99	23.83	23.78	23.83		
20	QPSK	50	0	23.05	22.93	22.91	23.5	1
20	QPSK	50	24	23.04	22.93	22.92		
20	QPSK	50	50	22.93	22.86	22.98		
20	QPSK	100	0	23.04	22.92	22.87	23.5	1
20	16QAM	1	0	23.27	23.25	23.19		
20	16QAM	1	49	23.23	23.18	23.23		
20	16QAM	1	99	23.15	23.13	23.12	22.5	2
20	16QAM	50	0	22.13	22.05	22.02		
20	16QAM	50	24	22.14	22.07	22.01		
20	16QAM	50	50	22.05	22.00	22.04	22.5	2
20	16QAM	100	0	22.13	22.02	21.99		
20	64QAM	1	0	22.27	22.22	22.19		
20	64QAM	1	49	22.21	22.16	22.21	22.5	2
20	64QAM	1	99	22.13	22.05	22.06		
20	64QAM	50	0	21.16	21.08	21.06		
20	64QAM	50	24	21.18	21.07	21.02	21.5	3
20	64QAM	50	50	21.04	21.02	21.06		
20	64QAM	100	0	21.15	21.04	20.98		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	24.06	23.97	23.85	24.5	0
15	QPSK	1	37	23.85	23.73	23.87		
15	QPSK	1	74	23.73	23.78	23.82		
15	QPSK	36	0	23.02	22.93	22.83	23.5	1
15	QPSK	36	20	23.01	22.91	22.82		
15	QPSK	36	39	22.85	22.76	22.92		
15	QPSK	75	0	23.02	22.87	22.79	23.5	1
15	16QAM	1	0	23.17	23.17	23.10		
15	16QAM	1	37	23.19	23.09	23.15		
15	16QAM	1	74	23.08	23.10	23.10	22.5	2
15	16QAM	36	0	22.12	22.02	22.00		
15	16QAM	36	20	22.06	22.02	21.94		
15	16QAM	36	39	22.00	21.91	21.95	22.5	2
15	16QAM	75	0	22.08	21.95	21.98		
15	64QAM	1	0	22.27	22.18	22.16		
15	64QAM	1	37	22.17	22.11	22.20	22.5	2
15	64QAM	1	74	22.08	22.01	21.98		
15	64QAM	36	0	21.11	21.07	21.03		
15	64QAM	36	20	21.09	21.03	20.92	21.5	3
15	64QAM	36	39	20.99	20.99	21.06		
15	64QAM	75	0	21.13	21.00	20.98		
Channel				20000	20175	20350	Tune-up limit	MPR



FCC SAR TEST REPORT

Report No. : FA010316

Frequency (MHz)				1715	1732.5	1750	(dBm)	(dB)
10	QPSK	1	0	24.06	23.91	23.75	24.5	0
10	QPSK	1	25	23.88	23.75	23.82		
10	QPSK	1	49	23.73	23.69	23.82		
10	QPSK	25	0	23.04	22.89	22.82	23.5	1
10	QPSK	25	12	22.97	22.87	22.90		
10	QPSK	25	25	22.91	22.81	22.96		
10	QPSK	50	0	22.95	22.83	22.81		
10	16QAM	1	0	23.26	23.17	23.13	23.5	1
10	16QAM	1	25	23.22	23.13	23.18		
10	16QAM	1	49	23.12	23.07	23.06		
10	16QAM	25	0	22.03	22.04	21.95	22.5	2
10	16QAM	25	12	22.11	22.03	21.97		
10	16QAM	25	25	22.03	21.97	22.00		
10	16QAM	50	0	22.13	22.00	21.95		
10	64QAM	1	0	22.25	22.21	22.13	22.5	2
10	64QAM	1	25	22.21	22.08	22.17		
10	64QAM	1	49	22.09	22.01	22.04		
10	64QAM	25	0	21.07	20.98	21.01	21.5	3
10	64QAM	25	12	21.10	21.05	21.02		
10	64QAM	25	25	20.98	20.93	20.96		
10	64QAM	50	0	21.10	21.00	20.98		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	24.05	23.98	23.78	24.5	0
5	QPSK	1	12	23.90	23.76	23.87		
5	QPSK	1	24	23.73	23.70	23.79		
5	QPSK	12	0	22.96	22.90	22.82	23.5	1
5	QPSK	12	7	23.02	22.90	22.85		
5	QPSK	12	13	22.93	22.79	22.94		
5	QPSK	25	0	23.01	22.87	22.85		
5	16QAM	1	0	23.17	23.17	23.18	23.5	1
5	16QAM	1	12	23.20	23.18	23.19		
5	16QAM	1	24	23.11	23.13	23.06		
5	16QAM	12	0	22.11	22.05	21.93	22.5	2
5	16QAM	12	7	22.08	22.07	21.98		
5	16QAM	12	13	21.96	21.97	21.97		
5	16QAM	25	0	22.11	21.93	21.91		
5	64QAM	1	0	22.21	22.16	22.17	22.5	2
5	64QAM	1	12	22.20	22.13	22.13		
5	64QAM	1	24	22.08	21.95	21.98		
5	64QAM	12	0	21.06	21.02	20.96	21.5	3
5	64QAM	12	7	21.14	21.04	21.02		
5	64QAM	12	13	21.02	20.97	21.01		
5	64QAM	25	0	21.08	20.99	20.98		
Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	23.99	23.93	23.76	24.5	0
3	QPSK	1	8	23.92	23.80	23.89		
3	QPSK	1	14	23.75	23.75	23.80		



3	QPSK	8	0	22.99	22.87	22.91	23.5	1
3	QPSK	8	4	23.02	22.88	22.88		
3	QPSK	8	7	22.92	22.81	22.95		
3	QPSK	15	0	22.98	22.92	22.78	23.5	1
3	16QAM	1	0	23.18	23.18	23.10		
3	16QAM	1	8	23.19	23.10	23.21		
3	16QAM	1	14	23.14	23.05	23.05	22.5	2
3	16QAM	8	0	22.12	21.95	21.97		
3	16QAM	8	4	22.04	21.98	21.92		
3	16QAM	8	7	22.05	21.95	21.94		
3	16QAM	15	0	22.10	22.00	21.91	22.5	2
3	64QAM	1	0	22.26	22.21	22.18		
3	64QAM	1	8	22.18	22.14	22.18		
3	64QAM	1	14	22.08	21.99	22.01	21.5	3
3	64QAM	8	0	21.12	21.06	20.98		
3	64QAM	8	4	21.10	20.99	21.00		
3	64QAM	8	7	21.01	20.96	21.03		
3	64QAM	15	0	21.14	20.94	20.97	Tune-up limit (dBm)	MPR (dB)
Channel				19957	20175	20393		
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	23.97	23.91	23.84	24.5	0
1.4	QPSK	1	3	23.90	23.75	23.89		
1.4	QPSK	1	5	23.74	23.70	23.76		
1.4	QPSK	3	0	22.99	22.84	22.91		
1.4	QPSK	3	1	22.94	22.88	22.87		
1.4	QPSK	3	3	22.88	22.82	22.94	23.5	1
1.4	QPSK	6	0	22.95	22.85	22.82	23.5	1
1.4	16QAM	1	0	23.22	23.23	23.19		
1.4	16QAM	1	3	23.19	23.12	23.13		
1.4	16QAM	1	5	23.15	23.08	23.12		
1.4	16QAM	3	0	22.12	22.03	21.94		
1.4	16QAM	3	1	22.12	22.03	21.99		
1.4	16QAM	3	3	21.95	21.92	22.01	22.5	2
1.4	16QAM	6	0	22.07	21.94	21.98	22.5	2
1.4	64QAM	1	0	22.26	22.13	22.13		
1.4	64QAM	1	3	22.16	22.10	22.19		
1.4	64QAM	1	5	22.12	21.97	21.99		
1.4	64QAM	3	0	21.85	21.77	21.80		
1.4	64QAM	3	1	21.86	21.78	21.75		
1.4	64QAM	3	3	21.78	21.77	21.74		
1.4	64QAM	6	0	21.12	21.01	20.96	21.5	3



<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	24.90	24.81	24.72	25	0
10	QPSK	1	25	24.86	24.79	24.60		
10	QPSK	1	49	24.81	24.74	24.53		
10	QPSK	25	0	23.99	23.90	23.78	24	1
10	QPSK	25	12	23.97	23.89	23.70		
10	QPSK	25	25	23.96	23.83	23.63		
10	QPSK	50	0	23.93	23.83	23.79	24	1
10	16QAM	1	0	23.91	23.96	23.81		
10	16QAM	1	25	23.87	23.81	23.88		
10	16QAM	1	49	23.92	23.86	23.84	23	2
10	16QAM	25	0	22.92	22.94	22.86		
10	16QAM	25	12	22.86	22.95	22.79		
10	16QAM	25	25	22.84	22.93	22.71	23	2
10	16QAM	50	0	22.82	22.94	22.88		
10	64QAM	1	0	22.91	22.86	22.99		
10	64QAM	1	25	22.83	22.85	22.85	23	2
10	64QAM	1	49	22.87	23.00	22.79		
10	64QAM	25	0	21.86	21.96	21.87		
10	64QAM	25	12	21.85	21.99	21.79	22	3
10	64QAM	25	25	21.85	21.94	21.71		
10	64QAM	50	0	21.82	21.94	21.89		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	24.88	24.77	24.65	25	0
5	QPSK	1	12	24.81	24.71	24.53		
5	QPSK	1	24	24.78	24.66	24.51		
5	QPSK	12	0	23.95	23.79	23.70	24	1
5	QPSK	12	7	23.94	23.83	23.67		
5	QPSK	12	13	23.89	23.77	23.55		
5	QPSK	25	0	23.83	23.79	23.72	24	1
5	16QAM	1	0	23.88	23.89	23.79		
5	16QAM	1	12	23.78	23.73	23.87		
5	16QAM	1	24	23.89	23.78	23.84	23	2
5	16QAM	12	0	22.86	22.92	22.83		
5	16QAM	12	7	22.76	22.91	22.79		
5	16QAM	12	13	22.82	22.85	22.70	23	2
5	16QAM	25	0	22.74	22.94	22.84		
5	64QAM	1	0	22.85	22.78	22.89		
5	64QAM	1	12	22.74	22.79	22.80	23	2
5	64QAM	1	24	22.77	22.94	22.74		
5	64QAM	12	0	21.82	21.86	21.77		
5	64QAM	12	7	21.79	21.99	21.77	22	3
5	64QAM	12	13	21.80	21.87	21.65		
5	64QAM	25	0	21.74	21.92	21.79		
Channel				20415	20525	20635	Tune-up limit	MPR



Frequency (MHz)				825.5	836.5	847.5	(dBm)	(dB)
3	QPSK	1	0	24.88	24.77	24.68	25	0
3	QPSK	1	8	24.81	24.72	24.57		
3	QPSK	1	14	24.74	24.68	24.46		
3	QPSK	8	0	23.90	23.78	23.72	24	1
3	QPSK	8	4	23.92	23.81	23.67		
3	QPSK	8	7	23.89	23.74	23.58		
3	QPSK	15	0	23.90	23.78	23.75		
3	16QAM	1	0	23.91	23.90	23.72	24	1
3	16QAM	1	8	23.85	23.71	23.81		
3	16QAM	1	14	23.82	23.80	23.80		
3	16QAM	8	0	22.89	22.87	22.76	23	2
3	16QAM	8	4	22.80	22.88	22.79		
3	16QAM	8	7	22.82	22.93	22.66		
3	16QAM	15	0	22.81	22.90	22.86		
3	64QAM	1	0	22.81	22.78	22.94	23	2
3	64QAM	1	8	22.78	22.79	22.83		
3	64QAM	1	14	22.82	23.00	22.79		
3	64QAM	8	0	21.78	21.88	21.82	22	3
3	64QAM	8	4	21.85	21.93	21.73		
3	64QAM	8	7	21.79	21.87	21.70		
3	64QAM	8	7	21.79	21.87	21.70		
3	64QAM	15	0	21.72	21.86	21.80		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	24.85	24.73	24.67	25	0
1.4	QPSK	1	3	24.81	24.78	24.60		
1.4	QPSK	1	5	24.77	24.70	24.44		
1.4	QPSK	3	0	23.93	23.77	23.73		
1.4	QPSK	3	1	23.94	23.79	23.64		
1.4	QPSK	3	3	23.87	23.77	23.61		
1.4	QPSK	6	0	23.89	23.83	23.78	24	1
1.4	16QAM	1	0	23.83	23.89	23.72	24	1
1.4	16QAM	1	3	23.86	23.75	23.85		
1.4	16QAM	1	5	23.87	23.80	23.78		
1.4	16QAM	3	0	22.83	22.92	22.77		
1.4	16QAM	3	1	22.78	22.85	22.77		
1.4	16QAM	3	3	22.81	22.90	22.62		
1.4	16QAM	6	0	22.79	22.92	22.84	23	2
1.4	64QAM	1	0	22.83	22.85	22.91	23	2
1.4	64QAM	1	3	22.78	22.75	22.79		
1.4	64QAM	1	5	22.79	22.96	22.76		
1.4	64QAM	3	0	22.60	22.66	22.56		
1.4	64QAM	3	1	22.54	22.69	22.50		
1.4	64QAM	3	3	22.55	22.65	22.47		
1.4	64QAM	6	0	21.81	21.92	21.89		



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	22.83	23.27	23.38	24	0
20	QPSK	1	49	23.08	23.45	23.40		
20	QPSK	1	99	23.65	23.69	23.66		
20	QPSK	50	0	22.11	22.55	22.45	23	1
20	QPSK	50	24	22.32	22.56	22.55		
20	QPSK	50	50	22.31	22.54	22.54		
20	QPSK	100	0	22.17	22.56	22.49	23	1
20	16QAM	1	0	22.12	22.55	22.69		
20	16QAM	1	49	22.43	22.74	22.69		
20	16QAM	1	99	22.67	22.92	22.81	22	2
20	16QAM	50	0	21.22	21.63	21.58		
20	16QAM	50	24	21.26	21.66	21.57		
20	16QAM	50	50	21.42	21.67	21.61	22	2
20	16QAM	100	0	21.26	21.65	21.55		
20	64QAM	1	0	21.08	21.51	21.65		
20	64QAM	1	49	21.40	21.69	21.63	22	2
20	64QAM	1	99	21.67	21.84	21.79		
20	64QAM	50	0	20.22	20.67	20.58		
20	64QAM	50	24	20.29	20.65	20.62	21	3
20	64QAM	50	50	20.41	20.69	20.65		
20	64QAM	100	0	20.26	20.64	20.61		
Channel				20825	21100	21375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	22.82	23.22	23.37	24	0
15	QPSK	1	37	23.06	23.41	23.40		
15	QPSK	1	74	23.36	23.60	23.47		
15	QPSK	36	0	22.01	22.53	22.42	23	1
15	QPSK	36	20	22.08	22.48	22.43		
15	QPSK	36	39	22.28	22.52	22.49		
15	QPSK	75	0	22.17	22.51	22.46	23	1
15	16QAM	1	0	22.05	22.49	22.68		
15	16QAM	1	37	22.43	22.65	22.69		
15	16QAM	1	74	22.64	22.89	22.76	22	2
15	16QAM	36	0	21.15	21.57	21.49		
15	16QAM	36	20	21.24	21.60	21.49		
15	16QAM	36	39	21.37	21.67	21.58	22	2
15	16QAM	75	0	21.26	21.65	21.49		
15	64QAM	1	0	21.07	21.42	21.59		
15	64QAM	1	37	21.32	21.61	21.57	22	2
15	64QAM	1	74	21.60	21.74	21.75		
15	64QAM	36	0	20.18	20.58	20.57		
15	64QAM	36	20	20.20	20.57	20.61	21	3
15	64QAM	36	39	20.33	20.60	20.59		
15	64QAM	75	0	20.20	20.59	20.57		
Channel				20800	21100	21400	Tune-up limit	MPR



Frequency (MHz)				2505	2535	2565	(dBm)	(dB)
10	QPSK	1	0	22.78	23.19	23.31	24	0
10	QPSK	1	25	23.06	23.44	23.36		
10	QPSK	1	49	23.32	23.60	23.53		
10	QPSK	25	0	22.06	22.52	22.38	23	1
10	QPSK	25	12	22.09	22.52	22.41		
10	QPSK	25	25	22.22	22.50	22.44		
10	QPSK	50	0	22.12	22.49	22.45		
10	16QAM	1	0	22.06	22.52	22.62	23	1
10	16QAM	1	25	22.33	22.71	22.61		
10	16QAM	1	49	22.64	22.84	22.75		
10	16QAM	25	0	21.20	21.62	21.57	22	2
10	16QAM	25	12	21.22	21.66	21.51		
10	16QAM	25	25	21.40	21.67	21.53		
10	16QAM	50	0	21.18	21.60	21.48		
10	64QAM	1	0	20.99	21.47	21.65	22	2
10	64QAM	1	25	21.31	21.61	21.61		
10	64QAM	1	49	21.62	21.81	21.78		
10	64QAM	25	0	20.20	20.62	20.54	21	3
10	64QAM	25	12	20.27	20.57	20.53		
10	64QAM	25	25	20.41	20.65	20.63		
10	64QAM	50	0	20.19	20.54	20.53		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	22.80	23.19	23.32	24	0
5	QPSK	1	12	23.06	23.39	23.39		
5	QPSK	1	24	23.28	23.56	23.50		
5	QPSK	12	0	22.09	22.54	22.45	23	1
5	QPSK	12	7	22.11	22.47	22.47		
5	QPSK	12	13	22.24	22.54	22.48		
5	QPSK	25	0	22.16	22.53	22.48		
5	16QAM	1	0	22.06	22.55	22.68	23	1
5	16QAM	1	12	22.43	22.71	22.66		
5	16QAM	1	24	22.61	22.88	22.77		
5	16QAM	12	0	21.19	21.55	21.48	22	2
5	16QAM	12	7	21.21	21.57	21.51		
5	16QAM	12	13	21.37	21.63	21.51		
5	16QAM	25	0	21.26	21.63	21.45		
5	64QAM	1	0	21.03	21.41	21.56	22	2
5	64QAM	1	12	21.34	21.67	21.58		
5	64QAM	1	24	21.67	21.84	21.72		
5	64QAM	12	0	20.22	20.61	20.56	21	3
5	64QAM	12	7	20.26	20.62	20.55		
5	64QAM	12	13	20.32	20.62	20.61		
5	64QAM	25	0	20.21	20.62	20.54		



Hotspot Power Mode

<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	23.87	23.75	23.59	24	0
20	QPSK	1	49	23.82	23.70	23.62		
20	QPSK	1	99	23.76	23.66	22.87		
20	QPSK	50	0	22.91	22.77	22.63	23.5	0.5
20	QPSK	50	24	22.90	22.77	22.77		
20	QPSK	50	50	22.85	22.72	22.72		
20	QPSK	100	0	22.86	22.74	22.61	23.5	0.5
20	16QAM	1	0	23.13	23.04	22.88		
20	16QAM	1	49	23.13	23.02	22.83		
20	16QAM	1	99	23.04	22.96	22.28	22.5	1.5
20	16QAM	50	0	22.02	21.89	21.69		
20	16QAM	50	24	22.01	21.92	21.82		
20	16QAM	50	50	21.95	21.87	21.79	22.5	1.5
20	16QAM	100	0	21.97	21.88	21.67		
20	64QAM	1	0	22.06	22.03	21.82		
20	64QAM	1	49	22.30	22.01	21.85	22.5	1.5
20	64QAM	1	99	22.10	21.96	21.39		
20	64QAM	50	0	21.01	20.90	20.73		
20	64QAM	50	24	21.01	20.91	20.86	21.5	2.5
20	64QAM	50	50	20.95	20.87	20.82		
20	64QAM	100	0	20.99	20.90	20.74		
Channel				18675	18900	19125		
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	23.86	23.66	23.53	24	0
15	QPSK	1	37	23.74	23.62	23.55		
15	QPSK	1	74	23.73	23.59	22.80		
15	QPSK	36	0	22.90	22.75	22.55	23.5	0.5
15	QPSK	36	20	22.88	22.68	22.71		
15	QPSK	36	39	22.78	22.65	22.69		
15	QPSK	75	0	22.77	22.69	22.59	23.5	0.5
15	16QAM	1	0	23.05	23.00	22.86		
15	16QAM	1	37	23.10	22.92	22.77		
15	16QAM	1	74	23.00	22.96	22.25	22.5	1.5
15	16QAM	36	0	22.02	21.89	21.60		
15	16QAM	36	20	21.91	21.87	21.72		
15	16QAM	36	39	21.93	21.87	21.70	22.5	1.5
15	16QAM	75	0	21.88	21.78	21.67		
15	64QAM	1	0	22.04	22.02	21.80		
15	64QAM	1	37	22.21	22.01	21.84	22.5	1.5
15	64QAM	1	74	22.00	21.93	21.33		
15	64QAM	36	0	20.92	20.90	20.63		
15	64QAM	36	20	21.01	20.82	20.83	21.5	2.5
15	64QAM	36	39	20.89	20.82	20.82		
15	64QAM	75	0	20.93	20.83	20.72		



Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	23.85	23.66	23.58	24	0
10	QPSK	1	25	23.75	23.67	23.58		
10	QPSK	1	49	23.71	23.57	22.87		
10	QPSK	25	0	22.87	22.67	22.63	23.5	0.5
10	QPSK	25	12	22.89	22.77	22.75		
10	QPSK	25	25	22.82	22.62	22.69		
10	QPSK	50	0	22.76	22.68	22.53		
10	16QAM	1	0	23.12	23.00	22.85	23.5	0.5
10	16QAM	1	25	23.07	22.93	22.80		
10	16QAM	1	49	23.04	22.86	22.28		
10	16QAM	25	0	21.93	21.83	21.69	22.5	1.5
10	16QAM	25	12	21.94	21.84	21.74		
10	16QAM	25	25	21.86	21.82	21.75		
10	16QAM	50	0	21.91	21.79	21.62		
10	64QAM	1	0	22.00	22.02	21.77	22.5	1.5
10	64QAM	1	25	22.30	21.97	21.75		
10	64QAM	1	49	22.10	21.94	21.33		
10	64QAM	25	0	20.91	20.86	20.67	21.5	2.5
10	64QAM	25	12	20.94	20.83	20.80		
10	64QAM	25	25	20.90	20.82	20.73		
10	64QAM	50	0	20.91	20.86	20.68		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	23.83	23.66	23.51	24	0
5	QPSK	1	12	23.75	23.60	23.52		
5	QPSK	1	24	23.70	23.66	22.81		
5	QPSK	12	0	22.88	22.77	22.59	23.5	0.5
5	QPSK	12	7	22.83	22.77	22.76		
5	QPSK	12	13	22.79	22.68	22.66		
5	QPSK	25	0	22.81	22.68	22.55		
5	16QAM	1	0	23.05	22.98	22.84	23.5	0.5
5	16QAM	1	12	23.07	22.99	22.74		
5	16QAM	1	24	23.01	22.88	22.18		
5	16QAM	12	0	21.92	21.83	21.60	22.5	1.5
5	16QAM	12	7	21.98	21.88	21.74		
5	16QAM	12	13	21.87	21.82	21.69		
5	16QAM	25	0	21.92	21.87	21.58		
5	64QAM	1	0	21.97	22.01	21.77	22.5	1.5
5	64QAM	1	12	22.23	21.96	21.80		
5	64QAM	1	24	22.01	21.88	21.33		
5	64QAM	12	0	21.01	20.90	20.64	21.5	2.5
5	64QAM	12	7	20.99	20.90	20.76		
5	64QAM	12	13	20.95	20.82	20.77		
5	64QAM	25	0	20.90	20.80	20.69		
Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	23.80	23.66	23.57	24	0
3	QPSK	1	8	23.74	23.63	23.54		



3	QPSK	1	14	23.72	23.57	22.84		
3	QPSK	8	0	22.87	22.73	22.62	23.5	0.5
3	QPSK	8	4	22.87	22.72	22.67		
3	QPSK	8	7	22.76	22.62	22.71		
3	QPSK	15	0	22.81	22.70	22.60		
3	16QAM	1	0	23.07	23.03	22.83	23.5	0.5
3	16QAM	1	8	23.11	22.92	22.79		
3	16QAM	1	14	23.01	22.95	22.23		
3	16QAM	8	0	21.96	21.83	21.69	22.5	1.5
3	16QAM	8	4	21.93	21.91	21.72		
3	16QAM	8	7	21.93	21.86	21.71		
3	16QAM	15	0	21.95	21.86	21.59		
3	64QAM	1	0	21.98	21.98	21.80	22.5	1.5
3	64QAM	1	8	22.29	21.93	21.77		
3	64QAM	1	14	22.01	21.86	21.30		
3	64QAM	8	0	21.00	20.89	20.66	21.5	2.5
3	64QAM	8	4	20.95	20.86	20.77		
3	64QAM	8	7	20.86	20.79	20.79		
3	64QAM	15	0	20.93	20.81	20.70		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	23.81	23.66	23.52	24	0
1.4	QPSK	1	3	23.80	23.62	23.55		
1.4	QPSK	1	5	23.68	23.61	22.81		
1.4	QPSK	3	0	22.82	22.75	22.62		
1.4	QPSK	3	1	22.83	22.73	22.67		
1.4	QPSK	3	3	22.76	22.71	22.71		
1.4	QPSK	6	0	22.85	22.64	22.56	23.5	0.5
1.4	16QAM	1	0	23.03	23.04	22.84	23.5	0.5
1.4	16QAM	1	3	23.08	22.94	22.81		
1.4	16QAM	1	5	23.04	22.91	22.23		
1.4	16QAM	3	0	21.95	21.82	21.65		
1.4	16QAM	3	1	22.00	21.82	21.82		
1.4	16QAM	3	3	21.89	21.79	21.77		
1.4	16QAM	6	0	21.91	21.81	21.60	22.5	1.5
1.4	64QAM	1	0	22.03	21.93	21.82	22.5	1.5
1.4	64QAM	1	3	22.26	21.96	21.83		
1.4	64QAM	1	5	22.06	21.86	21.35		
1.4	64QAM	3	0	21.81	21.93	21.95		
1.4	64QAM	3	1	21.61	21.47	21.46		
1.4	64QAM	3	3	21.48	21.38	21.32		
1.4	64QAM	6	0	20.91	20.87	20.72	21.5	2.5



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	22.84	22.74	22.64	23	0
20	QPSK	1	49	22.72	22.62	22.66		
20	QPSK	1	99	22.59	22.55	22.59		
20	QPSK	50	0	21.77	21.61	21.61	22.5	0.5
20	QPSK	50	24	21.77	21.60	21.62		
20	QPSK	50	50	21.65	21.59	21.62		
20	QPSK	100	0	21.75	21.63	21.59	22.5	0.5
20	16QAM	1	0	22.19	22.11	22.07		
20	16QAM	1	49	22.10	22.04	22.09		
20	16QAM	1	99	22.03	21.96	21.93	21.5	1.5
20	16QAM	50	0	20.90	20.78	20.74		
20	16QAM	50	24	20.86	20.77	20.74		
20	16QAM	50	50	20.75	20.71	20.76	21.5	1.5
20	16QAM	100	0	20.85	20.73	20.71		
20	64QAM	1	0	21.15	21.05	21.00		
20	64QAM	1	49	21.01	20.95	21.03	21.5	1.5
20	64QAM	1	99	20.96	20.88	20.87		
20	64QAM	50	0	19.87	19.77	19.74		
20	64QAM	50	24	19.85	19.78	19.77	21	2
20	64QAM	50	50	19.77	19.73	19.77		
20	64QAM	100	0	19.87	19.79	19.71		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	22.83	22.65	22.59	23	0
15	QPSK	1	37	22.69	22.57	22.64		
15	QPSK	1	74	22.67	22.53	22.58		
15	QPSK	36	0	21.78	21.63	21.61	22.5	0.5
15	QPSK	36	20	21.80	21.66	21.72		
15	QPSK	36	39	21.75	21.61	21.66		
15	QPSK	75	0	21.75	21.63	21.57	22.5	0.5
15	16QAM	1	0	22.21	22.04	22.03		
15	16QAM	1	37	22.08	22.02	22.05		
15	16QAM	1	74	22.07	21.98	21.94	21.5	1.5
15	16QAM	36	0	20.87	20.79	20.77		
15	16QAM	36	20	20.87	20.82	20.83		
15	16QAM	36	39	20.85	20.77	20.77	21.5	1.5
15	16QAM	75	0	20.86	20.77	20.70		
15	64QAM	1	0	21.15	20.94	20.97		
15	64QAM	1	37	21.02	20.95	20.98	21.5	1.5
15	64QAM	1	74	20.98	20.89	20.88		
15	64QAM	36	0	19.89	19.79	19.78		
15	64QAM	36	20	19.88	19.81	19.85	21	2
15	64QAM	36	39	19.89	19.78	19.79		
15	64QAM	75	0	19.86	19.75	19.70		
Channel				20000	20175	20350	Tune-up limit	MPR



Frequency (MHz)				1715	1732.5	1750	(dBm)	(dB)
10	QPSK	1	0	22.82	22.61	22.68	23	0
10	QPSK	1	25	22.83	22.58	22.66		
10	QPSK	1	49	22.70	22.53	22.60		
10	QPSK	25	0	21.84	21.60	21.69	22.5	0.5
10	QPSK	25	12	21.77	21.61	21.67		
10	QPSK	25	25	21.74	21.59	21.68		
10	QPSK	50	0	21.73	21.60	21.68		
10	16QAM	1	0	22.20	22.04	22.07	22.5	0.5
10	16QAM	1	25	22.20	22.02	22.05		
10	16QAM	1	49	22.06	22.00	21.98		
10	16QAM	25	0	20.97	20.77	20.81	21.5	1.5
10	16QAM	25	12	20.87	20.75	20.81		
10	16QAM	25	25	20.84	20.72	20.74		
10	16QAM	50	0	20.85	20.76	20.78		
10	64QAM	1	0	21.15	20.95	21.02	21.5	1.5
10	64QAM	1	25	21.13	20.96	20.96		
10	64QAM	1	49	20.98	20.91	20.93		
10	64QAM	25	0	20.01	19.77	19.83	21	2
10	64QAM	25	12	19.87	19.76	19.83		
10	64QAM	25	25	19.86	19.73	19.73		
10	64QAM	50	0	19.89	19.74	19.77		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	22.80	22.65	22.49	23	0
5	QPSK	1	12	22.62	22.50	22.57		
5	QPSK	1	24	22.65	22.47	22.50		
5	QPSK	12	0	21.77	21.54	21.55	22.5	0.5
5	QPSK	12	7	21.77	21.60	21.65		
5	QPSK	12	13	21.74	21.55	21.58		
5	QPSK	25	0	21.65	21.53	21.50		
5	16QAM	1	0	22.19	21.99	21.93	22.5	0.5
5	16QAM	1	12	22.07	21.98	21.96		
5	16QAM	1	24	22.05	21.95	21.92		
5	16QAM	12	0	20.87	20.72	20.77	21.5	1.5
5	16QAM	12	7	20.80	20.82	20.80		
5	16QAM	12	13	20.82	20.76	20.73		
5	16QAM	25	0	20.84	20.72	20.61		
5	64QAM	1	0	21.05	20.90	20.95	21.5	1.5
5	64QAM	1	12	21.02	20.90	20.89		
5	64QAM	1	24	20.98	20.80	20.87		
5	64QAM	12	0	19.79	19.77	19.68	21	2
5	64QAM	12	7	19.80	19.73	19.85		
5	64QAM	12	13	19.81	19.71	19.70		
5	64QAM	25	0	19.83	19.71	19.66		
Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	22.81	22.65	22.49	23	0
3	QPSK	1	8	22.67	22.49	22.62		
3	QPSK	1	14	22.63	22.45	22.54		



3	QPSK	8	0	21.68	21.60	21.60	22.5	0.5
3	QPSK	8	4	21.72	21.62	21.62		
3	QPSK	8	7	21.74	21.53	21.62		
3	QPSK	15	0	21.74	21.57	21.50	22.5	0.5
3	16QAM	1	0	22.19	22.03	22.01		
3	16QAM	1	8	22.03	21.98	21.97		
3	16QAM	1	14	22.05	21.91	21.90	21.5	1.5
3	16QAM	8	0	20.84	20.75	20.74		
3	16QAM	8	4	20.80	20.72	20.74		
3	16QAM	8	7	20.82	20.69	20.67	21.5	1.5
3	16QAM	15	0	20.82	20.77	20.60		
3	64QAM	1	0	21.05	20.94	20.97		
3	64QAM	1	8	20.97	20.95	20.97	21.5	1.5
3	64QAM	1	14	20.92	20.81	20.87		
3	64QAM	8	0	19.79	19.76	19.74		
3	64QAM	8	4	19.87	19.77	19.75	21	2
3	64QAM	8	7	19.88	19.73	19.69		
3	64QAM	15	0	19.81	19.69	19.62		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	22.83	22.63	22.50	23	0
1.4	QPSK	1	3	22.62	22.51	22.58		
1.4	QPSK	1	5	22.57	22.50	22.52		
1.4	QPSK	3	0	21.74	21.61	21.56		
1.4	QPSK	3	1	21.78	21.60	21.63		
1.4	QPSK	3	3	21.71	21.58	21.59	22.5	0.5
1.4	QPSK	6	0	21.74	21.57	21.51		
1.4	16QAM	1	0	22.12	21.99	21.98	22.5	0.5
1.4	16QAM	1	3	21.98	21.97	22.00		
1.4	16QAM	1	5	22.01	21.98	21.85		
1.4	16QAM	3	0	21.77	21.79	21.70		
1.4	16QAM	3	1	21.86	21.80	21.79		
1.4	16QAM	3	3	21.85	21.77	21.77	21.5	1.5
1.4	16QAM	6	0	20.82	20.76	20.69		
1.4	64QAM	1	0	21.05	20.84	20.96	21.5	1.5
1.4	64QAM	1	3	20.95	20.89	20.98		
1.4	64QAM	1	5	20.88	20.87	20.84		
1.4	64QAM	3	0	20.89	20.77	20.76		
1.4	64QAM	3	1	20.80	20.74	20.75		
1.4	64QAM	3	3	20.79	20.74	20.72	21	2
1.4	64QAM	6	0	19.84	19.68	19.62		



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	22.58	22.98	23.24	23.5	0
20	QPSK	1	49	22.83	23.18	23.24		
20	QPSK	1	99	23.13	23.35	23.43		
20	QPSK	50	0	21.90	22.29	22.30	23	0.5
20	QPSK	50	24	21.89	22.22	22.19		
20	QPSK	50	50	22.02	22.28	22.29		
20	QPSK	100	0	21.91	22.29	22.30	23	0.5
20	16QAM	1	0	21.90	22.31	22.46		
20	16QAM	1	49	22.20	22.51	22.46		
20	16QAM	1	99	22.46	22.67	22.66	22	1.5
20	16QAM	50	0	20.97	21.34	21.27		
20	16QAM	50	24	20.98	21.38	21.33		
20	16QAM	50	50	21.14	21.38	21.36	21	2.5
20	16QAM	100	0	20.99	21.35	21.31		
20	64QAM	1	0	20.86	21.26	21.42		
20	64QAM	1	49	21.13	21.50	21.40	22	1.5
20	64QAM	1	99	21.39	21.63	21.58		
20	64QAM	50	0	19.96	20.36	20.31		
20	64QAM	50	24	20.02	20.40	20.35	21	2.5
20	64QAM	50	50	20.15	20.39	20.35		
20	64QAM	100	0	20.02	20.39	20.31		
Channel				20825	21100	21375		
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	22.59	23.13	23.12	23.5	0
15	QPSK	1	37	22.73	23.20	23.24		
15	QPSK	1	74	23.03	23.37	23.33		
15	QPSK	36	0	21.71	22.26	22.15	23	0.5
15	QPSK	36	20	21.91	22.27	22.22		
15	QPSK	36	39	21.99	22.24	22.29		
15	QPSK	75	0	21.84	22.24	22.16	23	0.5
15	16QAM	1	0	21.91	22.43	22.46		
15	16QAM	1	37	22.09	22.51	22.55		
15	16QAM	1	74	22.37	22.68	22.62	22	1.5
15	16QAM	36	0	20.86	21.32	21.28		
15	16QAM	36	20	21.00	21.39	21.29		
15	16QAM	36	39	21.11	21.35	21.43	22	1.5
15	16QAM	75	0	20.99	21.33	21.29		
15	64QAM	1	0	20.85	21.39	21.42		
15	64QAM	1	37	21.02	21.46	21.50	22	1.5
15	64QAM	1	74	21.33	21.66	21.58		
15	64QAM	36	0	19.89	20.38	20.32		
15	64QAM	36	20	20.03	20.44	20.33	21	2.5
15	64QAM	36	39	20.16	20.42	20.49		
15	64QAM	75	0	19.99	20.37	20.30		
Channel				20800	21100	21400	Tune-up limit	MPR



Frequency (MHz)				2505	2535	2565	(dBm)	(dB)
10	QPSK	1	0	22.56	23.08	23.08	23.5	0
10	QPSK	1	25	22.67	23.16	23.20		
10	QPSK	1	49	22.88	23.22	23.28		
10	QPSK	25	0	21.73	22.21	22.10	23	0.5
10	QPSK	25	12	21.75	22.24	22.24		
10	QPSK	25	25	21.83	22.22	22.30		
10	QPSK	50	0	21.72	22.23	22.12		
10	16QAM	1	0	21.89	22.40	22.42	23	0.5
10	16QAM	1	25	22.01	22.49	22.51		
10	16QAM	1	49	22.25	22.54	22.53		
10	16QAM	25	0	20.83	21.30	21.23	22	1.5
10	16QAM	25	12	20.85	21.35	21.38		
10	16QAM	25	25	20.99	21.34	21.36		
10	16QAM	50	0	20.84	21.32	21.23		
10	64QAM	1	0	20.83	21.37	21.35	22	1.5
10	64QAM	1	25	20.97	21.45	21.49		
10	64QAM	1	49	21.18	21.51	21.52		
10	64QAM	25	0	19.84	20.32	20.24	21	2.5
10	64QAM	25	12	19.86	20.35	20.38		
10	64QAM	25	25	19.99	20.36	20.42		
10	64QAM	50	0	19.86	20.36	20.28		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	22.55	23.03	23.01	23.5	0
5	QPSK	1	12	22.67	23.15	23.15		
5	QPSK	1	24	22.88	23.12	23.22		
5	QPSK	12	0	21.65	22.16	22.08	23	0.5
5	QPSK	12	7	21.74	22.24	22.18		
5	QPSK	12	13	21.82	22.19	22.30		
5	QPSK	25	0	21.62	22.17	22.06		
5	16QAM	1	0	21.88	22.34	22.37	23	0.5
5	16QAM	1	12	21.92	22.49	22.43		
5	16QAM	1	24	22.25	22.49	22.48		
5	16QAM	12	0	20.82	21.21	21.14	22	1.5
5	16QAM	12	7	20.83	21.32	21.38		
5	16QAM	12	13	20.92	21.32	21.35		
5	16QAM	25	0	20.74	21.26	21.13		
5	64QAM	1	0	20.79	21.29	21.28	22	1.5
5	64QAM	1	12	20.91	21.44	21.45		
5	64QAM	1	24	21.09	21.50	21.48		
5	64QAM	12	0	19.81	20.30	20.14	21	2.5
5	64QAM	12	7	19.77	20.31	20.31		
5	64QAM	12	13	19.97	20.31	20.34		
5	64QAM	25	0	19.76	20.33	20.23		

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- a. 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- b. “special subframe S” contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- c. Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	6592 · Ts	2192 · Ts	2560 · Ts	7680 · Ts	2192 · Ts	2560 · Ts
1	19760 · Ts			20480 · Ts		
2	21952 · Ts			23040 · Ts		
3	24144 · Ts			25600 · Ts		
4	26336 · Ts			7680 · Ts	4384 · Ts	5120 · Ts
5	6592 · Ts	4384 · Ts	5120 · Ts	20480 · Ts		
6	19760 · Ts			23040 · Ts		
7	21952 · Ts			12800 · Ts		
8	24144 · Ts			-	-	-
9	13168 · Ts			-	-	-

Special subframe (30720·T_s): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720·T_s): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

- i. Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- ii. special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- iii. for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.167)/5 = 63.3\%$
- iv. for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.143)/5 = 62.9\%$
- v. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.



<LTE Band 38>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				37850	38000	38150		
Frequency (MHz)				2580	2595	2610		
20	QPSK	1	0	23.95	23.99	23.77	24.5	0
20	QPSK	1	49	23.85	23.83	23.69		
20	QPSK	1	99	23.55	23.45	23.54		
20	QPSK	50	0	22.93	22.99	22.81	23.5	1
20	QPSK	50	24	23.05	22.91	22.76		
20	QPSK	50	50	23.08	22.85	22.74		
20	QPSK	100	0	23.06	22.93	22.78	23.5	1
20	16QAM	1	0	23.05	23.10	22.88		
20	16QAM	1	49	22.95	22.93	22.76		
20	16QAM	1	99	22.75	22.65	22.74	22.5	2
20	16QAM	50	0	22.07	22.08	21.93		
20	16QAM	50	24	22.13	21.99	21.88		
20	16QAM	50	50	22.16	22.01	21.87	22.5	2
20	16QAM	100	0	22.15	22.06	21.85		
20	64QAM	1	0	21.80	21.86	21.65		
20	64QAM	1	49	21.74	21.66	21.59	22.5	2
20	64QAM	1	99	21.59	21.48	21.51		
20	64QAM	50	0	21.02	21.10	20.91		
20	64QAM	50	24	21.16	21.06	20.90	21.5	3
20	64QAM	50	50	21.16	20.94	20.85		
20	64QAM	100	0	21.15	21.05	20.88		
Channel				37825	38000	38175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2577.5	2595	2612.5		
15	QPSK	1	0	23.90	23.96	23.77	24.5	0
15	QPSK	1	37	23.80	23.79	23.67		
15	QPSK	1	74	23.48	23.37	23.53		
15	QPSK	36	0	22.93	22.99	22.77	23.5	1
15	QPSK	36	20	23.00	22.88	22.75		
15	QPSK	36	39	23.04	22.80	22.71		
15	QPSK	75	0	22.97	22.89	22.70	23.5	1
15	16QAM	1	0	23.02	23.04	22.86		
15	16QAM	1	37	22.94	22.89	22.70		
15	16QAM	1	74	22.73	22.62	22.70	22.5	2
15	16QAM	36	0	22.02	22.03	21.92		
15	16QAM	36	20	22.07	21.99	21.86		
15	16QAM	36	39	22.16	21.97	21.80	22.5	2
15	16QAM	75	0	22.06	21.97	21.82		
15	64QAM	1	0	21.74	21.82	21.63		
15	64QAM	1	37	21.66	21.60	21.59	22.5	2
15	64QAM	1	74	21.50	21.44	21.51		
15	64QAM	36	0	21.00	21.04	20.88		
15	64QAM	36	20	21.09	21.03	20.84	21.5	3
15	64QAM	36	39	21.12	20.89	20.78		
15	64QAM	75	0	21.11	20.95	20.81		
Channel				37800	38000	38200	Tune-up limit	MPR



Frequency (MHz)				2575	2595	2615	(dBm)	(dB)
10	QPSK	1	0	23.93	23.97	23.67	24.5	0
10	QPSK	1	25	23.79	23.73	23.59		
10	QPSK	1	49	23.50	23.40	23.53		
10	QPSK	25	0	22.93	22.89	22.74	23.5	1
10	QPSK	25	12	23.00	22.86	22.71		
10	QPSK	25	25	22.98	22.83	22.66		
10	QPSK	50	0	23.02	22.91	22.77		
10	16QAM	1	0	23.05	23.08	22.86	23.5	1
10	16QAM	1	25	22.92	22.83	22.70		
10	16QAM	1	49	22.70	22.65	22.67		
10	16QAM	25	0	21.99	22.04	21.84	22.5	2
10	16QAM	25	12	22.11	21.90	21.84		
10	16QAM	25	25	22.08	21.95	21.81		
10	16QAM	50	0	22.14	22.02	21.78		
10	64QAM	1	0	21.76	21.80	21.61	22.5	2
10	64QAM	1	25	21.68	21.62	21.50		
10	64QAM	1	49	21.52	21.43	21.45		
10	64QAM	25	0	21.01	21.00	20.85	21.5	3
10	64QAM	25	12	21.10	21.00	20.88		
10	64QAM	25	25	21.08	20.88	20.77		
10	64QAM	50	0	21.12	20.97	20.80		
Channel				37775	38000	38225	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2572.5	2595	2617.5		
5	QPSK	1	0	23.91	23.95	23.76	24.5	0
5	QPSK	1	12	23.82	23.81	23.60		
5	QPSK	1	24	23.45	23.37	23.49		
5	QPSK	12	0	22.84	22.96	22.75	23.5	1
5	QPSK	12	7	23.03	22.82	22.68		
5	QPSK	12	13	22.98	22.75	22.64		
5	QPSK	25	0	23.05	22.86	22.72		
5	16QAM	1	0	22.98	23.00	22.80	23.5	1
5	16QAM	1	12	22.88	22.93	22.75		
5	16QAM	1	24	22.75	22.65	22.66		
5	16QAM	12	0	22.03	22.08	21.86	22.5	2
5	16QAM	12	7	22.05	21.93	21.88		
5	16QAM	12	13	22.10	21.93	21.86		
5	16QAM	25	0	22.13	22.04	21.79		
5	64QAM	1	0	21.74	21.76	21.61	22.5	2
5	64QAM	1	12	21.74	21.56	21.59		
5	64QAM	1	24	21.56	21.42	21.49		
5	64QAM	12	0	21.02	21.03	20.89	21.5	3
5	64QAM	12	7	21.10	20.98	20.84		
5	64QAM	12	13	21.11	20.89	20.82		
5	64QAM	25	0	21.11	21.00	20.88		



<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Low Middle Ch. / Freq.	Power Middle Ch. / Freq.	Power High Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				39750	40185	40620	41055	41490		
Frequency (MHz)				2506	2549.5	2593	2636.5	2680		
20	QPSK	1	0	23.77	23.66	24.14	23.97	23.33	24.5	0
20	QPSK	1	49	23.60	23.60	24.01	23.85	23.23		
20	QPSK	1	99	23.72	23.61	23.91	23.96	23.33		
20	QPSK	50	0	22.83	22.98	23.34	23.27	23.29	23.5	1
20	QPSK	50	24	22.80	22.96	23.33	23.26	23.03		
20	QPSK	50	50	22.82	22.96	23.14	23.03	23.07		
20	QPSK	100	0	22.78	23.07	23.30	23.22	23.28	23.5	1
20	16QAM	1	0	22.84	23.08	23.49	23.33	22.50		
20	16QAM	1	49	23.05	23.14	23.35	23.21	23.28		
20	16QAM	1	99	22.93	23.11	23.45	23.45	22.69	22.5	2
20	16QAM	50	0	21.85	21.88	22.49	22.22	22.36		
20	16QAM	50	24	21.90	22.10	22.44	22.18	22.18		
20	16QAM	50	50	21.93	22.06	22.26	22.17	22.33	21.5	3
20	16QAM	100	0	21.89	22.07	22.31	22.14	22.23		
20	64QAM	1	0	22.21	21.77	22.22	22.04	21.42		
20	64QAM	1	49	22.26	21.94	22.35	22.11	22.06	22.5	2
20	64QAM	1	99	21.85	22.02	22.17	22.20	21.64		
20	64QAM	50	0	20.83	20.86	21.37	21.11	21.40		
20	64QAM	50	24	21.00	21.08	21.32	21.21	21.11	21.5	3
20	64QAM	50	50	21.03	21.15	21.34	21.30	21.26		
20	64QAM	100	0	20.97	21.06	21.31	21.24	21.28		
Channel				39725	40173	40620	41068	41515	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2503.5	2548.3	2593	2637.8	2682.5		
15	QPSK	1	0	23.49	23.53	24.13	23.87	23.12	24.5	0
15	QPSK	1	37	23.57	23.59	23.97	23.81	23.82		
15	QPSK	1	74	23.73	23.79	23.85	23.94	23.29		
15	QPSK	36	0	22.66	22.75	23.30	23.01	23.29	23.5	1
15	QPSK	36	20	22.76	22.95	23.28	23.25	23.01		
15	QPSK	36	39	22.73	23.05	23.13	23.02	23.06		
15	QPSK	75	0	22.77	23.04	23.26	23.13	23.18	23.5	1
15	16QAM	1	0	22.80	23.00	23.43	23.26	22.43		
15	16QAM	1	37	22.95	23.08	23.26	23.14	23.19		
15	16QAM	1	74	22.93	23.03	23.44	23.41	22.67	22.5	2
15	16QAM	36	0	21.85	21.85	22.46	22.16	22.26		
15	16QAM	36	20	21.81	22.02	22.35	22.11	22.17		
15	16QAM	36	39	21.87	22.02	22.17	22.09	22.29	22.5	2
15	16QAM	75	0	21.85	22.04	22.23	22.10	22.18		
15	64QAM	1	0	22.19	21.68	22.19	21.99	21.40		
15	64QAM	1	37	22.23	21.84	22.32	22.02	22.06	22.5	2
15	64QAM	1	74	21.79	22.02	22.11	22.15	21.60		
15	64QAM	36	0	20.75	20.86	21.33	21.07	21.37		
15	64QAM	36	20	21.00	21.01	21.23	21.12	21.02	21.5	3
15	64QAM	36	39	20.95	21.10	21.25	21.22	21.24		
15	64QAM	75	0	20.90	21.05	21.28	21.15	21.21		



Channel				39700	40160	40620	41080	41540	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2501	2547	2593	2639	2685		
10	QPSK	1	0	23.32	23.47	24.07	23.93	23.07	24.5	0
10	QPSK	1	25	23.43	23.48	23.85	23.76	23.73		
10	QPSK	1	49	23.66	23.60	23.75	23.83	23.13		
10	QPSK	25	0	22.75	22.60	23.20	22.82	23.20	23.5	1
10	QPSK	25	12	22.65	22.83	23.14	23.10	23.03		
10	QPSK	25	25	22.66	22.92	22.96	22.84	22.89		
10	QPSK	50	0	22.64	22.89	23.25	23.18	23.11		
10	16QAM	1	0	22.82	22.99	23.46	23.13	22.34	23.5	1
10	16QAM	1	25	22.95	23.13	23.26	23.19	23.13		
10	16QAM	1	49	22.74	23.04	23.32	23.33	22.53		
10	16QAM	25	0	21.75	21.79	22.40	22.11	22.22	22.5	2
10	16QAM	25	12	21.85	21.97	22.41	22.07	22.05		
10	16QAM	25	25	21.84	21.92	22.18	22.09	22.26		
10	16QAM	50	0	21.84	22.03	22.28	22.02	22.15		
10	64QAM	1	0	22.11	21.65	22.16	21.85	21.32	22.5	2
10	64QAM	1	25	22.22	21.78	22.24	21.98	21.96		
10	64QAM	1	49	21.76	22.02	22.12	22.19	21.59		
10	64QAM	25	0	20.75	20.74	21.32	21.02	21.28	21.5	3
10	64QAM	25	12	20.89	20.94	21.23	21.12	20.99		
10	64QAM	25	25	20.90	21.15	21.24	21.16	21.09		
10	64QAM	50	0	20.81	20.93	21.17	21.19	21.18		
Channel				39675	40148	40620	41093	41565	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2498.5	2545.8	2593	2640.30	2687.5		
5	QPSK	1	0	23.37	23.27	24.05	23.88	23.00	24.5	0
5	QPSK	1	12	23.52	23.36	23.94	23.76	23.93		
5	QPSK	1	24	23.72	23.58	23.85	24.04	23.42		
5	QPSK	12	0	22.69	22.74	23.31	22.85	23.11	23.5	1
5	QPSK	12	7	22.62	22.97	23.27	23.06	22.76		
5	QPSK	12	13	22.73	22.98	23.17	22.91	23.02		
5	QPSK	25	0	22.68	22.91	23.23	23.13	23.21		
5	16QAM	1	0	22.67	22.87	23.45	23.14	22.31	23.5	1
5	16QAM	1	12	23.01	23.12	23.26	23.16	23.35		
5	16QAM	1	24	22.83	23.11	23.21	23.47	22.69		
5	16QAM	12	0	21.81	21.74	22.38	22.10	22.19	22.5	2
5	16QAM	12	7	21.63	21.94	22.40	22.08	21.99		
5	16QAM	12	13	21.87	22.04	22.28	22.09	22.16		
5	16QAM	25	0	21.80	21.88	22.14	21.99	22.26		
5	64QAM	1	0	22.17	21.67	22.07	21.89	21.21	22.5	2
5	64QAM	1	12	22.16	21.70	22.27	21.94	22.09		
5	64QAM	1	24	21.75	21.89	22.09	22.20	21.73		
5	64QAM	12	0	20.70	20.75	21.22	21.01	21.38	21.5	3
5	64QAM	12	7	20.97	20.98	21.06	21.07	21.12		
5	64QAM	12	13	20.97	21.18	21.20	21.14	21.10		
5	64QAM	25	0	20.78	20.97	21.27	21.06	21.08		



12. WiFi Output Power (Unit: dBm)

General Note:

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.



<2.4GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	19.65	20.00	99.19
		6	2437	19.65	20.00	
		11	2462	19.65	20.00	
	802.11g 6Mbps	1	2412	14.35	15.00	98.31
		6	2437	19.65	20.00	
		11	2462	15.35	16.00	
	802.11n-HT20 MCS0	1	2412	12.55	13.50	97.92
		6	2437	19.85	20.00	
		11	2462	15.05	16.00	
	802.11n-HT40 MCS0	3	2422	11.85	12.00	94.49
		6	2437	14.15	15.00	
		9	2452	11.95	12.50	
	802.11ac-VHT20 MCS0	1	2412	12.65	13.50	98.19
		6	2437	19.95	20.00	
		11	2462	15.15	16.00	
802.11ac-VHT40 MCS0	3	2422	11.95	12.00	94.64	
	6	2437	14.25	15.00		
	9	2452	12.05	12.50		



<5GHz WLAN>

5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	36	5180	17.71	18.00	98.45
		40	5200	17.51	18.00	
		44	5220	17.41	18.00	
		48	5240	17.51	18.00	
	802.11n-HT20 MCS0	36	5180	17.31	17.50	98.44
		40	5200	17.21	18.00	
		44	5220	17.01	17.50	
		48	5240	17.21	17.50	
	802.11n-HT40 MCS0	38	5190	17.91	18.00	96.37
46		5230	17.71	18.00		
802.11ac-VHT20 MCS0	36	5180	17.41	17.50	97.94	
	40	5200	17.31	18.00		
	44	5220	17.11	17.50		
	48	5240	17.31	17.50		
802.11ac-VHT40 MCS0	38	5190	17.99	18.00	95.90	
	46	5230	17.81	18.00		
802.11ac-VHT80 MCS0	42	5210	17.71	18.00	92.68	

5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	52	5260	20.11	20.50	98.45
		56	5280	19.91	20.00	
		60	5300	19.91	20.00	
		64	5320	20.11	20.50	
	802.11n-HT20 MCS0	52	5260	19.51	20.00	98.44
		56	5280	19.61	20.00	
		60	5300	19.71	20.00	
		64	5320	19.91	20.00	
	802.11n-HT40 MCS0	54	5270	19.61	20.00	96.37
62		5310	16.61	17.00		
802.11ac-VHT20 MCS0	52	5260	19.61	20.00	97.94	
	56	5280	19.71	20.00		
	60	5300	19.81	20.00		
	64	5320	20.01	20.50		
802.11ac-VHT40 MCS0	54	5270	19.71	20.00	95.90	
	62	5310	16.71	17.00		
802.11ac-VHT80 MCS0	58	5290	16.11	17.50	92.68	



	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.5GHz WLAN	802.11a 6Mbps	100	5500	18.91	19.50	98.45
		116	5580	19.11	19.50	
		124	5620	19.01	19.50	
		132	5660	19.01	19.50	
		144	5720	19.11	19.50	
	802.11n-HT20 MCS0	100	5500	19.21	19.50	98.44
		116	5580	18.91	19.50	
		124	5620	18.81	19.50	
		132	5660	18.81	19.50	
		144	5720	19.11	19.50	
	802.11n-HT40 MCS0	102	5510	17.81	18.00	96.37
		110	5550	18.11	18.50	
		126	5630	18.01	18.50	
		134	5670	17.91	18.50	
		142	5710	18.41	18.55	
	802.11ac-VHT20 MCS0	100	5500	19.31	19.50	97.94
		116	5580	19.01	19.50	
		124	5620	18.91	19.50	
		132	5660	18.91	19.50	
		144	5720	19.21	19.50	
802.11ac-VHT40 MCS0	102	5510	17.91	18.00	95.90	
	110	5550	18.21	18.50		
	126	5630	18.11	18.50		
	134	5670	18.01	18.50		
	142	5710	18.51	18.55		
802.11ac-VHT80 MCS0	106	5530	15.51	16.00	92.68	
	122	5610	18.61	19.00		
	138	5690	18.91	19.00		

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.8GHz WLAN	802.11a 6Mbps	149	5745	17.61	18.00	98.45
		157	5785	17.81	18.00	
		165	5825	17.61	18.00	
	802.11n-HT20 MCS0	149	5745	17.21	18.00	98.44
		157	5785	17.81	18.00	
		165	5825	17.31	18.00	
	802.11n-HT40 MCS0	151	5755	17.51	18.00	96.37
		159	5795	17.71	18.00	
	802.11ac-VHT20 MCS0	149	5745	17.31	18.00	97.94
		157	5785	17.91	18.00	
		165	5825	17.41	18.00	
	802.11ac-VHT40 MCS0	151	5755	17.61	18.00	95.90
		159	5795	17.81	18.00	
802.11ac-VHT80 MCS0	155	5775	17.91	18.00	92.68	



13. Bluetooth Exclusions Applied

Mode Band	Max Average power(dBm)	
	BR/EDR	LE
2.4GHz Bluetooth	8.5	2.5

Note:

- Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:


$$[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [\sqrt{f(GHz)}] \leq 3.0$$
for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
8.5	< 5	2.48	2.23

Note:

Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 2.23 which is ≤ 3, SAR testing is not required.

14. Antenna Location



Bottom Side

Back View

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Ant.	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN Ant.	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Ant.	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN Ant.	Yes	Yes	Yes	No	Yes	No

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge



15. SAR Test Results

General Note:

- Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
 - For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix 63.3%/62.9% = 1.006 is applied to scale-up the measured SAR result.
The Reported TDD LTE SAR = measured SAR (W/kg) * Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
- Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥0.8W/kg.
- When hotspot mode is enabled, power reduction will be activated to limit the maximum power of WCDMA B2 / B4 and LTE B2 / B4 / B7.
- Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
- Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, when hotspot mode applies, 10-g product specific SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold, for this device only bottom side SAR for WWAN transmitter scaled to maximum output power is higher than 1.2W/kg of WCDMA B4 and LTE B2/B4, therefore product specific SAR is necessary.
- For 5.3GHz / 5.6GHz WLAN product specific SAR is necessary too, due to an overall diagonal dimension is > 16cm.

GSM Note:

- Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
- Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode, SAR measurement is not required for the secondary mode.

UMTS Note:

- Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
- Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is ≤ ¼ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than ¼ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

**LTE Note:**

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4/B5/B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 38 SAR test was covered by Band 41; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.



15.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Right Cheek	0mm	Battery 1	189	836.4	27.71	28.00	1.069	-0.05	0.460	0.492
	GSM850	GPRS (4 Tx slots)	Right Tilted	0mm	Battery 1	189	836.4	27.71	28.00	1.069	-0.08	0.281	0.300
	GSM850	GPRS (4 Tx slots)	Left Cheek	0mm	Battery 1	189	836.4	27.71	28.00	1.069	-0.02	0.429	0.459
	GSM850	GPRS (4 Tx slots)	Left Tilted	0mm	Battery 1	189	836.4	27.71	28.00	1.069	-0.18	0.203	0.217
01	GSM850	GPRS (4 Tx slots)	Right Cheek	0mm	Battery 2	189	836.4	27.71	28.00	1.069	-0.07	0.489	0.523
	GSM850	GPRS (4 Tx slots)	Right Cheek	0mm	Battery 3	189	836.4	27.71	28.00	1.069	-0.17	0.430	0.460
02	GSM1900	GPRS (4 Tx slots)	Right Cheek	0mm	Battery 1	512	1850.2	25.10	25.50	1.096	0.16	0.729	0.799
	GSM1900	GPRS (4 Tx slots)	Right Tilted	0mm	Battery 1	512	1850.2	25.10	25.50	1.096	0.16	0.235	0.258
	GSM1900	GPRS (4 Tx slots)	Left Cheek	0mm	Battery 1	512	1850.2	25.10	25.50	1.096	0.17	0.691	0.758
	GSM1900	GPRS (4 Tx slots)	Left Tilted	0mm	Battery 1	512	1850.2	25.10	25.50	1.096	0	0.175	0.192
	GSM1900	GPRS (4 Tx slots)	Right Cheek	0mm	Battery 2	512	1850.2	25.10	25.50	1.096	-0.08	0.701	0.769
	GSM1900	GPRS (4 Tx slots)	Right Cheek	0mm	Battery 3	512	1850.2	25.10	25.50	1.096	-0.06	0.662	0.726

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	Battery 1	9262	1852.4	23.98	24.00	1.005	0.03	0.791	0.795
	WCDMA II	RMC 12.2Kbps	Right Tilted	0mm	Battery 1	9262	1852.4	23.98	24.00	1.005	0	0.271	0.272
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	Battery 1	9262	1852.4	23.98	24.00	1.005	-0.01	0.797	0.801
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	Battery 1	9400	1880	23.80	24.00	1.047	-0.01	0.750	0.785
03	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	Battery 1	9538	1907.6	23.71	24.00	1.069	-0.03	0.771	0.824
	WCDMA II	RMC 12.2Kbps	Left Tilted	0mm	Battery 1	9262	1852.4	23.98	24.00	1.005	0	0.261	0.262
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	Battery 2	9538	1907.6	23.71	24.00	1.069	-0.01	0.722	0.772
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	Battery 3	9538	1907.6	23.71	24.00	1.069	0.01	0.763	0.816
	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	Battery 1	1312	1712.4	24.49	24.50	1.002	0.08	0.883	0.885
	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	Battery 1	1413	1732.6	24.30	24.50	1.047	0.01	0.886	0.928
	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	Battery 1	1513	1752.6	24.41	24.50	1.021	0.11	0.947	0.967
	WCDMA IV	RMC 12.2Kbps	Right Tilted	0mm	Battery 1	1312	1712.4	24.49	24.50	1.002	-0.06	0.211	0.211
	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	Battery 1	1312	1712.4	24.49	24.50	1.002	-0.05	0.672	0.674
	WCDMA IV	RMC 12.2Kbps	Left Tilted	0mm	Battery 1	1312	1712.4	24.49	24.50	1.002	0.09	0.162	0.162
04	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	Battery 2	1513	1752.6	24.41	24.50	1.021	0.07	1.030	1.052
	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	Battery 3	1513	1752.6	24.41	24.50	1.021	0.06	1.010	1.031
	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	Battery 1	4132	826.4	25.30	25.50	1.047	-0.11	0.617	0.646
	WCDMA V	RMC 12.2Kbps	Right Tilted	0mm	Battery 1	4132	826.4	25.30	25.50	1.047	-0.15	0.369	0.386
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	Battery 1	4132	826.4	25.30	25.50	1.047	-0.14	0.742	0.777
05	WCDMA V	RMC 12.2Kbps	Left Tilted	0mm	Battery 1	4132	826.4	25.30	25.50	1.047	-0.1	0.455	0.476
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	Battery 2	4132	826.4	25.30	25.50	1.047	-0.15	0.695	0.728
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	Battery 3	4132	826.4	25.30	25.50	1.047	-0.1	0.682	0.714



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
06	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	Battery 1	18700	1860	23.87	24.50	1.156	-0.01	0.773	0.894
	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	Battery 1	18900	1880	23.75	24.50	1.189	0.01	0.740	0.879
	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	Battery 1	19100	1900	23.59	24.50	1.233	0.02	0.708	0.873
	LTE Band 2	20M	QPSK	50	0	Right Cheek	0mm	Battery 1	18700	1860	22.91	23.50	1.146	0.03	0.617	0.707
	LTE Band 2	20M	QPSK	100	0	Right Cheek	0mm	Battery 1	18700	1860	22.86	23.50	1.159	0.03	0.559	0.648
	LTE Band 2	20M	QPSK	1	0	Right Tilted	0mm	Battery 1	18700	1860	23.87	24.50	1.156	-0.02	0.223	0.258
	LTE Band 2	20M	QPSK	50	0	Right Tilted	0mm	Battery 1	18700	1860	22.91	23.50	1.146	-0.17	0.175	0.200
	LTE Band 2	20M	QPSK	1	0	Left Cheek	0mm	Battery 1	18700	1860	23.87	24.50	1.156	0.05	0.662	0.765
	LTE Band 2	20M	QPSK	50	0	Left Cheek	0mm	Battery 1	18700	1860	22.91	23.50	1.146	0.06	0.537	0.615
	LTE Band 2	20M	QPSK	1	0	Left Tilted	0mm	Battery 1	18700	1860	23.87	24.50	1.156	-0.06	0.261	0.302
	LTE Band 2	20M	QPSK	50	0	Left Tilted	0mm	Battery 1	18700	1860	22.91	23.50	1.146	0.12	0.259	0.297
	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	Battery 2	18700	1860	23.87	24.50	1.156	0.08	0.728	0.842
	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	Battery 3	18700	1860	23.87	24.50	1.156	0.12	0.734	0.849
	LTE Band 4	20M	QPSK	1	0	Right Cheek	0mm	Battery 1	20175	1732.5	24.45	24.50	1.012	0.06	0.670	0.678
	LTE Band 4	20M	QPSK	50	0	Right Cheek	0mm	Battery 1	20175	1732.5	22.93	23.50	1.140	0.01	0.539	0.615
	LTE Band 4	20M	QPSK	1	0	Right Tilted	0mm	Battery 1	20175	1732.5	24.45	24.50	1.012	-0.07	0.129	0.130
	LTE Band 4	20M	QPSK	50	0	Right Tilted	0mm	Battery 1	20175	1732.5	22.93	23.50	1.140	-0.06	0.112	0.128
	LTE Band 4	20M	QPSK	1	0	Left Cheek	0mm	Battery 1	20175	1732.5	24.45	24.50	1.012	0.05	0.545	0.551
	LTE Band 4	20M	QPSK	50	0	Left Cheek	0mm	Battery 1	20175	1732.5	22.93	23.50	1.140	0.08	0.449	0.512
	LTE Band 4	20M	QPSK	1	0	Left Tilted	0mm	Battery 1	20175	1732.5	24.45	24.50	1.012	-0.02	0.159	0.161
	LTE Band 4	20M	QPSK	50	0	Left Tilted	0mm	Battery 1	20175	1732.5	22.93	23.50	1.140	0	0.129	0.147
	LTE Band 4	20M	QPSK	1	0	Right Cheek	0mm	Battery 2	20175	1732.5	24.45	24.50	1.012	0.02	0.808	0.817
07	LTE Band 4	20M	QPSK	1	0	Right Cheek	0mm	Battery 3	20175	1732.5	24.45	24.50	1.012	-0.03	0.892	0.902
	LTE Band 5	10M	QPSK	1	0	Right Cheek	0mm	Battery 1	20525	836.5	24.81	25.00	1.045	-0.12	0.595	0.622
	LTE Band 5	10M	QPSK	25	0	Right Cheek	0mm	Battery 1	20525	836.5	23.90	24.00	1.023	-0.1	0.484	0.495
	LTE Band 5	10M	QPSK	1	0	Right Tilted	0mm	Battery 1	20525	836.5	24.81	25.00	1.045	-0.14	0.345	0.360
	LTE Band 5	10M	QPSK	25	0	Right Tilted	0mm	Battery 1	20525	836.5	23.90	24.00	1.023	-0.07	0.279	0.285
08	LTE Band 5	10M	QPSK	1	0	Left Cheek	0mm	Battery 1	20525	836.5	24.81	25.00	1.045	-0.14	0.648	0.677
	LTE Band 5	10M	QPSK	25	0	Left Cheek	0mm	Battery 1	20525	836.5	23.90	24.00	1.023	-0.1	0.530	0.542
	LTE Band 5	10M	QPSK	1	0	Left Tilted	0mm	Battery 1	20525	836.5	24.81	25.00	1.045	-0.09	0.365	0.381
	LTE Band 5	10M	QPSK	25	0	Left Tilted	0mm	Battery 1	20525	836.5	23.90	24.00	1.023	-0.12	0.298	0.305
	LTE Band 5	10M	QPSK	1	0	Left Cheek	0mm	Battery 2	20525	836.5	24.81	25.00	1.045	-0.07	0.596	0.623
	LTE Band 5	10M	QPSK	1	0	Left Cheek	0mm	Battery 3	20525	836.5	24.81	25.00	1.045	-0.01	0.594	0.621
	LTE Band 7	20M	QPSK	1	99	Right Cheek	0mm	Battery 1	21100	2535	23.69	24.00	1.074	-0.06	1.170	1.257
	LTE Band 7	20M	QPSK	1	99	Right Cheek	0mm	Battery 1	20850	2510	23.65	24.00	1.084	-0.17	1.120	1.214
09	LTE Band 7	20M	QPSK	1	99	Right Cheek	0mm	Battery 1	21350	2560	23.66	24.00	1.081	-0.16	1.180	1.276
	LTE Band 7	20M	QPSK	50	24	Right Cheek	0mm	Battery 1	21100	2535	22.56	23.00	1.107	-0.12	0.811	0.897
	LTE Band 7	20M	QPSK	50	24	Right Cheek	0mm	Battery 1	20850	2510	22.32	23.00	1.169	-0.04	0.927	1.084
	LTE Band 7	20M	QPSK	50	24	Right Cheek	0mm	Battery 1	21350	2560	22.55	23.00	1.109	-0.14	0.961	1.066
	LTE Band 7	20M	QPSK	100	0	Right Cheek	0mm	Battery 1	21100	2535	22.56	23.00	1.107	-0.15	0.961	1.063
	LTE Band 7	20M	QPSK	1	99	Right Tilted	0mm	Battery 1	21100	2535	23.69	24.00	1.074	0.12	0.199	0.214
	LTE Band 7	20M	QPSK	50	24	Right Tilted	0mm	Battery 1	21100	2535	22.56	23.00	1.107	0.03	0.149	0.165
	LTE Band 7	20M	QPSK	1	99	Left Cheek	0mm	Battery 1	21100	2535	23.69	24.00	1.074	0.12	0.640	0.687
	LTE Band 7	20M	QPSK	50	24	Left Cheek	0mm	Battery 1	21100	2535	22.56	23.00	1.107	-0.15	0.525	0.581
	LTE Band 7	20M	QPSK	1	99	Left Tilted	0mm	Battery 1	21100	2535	23.69	24.00	1.074	-0.14	0.269	0.289
	LTE Band 7	20M	QPSK	50	24	Left Tilted	0mm	Battery 1	21100	2535	22.56	23.00	1.107	0.06	0.218	0.241
	LTE Band 7	20M	QPSK	1	99	Right Cheek	0mm	Battery 2	21350	2560	23.66	24.00	1.081	-0.15	1.150	1.244
	LTE Band 7	20M	QPSK	1	99	Right Cheek	0mm	Battery 3	21350	2560	23.66	24.00	1.081	-0.17	1.100	1.190



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	Battery 1	40620	2593	24.14	24.50	1.086	62.9	1.006	-0.15	0.883	0.965
	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	Battery 1	39750	2506	23.77	24.50	1.183	62.9	1.006	-0.04	0.692	0.824
	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	Battery 1	40185	2549.5	23.66	24.50	1.213	62.9	1.006	-0.17	0.799	0.975
10	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	Battery 1	41055	2636.5	23.97	24.50	1.130	62.9	1.006	-0.11	0.912	1.037
	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	Battery 1	41490	2680	23.33	24.50	1.309	62.9	1.006	-0.13	0.604	0.795
	LTE Band 41	20M	QPSK	50	0	Right Cheek	0mm	Battery 1	40620	2593	23.34	23.50	1.038	62.9	1.006	-0.06	0.745	0.778
	LTE Band 41	20M	QPSK	50	0	Right Cheek	0mm	Battery 1	39750	2506	22.83	23.50	1.167	62.9	1.006	-0.17	0.644	0.756
	LTE Band 41	20M	QPSK	50	0	Right Cheek	0mm	Battery 1	40185	2549.5	22.98	23.50	1.127	62.9	1.006	-0.08	0.666	0.755
	LTE Band 41	20M	QPSK	50	0	Right Cheek	0mm	Battery 1	41055	2636.5	23.27	23.50	1.054	62.9	1.006	-0.11	0.741	0.786
	LTE Band 41	20M	QPSK	50	0	Right Cheek	0mm	Battery 1	41490	2680	23.29	23.50	1.050	62.9	1.006	-0.07	0.725	0.765
	LTE Band 41	20M	QPSK	100	0	Right Cheek	0mm	Battery 1	40620	2593	23.30	23.50	1.047	62.9	1.006	-0.08	0.733	0.772
	LTE Band 41	20M	QPSK	1	0	Right Tilted	0mm	Battery 1	40620	2593	24.14	24.50	1.086	62.9	1.006	0.06	0.244	0.267
	LTE Band 41	20M	QPSK	50	0	Right Tilted	0mm	Battery 1	40620	2593	23.34	23.50	1.038	62.9	1.006	-0.09	0.204	0.213
	LTE Band 41	20M	QPSK	1	0	Left Cheek	0mm	Battery 1	40620	2593	24.14	24.50	1.086	62.9	1.006	0	0.472	0.516
	LTE Band 41	20M	QPSK	50	0	Left Cheek	0mm	Battery 1	40620	2593	23.34	23.50	1.038	62.9	1.006	-0.13	0.393	0.410
	LTE Band 41	20M	QPSK	1	0	Left Tilted	0mm	Battery 1	40620	2593	24.14	24.50	1.086	62.9	1.006	-0.13	0.296	0.324
	LTE Band 41	20M	QPSK	50	0	Left Tilted	0mm	Battery 1	40620	2593	23.34	23.50	1.038	62.9	1.006	0.01	0.257	0.268
	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	Battery 2	41055	2636.5	23.97	24.50	1.130	62.9	1.006	0.03	0.893	1.015
	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	Battery 3	41055	2636.5	23.97	24.50	1.130	62.9	1.006	0.05	0.872	0.991



<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Battery 1	6	2437	19.65	20.00	1.084	99.19	1.008	-0.01	0.571	0.624
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	Battery 1	6	2437	19.65	20.00	1.084	99.19	1.008	-0.05	0.421	0.460
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Battery 1	6	2437	19.65	20.00	1.084	99.19	1.008	-0.02	1.050	1.147
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Battery 1	1	2412	19.65	20.00	1.084	99.19	1.008	0.07	1.040	1.136
11	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Battery 1	11	2462	19.65	20.00	1.084	99.19	1.008	-0.09	1.070	1.169
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	Battery 1	6	2437	19.65	20.00	1.084	99.19	1.008	-0.05	0.628	0.686
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Battery 2	11	2462	19.65	20.00	1.084	99.19	1.008	0.02	1.010	1.104
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Battery 3	11	2462	19.65	20.00	1.084	99.19	1.008	0.07	1.060	1.158
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	Battery 1	52	5260	20.11	20.50	1.094	98.45	1.016	-0.08	0.297	0.330
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	Battery 1	52	5260	20.11	20.50	1.094	98.45	1.016	0	0.185	0.206
12	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	Battery 1	52	5260	20.11	20.50	1.094	98.45	1.016	-0.18	0.657	0.730
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	Battery 1	52	5260	20.11	20.50	1.094	98.45	1.016	0.02	0.362	0.402
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	Battery 2	52	5260	20.11	20.50	1.094	98.45	1.016	0.03	0.638	0.709
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	Battery 3	52	5260	20.11	20.50	1.094	98.45	1.016	-0.06	0.617	0.686
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	Battery 1	116	5580	19.11	19.50	1.094	98.45	1.016	-0.1	0.449	0.499
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	Battery 1	116	5580	19.11	19.50	1.094	98.45	1.016	-0.02	0.282	0.313
13	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	Battery 1	116	5580	19.11	19.50	1.094	98.45	1.016	-0.11	0.766	0.851
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	Battery 1	144	5720	19.11	19.50	1.094	98.45	1.016	-0.09	0.740	0.822
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	Battery 1	116	5580	19.11	19.50	1.094	98.45	1.016	-0.09	0.459	0.510
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	Battery 2	116	5580	19.11	19.50	1.094	98.45	1.016	0	0.742	0.825
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	Battery 3	116	5580	19.11	19.50	1.094	98.45	1.016	0.05	0.728	0.809
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Battery 1	155	5775	17.91	18.00	1.021	92.68	1.079	-0.02	0.286	0.315
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Battery 1	155	5775	17.91	18.00	1.021	92.68	1.079	0.06	0.205	0.226
14	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Battery 1	155	5775	17.91	18.00	1.021	92.68	1.079	-0.07	0.456	0.502
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Battery 1	155	5775	17.91	18.00	1.021	92.68	1.079	-0.06	0.304	0.335
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Battery 2	155	5775	17.91	18.00	1.021	92.68	1.079	0.05	0.439	0.484
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Battery 3	155	5775	17.91	18.00	1.021	92.68	1.079	0.08	0.429	0.473



15.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	10mm	Battery 1	OFF	189	836.4	27.71	28.00	1.069	-0.01	0.397	0.424
15	GSM850	GPRS (4 Tx slots)	Back	10mm	Battery 1	OFF	189	836.4	27.71	28.00	1.069	-0.1	0.424	0.453
	GSM850	GPRS (4 Tx slots)	Left Side	10mm	Battery 1	OFF	189	836.4	27.71	28.00	1.069	-0.02	0.276	0.295
	GSM850	GPRS (4 Tx slots)	Right Side	10mm	Battery 1	OFF	189	836.4	27.71	28.00	1.069	-0.18	0.266	0.284
	GSM850	GPRS (4 Tx slots)	Bottom Side	10mm	Battery 1	OFF	189	836.4	27.71	28.00	1.069	-0.08	0.318	0.340
	GSM850	GPRS (4 Tx slots)	Back	10mm	Battery 2	OFF	189	836.4	27.71	28.00	1.069	-0.13	0.402	0.430
	GSM850	GPRS (4 Tx slots)	Back	10mm	Battery 3	OFF	189	836.4	27.71	28.00	1.069	-0.1	0.294	0.314
16	GSM1900	GPRS (4 Tx slots)	Front	10mm	Battery 1	OFF	512	1850.2	25.10	25.50	1.096	0.09	1.060	1.162
	GSM1900	GPRS (4 Tx slots)	Front	10mm	Battery 1	OFF	661	1880	25.09	25.50	1.099	0.03	0.875	0.962
	GSM1900	GPRS (4 Tx slots)	Front	10mm	Battery 1	OFF	810	1909.8	24.00	25.50	1.413	-0.04	0.745	1.052
	GSM1900	GPRS (4 Tx slots)	Back	10mm	Battery 1	OFF	512	1850.2	25.10	25.50	1.096	-0.06	0.685	0.751
	GSM1900	GPRS (4 Tx slots)	Left Side	10mm	Battery 1	OFF	512	1850.2	25.10	25.50	1.096	-0.19	0.227	0.249
	GSM1900	GPRS (4 Tx slots)	Right Side	10mm	Battery 1	OFF	512	1850.2	25.10	25.50	1.096	-0.04	0.471	0.516
	GSM1900	GPRS (4 Tx slots)	Bottom Side	10mm	Battery 1	OFF	512	1850.2	25.10	25.50	1.096	-0.01	0.225	0.247
	GSM1900	GPRS (4 Tx slots)	Front	10mm	Battery 2	OFF	512	1850.2	25.10	25.50	1.096	0.09	0.722	0.792
	GSM1900	GPRS (4 Tx slots)	Front	10mm	Battery 3	OFF	512	1850.2	25.10	25.50	1.096	0.08	0.698	0.765

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	10mm	Battery 1	ON	9262	1852.4	23.41	23.50	1.021	0.04	0.877	0.895
	WCDMA II	RMC 12.2Kbps	Front	10mm	Battery 1	ON	9400	1880	23.27	23.50	1.054	0.01	0.864	0.911
17	WCDMA II	RMC 12.2Kbps	Front	10mm	Battery 1	ON	9538	1907.6	23.19	23.50	1.074	0.03	0.893	0.959
	WCDMA II	RMC 12.2Kbps	Back	10mm	Battery 1	ON	9262	1852.4	23.41	23.50	1.021	0.1	0.575	0.587
	WCDMA II	RMC 12.2Kbps	Left Side	10mm	Battery 1	ON	9262	1852.4	23.41	23.50	1.021	0.1	0.193	0.197
	WCDMA II	RMC 12.2Kbps	Right Side	10mm	Battery 1	ON	9262	1852.4	23.41	23.50	1.021	-0.1	0.295	0.301
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	Battery 1	ON	9262	1852.4	23.41	23.50	1.021	-0.01	0.274	0.280
	WCDMA II	RMC 12.2Kbps	Front	10mm	Battery 2	ON	9538	1907.6	23.19	23.50	1.074	0.08	0.875	0.940
	WCDMA II	RMC 12.2Kbps	Front	10mm	Battery 3	ON	9538	1907.6	23.19	23.50	1.074	-0.06	0.889	0.955
	WCDMA IV	RMC 12.2Kbps	Front	10mm	Battery 1	ON	1312	1712.4	22.99	23.00	1.002	-0.05	0.896	0.898
	WCDMA IV	RMC 12.2Kbps	Front	10mm	Battery 1	ON	1413	1732.6	22.94	23.00	1.014	-0.02	0.946	0.959
18	WCDMA IV	RMC 12.2Kbps	Front	10mm	Battery 1	ON	1513	1752.6	22.90	23.00	1.023	-0.02	0.954	0.976
	WCDMA IV	RMC 12.2Kbps	Back	10mm	Battery 1	ON	1312	1712.4	22.99	23.00	1.002	0.02	0.491	0.492
	WCDMA IV	RMC 12.2Kbps	Left Side	10mm	Battery 1	ON	1312	1712.4	22.99	23.00	1.002	0.03	0.100	0.100
	WCDMA IV	RMC 12.2Kbps	Right Side	10mm	Battery 1	ON	1312	1712.4	22.99	23.00	1.002	-0.14	0.278	0.279
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	Battery 1	ON	1312	1712.4	22.99	23.00	1.002	0.11	0.207	0.207
	WCDMA IV	RMC 12.2Kbps	Front	10mm	Battery 2	ON	1513	1752.6	22.90	23.00	1.023	0.09	0.932	0.954
	WCDMA IV	RMC 12.2Kbps	Front	10mm	Battery 3	ON	1513	1752.6	22.90	23.00	1.023	0.11	0.911	0.932
	WCDMA V	RMC 12.2Kbps	Front	10mm	Battery 1	OFF	4132	826.4	25.30	25.50	1.047	-0.16	0.560	0.586
	WCDMA V	RMC 12.2Kbps	Back	10mm	Battery 1	OFF	4132	826.4	25.30	25.50	1.047	-0.16	0.517	0.541
	WCDMA V	RMC 12.2Kbps	Left Side	10mm	Battery 1	OFF	4132	826.4	25.30	25.50	1.047	-0.14	0.301	0.315
	WCDMA V	RMC 12.2Kbps	Right Side	10mm	Battery 1	OFF	4132	826.4	25.30	25.50	1.047	-0.09	0.264	0.276
	WCDMA V	RMC 12.2Kbps	Bottom Side	10mm	Battery 1	OFF	4132	826.4	25.30	25.50	1.047	-0.01	0.328	0.343
19	WCDMA V	RMC 12.2Kbps	Front	10mm	Battery 2	OFF	4132	826.4	25.30	25.50	1.047	-0.16	0.570	0.597
	WCDMA V	RMC 12.2Kbps	Front	10mm	Battery 3	OFF	4132	826.4	25.30	25.50	1.047	-0.13	0.561	0.587



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Battery	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	10mm	Battery 1	ON	18700	1860	23.87	24.00	1.030	0	1.040	1.072
	LTE Band 2	20M	QPSK	1	0	Front	10mm	Battery 1	ON	18900	1880	23.75	24.00	1.059	0.04	1.030	1.091
20	LTE Band 2	20M	QPSK	1	0	Front	10mm	Battery 1	ON	19100	1900	23.59	24.00	1.099	0.05	0.996	1.095
	LTE Band 2	20M	QPSK	50	0	Front	10mm	Battery 1	ON	18700	1860	22.91	23.50	1.146	0.04	0.828	0.948
	LTE Band 2	20M	QPSK	50	0	Front	10mm	Battery 1	ON	18900	1880	22.77	23.50	1.183	0.03	0.821	0.971
	LTE Band 2	20M	QPSK	50	0	Front	10mm	Battery 1	ON	19100	1900	22.63	23.50	1.222	0.06	0.805	0.984
	LTE Band 2	20M	QPSK	100	0	Front	10mm	Battery 1	ON	18700	1860	22.86	23.50	1.159	0.04	0.828	0.959
	LTE Band 2	20M	QPSK	1	0	Back	10mm	Battery 1	ON	18700	1860	23.87	24.00	1.030	0.06	0.676	0.697
	LTE Band 2	20M	QPSK	50	0	Back	10mm	Battery 1	ON	18700	1860	22.91	23.50	1.146	0.07	0.550	0.630
	LTE Band 2	20M	QPSK	1	0	Left Side	10mm	Battery 1	ON	18700	1860	23.87	24.00	1.030	-0.18	0.230	0.237
	LTE Band 2	20M	QPSK	50	0	Left Side	10mm	Battery 1	ON	18700	1860	22.91	23.50	1.146	-0.15	0.185	0.212
	LTE Band 2	20M	QPSK	1	0	Right Side	10mm	Battery 1	ON	18700	1860	23.87	24.00	1.030	-0.18	0.458	0.472
	LTE Band 2	20M	QPSK	50	0	Right Side	10mm	Battery 1	ON	18700	1860	22.91	23.50	1.146	-0.1	0.367	0.420
	LTE Band 2	20M	QPSK	1	0	Bottom Side	10mm	Battery 1	ON	18700	1860	23.87	24.00	1.030	-0.07	0.376	0.387
	LTE Band 2	20M	QPSK	1	0	Bottom Side	10mm	Battery 1	ON	18700	1860	22.91	23.50	1.146	-0.09	0.307	0.352
	LTE Band 2	20M	QPSK	1	0	Front	10mm	Battery 2	ON	19100	1900	23.59	24.00	1.099	0	0.942	1.035
	LTE Band 2	20M	QPSK	1	0	Front	10mm	Battery 3	ON	19100	1900	23.59	24.00	1.099	0.04	0.865	0.951
21	LTE Band 4	20M	QPSK	1	0	Front	10mm	Battery 1	ON	20175	1732.5	22.74	23.00	1.062	0	0.885	0.940
	LTE Band 4	20M	QPSK	50	0	Front	10mm	Battery 1	ON	20175	1732.5	21.61	22.50	1.227	-0.06	0.654	0.803
	LTE Band 4	20M	QPSK	100	0	Front	10mm	Battery 1	ON	20175	1732.5	21.63	22.50	1.222	-0.05	0.673	0.822
	LTE Band 4	20M	QPSK	1	0	Back	10mm	Battery 1	ON	20175	1732.5	22.74	23.00	1.062	0.04	0.405	0.430
	LTE Band 4	20M	QPSK	50	0	Back	10mm	Battery 1	ON	20175	1732.5	21.61	22.50	1.227	0.07	0.301	0.369
	LTE Band 4	20M	QPSK	1	0	Left Side	10mm	Battery 1	ON	20175	1732.5	22.74	23.00	1.062	-0.01	0.094	0.100
	LTE Band 4	20M	QPSK	50	0	Left Side	10mm	Battery 1	ON	20175	1732.5	21.61	22.50	1.227	-0.05	0.073	0.090
	LTE Band 4	20M	QPSK	1	0	Right Side	10mm	Battery 1	ON	20175	1732.5	22.74	23.00	1.062	-0.09	0.245	0.260
	LTE Band 4	20M	QPSK	50	0	Right Side	10mm	Battery 1	ON	20175	1732.5	21.61	22.50	1.227	-0.14	0.188	0.231
	LTE Band 4	20M	QPSK	1	0	Bottom Side	10mm	Battery 1	ON	20175	1732.5	22.74	23.00	1.062	-0.14	0.167	0.177
	LTE Band 4	20M	QPSK	50	0	Bottom Side	10mm	Battery 1	ON	20175	1732.5	21.61	22.50	1.227	0.1	0.126	0.155
	LTE Band 4	20M	QPSK	1	0	Front	10mm	Battery 2	ON	20175	1732.5	22.74	23.00	1.062	-0.12	0.844	0.896
	LTE Band 4	20M	QPSK	1	0	Front	10mm	Battery 3	ON	20175	1732.5	22.74	23.00	1.062	-0.08	0.813	0.863
	LTE Band 5	10M	QPSK	1	0	Front	10mm	Battery 1	OFF	20525	836.5	24.81	25.00	1.045	-0.15	0.611	0.638
	LTE Band 5	10M	QPSK	25	0	Front	10mm	Battery 1	OFF	20525	836.5	23.90	24.00	1.023	-0.17	0.491	0.502
	LTE Band 5	10M	QPSK	1	0	Back	10mm	Battery 1	OFF	20525	836.5	24.81	25.00	1.045	-0.11	0.593	0.620
	LTE Band 5	10M	QPSK	25	0	Back	10mm	Battery 1	OFF	20525	836.5	23.90	24.00	1.023	-0.1	0.476	0.487
	LTE Band 5	10M	QPSK	1	0	Left Side	10mm	Battery 1	OFF	20525	836.5	24.81	25.00	1.045	-0.18	0.355	0.371
	LTE Band 5	10M	QPSK	25	0	Left Side	10mm	Battery 1	OFF	20525	836.5	23.90	24.00	1.023	-0.16	0.289	0.296
	LTE Band 5	10M	QPSK	1	0	Right Side	10mm	Battery 1	OFF	20525	836.5	24.81	25.00	1.045	-0.14	0.326	0.341
	LTE Band 5	10M	QPSK	25	0	Right Side	10mm	Battery 1	OFF	20525	836.5	23.90	24.00	1.023	-0.1	0.264	0.270
	LTE Band 5	10M	QPSK	1	0	Bottom Side	10mm	Battery 1	OFF	20525	836.5	24.81	25.00	1.045	-0.15	0.336	0.351
	LTE Band 5	10M	QPSK	25	0	Bottom Side	10mm	Battery 1	OFF	20525	836.5	23.90	24.00	1.023	-0.18	0.273	0.279
22	LTE Band 5	10M	QPSK	1	0	Front	10mm	Battery 2	OFF	20525	836.5	24.81	25.00	1.045	-0.12	0.623	0.651
	LTE Band 5	10M	QPSK	1	0	Front	10mm	Battery 3	OFF	20525	836.5	24.81	25.00	1.045	-0.16	0.598	0.625
	LTE Band 7	20M	QPSK	1	99	Front	10mm	Battery 1	ON	21350	2560	23.43	23.50	1.016	-0.03	0.655	0.666
	LTE Band 7	20M	QPSK	50	0	Front	10mm	Battery 1	ON	21350	2560	22.30	23.00	1.175	-0.06	0.532	0.625
23	LTE Band 7	20M	QPSK	1	99	Back	10mm	Battery 1	ON	21350	2560	23.43	23.50	1.016	-0.08	0.749	0.761
	LTE Band 7	20M	QPSK	50	0	Back	10mm	Battery 1	ON	21350	2560	22.30	23.00	1.175	-0.09	0.606	0.712
	LTE Band 7	20M	QPSK	1	99	Left Side	10mm	Battery 1	ON	21350	2560	23.43	23.50	1.016	-0.06	0.066	0.067
	LTE Band 7	20M	QPSK	50	0	Left Side	10mm	Battery 1	ON	21350	2560	22.30	23.00	1.175	0.02	0.051	0.060
	LTE Band 7	20M	QPSK	1	99	Right Side	10mm	Battery 1	ON	21350	2560	23.43	23.50	1.016	-0.06	0.557	0.566
	LTE Band 7	20M	QPSK	50	0	Right Side	10mm	Battery 1	ON	21350	2560	22.30	23.00	1.175	-0.02	0.449	0.528
	LTE Band 7	20M	QPSK	1	99	Bottom Side	10mm	Battery 1	ON	21350	2560	23.43	23.50	1.016	-0.06	0.723	0.735
	LTE Band 7	20M	QPSK	50	0	Bottom Side	10mm	Battery 1	ON	21350	2560	22.30	23.00	1.175	-0.12	0.610	0.717
	LTE Band 7	20M	QPSK	1	99	Back	10mm	Battery 2	ON	21350	2560	23.43	23.50	1.016	-0.03	0.722	0.734
	LTE Band 7	20M	QPSK	1	99	Back	10mm	Battery 3	ON	21350	2560	23.43	23.50	1.016	-0.07	0.713	0.725



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Battery	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	0	Front	10mm	Battery 1	OFF	40620	2593	24.14	24.50	1.086	62.9	1.006	-0.02	0.472	0.516
	LTE Band 41	20M	QPSK	50	0	Front	10mm	Battery 1	OFF	40620	2593	23.34	23.50	1.038	62.9	1.006	-0.16	0.385	0.402
	LTE Band 41	20M	QPSK	1	0	Back	10mm	Battery 1	OFF	40620	2593	24.14	24.50	1.086	62.9	1.006	-0.03	0.604	0.660
	LTE Band 41	20M	QPSK	1	0	Back	10mm	Battery 1	OFF	39750	2506	23.77	24.50	1.183	62.9	1.006	-0.18	0.443	0.527
24	LTE Band 41	20M	QPSK	1	0	Back	10mm	Battery 1	OFF	40185	2549.5	23.66	24.50	1.213	62.9	1.006	-0.13	0.600	0.732
	LTE Band 41	20M	QPSK	1	0	Back	10mm	Battery 1	OFF	41055	2636.5	23.97	24.50	1.130	62.9	1.006	-0.11	0.616	0.700
	LTE Band 41	20M	QPSK	1	0	Back	10mm	Battery 1	OFF	41490	2680	23.33	24.50	1.309	62.9	1.006	-0.16	0.373	0.491
	LTE Band 41	20M	QPSK	50	0	Back	10mm	Battery 1	OFF	40620	2593	23.34	23.50	1.038	62.9	1.006	-0.08	0.522	0.545
	LTE Band 41	20M	QPSK	100	0	Back	10mm	Battery 1	OFF	40620	2593	23.30	23.50	1.047	62.9	1.006	-0.07	0.514	0.541
	LTE Band 41	20M	QPSK	1	0	Left Side	10mm	Battery 1	OFF	40620	2593	24.14	24.50	1.086	62.9	1.006	-0.07	0.075	0.082
	LTE Band 41	20M	QPSK	50	0	Left Side	10mm	Battery 1	OFF	40620	2593	23.34	23.50	1.038	62.9	1.006	0.04	0.065	0.068
	LTE Band 41	20M	QPSK	1	0	Right Side	10mm	Battery 1	OFF	40620	2593	24.14	24.50	1.086	62.9	1.006	-0.09	0.487	0.532
	LTE Band 41	20M	QPSK	50	0	Right Side	10mm	Battery 1	OFF	40620	2593	23.34	23.50	1.038	62.9	1.006	-0.04	0.407	0.425
	LTE Band 41	20M	QPSK	1	0	Bottom Side	10mm	Battery 1	OFF	40620	2593	24.14	24.50	1.086	62.9	1.006	-0.05	0.592	0.647
	LTE Band 41	20M	QPSK	1	0	Bottom Side	10mm	Battery 1	OFF	39750	2506	23.77	24.50	1.183	62.9	1.006	-0.1	0.451	0.537
	LTE Band 41	20M	QPSK	1	0	Bottom Side	10mm	Battery 1	OFF	40185	2549.5	23.66	24.50	1.213	62.9	1.006	-0.07	0.558	0.681
	LTE Band 41	20M	QPSK	1	0	Bottom Side	10mm	Battery 1	OFF	41055	2636.5	23.97	24.50	1.130	62.9	1.006	-0.16	0.593	0.674
	LTE Band 41	20M	QPSK	1	0	Bottom Side	10mm	Battery 1	OFF	41490	2680	23.33	24.50	1.309	62.9	1.006	-0.18	0.350	0.461
	LTE Band 41	20M	QPSK	50	0	Bottom Side	10mm	Battery 1	OFF	40620	2593	23.34	23.50	1.038	62.9	1.006	-0.03	0.487	0.508
	LTE Band 41	20M	QPSK	100	0	Bottom Side	10mm	Battery 1	OFF	40620	2593	23.30	23.50	1.047	62.9	1.006	-0.06	0.534	0.563
	LTE Band 41	20M	QPSK	1	0	Back	10mm	Battery 2	OFF	40185	2549.5	23.66	24.50	1.213	62.9	1.006	-0.09	0.524	0.640
	LTE Band 41	20M	QPSK	1	0	Back	10mm	Battery 3	OFF	40185	2549.5	23.66	24.50	1.213	62.9	1.006	0.02	0.573	0.699

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Battery 1	6	2437	19.65	20.00	1.084	99.19	1.008	-0.01	0.327	0.357
25	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Battery 1	6	2437	19.65	20.00	1.084	99.19	1.008	-0.06	0.580	0.634
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Battery 1	6	2437	19.65	20.00	1.084	99.19	1.008	-0.03	0.427	0.467
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Battery 1	6	2437	19.65	20.00	1.084	99.19	1.008	0.03	0.339	0.370
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Battery 2	6	2437	19.65	20.00	1.084	99.19	1.008	-0.01	0.562	0.614
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Battery 3	6	2437	19.65	20.00	1.084	99.19	1.008	0.01	0.523	0.571
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	10mm	Battery 1	42	5210	17.71	18.00	1.069	92.68	1.079	-0.01	0.084	0.097
26	WLAN5GHz	802.11ac-VHT80 MCS0	Back	10mm	Battery 1	42	5210	17.71	18.00	1.069	92.68	1.079	-0.16	0.756	0.872
	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	Battery 1	38	5190	17.91	18.00	1.021	96.37	1.038	-0.04	0.798	0.846
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Side	10mm	Battery 1	42	5210	17.71	18.00	1.069	92.68	1.079	-0.06	0.428	0.494
	WLAN5GHz	802.11ac-VHT80 MCS0	Top Side	10mm	Battery 1	42	5210	17.71	18.00	1.069	92.68	1.079	-0.03	0.073	0.084
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	10mm	Battery 2	42	5210	17.71	18.00	1.069	92.68	1.079	-0.04	0.727	0.839
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	10mm	Battery 3	42	5210	17.71	18.00	1.069	92.68	1.079	-0.03	0.702	0.810
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	10mm	Battery 1	155	5775	17.91	18.00	1.021	92.68	1.079	0.02	0.156	0.172
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	10mm	Battery 1	155	5775	17.91	18.00	1.021	92.68	1.079	-0.12	1.080	1.190
	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	Battery 1	159	5795	17.71	18.00	1.069	96.37	1.038	-0.18	1.090	1.210
27	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	Battery 1	151	5755	17.51	18.00	1.119	96.37	1.038	0.08	1.060	1.232
	WLAN5GHz	802.11a 6Mbps	Back	10mm	Battery 1	157	5785	17.81	18.00	1.045	98.45	1.016	-0.01	1.030	1.093
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Side	10mm	Battery 1	155	5775	17.91	18.00	1.021	92.68	1.079	0.08	0.547	0.602
	WLAN5GHz	802.11ac-VHT80 MCS0	Top Side	10mm	Battery 1	155	5775	17.91	18.00	1.021	92.68	1.079	-0.07	0.122	0.135
	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	Battery 2	151	5755	17.51	18.00	1.119	96.37	1.038	0.05	1.010	1.174
	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	Battery 3	151	5755	17.51	18.00	1.119	96.37	1.038	-0.01	0.918	1.067



15.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Accessories	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	0mm	Battery 1	189	836.4	Soft Holster	27.71	28.00	1.069	-0.07	0.256	0.274
28	GSM850	GPRS (4 Tx slots)	Back	0mm	Battery 1	189	836.4	Soft Holster	27.71	28.00	1.069	-0.14	0.297	0.318
	GSM850	GPRS (4 Tx slots)	Back	0mm	Battery 2	189	836.4	Soft Holster	27.71	28.00	1.069	-0.11	0.258	0.276
	GSM850	GPRS (4 Tx slots)	Back	0mm	Battery 3	189	836.4	Soft Holster	27.71	28.00	1.069	-0.11	0.273	0.292
	GSM850	GPRS (4 Tx slots)	Back	0mm	Battery 1	189	836.4	Wearable Wrist	27.71	28.00	1.069	-0.17	0.207	0.221
	GSM1900	GPRS (4 Tx slots)	Front	0mm	Battery 1	512	1850.2	Soft Holster	25.10	25.50	1.096	-0.12	0.420	0.461
	GSM1900	GPRS (4 Tx slots)	Back	0mm	Battery 1	512	1850.2	Soft Holster	25.10	25.50	1.096	0.09	0.230	0.252
	GSM1900	GPRS (4 Tx slots)	Front	0mm	Battery 2	512	1850.2	Soft Holster	25.10	25.50	1.096	0.02	0.380	0.417
29	GSM1900	GPRS (4 Tx slots)	Front	0mm	Battery 3	512	1850.2	Soft Holster	25.10	25.50	1.096	0.19	0.476	0.522
	GSM1900	GPRS (4 Tx slots)	Back	0mm	Battery 1	512	1850.2	Wearable Wrist	25.10	25.50	1.096	-0.07	0.322	0.353

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Accessories	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
30	WCDMA II	RMC 12.2Kbps	Front	0mm	Battery 1	9262	1852.4	Soft Holster	23.98	24.00	1.005	0.09	0.703	0.706
	WCDMA II	RMC 12.2Kbps	Back	0mm	Battery 1	9262	1852.4	Soft Holster	23.98	24.00	1.005	0.06	0.349	0.351
	WCDMA II	RMC 12.2Kbps	Front	0mm	Battery 2	9262	1852.4	Soft Holster	23.98	24.00	1.005	-0.11	0.686	0.689
	WCDMA II	RMC 12.2Kbps	Front	0mm	Battery 3	9262	1852.4	Soft Holster	23.98	24.00	1.005	0.03	0.641	0.644
	WCDMA II	RMC 12.2Kbps	Back	0mm	Battery 1	9262	1852.4	Wearable Wrist	23.98	24.00	1.005	0.04	0.293	0.294
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 1	1312	1712.4	Soft Holster	24.49	24.50	1.002	-0.14	0.894	0.896
31	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 1	1413	1732.6	Soft Holster	24.30	24.50	1.047	-0.08	0.942	0.986
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 1	1513	1752.6	Soft Holster	24.41	24.50	1.021	-0.05	0.920	0.939
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Battery 1	1312	1712.4	Soft Holster	24.49	24.50	1.002	0.07	0.466	0.467
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 2	1413	1732.6	Soft Holster	24.30	24.50	1.047	-0.05	0.824	0.863
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 3	1413	1732.6	Soft Holster	24.30	24.50	1.047	0.02	0.797	0.835
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Battery 1	1413	1732.6	Wearable Wrist	24.30	24.50	1.047	-0.06	0.384	0.402
	WCDMA V	RMC 12.2Kbps	Front	0mm	Battery 1	4132	826.4	Soft Holster	25.30	25.50	1.047	-0.02	0.351	0.368
	WCDMA V	RMC 12.2Kbps	Back	0mm	Battery 1	4132	826.4	Soft Holster	25.30	25.50	1.047	-0.1	0.358	0.375
32	WCDMA V	RMC 12.2Kbps	Back	0mm	Battery 2	4132	826.4	Soft Holster	25.30	25.50	1.047	-0.13	0.400	0.419
	WCDMA V	RMC 12.2Kbps	Back	0mm	Battery 3	4132	826.4	Soft Holster	25.30	25.50	1.047	-0.08	0.311	0.326
	WCDMA V	RMC 12.2Kbps	Back	0mm	Battery 2	4132	826.4	Wearable Wrist	25.30	25.50	1.047	-0.13	0.346	0.362



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Accessories	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
33	LTE Band 2	20M	QPSK	1	0	Front	0mm	Battery 1	18700	1860	Soft Holster	23.87	24.50	1.156	0.01	0.582	0.673
	LTE Band 2	20M	QPSK	50	0	Front	0mm	Battery 1	18700	1860	Soft Holster	22.91	23.50	1.146	0.06	0.466	0.534
	LTE Band 2	20M	QPSK	1	0	Back	0mm	Battery 1	18700	1860	Soft Holster	23.87	24.50	1.156	0.04	0.353	0.408
	LTE Band 2	20M	QPSK	50	0	Back	0mm	Battery 1	18700	1860	Soft Holster	22.91	23.50	1.146	0.02	0.284	0.325
	LTE Band 2	20M	QPSK	1	0	Front	0mm	Battery 2	18700	1860	Soft Holster	23.87	24.50	1.156	0.02	0.536	0.620
	LTE Band 2	20M	QPSK	1	0	Front	0mm	Battery 3	18700	1860	Soft Holster	23.87	24.50	1.156	0	0.549	0.635
	LTE Band 2	20M	QPSK	1	0	Back	0mm	Battery 1	18700	1860	Wearable Wrist	23.87	24.50	1.156	0.01	0.245	0.283
34	LTE Band 4	20M	QPSK	1	0	Front	0mm	Battery 1	20175	1732.5	Soft Holster	24.45	24.50	1.012	-0.05	0.798	0.807
	LTE Band 4	20M	QPSK	50	0	Front	0mm	Battery 1	20175	1732.5	Soft Holster	22.93	23.50	1.140	-0.01	0.638	0.727
	LTE Band 4	20M	QPSK	100	0	Front	0mm	Battery 1	20175	1732.5	Soft Holster	22.92	23.50	1.143	0.01	0.643	0.735
	LTE Band 4	20M	QPSK	1	0	Back	0mm	Battery 1	20175	1732.5	Soft Holster	24.45	24.50	1.012	-0.06	0.422	0.427
	LTE Band 4	20M	QPSK	50	0	Back	0mm	Battery 1	20175	1732.5	Soft Holster	22.93	23.50	1.140	0.07	0.326	0.372
	LTE Band 4	20M	QPSK	1	0	Front	0mm	Battery 2	20175	1732.5	Soft Holster	24.45	24.50	1.012	-0.05	0.788	0.797
	LTE Band 4	20M	QPSK	1	0	Front	0mm	Battery 3	20175	1732.5	Soft Holster	24.45	24.50	1.012	-0.03	0.788	0.797
	LTE Band 4	20M	QPSK	1	0	Back	0mm	Battery 1	20175	1732.5	Wearable Wrist	24.45	24.50	1.012	-0.17	0.606	0.613
	LTE Band 5	10M	QPSK	1	0	Front	0mm	Battery 1	20525	836.5	Soft Holster	24.81	25.00	1.045	-0.02	0.281	0.294
	LTE Band 5	10M	QPSK	25	0	Front	0mm	Battery 1	20525	836.5	Soft Holster	23.90	24.00	1.023	-0.04	0.223	0.228
	LTE Band 5	10M	QPSK	1	0	Back	0mm	Battery 1	20525	836.5	Soft Holster	24.81	25.00	1.045	-0.1	0.307	0.321
	LTE Band 5	10M	QPSK	25	0	Back	0mm	Battery 1	20525	836.5	Soft Holster	23.90	24.00	1.023	-0.1	0.252	0.258
	LTE Band 5	10M	QPSK	1	0	Back	0mm	Battery 2	20525	836.5	Soft Holster	24.81	25.00	1.045	-0.15	0.320	0.334
	LTE Band 5	10M	QPSK	1	0	Back	0mm	Battery 3	20525	836.5	Soft Holster	24.81	25.00	1.045	-0.15	0.318	0.332
35	LTE Band 5	10M	QPSK	1	0	Back	0mm	Battery 2	20525	836.5	Wearable Wrist	24.81	25.00	1.045	-0.17	0.393	0.411
	LTE Band 7	20M	QPSK	1	99	Front	0mm	Battery 1	21100	2535	Soft Holster	23.69	24.00	1.074	-0.17	0.481	0.517
	LTE Band 7	20M	QPSK	50	24	Front	0mm	Battery 1	21100	2535	Soft Holster	22.56	23.00	1.107	0	0.394	0.436
36	LTE Band 7	20M	QPSK	1	99	Back	0mm	Battery 1	21100	2535	Soft Holster	23.69	24.00	1.074	-0.11	0.495	0.532
	LTE Band 7	20M	QPSK	50	24	Back	0mm	Battery 1	21100	2535	Soft Holster	22.56	23.00	1.107	0	0.434	0.480
	LTE Band 7	20M	QPSK	1	99	Back	0mm	Battery 2	21100	2535	Soft Holster	23.69	24.00	1.074	-0.07	0.491	0.527
	LTE Band 7	20M	QPSK	1	99	Back	0mm	Battery 3	21100	2535	Soft Holster	23.69	24.00	1.074	-0.1	0.375	0.403
	LTE Band 7	20M	QPSK	1	99	Back	0mm	Battery 1	21100	2535	Wearable Wrist	23.69	24.00	1.074	-0.03	0.480	0.516

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Accessories	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	0	Front	0mm	Battery 1	40620	2593	Soft Holster	24.14	24.50	1.086	62.9	1.006	-0.05	0.291	0.318
	LTE Band 41	20M	QPSK	50	0	Front	0mm	Battery 1	40620	2593	Soft Holster	23.34	23.50	1.038	62.9	1.006	-0.09	0.281	0.293
	LTE Band 41	20M	QPSK	1	0	Back	0mm	Battery 1	40620	2593	Soft Holster	24.14	24.50	1.086	62.9	1.006	-0.14	0.312	0.341
	LTE Band 41	20M	QPSK	50	0	Back	0mm	Battery 1	40620	2593	Soft Holster	23.34	23.50	1.038	62.9	1.006	-0.15	0.257	0.268
37	LTE Band 41	20M	QPSK	1	0	Back	0mm	Battery 2	40620	2593	Soft Holster	24.14	24.50	1.086	62.9	1.006	-0.03	0.317	0.346
	LTE Band 41	20M	QPSK	1	0	Back	0mm	Battery 3	40620	2593	Soft Holster	24.14	24.50	1.086	62.9	1.006	-0.11	0.253	0.277
	LTE Band 41	20M	QPSK	1	0	Back	0mm	Battery 2	40620	2593	Wearable Wrist	24.14	24.50	1.086	62.9	1.006	-0.08	0.269	0.294



<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Accessories	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	0mm	Battery 1	6	2437	Soft Holster	19.65	20.00	1.084	99.19	1.008	0.04	0.061	0.067
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Battery 1	6	2437	Soft Holster	19.65	20.00	1.084	99.19	1.008	-0.09	0.158	0.173
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Battery 2	6	2437	Soft Holster	19.65	20.00	1.084	99.19	1.008	0.06	0.147	0.161
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Battery 3	6	2437	Soft Holster	19.65	20.00	1.084	99.19	1.008	-0.03	0.138	0.151
38	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Battery 1	6	2437	Wearable Wrist	19.65	20.00	1.084	99.19	1.008	-0.06	0.277	0.303
	WLAN5GHz	802.11a 6Mbps	Front	0mm	Battery 1	52	5260	Soft Holster	20.11	20.50	1.094	98.45	1.016	0.08	0.140	0.156
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	52	5260	Soft Holster	20.11	20.50	1.094	98.45	1.016	-0.09	0.478	0.531
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 2	52	5260	Soft Holster	20.11	20.50	1.094	98.45	1.016	-0.05	0.463	0.515
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 3	52	5260	Soft Holster	20.11	20.50	1.094	98.45	1.016	-0.03	0.439	0.488
39	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	52	5260	Wearable Wrist	20.11	20.50	1.094	98.45	1.016	-0.01	0.877	0.975
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	64	5320	Wearable Wrist	20.11	20.50	1.094	98.45	1.016	0.06	0.851	0.946
	WLAN5GHz	802.11a 6Mbps	Front	0mm	Battery 1	116	5580	Soft Holster	19.11	19.50	1.094	98.45	1.016	-0.07	0.181	0.201
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	116	5580	Soft Holster	19.11	19.50	1.094	98.45	1.016	-0.09	0.538	0.598
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 2	116	5580	Soft Holster	19.11	19.50	1.094	98.45	1.016	0.09	0.521	0.579
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 3	116	5580	Soft Holster	19.11	19.50	1.094	98.45	1.016	0	0.488	0.542
40	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	116	5580	Wearable Wrist	19.11	19.50	1.094	98.45	1.016	-0.1	0.880	0.978
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	144	5720	Wearable Wrist	19.11	19.50	1.094	98.45	1.016	0.04	0.843	0.937
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	0mm	Battery 1	155	5775	Soft Holster	17.91	18.00	1.021	92.68	1.079	0.07	0.120	0.132
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Battery 1	155	5775	Soft Holster	17.91	18.00	1.021	92.68	1.079	-0.14	0.302	0.333
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Battery 2	155	5775	Soft Holster	17.91	18.00	1.021	92.68	1.079	0.08	0.279	0.307
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Battery 3	155	5775	Soft Holster	17.91	18.00	1.021	92.68	1.079	0.03	0.248	0.273
41	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Battery 1	155	5775	Wearable Wrist	17.91	18.00	1.021	92.68	1.079	-0.07	0.682	0.751



15.4 Product Specific SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 1	1312	1712.4	24.49	24.50	1.002	-0.07	2.370	2.375
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 1	1413	1732.6	24.30	24.50	1.047	-0.07	2.400	2.513
42	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 1	1513	1752.6	24.41	24.50	1.021	-0.02	2.540	2.593

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	0mm	Battery 1	18700	1860	23.87	24.50	1.156	-0.12	2.310	2.671
	LTE Band 2	20M	QPSK	1	0	Front	0mm	Battery 1	18900	1880	23.75	24.50	1.189	-0.14	2.280	2.710
43	LTE Band 2	20M	QPSK	1	0	Front	0mm	Battery 1	19100	1900	23.59	24.50	1.233	-0.1	2.330	2.873
44	LTE Band 4	20M	QPSK	1	0	Front	0mm	Battery 1	20175	1732.5	24.45	24.50	1.012	-0.03	2.220	2.246

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5GHz	802.11a 6Mbps	Front	0mm	Battery 1	52	5260	20.11	20.50	1.094	98.45	1.016	0.01	0.309	0.343
45	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	52	5260	20.11	20.50	1.094	98.45	1.016	-0.14	1.370	1.523
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Battery 1	52	5260	20.11	20.50	1.094	98.45	1.016	0.06	1.140	1.267
	WLAN5GHz	802.11a 6Mbps	Top Side	0mm	Battery 1	52	5260	20.11	20.50	1.094	98.45	1.016	-0.05	0.086	0.096
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 2	52	5260	20.11	20.50	1.094	98.45	1.016	-0.01	1.300	1.445
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 3	52	5260	20.11	20.50	1.094	98.45	1.016	0.1	1.230	1.367
	WLAN5GHz	802.11a 6Mbps	Front	0mm	Battery 1	116	5580	19.11	19.50	1.094	98.45	1.016	-0.01	0.454	0.505
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	116	5580	19.11	19.50	1.094	98.45	1.016	0.04	1.810	2.012
46	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	144	5720	19.11	19.50	1.094	98.45	1.016	0.13	1.830	2.034
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Battery 1	116	5580	19.11	19.50	1.094	98.45	1.016	0.09	1.540	1.712
	WLAN5GHz	802.11a 6Mbps	Top Side	0mm	Battery 1	116	5580	19.11	19.50	1.094	98.45	1.016	0.09	0.120	0.133
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 2	144	5720	19.11	19.50	1.094	98.45	1.016	-0.08	1.720	1.912
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 3	144	5720	19.11	19.50	1.094	98.45	1.016	0	1.590	1.767



15.5 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Battery	Power Reduction	Ch.	Freq. (MHz)	Accessories	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	Battery 2	-	1513	1752.6	-	24.41	24.50	1.021	-	-	0.07	1.030	-	1.052
2nd	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	Battery 2	-	1513	1752.6	-	24.41	24.50	1.021	-	-	0.01	1.000	1.03	1.021
1st	LTE Band 7	20M_QPSK_1_99	Right Cheek	0mm	Battery 1	-	21350	2560	-	23.66	24.00	1.081	-	-	-0.16	1.180	-	1.276
2nd	LTE Band 7	20M_QPSK_1_99	Right Cheek	0mm	Battery 1	-	21350	2560	-	23.66	24.00	1.081	-	-	-0.09	1.160	1.37	1.254
1st	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Battery 1	-	11	2462	-	19.65	20.00	1.084	99.19	1.008	-0.09	1.070	-	1.169
2nd	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Battery 1	-	11	2462	-	19.65	20.00	1.084	99.19	1.008	0.07	1.050	1.02	1.147
1st	GSM1900	GPRS (4 Tx slots)	Front	10mm	Battery 1	OFF	512	1850.2	-	25.10	25.50	1.096	-	-	0.09	1.060	-	1.162
2nd	GSM1900	GPRS (4 Tx slots)	Front	10mm	Battery 1	OFF	512	1850.2	-	25.10	25.50	1.096	-	-	0.01	1.010	1.05	1.107
1st	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	Battery 1	-	159	5795	-	17.71	18.00	1.069	96.37	1.038	-0.18	1.090	-	1.210
2nd	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	Battery 1	-	159	5795	-	17.71	18.00	1.069	96.37	1.038	0.14	1.060	1.03	1.176
1st	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	-	52	5260	Wearable Wrist	20.11	20.50	1.094	98.45	1.016	-0.01	0.877	-	0.975
2nd	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	-	52	5260	Wearable Wrist	20.11	20.50	1.094	98.45	1.016	0.06	0.848	1.03	0.943
1st	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	-	116	5580	Wearable Wrist	19.11	19.50	1.094	98.45	1.016	-0.1	0.880	-	0.978
2nd	WLAN5GHz	802.11a 6Mbps	Back	0mm	Battery 1	-	116	5580	Wearable Wrist	19.11	19.50	1.094	98.45	1.016	0.06	0.830	1.06	0.923

No.	Band	Mode	Test Position	Gap (mm)	Battery	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Ratio	Reported 10g SAR (W/kg)
1st	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 1	1513	1752.6	24.41	24.50	1.021	-0.02	2.540		2.593
2nd	WCDMA IV	RMC 12.2Kbps	Front	0mm	Battery 1	1513	1752.6	24.41	24.50	1.021	-0.04	2.510	1.01	2.563
1st	LTE Band 2	20M_QPSK_1_0	Front	0mm	Battery 1	19100	1900	23.59	24.50	1.233	-0.1	2.330		2.873
2nd	LTE Band 2	20M_QPSK_1_0	Front	0mm	Battery 1	19100	1900	23.59	24.50	1.233	-0.07	2.300	1.01	2.836

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8W/kg$.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45W/kg$, only one repeated measurement is required.
3. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. The ratio is the difference in percentage between original and repeated *measured* SAR.
5. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

16. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Head	Body-worn	Hotspot	Product Specific
1.	WWAN + 2.4GHz WLAN	Yes	Yes	Yes	Yes
2.	WWAN + Bluetooth	Yes	Yes	Yes	Yes
3.	WWAN + 5GHz WLAN	Yes	Yes	Yes	Yes

General Note:

1. This device WLAN 2.4GHz / 5.2GHz / 5.8GHz supports Hotspot operation and Bluetooth support tethering applications.
2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. All licensed modes share the same antenna part and cannot transmit simultaneously
4. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
5. The Scaled SAR summation is calculated based on the same configuration and test position.
6. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
 - v) The SPLSR calculated results please refer to section 16.5.
7. For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v06 based on the formula below.
 - i) $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - ii) When the minimum separation distance is < 5mm, the distance is used 5mm to determine SAR test exclusion.
 - iii) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Bluetooth Max Power	Exposure Position	Head	Hotspot	Body worn
	Test separation	0 mm	10 mm	0 mm
2.0 dBm	Estimated SAR (W/kg)	0.297 W/kg	0.149 W/kg	0.297 W/kg



16.1 Head Exposure Conditions

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	SPLSR	Case No	SPLSR	Case No	
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth								
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	Estimated 1g SAR (W/kg)								
GSM	GSM850	Right Cheek	0.523	0.624	0.499	0.297	1.147	1.022	0.820				
		Right Tilted	0.300	0.460	0.313	0.297	0.760	0.613	0.597				
		Left Cheek	0.459	1.169	0.851	0.297	1.628	1.310	0.756	0.03	Case 1		
		Left Tilted	0.217	0.686	0.510	0.297	0.903	0.727	0.514				
	GSM1900	Right Cheek	0.799	0.624	0.499	0.297	1.423	1.298	1.096				
		Right Tilted	0.258	0.460	0.313	0.297	0.718	0.571	0.555				
		Left Cheek	0.758	1.169	0.851	0.297	1.927	1.609	1.055	0.03	Case 1	0.02	Case 1
		Left Tilted	0.192	0.686	0.510	0.297	0.878	0.702	0.489				
WCDMA	WCDMA II	Right Cheek	0.795	0.624	0.499	0.297	1.419	1.294	1.092				
		Right Tilted	0.272	0.460	0.313	0.297	0.732	0.585	0.569				
		Left Cheek	0.824	1.169	0.851	0.297	1.993	1.675	1.121	0.03	Case 1	0.02	Case 1
		Left Tilted	0.262	0.686	0.510	0.297	0.948	0.772	0.559				
	WCDMA IV	Right Cheek	1.052	0.624	0.499	0.297	1.676	1.551	1.349	0.03	Case 2		
		Right Tilted	0.211	0.460	0.313	0.297	0.671	0.524	0.508				
		Left Cheek	0.674	1.169	0.851	0.297	1.843	1.525	0.971	0.03	Case 1		
		Left Tilted	0.162	0.686	0.510	0.297	0.848	0.672	0.459				
	WCDMA V	Right Cheek	0.646	0.624	0.499	0.297	1.270	1.145	0.943				
		Right Tilted	0.386	0.460	0.313	0.297	0.846	0.699	0.683				
		Left Cheek	0.777	1.169	0.851	0.297	1.946	1.628	1.074	0.04	Case 1	0.03	Case 1
		Left Tilted	0.476	0.686	0.510	0.297	1.162	0.986	0.773				
LTE	LTE Band 2	Right Cheek	0.894	0.624	0.499	0.297	1.518	1.393	1.191				
		Right Tilted	0.258	0.460	0.313	0.297	0.718	0.571	0.555				
		Left Cheek	0.765	1.169	0.851	0.297	1.934	1.616	1.062	0.03	Case 1	0.02	Case 1
		Left Tilted	0.302	0.686	0.510	0.297	0.988	0.812	0.599				
	LTE Band 4	Right Cheek	0.902	0.624	0.499	0.297	1.526	1.401	1.199				
		Right Tilted	0.130	0.460	0.313	0.297	0.590	0.443	0.427				
		Left Cheek	0.551	1.169	0.851	0.297	1.720	1.402	0.848	0.03	Case 1		
		Left Tilted	0.161	0.686	0.510	0.297	0.847	0.671	0.458				
	LTE Band 5	Right Cheek	0.622	0.624	0.499	0.297	1.246	1.121	0.919				
		Right Tilted	0.360	0.460	0.313	0.297	0.820	0.673	0.657				
		Left Cheek	0.677	1.169	0.851	0.297	1.846	1.528	0.974	0.03	Case 1		
		Left Tilted	0.381	0.686	0.510	0.297	1.067	0.891	0.678				
	LTE Band 7	Right Cheek	1.276	0.624	0.499	0.297	1.900	1.775	1.573	0.04	Case 2	0.04	Case 2
		Right Tilted	0.214	0.460	0.313	0.297	0.674	0.527	0.511				
		Left Cheek	0.687	1.169	0.851	0.297	1.856	1.538	0.984	0.04	Case 1		
		Left Tilted	0.289	0.686	0.510	0.297	0.975	0.799	0.586				
	LTE Band 41	Right Cheek	1.037	0.624	0.499	0.297	1.661	1.536	1.334	0.03	Case 2		
		Right Tilted	0.267	0.460	0.313	0.297	0.727	0.580	0.564				
		Left Cheek	0.516	1.169	0.851	0.297	1.685	1.367	0.813	0.04	Case 1		
		Left Tilted	0.324	0.686	0.510	0.297	1.010	0.834	0.621				



16.2 Body Exposure Conditions

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	SPLSR	Case No	SPLSR	Case No	
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth								
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	Estimated 1g SAR (W/kg)								
GSM	GSM850	Front	0.424	0.357	0.172	0.149	0.781	0.596	0.573				
		Back	0.453	0.634	1.232	0.149	1.087	1.685	0.602	0.02	Case 3		
		Left side	0.295				0.295	0.295	0.295				
		Right side	0.284	0.467	0.602	0.149	0.751	0.886	0.433				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.340				0.340	0.340	0.340				
	GSM1900	Front	1.162	0.357	0.172	0.149	1.519	1.334	1.311				
		Back	0.751	0.634	1.232	0.149	1.385	1.983	0.900	0.02	Case 3		
		Left side	0.249				0.249	0.249	0.249				
		Right side	0.516	0.467	0.602	0.149	0.983	1.118	0.665				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.247				0.247	0.247	0.247				
WCDMA	WCDMA II	Front	0.959	0.357	0.172	0.149	1.316	1.131	1.108				
		Back	0.587	0.634	1.232	0.149	1.221	1.819	0.736	0.02	Case 3		
		Left side	0.197				0.197	0.197	0.197				
		Right side	0.301	0.467	0.602	0.149	0.768	0.903	0.450				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.280				0.280	0.280	0.280				
	WCDMA IV	Front	0.976	0.357	0.172	0.149	1.333	1.148	1.125				
		Back	0.492	0.634	1.232	0.149	1.126	1.724	0.641	0.02	Case 3		
		Left side	0.100				0.100	0.100	0.100				
		Right side	0.279	0.467	0.602	0.149	0.746	0.881	0.428				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.207				0.207	0.207	0.207				
	WCDMA V	Front	0.597	0.357	0.172	0.149	0.954	0.769	0.746				
		Back	0.541	0.634	1.232	0.149	1.175	1.773	0.690	0.02	Case 3		
		Left side	0.315				0.315	0.315	0.315				
		Right side	0.276	0.467	0.602	0.149	0.743	0.878	0.425				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.343				0.343	0.343	0.343				
LTE	LTE Band 2	Front	1.095	0.357	0.172	0.149	1.452	1.267	1.244				
		Back	0.697	0.634	1.232	0.149	1.331	1.929	0.846	0.02	Case 3		
		Left side	0.237				0.237	0.237	0.237				
		Right side	0.472	0.467	0.602	0.149	0.939	1.074	0.621				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.387				0.387	0.387	0.387				
	LTE Band 4	Front	0.940	0.357	0.172	0.149	1.297	1.112	1.089				
		Back	0.430	0.634	1.232	0.149	1.064	1.662	0.579	0.02	Case 3		
		Left side	0.100				0.100	0.100	0.100				
		Right side	0.260	0.467	0.602	0.149	0.727	0.862	0.409				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.177				0.177	0.177	0.177				
	LTE Band 5	Front	0.638	0.357	0.172	0.149	0.995	0.810	0.787				
		Back	0.620	0.634	1.232	0.149	1.254	1.852	0.769	0.04	Case 3		
		Left side	0.371				0.371	0.371	0.371				
		Right side	0.341	0.467	0.602	0.149	0.808	0.943	0.490				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.351				0.351	0.351	0.351				
	LTE Band 7	Front	0.666	0.357	0.172	0.149	1.023	0.838	0.815				
		Back	0.761	0.634	1.232	0.149	1.395	1.993	0.910	0.03	Case 3		



FCC SAR TEST REPORT

Report No. : FA010316

		Left side	0.067				0.067	0.067	0.067				
		Right side	0.566	0.467	0.602	0.149	1.033	1.168	0.715				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.735				0.735	0.735	0.735				
	LTE Band 41	Front	0.516	0.357	0.172	0.149	0.873	0.688	0.665				
		Back	0.732	0.634	1.232	0.149	1.366	1.964	0.881	0.03	Case 3		
		Left side	0.082				0.082	0.082	0.082				
		Right side	0.532	0.467	0.602	0.149	0.999	1.134	0.681				
		Top side		0.370	0.135	0.149	0.370	0.135	0.149				
		Bottom side	0.681				0.681	0.681	0.681				

16.3 Body-Worn Accessory Exposure Conditions

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	SPLSR	Case No	
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth						
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	Estimated 1g SAR (W/kg)						
GSM	GSM850	Front	0.274	0.067	0.201	0.297	0.341	0.475	0.571		
		Back	0.318	0.303	0.978	0.297	0.621	1.296	0.615		
	GSM1900	Front	0.522	0.067	0.201	0.297	0.589	0.723	0.819		
		Back	0.353	0.303	0.978	0.297	0.656	1.331	0.650		
WCDMA	WCDMA II	Front	0.706	0.067	0.201	0.297	0.773	0.907	1.003		
		Back	0.351	0.303	0.978	0.297	0.654	1.329	0.648		
	WCDMA IV	Front	0.986	0.067	0.201	0.297	1.053	1.187	1.283		
		Back	0.467	0.303	0.978	0.297	0.770	1.445	0.764		
	WCDMA V	Front	0.368	0.067	0.201	0.297	0.435	0.569	0.665		
		Back	0.419	0.303	0.978	0.297	0.722	1.397	0.716		
LTE	LTE Band 2	Front	0.673	0.067	0.201	0.297	0.740	0.874	0.970		
		Back	0.408	0.303	0.978	0.297	0.711	1.386	0.705		
	LTE Band 4	Front	0.807	0.067	0.201	0.297	0.874	1.008	1.104		
		Back	0.613	0.303	0.978	0.297	0.916	1.591	0.910		
	LTE Band 5	Front	0.294	0.067	0.201	0.297	0.361	0.495	0.591		
		Back	0.411	0.303	0.978	0.297	0.714	1.389	0.708		
	LTE Band 7	Front	0.517	0.067	0.201	0.297	0.584	0.718	0.814		
		Back	0.532	0.303	0.978	0.297	0.835	1.510	0.829		
	LTE Band 41	Front	0.318	0.067	0.201	0.297	0.385	0.519	0.615		
		Back	0.346	0.303	0.978	0.297	0.649	1.324	0.643		

16.4 Product Specific Exposure Conditions


WWAN Band	Exposure Position	1	3	1+3 Summed 10g SAR (W/kg)	
		WWAN	5GHz WLAN		
		10g SAR (W/kg)	10g SAR (W/kg)		
WCDMA	WCDMA IV	Front	2.593	0.505	3.098
		Back		2.034	2.034
		Left side			0.000
		Right side		1.712	1.712
		Top side		0.133	0.133
		Bottom side			0.000
		LTE	LTE Band 2	Front	2.873
Back				2.034	2.034
Left side					0.000
Right side				1.712	1.712
Top side				0.133	0.133
Bottom side					0.000
LTE Band 4	Front			2.246	0.505
	Back			2.034	2.034
	Left side				0.000
	Right side			1.712	1.712
	Top side			0.133	0.133
	Bottom side				0.000

16.5 SPLSR Evaluation and Analysis


General Note:

- SPLSR = $(SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary
- The detail hotspot point for each transmitter in each exposure condition are showing as below figure and the minimum 3D distance for each sum combination is used for SPLSR analysis.


Case No.	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 1	GSM850	Left Cheek	0.459	0	44.21	-46.4	-3.42	76.0	1.63	0.03	Not required
	WLAN 2.4G		1.169	0	20.34	25.72	-1.16				
	GSM1900	Left Cheek	0.758	0	48.21	-59.41	-1.38	89.6	1.93	0.03	Not required
	WLAN 2.4G		1.169	0	20.34	25.72	-1.16				
	GSM1900	Left Cheek	0.758	0	48.21	-59.41	-1.38	89.9	1.61	0.02	Not required
	WLAN 5GHz		0.851	0	19.41	25.73	-1.41				
	WCDMA II	Left Cheek	0.824	0	48.72	-59.4	-1.31	89.7	1.99	0.03	Not required
	WLAN 2.4G		1.169	0	20.34	25.72	-1.16				
	WCDMA II	Left Cheek	0.824	0	48.72	-59.4	-1.31	90.0	1.68	0.02	Not required
	WLAN 5GHz		0.851	0	19.41	25.73	-1.41				
	WCDMA IV	Left Cheek	0.674	0	49.33	-58.31	-1.37	88.9	1.84	0.03	Not required
	WLAN 2.4G		1.169	0	20.34	25.72	-1.16				
	WCDMA V	Left Cheek	0.777	0	44.21	-46.4	-3.42	76.0	1.95	0.04	Not required
	WLAN 2.4G		1.169	0	20.34	25.72	-1.16				
	WCDMA V	Left Cheek	0.777	0	44.21	-46.4	-3.42	76.3	1.63	0.03	Not required
	WLAN 5G		0.851	0	19.41	25.73	-1.41				
	LTE Band 2	Left Cheek	0.765	0	49.3	-58.23	-1.31	88.8	1.93	0.03	Not required
	WLAN 2.4G		1.169	0	20.34	25.72	-1.16				
	LTE Band 2	Left Cheek	0.765	0	49.3	-58.23	-1.31	89.1	1.62	0.02	Not required
	WLAN 5GHz		0.851	0	19.41	25.73	-1.41				
	LTE Band 4	Left Cheek	0.551	0	50.26	-55.3	-2.63	86.4	1.72	0.03	Not required
	WLAN 2.4G		1.169	0	20.34	25.72	-1.16				
	LTE Band 5	Left Cheek	0.677	0	45.03	-45.01	-3.34	74.9	1.85	0.03	Not required
	WLAN 2.4G		1.169	0	20.34	25.72	-1.16				
LTE Band 7	Left Cheek	0.687	0	60.12	-24.77	-4.47	64.4	1.86	0.04	Not required	
WLAN 2.4G		1.169	0	20.34	25.72	-1.16					
LTE Band 41	Left Cheek	0.516	0	51.29	-16.7	-4.11	52.6	1.69	0.04	Not required	
WLAN 2.4G		1.169	0	20.34	25.72	-1.16					



Case No.	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 2	WCDMA IV	Right Cheek	1.052	0	52.07	59.91	-0.8	81.5	1.68	0.03	Not required
	WLAN 2.4G		0.624	0	14.24	-12.32	-1.32				
	LTE Band 7	Right Cheek	1.276	0	40.21	55.31	-4.83	72.5	1.90	0.04	Not required
	WLAN 2.4G		0.624	0	14.24	-12.32	-1.32				
	LTE Band 7	Right Cheek	1.276	0	40.21	55.31	-4.83	60.4	1.78	0.04	Not required
	WLAN 5GHz		0.499	0	-14.04	31.66	7.12				
	LTE Band 41	Right Cheek	1.037	0	39.76	56.49	-4.72	73.5	1.66	0.03	Not required
	WLAN 2.4G		0.624	0	14.24	-12.32	-1.32				



Case No.	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (cm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 3	GSM850	Back	0.453	0	15	-66	-1.2	128.4	1.69	0.02	Not required
	WLAN 5GHz		1.232	0	-35.6	52	-1.22				
	GSM1900	Back	0.751	0	9	-50.9	-2.18	112.2	1.98	0.02	Not required
	WLAN 5GHz		1.232	0	-35.6	52	-1.22				
	WCDMA II	Back	0.587	0	7.4	-51.7	-2.19	112.3	1.82	0.02	Not required
	WLAN 5GHz		1.232	0	-35.6	52	-1.22				
	WCDMA IV	Back	0.492	0	5.4	-47	-2.24	107.2	1.72	0.02	Not required
	WLAN 5GHz		1.232	0	-35.6	52	-1.22				
	WCDMA V	Back	0.541	0	15.2	-65.6	-1.2	128.1	1.77	0.02	Not required
	WLAN 5GHz		1.232	0	-35.6	52	-1.22				
	LTE Band 2	Back	0.697	0	5.8	-51.7	-2.23	111.7	1.93	0.02	Not required
	WLAN 5GHz		1.232	0	-35.6	52	-1.22				
	LTE Band 4	Back	0.43	0	7.4	-48.3	-2.24	109.1	1.66	0.02	Not required
	WLAN 5GHz		1.232	0	-35.6	52	-1.22				
	LTE Band 5	Back	0.62	0	-0.6	2	-1.67	61.0	1.85	0.04	Not required
	WLAN 5GHz		1.232	0	-35.6	52	-1.22				
	LTE Band 7	Back	0.761	0	-33.8	-56.8	-4.19	108.9	1.99	0.03	Not required
	WLAN 5GHz		1.232	0	-35.6	52	-1.22				
LTE Band 41	Back	0.732	0	-35.4	-58	-4.15	110.0	1.96	0.03	Not required	
WLAN 5GHz		1.232	0	-35.6	52	-1.22					



Test Engineer : Ginger Chiang, Jack Yang, Randy Lin, Willy Yu and Ray Sun



17. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [11] FCC KDB 941225 D07 v01r02, "SAR Evaluation Procedures for UMPC Mini-Tablet Devices", Oct 2015.
- [12] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [13] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.