



FCC RF Test Report

APPLICANT : Zebra Technologies Corporation
EQUIPMENT : Touch computer
BRAND NAME : Zebra
MODEL NAME : TC75EK
FCC ID : UZ7TC75EK
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jul. 28, 2016 and completely tested on Sep. 07, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY 3
SUMMARY OF TEST RESULT 4
1 GENERAL DESCRIPTION 5
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 7
1.5 Modification of EUT 7
1.6 Emission Designator 8
1.7 Testing Location 10
1.8 Applicable Standards 10
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 11
2.1 Test Mode 11
2.2 Connection Diagram of Test System 14
2.3 Support Unit used in test configuration and system 14
2.4 Measurement Results Explanation Example 14
2.5 Frequency List of Low/Middle/High Channels 15
3 CONDUCTED TEST ITEMS 19
3.1 Measuring Instruments 19
3.2 Test Setup 19
3.3 Test Result of Conducted Test 19
3.4 Conducted Output Power 20
3.5 Peak-to-Average Ratio 21
3.6 Occupied Bandwidth 22
3.7 Conducted Band Edge 23
3.8 Conducted Spurious Emission 25
3.9 Frequency Stability 26
4 RADIATED TEST ITEMS 27
4.1 Measuring Instruments 27
4.2 Test Setup 27
4.3 Test Result of Radiated Test 27
4.4 Effective Radiated Power and Effective Isotropic Radiated Power 28
4.5 Radiated Spurious Emission 30
5 LIST OF MEASURING EQUIPMENT 31
6 UNCERTAINTY OF EVALUATION 32
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG672834B	Rev. 01	Initial issue of report	Sep. 29, 2016
FG672834B	Rev. 02	Revising the specification of accessories.	Oct. 04, 2016
FG672834B	Rev. 03	Revising the Adapter information in specification of accessories.	Oct. 07, 2016



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(c)(2)(4) §27.53(g) §27.53(h)	Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 17) (Band 25) (Band 26)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(c)(2) §27.53(g) §27.53(h)	Conducted Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 17) (Band 25) (Band 26)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§22.913(a)(2)	Effective Radiated Power (Band 5) (Band 26)	ERP < 7 Watt	PASS	-
	§27.50(b)(10) §27.50(c)(10)	Effective Radiated Power (Band 12) (Band 13) (Band 17)	ERP < 3 Watt		
	§24.232(c) §27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 2)(Band 25)	EIRP < 2Watt		
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	EIRP < 1Watt		
4.5	§2.1053 §22.917(a) §24.238(a) §27.53(c)(2) §27.53(f) §27.53(g) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 17) (Band 25) (Band 26)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 9.49 dB at 1568.000 MHz



1 General Description

1.1 Applicant

Zebra Technologies Corporation
1 Zebra Plaza Holtsville, NY 11742

1.2 Manufacturer

Wistron Corporation
21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist, New Taipei City 221, Taiwan R.O.C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Touch computer
Brand Name	Zebra
Model Name	TC75EK
FCC ID	UZ7TC75EK
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DV
SW Version	Android version 6.0.1
FW Version	91-10-01-MG-00
MFD	14JUL16
EUT Stage	Engineering Sample



Specification of Accessories				
AC Adapter	Brand Name	Zebra	Part Number	PWR-BUA5V16W0WW
Snap-On USB/Charge Cable	Brand Name	Symbol	Part Number	CBL-TC7X-USB1-01
Snap-On Charging Cable Cup	Brand Name	Symbol	Part Number	CHG-TC7X-CBL1-01
Battery	Brand Name	Zebra	Part Number	BT-000318-01
Earphone 1	Brand Name	Zebra	Part Number	HDST-35MM-PTVP-01
Earphone 2	Brand Name	Zebra	Part Number	HS2100-OTH
Earphone 3	Brand Name	Zebra	Part Number	HS3100-OTH
Snap-on 3.5MM Audio Nugget	Brand Name	Symbol	Part Number	ADP-TC7X-AUD35-01
3.5mm Jack 43"(1.1m) Standard Cable	Brand Name	Zebra	Part Number	CBL-HS2100-3MS1-01
Soft Holster	Brand Name	Zebra	Part Number	SG-TC7X-HLSTR1-01
Rigid Holster	Brand Name	Zebra	Part Number	SG-TC7X-RHLSTR1-01
Power Cord	Brand Name	LOROM	Part Number	50-16000-182R
Cable line	Brand Name	Zebra	Part Number	CBL-DC-383A1-01



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 17 : 706.5 MHz ~ 713.5 MHz LTE Band 25 : 1850.7MHz ~ 1914.3 MHz LTE Band 26 : 824.7MHz ~ 848.3 MHz
Rx Frequency	LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 13 : 748.5 MHz ~ 753.5 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz LTE Band 25 : 1930.7MHz ~ 1994.3 MHz LTE Band 26 : 869.7MHz ~ 893.3MHz
Bandwidth	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 12 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 13 : 5MHz / 10MHz LTE Band 17 : 5MHz / 10MHz LTE Band 25 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 26 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
Maximum Output Power to Antenna	LTE Band 2 : 23.83 dBm LTE Band 4 : 24.34 dBm LTE Band 5 : 24.00 dBm LTE Band 13 : 24.12 dBm LTE Band 12 : 24.37 dBm LTE Band 17 : 24.11 dBm LTE Band 25 : 23.85 dBm LTE Band 26 : 24.28 dBm
Type of Modulation	QPSK / 16QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Emission Designator

LTE Band 2		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1850.7 ~ 1909.3	1M10G7D	-	0.2864	1M10W7D	-	0.2328
3	1851.5 ~ 1908.5	2M72G7D	-	0.2673	2M75W7D	-	0.2234
5	1852.5 ~ 1907.5	4M49G7D	-	0.3199	4M51W7D	-	0.2270
10	1855.0 ~ 1905.0	9M09G7D	0.0067	0.3105	9M01W7D	-	0.2218
15	1857.5 ~ 1902.5	13M4G7D	-	0.3524	13M5W7D	-	0.2244
20	1860.0 ~ 1900.0	18M4G7D	-	0.3296	18M3W7D	-	0.2506
LTE Band 25		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1850.7 ~ 1914.3	1M09G7D	-	0.3006	1M09W7D	-	0.2472
3	1851.5 ~ 1913.5	2M74G7D	-	0.2851	2M73W7D	-	0.2328
5	1852.5 ~ 1912.5	4M50G7D	-	0.3221	4M50W7D	-	0.2483
10	1855.0 ~ 1910.0	9M07G7D	0.0077	0.3381	9M07W7D	-	0.2483
15	1857.5 ~ 1907.5	13M4G7D	-	0.2917	13M4W7D	-	0.2350
20	1860.0 ~ 1905.0	18M2G7D	-	0.3289	18M2W7D	-	0.2399
LTE Band 4		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1710.7 ~ 1754.3	1M10G7D	-	0.3908	1M10W7D	-	0.3243
3	1711.5 ~ 1753.5	2M72G7D	-	0.3926	2M73W7D	-	0.3083
5	1712.5 ~ 1752.5	4M49G7D	-	0.3926	4M50W7D	-	0.3228
10	1715.0 ~ 1750.0	9M05G7D	0.0063	0.4365	9M05W7D	-	0.3420
15	1717.5 ~ 1747.5	13M5G7D	-	0.4335	13M4W7D	-	0.3243
20	1720.0 ~ 1745.0	18M3G7D	-	0.3698	18M4W7D	-	0.3639
LTE Band 5		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	824.7 ~ 848.3	1M10G7D	-	0.1138	1M10W7D	-	0.0857
3	825.5 ~ 847.5	2M72G7D	-	0.1033	2M73W7D	-	0.0800
5	826.5 ~ 846.5	4M50G7D	-	0.1130	4M50W7D	-	0.0793
10	829.0 ~ 844.0	9M01G7D	0.0105	0.1099	9M03W7D	-	0.0822



LTE Band 12		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	699.7 ~ 715.3	1M10G7D	-	0.1242	1M10W7D	-	0.0877
3	700.5 ~ 714.5	2M72G7D	-	0.1109	2M73W7D	-	0.0855
5	701.5 ~ 713.5	4M51G7D	-	0.1127	4M48W7D	-	0.0839
10	704.0 ~ 711.0	9M05G7D	0.0081	0.1122	9M07W7D	-	0.0824
LTE Band 13		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
5	779.5 ~ 784.5	4M50G7D	-	0.0927	4M49W7D	-	0.0661
10	782.0	8M95G7D	0.0118	0.0912	8M99W7D	-	0.0625
LTE Band 17		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
5	706.5 ~ 713.5	4M50G7D	-	0.1109	4M49W7D	-	0.0755
10	709.0 ~ 711.0	9M03G7D	0.0104	0.1005	9M03W7D	-	0.0780
LTE Band 26		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	824.7 ~ 848.3	1M10G7D	-	0.1086	1M10W7D	-	0.0818
3	825.5 ~ 847.5	2M72G7D	-	0.1000	2M72W7D	-	0.0769
5	826.5 ~ 846.5	4M49G7D	-	0.1021	4M50W7D	-	0.0776
10	829.0 ~ 844.0	9M03G7D	0.0118	0.1057	9M01W7D	-	0.0804
15	831.5 ~ 841.5	13M4G7D	-	0.1109	13M5W7D	-	0.0750



1.7 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No.
	TH05-HY

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	03CH10-HY

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	5	✓	✓	✓	✓	-	-	✓	✓	✓	✓	✓	✓	✓	✓
	12	✓	✓	✓	✓	-	-	✓	✓	✓	✓	✓	✓	✓	✓
	13	-	-	✓	✓	-	-	✓	✓	✓	✓	✓	✓	✓	✓
	17	-	-	✓	✓	-	-	✓	✓	✓	✓	✓	✓	✓	✓
	25	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	26	✓	✓	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓	✓
Peak-to-Average Ratio	2						✓	✓	✓	✓		✓	✓	✓	✓
	4						✓	✓	✓	✓		✓	✓	✓	✓
	5				✓	-	-	✓	✓	✓		✓	✓	✓	✓
	12				✓	-	-	✓	✓	✓		✓	✓	✓	✓
	13	-	-		✓	-	-	✓	✓	✓		✓	✓	✓	✓
	17	-	-		✓	-	-	✓	✓	✓		✓	✓	✓	✓
	25						✓	✓	✓	✓		✓	✓	✓	✓
	26					✓	-	✓	✓	✓		✓	✓	✓	✓
26dB and 99% Bandwidth	2	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓
	4	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓
	5	✓	✓	✓	✓	-	-	✓	✓			✓	✓	✓	✓
	12	✓	✓	✓	✓	-	-	✓	✓			✓	✓	✓	✓
	13	-	-	✓	✓	-	-	✓	✓			✓	✓	✓	✓
	17	-	-	✓	✓	-	-	✓	✓			✓	✓	✓	✓
	25	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓
	26	✓	✓	✓	✓	✓	-	✓	✓			✓	✓	✓	✓




Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Conducted Band Edge	2	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓
	4	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓
	5	✓	✓	✓	✓	-	-	✓	✓	✓		✓	✓		✓
	12	✓	✓	✓	✓	-	-	✓	✓	✓		✓	✓		✓
	13	-	-	✓	✓	-	-	✓	✓	✓		✓	✓		✓
	17	-	-	✓	✓	-	-	✓	✓	✓		✓	✓		✓
	25	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓
	26	✓	✓	✓	✓	✓	-	✓	✓	✓		✓	✓		✓
Conducted Spurious Emission	2	✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
	4	✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
	5	✓	✓	✓	✓	-	-	✓	✓	✓			✓	✓	✓
	12	✓	✓	✓	✓	-	-	✓	✓	✓			✓	✓	✓
	13	-	-	✓	✓	-	-	✓	✓	✓			✓	✓	✓
	17	-	-	✓	✓	-	-	✓	✓	✓			✓	✓	✓
	25	✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
	26	✓	✓	✓	✓	✓	-	✓	✓	✓			✓	✓	✓
Frequency Stability	2				✓			✓				✓		✓	
	4				✓			✓				✓		✓	
	5				✓	-	-	✓				✓		✓	
	12				✓	-	-	✓				✓		✓	
	13	-	-	✓	✓	-	-	✓				✓		✓	
	17	-	-	✓	✓	-	-	✓				✓		✓	
	25				✓			✓				✓		✓	
	26				✓	✓	-	✓				✓		✓	



Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
E.R.P/ E.I.R.P.	2	√	√	√	√	√	√	√	√	√	√		√	√	√
	4	√	√	√	√	√	√	√	√	√	√		√	√	√
	5	√	√	√	√	-	-	√	√	√	√		√	√	√
	12	√	√	√	√	√	√	√	√	√	√		√	√	√
	13	-	-	√	√	√	√	√	√	√			√	√	√
	17	-	-	√	√	-	-	√	√	√			√	√	√
	25	√	√	√	√	√	√	√	√	√	√		√	√	√
	26	√	√	√	√	√	-	√	√	√	√		√	√	√
Radiated Spurious Emission	2	√	√	√	√	√	√	√		√			√	√	√
	4	√	√	√	√	√	√	√		√			√	√	√
	5	√	√	√	√	-	-	√		√			√	√	√
	12	√	√	√	√	-	-	√		√			√	√	√
	13	-	-	√	√	-	-	√		√			√	√	√
	17	-	-	√	√	-	-	√		√			√	√	√
	25	√	√	√	√	√	√	√		√			√	√	√
	26	√	√	√	√	√	-	√		√			√	√	√
Note	<p>1. The mark “√ “ means that this configuration is chosen for testing</p> <p>2. The mark “-“ means that this bandwidth is not supported.</p> <p>3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.</p>														

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23060	23095	23130
	Frequency	704	707.5	711
5	Channel	23035	23095	23155
	Frequency	701.5	707.5	713.5
3	Channel	23025	23095	23165
	Frequency	700.5	707.5	714.5
1.4	Channel	23017	23095	23173
	Frequency	699.7	707.5	715.3

LTE Band 13 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23230	-
	Frequency	-	782	-
5	Channel	23205	23230	23255
	Frequency	779.5	782	784.5



LTE Band 17 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23780	23790	23800
	Frequency	709	710	711
5	Channel	23755	23790	23825
	Frequency	706.5	710	713.5

LTE Band 25 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	26140	26340	26590
	Frequency	1860	1880	1905
15	Channel	26115	26340	26615
	Frequency	1857.5	1880	1907.5
10	Channel	26090	26340	26640
	Frequency	1855	1880	1910
5	Channel	26065	26340	26665
	Frequency	1852.5	1880	1912.5
3	Channel	26055	26340	26675
	Frequency	1851.5	1880	1913.5
1.4	Channel	26047	26340	26683
	Frequency	1850.7	1880	1914.3



LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26865	26915	26965
	Frequency	831.5	836.5	841.5
10	Channel	26840	26915	26990
	Frequency	829	836.5	844
5	Channel	26815	26915	27015
	Frequency	826.5	836.5	846.5
3	Channel	26805	26915	27025
	Frequency	825.5	836.5	847.5
1.4	Channel	26797	26915	27033
	Frequency	824.7	836.5	848.3


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (c)

For operations in the 776-788 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 100 kHz bandwidth. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed. In addition, the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least $65 + 10 \log_{10} p(\text{watts})$, dB, for mobile and portable equipment.

27.53 (g)

For operations in the 698 -746 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 100 kHz bandwidth. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.



3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- [43 + 10log(P)] (dB)
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- [43 + 10log(P)] (dB)
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
= -13dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Effective Radiated Power and Effective Isotropic Radiated Power

4.4.1 Description of the ERP/EIRP Measurement

Effective radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-D-2010, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average ERP of 7 watts with LTE band 5 /26 and 3 watts with LTE band 12 / 13 / 17.

Equivalent isotropic radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-D-2010, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average EIRP of 2 watts with LTE band 2 / 25 and 1 watt with LTE band 4.

4.4.2 Test Procedures

1. The EUT was placed on a non-conductive rotating platform (0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz) in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
2. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	LTE Average					
LTE BW	1.4M	3M	5M	10M	15M	20M
Span	3MHz	6MHz	10MHz	20MHz	30MHz	40MHz
RBW	30kHz	100kHz	100kHz	300kHz	300kHz	300kHz
VBW	100kHz	300kHz	300kHz	1MHz	1MHz	1MHz
Detector	RMS	RMS	RMS	RMS	RMS	RMS
Trace	Average	Average	Average	Average	Average	Average
Average Type	Power	Power	Power	Power	Power	Power
Sweep Count	100	100	100	100	100	100



4.5 Radiated Spurious Emission

4.5.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-D-2010. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For LTE Band 12,13,17

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13 dBm.



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LTE Base Station	Anritsu	MT8820C	6201432821	GSM/GPRS /WCDMA/LTE	Oct. 16, 2015	Aug. 31, 2016 ~ Sep. 03, 2016	Oct. 15, 2016	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	100895	9kHz~30GHz	Apr. 26, 2016	Aug. 31, 2016 ~ Sep. 03, 2016	Apr. 25 2017	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-30°C~70°C	Sep. 08, 2015	Aug. 31, 2016 ~ Sep. 03, 2016	Sep. 07, 2016	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890089	1V~20V 0.5A~5A	Jan. 18, 2016	Aug. 31, 2016 ~ Sep. 03, 2016	Jan. 17, 2017	Conducted (TH05-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Nov. 16, 2015	Aug. 31, 2016 ~ Sep. 07, 2016	Nov. 15, 2016	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D	35413	30MHz~1GHz	Jan. 13, 2016	Aug. 31, 2016 ~ Sep. 07, 2016	Jan. 12, 2017	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1325	1GHz ~ 18GHz	Sep. 30, 2015	Aug. 31, 2016 ~ Sep. 07, 2016	Sep. 29, 2016	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY53270078	1GHz~26.5GHz	Nov. 13, 2015	Aug. 31, 2016 ~ Sep. 07, 2016	Nov. 12, 2016	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHz	Oct. 15, 2015	Aug. 31, 2016 ~ Sep. 07, 2016	Oct. 14, 2016	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Aug. 31, 2016 ~ Sep. 07, 2016	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	Aug. 31, 2016 ~ Sep. 07, 2016	N/A	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D	35414	30MHz~1GHz	Nov. 17, 2015	Aug. 31, 2016 ~ Sep. 07, 2016	Nov. 16, 2016	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 08, 2015	Aug. 31, 2016 ~ Sep. 07, 2016	Oct. 07, 2016	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 15, 2016	Aug. 31, 2016 ~ Sep. 07, 2016	Apr. 14, 2017	Radiation (03CH10-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY55420170	N/A	Mar. 10, 2016	Aug. 31, 2016 ~ Sep. 07, 2016	Mar. 09, 2017	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz- 40GHz	Oct. 12, 2015	Aug. 31, 2016 ~ Sep. 07, 2016	Oct. 11, 2016	Radiation (03CH10-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 19, 2016	Aug. 31, 2016 ~ Sep. 07, 2016	May 18, 2017	Radiation (03CH10-HY)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.6
---	-----

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.9
---	-----



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.41	23.30	23.25
20	1	49		23.42	23.31	23.45
20	1	99		23.16	23.12	23.43
20	50	0		22.40	22.39	22.62
20	50	24		22.23	22.31	22.58
20	50	50		22.36	22.38	22.61
20	100	0		22.46	22.35	22.59
20	1	0	16-QAM	22.27	22.17	22.35
20	1	49		22.25	22.30	22.41
20	1	99		22.07	21.92	22.46
20	50	0		21.35	21.38	21.52
20	50	24		21.38	21.46	21.72
20	50	50		21.31	21.25	21.59
20	100	0		21.50	21.30	21.57
15	1	0	QPSK	23.23	23.33	23.45
15	1	37		23.29	23.42	23.46
15	1	74		23.25	23.25	23.44
15	36	0		22.30	22.27	22.50
15	36	20		22.22	22.35	22.51
15	36	39		22.28	22.32	22.49
15	75	0		22.34	22.25	22.54
15	1	0	16-QAM	22.20	22.16	22.19
15	1	37		21.98	22.18	22.32
15	1	74		22.12	22.00	22.39
15	36	0		21.36	21.28	21.54
15	36	20		21.19	21.27	21.53
15	36	39		21.25	21.22	21.58
15	75	0		21.41	21.24	21.60



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.27	23.12	23.16
10	1	25		23.17	23.30	23.31
10	1	49		22.88	23.37	23.24
10	25	0		22.25	22.26	22.46
10	25	12		22.31	22.22	22.55
10	25	25		22.15	22.23	22.46
10	50	0		22.25	22.28	22.54
10	1	0	16-QAM	22.18	22.15	22.35
10	1	25		22.00	22.38	22.43
10	1	49		21.93	22.08	22.37
10	25	0		21.24	21.21	21.55
10	25	12		21.31	21.30	21.45
10	25	25		21.08	21.18	21.54
10	50	0		21.15	21.19	21.54
5	1	0	QPSK	23.11	23.21	23.44
5	1	12		23.25	23.42	23.52
5	1	24		23.06	23.26	23.52
5	12	0		22.17	22.23	22.35
5	12	7		22.21	22.22	22.38
5	12	13		22.19	22.18	22.50
5	25	0		22.19	22.19	22.44
5	1	0	16-QAM	21.50	22.00	22.23
5	1	12		21.62	21.78	22.26
5	1	24		21.91	21.83	22.04
5	12	0		21.08	21.14	21.25
5	12	7		21.22	21.03	21.27
5	12	13		20.96	21.19	21.22
5	25	0		21.27	21.44	21.47



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.45	23.35	23.74
3	1	8		23.45	23.25	23.72
3	1	14		23.16	23.34	23.56
3	8	0		22.38	22.35	22.68
3	8	4		22.24	22.31	22.64
3	8	7		22.25	22.35	22.67
3	15	0		22.30	22.30	22.56
3	1	0	16-QAM	21.99	22.22	22.49
3	1	8		22.03	22.10	22.32
3	1	14		21.97	22.13	22.29
3	8	0		21.30	21.33	21.62
3	8	4		21.54	21.25	21.39
3	8	7		21.30	21.28	21.82
3	15	0		21.09	21.25	21.49
1.4	1	0	QPSK	23.29	23.33	23.57
1.4	1	3		23.29	23.52	23.76
1.4	1	5		23.11	23.44	23.63
1.4	3	0		23.49	23.49	23.64
1.4	3	1		23.63	23.67	23.83
1.4	3	3		23.50	23.47	23.63
1.4	6	0		22.33	22.33	22.53
1.4	1	0	16-QAM	22.26	22.27	22.47
1.4	1	3		22.42	22.51	22.51
1.4	1	5		21.95	22.31	22.41
1.4	3	0		22.21	22.61	22.76
1.4	3	1		22.15	22.54	22.78
1.4	3	3		22.15	22.68	22.85
1.4	6	0		20.77	21.47	21.55



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.40	23.21	23.50
20	1	49		23.54	23.27	23.60
20	1	99		23.53	23.24	23.58
20	50	0		22.52	22.42	22.67
20	50	24		22.52	22.43	22.71
20	50	50		22.53	22.53	22.73
20	100	0		22.50	22.41	22.74
20	1	0	16-QAM	22.28	22.32	22.41
20	1	49		22.25	22.20	22.54
20	1	99		22.17	22.29	22.55
20	50	0		21.58	21.22	21.63
20	50	24		21.47	21.21	21.78
20	50	50		21.58	21.47	21.63
20	100	0		21.44	21.25	21.70
15	1	0	QPSK	23.45	23.25	23.43
15	1	37		23.57	23.38	23.75
15	1	74		23.38	23.55	23.76
15	36	0		22.48	22.32	22.62
15	36	20		22.38	22.41	22.71
15	36	39		22.44	22.41	22.70
15	75	0		22.39	22.35	22.69
15	1	0	16-QAM	22.30	22.21	22.47
15	1	37		22.12	22.10	22.42
15	1	74		22.21	22.21	22.46
15	36	0		21.45	21.26	21.54
15	36	20		21.33	21.30	21.64
15	36	39		21.29	21.20	21.61
15	75	0		21.37	21.23	21.68



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.49	23.25	23.40
10	1	25		23.38	23.41	23.50
10	1	49		22.96	23.09	23.43
10	25	0		22.36	22.25	22.62
10	25	12		22.41	22.35	22.71
10	25	25		22.29	22.29	22.66
10	50	0		22.32	22.28	22.62
10	1	0	16-QAM	22.18	22.11	22.45
10	1	25		22.31	22.27	22.65
10	1	49		22.06	22.18	22.55
10	25	0		21.30	21.33	21.58
10	25	12		21.40	21.28	21.60
10	25	25		21.24	21.24	21.65
10	50	0		21.28	21.07	21.61
5	1	0	QPSK	22.97	23.15	23.36
5	1	12		23.21	23.43	23.69
5	1	24		22.98	22.87	23.50
5	12	0		22.31	22.27	22.61
5	12	7		22.35	22.20	22.61
5	12	13		22.31	22.24	22.67
5	25	0		22.38	22.23	22.68
5	1	0	16-QAM	22.06	21.98	22.38
5	1	12		22.25	21.88	22.41
5	1	24		22.00	21.93	22.38
5	12	0		21.17	21.11	21.44
5	12	7		21.26	21.23	21.61
5	12	13		21.05	21.05	21.45
5	25	0		21.17	21.22	21.57



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.29	23.08	23.58
3	1	8		23.16	23.21	23.85
3	1	14		22.99	22.94	23.71
3	8	0		22.34	22.26	22.60
3	8	4		22.39	22.43	22.62
3	8	7		22.35	22.43	22.68
3	15	0		22.35	22.34	22.66
3	1	0	16-QAM	22.18	22.17	22.53
3	1	8		22.06	22.05	22.43
3	1	14		21.90	22.17	22.55
3	8	0		21.26	21.24	21.64
3	8	4		21.21	21.17	21.84
3	8	7		21.54	21.31	21.71
3	15	0		21.33	21.15	21.74
1.4	1	0	QPSK	23.39	23.18	23.53
1.4	1	3		23.46	23.17	23.60
1.4	1	5		23.39	23.32	23.67
1.4	3	0		23.51	23.48	23.80
1.4	3	1		23.69	23.40	23.81
1.4	3	3		23.53	23.48	23.84
1.4	6	0		22.37	22.46	22.59
1.4	1	0	16-QAM	22.24	22.17	22.47
1.4	1	3		22.38	22.38	22.61
1.4	1	5		22.21	22.20	22.53
1.4	3	0		22.63	22.57	22.53
1.4	3	1		22.64	22.68	22.86
1.4	3	3		22.71	22.26	22.95
1.4	6	0		21.22	21.33	21.61



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.76	24.12	24.16
20	1	49		23.75	23.93	24.15
20	1	99		23.71	24.10	24.05
20	50	0		22.86	22.84	23.18
20	50	24		22.84	22.91	23.29
20	50	50		22.96	22.95	23.30
20	100	0		22.82	22.83	23.33
20	1	0	16-QAM	22.52	22.77	23.05
20	1	49		22.73	22.71	23.20
20	1	99		22.65	22.87	23.23
20	50	0		21.81	21.87	22.31
20	50	24		21.77	21.93	22.41
20	50	50		22.01	21.91	22.32
20	100	0		21.76	21.85	22.28
15	1	0	QPSK	23.80	23.57	24.09
15	1	37		24.18	24.11	24.32
15	1	74		23.82	23.94	24.34
15	36	0		22.78	22.86	23.26
15	36	20		22.80	22.95	23.22
15	36	39		22.79	22.92	23.33
15	75	0		22.83	22.85	23.21
15	1	0	16-QAM	22.40	22.69	23.13
15	1	37		22.65	22.63	23.28
15	1	74		22.73	22.80	23.25
15	36	0		21.73	21.80	22.23
15	36	20		21.66	21.91	22.21
15	36	39		21.76	21.94	22.38
15	75	0		21.68	21.93	22.29



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.71	23.62	24.09
10	1	25		23.97	23.91	24.24
10	1	49		23.52	24.03	24.14
10	25	0		22.75	22.83	23.28
10	25	12		22.78	22.82	23.26
10	25	25		22.77	22.93	23.37
10	50	0		22.82	22.96	23.31
10	1	0	16-QAM	22.58	22.41	23.27
10	1	25		22.86	22.91	23.48
10	1	49		22.56	22.72	23.30
10	25	0		21.79	21.77	22.35
10	25	12		21.82	21.85	22.45
10	25	25		21.72	22.04	22.46
10	50	0		21.68	22.04	22.39
5	1	0	QPSK	23.63	23.49	24.05
5	1	12		24.16	24.12	24.16
5	1	24		23.60	23.84	24.23
5	12	0		22.73	22.73	23.37
5	12	7		22.81	22.90	23.36
5	12	13		22.79	22.89	23.35
5	25	0		22.71	22.93	23.30
5	1	0	16-QAM	22.47	22.62	23.15
5	1	12		22.38	22.33	23.21
5	1	24		22.51	22.65	23.19
5	12	0		21.64	21.94	22.34
5	12	7		21.86	22.10	22.36
5	12	13		21.66	21.75	22.30
5	25	0		21.56	21.74	22.50



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.64	23.68	24.29
3	1	8		23.63	23.85	24.21
3	1	14		23.42	23.89	24.04
3	8	0		22.68	22.75	23.15
3	8	4		22.65	23.04	23.20
3	8	7		22.75	22.92	23.21
3	15	0		22.76	22.96	23.21
3	1	0	16-QAM	22.62	22.70	23.13
3	1	8		22.56	22.67	23.00
3	1	14		22.59	22.79	23.10
3	8	0		21.62	21.53	22.31
3	8	4		21.63	22.01	22.19
3	8	7		21.72	21.97	22.29
3	15	0		21.53	21.77	22.19
1.4	1	0	QPSK	23.63	23.69	24.15
1.4	1	3		23.72	23.78	24.11
1.4	1	5		23.61	23.63	24.20
1.4	3	0		23.81	23.88	24.12
1.4	3	1		23.74	24.03	24.25
1.4	3	3		23.79	23.94	24.23
1.4	6	0		22.67	22.89	23.09
1.4	1	0	16-QAM	22.54	22.53	23.05
1.4	1	3		22.68	23.16	23.29
1.4	1	5		22.56	22.73	23.13
1.4	3	0		22.67	22.77	23.04
1.4	3	1		22.64	22.80	23.16
1.4	3	3		22.61	23.05	23.13
1.4	6	0		21.42	21.70	22.02



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.92	23.86	23.81
10	1	25		23.96	23.91	23.89
10	1	49		23.92	23.90	23.80
10	25	0		22.95	22.96	22.89
10	25	12		22.96	22.97	22.99
10	25	25		22.94	22.92	22.98
10	50	0		22.95	22.94	22.96
10	1	0	16-QAM	22.67	22.68	22.65
10	1	25		22.86	22.99	22.87
10	1	49		22.76	22.67	22.87
10	25	0		21.94	21.98	21.88
10	25	12		21.94	22.00	21.93
10	25	25		21.96	21.90	21.93
10	50	0		21.93	21.96	21.98
5	1	0	QPSK	23.73	23.87	23.82
5	1	12		23.97	23.95	23.98
5	1	24		23.54	23.57	23.87
5	12	0		22.87	22.90	22.94
5	12	7		22.96	22.96	22.99
5	12	13		22.93	22.88	22.97
5	25	0		22.91	22.92	22.92
5	1	0	16-QAM	22.56	22.68	22.70
5	1	12		22.64	23.00	22.64
5	1	24		22.63	22.73	22.76
5	12	0		21.82	21.98	21.95
5	12	7		21.97	21.94	21.93
5	12	13		21.90	21.81	21.87
5	25	0		21.91	21.96	21.82



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.99	23.88	23.96
3	1	8		23.72	23.90	23.86
3	1	14		23.63	23.60	23.79
3	8	0		22.86	22.96	22.98
3	8	4		22.96	22.94	23.00
3	8	7		22.96	22.95	22.96
3	15	0		22.93	22.98	22.97
3	1	0	16-QAM	22.77	22.85	22.88
3	1	8		22.68	22.69	22.88
3	1	14		22.57	22.68	22.94
3	8	0		21.96	21.72	22.00
3	8	4		21.92	21.94	21.95
3	8	7		21.91	21.95	21.96
3	15	0		22.00	21.78	21.99
1.4	1	0	QPSK	23.83	23.95	23.93
1.4	1	3		23.68	23.96	24.00
1.4	1	5		23.62	23.92	23.89
1.4	3	0		23.97	23.88	23.95
1.4	3	1		23.98	23.96	23.96
1.4	3	3		23.94	23.94	23.98
1.4	6	0		22.87	22.90	22.90
1.4	1	0	16-QAM	22.59	22.80	22.95
1.4	1	3		22.90	22.94	22.99
1.4	1	5		22.55	22.84	22.73
1.4	3	0		22.81	22.93	22.98
1.4	3	1		22.96	22.98	23.00
1.4	3	3		22.84	22.95	22.96
1.4	6	0		21.70	21.88	21.83



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.87	24.18	23.96
10	1	25		24.08	23.94	24.11
10	1	49		23.85	23.83	23.87
10	25	0		23.19	23.09	23.08
10	25	12		23.09	23.02	23.12
10	25	25		23.07	23.08	23.03
10	50	0		23.09	23.11	23.12
10	1	0	16-QAM	22.99	22.94	22.79
10	1	25		23.17	23.05	23.05
10	1	49		22.85	22.85	22.81
10	25	0		22.30	22.11	22.20
10	25	12		22.43	22.19	22.34
10	25	25		22.14	22.17	22.02
10	50	0		22.17	22.18	22.13
5	1	0	QPSK	24.05	23.90	23.86
5	1	12		24.06	24.16	24.14
5	1	24		23.89	23.86	23.70
5	12	0		23.20	23.03	23.06
5	12	7		23.34	23.09	23.04
5	12	13		23.21	23.09	22.91
5	25	0		23.21	23.09	22.95
5	1	0	16-QAM	23.05	23.14	22.74
5	1	12		23.03	23.11	23.04
5	1	24		22.93	22.76	22.59
5	12	0		22.24	22.09	22.08
5	12	7		22.31	22.11	22.05
5	12	13		22.40	22.00	21.97
5	25	0		22.40	22.16	21.96



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.90	23.96	23.90
3	1	8		24.21	23.96	23.97
3	1	14		24.37	23.83	23.85
3	8	0		23.17	23.22	23.04
3	8	4		23.32	23.09	23.02
3	8	7		23.31	23.05	23.05
3	15	0		23.24	23.08	23.02
3	1	0	16-QAM	23.10	22.90	22.87
3	1	8		23.03	22.83	22.83
3	1	14		23.13	22.93	23.00
3	8	0		22.40	22.14	22.10
3	8	4		22.41	22.03	22.07
3	8	7		22.43	22.17	22.18
3	15	0		22.36	21.99	22.15
1.4	1	0	QPSK	24.11	23.93	24.02
1.4	1	3		24.37	23.93	24.11
1.4	1	5		24.30	23.90	24.11
1.4	3	0		24.22	24.21	24.17
1.4	3	1		24.26	24.19	24.13
1.4	3	3		24.29	24.31	24.19
1.4	6	0		23.19	22.94	22.98
1.4	1	0	16-QAM	23.11	22.85	22.94
1.4	1	3		23.25	22.98	23.07
1.4	1	5		23.16	22.84	22.95
1.4	3	0		23.44	22.94	22.99
1.4	3	1		23.41	23.13	23.03
1.4	3	3		23.50	23.13	23.00
1.4	6	0		22.21	22.18	22.14



LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK		23.72	
10	1	25			24.03	
10	1	49			23.86	
10	25	0			22.84	
10	25	12			22.77	
10	25	25			22.75	
10	50	0			22.78	
10	1	0	16-QAM		22.88	
10	1	25			22.78	
10	1	49			22.64	
10	25	0			22.19	
10	25	12			22.11	
10	25	25			22.08	
10	50	0			21.93	
5	1	0	QPSK	23.92	23.68	23.43
5	1	12		24.01	23.91	24.12
5	1	24		23.71	23.45	23.74
5	12	0		22.79	22.84	22.84
5	12	7		22.89	22.78	22.74
5	12	13		22.78	22.76	22.82
5	25	0		22.86	22.76	22.77
5	1	0		22.68	22.88	22.62
5	1	12		22.63	23.16	22.62
5	1	24		22.66	22.56	22.58
5	12	0	16-QAM	21.78	21.90	21.90
5	12	7		22.05	21.93	21.95
5	12	13		21.85	21.73	21.93
5	25	0		21.93	21.92	21.83



LTE Band 17 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.88	23.86	23.70
10	1	25		24.06	24.11	24.01
10	1	49		23.91	23.82	23.74
10	25	0		22.94	22.75	22.77
10	25	12		22.92	22.83	22.84
10	25	25		22.90	22.85	22.80
10	50	0		22.87	22.82	22.83
10	1	0	16-QAM	22.72	22.58	22.57
10	1	25		22.82	22.73	22.73
10	1	49		22.68	22.44	22.53
10	25	0		22.00	21.83	21.66
10	25	12		22.08	21.80	21.96
10	25	25		21.95	21.96	22.00
10	50	0		21.82	21.89	21.79
5	1	0	QPSK	23.83	23.76	23.66
5	1	12		23.90	23.88	23.76
5	1	24		23.67	23.71	23.65
5	12	0		22.83	22.76	22.70
5	12	7		22.94	22.80	22.79
5	12	13		22.88	22.80	22.68
5	25	0		22.85	22.76	22.70
5	1	0	16-QAM	22.57	22.53	22.41
5	1	12		22.56	22.51	22.54
5	1	24		22.47	22.49	22.52
5	12	0		21.84	21.56	21.90
5	12	7		21.72	21.76	21.73
5	12	13		21.75	21.86	21.62
5	25	0		21.73	22.02	21.81



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.65	23.53	23.70
15	1	37		23.83	24.15	24.13
15	1	74		23.65	23.99	23.83
15	36	0		22.75	22.99	22.99
15	36	18		22.74	22.97	22.98
15	36	37		22.71	22.99	22.98
15	75	0		22.82	22.98	22.95
15	1	0	16-QAM	22.48	22.55	22.66
15	1	37		22.85	22.90	22.84
15	1	74		22.67	22.78	22.75
15	36	0		21.72	22.03	22.24
15	36	18		21.85	22.00	22.03
15	36	37		21.85	21.90	22.01
15	75	0		21.64	21.86	22.08
10	1	0	QPSK	23.65	23.53	23.70
10	1	24		23.83	24.15	24.13
10	1	49		23.65	24.24	23.83
10	25	0		22.73	22.99	22.99
10	25	12		22.81	22.97	22.99
10	25	24		22.83	22.99	22.98
10	50	0		22.82	22.98	22.95
10	1	0	16-QAM	22.48	22.55	22.66
10	1	24		22.85	22.90	22.84
10	1	49		22.67	22.78	22.75
10	25	0		21.72	22.03	22.24
10	25	12		21.85	22.00	22.03
10	25	24		21.85	21.90	22.01
10	50	0		21.64	21.86	22.08



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.23	23.59	23.45
5	1	12		23.86	24.28	24.11
5	1	24		23.47	24.06	23.61
5	12	0		22.67	22.84	22.93
5	12	6		22.73	22.88	22.87
5	12	11		22.80	22.97	22.93
5	25	0		22.66	22.93	22.90
5	1	0	16-QAM	22.69	22.55	22.53
5	1	12		22.45	22.58	22.68
5	1	24		22.55	22.65	22.61
5	12	0		21.45	21.86	21.93
5	12	6		21.50	22.12	22.12
5	12	11		21.65	22.00	21.82
5	25	0		21.71	21.95	21.92
3	1	0	QPSK	23.36	23.70	23.83
3	1	7		23.56	23.80	23.64
3	1	14		23.33	24.11	24.02
3	8	0		22.82	22.97	23.00
3	8	4		22.79	22.94	23.00
3	8	7		22.70	22.95	22.97
3	15	0		22.75	22.93	22.94
3	1	0	16-QAM	22.35	22.99	22.77
3	1	7		22.42	22.62	22.77
3	1	14		22.57	22.73	22.84
3	8	0		21.71	21.60	22.01
3	8	4		21.69	22.12	21.96
3	8	7		21.79	22.04	22.07
3	15	0		21.60	21.95	21.90



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.39	23.92	23.94
1.4	1	2		23.44	23.99	23.87
1.4	1	5		23.68	23.94	23.93
1.4	3	0		23.59	23.97	23.92
1.4	3	1		23.89	24.13	24.00
1.4	3	2		23.71	24.11	24.09
1.4	6	0		22.71	22.93	22.91
1.4	1	0	16-QAM	22.52	22.73	22.82
1.4	1	2		22.68	22.84	23.08
1.4	1	5		22.52	22.69	22.88
1.4	3	0		22.76	23.08	23.13
1.4	3	1		22.74	22.97	22.93
1.4	3	2		22.75	22.88	22.81
1.4	6	0		21.59	21.65	22.03



LTE Band 2


Peak-to-Average Ratio

Mode	LTE Band 2 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.33	4.67	4.72	5.59	PASS
Middle CH	3.57	4.26	4.9	5.28	
Highest CH	3.83	4.41	5.22	5.54	




LTE Band 2 / 20MHz / QPSK

Lowest Channel / 1RB




Date: 31.AUG.2016 22:25:57

Lowest Channel / Full RB




Date: 31.AUG.2016 22:12:14

Middle Channel / 1RB



Date: 31.AUG.2016 22:28:41

Middle Channel / Full RB



Date: 31.AUG.2016 22:12:56

Highest Channel / 1RB



Date: 31.AUG.2016 22:29:07

Highest Channel / Full RB



Date: 31.AUG.2016 22:12:19



LTE Band 2 / 20MHz / 16QAM

Lowest Channel / 1RB




Date: 31.AUG.2016 22:24:06

Lowest Channel / Full RB




Date: 31.AUG.2016 22:24:38

Middle Channel / 1RB




Date: 31.AUG.2016 22:24:49

Middle Channel / Full RB



Date: 31.AUG.2016 22:25:11

Highest Channel / 1RB



Date: 31.AUG.2016 22:25:24

Highest Channel / Full RB



Date: 31.AUG.2016 22:25:35




26dB Bandwidth

Mode	LTE Band 2 : 26dB BW(MHz)											
	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
BW												
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.281	1.259	2.985	3.003	4.885	4.895	9.93	9.65	14.535	14.565	20.02	20.14
Middle CH	1.262	1.284	3.039	3.033	4.945	4.935	9.79	9.77	14.296	14.505	20.26	20.06
Highest CH	1.312	1.287	3.027	3.015	4.965	4.885	9.73	9.85	14.176	14.416	20.02	20.02




LTE Band 2

Lowest Channel / 1.4MHz / QPSK




Date: 31.AUG.2016 21:58:00

Lowest Channel / 1.4MHz / 16QAM




Date: 31.AUG.2016 21:58:12

Middle Channel / 1.4MHz / QPSK




Date: 31.AUG.2016 22:05:22

Middle Channel / 1.4MHz / 16QAM




Date: 31.AUG.2016 22:05:34

Highest Channel / 1.4MHz / QPSK



Date: 31.AUG.2016 22:08:06

Highest Channel / 1.4MHz / 16QAM




Date: 31.AUG.2016 22:08:18




LTE Band 2

Lowest Channel / 3MHz / QPSK




Date: 31.AUG.2016 20:29:02

Lowest Channel / 3MHz / 16QAM




Date: 31.AUG.2016 20:12:14

Middle Channel / 3MHz / QPSK




Date: 31.AUG.2016 20:36:24

Middle Channel / 3MHz / 16QAM




Date: 31.AUG.2016 20:36:35

Highest Channel / 3MHz / QPSK



Date: 31.AUG.2016 20:39:08

Highest Channel / 3MHz / 16QAM




Date: 31.AUG.2016 20:39:20




LTE Band 2

Lowest Channel / 5MHz / QPSK




Date: 31.AUG.2016 20:46:30

Lowest Channel / 5MHz / 16QAM




Date: 31.AUG.2016 20:46:42

Middle Channel / 5MHz / QPSK




Date: 31.AUG.2016 20:53:51

Middle Channel / 5MHz / 16QAM




Date: 31.AUG.2016 20:54:03

Highest Channel / 5MHz / QPSK



Date: 31.AUG.2016 20:56:36

Highest Channel / 5MHz / 16QAM




Date: 31.AUG.2016 20:56:47




LTE Band 2

Lowest Channel / 10MHz / QPSK




Date: 31.AUG.2016 21:03:58

Lowest Channel / 10MHz / 16QAM




Date: 31.AUG.2016 21:04:10

Middle Channel / 10MHz / QPSK




Date: 31.AUG.2016 21:11:20

Middle Channel / 10MHz / 16QAM




Date: 31.AUG.2016 21:11:31

Highest Channel / 10MHz / QPSK



Date: 31.AUG.2016 21:14:04

Highest Channel / 10MHz / 16QAM




Date: 31.AUG.2016 21:14:15




LTE Band 2

Lowest Channel / 15MHz / QPSK




Date: 31.AUG.2016 21:21:25

Lowest Channel / 15MHz / 16QAM




Date: 31.AUG.2016 21:21:37

Middle Channel / 15MHz / QPSK




Date: 31.AUG.2016 21:28:47

Middle Channel / 15MHz / 16QAM




Date: 31.AUG.2016 21:28:58

Highest Channel / 15MHz / QPSK



Date: 31.AUG.2016 21:31:31

Highest Channel / 15MHz / 16QAM




Date: 31.AUG.2016 21:31:43




LTE Band 2

Lowest Channel / 20MHz / QPSK




Date: 31.AUG.2016 21:38:53

Lowest Channel / 20MHz / 16QAM




Date: 31.AUG.2016 21:39:04

Middle Channel / 20MHz / QPSK




Date: 31.AUG.2016 21:46:15

Middle Channel / 20MHz / 16QAM




Date: 31.AUG.2016 21:46:26

Highest Channel / 20MHz / QPSK



Date: 31.AUG.2016 21:48:59

Highest Channel / 20MHz / 16QAM



Date: 31.AUG.2016 21:49:10




Occupied Bandwidth

Mode	LTE Band 2 : 99%OBW(MHz)											
	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
BW	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.09	2.72	2.7	4.48	4.48	9.09	8.99	13.37	13.46	18.38	18.3
Middle CH	1.09	1.09	2.72	2.71	4.47	4.5	8.93	9.01	13.37	13.4	18.26	18.26
Highest CH	1.1	1.1	2.7	2.75	4.49	4.51	9.01	9.01	13.34	13.28	18.1	18.22




LTE Band 2

Lowest Channel / 1.4MHz / QPSK




Date: 31.AUG.2016 21:57:36

Lowest Channel / 1.4MHz / 16QAM




Date: 31.AUG.2016 21:57:48

Middle Channel / 1.4MHz / QPSK




Date: 31.AUG.2016 22:04:58

Middle Channel / 1.4MHz / 16QAM




Date: 31.AUG.2016 22:05:10

Highest Channel / 1.4MHz / QPSK



Date: 31.AUG.2016 22:07:43

Highest Channel / 1.4MHz / 16QAM




Date: 31.AUG.2016 22:07:54




LTE Band 2

Lowest Channel / 3MHz / QPSK




Date: 31.AUG.2016 20:28:38

Lowest Channel / 3MHz / 16QAM




Date: 31.AUG.2016 20:28:50

Middle Channel / 3MHz / QPSK




Date: 31.AUG.2016 20:36:00

Middle Channel / 3MHz / 16QAM




Date: 31.AUG.2016 20:36:12

Highest Channel / 3MHz / QPSK



Date: 31.AUG.2016 20:38:45

Highest Channel / 3MHz / 16QAM




Date: 31.AUG.2016 20:38:56




LTE Band 2

Lowest Channel / 5MHz / QPSK




Date: 31.AUG.2016 20:46:06

Lowest Channel / 5MHz / 16QAM




Date: 31.AUG.2016 20:46:18

Middle Channel / 5MHz / QPSK




Date: 31.AUG.2016 20:53:28

Middle Channel / 5MHz / 16QAM




Date: 31.AUG.2016 20:53:40

Highest Channel / 5MHz / QPSK



Date: 31.AUG.2016 20:56:12

Highest Channel / 5MHz / 16QAM




Date: 31.AUG.2016 20:56:24




LTE Band 2

Lowest Channel / 10MHz / QPSK




Date: 31.AUG.2016 21:03:14

Lowest Channel / 10MHz / 16QAM




Date: 31.AUG.2016 21:03:46

Middle Channel / 10MHz / QPSK




Date: 31.AUG.2016 21:10:56

Middle Channel / 10MHz / 16QAM




Date: 31.AUG.2016 21:11:08

Highest Channel / 10MHz / QPSK



Date: 31.AUG.2016 21:13:40

Highest Channel / 10MHz / 16QAM




Date: 31.AUG.2016 21:13:52




LTE Band 2

Lowest Channel / 15MHz / QPSK




Date: 31.AUG.2016 21:21:02

Lowest Channel / 15MHz / 16QAM




Date: 31.AUG.2016 21:21:13

Middle Channel / 15MHz / QPSK




Date: 31.AUG.2016 21:28:23

Middle Channel / 15MHz / 16QAM




Date: 31.AUG.2016 21:28:35

Highest Channel / 15MHz / QPSK



Date: 31.AUG.2016 21:31:07

Highest Channel / 15MHz / 16QAM




Date: 31.AUG.2016 21:31:19




LTE Band 2

Lowest Channel / 20MHz / QPSK




Date: 31.AUG.2016 21:38:29

Lowest Channel / 20MHz / 16QAM




Date: 31.AUG.2016 21:38:41

Middle Channel / 20MHz / QPSK




Date: 31.AUG.2016 21:45:51

Middle Channel / 20MHz / 16QAM




Date: 31.AUG.2016 21:46:03

Highest Channel / 20MHz / QPSK



Date: 31.AUG.2016 21:48:35

Highest Channel / 20MHz / 16QAM



Date: 31.AUG.2016 21:48:47



Conducted Band Edge