



FCC RADIO TEST REPORT

FCC ID : UZ7VC8300
Equipment : Vehicle Computer
Brand Name : Zebra
Model Name : VC8300
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC Part 15 Subpart C §15.247

The product was received on Nov. 08, 2018 and testing was started from Nov. 22, 2018 and completed on Mar. 22, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Reviewed by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	7
1.4 Testing Location	8
1.5 Applicable Standards.....	8
2 Test Configuration of Equipment Under Test.....	9
2.1 Carrier Frequency Channel	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	13
2.4 Support Unit used in test configuration and system	15
2.5 EUT Operation Test Setup	15
2.6 Measurement Results Explanation Example.....	15
3 Test Result.....	16
3.1 Number of Channel Measurement	16
3.2 Hopping Channel Separation Measurement	18
3.3 Dwell Time Measurement.....	24
3.4 20dB and 99% Bandwidth Measurement	26
3.5 Output Power Measurement.....	37
3.6 Conducted Band Edges Measurement.....	39
3.7 Conducted Spurious Emission Measurement	46
3.8 Radiated Band Edges and Spurious Emission Measurement	56
3.9 AC Conducted Emission Measurement.....	61
3.10 Antenna Requirements.....	63
4 List of Measuring Equipment	64
5 Uncertainty of Evaluation.....	66
Appendix A. AC Conducted Emission Test Result	
Appendix B. Radiated Spurious Emission	
Appendix C. Radiated Spurious Emission Plots	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR8N0846A	01	Initial issue of report	Apr. 09, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 5.46 dB at 40.800 MHz
3.9	15.207	AC Conducted Emission	Pass	Under limit 13.80 dB at 0.236 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Polly Tsai



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Vehicle Computer
Brand Name	Zebra
Model Name	VC8300
FCC ID	UZ7VC8300
Sample 1	EUT with SKU 1
Sample 2	EUT with SKU 2
Sample 3	EUT with SKU 3
Sample 4	EUT with SKU 4
Sample 5	EUT with SKU 5
Sample 6	EUT with SKU 6
Sample 7	EUT with SKU 7
EUT supports Radios application	WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	EVT1
SW Version	Zebra/VC8300/VC8310:8.1.0/01-14-12-00-ON-U00-PRD/266: eng/release-keys
FW Version	01-14-12.00-ON-U00-PRD
MFD	03Nov18
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

Specification of Accessories				
AC Adapter	Brand Name	Zebra	Model Name	FSP150-AAAN2-Z
Battery	Brand Name	Zebra	Model Name	BT000254A01
Car Charger	Brand Name	Zebra	Model Name	CA1210
RJ50/USB cable	Brand Name	Zebra	Model Name	CBA-U01-S07ZAR
Scanner	Brand Name	Zebra	Model Name	DS3508
Scanner	Brand Name	Zebra	Model Name	LS3408
Audio Speaker	Brand Name	Zebra	Model Name	M1000
Ferrite Core	Brand Name	Zebra	Model Name	M1000
Keyboard (ikey)	Brand Name	Zebra	Model Name	SLK-101-M-USB-3F
Keyboard (remote keyboard)	Brand Name	Zebra	Model Name	KYBD-QWH-VC80
External Antenna (Monopole)	Brand Name	Zebra	Model Name	AN2010
External Antenna (Monopole)	Brand Name	Zebra	Model Name	AN2020
External Antenna (Dipole)	Brand Name	Zebra	Model Name	AN2030
Power Pre-regulator	Brand Name	PSION	Model Name	PS1370

<Sample Information>

Model Name	VC80x 8"			VC80x 10"			
	SKU1	SKU2	SKU3	SKU4	SKU5	SKU6	SKU7
SKU Name	Warehouse 1	Warehouse 2	Freezer SK HYNIX eMMC & MICRON DRAM	Warehouse	Outdoor	Warehouse	Freezer
OS	Android O	Android O	Android O	Android O	Android O	Android O	Android O
Display	Tianma	Tianma	Tianma	AUO	Mitsubishi	AUO	AUO
DTB board / Fuxture	DTB 8" CTP (TCA8414)	DTB 8" CTP (TCA8414)	DTB 8" CTP (TCA8414)	DTB AUO CTP (TCA8414)	DTB MIT CTP (TCA8414)	DTB AUO RTP (TCA8414)	DTB AUO RTP (TCA8414)
TP Type (Gunze)	CTP 8"	CTP 8"	CTP 8" w/ Heater	CTP 10"	CTP 10"	RTP	RTP w/ Heater
KB printing	QWERTY	AZETY	QWERTY				
KB Board	NO	NO	NO	Yes	Yes	Yes	Yes
KB	Yes	Yes	Yes	NO	NO	NO	NO
MLB	SDA660	SDA660	SDA660	SDA660	SDA660	SDA660	SDA660
PWR Board	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USB Board	Yes	Yes	Yes	Yes	Yes	Yes	Yes
DB9 Board	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Battery Heater Board	Yes	Yes	Yes	Yes	Yes	Yes	Yes

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 4.28 dBm (0.0027 W) Bluetooth EDR (2Mbps) : 3.45 dBm (0.0022 W) Bluetooth EDR (3Mbps) : 3.83 dBm (0.0024 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.844MHz Bluetooth EDR (2Mbps) : 1.168MHz Bluetooth EDR (3Mbps) : 1.148MHz
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

Antenna No.	Chain No.	Model	Antenna Type	Antenna Gain (dBi) Exclude Cable loss	Internal Cable loss (dB)	External Cable loss (dB)	Antenna Gain (dBi) Include Cable loss	Frequency (GHz)
1	Int. Chain 0	AN-000242-01	Patch	3.30	N/A	N/A	3.30	2.4~2.4835
				4.53	N/A	N/A	4.53	5.15~5.85
	Int. Chain 1			4.00	N/A	N/A	4.00	2.4~2.4835
				4.79	N/A	N/A	4.79	5.15~5.85
2	Ext. Chain 0	AN2010	Monopole	2	0.6	1.8	-0.4	2.4~2.4835
				2	0.9	2.6	-1.5	5.15~5.85
	Ext. Chain 1			2	0.6	1.8	-0.4	2.4~2.4835
				2	0.9	2.6	-1.5	5.15~5.85
3	Ext. Chain 0	AN2020	Monopole	5	0.6	1.8	2.6	2.4~2.4835
	Ext. Chain 1			5	0.6	1.8	2.6	2.4~2.4835
4	Ext. Chain 0	AN2030	Dipole	2	0.6	N/A	1.4	2.4~2.4835
				3.7	0.9	N/A	2.8	5.15~5.85
	Ext. Chain 1			2	0.6	N/A	1.4	2.4~2.4835
				3.7	0.9	N/A	2.8	5.15~5.85

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH11-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No. TW1190 and TW0007

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode

Channel	Frequency	Bluetooth Average Output Power		
		GFSK / 1Mbps		
		DH1	DH3	DH5
Ch00	2402MHz	2.11 dBm	2.07 dBm	2.03 dBm
Ch39	2441MHz	3.90 dBm	3.87 dBm	3.82 dBm
Ch78	2480MHz	2.78 dBm	2.73 dBm	2.71 dBm

Channel	Frequency	Bluetooth Average Output Power		
		$\pi/4$ -DQPSK / 2Mbps		
		2DH1	2DH3	2DH5
Ch00	2402MHz	-1.25 dBm	-1.39 dBm	-1.40 dBm
Ch39	2441MHz	0.67 dBm	0.48 dBm	0.46 dBm
Ch78	2480MHz	-0.46 dBm	-0.62 dBm	-0.64 dBm

Channel	Frequency	Bluetooth Average Output Power		
		8-DPSK / 3Mbps		
		3DH1	3DH3	3DH5
Ch00	2402MHz	-1.29 dBm	-1.44 dBm	-1.45 dBm
Ch39	2441MHz	0.65 dBm	0.48 dBm	0.46 dBm
Ch78	2480MHz	-0.46 dBm	-0.61 dBm	-0.66 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		GFSK / 1Mbps		
		DH1	DH3	DH5
Ch00	2402MHz	2.66 dBm	2.64 dBm	2.61 dBm
Ch39	2441MHz	4.28 dBm	4.24 dBm	4.23 dBm
Ch78	2480MHz	3.30 dBm	3.24 dBm	3.23 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		$\pi/4$ -DQPSK / 2Mbps		
		2DH1	2DH3	2DH5
Ch00	2402MHz	1.68 dBm	1.67 dBm	1.66 dBm
Ch39	2441MHz	3.45 dBm	3.41 dBm	3.37 dBm
Ch78	2480MHz	2.43 dBm	2.40 dBm	2.37 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		8-DPSK / 3Mbps		
		3DH1	3DH3	3DH5
Ch00	2402MHz	2.01 dBm	1.99 dBm	1.98 dBm
Ch39	2441MHz	3.83 dBm	3.82 dBm	3.81 dBm
Ch78	2480MHz	2.79 dBm	2.75 dBm	2.73 dBm

Remark: The data rate was set in 1Mbps for all the test items due to the highest RF output power.


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane for Ant. 1, Y plane for Ant. 3, and Vertical for Ant. 4) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps π /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + Audio Speaker (M1000) + Keyboard (SLK-101-M-USB-3F) + Scanner (LS3408) + RS-232 (Cable Load)* 2 + Int. Antenna + Ext. Antenna (AN2020) + Adapter + MPEG4 for Sample 4		
Remark:			
1. For radiated test cases, the worst mode data rate 1Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.			
2. For Radiated Test Cases, the tests were performed with Sample 3, and each antenna (Ant. 1, Ant. 3, Ant. 4) was tested in mode 1~3.			



2.3 Connection Diagram of Test System

<EUT with Antenna 1>



<EUT with Antenna 2>



<EUT with Antenna 4>

<AC Conducted Emission Mode>


2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to contact with base station to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup







3.1.5 Test Result of Number of Hopping Frequency

Test Engineer :	Shiming Liu	Temperature :	21~25℃
		Relative Humidity :	51~54%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 22.MAR.2019 17:10:58



Date: 22.MAR.2019 17:11:39

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup






3.2.5 Test Result of Hopping Channel Separation

Test Engineer :	Shiming Liu	Temperature :	21~25℃
		Relative Humidity :	51~54%

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.990	0.6000	Pass
DH	1Mbps	1	39	2441	0.696	0.5973	Pass
DH	1Mbps	1	78	2480	0.996	0.5973	Pass
2DH	2Mbps	1	0	2402	1.008	0.8440	Pass
2DH	2Mbps	1	39	2441	1.290	0.8440	Pass
2DH	2Mbps	1	78	2480	0.996	0.8400	Pass
3DH	3Mbps	1	0	2402	1.002	0.8240	Pass
3DH	3Mbps	1	39	2441	1.308	0.8200	Pass
3DH	3Mbps	1	78	2480	1.002	0.8240	Pass

<1Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 22.MAR.2019 17:10:12




Channel Separation Plot on Channel 39 - 40



Date: 22.MAR.2019 17:21:38

Channel Separation Plot on Channel 77 - 78




Date: 22.MAR.2019 17:29:11




<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 22.MAR.2019 17:48:55


Channel Separation Plot on Channel 39 - 40



Date: 22.MAR.2019 17:56:44




Channel Separation Plot on Channel 77 - 78



Date: 22.MAR.2019 18:42:24

<3Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 22.MAR.2019 18:47:09




Channel Separation Plot on Channel 39 - 40



Date: 22.MAR.2019 18:54:09

Channel Separation Plot on Channel 77 - 78



Date: 22.MAR.2019 18:59:26

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup




3.3.5 Test Result of Dwell Time

Test Engineer :	Shiming Liu	Temperature :	21~25℃
		Relative Humidity :	51~54%

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec) (MHz)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

Package Transfer Time Plot



Date: 15.JAN.2019 20:37:17

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1-5% of the OBW; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW $\geq$ 1-5% of the 99% bandwidth; VBW $\geq$ 3 * RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Test Engineer :	Shiming Liu	Temperature :	21~25℃
		Relative Humidity :	51~54%


Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	20db BW (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.900	Pass
DH	1Mbps	1	39	2441	0.896	Pass
DH	1Mbps	1	78	2480	0.896	Pass
2DH	2Mbps	1	0	2402	1.266	Pass
2DH	2Mbps	1	39	2441	1.266	Pass
2DH	2Mbps	1	78	2480	1.260	Pass
3DH	3Mbps	1	0	2402	1.236	Pass
3DH	3Mbps	1	39	2441	1.230	Pass
3DH	3Mbps	1	78	2480	1.236	Pass

<1Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 22.MAR.2019 17:13:28




20 dB Bandwidth Plot on Channel 78






<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 22.MAR.2019 17:51:36


20 dB Bandwidth Plot on Channel 39



Date: 22.MAR.2019 17:58:38




20 dB Bandwidth Plot on Channel 78




Date: 22.MAR.2019 18:43:34

<3Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 22.MAR.2019 18:48:55

**20 dB Bandwidth Plot on Channel 39**

Date: 22.MAR.2019 18:56:35

20 dB Bandwidth Plot on Channel 78


Date: 22.MAR.2019 19:00:59




Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.844	Pass
DH	1Mbps	1	39	2441	0.840	Pass
DH	1Mbps	1	78	2480	0.840	Pass
2DH	2Mbps	1	0	2402	1.164	Pass
2DH	2Mbps	1	39	2441	1.168	Pass
2DH	2Mbps	1	78	2480	1.168	Pass
3DH	3Mbps	1	0	2402	1.148	Pass
3DH	3Mbps	1	39	2441	1.144	Pass
3DH	3Mbps	1	78	2480	1.144	Pass

99% Occupied Bandwidth Plot on Channel 00



99% Occupied Bandwidth Plot on Channel 39


Date: 22.MAR.2019 17:25:46


99% Occupied Bandwidth Plot on Channel 78


Date: 22.MAR.2019 17:31:53




<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 22.MAR.2019 17:52:40


99% Occupied Bandwidth Plot on Channel 39



Date: 22.MAR.2019 17:59:15




99% Occupied Bandwidth Plot on Channel 78



Date: 22.MAR.2019 18:44:30

<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 22.MAR.2019 18:49:54




99% Occupied Bandwidth Plot on Channel 39



Date: 22.MAR.2019 18:57:12

99% Occupied Bandwidth Plot on Channel 78



Date: 22.MAR.2019 19:02:07

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup





3.5.5 Test Result of Peak Output Power

Test Engineer :		Shiming Liu		Temperature :	21~25℃
				Relative Humidity :	51~54%
DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	2.66	20.97	Pass
	39	1	4.28	20.97	Pass
	78	1	3.30	20.97	Pass
2DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
2DH1	0	1	1.68	20.97	Pass
	39	1	3.45	20.97	Pass
	78	1	2.43	20.97	Pass
3DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
3DH1	0	1	2.01	20.97	Pass
	39	1	3.83	20.97	Pass
	78	1	2.79	20.97	Pass

3.5.6 Test Result of Average Output Power (Reporting Only)

Test Engineer :		Shiming Liu		Temperature :	21~25℃
				Relative Humidity :	51~54%
DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)	
DH1	0	1	2.11	5.19	
	39	1	3.90	5.19	
	78	1	2.78	5.19	
2DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)	
2DH1	0	1	-1.25	5.11	
	39	1	0.67	5.11	
	78	1	-0.46	5.11	
3DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)	
3DH1	0	1	-1.29	5.11	
	39	1	0.65	5.11	
	78	1	-0.46	5.11	

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup






3.6.5 Test Result of Conducted Band Edges

Test Engineer :	Shiming Liu	Temperature :	21~25℃
		Relative Humidity :	51~54%


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 22.MAR.2019 17:13:49


High Band Edge Plot on Channel 78



Date: 22.MAR.2019 17:31:17


<2Mbps>

Low Band Edge Plot on Channel 00




Date: 22.MAR.2019 17:51:59


High Band Edge Plot on Channel 78



Date: 22.MAR.2019 18:43:53

<3Mbps>
Low Band Edge Plot on Channel 00


Date: 22.MAR.2019 18:49:18

High Band Edge Plot on Channel 78


Date: 22.MAR.2019 19:01:25




3.6.6 Test Result of Conducted Hopping Mode Band Edges

Test Engineer :	Shiming Liu	Temperature :	21~25°C
		Relative Humidity :	51~54%


<1Mbps>

Hopping Mode Low Band Edge Plot



Date: 22.MAR.2019 17:14:26


Hopping Mode High Band Edge Plot



Date: 22.MAR.2019 17:33:35


<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 22.MAR.2019 17:54:34


Hopping Mode High Band Edge Plot



Date: 22.MAR.2019 17:55:30


<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 22.MAR.2019 18:52:25

Hopping Mode High Band Edge Plot



Date: 22.MAR.2019 18:52:57

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup




3.7.5 Test Result of Conducted Spurious Emission

Test Engineer :	Shiming Liu	Temperature :	21~25℃
		Relative Humidity :	51~54%


<1Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz




Date: 22.MAR.2019 17:18:37


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 22.MAR.2019 17:19:11

CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 22.MAR.2019 17:27:25

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 22.MAR.2019 17:28:00

CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 22.MAR.2019 17:32:23


CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 22.MAR.2019 17:32:56




<2Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 22.MAR.2019 17:53:16


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 22.MAR.2019 17:53:45




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 22.MAR.2019 17:59:53


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 22.MAR.2019 18:00:21




CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




**<3Mbps>****CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 22.MAR.2019 18:50:40

CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 22.MAR.2019 18:51:07

CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 22.MAR.2019 18:57:50

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 22.MAR.2019 18:58:18

**CSE Plot on Ch 78 between 30MHz ~ 3 GHz**

Date: 22.MAR.2019 19:02:48

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 22.MAR.2019 19:03:16

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

See list of measuring equipment of this test report.

3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
$$\text{On time} = N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$$

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

**<Ant. 1>**

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20\log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

<Ant. 3>


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from $20\log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

<Ant. 4>


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from $20\log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.8.7 Duty Cycle

Please refer to Appendix D.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	N/A	Dec. 27, 2018	Nov. 23, 2018~ Mar. 22, 2019	Dec. 26, 2019	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	50MHz~18GHz	Dec. 27, 2018	Nov. 23, 2018~ Mar. 22, 2019	Dec. 26, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	Nov. 23, 2018~ Mar. 22, 2019	Nov. 20, 2019	Conducted (TH05-HY)
BT Base Station (Measure)	Rohde & Schwarz	CBT	101136	BT 3.0	Sep. 27, 2018	Nov. 23, 2018~ Mar. 22, 2019	Sep. 26, 2019	Conducted (TH05-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	Nov. 22, 2018~ Jan. 28, 2019	Jul. 15, 2019	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 23, 2018	Nov. 22, 2018~ Jan. 28, 2019	Oct. 22, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT-N0602	30MHz~1GHz	Oct. 13, 2018	Nov. 22, 2018~ Jan. 28, 2019	Oct. 12, 2019	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 30, 2018	Nov. 22, 2018~ Jan. 28, 2019	Oct. 29, 2019	Radiation (03CH11-HY)
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz~30 MHz	Mar. 29, 2018	Nov. 22, 2018~ Jan. 28, 2019	Mar. 28, 2019	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 14, 2018	Nov. 22, 2018~ Jan. 28, 2019	Nov. 13, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Oct. 19, 2018	Nov. 22, 2018~ Jan. 28, 2019	Oct. 18, 2019	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Nov. 22, 2018~ Jan. 28, 2019	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Nov. 22, 2018~ Jan. 28, 2019	N/A	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-303K	1710001800054002	1GHz~18GHz	Apr. 17, 2018	Nov. 22, 2018~ Jan. 28, 2019	Apr. 16, 2019	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz ~ 40GHz	Nov. 20, 2018	Nov. 22, 2018~ Jan. 28, 2019	Nov. 19, 2019	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Nov. 22, 2018~ Jan. 28, 2019	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz-30MHz	Mar. 14, 2018	Nov. 22, 2018~ Jan. 28, 2019	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 14, 2018	Nov. 22, 2018~ Jan. 28, 2019	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	30M-18G	Mar. 14, 2018	Nov. 22, 2018~ Jan. 28, 2019	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 14, 2018	Nov. 22, 2018~ Jan. 28, 2019	Mar. 13, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60SS	SN3	2.7G High Pass	Sep. 16, 2018	Nov. 22, 2018~ Jan. 28, 2019	Sep. 17, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN11	1G Low Pass	Sep. 16, 2018	Nov. 22, 2018~ Jan. 28, 2019	Sep. 17, 2019	Radiation (03CH11-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Dec. 27, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Nov. 12, 2018	Dec. 27, 2018	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Dec. 27, 2018	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Dec. 27, 2018	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Dec. 27, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Dec. 27, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Dec. 27, 2018	Jan. 02, 2019	Conduction (CO05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)


Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Appendix A. AC Conducted Emission Test Results


Test Engineer :	Rick Lin	Temperature :	23~24℃
		Relative Humidity :	56~58%
Test Voltage :	120Vac / 60Hz	Phase :	Line



Final Result :

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.233250	---	37.21	52.33	15.12	L1	OFF	19.5
0.233250	43.51	---	62.33	18.82	L1	OFF	19.5
0.352500	---	32.20	48.90	16.70	L1	OFF	19.5
0.352500	39.44	---	58.90	19.46	L1	OFF	19.5
0.469500	---	25.33	46.52	21.19	L1	OFF	19.5
0.469500	37.37	---	56.52	19.15	L1	OFF	19.5
0.822750	---	26.99	46.00	19.01	L1	OFF	19.5
0.822750	34.24	---	56.00	21.76	L1	OFF	19.5
1.059000	---	25.48	46.00	20.52	L1	OFF	19.5
1.059000	34.55	---	56.00	21.45	L1	OFF	19.5
1.293000	---	25.28	46.00	20.72	L1	OFF	19.6
1.293000	33.59	---	56.00	22.41	L1	OFF	19.6

Test Engineer :	Rick Lin	Temperature :	23~24°C
		Relative Humidity :	56~58%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral


Final Result :

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.235500	---	38.45	52.25	13.80	N	OFF	19.5
0.235500	45.91	---	62.25	16.34	N	OFF	19.5
0.345750	---	29.91	49.06	19.15	N	OFF	19.5
0.345750	39.62	---	59.06	19.44	N	OFF	19.5
0.469500	---	28.68	46.52	17.84	N	OFF	19.5
0.469500	41.03	---	56.52	15.49	N	OFF	19.5
0.674250	---	27.66	46.00	18.34	N	OFF	19.5
0.674250	37.71	---	56.00	18.29	N	OFF	19.5
1.059000	---	26.25	46.00	19.75	N	OFF	19.5
1.059000	35.48	---	56.00	20.52	N	OFF	19.5
1.527000	---	26.16	46.00	19.84	N	OFF	19.6
1.527000	33.32	---	56.00	22.68	N	OFF	19.6



Appendix B. Radiated Spurious Emission

Test Engineer :	Hao Hsu, Ace Zhu, Ken Wu, and J.C. Liang	Temperature :	21~26°C
		Relative Humidity :	52~57%

<For Antenna 1>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2361.555	43.9	-30.1	74	42.94	27.55	6.53	33.12	116	146	P	H
		2361.555	19.11	-34.89	54	-	-	-	-	-	-	A	H
	*	2402	100.33	-	-	99.51	27.4	6.59	33.17	116	146	P	H
	*	2402	75.54	-	-	-	-	-	-	-	-	A	H
													H
		2313.885	43.83	-30.17	74	42.7	27.74	6.46	33.07	107	251	P	V
		2313.885	19.04	-34.96	54	-	-	-	-	-	-	A	V
	*	2402	91.6	-	-	90.78	27.4	6.59	33.17	107	251	P	V
	*	2402	66.81	-	-	-	-	-	-	-	-	A	V
													V
BT CH 39 2441MHz		2353.82	44.29	-29.71	74	43.3	27.58	6.52	33.11	144	182	P	H
		2353.82	19.5	-34.5	54	-	-	-	-	-	-	A	H
	*	2441	101.95	-	-	101.23	27.32	6.62	33.22	144	182	P	H
	*	2441	77.16	-	-	-	-	-	-	-	-	A	H
		2488.73	43.41	-30.59	74	42.73	27.3	6.66	33.28	144	182	P	H
		2488.73	18.62	-35.38	54	-	-	-	-	-	-	A	H
		2377.9	43.89	-30.11	74	42.98	27.49	6.56	33.14	134	292	P	V
		2377.9	19.1	-34.9	54	-	-	-	-	-	-	A	V
	*	2441	91.23	-	-	90.51	27.32	6.62	33.22	134	292	P	V
	*	2441	66.44	-	-	-	-	-	-	-	-	A	V
		2491.81	43.29	-30.71	74	42.61	27.3	6.66	33.28	134	292	P	V
		2491.81	18.5	-35.5	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	100.04	-	-	99.36	27.3	6.65	33.27	100	180	P	H
	*	2480	75.25	-	-	-	-	-	-	-	-	A	H
		2484.08	46.2	-27.8	74	45.51	27.3	6.66	33.27	100	180	P	H
		2484.08	21.41	-32.59	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	87.98	-	-	87.3	27.3	6.65	33.27	100	293	P	V
	*	2480	63.19	-	-	-	-	-	-	-	-	A	V
		2488.08	43.77	-30.23	74	43.09	27.3	6.66	33.28	100	293	P	V
		2488.08	18.98	-35.02	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	37.7	-36.3	74	55.11	31.1	10.07	58.58	100	0	P	H
		4804	12.91	-41.09	54	-	-	-	-	-	-	A	H
													H
													H
		4804	36.78	-37.22	74	54.19	31.1	10.07	58.58	100	0	P	V
		4804	11.99	-42.01	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	37.62	-36.38	74	54.98	31.04	10.15	58.55	100	0	P	H
		4882	12.83	-41.17	54	-	-	-	-	-	-	A	H
		7323	41.2	-32.8	74	50.98	36.55	12.48	58.81	100	0	P	H
		7323	16.41	-37.59	54	-	-	-	-	-	-	A	H
		4882	37.57	-36.43	74	54.93	31.04	10.15	58.55	100	0	P	V
		4882	12.78	-41.22	54	-	-	-	-	-	-	A	V
		7323	41.12	-32.88	74	50.9	36.55	12.48	58.81	100	0	P	V
		7323	16.33	-37.67	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	38.55	-35.45	74	55.52	31.32	10.22	58.51	100	0	P	H
		4960	13.76	-40.24	54	-	-	-	-	-	-	A	H
		7440	42.01	-31.99	74	51.72	36.48	12.47	58.66	100	0	P	H
		7440	17.22	-36.78	54	-	-	-	-	-	-	A	H
		4960	39.13	-34.87	74	56.1	31.32	10.22	58.51	100	0	P	V
		4960	14.34	-39.66	54	-	-	-	-	-	-	A	V
		7440	41.55	-32.45	74	51.26	36.48	12.47	58.66	100	0	P	V
		7440	16.76	-37.24	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		186.87	35.86	-7.64	43.5	51.6	14.61	1.9	32.25	100	0	P	H
		231.42	35.66	-10.34	46	49.72	16.12	2.04	32.22	-	-	P	H
		243.57	35.92	-10.08	46	48.61	17.44	2.08	32.21	-	-	P	H
		301.4	29.31	-16.69	46	40.1	19.09	2.3	32.18	-	-	P	H
		612.9	27.46	-18.54	46	30.95	25.45	3.26	32.2	-	-	P	H
		951.7	33.63	-12.37	46	29.7	30.65	4.15	30.87	-	-	P	H
													H
													H
													H
													H
													H
													H
		40.8	33.42	-6.58	40	46.28	18.64	0.87	32.37	100	0	P	V
		195.24	31.44	-12.06	43.5	46.99	14.75	1.94	32.24	-	-	P	V
		242.49	31.15	-14.85	46	43.96	17.32	2.08	32.21	-	-	P	V
		565.3	27.6	-18.4	46	30.69	25.96	3.14	32.19	-	-	P	V
		797	30.61	-15.39	46	30.58	28.17	3.75	31.89	-	-	P	V
		948.2	33.41	-12.59	46	29.7	30.47	4.15	30.91	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



<For Antenna 3>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2339.715	43.4	-30.6	74	42.91	27.64	6.5	33.65	400	265	P	H
		2339.715	18.64	-35.36	54	-	-	-	-	-	-	A	H
	*	2402	100.6	-	-	100.24	27.4	6.59	33.63	400	265	P	H
	*	2402	75.84	-	-	-	-	-	-	-	-	A	H
													H
													H
		2316.3	42.93	-31.07	74	42.4	27.73	6.46	33.66	101	39	P	V
		2316.3	18.17	-35.83	54	-	-	-	-	-	-	A	V
	*	2402	95.7	-	-	95.34	27.4	6.59	33.63	101	39	P	V
	*	2402	70.94	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2336.88	42.85	-31.15	74	42.35	27.65	6.5	33.65	390	260	P	H
		2336.88	18.09	-35.91	54	-	-	-	-	-	-	A	H
	*	2441	100.3	-	-	99.97	27.32	6.62	33.61	390	260	P	H
	*	2441	75.54	-	-	-	-	-	-	-	-	A	H
		2493.63	42.61	-31.39	74	42.24	27.3	6.66	33.59	390	260	P	H
		2493.63	17.85	-36.15	54	-	-	-	-	-	-	A	H
		2362.22	43.2	-30.8	74	42.76	27.55	6.53	33.64	100	39	P	V
		2362.22	18.44	-35.56	54	-	-	-	-	-	-	A	V
	*	2441	95.06	-	-	94.73	27.32	6.62	33.61	100	39	P	V
	*	2441	70.3	-	-	-	-	-	-	-	-	A	V
		2484.39	42.74	-31.26	74	42.38	27.3	6.66	33.6	100	39	P	V
		2484.39	17.98	-36.02	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	97.92	-	-	97.57	27.3	6.65	33.6	397	299	P	H
	*	2480	73.16	-	-	-	-	-	-	-	-	A	H
		2483.6	45.87	-28.13	74	45.51	27.3	6.66	33.6	397	299	P	H
		2483.6	21.11	-32.89	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	93.46	-	-	93.11	27.3	6.65	33.6	100	37	P	V
	*	2480	68.7	-	-	-	-	-	-	-	-	A	V
		2483.52	43.65	-30.35	74	43.29	27.3	6.66	33.6	100	37	P	V
		2483.52	18.89	-35.11	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	38.15	-35.85	74	55.56	31.1	10.071	58.58	100	0	P	H
		4804	13.39	-40.61	54	-	-	-	-	-	-	A	H
													H
													H
		4804	38.02	-35.98	74	55.43	31.1	10.07	58.58	100	0	P	V
		4804	13.26	-40.74	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	37.66	-36.34	74	55.02	31.04	10.15	58.55	100	0	P	H
		4882	12.9	-41.1	54	-	-	-	-	-	-	A	H
		7323	41.79	-32.21	74	51.57	36.55	12.48	58.81	100	0	P	H
		7323	17.03	-36.97	54	-	-	-	-	-	-	A	H
		4882	38.92	-35.08	74	56.28	31.04	10.15	58.55	100	0	P	V
		4882	14.16	-39.84	54	-	-	-	-	-	-	A	V
		7323	41.45	-32.55	74	51.23	36.55	12.48	58.81	100	0	P	V
		7323	16.69	-37.31	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	39.04	-34.96	74	56.01	31.32	10.22	58.51	100	0	P	H
		4960	14.28	-39.72	54	-	-	-	-	-	-	A	H
		7440	41.62	-32.38	74	51.33	36.48	12.47	58.66	100	0	P	H
		7440	16.86	-37.14	54	-	-	-	-	-	-	A	H
		4960	38.92	-35.08	74	55.89	31.32	10.22	58.51	100	0	P	V
		4960	14.16	-39.84	54	-	-	-	-	-	-	A	V
		7440	42.17	-31.83	74	51.88	36.48	12.47	58.66	100	0	P	V
		7440	17.41	-36.59	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		136.65	32.28	-11.22	43.5	45.79	17.2	1.58	32.29	-	-	P	H
		186.6	37.73	-5.77	43.5	53.47	14.61	1.9	32.25	100	0	P	H
		241.41	34.39	-11.61	46	47.35	17.19	2.07	32.22	-	-	P	H
		354.6	30.05	-15.95	46	39.39	20.36	2.47	32.17	-	-	P	H
		626.9	27.87	-18.13	46	30.75	26.01	3.3	32.19	-	-	P	H
		949.6	33.48	-12.52	46	29.67	30.55	4.15	30.89	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
		40.8	33.53	-6.47	40	46.39	18.64	0.87	32.37	100	0	P	V
		137.46	32.48	-11.02	43.5	46	17.19	1.58	32.29	-	-	P	V
		187.14	34.7	-8.8	43.5	50.43	14.61	1.91	32.25	-	-	P	V
		567.4	27.67	-18.33	46	30.8	25.91	3.15	32.19	-	-	P	V
		729.1	29.92	-16.08	46	30.93	27.48	3.57	32.06	-	-	P	V
		891.5	36.39	-9.61	46	34.75	29.03	4.01	31.4	-	-	P	V
													V
													V
													V
													V
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



<For Antenna 4>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2379.3	43.78	-30.22	74	43.37	27.48	6.56	33.63	240	328	P	H
		2379.3	19.02	-34.98	54	-	-	-	-	-	-	A	H
	*	2402	94.17	-	-	93.81	27.4	6.59	33.63	240	328	P	H
	*	2402	69.41	-	-	-	-	-	-	-	-	A	H
													H
													H
		2327.85	43.75	-30.25	74	43.23	27.69	6.48	33.65	346	360	P	V
		2327.85	18.99	-35.01	54	-	-	-	-	-	-	A	V
	*	2402	100.17	-	-	99.81	27.4	6.59	33.63	346	360	P	V
	*	2402	75.41	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2316.72	43.23	-30.77	74	42.69	27.73	6.47	33.66	343	328	P	H
		2316.72	18.47	-35.53	54	-	-	-	-	-	-	A	H
	*	2441	92.2	-	-	91.87	27.32	6.62	33.61	343	328	P	H
	*	2441	67.44	-	-	-	-	-	-	-	-	A	H
		2484.95	44.96	-29.04	74	44.6	27.3	6.66	33.6	343	328	P	H
		2484.95	20.2	-33.8	54	-	-	-	-	-	-	A	H
		2363.76	43.49	-30.51	74	43.05	27.54	6.54	33.64	332	360	P	V
		2363.76	18.73	-35.27	54	-	-	-	-	-	-	A	V
	*	2441	99.35	-	-	99.02	27.32	6.62	33.61	332	360	P	V
	*	2441	74.59	-	-	-	-	-	-	-	-	A	V
		2485.02	52.06	-21.94	74	51.7	27.3	6.66	33.6	332	360	P	V
		2485.02	27.3	-26.7	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	90.2	-	-	89.85	27.3	6.65	33.6	282	93	P	H
	*	2480	65.44	-	-	-	-	-	-	-	-	A	H
		2490.92	43.68	-30.32	74	43.31	27.3	6.66	33.59	282	93	P	H
		2490.92	18.92	-35.08	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	98.54	-	-	98.19	27.3	6.65	33.6	330	359	P	V
	*	2480	73.78	-	-	-	-	-	-	-	-	A	V
		2483.52	46	-28	74	45.64	27.3	6.66	33.6	330	359	P	V
		2483.52	21.24	-32.76	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	36.95	-37.05	74	54.36	31.1	10.07	58.58	100	0	P	H
		4804	12.19	-41.81	54	-	-	-	-	-	-	A	H
													H
													H
		4804	36.89	-37.11	74	54.3	31.1	10.07	58.58	100	0	P	V
		4804	12.13	-41.87	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	37.75	-36.25	74	55.11	31.04	10.15	58.55	100	0	P	H
		4882	12.99	-41.01	54	-	-	-	-	-	-	A	H
		7323	40.31	-33.69	74	50.09	36.55	12.48	58.81	100	0	P	H
		7323	15.55	-38.45	54	-	-	-	-	-	-	A	H
		4882	37.54	-36.46	74	54.9	31.04	10.15	58.55	100	0	P	V
		4882	12.78	-41.22	54	-	-	-	-	-	-	A	V
		7323	41.42	-32.58	74	51.2	36.55	12.48	58.81	100	0	P	V
		7323	16.66	-37.34	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	38.07	-35.93	74	55.04	31.32	10.22	58.51	100	0	P	H
		4960	13.31	-40.69	54	-	-	-	-	-	-	A	H
		7440	41.69	-32.31	74	51.4	36.48	12.47	58.66	100	0	P	H
		7440	16.93	-37.07	54	-	-	-	-	-	-	A	H
		4960	38.83	-35.17	74	55.8	31.32	10.22	58.51	100	0	P	V
		4960	14.07	-39.93	54	-	-	-	-	-	-	A	V
		7440	42.19	-31.81	74	51.9	36.48	12.47	58.66	100	0	P	V
		7440	17.43	-36.57	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		186.87	37.4	-6.1	43.5	53.14	14.61	1.9	32.25	100	0	P	H
		231.42	36.35	-9.65	46	50.41	16.12	2.04	32.22	-	-	P	H
		241.41	36.35	-9.65	46	49.31	17.19	2.07	32.22	-	-	P	H
		885.9	33.83	-12.17	46	32.17	29.08	4	31.42	-	-	P	H
		894.3	34.29	-11.71	46	32.63	29.02	4.02	31.38	-	-	P	H
		953.8	34.45	-11.55	46	30.41	30.74	4.16	30.86	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
		40.8	34.54	-5.46	40	47.4	18.64	0.87	32.37	100	0	P	V
		186.87	29.78	-13.72	43.5	45.52	14.61	1.9	32.25	-	-	P	V
		241.41	31.81	-14.19	46	44.77	17.19	2.07	32.22	-	-	P	V
		773.2	30.22	-15.78	46	30.56	27.91	3.7	31.95	-	-	P	V
		873.3	32.45	-13.55	46	30.74	29.22	3.98	31.49	-	-	P	V
		951	33.24	-12.76	46	29.35	30.62	4.15	30.88	-	-	P	V
													V
													V
													V
													V
													V
													V
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Hao Hsu, Ace Zhu, Ken Wu, and J.C. Liang	Temperature :	21~26°C
		Relative Humidity :	52~57%

Note symbol

-L	Low channel location
-R	High channel location



<For Antenna 1>

2.4GHz 2400~2483.5MHz




BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
Peak	Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846






BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Left blank





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Horizontal	Fundamental
Peak	Level (dBuV/m) Date: 2018.12.12 PEAK_BE_74 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Level (dBuV/m) Date: 2018.12.12 PEAK_74 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846





2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-4FY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 8N0846	 Site : 03CH11-4FY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 8N0846





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH39 2441MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : BN0846



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH78 2480MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2019-01-23 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : BN0846	Level (dBuV/m) Date: 2019-01-23 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : BN0846

Emission below 1GHz
2.4GHz BT (LF)



BT	2.4GHz 2400~2483.5MHz	
	BT LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH11-44Y Condition : QP 3m BT-LOG 6111D-LF_ETC HORIZONTAL Detector : Peak Project : 8N0846	 Site : 03CH11-44Y Condition : QP 3m BT-LOG 6111D-LF_ETC VERTICAL Detector : Peak Project : 8N0846



<For Antenna 3>

2.4GHz 2400~2483.5MHz




BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : Peak Project : RN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : Peak Project : RN0846






BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Vertical	Fundamental
Peak	Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Left blank





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Horizontal	Fundamental
Peak	Level (dBuV/m) Date: 2019-01-25 PEAK_BE_74 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Level (dBuV/m) Date: 2019-01-25 PEAK_74 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-4FY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 8N0846	 Site : 03CH11-4FY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 8N0846





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH39 2441MHz	
	Horizontal	Vertical
Peak Avg.	Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : BN0846	Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : BN0846



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH78 2480MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2019-01-25 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : BN0846	Level (dBuV/m) Date: 2019-01-25 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : BN0846

Emission below 1GHz
2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
	BT LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH11-HY Condition : QP 3m BT-LOG 6111D-LF_ETC HORIZONTAL Detector : Peak Project : 8N0846	 Site : 03CH11-HY Condition : QP 3m BT-LOG 6111D-LF_ETC VERTICAL Detector : Peak Project : 8N0846



<For Antenna 4>

2.4GHz 2400~2483.5MHz




BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
Peak	Level (dBuV/m) Date: 2019-01-23 Frequency (MHz) Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 8N0846	Level (dBuV/m) Date: 2019-01-23 Frequency (MHz) Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 8N0846






BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Vertical	Fundamental
Peak	Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Vertical	Fundamental
Peak	Level (dBuV/m) Date: 2019-01-23 PEAK_BE_74 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846	Level (dBuV/m) Date: 2019-01-23 PEAK_74 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : BN0846



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-1FY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 8N0846	 Site : 03CH11-1FY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 8N0846



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH39 2441MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2019-01-24 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : BN0846	Level (dBuV/m) Date: 2019-01-24 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : BN0846





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH78 2480MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2019-01-24 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : BN0846	Level (dBuV/m) Date: 2019-01-24 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : BN0846



Emission below 1GHz


2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
	BT LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH11-4FY Condition : QP 3m BT-LOG 6111D-LF_ETC HORIZONTAL Detector : Peak Project : 8N0846	 Site : 03CH11-4FY Condition : QP 3m BT-LOG 6111D-LF_ETC VERTICAL Detector : Peak Project : 8N0846


Appendix D. Duty Cycle Plots

<For Ant. 1>

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39




Note:


1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.

<For Ant. 3>

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39




Note:


1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.89 / 100 = 5.78 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.

<For Ant. 4>

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.89 / 100 = 5.78 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.89 \text{ ms} \times 20 \text{ channels} = 57.8 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.89 \text{ ms} \times 2 = 5.78 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.78 \text{ ms}/100\text{ms}) = -24.76 \text{ dB}$$