FCC ID : UZ7WCMTA

EQUIPMENT : Touch Computer

BRAND NAME : Zebra

MODEL NAME : WCMTA

Applicant : Zebra Technologies Corporation

1 Zebra Plaza, Holtsville, NY 11742

Manufacturer Zebra Technologies Corporation

1 Zebra Plaza, Holtsville, NY 11742

STANDARD : 47 CFR Part 2, and 90(S)

CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

TEST DATE(S) : Feb. 14, 2023 ~ Mar. 01, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

JasonJia

Approved by: Jason Jia





Report No.: FG311602E

Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158

Page Number : 1 of 21
Report Issued Date : Apr. 27, 2023

Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

TABLE OF CONTENTS

RE	VISIO	ON HISTORY	3
SU	MMA	RY OF TEST RESULT	4
1	GEN	IERAL DESCRIPTION	5
	1.1	Feature of Equipment Under Test	5
	1.2	Product Specification of Equipment Under Test	
	1.3	Modification of EUT	
	1.4	Maximum Conducted Power and Emission Designator	
	1.5	Testing Site	
	1.6	Test Software Applied Standards	
	1.7		
2	TES	T CONFIGURATION OF EQUIPMENT UNDER TEST	8
	2.1	Test Mode	
	2.2	Connection Diagram of Test System	
	2.3	Support Unit used in test configuration and system	
	2.4	Measurement Results Explanation Example	
	2.5	Frequency List of Low/Middle/High Channels	10
3	TES	T RESULT	11
	3.1	Conducted Output Power Measurement	11
	3.2	99% Occupied Bandwidth and 26dB Bandwidth Measurement	12
	3.3	Emissions Mask Measurement	
	3.4	Emissions Mask – Out Of Band Emissions Measurement	
	3.5	Field Strength of Spurious Radiation Measurement	
	3.6	Frequency Stability Measurement	19
4	LIST	OF MEASURING EQUIPMENT	21
5	UNC	ERTAINTY OF EVALUATION	22
ΑP	PEND	DIX A. TEST RESULTS OF CONDUCTED TEST	
ΑP	PEND	DIX B. TEST RESULTS OF RADIATED TEST	
ΑP	PEND	DIX C. TEST SETUP PHOTOGRAPHS	

TEL: +86-512-57900158

Page Number : 2 of 21
Report Issued Date : Apr. 27, 2023
Report Version : Rev. 01

Report No. : FG311602E

Report Template No.: BU5-FWLTE Version 2.0

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG311602E	Rev. 01	Initial issue of report	Apr. 27, 2023

 Sporton International Inc. (Kunshan)
 Page Number
 : 3 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 27, 2023

 Report Version
 : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

SUMMARY OF TEST RESULT

Report Section	FCC Rule Description		Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	_	Report only	-
3.2	§2.1049 §90.209			Report only	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< 50+10log ₁₀ (P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1053 §90.691	§2.1053 Field Strength of Spurious < 43+10log ₁₀ (P[Watts])		PASS	Under limit 45.64 dB at 3256.00 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Sporton International Inc. (Kunshan)
TEL: +86-512-57900158

Page Number : 4 of 21
Report Issued Date : Apr. 27, 2023
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

1 General Description

1.1 Feature of Equipment Under Test

Product Feature						
Equipment	Touch Computer					
Brand Name	Zebra					
Model Name	WCMTA					
FCC ID	UZ7WCMTA					
Sample 1	Scanner(SE4710)					
Sample 2	Scanner(SE5500)					
HW Version	DV					
SW Version	13-09-09.00-TG-U00-PRD-ATH-04					
MFD	09MAR23					
EUT Stage	Identical Prototype					

Remark:

- **1.** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 2. There are two types of EUT: the main differences between them are the scanner and memory. According to the difference, we choose the Sample 1 to perform full test, and verify the worst RSE for Sample 2.

Specification of Accessory							
Battery 1	Brand Name	Zebra	Model Number	BT-000473			

	Supported Unit used in test configuration and system									
Battery 2	Brand Name	Zebra	Model Number	BT-000473B						
Battery 3	Brand Name	Zebra	Model Number	BT-000473E						
AC Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V12W0US						
Earphone 1	Brand Name	Zebra	Part Number	HDST-35MM-PTT1-01						
Earphone 2	Brand Name	Zebra	Part Number	HDST-USBC-PTT1-01						
USB Cable (Type C to Type A)	Brand Name	Zebra	Part Number	CBL-TC5X-USBC2A-01						
Type C-Audio Cable (Type C to 3.5mm)	Brand Name	Zebra	Part Number	ADP-USBC-35MM1-01						
Trigger Handle	Brand Name	Zebra	Part Number	TRG-TC2L-SNP1-01						
Hand Strap	Brand Name	Zebra	Part Number	SG-TC2L-HSTRP1-01						
Soft Holster	Brand Name	Zebra	Part Number	SG-TC2L-HLSTR1-01						

Sporton International Inc. (Kunshan)Page Number: 5 of 21TEL: +86-512-57900158Report Issued Date: Apr. 27, 2023Report Version: Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard							
Tx Frequency	814 ~ 824 MHz						
Rx Frequency	859 ~ 869 MHz						
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz						
Maximum Output Power to Antenna	23.75 dBm						
Antenna Gain	-3 dBi						
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM						

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Maximum Conducted Power and Emission Designator

L	TE Band 26	QPS	K	16QAM/64QAM/256QAM			
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)		
1.4	814.7 ~ 823.3	0.2270	1M09G7D	0.1888	1M10W7D		
3	815.5 ~ 822.5	0.2259	2M71G7D	0.1879	2M73W7D		
5	816.5 ~ 821.5	0.2296	4M49G7D	0.1914	4M49W7D		
10	819.0	0.2218	9M05G7D	0.1892	9M05W7D		
15	824	0.2371	13M4G7D	0.1982	13M4W7D		

 Sporton International Inc. (Kunshan)
 Page Number
 : 6 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 27, 2023

 Report Version
 : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Ir	porton International Inc. (Kunshan)							
	No. 1098, Pengxi North Road, Kunshan Economic Development Zone								
Test Site Location	Jiangsu Province 215300 People's Republic of China								
	TEL: +86-512-57900158								
	Sporton Sito No	FCC Designation No.	FCC Test Firm						
Test Site No.	Sporton Site No.	rcc besignation No.	Registration No.						
	03CH06-KS TH01-KS	CN1257	314309						

1.6 Test Software

ltem	Site	Manufacturer	Name	Version	
1.	03CH06-KS	AUDIX	E3	6.2009-8-24al	

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 90(S)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Sporton International Inc. (Kunshan)Page Number: 7 of 21TEL: +86-512-57900158Report Issued Date: Apr. 27, 2023Report Version: Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

Test Configuration of Equipment Under Test

Test Mode 2.1

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.


Test Items	Band	Bandwidth (MHz) Modulation							RB#			Test Channel					
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	М	н
Max. Output Power	26	v	٧	v	v	v	-	v	v	v	V	٧	v	v	٧	v	v
26dB and 99% Bandwidth	26	v	٧	v	v	v	-	v	v					v		v	
Emission masks In-band emissions	26	٧	v	v	v	v	-	v	v	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v				v			v	v	v
Frequency Stability	26				v		-	v						v		v	
Radiated Spurious Emission	26		Worst Case								v						
1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. It over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies.																	

Sporton International Inc. (Kunshan)

: 8 of 21 Page Number TEL: +86-512-57900158 Report Issued Date: Apr. 27, 2023 Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment Trade Nam		Model No.	FCC ID	Data Cable	Power Cord	
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m	

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.8 dB.

Example:

Offset(dB) = RF cable loss(dB).

= 4.9 (dB)

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158

Page Number : 9 of 21 Report Issued Date : Apr. 27, 2023

Report No.: FG311602E

Report Version : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List						
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest		
10	Channel	-	26740	-		
10	Frequency	-	819	-		
E	Channel	26715	26740	26765		
5	Frequency	816.5	819	821.5		
2	Channel	26705	26740	26775		
3	Frequency	815.5	819	822.5		
1.4	Channel	26697	26740	26783		
1.4	Frequency	814.7	819	823.3		

LTE Band 26 Cross-rule Channel and Frequency List						
BW [MHz]	Channel/Frequency(MHz)	-	Middle	-		
15	Channel	-	26790	-		
15	Frequency	-	824	-		
10	Channel	-	26790	-		
10	Frequency	-	824	-		
5	Channel	-	26790	-		
5	Frequency	-	824	-		
3	Channel	-	26790	-		
3	Frequency	-	824	-		
4.4	Channel	-	26790	-		
1.4	Frequency	-	824	-		

 Sporton International Inc. (Kunshan)
 Page Number
 : 10 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 27, 2023

 Report Version
 : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through the system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

Report Template No.: BU5-FWLTE Version 2.0

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

 Sporton International Inc. (Kunshan)
 Page Number
 : 12 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 27, 2023

 Report Version
 : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

- (a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:
- (1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log₁₀(f/6.1) decibels or 50 + 10 Log₁₀(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.
- (2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log₁₀(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and base station via power divider.
- 2. The emissions mask of low and high channels for the highest RF powers were measured.
- The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
- 4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.


 Sporton International Inc. (Kunshan)
 Page Number
 : 13 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 27, 2023

 Report Version
 : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

TEL: +86-512-57900158

Page Number : 14 of 21
Report Issued Date : Apr. 27, 2023
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

3.4 Emissions Mask - Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
 The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

 Sporton International Inc. (Kunshan)
 Page Number
 : 15 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 27, 2023

 Report Version
 : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43+10\log_{10}(P[Watts])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

- 1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15
- 12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

 Sporton International Inc. (Kunshan)
 Page Number
 : 16 of 21


 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 27, 2023

 Report Version
 : Rev. 01


Report Template No.: BU5-FWLTE Version 2.0

3.5.4 Test Setup


For radiated test from 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



Sporton International Inc. (Kunshan)

TEL: +86-512-57900158

Page Number : 17 of 21
Report Issued Date : Apr. 27, 2023
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

3.5.5 Test Result of Field Strength of Spurious Radiated

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

Sporton International Inc. (Kunshan)Page Number: 18 of 21TEL: +86-512-57900158Report Issued Date: Apr. 27, 2023Report Version: Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation


- 1. The EUT was set up in the thermal chamber and connected with the base station.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three
 hours. Power was applied and the maximum change in frequency was recorded within one
 minute.
- 3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

- 1. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
- The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
- 3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
- 4. battery operating end point, which shall be specified by the manufacturer.
- 5. The variation in frequency was measured for the worst case.

Report Template No.: BU5-FWLTE Version 2.0

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.

TEL: +86-512-57900158

Page Number : 20 of 21
Report Issued Date : Apr. 27, 2023
Report Version : Rev. 01
Report Template No.: BU5-FWLTE Version 2.0

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Feb. 14, 2023	Oct. 11, 2023	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Feb. 14, 2023	NCR	Conducted (TH01-KS)
Temperature &h umidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 15, 2022	Feb. 14, 2023	Jul. 14, 2023	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz-44GHz	Oct. 13, 2022	Mar. 01, 2023	Oct. 12, 2023	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 16, 2022	Mar. 01, 2023	Oct. 15, 2023	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz-1GHz	May 24, 2022	Mar. 01, 2023	May 23, 2023	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 18, 2022	Mar. 01, 2023	Apr. 17, 2023	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 08, 2023	Mar. 01, 2023	Jan. 07, 2024	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	380827	9KHz ~1GHZ	Jul. 11, 2022	Mar. 01, 2023	Jul. 10, 2023	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 05, 2023	Mar. 01, 2023	Jan. 04, 2024	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2082395	1Ghz-18Ghz	Jan. 05, 2023	Mar. 01, 2023	Jan. 04, 2024	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270319	500MHz~26.5GHz	Oct. 12, 2022	Mar. 01, 2023	Oct. 12, 2023	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Mar. 01, 2023	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Mar. 01, 2023	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Mar. 01, 2023	NCR	Radiation (03CH06-KS)

NCR: No Calibration Required

Sporton International Inc. (Kunshan)Page Number: 21 of 21TEL: +86-512-57900158Report Issued Date: Apr. 27, 2023Report Version: Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB
Conducted Emissions	±0.48 dB
Occupied Channel Bandwidth	±0.1 %

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	2.5dB
Confidence of 95% (U = 2Uc(y))	2.505

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of	2.1dB
Confidence of 95% (U = 2Uc(y))	2.106

----- THE END -----

 Sporton International Inc. (Kunshan)
 Page Number
 : 22 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 27, 2023

 Report Version
 : Rev. 01

Report Template No.: BU5-FWLTE Version 2.0

Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power)

BW [MHz]	Modulation	RB Size	RB Offset	Power Low	Power Middle	Power High
[=]				Ch. / Freq.	Ch. / Freq.	Ch. / Freq.
	Chai	nnel		26790		
	Frequenc	cy (MHz)		824		
15	QPSK	1	0	23.75		
15	QPSK	1	37	23.69		
15	QPSK	1	74	23.51		
15	QPSK	36	0	22.58		
15	QPSK	36	20	22.54		
15	QPSK	36	39	22.58		
15	QPSK	75	0	22.63		
15	16QAM	1	0	22.97		
15	16QAM	1	37	22.93		
15	16QAM	1	74	22.90		
15	16QAM	36	0	21.73		
15	16QAM	36	20	21.60		
15	16QAM	36	39	21.64		
15	16QAM	75	0	21.73		
15	64QAM	1	0	21.85		
15	64QAM	1	37	21.74		
15	64QAM	1	74	21.69		
15	64QAM	36	0	20.74		
15	64QAM	36	20	20.69		
15	64QAM	36	39	20.65		
15	64QAM	75	0	20.77		
15	256QAM	1	0	18.68		
15	256QAM	1	37	18.63		
15	256QAM	1	74	18.61		
15	256QAM	36	0	18.75		
15	256QAM	36	20	18.73		
15	256QAM	36	39	18.74		
15	256QAM	75	0	18.77		
	Chai				26740	
	Frequenc	cy (MHz)			819	
10	QPSK	1	0		23.46	
10	QPSK	1	25		23.40	
10	QPSK	1	49		23.21	
10	QPSK	25	0		22.45	
10	QPSK	25	12		22.38	
10	QPSK	25	25		22.33	
10	QPSK	50	0		22.39	
10	16QAM	1	0		22.77	
10	16QAM	1	25		22.51	

TEL: +86-512-57900158



10	16QAM	1	49		22.61	
10	16QAM	25	0		21.31	
10	16QAM	25	12		21.18	
10	16QAM	25	25		21.33	
10	16QAM	50	0		21.36	
10	64QAM	1	0		21.48	
10	64QAM	1	25		21.51	
10	64QAM	1	49		21.35	
10	64QAM	25	0		20.41	
10	64QAM	25	12		20.44	
					20.44	
10	64QAM	25	25			
10	64QAM	50	0		20.51	
10	256QAM	1	0		18.33	
10	256QAM	1	25		18.28	
10	256QAM	1	49		18.31	
10	256QAM	25	0		18.18	
10	256QAM	25	12		18.18	
10	256QAM	25	25		18.23	
10	256QAM	50	0		18.46	
	Cha			26715	26740	26765
	Frequen	cy (MHz)		816.5	819	821.5
5	QPSK	1	0	23.55	23.61	23.54
5	QPSK	1	12	23.49	23.51	23.53
5	QPSK	1	24	23.38	23.31	23.34
5	QPSK	12	0	22.42	22.50	22.52
5	QPSK	12	7	22.31	22.39	22.35
5	QPSK	12	13	22.36	22.38	22.36
5	QPSK	25	0	22.55	22.47	22.41
5	16QAM	1	0	22.69	22.82	22.74
5	16QAM	1	12	22.68	22.66	22.61
5	16QAM	1	24	22.61	22.71	22.60
5	16QAM	12	0	21.33	21.44	21.47
5	16QAM	12	7	21.28	21.31	21.31
5	16QAM	12	13	21.49	21.46	21.51
5	16QAM	25	0	21.47	21.49	21.50
5	64QAM	1	0	21.40	21.55	21.65
5	64QAM	1	12	21.43	21.46	21.25
5	64QAM	1	24	21.37	21.42	21.18
5	64QAM	12	0	20.49	20.42	20.29
5	64QAM	12	7	20.24	20.43	20.44
5	64QAM	12	13	20.26	20.17	20.20
5	64QAM	25	0	20.56	20.52	20.43
5	256QAM	1	0	18.26	18.28	18.34
5	256QAM	1	12	18.21	18.22	18.28
5	256QAM	1	24	18.08	18.18	18.40
5	256QAM	12	0	18.47	18.12	18.42
5	256QAM	12	7	18.33	18.19	18.48
5	256QAM	12	13	18.36	18.30	18.61
5	256QAM	25	0	18.39	18.53	18.46
	Cha	nnel		26705	26740	26775

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158

Page Number

: A2 of A37



	Frequen	cv (MHz)		815.5	819	822.5
3	QPSK	1	0	23.42	23.54	23.53
3	QPSK	1	8	23.48	23.47	23.48
3	QPSK	1	14	23.33	23.20	23.22
3	QPSK	8	0	22.38	22.46	22.45
3	QPSK	8	4	22.31	22.19	22.26
3	QPSK	8	7	22.35	22.19	22.32
3	QPSK	15	0	22.42	22.45	22.39
3	16QAM	1	0	22.70	22.71	22.74
3	16QAM	1	8	22.76	22.62	22.74
3	16QAM	1	14	22.54	22.62	22.62
3	16QAM	8	0	21.37	21.28	21.32
3	16QAM	8	4	21.37	21.29	21.32
3	16QAM	8	7	21.19	21.29	21.30
3	16QAM	15	0			
		15	0	21.34	21.31	21.31
3	64QAM			21.46	21.46	21.71
3	64QAM	1	8	21.45	21.53	21.24
3	64QAM	1	14	21.34	21.39	21.28
3	64QAM	8	0	20.53	20.41	20.24
3	64QAM	8	4	20.22	20.53	20.41
3	64QAM	8	7	20.21	20.21	20.25
3	64QAM	15	0	20.43	20.59	20.30
3	256QAM	1	0	18.34	18.31	18.33
3	256QAM	1	8	18.28	18.34	18.34
3	256QAM	1	14	18.18	18.19	18.43
3	256QAM	8	0	18.54	18.16	18.39
3	256QAM	8	4	18.36	18.12	18.49
3	256QAM	8	7	18.40	18.23	18.59
3	256QAM	15	0	18.47	18.56	18.48
	Cha			26697	26740	26783
	Frequen			814.7	819	823.3
1.4	QPSK	1	0	23.51	23.56	23.52
1.4	QPSK	1	3	23.47	23.54	23.38
1.4	QPSK	1	5	23.30	23.38	23.29
1.4	QPSK	3	0	22.41	22.45	22.38
1.4	QPSK	3	1	22.35	22.24	22.22
1.4	QPSK	3	3	22.28	22.36	22.25
1.4	QPSK	6	0	22.48	22.34	22.36
1.4	16QAM	1	0	22.71	22.76	22.64
1.4	16QAM	1	3	22.50	22.54	22.59
1.4	16QAM	1	5	22.62	22.55	22.59
1.4	16QAM	3	0	21.31	21.38	21.29
1.4	16QAM	3	1	21.22	21.31	21.16
1.4	16QAM	3	3	21.43	21.43	21.46
1.4	16QAM	6	0	21.39	21.35	21.34
1.4	64QAM	1	0	21.46	21.52	21.55
1.4	64QAM	1	3	21.52	21.45	21.25
1.4	64QAM	1	5	21.32	21.38	21.31
1.4	64QAM	3	0	20.47	20.39	20.22
1.4	64QAM	3	1	20.29	20.46	20.46

Sporton International Inc. (Kunshan)

TEL: +86-512-57900158

Page Number

: A3 of A37



1.4	64QAM	3	3	20.15	20.17	20.24
1.4	64QAM	6	0	20.58	20.59	20.37
1.4	256QAM	1	0	18.39	18.33	18.42
1.4	256QAM	1	3	18.25	18.35	18.38
1.4	256QAM	1	5	18.14	18.27	18.41
1.4	256QAM	3	0	18.47	18.12	18.30
1.4	256QAM	3	1	18.40	18.20	18.47
1.4	256QAM	3	3	18.39	18.26	18.53
1.4	256QAM	6	0	18.41	18.58	18.52

Report No. : FG311602E


Sporton International Inc. (Kunshan) Page Number : A4 of A37

TEL: +86-512-57900158


LTE Band 26_Part 90S

Peak-to-Average Ratio

Mode		LTE Band 26 / 15MHz				
Mod.	QPSK	16QAM	64QAM	256QAM	Limit: 13dB	
RB Size	Full RB	Full RB	Full RB	Full RB	Result	
Low CH	5.07	5.91	6.49	6.52	PASS	



TEL: +86-512-57900158




26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)				
BW	15MHz				
Mod.	QPSK 16QAM				
Low CH	14.48	14.48			
BW	10N	ЛНz			
Mod.	QPSK	16QAM			
Mid CH	9.77	9.87			
BW	5MHz				
Mod.	QPSK	16QAM			
Mid CH	4.96	4.85			
BW	3M	Hz			
Mod.	QPSK	16QAM			
Mid CH	3.03	3.07			
BW	1.4MHz				
Mod.	QPSK	16QAM			
Mid CH	1.24	1.24			


Page Number

: A7 of A37



Report No.: FG311602E

TEL: +86-512-57900158




TEL: +86-512-57900158

Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)	
BW	15MHz	
Mod.	QPSK	16QAM
Low CH	13.43	13.43
BW	10MHz	
Mod.	QPSK	16QAM
Mid CH	9.05	9.05
BW	5MHz	
Mod.	QPSK	16QAM
Mid CH	4.49	4.49
BW	3MHz	
Mod.	QPSK	16QAM
Mid CH	2.71	2.73
BW	1.4MHz	
Mod.	QPSK	16QAM
Mid CH	1.09	1.10


TEL: +86-512-57900158

: A10 of A37




Report No.: FG311602E

TEL: +86-512-57900158



TEL: +86-512-57900158


Conducted Band Edge



Sporton International Inc. (Kunshan)


TEL: +86-512-57900158


Page Number : A13 of A37





Report No.: FG311602E


TEL: +86-512-57900158



















: A20 of A37

















: A27 of A37

Page Number